CONTENTS

iii

NAS 1.26:2915

NASA Contractor Report 2915

Two-Dimensional Wind Tunnel
Test of an Oscillating
Rotor Airfoil

Volume II

L. U. Dadone

NASA

NASA Contractor Report 2915

Two-Dimensional Wind Tunnel Test of an Oscillating Rotor Airfoil

Volume II

L. U. Dadone

Boeing Vertol Company
Philadelphia, Pennsylvania

NASA

National Aeronautics
and Space Administration

**Scientific and Technical
Information Office**

1977

TWO-DIMENSIONAL WIND TUNNEL TEST OF AN OSCILLATING ROTOR AIRFOIL DATA REPORT

(Volume II)

by

L. U. Dadone
Boeing Vertol Company

SUMMARY

An experimental investigation was conducted to determine the quasi-steady and unsteady characteristics of the NLR 7223-62 airfoil, an advanced section designed for helicopter rotor applications. The data were obtained with an airfoil model equipped with 17 differential transducers and mounted in the variable density test section of a blow-down wind tunnel. The test equipment and procedures were similar to other oscillating airfoil tests previously conducted in the same facility.

Quasi-steady pressure data were acquired at Mach numbers between M = 0.2 and 0.9 with porous floor and ceiling (4.9% porosity). Drag data were acquired at a limited number of conditions with a wake-traversing probe. Static and oscillatory tests were then run with solid floor and ceiling at Mach numbers between M = 0.2 and M = 0.7.

The oscillatory test was run at frequencies from 23 Hz to approximately 90 Hz, with amplitudes of oscillation ranging from 2.5° to 10.0°. The test results are presented in two volumes. The first volume documents the test procedure and discusses some of the key results. The second volume is a data report and it contains tabulations of all static and oscillatory data.

LIST OF SYMBOLS

Computer Listing	Text	Description
AERO DAMP		symbol for $\left[2\pi^2 f_D(\Delta\alpha)^2\right]^{-1} \oint C_m d\alpha$, work-per-cycle coefficient
ALPHA	α	airfoil angle of attack, deg
ALPHA·NMAX		airfoil angle of attack at maximum value of normal force during a cycle of oscillation, deg

Computer Listing	Text	Description
ALPHA·0	α_o	mean angle of attack during oscillation cycle, deg
	c	airfoil chord, m
	C_d	airfoil drag coefficient (drag force/unit span)/$q_\infty c$
CM	C_m	airfoil pitching-moment coefficient, (pitching moment/unit span)/$q_\infty c^2$
CM(MIN)		maximum magnitude of pitching-moment coefficient attained during oscillation
CN	C_n	airfoil normal force coefficient, (normal force/unit span)/$q_\infty c$
CN(MAX)		maximum magnitude of normal-force coefficient attained during oscillation
DCP	ΔC_p	differential pressure coefficient, $\Delta P/q_\infty$
DEL·ALPHA	$\Delta\alpha$	amplitude of pitching motion, deg
DRIVE HZ	f_D	drive frequency of airfoil motion in pitch, Hertz
K	k	reduced frequency, $\pi fc/V$
MACH NO.	M	Mach number
n PHI		computer symbol for phase lead of response with respect to forcing motion for the nth harmonic, deg
	P_T	tunnel test section total pressure, N/m^2 (lb/in^2)
Q	q	dynamic pressure, defined as $\tfrac{1}{2}\rho V^2$, N/m^2 (lb/ft^2)
RES n		magnitude of resultant for the nth harmonic
RN	R_n	Reynolds number based on airfoil chord

2

Computer Listing	Text	Description
TDR		ratio of the work-per-cycle coefficient to the theoretical value
TP		test point identification
V		tunnel velocity, m/sec (ft/sec)
X/C	x/c	chordwise position, measured from the leading edge as a fraction of the chord

SUMMARY OF TEST CONDITIONS

QUASI-STEADY FLOW CONDITIONS

1.   Floor and Ceiling with 4.9% Porosity

1.1   Pressures and Integrated Data

2. Solid Floor and Ceiling

   Pressures and Integrated Data

Mach No.	Rn x 10^{-6}	Page No.
0.2	3.2	48
0.3	4.8	50
0.4	2.3	53
	4.7	56
	6.3	59
	7.0	62
0.5	7.9	65
0.6	3.1	68
	6.2	70
	9.1	72
0.7	10.0	75

4

FORCED PITCH OSCILLATION FOR THE NLR 7223-62 AIRFOIL

$\Delta\alpha$ (DEG)	f_D (HZ)	M	α_0 (DEG) 0.0	2.5	5.0	7.5	10.0	12.5	15.0	17.5	20.0	Rn $\times 10^{-6}$	k
			PAGE NUMBER OF COMPUTER DATA										
2.5	23	0.2	78	78	79	79	80	80	81	81	82	3.2	0.17
	23	0.3	82	83	83	84	84	85	85	86	86	4.8	0.12
	46		87	87	88	88	89	89	90	90	91	4.8	0.23
	69		91	92	92	93	93	94	94	95	95	4.8	0.34
	23	0.4	96	96	97	97	98	98	99	99	100	6.4	0.09
	46		100	101	101	102	102	103	103	104	104	6.4	0.18
	69		105	105	106	106	107	107	108	108	109	6.4	0.26
	23	0.5	109	110	110	111	111	112	112	113	-	7.9	0.07
	46		113	114	114	115	115	116	116	117	-	7.9	0.14
	69		117	118	118	119	119	120	120	121	-	8.0	0.22
	23	0.6	121	122	122	123	123	124	124	-	-	9.5	0.06
	46		125	125	126	126	127	127	128	-	-	9.5	0.12
	69		128	129	129	130	130	131	131	-	-	9.5	0.18
	23	0.7	132	132	133	133	134	134	-	-	-	10.0	0.05
	46		-	135	-	135	136	136	-	-	-	10.0	0.11
	69		137	137	138	138	139	-	-	-	-	10.0	0.16

5

FORCED PITCH OSCILLATION FOR THE NLR 7223-62 AIRFOIL

$\Delta\alpha$ (DEG)	f_D (HZ)	M	α_o (DEG) 0.0	2.5	5.0	7.5	10.0	12.5	15.0	17.5	20.0	Rn $\times 10^{-6}$	k
			PAGE NUMBER OF COMPUTER DATA										
5.0	23	0.2	139	140	140	141	141	142	142	143	143	3.2	0.175
	46		144	144	145	145	146	146	147	147	148	3.2	0.35
	69		148	149	149	150	150	151	151	152	152	3.2	0.51
	23	0.3	153	153	154	154	155	155	156	156	157	4.8	0.12
	46		157	158	158	159	159	160	160	161	161	4.8	0.23
	69		162	162	163	163	164	164	165	165	166	4.8	0.35
	23	0.4	166	167	167	168	168	169	169	170	170	2.4	0.09
			171	171	172	172	173	173	174	174	175	4.7	
			175	176	176	177	177	178	178	179	179	6.4	
			180	180	181	181	182	182	183	183	184	7.0	
	46		184	185	185	186	186	187	187	188	188	6.4	0.17
	50		-	-	189	189	190	190	191	-	-	6.4	0.19
	52		-	-	191	192	192	193	193	-	-	6.4	0.192
	53		-	-	194	194	195	195	196	-	-	6.4	0.195
	54		-	-	196	197	197	198	198	-	-	6.4	0.20
	69		199	199	200	200	201	201	202	202	203	6.4	0:26

FORCED PITCH OSCILLATION FOR THE NLR 7223-62 AIRFOIL

Δα (DEG)	f_D (HZ)	M	α_0 (DEG) 0.0	2.5	5.0	7.5	10.0	12.5	15.0	17.5	20.0	Rn x10⁻⁶	k
			PAGE NUMBER OF COMPUTER DATA										
5.0	38	0.4	203	204	204	205	205	206	206	-	-	2.4	0.34
	23	0.5	207	207	208	208	209	209	-	210	210	7.9	0.07
			-	-	-	-	211	211	212	-	-	8.0	0.07
	46		213	213	214	214	215	215	216	216	217	8.0	0.14
	69		217	218	218	219	219	220	-	220	-	8.2	0.20
			221	221	-	-	-	-	-	-	-	8.2	0.20
	23	0.6	222	222	223	223	224	-	-	-	-	9.3	0.06
			-	-	-	-	224	225	225	226	-	9.2	0.06
			226	227	227	228	228	229	229	230	-	6.2	0.06
			-	230	-	231	231	232	232	-	-	3.1	0.06
	46		-	-	-	-	-	233	234	234	-	9.2	0.12
			-	-	-	-	235	-	-	-	-	9.3	0.12
	69		235	236	236	237	237	238	238	-	-	9.2	0.18
	23	0.7	239	239	240	240	241	241	-	-	-	10.0	0.05

FORCED PITCH OSCILLATION FOR THE NLR 7223-62 AIRFOIL

$\Delta\alpha$ (DEG)	f_D (HZ)	M	α_o (DEG)									Rn $\times 10^{-6}$	k
			0.0	2.5	5.0	7.5	10.0	12.5	15.0	17.5	20.0		
			PAGE NUMBER OF COMPUTER DATA										
7.5	23	0.2	-	242	242	243	243	244	-	-	-	3.2	0.17
		0.3	244	245	245	246	246	247	-	-	-	4.8	0.116
		0.4	247	248	248	249	249	-	-	-	-	6.4	0.09
	46		250	250	251	251	252	-	-	-	-	6.4	0.17
	23	0.5	252	253	253	254	-	-	-	-	-	8.0	0.07
	46		254	255	255	256	-	-	-	-	-	8.0	0.14
	23	0.6	256	257	257	-	-	-	-	-	-	9.4	0.06
		0.7	258	258	259	-	-	-	-	-	-	9.4	0.057

FORCED PITCH OSCILLATION FOR THE NLR 7223-62 AIRFOIL

$\Delta\alpha$ (DEG)	f (HZ)	M	α_0 (DEG) 0.0	2.5	5.0	7.5	10.0	12.5	15.0	17.5	20.0	Rn x10⁻⁶	k
			PAGE NUMBER OF COMPUTER DATA										
10.0	23	0.2	259	260	260	261	261	-	-	-	-	3.2	0.17
		0.3	262	-	262	263	263	-	-	-	-	4.8	0.115
		0.4	264	264	265	265	266	-	-	-	-	6.4	0.086
	46		266	267	267	268	-	-	-	-	-	6.4	0.17
	69		268	269	269	270	-	-	-	-	-	6.4	0.27
	23	0.5	270	271	271	272	-	-	-	-	-	7.9	0.07
		0.6	272	273	273	-	-	-	-	-	-	9.3	0.06
		0.7	274	274	275	-	-	-	-	-	-	10.0	0.052
5.0	40	0.2	-	-	-	-	-	276[1]	276	277[2]	-	3.3	0.29
7.5			-	-	-	-	-	277[1]	278	278[2]	-		
10.0			-	-	-	-	-	279[1]	279	280[2]	-		

NOTES:

[1] $\alpha_0 = 14°$
[2] $\alpha_0 = 16°$

9

TABLE I. SUMMARY OF MODEL CHARACTERISTICS

Airfoil Section	NLR 7223-62 (or NLR-1)
Model Span	0.3048m (12 inches, nominal)
Model Scale	1/4.23, based on a 0.686m (2.25 ft) full-scale blade chord
Model Chord	0.162m (6.38 in.)
Thickness Ratio	8.6 percent
Construction	Machined from Maraging Steel

<u>Transducers</u>:

Type	Kulite Model No. 63-11967, Differential
Number Installed	17
Location in Percent Chord	1.01, 1.99, 3.0, 4.91, 7.37, 9.91, 14.93, 19.99, 24.97, 29.98, 39.91, 50.07, 60.05, 70.09, 80.02, 89.96, 96.91
Pressure Range	$\pm$ 5.17x10^5 N/m^2 ($\pm$ 75 psi) from 1 to 5 percent chord
	$\pm$ 3.45x10^5 N/m^2 ($\pm$ 50 psi) from 7.5 to 97 percent chord
Minimum Natural Frequency as Installed	2,800 Hz

FLOOR AND CEILING WITH 4.9% POROSITY

$M = 0.199$ $Rn = 1.55 \times 10^6$

DATA TYPE	X/C											
ALPHA		-8.277	-7.662	-6.855	-6.305	-5.905	-4.415	-3.876	-3.512	-2.544	-2.107	-1.462
CN		-0.486	-0.414	-0.434	-0.378	-0.365	-0.233	-0.205	-0.132	-0.120	-0.073	-0.003
CM		-0.033	-0.057	-0.041	-0.041	-0.027	-0.034	-0.022	-0.025	-0.014	-0.021	-0.015
CCP 1	.010	-2.620	-2.834	-2.935	-3.390	-4.855	-3.941	-3.263	-2.666	-2.430	-2.515	-1.809
DCP 2	.020	-2.108	-2.170	-2.393	-2.765	-2.894	-1.581	-1.508	-1.467	-1.393	-1.250	-1.046
DCP 3	.030	-1.826	-1.991	-2.096	-2.223	-2.324	-1.496	-1.422	-1.176	-1.081	-0.706	-0.581
DCP 4	.049	-2.050	-2.007	-2.231	-2.275	-1.630	-1.221	-1.161	-0.563	-0.695	-0.741	-0.394
DCP 5	.074	-1.920	-1.815	-1.820	-1.806	-1.365	-0.842	-0.764	-0.670	-0.381	-0.310	-0.175
DCP 6	.099	-1.475	-1.701	-1.237	-1.184	-0.725	-0.455	-0.363	-0.281	-0.234	-0.017	0.252
DCP 7	.149	-1.254	-1.291	-1.057	-0.936	-0.611	-0.473	-0.536	-0.313	-0.203	-0.161	-0.175
DCP 8	.200	-1.015	-0.648	-0.625	-0.418	-0.571	-0.397	-0.044	-0.080	-0.079	-0.062	0.291
DCP 9	.250	-0.644	-0.642	-0.393	-0.357	-0.434	-0.320	-0.204	-0.112	-0.150	0.025	0.085
DCP10	.300	-0.617	-0.495	-0.385	-0.247	-0.173	-0.240	-0.180	-0.165	-0.118	-0.060	-0.001
DCP11	.395	-0.393	-0.280	-0.316	-0.228	-0.340	-0.147	-0.138	0.022	0.020	-0.035	0.062
DCP12	.501	-0.142	-0.135	-0.156	-0.193	-0.111	-0.033	-0.004	0.017	0.068	-0.007	0.112
DCP13	.600	-0.257	-0.329	-0.054	0.002	-0.114	0.026	-0.163	-0.028	-0.064	0.101	0.147
DCP14	.701	0.133	0.116	0.051	0.094	0.022	0.085	0.037	0.018	0.021	0.169	0.090
DCP15	.800	0.135	0.166	0.109	0.063	0.139	0.072	0.082	0.175	0.117	0.045	0.142
DCP16	.900	-0.103	0.044	-0.061	-0.044	-0.168	0.019	-0.025	-0.026	-0.087	-0.097	-0.127
DCP17	.969	-0.131	-0.052	-0.075	-0.192	-0.221	-0.166	-0.119	-0.056	-0.214	-0.086	-0.223

DATA TYPE	X/C											
ALPHA		-0.464	0.100	1.007	1.370	1.575	4.010	4.336	4.883	5.613	6.390	6.850
CN		0.095	0.131	0.216	0.255	0.297	0.474	0.508	0.552	0.635	0.688	0.745
CM		-0.015	-0.027	-0.018	-0.013	-0.016	-0.036	-0.036	-0.012	-0.015	-0.008	-0.022
DCP 1	.010	-1.138	-1.062	-0.785	-0.184	0.128	1.436	1.760	1.914	1.526	2.455	2.095
DCP 2	.020	-0.455	-0.265	0.004	0.197	0.585	1.328	1.707	1.901	2.226	2.397	2.722
DCP 3	.030	-0.115	-0.111	0.345	0.585	0.719	1.525	1.855	1.677	2.125	2.505	2.818
DCP 4	.049	-0.109	0.087	0.094	0.473	0.679	1.262	1.525	1.606	1.855	1.954	2.174
DCP 5	.074	0.092	0.236	0.453	0.480	0.554	1.263	1.341	1.490	1.651	1.944	1.960
DCP 6	.099	0.287	0.363	0.687	0.630	0.840	1.446	1.459	1.440	1.636	1.825	2.016
DCP 7	.149	0.117	0.241	0.283	0.357	0.573	0.788	0.939	1.070	1.365	1.139	1.327
DCP 8	.200	0.156	0.203	0.560	0.564	0.390	0.926	0.710	0.887	1.191	1.250	1.117
DCP 9	.250	0.180	0.190	0.335	0.353	0.470	0.716	0.820	0.634	0.786	0.885	0.972
DCP10	.300	0.166	0.183	0.227	0.364	0.394	0.485	0.568	0.637	0.755	0.816	0.853
DCP11	.399	0.267	0.112	0.301	0.285	0.318	0.505	0.433	0.492	0.744	0.705	0.653
DCP12	.501	0.183	0.151	0.323	0.305	0.348	0.436	0.441	0.483	0.516	0.558	0.599
DCP13	.600	0.139	0.117	0.216	0.233	0.290	0.275	0.245	0.368	0.425	0.374	0.604
DCP14	.701	0.167	0.248	0.262	0.233	0.145	0.217	0.363	0.301	0.356	0.423	0.415
DCP15	.800	0.114	0.172	0.142	0.151	0.183	0.209	0.230	0.262	0.259	0.233	0.205
DCP16	.900	-0.075	-0.072	-0.057	-0.157	-0.137	-0.022	-0.113	0.002	-0.042	-0.029	0.080
DCP17	.969	-0.276		-0.234	-0.122	-0.040	-0.202	-0.105	-0.181	-0.175	-0.205	-0.062

M = 0.199   Rn = 1.55 x 10^6

FLOOR AND CEILING WITH 4.9% POROSITY

DATA TYPE	X/C											
ALPHA		7.412	7.937	9.614	11.093	11.440	13.422	14.622	15.093	16.008	16.297	16.556
CN		0.744	0.840	0.989	1.042	1.097	1.137	1.175	1.145	0.934	0.922	0.916
CM		-0.003	-0.005	-0.005	0.001	0.006	0.014	0.005	-0.055	-0.075	-0.090	-0.084
DCP 1	.010	3.048	3.072	4.316	5.656	5.796	5.715	6.243	1.411	1.127	0.372	1.258
DCP 2	.020	2.586	3.475	3.630	4.089	4.444	4.821	4.821	2.665	1.603	1.540	1.642
DCP 3	.030	2.864	2.579	3.726	4.052	4.443	4.741	4.468	2.538	1.823	1.755	1.647
DCP 4	.049	2.364	2.545	3.122	3.260	3.676	3.668	4.016	3.746	3.020	3.081	3.042
DCP 5	.074	2.038	2.347	2.761	2.964	3.145	3.395	3.371	3.143	2.531	2.405	2.360
DCP 6	.099	1.921	2.229	2.617	2.728	2.904	3.025	3.025	2.691	2.174	2.146	1.962
DCP 7	.149	1.434	1.619	1.834	1.920	2.023	2.140	2.173	1.837	1.234	1.332	1.502
DCP 8	.200	1.223	1.386	1.458	1.773	1.743	1.874	1.794	2.101	1.301	1.233	1.256
DCP 9	.250	0.987	1.121	1.322	1.379	1.420	1.568	1.503	1.616	1.211	1.117	0.991
DCP10	.300	0.811	0.908	1.138	1.164	1.209	1.287	1.358	1.418	1.104	0.962	0.991
DCP11	.399	0.658	0.903	0.879	0.914	1.026	1.035	1.115	1.296	1.031	0.897	0.568
DCP12	.501	0.613	0.660	0.780	0.765	0.835	0.815	0.892	1.044	0.867	0.896	0.875
DCP13	.600	0.463	0.409	0.656	0.584	0.521	0.547	0.654	0.735	0.670	0.811	0.644
DCP14	.701	0.369	0.424	0.457	0.396	0.451	0.477	0.384	0.567	0.626	0.676	0.686
DCP15	.800	0.250	0.265	0.291	0.265	0.288	0.238	0.321	0.434	0.568	0.577	0.608
DCP16	.900	-0.049	-0.066	0.007	0.066	-0.007	0.012	0.058	0.221	0.291	0.335	0.235
DCP17	.965	-0.134	-0.063	-0.134	-0.055	-0.051	-0.138	-0.118	-0.152	-0.063	-0.061	0.335

DATA TYPE	X/C		
ALPHA		18.726	19.851
CN		0.965	0.935
CM		-0.096	-0.061
DCP 1	.010	0.254	1.566
DCP 2	.020	1.458	1.703
DCP 3	.030	1.734	1.663
DCP 4	.049	3.195	2.723
DCP 5	.074	2.474	2.765
DCP 6	.099	2.174	2.640
DCP 7	.149	1.447	1.668
DCP 8	.200	1.280	1.445
DCP 9	.250	1.358	1.046
DCP10	.300	0.955	0.564
DCP11	.399	1.111	0.996
DCP12	.501	1.307	0.841
DCP13	.600	0.729	0.671
DCP14	.701	0.770	0.564
DCP15	.800	0.621	0.503
DCP16	.900	0.237	0.203
DCP17	.965	0.015	-0.046

$M = 0.2$ $R_n = 3.2 \times 10^6$

AIRFOIL NLR 7223-62
STEADY FORCES AND MOMENTS
FLOOR AND CEILING WITH 4.9%
POROSITY

DATA TYPE	X/C						
ALPHA		-10.1	-8.68	-7.24	-5.72	-4.36	-3.01
CN		-0.638	-0.579	-0.491	-0.407	-0.293	-0.159
CM		-0.024	-0.030	-0.039	-0.036	-0.034	-0.032
DCP 1	.010	-2.416	-2.314	-5.054	-4.706	-3.603	-2.555
DCP 2	.020	1.809	2.008	1.091	1.560	2.221	2.888
DCP 3	.030	-2.866	-2.188	-2.287	-2.307	-1.822	-1.300
DCP 4	.049	-2.040	-2.399	-2.101	-1.700	-1.303	-0.867
DCP 5	.074	-1.897	-2.009	-1.625	-1.312	-0.964	-0.589
DCP 6	.099	-1.645	-1.579	-1.207	-0.917	-0.633	-0.329
DCP 7	.149	-1.475	-1.282	-0.927	-0.704	-0.497	-0.255
DCP 8	.200	-1.334	-1.165	-0.745	-0.575	-0.403	-0.204
DCP 9	.250	-1.084	-1.035	-0.618	-0.478	-0.321	-0.170
DCP 10	.300	-0.828	-0.828	-0.464	-0.340	-0.216	-0.068
DCP 11	.399	-0.552	-0.507	-0.333	-0.254	-0.174	-0.052
DCP 12	.501	-0.398	-0.302	-0.284	-0.227	-0.161	-0.077
DCP 13	.600	-0.186	-0.092	-0.110	-0.092	-0.046	0.019
DCP 14	.701	-0.052	-0.0	-0.0	0.009	0.052	0.106
DCP 15	.800	-0.009	0.009	0.009	-0.0	0.018	-0.045
DCP 16	.900	-0.133	-0.113	-0.150	-0.160	-0.171	-0.153
DCP 17	.969	0.206	0.354	0.426	0.484	0.507	0.5306
ALPHA		-1.643	-0.276	1.097	2.458	3.831	5.197
CN		-0.039	0.090	0.209	0.3348	0.468	0.597
CM		-.030	-0.029	-0.026	-0.024	-0.023	-0.020
DCP 1	.010	-1.635	-0.775	0.059	0.873	1.698	2.537
DCP 2	.020	-	-	-	-	-	-
DCP 3	.030	-0.776	-0.250	0.293	0.853	1.446	2.034
DCP 4	.049	-0.440	0.006	0.436	0.904	1.390	1.860
DCP 5	.074	-0.248	0.125	0.479	0.848	1.228	1.628
DCP 6	.099	-0.036	0.271	0.556	0.865	1.185	1.506
DCP 7	.149	-0.040	0.211	0.425	0.668	0.871	1.134
DCP 8	.200	-0.027	0.162	0.336	0.523	0.720	0.918
DCP 9	.250	0.024	0.140	0.291	0.453	0.625	0.789
DCP 10	.300	0.061	0.199	0.340	0.460	0.612	0.749
DCP 11	.399	0.042	0.158	0.254	0.363	0.474	0.573
DCP 12	.501	0.0	0.096	0.167	0.239	0.330	0.412
DCP 13	.600	0.076	0.124	0.183	0.242	0.303	0.363
DCP 14	.701	0.142	0.189	0.226	0.274	0.322	0.360
DCP 15	.800	0.073	0.101	0.111	0.140	0.178	0.198
DCP 16	.900	-0.145	-0.137	-0.128	-0.119	-0.100	-0.090
DCP 17	.969	0.526	0.444	0.350	0.294	0.296	0.228

13

AIRFOIL NLR 7223-62
STEADY FORCES AND MOMENTS
FLOOR AND CEILING WITH 4.9%
POROSITY

DATA TYPE	X/C						
ALPHA		6.564	7.920	9.291	10.65	12.185	13.53
CN		0.725	0.856	0.986	1.099	1.224	1.327
CM		-0.018	-0.015	-0.011	-0.008	-0.007	-
DCP 1	.010	3.348	4.271	5.266	5.860	6.056	6.599
DCP 2	.020	-	-	-	-	-	-
DCP 3	.030	2.568	3.166	3.753	4.304	4.928	5.471
DCP 4	.049	2.340	2.843	3.326	3.787	4.297	4.722
DCP 5	.074	2.005	2.395	2.780	3.148	3.560	3.896
DCP 6	.099	1.821	2.149	2.469	2.765	3.096	3.373
DCP 7	.149	1.382	1.640	1.876	2.090	2.351	2.556
DCP 8	.200	1.109	1.300	1.504	1.675	1.880	2.056
DCP 9	.250	0.946	1.113	1.273	1.430	1.608	1.743
DCP 10	.300	0.879	1.018	1.143	1.264	1.405	1.522
DCP 11	.399	0.695	0.797	0.899	0.999	1.112	1.193
DCP 12	.501	0.503	0.578	0.662	0.735	0.820	0.887
DCP 13	.600	0.414	0.475	0.527	0.577	0.629	0.662
DCP 14	.701	0.399	0.438	0.477	0.497	0.536	0.547
DCP 15	.800	0.218	0.238	0.258	0.268	0.288	0.299
DCP 16	.900	-0.081	-0.071	-0.051	-0.051	-0.031	-0.020
DCP 17	.969	0.209	0.230	0.221	0.181	0.040	-

DATA TYPE	X/C					
ALPHA		14.85	16.19	17.53	18.88	20.14
CN		1.407	1.069	0.971	0.982	1.056
CM		0.002	-0.059	-0.070	-0.064	-0.079
DCP 1	.010	7.333	4.527	3.799	3.981	1.839
DCP 2	.020	-	-	-	-	-
DCP 3	.030	5.927	3.702	3.396	3.349	1.713
DCP 4	.049	5.038	3.326	2.794	2.639	3.729
DCP 5	.074	4.146	2.390	1.871	1.764	2.700
DCP 6	.099	3.557	1.783	1.402	1.486	2.052
DCP 7	.149	2.712	1.453	1.256	1.383	1.865
DCP 8	.200	2.192	1.284	1.122	1.244	1.275
DCP 9	.250	1.858	1.210	1.053	1.174	1.176
DCP 10	.300	1.613	1.180	1.034	1.122	1.125
DCP 11	.399	1.261	1.086	0.975	1.030	1.054
DCP 12	.501	0.925	0.936	0.881	0.880	0.928
DCP 13	.600	0.683	0.795	0.795	0.743	0.836
DCP 14	.701	0.548	0.729	0.767	0.699	0.825
DCP 15	.800	0.299	0.580	0.638	0.589	0.688
DCP 16	.900	-0.020	0.267	0.288	0.277	0.319
DCP 17	.969	-	-	-	-	-

14

$M = 0.3$ $R_n = 4.8 \times 10^6$

AIRFOIL NLR 7223-62
STEADY FORCES AND MOMENTS
FLOOR AND CEILING WITH 4.9%
POROSITY

DATA TYPE	X/C						
ALPHA		-9.78	-8.46	-7.12	-5.73	-4.369	-3.00
CN		-0.665	-0.582	-0.553	-0.448	-0.323	-0.192
CM		-0.012	-0.031	-0.031	-0.030	-0.028	-0.026
DCP 1	.010	-2.083	-2.357	-5.189	-4.747	-3.795	-2.690
DCP 2	.020	-	-	-	-	-	-
DCP 3	.030	-1.910	-2.409	-2.867	-2.391	-1.886	-1.353
DCP 4	.049	-2.127	-2.427	-2.114	-1.729	-1.312	-0.880
DCP 5	.074	-1.968	-2.189	-1.611	-1.289	-0.938	-0.585
DCP 6	.099	-1.798	-1.885	-1.255	-0.979	-0.685	-0.381
DCP 7	.149	-1.625	-1.434	- .982	-0.765	-0.539	-0.300
DCP 8	.200	-1.176	-0.932	-0.813	-0.635	-0.454	-0.261
DCP 9	.250	-1.108	-0.912	-0.685	-0.536	-0.374	-0.211
DCP 10	.300	-1.026	-0.738	-0.546	-0.420	-0.279	-0.137
DCP 11	.399	-0.736	-0.446	-0.410	-0.314	-0.200	-0.094
DCP 12	.501	-0.471	-0.293	-0.339	-0.268	-0.188	-0.104
DCP 13	.600	-0.240	-0.156	-0.220	-0.173	-0.113	-0.049
DCP 14	.701	-0.041	-0.008	-0.045	-0.011	0.034	0.080
DCP 15	.800	-0.015	-0.008	-0.031	-0.023	0.0	0.023
DCP 16	.900	-0.086	-0.082	-0.131	-0.144	-0.136	-0.129
DCP 17	.969	-	-	-	-	-	-
ALPHA		-1.64	-0.24	1.14	2.50	3.88	6.62
CN		-0.059	0.075	0.204	0.341	0.480	0.742
CM		-0.024	-0.023	-0.022	-0.021	-0.020	-0.016
DCP 1	.010	-1.69	-0.779	0.087	0.946	1.797	3.461
DCP 2	.020	-	-	-	-	-	-
DCP 3	.030	-0.795	-0.247	0.324	0.914	1.512	2.640
DCP 4	.049	-0.427	0.039	0.506	0.986	1.484	2.447
DCP 5	.074	-0.2105	0.183	0.547	0.940	1.336	2.105
DCP 6	.099	-0.062	0.261	0.578	0.906	1.245	1.881
DCP 7	.149	-0.059	0.185	0.420	0.665	0.900	1.409
DCP 8	.200	-0.062	0.140	0.323	0.528	0.739	1.137
DCP 9	.250	-0.049	0.124	0.289	0.458	0.640	0.965
DCP 10	.300	0.003	0.152	0.292	0.436	0.584	0.866
DCP 11	.399	0.022	0.136	0.245	0.360	0.481	0.700
DCP 12	.501	-0.015	0.075	0.158	0.249	0.341	0.511
DCP 13	.600	0.016	0.078	0.144	0.211	0.283	0.405
DCP 14	.701	0.123	0.174	0.221	0.273	0.321	0.413
DCP 15	.800	0.051	0.079	0.103	0.135	0.168	0.217
DCP 16	.900	-0.117	-0.113	-0.114	-0.097	-0.072	-0.055
DCP 17	.969	-	-	-	-	-	-

15

$M = 0.3 \quad Rn = 4.8 \times 10^6$

DATA TYPE	X/C						
ALPHA		7.982	9.35	10.71	12.27	13.79	15.22
CN		0.878	1.006	1.124	1.244	1.266	1.106
CM		-0.014	-0.011	-0.009	-0.002	0.011	-0.050
DCP 1	.010	4.406	5.204	5.804	7.051	7.698	4.823
DCP 2	.020	-	-	-	-	-	-
DCP 3	.030	3.260	3.874	4.426	4.994	5.265	3.708
DCP 4	.049	2.936	3.419	3.889	4.331	4.483	3.487
DCP 5	.074	2.499	2.886	3.246	3.601	3.720	2.621
DCP 6	.099	2.203	2.521	2.823	3.115	3.204	2.049
DCP 7	.149	1.659	1.894	2.117	2.340	2.415	1.601
DCP 8	.200	1.334	1.528	1.721	1.905	1.963	1.414
DCP 9	.250	1.138	1.297	1.455	1.613	1.662	1.313
DCP 10	.300	1.000	1.138	1.260	1.390	1.419	1.233
DCP 11	.399	0.812	0.923	1.022	1.115	1.117	1.138
DCP 12	.501	0.600	0.680	0.761	0.827	0.809	0.953
DCP 13	.600	0.469	0.528	0.583	0.625	0.580	0.784
DCP 14	.701	0.457	0.497	0.525	0.541	0.467	0.686
DCP 15	.800	0.242	0.266	0.278	0.283	0.247	0.499
DCP 16	.900	-0.043	-0.034	-0.021	-0.017	0.009	0.241
DCP 17	.969	-	-	-	-	-	-

DATA TYPE	X/C				
ALPHA		16.66	18.15	19.65	20.19
CN		0.980	0.983	1.052	0.980
CM		-0.067	-0.065	-0.079	-0.070
DCP 1	.010	3.851	3.968	2.654	1.936
DCP 2	.020	-	-	-	-
DCP 3	.030	3.321	3.113	1.673	1.606
DCP 4	.049	2.764	2.561	3.272	3.238
DCP 5	.074	1.867	1.758	2.428	2.419
DCP 6	.099	1.459	1.520	1.973	1.967
DCP 7	.149	1.279	1.388	1.719	1.736
DCP 8	.200	1.172	1.286	1.499	1.286
DCP 9	.250	1.102	1.191	1.223	1.117
DCP 10	.300	1.067	1.120	1.125	1.050
DCP 11	.399	1.031	1.044	1.062	0.984
DCP 12	.501	0.911	0.903	0.944	0.853
DCP 13	.600	0.801	0.762	0.841	0.747
DCP 14	.701	0.738	0.709	0.812	0.749
DCP 15	.800	0.576	0.555	0.668	0.621
DCP 16	.900	0.289	0.280	0.314	0.302
DCP 17	.969	-	-	-	-

16

$M = 0.4$ $R_n = 6.3 \times 16^6$

AIRFOIL NLR 7223-62
STEADY FORCES AND MOMENTS
FLOOR AND CEILING WITH 4.9%
POROSITY

DATA TYPE	X/C						
ALPHA		-10.11	-8.48	-7.27	-4.20	-2.82	0.12
CN		-0.727	-0.598	-0.540	-0.336	-0.197	0.106
CM		0.003	-0.035	-0.035	-0.028	-0.026	-0.023
DCP 1	.010	-1.973	-2.450	-4.220	-4.002	-2.741	-0.591
DCP 2	.020	-	-	-	-	-	-
DCP 3	.030	-1.794	-3.081	-3.316	-1.918	-1.360	-0.106
DCP 4	.049	-2.318	-2.572	-2.347	-1.323	-0.862	0.169
DCP 5	.074	-2.087	-2.329	-1.691	-0.941	-0.561	0.309
DCP 6	.099	-1.824	-1.835	-1.346	-0.700	-0.575	0.346
DCP 7	.149	-1.510	-1.361	-1.029	-0.540	-0.293	0.257
DCP 8	.200	-1.163	-1.033	-0.762	-0.466	-0.266	0.176
DCP 9	.250	-1.148	-0.865	-0.687	-0.386	-0.215	0.167
DCP 10	.300	-1.105	-0.698	-0.523	-0.295	-0.147	0.182
DCP 11	.399	-0.886	-0.416	-0.411	-0.224	-0.106	0.153
DCP 12	.501	-0.622	-0.303	-0.313	-0.187	-0.100	0.099
DCP 13	.600	-0.359	-0.173	-0.185	-0.121	-0.056	0.092
DCP 14	.701	-0.104	-0.006	-0.009	.029	0.077	0.186
DCP 15	.800	-0.060	-0.002	-0.004	-0.011	0.011	0.079
DCP 16	.900	-0.115	-0.080	-0.092	-0.148	-0.144	-0.121
DCP 17	.969	-	-	-	-	-	-

DATA TYPE	X/C						
ALPHA		1.36	4.68	5.70	6.70	7.70	8.71
CN		0.235	0.578	0.683	0.783	0.884	0.985
CM		-0.021	-0.018	-0.017	-0.016	-0.013	-0.008
DCP 1	.010	1.215	2.313	2.968	3.642	4.481	5.731
DCP 2	.020	-	-	-	-	-	-
DCP 3	.030	0.438	1.951	2.420	2.837	3.295	3.720
DCP 4	.049	0.624	1.872	2.253	2.637	3.014	3.367
DCP 5	.074	0.659	1.664	1.964	2.266	2.562	2.846
DCP 6	.099	0.661	1.522	1.755	2.004	2.244	2.473
DCP 7	.149	0.503	1.107	1.298	1.490	1.668	1.841
DCP 8	.200	1.380	0.888	1.048	1.199	1.343	1.484
DCP 9	.250	1.334	1.759	1.894	1.016	1.138	1.255
DCP 10	.300	1.316	0.682	0.794	0.901	1.004	1.101
DCP 11	.399	1.263	0.559	0.645	0.728	0.810	0.886
DCP 12	.501	0.183	0.411	0.482	0.544	0.605	0.664
DCP 13	.600	0.154	0.323	0.378	0.428	0.473	0.514
DCP 14	.701	0.236	0.359	0.394	0.425	0.455	0.477
DCP 15	.800	0.105	0.178	0.201	0.222	0.238	0.249
DCP 16	.900	-0.114	-0.082	-0.076	-0.066	-0.056	-0.051
DCP 17	.969	-	-	-	-	-	-

17

M = 0.4

$R_n = 6.3 \times 16^6$

AIRFOIL NLR 7223-62
STEADY FORCES AND MOMENTS
FLOOR AND CEILING WITH 4.9%
POROSITY

DATA TYPE	X/C					
ALPHA		9.70	10.71	11.69	12.36	16.48
CN		1.055	1.086	1.086	1.017	1.015
CM		-0.004	0.002	0.012	0.009	-0.046
DCP 1	.010	6.421	6.566	5.922	4.593	3.688
DCP 2	.020	-	-	-	-	-
DCP 3	.030	3.956	4.364	5.065	4.876	3.175
DCP 4	.049	3.606	3.722	4.079	3.361	2.677
DCP 5	.074	3.059	3.170	3.238	2.933	2.398
DCP 6	.099	2.652	2.743	2.741	2.642	2.179
DCP 7	.149	1.986	2.071	2.101	2.129	1.727
DCP 8	.200	1.604	1.684	1.711	1.681	1.461
DCP 9	.250	1.359	1.418	1.432	1.379	1.298
DCP10	.300	1.182	1.229	1.229	1.158	1.144
DCP11	.399	0.947	0.975	0.961	0.918	1.004
DCP12	.501	0.710	0.720	0.698	0.653	0.840
DCP13	.600	0.540	0.533	0.486	0.437	0.673
DCP14	.701	0.477	0.445	0.379	0.335	0.602
DCP15	.800	0.243	0.215	0.176	0.200	0.491
DCP16	.900	-0.049	-0.053	-0.037	0.024	0.229
DCP17	.969	-	-	-	-	-

DATA TYPE	X/C	$M = 0.5$ $Rn = 7.9 \times 10^6$									

AIRFOIL NLR 7223-62
STEADY FORCES AND MOMENT
FLOOR AND CEILING WITH 4.5% POROSITY

	X/C										
ALPHA		-9.99	-8.99	-8.16	-6.82	-5.89	-5.00	-4.10	-3.06	-2.04	-1.07
CN		-0.695	-0.670	-0.611	-0.508	-0.459	-0.407	-0.319	-0.227	-0.119	-0.010
CM		-0.002	-0.022	-0.031	-0.035	-0.031	-0.027	-0.020	-0.018	-0.018	-0.017
DCP 1	.010	-2.231	-2.568	-2.530	-3.983	4.257	-	-3.863	-3.417	-2.659	-1.637
DCP 2	.020	-2.933	-3.485	-3.561	-3.220	3.252	-3.028	-2.715	-2.095	-1.590	-1.035
DCP 3	.030	-2.619	-2.957	-2.954	-2.992	2.775	-2.668	-1.989	-1.567	-1.130	-0.688
DCP 4	.049	-2.052	-2.075	-2.492	-2.405	2.210	-2.046	-1.306	-0.986	-0.618	-0.257
DCP 5	.074	-1.821	-2.050	-2.269	-1.810	1.585	-1.423	-0.903	-0.630	-0.324	-0.029
DCP 6	.099	-1.740	-1.846	-1.722	1.392	1.142	-0.986	-0.692	-0.457	-0.193	0.059
DCP 7	.149	-1.545	-1.553	-1.321	1.039	0.820	-0.666	-0.537	-0.358	-0.163	0.032
DCP 8	.200	-1.189	-1.168	-1.051	0.791	0.683	-0.571	-0.465	-0.315	-0.149	0.013
DCP 9	.250	-1.161	-1.223	-1.058	0.655	0.565	-0.476	-0.380	-0.252	-0.110	0.024
DCP 10	.300	-1.031	-1.012	-0.836	0.513	0.451	-0.375	-0.294	-0.185	-0.064	0.052
DCP 11	.399	-0.777	-0.623	-0.476	0.380	0.340	-0.289	-0.228	-0.144	-0.048	0.045
DCP 12	.501	-0.510	-0.368	-0.305	0.270	0.247	-0.216	-0.175	-0.114	-0.040	0.032
DCP 13	.600	-0.277	-0.205	-0.161	0.141	0.132	-0.120	-0.095	-0.051	0.004	0.059
DCP 14	.701	-0.062	-0.009	0.013	0.132	0.034	0.038	0.052	0.081	0.121	0.160
DCP 15	.800	-0.036	0.005	0.021	0.026	0.016	0.008	0.006	0.015	0.038	0.062
DCP 16	.900	-0.084	-0.053	-0.036	-0.039	-0.060	-0.082	-0.101	-0.117	-0.115	-0.108
DCP 17	.969	-0.037	-0.017	-0.003	-0.006	-0.010	-0.022	-0.028	-0.041	-0.048	0.053

	X/C										
ALPHA		-0.05	0.99	1.95	2.97	4.0	4.9	6.00	6.99	7.95	8.97
CN		0.104	0.220	0.326	0.439	0.551	0.659	0.768	0.875	0.955	0.994
CM		-0.017	-0.017	-0.017	-0.017	-0.016	-0.015	-0.013	-0.009	-0.007	0.000
DCP 1	.010	-0.948	-0.240	0.426	0.977	1.623	2.349	3.152	4.294	4.304	4.307
DCP 2	.020	-0.456	0.114	0.638	1.185	1.739	2.278	2.827	3.813	4.606	4.609
DCP 3	.030	-0.220	0.265	0.708	1.191	1.680	2.160	2.651	2.810	4.317	4.668
DCP 4	.049	0.143	0.549	0.929	1.352	1.778	2.199	2.663	3.187	3.196	3.198
DCP 5	.074	0.304	0.645	0.947	1.285	1.627	1.965	2.313	2.636	2.575	3.715
DCP 6	.099	0.335	0.620	0.879	1.166	1.454	1.722	2.003	2.260	2.419	2.271
DCP 7	.149	0.247	0.463	0.655	0.868	1.078	1.276	1.475	1.660	1.802	1.845
DCP 8	.200	0.172	0.359	0.519	0.691	0.859	1.016	1.176	1.327	1.445	1.512
DCP 9	.250	0.175	0.325	0.461	0.606	0.746	0.878	1.014	1.138	1.246	1.310
DCP 10	.300	0.177	0.304	0.418	0.542	0.659	0.770	0.881	0.983	1.076	1.131
DCP 11	.399	0.147	0.248	0.339	0.436	0.533	0.622	0.708	0.791	0.863	0.900
DCP 12	.501	0.111	0.189	0.260	0.336	0.409	0.480	0.547	0.611	0.666	0.686
DCP 13	.600	0.118	0.178	0.232	0.367	0.346	0.398	0.450	0.495	0.535	0.535
DCP 14	.701	0.203	0.246	0.284	0.326	0.365	0.400	0.433	0.459	0.481	0.452
DCP 15	.800	0.085	0.110	0.133	0.158	0.181	0.201	0.217	0.230	0.239	0.207
DCP 16	.900	-0.102	-0.095	-0.088	-0.080	-0.073	-0.066	-0.061	-0.058	-0.057	-0.070
DCP 17	.969	0.058	-0.064	-0.068	-0.071	-0.075	-0.078	-0.083	-0.086	-0.089	-0.095

AIRFOIL NLR 7223-62
STEADY FORCES AND MOMENT
FLOOR AND CEILING WITH 4.5% POROSITY

DATA TYPE	X/C	$M = 0.5$ $Rn = 7.9 \times 10^6$									
ALPHA		10.11	10.42	10.59	10.77	11.10	11.77	12.12	12.28	12.45	12.60
CN		1.044	1.063	1.060	1.070	1.012	0.997	1.013	0.999	0.992	1.001
CM		0.004	0.004	0.001	0.002	-0.001	-0.004	-0.009	-0.021	-0.010	-0.031
DCP 1	.010	4.309	4.324	4.322	4.318	4.318	4.322	4.317	3.575	4.320	3.105
DCP 2	.020	4.612	4.628	4.626	4.622	4.622	4.626	4.460	3.373	4.388	3.167
DCP 3	.030	4.670	4.686	4.685	4.680	4.680	4.685	4.680	4.120	3.557	4.119
DCP 4	.049	3.200	3.211	3.210	3.207	2.99	3.060	3.108	2.965	3.106	2.760
DCP 5	.074	3.453	3.461	3.353	3.422	2.613	2.489	2.600	2.576	2.605	2.506
DCP 6	.099	2.539	2.596	2.527	2.582	2.364	2.150	2.254	2.316	2.284	2.271
DCP 7	.149	1.941	1.962	1.909	1.939	1.930	1.974	1.943	1.884	2.058	1.880
DCP 8	.200	1.838	1.903	1.844	1.892	1.830	1.752	1.709	1.626	1.745	1.627
DCP 9	.250	1.646	1.730	1.730	1.752	1.664	1.547	1.548	1.538	1.495	1.549
DCP 10	.300	1.318	1.372	1.385	1.416	1.323	1.266	1.291	1.342	1.229	1.337
DCP 11	.399	0.957	0.982	1.014	1.015	0.948	0.957	0.971	1.033	0.938	1.034
DCP 12	.501	0.678	0.692	0.707	0.708	0.681	0.685	0.696	0.735	0.677	0.775
DCP 13	.600	0.479	0.481	0.483	0.479	0.477	0.480	0.497	0.522	0.491	0.570
DCP 14	.701	0.361	0.349	0.355	0.343	0.351	0.357	0.379	0.399	0.384	0.443
DCP 15	.800	0.171	0.171	0.179	0.171	0.176	0.200	0.230	0.262	0.242	0.279
DCP 16	.900	-0.015	-0.006	0.001	0.004	-0.004	0.010	0.033	0.039	0.026	0.057
DCP 17	.969	-0.045	-0.046	-0.045	-0.036	-0.054	-0.036	-0.027	-0.037	-0.036	-0.023

ALPHA		13.11	13.97	15.02	16.07	17.07	18.05	18.987	20.18
CN		0.998	0.974	0.983	0.998	0.991	1.007	1.011	1.044
CM		-0.033	-0.042	-0.052	-0.061	-0.081	-0.089	-0.093	-0.0921
DCP 1	.010	3.300	2.956	2.921	2.492	2.043	1.944	1.844	2.929
DCP 2	.020	3.034	2.809	2.888	2.677	2.077	1.996	1.957	3.063
DCP 3	.030	3.688	3.503	3.311	2.953	2.368	2.196	2.194	2.424
DCP 4	.049	3.109	2.845	2.889	2.726	2.829	2.813	2.727	2.376
DCP 5	.074	2.529	2.316	2.243	2.229	2.370	2.397	2.373	2.076
DCP 6	.099	2.223	2.044	1.909	2.031	2.076	2.067	2.104	1.891
DCP 7	.149	1.891	1.795	1.725	1.866	1.833	1.815	1.805	1.710
DCP 8	.200	1.566	1.554	1.575	1.579	1.329	1.332	1.329	1.537
DCP 9	.250	1.481	1.464	1.448	1.415	1.259	1.264	1.257	1.385
DCP 10	.300	1.293	1.271	1.268	1.282	1.162	1.164	1.170	1.320
DCP 11	.399	1.041	1.017	1.040	1.057	1.047	1.074	1.067	1.160
DCP 12	.501	0.779	0.784	0.797	0.862	0.900	0.958	0.952	0.981
DCP 13	.600	0.569	0.614	0.628	0.675	0.754	0.807	0.822	0.820
DCP 14	.701	0.441	0.486	0.530	0.571	0.667	0.713	0.734	0.702
DCP 15	.800	0.308	0.315	0.387	0.402	0.511	0.530	0.560	0.538
DCP 16	.900	0.071	0.087	0.125	0.138	0.196	0.202	0.218	0.223
DCP 17	.969	-0.021	0.000	-0.003	0.001	0.010	0.015	0.026	0.042

20

M = 0.592   Rn = 3.2 x 10^6

DATA TYPE	x/C											
ALPHA		-9.712	-9.191	-8.286	-7.882	-7.315	-6.832	-5.888	-5.435	-5.077	-4.225	-3.524
CN		-0.576	-0.591	-0.587	-0.558	-0.537	-0.495	-0.464	-0.423	-0.376	-0.317	-0.256
CM		0.016	0.008	-0.005	-0.014	-0.023	-0.034	-0.036	-0.042	-0.038	-0.030	-0.027
DCP 1	.010	-1.563	-1.505	-1.576	-1.546	-1.564	-1.585	-1.666	-1.634	-1.643	-1.745	-1.755
DCP 2	.020	-1.420	-1.437	-1.482	-1.480	-1.465	-1.488	-1.536	-1.558	-1.547	-1.614	-1.641
DCP 3	.030	-2.656	-2.776	-2.825	-2.762	-2.717	-2.735	-2.728	-2.695	-2.585	-2.496	-2.387
DCP 4	.049	-0.870	-0.946	-1.043	-1.035	-1.054	-1.082	-1.093	-1.143	-1.158	-1.197	-0.995
DCP 5	.074	-1.334	-1.545	-1.587	-1.604	-1.682	-1.639	-1.633	-1.665	-1.653	-1.451	-1.052
DCP 6	.099	-1.182	-1.393	-1.454	-1.462	-1.544	-1.573	-1.538	-1.539	-1.447	-1.126	-0.763
DCP 7	.149	-1.101	-1.233	-1.333	-1.299	-1.338	-1.319	-1.258	-1.320	-1.097	-0.608	-0.493
DCP 8	.200	-1.067	-1.164	-1.237	-1.251	-1.296	-1.199	-1.176	-1.018	-0.735	-0.545	-0.424
DCP 9	.250	-0.992	-1.086	-1.121	-1.087	-1.082	-1.044	-0.872	-0.750	-0.551	-0.421	-0.345
DCP10	.300	-0.853	-0.887	-0.867	-0.840	-0.785	-0.685	-0.638	-0.467	-0.418	-0.335	-0.276
DCP11	.395	-0.755	-0.595	-0.624	-0.558	-0.536	-0.452	-0.375	-0.290	-0.263	-0.233	-0.191
DCP12	.501	-0.498	-0.474	-0.452	-0.390	-0.330	-0.304	-0.231	-0.201	-0.175	-0.168	-0.157
DCP13	.600	-0.318	-0.295	-0.276	-0.251	-0.133	-0.111	-0.064	-0.064	-0.062	-0.070	-0.055
DCP14	.701	-0.065	-0.082	-0.023	0.010	0.024	0.083	0.082	0.121	0.110	0.103	0.115
DCP15	.800	-0.024	-0.098	-0.007	0.037	0.044	0.130	0.069	0.076	0.072	0.065	0.075
DCP16	.900	-0.170	-0.118	-0.058	-0.076	-0.049	-0.042	-0.041	-0.033	-0.066	-0.085	-0.094
DCP17	.969	-0.066	-0.049	-0.025	0.036	-0.012	0.037	0.001	0.026	0.026	-0.051	-0.011

DATA TYPE	x/C											
ALPHA		-3.035	-2.565	-1.671	-1.294	-0.823	-0.152	0.751	1.284	1.555	2.350	3.357
CN		-0.205	-0.136	-0.086	-0.023	0.045	0.106	0.166	0.235	0.295	0.363	0.434
CM		-0.024	-0.025	-0.017	-0.018	-0.020	-0.016	-0.015	-0.014	-0.013	-0.012	-0.013
DCP 1	.010	-1.737	-1.610	-1.343	-1.103	-0.815	-0.517	-0.285	-0.327	0.237	0.443	0.676
DCP 2	.020	-1.558	-1.434	-1.155	-0.801	-0.574	-0.360	-0.173	-0.302	0.237	0.440	0.634
DCP 3	.033	-2.285	-1.633	-1.062	-0.925	-0.616	-0.344	-0.324	0.264	0.558	0.837	1.165
DCP 4	.049	-0.683	-0.495	-0.392	-0.240	-0.118	0.021	0.165	0.345	0.492	0.635	0.817
DCP 5	.074	-0.718	-0.506	-0.311	-0.126	0.060	0.257	0.480	0.705	0.934	1.134	1.414
DCP 6	.099	-0.526	-0.391	-0.228	-0.034	0.141	0.285	0.472	0.685	0.855	1.043	1.287
DCP 7	.149	-0.403	-0.263	-0.156	-0.051	0.115	0.248	0.356	0.534	0.675	0.830	0.958
DCP 8	.200	-0.385	-0.257	-0.185	-0.064	0.001	0.163	0.278	0.391	0.441	0.596	0.708
DCP 9	.250	-0.270	-0.211	-0.102	-0.026	0.074	0.184	0.261	0.365	0.459	0.544	0.636
DCP10	.300	-0.202	-0.134	-0.073	0.013	0.073	0.175	0.253	0.315	0.397	0.478	0.545
DCP11	.394	-0.158	-0.071	-0.033	0.012	0.084	0.152	0.203	0.274	0.328	0.390	0.465
DCP12	.501	-0.136	-0.074	-0.020	0.025	0.065	0.107	0.158	0.237	0.234	0.294	0.336
DCP13	.600	-0.023	0.007	0.038	0.067	0.117	0.144	0.175	0.202	0.235	0.275	0.300
DCP14	.701	0.131	0.144	0.153	0.174	0.214	0.205	0.254	0.265	0.276	0.213	0.312
DCP15	.800	0.054	0.086	0.062	0.072	0.102	0.102	0.089	0.137	0.140	0.121	0.143
DCP16	.900	-0.384	-0.063	-0.131	-0.136	-0.107	-0.111	-0.110	-0.119	-0.142	-0.133	-0.092
DCP17	.969	-0.017	0.017	-0.021	-0.024	-0.022	-0.063	-0.058	-0.052	-0.036	-0.057	-0.046

21

AIRFOIL NLR 7223-62 STEADY FORCES AND MOMENTS

M = 0.592 Rn = 3.2 x 10^6

FLOOR AND CEILING WITH 4.9% POROSITY

DATA TYPE	x/C											
ALPHA		3.580	4.115	4.885	5.693	5.837	6.545	7.553	7.823	8.448	9.165	9.544
CN		0.495	0.545	0.600	0.684	0.755	0.803	0.832	0.844	0.884	0.887	0.917
CM		-0.012	-0.008	-0.005	-0.000	0.002	0.004	0.012	0.014	0.008	0.010	0.000
DCP 1	.010	0.916	1.140	1.315	1.515	1.771	1.895	1.955	2.075	2.154	2.214	2.263
DCP 2	.020	0.790	1.002	1.162	1.267	1.430	1.651	1.785	1.847	1.565	2.055	2.081
DCP 3	.030	1.458	1.703	1.916	2.117	2.315	2.588	2.853	3.000	3.147	3.283	3.366
DCP 4	.049	0.999	1.173	1.285	1.411	1.507	1.563	1.683	1.782	1.864	1.828	1.854
DCP 5	.074	1.678	1.573	2.237	2.454	2.625	2.708	2.838	2.937	2.877	2.897	2.811
DCP 6	.099	1.521	1.761	2.062	2.351	2.581	2.657	2.716	2.725	2.735	2.505	2.426
DCP 7	.149	0.913	0.588	1.106	1.865	2.282	2.442	2.398	2.134	2.075	2.092	2.136
DCP 8	.200	0.785	0.892	0.950	0.566	1.123	1.454	1.680	1.758	1.768	1.757	1.895
DCP 9	.250	0.737	0.831	0.855	0.902	0.555	1.028	1.224	1.406	1.505	1.582	1.665
DCP10	.300	0.642	0.721	0.772	0.806	0.850	0.850	0.943	1.059	1.173	1.256	1.247
DCP11	.399	0.534	0.565	0.594	0.659	0.705	0.733	0.702	0.741	0.856	0.885	0.887
DCP12	.501	0.398	0.438	0.446	0.572	0.534	0.515	0.548	0.534	0.572	0.577	0.627
DCP13	.600	0.355	0.358	0.375	0.418	0.445	0.449	0.414	0.432	0.427	0.449	0.464
DCP14	.701	0.348	0.371	0.375	0.360	0.356	0.395	0.364	0.321	0.334	0.315	0.326
DCP15	.800	0.146	0.140	0.166	0.176	0.159	0.176	0.155	0.133	0.152	0.115	0.158
DCP16	.900	-0.124	-0.124	-0.118	-0.127	-0.116	-0.087	-0.098	-0.055	-0.086	-0.094	-0.027
DCP17	.969	-0.061	-0.086	-0.084	-0.083	-0.080	-0.076	-0.135	-0.081	-0.060	-0.077	-0.030

DATA TYPE	x/C											
ALPHA		10.214	10.806	11.651	12.259	12.544	13.115	14.012	14.517	15.061	15.504	16.226
CN		0.536	0.906	0.915	0.932	0.904	0.832	0.824	0.814	0.841	0.849	0.857
CM		-0.013	-0.025	-0.045	-0.060	-0.074	-0.071	-0.075	-0.074	-0.077	-0.076	-0.074
DCP 1	.010	2.267	2.293	1.971	1.811	1.482	1.244	1.125	1.150	1.146	1.115	1.112
DCP 2	.020	2.121	2.294	1.833	1.616	1.367	1.136	1.042	1.002	1.037	1.035	1.037
DCP 3	.030	3.337	3.255	2.773	2.666	2.096	1.836	1.710	1.662	1.644	1.637	1.675
DCP 4	.049	1.828	1.672	1.657	1.667	1.741	1.700	1.677	1.602	1.597	1.582	1.570
DCP 5	.074	2.680	2.501	2.481	2.448	2.472	2.465	2.484	2.452	2.472	2.445	2.495
DCP 6	.099	2.381	2.133	2.163	2.156	2.281	2.242	2.231	2.193	2.264	2.255	2.353
DCP 7	.149	2.070	1.894	1.732	1.733	1.607	1.402	1.237	1.310	1.419	1.457	1.435
DCP 8	.200	1.621	1.665	1.471	1.424	1.143	0.956	0.943	1.022	1.008	1.117	1.055
DCP 9	.250	1.553	1.483	1.326	1.347	1.165	1.057	0.981	0.998	1.035	1.040	1.027
DCP10	.300	1.267	1.260	1.166	1.173	1.042	0.949	0.916	0.889	0.930	0.955	0.978
DCP11	.399	0.566	0.951	1.050	1.027	1.320	0.890	0.845	0.847	0.891	0.935	0.898
DCP12	.501	0.716	0.691	0.835	0.846	0.830	0.730	0.744	0.757	0.780	0.777	0.788
DCP13	.600	0.510	0.533	0.641	0.682	0.740	0.668	0.721	0.673	0.697	0.687	0.714
DCP14	.701	0.405	0.406	0.539	0.605	0.645	0.645	0.657	0.620	0.675	0.667	0.658
DCP15	.800	0.197	0.265	0.376	0.395	0.465	0.531	0.553	0.514	0.532	0.507	0.524
DCP16	.900	-0.007	0.048	0.055	0.074	0.154	0.160	0.177	0.168	0.147	0.184	0.162
DCP17	.969	-0.033	-0.024	-0.011	0.020	0.016	-0.025	-0.005	-0.014	0.004	-0.017	-0.017

AIRFOIL NLR 7223-62   STEADY FORCES AND MOMENTS

M = 0.592 Rn = 3.2 x 10^6   FLOOR AND CEILING WITH 4.9% POROSITY

DATA TYPE	x/C						
ALPHA		16.865	17.408	17.560	18.862	19.336	19.518
CN		C.878	0.911	0.932	0.952	C.985	0.987
CM		-0.079	-0.083	-0.091	-0.091	-0.096	-0.097
DCP 1	.010	1.145	1.152	1.147	1.152	1.184	1.185
DCP 2	.023	1.028	1.071	1.089	1.108	1.095	1.119
DCP 3	.030	1.711	1.731	1.736	1.810	1.830	1.814
DCP 4	.049	1.625	1.631	1.587	1.495	1.512	1.477
DCP 5	.074	2.471	2.527	2.534	2.487	2.486	2.441
DCP 6	.099	2.395	2.424	2.387	2.456	2.518	2.461
DCP 7	.149	1.585	1.740	1.786	1.805	1.970	2.080
DCP 8	.200	1.086	1.155	1.132	1.251	1.297	1.243
DCP 9	.250	1.086	1.125	1.146	1.185	1.225	1.235
DCP10	.333	0.993	1.041	1.043	1.104	1.135	1.136
DCP11	.399	0.917	0.937	0.974	1.025	1.057	1.066
DCP12	.501	C.811	0.835	0.876	0.885	0.917	0.911
DCP13	.630	0.735	0.734	0.763	C.802	0.747	0.819
DCP14	.701	C.669	0.688	0.727	0.730	C.755	0.740
DCP15	.800	0.544	0.562	0.586	0.594	0.603	C.605
DCP16	.900	0.188	0.190	0.228	0.230	0.242	0.257
DCP17	.969	-0.008	-0.030	0.025	0.012	0.016	0.004

AIRFOIL NLR 7223-62 STEADY FORCES AND MOMENTS

M = 0.594 Rn = 6.3 x 10^6

FLOOR AND CEILING WITH 4.5% POROSITY

DATA TYPE	x/c											
ALPHA		-9.525	-8.528	-8.253	-7.742	-7.127	-6.253	-5.905	-5.341	-4.820	-4.010	-3.568
CN		-0.675	-0.671	-0.558	-0.573	-0.550	-0.495	-0.465	-0.435	-0.366	-0.314	-0.263
CM		0.015	0.007	-0.016	-0.028	-0.032	-0.040	-0.038	-0.036	-0.031	-0.026	-0.022
DCP 1	.010	-2.076	-1.931	-1.777	-2.137	-1.697	-1.748	-1.849	-1.780	-1.875	-2.002	-2.021
DCP 2	.020	-1.835	-1.614	-1.624	-1.829	-1.608	-1.619	-1.552	-1.633	-1.760	-1.807	-1.747
DCP 3	.030	-2.790	-3.164	-3.018	-2.796	-3.005	-2.827	-2.412	-2.758	-2.667	-2.628	-2.386
DCP 4	.049	-1.337	-1.255	-1.323	-1.416	-1.421	-1.396	-1.295	-1.192	-1.308	-1.195	-0.548
DCP 5	.074	-1.837	-1.902	-1.825	-1.856	-1.996	-1.965	-1.961	-1.831	-1.647	-1.298	-0.935
DCP 6	.099	-1.705	-1.772	-1.585	-1.641	-1.715	-1.675	-1.641	-1.562	-1.221	-0.875	-0.631
DCP 7	.149	-1.433	-1.576	-1.469	-1.433	-1.430	-1.388	-1.375	-1.211	-0.810	-0.618	-0.512
DCP 8	.233	-3.995	-1.162	-1.191	-1.088	-1.272	-1.092	-1.063	-0.946	-0.628	-0.478	-0.424
DCP 9	.250	-0.975	-1.062	-1.105	-1.018	-0.917	-0.882	-3.773	-0.736	-0.447	-0.410	-0.364
DCP10	.300	-3.899	-0.868	-3.842	-0.582	-0.728	-0.623	-3.568	-3.486	-0.416	-0.311	-3.267
DCP11	.399	-0.756	-0.627	-0.605	-3.574	-0.443	-3.393	-0.352	-0.268	-3.268	-0.244	-3.175
DCP12	.501	-0.616	-3.493	-0.425	-0.361	-3.333	-0.257	-3.233	-0.220	-0.208	-3.175	-0.145
DCP13	.633	-3.360	-0.442	-0.271	-0.130	-0.183	-0.056	-0.103	-3.079	-0.074	-3.093	-0.071
DCP14	.701	-3.227	-3.128	-0.007	0.032	0.081	3.087	0.062	0.058	0.059	0.073	0.072
DCP15	.800	-0.068	-3.090	3.017	0.061	3.050	0.068	0.067	0.066	0.043	3.025	0.033
DCP16	.930	-3.138	-0.121	-0.048	-3.062	-0.062	-3.023	-0.027	-3.051	-0.055	-0.067	-3.083
DCP17	.969	-0.064	-3.068	-0.000	0.020	0.014	3.009	3.008	-0.009	0.034	-0.014	-0.015

DATA TYPE	x/c											
ALPHA		-2.542	-2.333	-1.435	-1.093	-0.481	0.236	0.838	1.211	1.831	2.804	3.238
CN		-0.210	-0.149	-0.088	-3.024	0.044	3.112	0.178	0.245	3.312	0.376	3.444
CM		-0.019	-3.018	-0.015	-0.014	-3.015	-0.014	-3.015	-0.015	-3.013	-3.013	-0.012
DCP 1	.013	-1.925	-1.758	-1.501	-1.123	-0.795	-0.518	-0.252	0.001	3.225	0.447	0.687
DCP 2	.020	-1.717	-1.533	-0.883	-0.776	-3.561	-0.352	-3.166	0.053	0.254	3.439	0.632
DCP 3	.030	-1.572	-1.320	-1.155	-0.875	-3.602	-0.285	0.007	3.312	0.601	0.904	1.196
DCP 4	.049	-3.667	-3.532	-0.396	-3.267	-0.106	0.030	3.186	0.341	3.532	0.665	3.846
DCP 5	.074	-0.675	-0.533	-0.320	-0.141	3.082	0.325	0.507	0.727	0.978	1.213	1.474
DCP 6	.399	-3.511	-0.364	-3.192	-0.012	0.156	3.355	0.536	3.731	0.923	1.141	1.363
DCP 7	.149	-3.400	-3.279	-0.182	-3.024	0.102	0.246	3.381	0.527	3.681	0.746	0.880
DCP 8	.203	-0.345	-0.241	-3.144	-0.041	3.076	0.210	0.295	3.432	0.524	0.638	0.765
DCP 9	.253	-3.285	-0.180	-3.103	-0.008	0.068	3.169	0.264	3.361	0.464	0.547	3.651
DCP10	.700	-0.195	-3.143	-0.045	3.020	0.105	0.180	3.260	0.340	3.414	3.525	0.586
DCP11	.399	-0.148	-0.099	-3.037	0.028	3.095	0.160	0.228	3.284	0.358	3.410	0.476
DCP12	.501	-3.112	-0.077	-0.039	0.017	0.062	0.126	0.174	3.213	3.267	0.305	0.344
DCP13	.600	-0.040	-3.013	0.026	0.058	3.098	0.141	3.168	0.202	3.234	3.267	0.294
DCP14	.731	3.075	0.111	3.134	0.152	0.175	3.196	0.230	3.254	0.270	3.306	3.322
DCP15	.833	3.041	3.051	0.044	3.056	0.091	3.083	3.135	0.125	3.131	0.121	3.153
DCP16	.900	-0.103	-3.103	-3.112	-0.120	-3.122	-0.113	-0.105	-3.107	-0.110	-3.137	-3.058
DCP17	.969	-3.014	-0.027	-3.030	-0.032	-0.012	-3.061	-0.062	-0.056	-0.072	-3.053	-3.073

M = 0.594   Rn = 6.3 x 10⁶

DATA TYPE	X/C											
ALPHA		3.647	4.318	5.186	5.457	5.573	6.784	7.601	7.874	8.336	9.315	9.932
CN		0.514	0.582	0.631	0.711	0.771	0.828	0.871	0.901	0.886	0.906	0.892
CM		-0.012	-0.005	-0.006	-0.004	-0.000	0.002	0.008	0.013	0.016	0.013	0.011
DCP 1	.010	0.923	1.134	1.328	1.552	1.768	1.927	2.021	2.103	2.163	2.191	2.228
DCP 2	.020	0.849	1.019	1.163	1.306	1.480	1.716	1.836	1.937	2.006	2.054	2.091
DCP 3	.030	1.486	1.734	1.571	2.149	2.303	2.713	2.950	3.115	3.211	3.302	3.377
DCP 4	.349	1.033	1.182	1.306	1.416	1.472	1.631	1.722	1.827	1.893	1.931	1.948
DCP 5	.074	1.746	2.045	2.311	2.507	2.605	2.750	2.921	3.069	3.146	3.146	3.072
DCP 6	.099	1.597	1.581	2.365	2.580	2.699	2.828	2.977	3.078	2.989	2.990	2.585
DCP 7	.149	1.035	1.104	1.104	1.875	2.438	2.591	2.676	2.554	2.215	2.176	2.082
DCP 8	.200	0.838	0.955	0.997	0.995	1.121	1.423	1.654	1.742	1.825	1.833	1.802
DCP 9	.250	0.738	0.825	0.889	0.914	0.911	0.586	1.171	1.391	1.386	1.463	1.526
DCP10	.300	0.660	0.736	0.777	0.813	0.853	0.832	0.832	1.032	1.083	1.177	1.183
DCP11	.399	0.541	0.620	0.642	0.683	0.708	0.754	0.764	0.762	0.792	0.827	0.862
DCP12	.501	0.393	0.437	0.475	0.516	0.528	0.565	0.564	0.570	0.532	0.548	0.569
DCP13	.600	0.351	0.379	0.411	0.418	0.443	0.463	0.460	0.451	0.413	0.423	0.415
DCP14	.701	0.350	0.367	0.368	0.398	0.407	0.358	0.395	0.361	0.339	0.315	0.308
DCP15	.800	0.161	0.162	0.175	0.195	0.198	0.200	0.196	0.170	0.153	0.156	0.169
DCP16	.900	-0.087	-0.135	-0.119	-0.099	-0.093	-0.076	-0.086	-0.091	-0.097	-0.065	-0.062
DCP17	.969	-0.092	-0.080	-0.072	-0.083	-0.078	-0.073	-0.083	-0.087	-0.078	-0.067	-0.108

DATA TYPE	X/C											
ALPHA		10.275	10.855	11.600	12.432	12.608	13.172	14.078	14.820	15.038	15.615	16.221
CN		0.902	0.898	0.936	0.928	0.965	0.942	0.921	0.865	0.850	0.886	0.927
CM		0.000	-0.006	-0.025	-0.041	-0.064	-0.068	-0.075	-0.083	-0.083	-0.091	-0.093
DCP 1	.010	2.268	2.297	2.274	2.160	1.557	1.774	1.959	2.082	2.103	2.125	2.144
DCP 2	.020	2.139	2.170	2.139	1.580	1.786	1.594	1.880	2.104	2.088	2.045	2.023
DCP 3	.030	3.417	3.343	3.258	3.235	2.585	2.878	3.343	3.401	3.224	2.993	2.956
DCP 4	.049	1.901	1.735	1.755	1.631	1.715	1.636	1.685	1.626	1.611	1.620	1.665
DCP 5	.074	2.757	2.477	2.608	2.459	2.580	2.546	2.616	1.955	2.057	2.260	2.481
DCP 6	.099	2.375	2.295	2.294	2.283	2.406	2.337	2.374	1.409	1.371	1.410	1.503
DCP 7	.149	2.052	2.090	1.930	1.677	1.667	1.631	1.357	1.246	1.200	1.208	1.316
DCP 8	.200	1.788	1.770	1.625	1.383	1.394	1.276	1.114	1.138	1.096	1.143	1.219
DCP 9	.250	1.565	1.456	1.418	1.411	1.265	1.205	1.011	1.082	1.026	1.072	1.154
DCP10	.300	1.225	1.233	1.268	1.275	1.160	1.156	1.015	1.031	0.994	1.047	1.084
DCP11	.399	0.946	1.011	1.075	1.132	1.117	1.035	0.938	0.917	0.937	0.945	1.012
DCP12	.501	0.629	0.635	0.763	0.792	0.502	0.925	0.867	0.831	0.757	0.824	0.882
DCP13	.600	0.414	0.458	0.584	0.605	0.700	0.704	0.713	0.705	0.658	0.800	0.852
DCP14	.701	0.320	0.345	0.420	0.491	0.613	0.594	0.644	0.685	0.616	0.680	0.605
DCP15	.800	0.184	0.184	0.223	0.310	0.386	0.445	0.516	0.499	0.488	0.538	0.585
DCP16	.900	-0.025	-0.028	0.042	0.071	0.170	0.172	0.241	0.234	0.313	0.275	0.284
DCP17	.969	-0.066	-0.057	-0.040	-0.057	0.006	0.004	0.051	0.088	0.097	0.056	0.066

AIRFOIL NLR 7223-62   STEADY FORCES AND MOMENTS

$M = 0.594$ $Rn = 6.3 \times 10^6$ FLOOR AND CEILING WITH 4.9% POROSITY

DATA TYPE	X/C						
ALPHA		17.060	17.356	18.046	18.665	19.471	19.856
CN		0.906	0.929	0.946	0.943	1.035	0.999
CM		-0.092	-0.096	-0.095	-0.092	-0.106	-0.105
DCP 1	.010	2.125	2.157	2.177	2.190	2.201	2.187
DCP 2	.020	1.990	2.026	2.000	2.066	2.049	2.025
DCP 3	.030	2.863	2.946	2.864	2.898	2.883	2.829
DCP 4	.049	1.640	1.664	1.682	1.681	1.732	1.708
DCP 5	.074	2.506	2.620	2.721	2.753	2.880	2.851
DCP 6	.099	1.464	1.464	1.496	1.541	1.594	1.624
DCP 7	.149	1.246	1.285	1.312	1.351	1.398	1.398
DCP 8	.200	1.185	1.210	1.250	1.250	1.330	1.305
DCP 9	.250	1.132	1.110	1.156	1.183	1.232	1.251
DCP10	.300	1.034	1.070	1.101	1.104	1.146	1.168
DCP11	.399	0.987	1.000	1.033	0.995	1.076	1.081
DCP12	.501	0.804	0.853	0.896	0.907	0.986	0.946
DCP13	.600	0.762	0.820	0.832	0.737	0.892	0.836
DCP14	.701	0.753	0.704	0.740	0.699	0.771	0.835
DCP15	.800	0.579	0.596	0.582	0.609	0.619	0.625
DCP16	.900	0.241	0.301	0.260	0.271	0.318	0.281
DCP17	.969	0.074	0.067	0.032	0.062	0.079	0.065

M = 0.597 Rn = 9.4 x 10^6

FLOOR AND CEILING WITH 4.9% POROSITY

DATA TYPE	x/c											
ALPHA		-6.847	-8.153	-7.394	-7.197	-6.583	-5.789	-5.041	-4.676	-4.040	-3.413	-2.513
CN		-0.662	-0.630	-0.563	-0.577	-0.522	-0.483	-0.457	-0.437	-0.350	-0.298	-0.237
CM		-0.015	-0.027	-0.040	-0.045	-0.050	-0.049	-0.044	-0.041	-0.035	-0.030	-0.027
DCP 1	.010	-2.893	-2.696	-3.038	-3.216	-3.145	-3.275	-3.268	-3.374	-3.337	-3.431	-3.414
DCP 2	.020	-3.079	-2.941	-3.229	-3.017	-3.060	-3.097	-2.836	-3.011	-3.015	-3.018	-2.577
DCP 3	.030	-2.655	-2.633	-2.616	-2.630	-2.662	-2.572	-2.694	-2.708	-2.491	-2.320	-1.804
DCP 4	.049	-2.329	-2.264	-1.992	-2.466	-2.394	-2.224	-2.117	-2.237	-1.932	-1.554	-1.040
DCP 5	.074	-1.880	-1.931	-1.814	-2.125	-2.043	-1.974	-1.817	-1.583	-1.283	-0.895	-0.662
DCP 6	.099	-1.737	-1.732	-1.657	-1.796	-1.830	-1.701	-1.525	-1.202	-0.841	-0.626	-0.477
DCP 7	.149	-1.301	-1.392	-1.570	-1.402	-1.241	-1.142	-1.114	-0.797	-0.606	-0.461	-0.406
DCP 8	.200	-1.116	-1.147	-1.085	-1.136	-0.991	-0.865	-0.680	-0.585	-0.516	-0.436	-0.350
DCP 9	.253	-1.176	-1.057	-0.902	-0.935	-0.715	-0.604	-0.564	-0.495	-0.405	-0.346	-0.274
DCP10	.300	-0.976	-0.855	-0.662	-0.695	-0.563	-0.473	-0.443	-0.355	-0.321	-0.270	-0.184
DCP11	.355	-0.655	-0.625	-0.416	-0.428	-0.375	-0.305	-0.337	-0.273	-0.237	-0.184	-0.136
DCP12	.501	-0.415	-0.384	-0.313	-0.260	-0.242	-0.227	-0.214	-0.168	-0.162	-0.141	-0.096
DCP13	.600	-0.280	-0.229	-0.144	-0.117	-0.106	-0.136	-0.106	-0.095	-0.075	-0.066	-0.036
DCP14	.701	-0.025	0.006	0.046	0.062	0.063	0.092	0.076	0.081	0.076	0.083	0.101
DCP15	.800	-0.028	0.017	0.045	0.045	0.058	0.055	0.040	0.035	0.040	0.031	0.027
DCP16	.900	-0.065	-0.066	-0.041	-0.025	-0.021	-0.032	-0.032	-0.065	-0.086	-0.057	-0.107
DCP17	.969	-0.015	-0.017	-0.017	0.006	0.012	-0.014	-0.032	-0.006	-0.004	-0.024	-0.016

DATA TYPE	x/c											
ALPHA		-2.356	-1.847	-1.153	-0.321	0.201	0.591	1.320	2.157	2.505	3.031	3.854
CN		-0.180	-0.112	-0.042	0.031	0.113	0.175	0.250	0.322	0.396	0.468	0.535
CM		-0.022	-0.021	-0.018	-0.016	-0.017	-0.015	-0.014	-0.013	-0.011	-0.009	-0.008
DCP 1	.010	-3.385	-2.821	-2.051	-1.537	-0.917	-0.371	-0.266	0.117	0.613	1.020	1.265
DCP 2	.020	-2.232	-1.551	-1.265	-0.904	-0.562	-0.215	0.125	0.453	0.780	1.114	1.435
DCP 3	.030	-1.308	-1.142	-0.855	-0.556	-0.265	0.012	0.313	0.610	0.905	1.191	1.472
DCP 4	.049	-0.857	-0.657	-0.421	-0.175	0.103	0.331	0.586	0.850	1.134	1.419	1.717
DCP 5	.074	-0.515	-0.335	-0.143	0.074	0.276	0.493	0.737	0.955	1.195	1.434	1.722
DCP 6	.099	-0.338	-0.176	-0.025	0.166	0.350	0.540	0.726	0.927	1.126	1.327	1.553
DCP 7	.149	-0.284	-0.154	-0.027	0.086	0.236	0.376	0.516	0.642	0.792	0.925	1.053
DCP 8	.200	-0.266	-0.156	-0.056	0.065	0.182	0.283	0.410	0.524	0.632	0.733	0.834
DCP 9	.250	-0.192	-0.117	-0.017	0.076	0.177	0.284	0.364	0.462	0.553	0.646	0.734
DCP10	.300	-0.140	-0.054	0.026	0.115	0.191	0.246	0.356	0.426	0.510	0.591	0.658
DCP11	.355	-0.075	-0.026	0.041	0.131	0.161	0.233	0.292	0.360	0.431	0.480	0.525
DCP12	.501	-0.072	-0.015	0.027	0.076	0.125	0.155	0.211	0.264	0.295	0.360	0.412
DCP13	.600	-0.014	0.007	0.052	0.076	0.137	0.157	0.206	0.237	0.267	0.301	0.337
DCP14	.701	0.121	0.145	0.162	0.187	0.230	0.261	0.264	0.296	0.319	0.342	0.361
DCP15	.800	0.037	0.048	0.061	0.065	0.041	0.101	0.123	0.122	0.151	0.163	0.175
DCP16	.900	-0.117	-0.120	-0.125	-0.124	-0.114	-0.111	-0.124	-0.107	-0.106	-0.105	-0.094
DCP17	.969	-0.038	-0.045	-0.064	-0.050	-0.045	-0.062	-0.063	-0.060	-0.084	-0.077	-0.083

AIRFOIL NLR 7223-62 STEADY FORCES AND MOMENTS

M = 0.597 Rn = 9.4 x 10^6

FLOOR AND CEILING WITH 4.9% POROSITY

DATA TYPE	X/C											
ALPHA		4.591	4.887	5.495	6.156	7.053	7.258	8.016	8.554	9.288	9.524	10.226
CN		0.616	0.670	0.736	0.808	0.884	0.930	0.968	0.968	0.996	0.983	0.975
CM		-0.004	-0.001	0.001	0.006	0.014	0.018	0.024	0.027	0.023	0.014	-0.001
DCP 1	.010	1.825	1.951	2.440	2.742	3.064	3.137	3.508	3.297	3.372	3.553	3.481
DCP 2	.020	1.724	1.985	2.224	2.552	2.918	3.132	3.297	3.403	3.490	3.556	3.631
DCP 3	.030	1.725	1.952	2.111	2.312	2.757	2.984	3.140	3.246	3.353	3.434	3.509
DCP 4	.049	1.966	2.203	2.375	2.465	2.532	2.537	2.547	2.548	2.555	2.563	2.573
DCP 5	.074	1.587	2.278	2.468	2.593	2.731	2.928	3.070	3.180	3.292	3.353	3.416
DCP 6	.099	2.022	2.353	2.579	2.705	2.844	2.999	3.123	3.219	3.252	3.076	2.801
DCP 7	.149	1.159	1.113	1.501	2.028	2.631	2.741	2.781	2.385	2.235	1.915	1.850
DCP 8	.200	0.931	1.002	1.005	1.277	1.562	1.788	1.960	1.906	1.608	1.585	1.428
DCP 9	.250	0.811	0.891	0.922	0.941	1.027	1.201	1.365	1.367	1.677	1.579	1.497
DCP10	.300	0.736	0.781	0.837	0.856	0.853	0.902	0.583	0.593	1.408	1.295	1.267
DCP11	.399	0.598	0.649	0.697	0.738	0.759	0.766	0.808	0.830	0.560	1.058	1.070
DCP12	.501	0.438	0.490	0.515	0.549	0.564	0.576	0.568	0.595	0.641	0.615	0.729
DCP13	.600	0.380	0.400	0.430	0.446	0.456	0.445	0.441	0.399	0.434	0.444	0.478
DCP14	.701	0.382	0.357	0.408	0.407	0.410	0.391	0.341	0.303	0.295	0.306	0.370
DCP15	.800	0.177	0.183	0.191	0.196	0.188	0.195	0.167	0.148	0.130	0.165	0.228
DCP16	.900	-0.098	-0.102	-0.093	-0.082	-0.086	-0.075	-0.074	-0.084	-0.097	-0.055	0.004
DCP17	.969	-0.075	-0.085	-0.075	-0.078	-0.078	-0.093	-0.058	-0.090	-0.066	-0.018	-0.064

DATA TYPE	X/C											
ALPHA		10.757	11.772	12.074	12.754	13.204	13.531	14.665	15.240	15.761	16.402	17.127
CN		0.997	1.001	0.955	0.965	0.968	0.988	0.994	0.997	0.935	0.985	1.000
CM		-0.011	-0.019	-0.025	-0.027	-0.034	-0.045	-0.055	-0.065	-0.063	-0.086	-0.091
DCP 1	.010	3.574	3.572	3.551	3.387	3.254	2.596	3.051	2.701	3.133	1.874	1.845
DCP 2	.020	3.700	3.774	3.755	3.495	3.484	3.181	3.215	2.877	3.022	1.851	1.783
DCP 3	.030	3.603	3.656	3.738	3.585	3.557	3.349	3.546	3.004	2.755	2.052	2.007
DCP 4	.049	2.593	2.564	2.525	2.292	2.301	2.174	2.432	2.229	2.521	2.498	2.536
DCP 5	.074	3.403	3.029	2.780	2.314	2.236	2.131	2.352	2.161	2.193	2.416	2.531
DCP 6	.099	2.609	2.495	2.292	2.172	2.112	2.036	2.214	2.102	1.680	2.238	2.327
DCP 7	.149	1.654	1.687	1.465	1.748	1.696	1.712	1.556	1.741	1.474	1.814	1.893
DCP 8	.200	1.485	1.471	1.316	1.535	1.440	1.481	1.262	1.361	1.271	1.156	1.170
DCP 9	.250	1.430	1.491	1.375	1.461	1.430	1.552	1.310	1.375	1.218	1.191	1.130
DCP10	.300	1.298	1.243	1.175	1.292	1.299	1.375	1.172	1.221	1.173	1.139	1.097
DCP11	.399	0.991	1.092	1.056	1.061	1.047	1.121	1.034	1.125	0.984	1.041	1.023
DCP12	.501	0.800	0.782	0.771	0.747	0.815	0.891	0.872	0.865	0.839	0.904	0.903
DCP13	.600	0.570	0.562	0.585	0.601	0.584	0.654	0.819	0.793	0.737	0.816	0.806
DCP14	.701	0.419	0.439	0.455	0.467	0.542	0.502	0.583	0.621	0.555	0.718	0.770
DCP15	.800	0.261	0.265	0.298	0.278	0.333	0.344	0.435	0.474	0.468	0.545	0.655
DCP16	.900	0.012	0.081	0.063	0.062	0.069	0.086	0.155	0.118	0.157	0.232	0.214
DCP17	.969	-0.006	-0.002	0.025	-0.001	-0.057	-0.008	0.028	-0.003	0.005	0.042	0.028

AIRFOIL NLR 7223-62   STEADY FORCES AND MOMENTS

M = 0.597   Rn = 9.4 x 10^6 FLOOR AND CEILING WITH 4.9% POROSITY

DATA TYPE	x/C				
ALPHA		17.621	18.054	19.457	20.193
CN		1.006	1.002	1.032	1.056
CM		-0.091	-0.084	-0.085	-0.093
DCP 1	.013	1.845	1.875	1.857	2.168
DCP 2	.020	1.792	1.803	1.824	2.165
DCP 3	.033	2.001	1.945	1.875	2.407
DCP 4	.049	2.542	2.565	2.560	2.324
DCP 5	.074	2.502	2.547	2.576	2.281
DCP 6	.099	2.350	2.340	2.377	2.138
DCP 7	.149	1.954	2.112	2.162	1.987
DCP 8	.203	1.198	1.186	1.287	1.395
DCP 9	.250	1.139	1.147	1.205	1.380
DCP10	.300	1.070	1.082	1.135	1.277
DCP11	.399	1.304	1.027	1.058	1.123
DCP12	.501	0.925	0.865	0.922	0.991
DCP13	.600	0.846	0.806	0.820	0.870
CCP14	.701	0.752	0.739	0.755	0.773
DCP15	.800	0.627	0.612	0.624	0.593
DCP16	.933	0.235	0.222	0.232	0.205
CCP17	.969	0.036	-0.001	0.019	0.027

29

AIRFOIL NLR 7223-62   STEADY FORCES AND MOMENTS

M = 0.593 Rn = 9.4 x 10^6

FLOOR AND CEILING WITH 4.9% POROSITY

DATA TYPE	x/C											
ALPHA		1.234	1.156	2.363	3.035	3.761	4.445	4.781	5.413	5.567	6.685	7.428
CN		0.244	0.316	0.389	0.468	0.544	0.618	0.681	0.750	0.807	0.882	0.935
CM		-0.014	-0.014	-0.012	-0.012	-0.010	-0.005	-0.003	-0.001	0.005	0.011	0.018
DCP 1	.010	-0.081	0.324	0.734	1.096	1.492	1.886	2.252	2.594	3.030	3.293	3.457
DCP 2	.020	0.035	0.395	0.724	1.067	1.393	1.705	1.994	2.252	2.493	2.943	3.186
DCP 3	.030	0.264	0.541	0.853	1.164	1.466	1.740	1.980	2.165	2.350	2.772	3.014
DCP 4	.049	0.549	0.814	1.085	1.374	1.695	1.588	2.232	2.400	2.488	2.760	2.971
DCP 5	.074	0.695	0.917	1.157	1.415	1.705	1.978	2.285	2.474	2.604	2.767	2.970
DCP 6	.099	0.658	0.880	1.085	1.710	1.552	1.587	2.341	2.563	2.710	2.837	2.998
DCP 7	.149	0.518	0.635	0.746	0.895	1.042	1.133	1.081	1.543	1.946	2.647	2.781
DCP 8	.200	0.384	0.497	0.620	0.730	0.835	0.934	0.991	1.004	1.166	1.205	1.424
DCP 9	.250	0.350	0.454	0.552	0.634	0.728	0.822	0.889	0.939	0.951	0.990	1.192
DCP10	.300	0.335	0.418	0.496	0.573	0.657	0.724	0.802	0.840	0.863	0.840	0.886
DCP11	.399	0.288	0.335	0.408	0.478	0.534	0.594	0.655	0.706	0.745	0.768	0.786
DCP12	.501	0.226	0.273	0.326	0.352	0.415	0.466	0.508	0.530	0.548	0.586	0.595
DCP13	.600	0.208	0.237	0.272	0.330	0.355	0.358	0.426	0.454	0.476	0.476	0.478
DCP14	.701	0.264	0.308	0.311	0.347	0.373	0.385	0.420	0.435	0.416	0.434	0.416
DCP15	.800	0.116	0.140	0.148	0.174	0.186	0.180	0.190	0.196	0.203	0.207	0.180
DCP16	.900	-0.125	-0.124	-0.105	-0.095	-0.104	-0.109	-0.098	-0.084	-0.080	-0.075	-0.075
DCP17	.969	-0.066	-0.062	-0.071	-0.083	-0.066	-0.081	-0.103	-0.083	-0.103	-0.094	-0.089

DATA TYPE	x/C											
ALPHA		8.105	8.484	9.081	9.710	10.182	11.045	11.676	11.966	12.575	13.283	13.826
CN		0.997	1.006	1.031	1.027	1.036	1.021	1.010	0.928	1.022	1.303	0.976
CM		0.024	0.028	0.024	0.015	-0.002	-0.014	-0.017	-0.012	-0.033	-0.043	-0.033
DCP 1	.010	3.605	3.715	3.787	3.826	3.873	3.883	3.851	4.063	3.761	3.704	3.925
DCP 2	.020	3.342	3.475	3.571	3.624	3.695	3.734	3.765	3.612	3.833	3.741	3.742
DCP 3	.030	3.192	3.325	3.407	3.466	3.538	3.615	3.668	3.206	3.664	3.567	3.334
DCP 4	.049	3.142	3.267	3.358	3.417	3.467	3.504	3.455	2.543	3.206	2.466	2.724
DCP 5	.074	3.133	3.240	3.313	3.367	3.307	3.240	2.889	2.106	2.629	2.540	2.336
DCP 6	.099	3.148	3.236	3.249	3.085	2.835	2.601	2.509	1.556	2.389	2.337	1.918
DCP 7	.149	2.885	2.531	2.252	1.586	1.763	1.578	1.532	1.795	1.580	1.535	1.613
DCP 8	.200	1.712	1.788	1.613	1.561	1.472	1.390	1.353	1.592	1.386	1.271	1.504
DCP 9	.250	1.365	1.489	1.685	1.578	1.525	1.386	1.358	1.406	1.368	1.242	1.405
DCP10	.300	1.092	1.264	1.384	1.345	1.381	1.245	1.284	1.292	1.228	1.221	1.280
DCP11	.399	0.805	0.808	0.997	1.098	1.087	1.092	1.136	0.965	1.072	1.035	1.080
DCP12	.501	0.595	0.594	0.634	0.715	0.738	0.801	0.815	0.735	0.843	0.835	0.803
DCP13	.600	0.472	0.447	0.456	0.395	0.595	0.600	0.592	0.543	0.690	0.722	0.603
DCP14	.701	0.392	0.350	0.315	0.334	0.393	0.435	0.489	0.400	0.607	0.534	0.476
DCP15	.800	0.197	0.168	0.168	0.154	0.226	0.254	0.255	0.250	0.291	0.377	0.324
DCP16	.900	-0.095	-0.095	-0.100	-0.005	0.003	0.061	0.043	-0.034	0.090	0.157	0.125
DCP17	.969	-0.098	-0.077	-0.058	-0.032	-0.045	-0.003	-0.028	-0.053	-0.025	0.025	-0.045

$M = 0.593$ $R_a = 9.4 \times 10^6$

FLOOR AND CEILING WITH 4.9% POROSITY

DATA TYPE	x/C										
ALPHA		14.720	15.284	15.375	16.175	16.752	17.467	18.180	18.896	19.153	15.627
CN		1.017	0.991	1.027	1.030	0.577	1.011	1.027	1.105	1.055	1.010
CM		-0.075	-0.060	-0.060	-0.068	-0.081	-0.092	-0.087	-0.073	-0.085	-0.088
DCP 1	.013	3.633	3.881	3.725	3.750	3.703	3.724	3.747	3.566	3.714	3.177
DCP 2	.020	3.678	3.658	3.416	3.361	3.531	3.555	3.532	3.251	3.457	2.822
DCP 3	.033	3.522	2.992	2.944	3.076	3.115	3.100	2.568	2.731	2.841	2.889
DCP 4	.049	2.805	2.566	2.385	2.553	2.762	2.827	2.846	2.611	2.535	1.555
DCP 5	.074	2.456	2.196	2.347	2.417	2.580	2.704	2.785	2.472	2.455	1.708
DCP 6	.399	2.056	1.780	2.217	1.791	1.422	1.392	1.492	2.204	1.825	1.671
DCP 7	.149	1.293	1.481	1.615	1.673	1.257	1.340	1.357	1.588	1.592	1.532
DCP 8	.200	1.220	1.436	1.443	1.406	1.194	1.224	1.277	1.605	1.296	1.346
DCP 9	.250	1.166	1.325	1.377	1.391	1.135	1.164	1.215	1.531	1.307	1.398
DCP10	.300	1.130	1.198	1.236	1.237	1.041	1.082	1.145	1.418	1.228	1.374
DCP11	.399	1.086	1.133	1.056	1.081	1.021	1.006	1.067	1.131	1.110	1.214
DCP12	.531	0.858	0.861	0.919	0.941	0.877	0.888	0.892	0.957	0.984	0.556
DCP13	.600	0.806	0.657	0.601	0.801	0.742	0.803	0.855	0.857	0.817	0.821
DCP14	.731	0.652	0.653	0.641	0.646	0.720	0.724	0.766	0.665	0.746	0.705
DCP15	.800	0.545	0.394	0.441	0.502	0.578	0.621	0.572	0.456	0.590	0.506
DCP16	.900	0.286	0.176	0.178	0.155	0.275	0.393	0.284	0.212	0.295	0.191
DCP17	.969	0.085	0.032	0.058	-0.033	0.070	0.046	0.075	0.024	0.068	0.023

31

M = 0.699   Rn = 10.0 x 10^6

FLOOR AND CEILING WITH 4.9% POROSITY

DATA TYPE	x/c											
ALPHA		-1.641	-0.944	-0.242	0.563	0.823	1.363	1.542	2.641	3.205	3.576	4.741
CN		-0.102	-0.028	0.061	0.146	0.224	0.312	0.388	0.481	0.576	0.691	0.755
CM		-0.026	-0.021	-0.020	-0.015	-0.015	-0.012	-0.011	-0.009	-0.006	-0.006	-0.003
DCP 1	.010	-2.395	-2.090	-1.411	-0.870	-0.458	-0.046	0.307	0.605	0.767	1.053	1.390
DCP 2	.020	-2.049	-1.472	-0.589	-0.617	-0.264	0.075	0.376	0.637	0.877	1.113	1.331
DCP 3	.030	-1.724	-0.878	-0.627	-0.312	-0.009	0.270	0.523	0.744	0.940	1.128	1.286
DCP 4	.049	-0.468	-0.440	-0.176	0.123	0.375	0.643	0.890	1.085	1.258	1.423	1.562
DCP 5	.074	-0.312	-0.128	0.121	0.385	0.628	0.861	1.038	1.212	1.405	1.555	1.694
DCP 6	.099	-0.174	0.010	0.247	0.493	0.764	1.041	1.222	1.375	1.539	1.680	1.807
DCP 7	.149	-0.137	0.014	0.185	0.344	0.498	0.832	1.247	1.431	1.565	1.698	1.815
DCP 8	.200	-0.133	-0.010	0.135	0.248	0.380	0.490	0.503	1.334	1.492	1.627	1.737
DCP 9	.250	-0.055	0.011	0.125	0.244	0.354	0.466	0.493	0.560	1.473	1.606	1.715
DCP10	.300	-0.042	0.045	0.146	0.242	0.345	0.425	0.482	0.480	0.658	1.536	1.650
DCP11	.399	-0.327	0.046	0.129	0.197	0.269	0.354	0.418	0.448	0.421	0.476	0.754
DCP12	.501	-0.007	0.044	0.096	0.15	0.221	0.255	0.322	0.360	0.369	0.346	0.344
DCP13	.600	0.064	0.086	0.125	0.176	0.204	0.237	0.288	0.321	0.324	0.342	0.314
DCP14	.701	0.167	0.192	0.231	0.252	0.274	0.298	0.324	0.351	0.374	0.365	0.340
DCP15	.800	0.062	0.067	0.091	0.104	0.100	0.117	0.135	0.143	0.158	0.163	0.146
DCP16	.900	-0.123	-0.149	-0.139	-0.133	-0.139	-0.144	-0.145	-0.128	-0.131	-0.111	-0.136
DCP17	.969	-0.037	-0.048	-0.064	-0.060	-0.073	-0.068	-0.073	-0.081	-0.082	-0.065	-0.086

DATA TYPE	x/c											
ALPHA		5.216	5.588	6.337	6.815	7.297	7.566	8.835	9.636	9.810	10.392	11.048
CN		0.814	0.855	0.851	0.900	0.871	0.934	0.988	0.947	1.032	1.035	0.922
CM		-0.001	0.001	-0.005	-0.015	-0.020	-0.016	-0.024	-0.026	-0.040	-0.047	-0.050
DCP 1	.010	1.576	1.804	1.918	2.089	2.206	2.337	2.441	2.557	2.626	2.696	2.765
DCP 2	.020	1.467	1.589	1.691	1.829	1.971	2.121	2.260	2.345	2.457	2.571	2.627
DCP 3	.030	1.419	1.526	1.627	1.718	1.869	2.016	2.165	2.252	2.354	2.457	2.510
DCP 4	.049	1.687	1.767	1.826	1.939	1.971	2.071	2.186	2.256	2.347	2.434	2.494
DCP 5	.074	1.801	1.862	1.927	2.010	2.064	2.137	2.232	2.296	2.371	2.450	2.495
DCP 6	.099	1.923	1.996	2.044	2.107	2.158	2.238	2.293	2.340	2.415	2.477	2.484
DCP 7	.149	1.906	1.580	2.064	2.098	2.130	2.184	2.252	2.264	2.335	2.323	2.036
DCP 8	.200	1.836	1.904	1.927	2.016	1.730	2.055	2.168	1.675	1.941	1.577	1.035
DCP 9	.250	1.825	1.877	1.768	1.937	1.441	1.734	1.886	1.210	1.486	1.545	0.984
DCP10	.300	1.744	1.802	1.316	1.286	1.112	1.312	1.345	1.214	1.184	1.188	0.919
DCP11	.399	0.918	0.990	0.995	0.971	0.939	0.980	0.960	1.036	0.936	0.948	0.874
DCP12	.501	0.499	0.698	0.708	0.734	0.753	0.723	0.732	0.796	0.777	0.786	0.753
DCP13	.600	0.280	0.366	0.432	0.475	0.568	0.559	0.617	0.605	0.655	0.667	0.684
DCP14	.701	0.292	0.236	0.303	0.367	0.362	0.381	0.476	0.523	0.538	0.676	0.573
DCP15	.600	0.130	0.081	0.102	0.183	0.198	0.215	0.274	0.252	0.372	0.436	0.427
DCP16	.900	-0.120	-0.159	-0.121	-0.057	-0.025	-0.095	-0.035	-0.018	0.087	0.069	0.176
DCP17	.969	-0.375	-0.117	-0.092	-0.085	-0.030	-0.026	-0.076	-0.053	0.020	-0.023	0.034

AIRFOIL NLR 7223-62   STEADY FORCES AND MOMENTS

FLOOR AND CEILING WITH 4.9% POROSITY

M = 0.699   Rn = 10.0 x 10^6

DATA TYPE	x/C											
ALPHA		11.569	12.218	13.029	13.591	13.504	14.572	15.189	15.712	16.534	16.575	17.738
CN		0.956	0.540	0.971	0.996	0.582	1.031	1.047	1.085	1.122	1.150	1.185
CM		-0.054	-0.050	-0.055	-0.056	-0.049	-0.063	-0.065	-0.072	-0.082	-0.085	-0.110
DCP 1	.010	2.860	2.872	2.995	3.056	3.082	3.143	3.183	3.210	3.247	3.294	3.276
DCP 2	.020	2.726	2.776	2.662	2.920	2.960	3.052	3.112	3.158	3.217	3.217	3.150
DCP 3	.030	2.594	2.648	2.746	2.808	2.855	2.926	2.976	3.024	3.032	2.956	3.045
DCP 4	.049	2.586	2.607	2.692	2.704	2.747	2.839	2.851	2.866	2.852	2.667	2.054
DCP 5	.074	2.576	2.613	2.691	2.723	2.716	2.725	2.722	2.763	2.735	2.594	2.047
DCP 6	.099	2.538	2.536	2.572	2.601	2.591	2.576	2.454	2.543	2.513	2.465	2.219
DCP 7	.149	2.054	2.025	2.057	2.158	2.176	2.256	2.314	2.369	2.452	2.422	2.095
DCP 8	.200	1.081	1.060	1.027	1.121	1.094	1.093	1.135	1.206	1.282	1.481	1.866
DCP 9	.250	1.045	1.002	1.010	1.054	1.014	1.108	1.100	1.160	1.223	1.367	1.614
DCP10	.300	1.011	0.956	0.996	1.011	1.000	1.025	1.066	1.087	1.119	1.276	1.455
DCP11	.369	0.881	0.913	0.947	0.962	0.926	0.928	0.997	1.002	1.076	1.157	1.153
DCP12	.501	0.755	0.744	0.765	0.795	0.770	0.861	0.877	0.887	0.938	0.941	1.048
DCP13	.600	0.725	0.677	0.692	0.661	0.630	0.695	0.754	0.813	0.862	0.860	0.928
DCP14	.701	0.606	0.590	0.582	0.621	0.654	0.741	0.698	0.770	0.736	0.784	0.850
DCP15	.800	0.454	0.497	0.525	0.535	0.546	0.554	0.534	0.582	0.643	0.640	0.733
DCP16	.900	0.196	0.216	0.271	0.241	0.185	0.270	0.261	0.296	0.323	0.374	0.367
DCP17	.965	0.030	-0.035	-0.000	-0.017	-0.133	-0.058	-0.005	-0.057	0.023	-0.014	0.017

DATA TYPE	x/C			
ALPHA		18.183	19.629	19.249
CN		1.196	1.233	1.217
CM		-0.093	-0.122	-0.134
DCP 1	.010	3.316	3.331	3.089
DCP 2	.020	3.009	2.916	2.971
DCP 3	.030	2.675	2.652	2.592
DCP 4	.049	2.335	2.315	2.017
DCP 5	.074	2.064	1.868	1.943
DCP 6	.099	2.157	1.962	1.886
DCP 7	.149	2.312	2.158	1.955
DCP 8	.200	1.951	1.865	1.841
DCP 9	.250	1.757	1.666	1.752
DCP10	.300	1.572	1.525	1.572
DCP11	.369	1.466	1.304	1.357
DCP12	.501	1.171	1.075	1.146
DCP13	.600	0.922	0.928	1.020
DCP14	.701	0.762	0.540	0.926
DCP15	.800	0.632	0.762	0.604
DCP16	.900	0.203	0.360	0.394
DCP17	.965	-0.122	0.027	0.023

AIRFOIL NLR 7223-62 STEADY FORCES AND MOMENTS

FLOOR AND CEILING WITH 4.9% POROSITY

M = 0.702 Rn = 10.0 x 10^6

ALPHA		-0.208	0.696	1.930	3.028	3.995	5.032	5.895	6.751	7.912	8.031	9.854
CN		0.139	0.272	0.434	0.575	0.720	0.617	0.840	0.934	0.917	0.941	0.944
CM		-0.018	-0.015	-0.009	-0.006	-0.004	-0.001	-0.005	-0.026	-0.009	-0.017	-0.025
DCP 1	.010	-1.035	-0.225	0.326	0.747	1.226	1.494	1.748	2.125	2.147	2.437	2.573
DCP 2	.020	-0.844	-0.077	0.452	0.648	1.164	1.446	1.633	1.875	2.035	2.272	2.421
DCP 3	.030	-0.341	0.139	0.605	0.945	1.201	1.426	1.570	1.766	1.948	2.173	2.311
DCP 4	.049	0.042	0.521	0.903	1.242	1.473	1.664	1.762	1.919	2.011	2.191	2.317
DCP 5	.074	0.477	0.872	1.191	1.486	1.663	1.845	1.946	2.066	2.134	2.281	2.370
DCP 6	.099	0.474	0.931	1.288	1.534	1.720	1.901	1.996	2.117	2.163	2.289	2.342
DCP 7	.149	0.328	0.520	1.306	1.542	1.721	1.882	1.979	2.102	2.132	2.241	2.248
DCP 8	.200	0.243	0.444	1.081	1.465	1.662	1.825	1.907	2.026	2.068	2.172	1.629
DCP 9	.250	0.235	0.415	0.474	1.450	1.632	1.783	1.742	1.927	1.894	2.004	1.273
DCP10	.300	0.216	0.365	0.479	0.664	1.562	1.715	1.500	1.318	1.295	1.355	1.172
DCP11	.399	0.190	0.325	0.434	0.410	0.713	0.967	0.929	0.967	1.000	1.030	1.060
DCP12	.501	0.156	0.247	0.330	0.364	0.321	0.635	0.651	0.718	0.742	0.843	0.816
DCP13	.600	0.170	0.229	0.292	0.336	0.307	0.288	0.440	0.576	0.555	0.587	0.622
DCP14	.701	0.256	0.305	0.340	0.370	0.347	0.246	0.261	0.414	0.347	0.417	0.442
DCP15	.800	0.094	0.116	0.142	0.145	0.162	0.114	0.133	0.205	0.122	0.175	0.270
DCP16	.900	-0.137	-0.141	-0.139	-0.121	-0.115	-0.139	-0.064	-0.014	-0.099	-0.061	-0.023
DCP17	.969	-0.057	-0.075	-0.083	-0.074	-0.084	-0.103	-0.102	-0.067	-0.084	-0.080	-0.080

ALPHA		9.708	9.865	10.621	10.548	10.928	10.866	10.967	11.658	11.854	12.073	12.029
CN		0.485	0.902	0.909	0.917	0.932	0.943	0.924	0.936	0.937	0.953	0.945
CM		-0.027	-0.031	-0.046	-0.047	-0.053	-0.049	-0.043	-0.051	-0.046	-0.047	-0.052
DCP 1	.010	2.591	2.547	2.672	2.601	2.595	2.681	2.778	2.729	2.807	2.841	2.825
DCP 2	.020	2.470	2.445	2.504	2.566	2.567	2.593	2.614	2.707	2.706	2.714	2.714
DCP 3	.030	2.354	2.331	2.399	2.459	2.455	2.478	2.502	2.586	2.583	2.601	2.602
DCP 4	.049	2.155	2.330	2.382	2.441	2.440	2.457	2.480	2.561	2.547	2.554	2.571
DCP 5	.074	2.424	2.404	2.451	2.501	2.489	2.519	2.525	2.614	2.603	2.618	2.618
DCP 6	.099	2.413	2.393	2.432	2.467	2.458	2.493	2.482	2.453	2.512	2.511	2.497
DCP 7	.149	2.344	2.148	2.027	2.026	2.042	2.074	2.052	2.045	2.096	2.101	2.044
DCP 8	.200	1.036	1.197	1.035	1.060	1.094	1.142	1.069	1.057	1.049	1.107	1.153
DCP 9	.250	1.308	1.131	1.012	1.037	1.036	1.055	1.024	0.984	1.035	1.057	1.020
DCP10	.300	1.225	1.009	0.965	0.964	0.967	1.051	0.976	0.911	0.962	1.008	0.962
DCP11	.399	1.114	0.965	0.903	0.856	0.870	0.923	0.872	0.848	0.910	0.907	0.879
DCP12	.501	0.816	0.763	0.811	0.751	0.780	0.758	0.821	0.760	0.777	0.805	0.766
DCP13	.600	0.641	0.586	0.622	0.645	0.660	0.670	0.674	0.655	0.653	0.678	0.646
DCP14	.701	0.451	0.498	0.550	0.556	0.678	0.604	0.557	0.602	0.550	0.613	0.643
DCP15	.800	0.246	0.280	0.365	0.420	0.415	0.345	0.400	0.475	0.451	0.400	0.435
DCP16	.900	0.020	0.040	0.173	0.136	0.165	0.161	0.117	0.164	0.155	0.171	0.214
DCP17	.969	-0.066	0.005	0.000	-0.001	-0.011	-0.009	-0.036	0.026	-0.024	-0.041	-0.003

FLOOR AND CEILING WITH 4.9% POROSITY

$M = 0.702$ $Rn = 10.0 \times 10^6$

ALPHA		12.353	12.803	12.960	12.849	13.297	13.831	13.940	13.761	13.964	14.560	15.022
CN		0.960	0.978	0.976	0.976	0.997	1.015	1.011	1.010	1.015	1.045	1.057
CM		-0.052	-0.056	-0.057	-0.052	-0.058	-0.063	-0.057	-0.057	-0.060	-0.065	-0.067
DCP 1	.010	2.928	2.818	2.805	2.661	2.968	2.662	2.998	2.996	3.011	3.112	3.138
DCP 2	.020	2.800	2.858	2.830	2.847	2.879	2.960	2.955	2.932	2.963	3.059	3.071
DCP 3	.030	2.681	2.733	2.698	2.718	2.755	2.843	2.833	2.811	2.844	2.934	2.951
DCP 4	.049	2.649	2.696	2.670	2.672	2.710	2.765	2.763	2.735	2.771	2.755	2.787
DCP 5	.074	2.677	2.698	2.705	2.691	2.704	2.725	2.748	2.699	2.729	2.685	2.749
DCP 6	.099	2.535	2.565	2.540	2.520	2.556	2.548	2.568	2.542	2.565	2.451	2.491
DCP 7	.149	2.081	2.109	2.111	2.154	2.131	2.199	2.204	2.223	2.238	2.297	2.335
DCP 8	.200	1.052	1.043	1.136	1.125	1.048	1.113	1.141	1.211	1.166	1.212	1.201
DCP 9	.250	1.028	0.995	1.027	1.107	1.051	1.055	1.073	1.096	1.078	1.126	1.133
DCP10	.300	0.973	0.996	0.958	0.970	1.068	1.076	1.011	0.956	0.977	1.068	1.021
DCP11	.399	0.840	0.915	0.852	0.918	0.941	0.935	0.915	0.943	0.936	1.008	1.006
DCP12	.501	0.818	0.761	0.774	0.797	0.823	0.805	0.829	0.829	0.786	0.871	0.911
DCP13	.600	0.669	0.705	0.677	0.625	0.668	0.667	0.751	0.733	0.742	0.771	0.763
DCP14	.701	0.541	0.632	0.668	0.667	0.690	0.691	0.715	0.642	0.700	0.663	0.686
DCP15	.800	0.481	0.483	0.536	0.488	0.491	0.584	0.513	0.547	0.532	0.534	0.631
DCP16	.900	0.231	0.216	0.245	0.211	0.227	0.253	0.195	0.232	0.241	0.246	0.234
DCP17	.969	0.030	-0.026	-0.073	-0.050	-0.012	0.007	-0.064	-0.091	-0.018	0.035	-0.054

ALPHA		15.071	14.718	15.123	15.771	15.694	15.671	16.370	16.575	16.706	16.620	16.763
CN		1.054	1.055	1.075	1.067	1.109	1.102	1.122	1.117	1.129	1.090	1.119
CM		-0.067	-0.069	-0.069	-0.072	-0.083	-0.077	-0.060	-0.042	-0.085	-0.044	-0.058
DCP 1	.010	2.964	3.076	3.160	3.244	3.173	3.174	3.240	3.261	3.265	3.245	3.258
DCP 2	.020	3.039	3.056	3.120	3.183	3.142	3.128	3.180	3.222	3.224	3.138	2.931
DCP 3	.030	2.926	2.937	2.992	3.043	3.011	3.012	3.045	3.014	3.049	2.928	1.998
DCP 4	.049	2.781	2.747	2.810	2.831	2.814	2.801	2.841	2.384	2.832	2.011	2.344
DCP 5	.074	2.733	2.685	2.744	2.711	2.696	2.751	2.723	2.295	2.721	1.952	2.315
DCP 6	.099	2.520	2.462	2.517	2.508	2.501	2.526	2.529	2.177	2.548	1.827	2.251
DCP 7	.149	2.338	2.339	2.346	2.435	2.418	2.422	2.451	2.060	2.108	1.722	2.075
DCP 8	.200	1.263	1.163	1.240	1.171	1.250	1.249	1.300	1.406	1.365	1.464	1.769
DCP 9	.250	1.153	1.144	1.139	1.140	1.224	1.192	1.223	1.453	1.251	1.548	1.345
DCP10	.300	1.064	1.131	1.087	1.103	1.114	1.136	1.131	1.319	1.174	1.453	1.257
DCP11	.399	0.968	0.995	1.068	0.949	1.076	1.093	1.120	1.152	1.101	1.241	1.138
DCP12	.501	0.902	0.847	0.893	0.916	0.898	0.892	0.913	1.035	0.959	1.052	1.021
DCP13	.600	0.719	0.754	0.801	0.842	0.757	0.770	0.835	0.849	0.840	0.962	0.900
DCP14	.701	0.614	0.740	0.710	0.789	0.619	0.717	0.775	0.797	0.807	0.777	0.824
DCP15	.800	0.626	0.572	0.585	0.577	0.639	0.640	0.619	0.635	0.684	0.541	0.683
DCP16	.900	0.290	0.258	0.256	0.250	0.130	0.346	0.329	0.279	0.334	0.213	0.307
DCP17	.969	-0.023	-0.052	-0.036	-0.059	0.043	-0.016	-0.026	-0.007	0.010	-0.121	-0.088

AIRFOIL NLR 7223-62 STEADY FORCES AND MOMENTS

FLOOR AND CEILING WITH 4.9% POROSITY

M = 0.702 Rn = 10.0 x 10^6

ALPHA		17.428	17.930	17.723	17.631	18.113	16.566	16.714	16.925	16.634	16.343	16.427
CN		1.126	1.125	1.156	1.136	1.124	1.163	1.180	1.164	1.156	1.190	1.215
CM		-0.114	-0.111	-0.112	-0.114	-0.119	-0.132	-0.137	-0.131	-0.128	-0.136	-0.146
DCP 1	.010	3.126	3.325	3.294	3.274	3.345	3.284	3.316	3.321	3.264	3.063	3.069
DCP 2	.020	3.099	3.017	2.973	2.998	3.115	2.948	3.156	3.144	3.056	2.859	2.998
DCP 3	.030	3.035	2.892	1.981	2.025	2.741	2.843	2.767	2.843	2.666	2.629	2.647
DCP 4	.049	1.892	1.843	2.365	2.179	1.825	1.804	1.803	1.815	1.847	1.636	1.863
DCP 5	.074	1.830	1.781	2.320	2.136	1.735	1.741	1.726	1.755	1.754	1.742	1.776
DCP 6	.099	1.730	1.711	2.249	2.052	1.617	1.634	1.651	1.677	1.673	1.676	1.708
DCP 7	.149	1.662	1.585	2.028	1.966	1.492	1.563	1.544	1.522	1.557	1.557	1.593
DCP 8	.200	1.597	1.498	1.826	1.805	1.357	1.375	1.411	1.427	1.461	1.495	1.516
DCP 9	.250	1.665	1.723	1.364	1.367	1.577	1.652	1.597	1.526	1.643	1.742	1.782
DCP10	.300	1.452	1.666	1.284	1.305	1.674	1.648	1.755	1.735	1.665	1.721	1.747
DCP11	.399	1.257	1.456	1.197	1.216	1.444	1.438	1.530	1.460	1.468	1.465	1.476
DCP12	.501	1.078	1.036	1.061	1.054	1.120	1.216	1.207	1.168	1.166	1.229	1.258
DCP13	.600	0.978	0.869	0.934	0.929	0.951	1.021	1.024	1.001	0.903	1.006	1.041
DCP14	.701	0.869	0.816	0.854	0.844	0.850	0.895	0.873	0.864	0.855	0.846	0.914
DCP15	.800	0.679	0.669	0.740	0.716	0.674	0.712	0.727	0.721	0.754	0.746	0.793
DCP16	.900	0.295	0.270	0.368	0.374	0.283	0.323	0.350	0.349	0.336	0.343	0.366
DCP17	.969	-0.052	-0.027	0.016	0.001	-0.025	0.013	0.075	0.016	0.006	0.094	0.130

ALPHA		19.533	19.538	19.644	19.738	19.542
CN		1.246	1.210	1.206	1.207	1.202
CM		-0.157	-0.144	-0.143	-0.145	-0.143
DCP 1	.010	3.195	3.062	3.055	3.063	2.921
DCP 2	.020	3.077	2.963	2.934	2.867	2.837
DCP 3	.030	2.850	2.862	2.776	2.736	2.810
DCP 4	.049	1.871	1.855	1.853	1.850	1.874
DCP 5	.074	1.776	1.793	1.792	1.778	1.782
DCP 6	.099	1.706	1.705	1.716	1.700	1.714
DCP 7	.149	1.624	1.607	1.620	1.557	1.602
DCP 8	.200	1.485	1.464	1.491	1.514	1.519
DCP 9	.250	1.675	1.761	1.736	1.742	1.826
DCP10	.300	1.774	1.763	1.711	1.735	1.663
DCP11	.399	1.543	1.516	1.457	1.491	1.478
DCP12	.501	1.303	1.218	1.241	1.204	1.218
DCP13	.600	1.122	1.019	1.059	1.056	1.035
DCP14	.701	0.977	0.875	0.921	0.904	0.899
DCP15	.800	0.801	0.748	0.745	0.750	0.757
DCP16	.900	0.415	0.401	0.364	0.391	0.402
DCP17	.969	0.150	0.103	0.047	0.062	0.104

M = 0.750   Rn = 10.0 x 10^6

FLOOR AND CEILING WITH 4.9% POROSITY

ALPHA		2.145	1.476	0.674	-0.031	-0.623	-1.336	-1.854	-2.766	-2.786	-3.544	-4.215
CN		0.404	0.316	0.218	0.110	0.018	-0.076	-0.182	-0.334	-0.432	-0.535	-0.608
CM		-0.013	-0.014	-0.015	-0.021	-0.024	-0.026	-0.034	-0.037	-0.043	-0.047	-0.037
DCP 1	.010	-0.064	-0.261	-0.718	-1.155	-1.742	-1.583	-2.195	-2.349	-2.494	-2.625	-2.712
DCP 2	.020	0.343	-0.237	-0.552	-0.927	-1.372	-1.719	-1.946	-2.127	-2.336	-2.446	-2.552
DCP 3	.030	0.247	0.311	-0.256	-0.564	-1.061	-1.453	-1.658	-1.887	-2.054	-2.198	-2.314
DCP 4	.049	0.608	0.547	0.186	-0.074	-0.321	-0.695	-1.285	-1.493	-1.690	-1.825	-1.952
DCP 5	.074	0.775	0.617	0.475	0.196	-0.066	-0.513	-0.855	-1.164	-1.376	-1.533	-1.675
DCP 6	.099	0.565	0.613	0.635	0.418	0.144	0.016	-0.731	-1.005	-1.196	-1.356	-1.497
DCP 7	.149	1.013	0.675	0.695	0.315	0.392	-0.045	-0.587	-0.515	-0.645	-1.248	-1.382
DCP 8	.200	0.577	0.626	0.585	0.187	0.045	-0.358	-0.366	-0.906	-1.065	-1.207	-1.327
DCP 9	.250	0.482	0.634	0.262	0.217	0.276	-0.055	-0.067	-0.536	-1.054	-1.184	-1.302
DCP10	.300	0.945	0.561	0.333	0.225	0.103	-0.335	-0.051	-0.506	-0.525	-1.071	-1.183
DCP11	.399	0.432	0.256	0.275	0.175	0.067	0.036	-0.263	-0.697	-0.695	-0.402	-0.782
DCP12	.501	0.167	0.246	0.213	0.150	0.094	0.016	-0.046	-0.365	-0.026	-0.064	-0.262
DCP13	.600	0.239	0.236	0.221	0.167	0.134	0.086	0.033	-0.005	-0.337	0.052	0.015
DCP14	.701	0.334	0.312	0.311	0.265	0.243	0.226	0.196	0.164	0.167	0.171	0.184
DCP15	.800	0.105	0.103	0.137	0.073	0.092	0.076	0.054	0.027	0.035	0.036	0.067
DCP16	.900	-0.152	-0.162	-0.163	-0.152	-0.161	-0.153	-0.143	-0.146	-0.152	-0.136	-0.095
DCP17	.969	-0.086	-0.061	-0.068	-0.063	-0.067	-0.044	-0.036	-0.053	-0.057	-0.134	-0.031

ALPHA		-1.783	-1.174	-0.748	-0.149	0.377	1.073	1.619	6.485	7.171	7.868	8.634
CN		-0.123	-0.033	0.062	0.155	0.256	0.368	0.464	0.758	0.786	0.805	0.796
CM		-0.032	-0.028	-0.022	-0.019	-0.019	-0.015	-0.015	-0.026	-0.030	-0.036	-0.038
DCP 1	.010	-2.085	-1.864	-1.500	-0.927	-0.520	-0.179	0.104	1.513	1.626	1.796	1.900
DCP 2	.020	-1.843	-1.575	-1.079	-0.721	-0.369	-0.075	0.183	1.353	1.418	1.579	1.671
DCP 3	.030	-1.576	-1.290	-0.753	-0.411	-0.115	0.138	0.347	1.316	1.378	1.501	1.602
DCP 4	.049	-1.156	-0.581	-0.216	0.041	0.286	0.511	0.706	1.524	1.565	1.664	1.719
DCP 5	.074	-0.731	-0.311	0.022	0.273	0.490	0.689	0.855	1.649	1.685	1.781	1.819
DCP 6	.099	-0.478	0.008	0.271	0.527	0.713	0.884	1.027	1.737	1.762	1.861	1.896
DCP 7	.149	-0.053	-0.007	0.190	0.510	0.805	0.966	1.101	1.721	1.760	1.848	1.880
DCP 8	.200	-0.130	-0.036	0.119	0.230	0.755	0.911	1.078	1.671	1.706	1.687	1.615
DCP 9	.250	-0.095	0.006	0.145	0.263	0.307	0.918	1.056	1.496	1.533	1.247	1.137
DCP10	.300	-0.046	0.040	0.161	0.268	0.294	0.657	1.010	1.108	1.107	1.000	0.947
DCP11	.399	-0.025	0.054	0.154	0.229	0.308	0.254	0.717	0.757	0.776	0.833	0.745
DCP12	.501	-0.006	0.051	0.108	0.180	0.236	0.232	0.200	0.607	0.644	0.710	0.594
DCP13	.600	0.061	0.102	0.142	0.182	0.245	0.260	0.215	0.473	0.548	0.579	0.576
DCP14	.701	0.224	0.237	0.254	0.293	0.307	0.327	0.325	0.389	0.426	0.466	0.535
DCP15	.800	0.067	0.084	0.067	0.084	0.112	0.095	0.115	0.288	0.288	0.291	0.363
DCP16	.900	-0.142	-0.143	-0.147	-0.161	-0.143	-0.133	-0.134	-0.051	-0.066	0.003	0.059
DCP17	.969	-0.043	-0.035	-0.048	-0.077	-0.068	-0.075	-0.072	-0.110	-0.092	-0.105	-0.149

AIRFOIL NLR 7223-62   STEADY FORCES AND MOMENTS

FLOOR AND CEILING WITH 4.9% POROSITY

M ≈ 0.750   Rn = 10.0 x 10^6

ALPHA		9.054	9.43?	10.087	10.703	11.247	11.861	12.512	13.217	13.904	14.267
CN		0.913	0.568	0.902	0.892	0.875	0.921	0.954	0.995	1.054	1.075
CM		-0.045	-0.0?8	-0.051	-0.051	-0.054	-0.067	-0.072	-0.078	-0.092	-0.095
DCP 1	.010	2.054	2.178	2.293	2.347	2.462	2.507	2.589	2.643	2.703	2.765
DCP 2	.020	1.819	1.941	2.082	2.158	2.269	2.327	2.433	2.495	2.556	2.626
DCP 3	.030	1.750	1.872	1.996	2.068	2.179	2.223	2.321	2.382	2.456	2.518
DCP 4	.049	1.815	1.911	2.018	2.073	2.171	2.208	2.299	2.349	2.420	2.477
DCP 5	.074	1.890	1.964	2.057	2.110	2.196	2.232	2.325	2.371	2.424	2.484
DCP 6	.099	1.952	2.013	2.096	2.142	2.213	2.247	2.329	2.373	2.426	2.483
DCP 7	.149	1.926	1.968	2.048	2.080	2.044	2.052	2.117	2.122	2.175	2.212
DCP 8	.200	1.878	1.516	1.657	1.486	1.086	1.118	1.120	1.200	1.223	1.256
DCP 9	.250	1.816	1.213	1.119	1.000	0.974	0.987	1.094	1.089	1.189	1.196
DCP10	.300	1.278	1.052	0.991	0.974	0.873	0.989	0.974	1.052	1.092	1.130
DCP11	.399	0.858	0.854	0.899	0.821	0.815	0.832	0.864	0.953	1.043	1.015
DCP12	.501	0.684	0.677	0.747	0.782	0.756	0.778	0.749	0.845	0.905	0.926
DCP13	.600	0.593	0.581	0.609	0.623	0.603	0.686	0.709	0.721	0.794	0.825
DCP14	.701	0.561	0.572	0.607	0.600	0.589	0.632	0.667	0.700	0.759	0.735
DCP15	.800	0.447	0.454	0.488	0.469	0.506	0.544	0.607	0.617	0.655	0.688
DCP16	.900	0.055	0.152	0.152	0.177	0.221	0.288	0.307	0.320	0.354	0.402
DCP17	.949	-0.180	-0.187	-0.203	-0.179	-0.149	-0.068	-0.046	-0.044	0.045	0.048

M = 0.797 Rn = 10.5 x 10^6

ALPHA		-1.687	-1.062	-0.507	-0.045	0.614	1.098	1.721	2.341	3.143	3.836	4.234
CN		-0.131	-0.012	0.105	0.221	0.332	0.416	0.455	0.479	0.478	0.505	0.495
CM		-0.035	-0.031	-0.029	-0.028	-0.035	-0.040	-0.039	-0.031	-0.018	-0.015	0.001
DCP 1	.010	-1.831	-1.668	-1.423	-0.981	-0.675	-0.428	-0.258	-0.064	0.097	0.278	0.420
DCP 2	.020	-1.592	-1.400	-1.033	-0.813	-0.543	-0.312	-0.163	0.022	0.160	0.313	0.435
DCP 3	.030	-1.366	-1.165	-0.881	-0.512	-0.282	-0.095	0.035	0.186	0.309	0.443	0.539
DCP 4	.049	-0.969	-0.711	-0.183	-0.048	0.123	0.286	0.394	0.524	0.619	0.739	0.830
DCP 5	.074	-0.479	-0.352	-0.136	0.137	0.312	0.459	0.554	0.668	0.756	0.877	0.963
DCP 6	.099	-0.348	-0.113	0.234	0.419	0.562	0.676	0.747	0.843	0.923	1.018	1.097
DCP 7	.149	-0.333	0.080	0.335	0.517	0.654	0.761	0.831	0.922	0.982	1.067	1.127
DCP 8	.200	-0.393	0.016	0.314	0.505	0.618	0.734	0.802	0.896	0.955	1.033	1.089
DCP 9	.250	-0.398	0.029	0.283	0.519	0.638	0.735	0.802	0.887	0.942	1.027	1.078
DCP10	.300	-0.333	0.078	0.189	0.513	0.628	0.730	0.795	0.869	0.917	0.987	1.046
DCP11	.399	0.124	0.074	0.162	0.497	0.637	0.728	0.778	0.850	0.895	0.964	0.993
DCP12	.501	0.091	0.092	0.217	0.237	0.624	0.712	0.749	0.807	0.844	0.661	0.377
DCP13	.600	0.131	0.146	0.202	0.152	0.416	0.763	0.802	0.563	0.215	0.201	0.204
DCP14	.701	0.270	0.299	0.326	0.324	0.184	0.148	0.179	0.146	0.145	0.169	0.181
DCP15	.800	0.056	0.061	0.066	0.072	0.045	-0.001	-0.019	-0.001	0.032	0.078	0.104
DCP16	.900	-0.159	-0.151	-0.168	-0.159	-0.169	0.196	-0.208	-0.185	-0.211	-0.201	-0.196
DCP17	.969	-0.059	-0.047	-0.057	-0.056	-0.071	-0.086	-0.118	-0.113	-0.120	-0.114	-0.364

ALPHA		4.728	5.358	5.907	6.476	7.289	7.851	8.514	8.992	9.601	10.150	10.777
CN		0.530	0.576	0.628	0.679	0.735	0.801	0.865	0.951	1.026	1.099	1.197
CM		0.001	-0.006	-0.018	-0.025	-0.041	-0.053	-0.069	-0.093	-0.110	-0.130	-0.161
DCP 1	.010	0.574	0.728	0.846	1.045	1.074	1.257	1.387	1.530	1.654	1.781	1.880
DCP 2	.020	0.571	0.709	0.810	0.950	1.039	1.159	1.248	1.331	1.454	1.573	1.683
DCP 3	.030	0.651	0.765	0.838	0.963	1.038	1.131	1.219	1.291	1.390	1.509	1.612
DCP 4	.049	0.924	1.027	1.086	1.186	1.242	1.322	1.388	1.448	1.523	1.588	1.668
DCP 5	.074	1.047	1.143	1.208	1.300	1.343	1.438	1.496	1.545	1.610	1.667	1.730
DCP 6	.099	1.168	1.262	1.295	1.405	1.442	1.518	1.581	1.625	1.691	1.736	1.783
DCP 7	.149	1.202	1.275	1.322	1.408	1.440	1.515	1.565	1.611	1.670	1.720	1.761
DCP 8	.200	1.148	1.219	1.271	1.347	1.390	1.459	1.513	1.553	1.610	1.655	1.701
DCP 9	.250	1.138	1.205	1.241	1.322	1.359	1.427	1.471	1.513	1.566	1.611	1.651
DCP10	.300	1.092	1.160	1.194	1.261	1.303	1.358	1.406	1.444	1.492	1.540	1.571
DCP11	.399	1.056	1.013	1.081	1.059	1.154	1.247	1.332	1.387	1.434	1.478	1.518
DCP12	.501	0.348	0.395	0.448	0.497	0.548	0.606	0.698	0.986	1.240	1.368	1.408
DCP13	.600	0.221	0.273	0.324	0.373	0.433	0.506	0.554	0.628	0.694	0.818	1.305
DCP14	.701	0.210	0.239	0.296	0.336	0.390	0.441	0.515	0.582	0.641	0.716	0.792
DCP15	.800	0.135	0.191	0.243	0.268	0.319	0.392	0.440	0.532	0.582	0.651	0.720
DCP16	.900	-0.145	-0.125	-0.063	-0.027	0.053	0.090	0.157	0.243	0.288	0.352	0.425
DCP17	.969	-0.475	-0.433	-0.393	-0.335	-0.272	-0.241	-0.163	-0.083	-0.031	0.040	0.117

AIRFOIL NLR 7223-62 STEADY FORCES AND MOMENTS

M = 0.797 Rn = 10.5 x 10^6 FLOOR AND CEILING WITH 4.9% POROSITY

ALPHA		11.200	12.076	12.639	13.817	13.783
CN		1.280	1.437	1.524	1.563	1.608
CM		-0.186	-0.258	-0.293	-0.300	-0.308
DCP 1	.010	2.010	2.070	2.127	2.237	2.291
DCP 2	.020	1.801	1.888	1.985	2.062	2.156
DCP 3	.030	1.727	1.812	1.906	1.984	2.072
DCP 4	.049	1.754	1.813	1.893	1.963	2.042
DCP 5	.074	1.803	1.859	1.932	1.990	2.060
DCP 6	.099	1.845	1.896	1.959	2.013	2.078
DCP 7	.149	1.811	1.852	1.909	1.958	2.018
DCP 8	.200	1.760	1.797	1.848	1.894	1.948
DCP 9	.250	1.705	1.746	1.795	1.837	1.890
DCP10	.300	1.624	1.656	1.706	1.745	1.792
DCP11	.399	1.566	1.601	1.648	1.685	1.731
DCP12	.501	1.454	1.490	1.533	1.566	1.615
DCP13	.600	1.398	1.432	1.470	1.503	1.543
DCP14	.701	1.026	1.408	1.444	1.473	1.506
DCP15	.800	0.786	1.405	1.495	1.516	1.553
DCP16	.900	0.510	0.753	1.218	1.251	1.275
DCP17	.969	0.209	0.406	0.456	0.517	0.543

M = 0.800   Rn = 10.5 x 10⁶

ALPHA		1.626	1.052	0.557	-0.253	-0.983	-1.486	-2.193	-2.558	-4.695	-5.139	-5.930
CN		0.425	0.365	0.260	0.158	0.028	-0.079	-0.231	-0.346	-0.523	-0.550	-0.537
CM		-0.039	-0.038	-0.027	-0.028	-0.030	-0.034	-0.031	-0.026	-0.003	-0.012	-0.030
DCP 1	.010	-0.425	-0.637	-0.900	-1.293	-1.609	-1.775	-1.956	-2.065	-2.239	-2.377	-2.425
DCP 2	.020	-0.252	-0.450	-0.687	-0.938	-1.271	-1.510	-1.680	-1.838	-2.049	-2.185	-2.238
DCP 3	.030	-0.050	-0.216	-0.416	-0.760	-1.019	-1.287	-1.470	-1.624	-1.837	-1.989	-2.049
DCP 4	.049	0.323	0.176	0.024	-0.156	-0.563	-0.868	-1.073	-1.235	-1.471	-1.625	-1.687
DCP 5	.074	0.485	0.354	0.204	-0.049	-0.264	-0.417	-0.573	-0.778	-1.131	-1.311	-1.392
DCP 6	.099	0.697	0.592	0.475	0.308	0.014	-0.251	-0.484	-0.726	-1.013	-1.177	-1.246
DCP 7	.149	0.781	0.687	0.568	0.414	0.212	-0.249	-0.476	-0.685	-0.927	-1.082	-1.148
DCP 8	.200	0.750	0.647	0.547	0.394	0.069	-0.316	-0.546	-0.714	-0.912	-1.050	-1.101
DCP 9	.250	0.756	0.667	0.561	0.414	0.049	-0.256	-0.538	-0.696	-0.882	-1.007	-1.058
DCP10	.300	0.744	0.656	0.545	0.414	0.146	0.103	-0.466	-0.612	-0.792	-0.913	-0.962
DCP11	.399	0.736	0.662	0.565	0.380	0.108	0.072	-0.474	-0.615	-0.778	-0.894	-0.890
DCP12	.501	0.711	0.649	0.553	0.116	0.144	0.067	0.127	-0.350	-0.756	-0.307	-0.272
DCP13	.600	0.765	0.704	0.125	0.208	0.178	0.118	0.140	0.156	-0.111	-0.123	-0.133
DCP14	.701	0.196	0.137	0.227	0.325	0.311	0.283	0.276	0.296	0.123	0.094	0.065
DCP15	.800	-0.024	0.005	0.050	0.065	0.061	0.064	0.067	0.088	0.054	-0.016	0.362
DCP16	.900	-0.215	-0.204	-0.184	-0.168	-0.173	-0.160	-0.171	-0.141	-0.091	-0.104	-0.158
DCP17	.969	-0.093	-0.087	-0.061	-0.067	-0.059	-0.041	-0.057	-0.061	-0.079	-0.059	-0.056

ALPHA		-6.497	-7.072	-7.508	-8.021	-8.819	-9.433	-10.113
CN		-0.535	-0.561	-0.559	-0.602	-0.666	-0.738	-0.807
CM		-0.037	-0.036	-0.057	-0.053	-0.041	-0.025	-0.004
DCP 1	.010	-2.503	-2.573	-2.618	-2.643	-2.837	-2.781	-2.768
DCP 2	.020	-2.303	-2.369	-2.427	-2.486	-2.532	-2.593	-2.615
DCP 3	.030	-2.122	-2.178	-2.243	-2.308	-2.367	-2.437	-2.464
DCP 4	.049	-1.760	-1.836	-1.911	-1.979	-2.046	-2.113	-2.151
DCP 5	.074	-1.471	-1.549	-1.639	-1.707	-1.783	-1.858	-1.901
DCP 6	.099	-1.328	-1.400	-1.475	-1.543	-1.611	-1.686	-1.734
DCP 7	.149	-1.231	-1.304	-1.382	-1.445	-1.506	-1.570	-1.606
DCP 8	.200	-1.164	-1.227	-1.295	-1.365	-1.427	-1.489	-1.524
DCP 9	.250	-1.119	-1.183	-1.247	-1.299	-1.361	-1.415	-1.447
DCP10	.300	-1.015	-1.071	-1.084	-1.132	-1.213	-1.281	-1.327
DCP11	.399	-0.637	-0.557	-0.534	-0.582	-0.701	-0.852	-1.036
DCP12	.501	-0.303	-0.321	-0.381	-0.445	-0.506	-0.590	-0.648
DCP13	.600	-0.136	-0.173	-0.238	-0.286	-0.361	-0.433	-0.487
DCP14	.701	0.054	-0.017	-0.045	-0.106	-0.152	-0.212	-0.278
DCP15	.800	0.420	0.386	0.358	0.270	0.238	0.173	0.098
DCP16	.900	-0.157	-0.093	0.339	0.301	0.265	0.209	0.123
DCP17	.969	-0.087	-0.102	-0.064	0.162	0.100	0.045	-0.042

AIRFOIL NLR 7223-62   STEADY FORCES AND MOMENTS

M = 0.849   Rn = 11.0 x 10⁶

FLOOR AND CEILING WITH 4.9% POROSITY

ALPHA		1.283	0.693	0.192	-0.481	-1.377	-1.887	-2.585	-3.070	-3.546	-4.261	-4.928
CN		0.179	0.107	0.028	-0.036	-0.120	-0.199	-0.206	-0.282	-0.329	-0.389	-0.470
CM		-0.009	0.004	0.016	0.012	0.016	0.016	-0.009	-0.015	-0.021	-0.013	0.009
DCP 1	.010	-0.835	-1.147	-1.326	-1.387	-1.526	-1.645	-1.684	-1.868	-1.911	-1.947	-2.130
DCP 2	.020	-0.682	-0.812	-0.898	-1.091	-1.227	-1.355	-1.438	-1.565	-1.651	-1.728	-1.806
DCP 3	.030	-0.429	-0.634	-0.764	-0.868	-1.010	-1.147	-1.233	-1.359	-1.439	-1.519	-1.600
DCP 4	.049	-0.021	-0.090	-0.253	-0.450	-0.582	-0.735	-0.831	-0.982	-1.071	-1.149	-1.232
DCP 5	.074	0.083	-0.016	-0.095	-0.187	-0.275	-0.319	-0.363	-0.520	-0.654	-0.787	-0.898
DCP 6	.099	0.369	0.282	0.114	0.023	-0.053	-0.155	-0.236	-0.431	-0.570	-0.684	-0.780
DCP 7	.149	0.459	0.381	0.304	0.135	0.038	-0.062	-0.164	-0.415	-0.526	-0.631	-0.725
DCP 8	.200	0.410	0.338	0.273	0.092	-0.002	-0.126	-0.312	-0.464	-0.548	-0.630	-0.706
DCP 9	.250	0.419	0.326	0.239	0.115	-0.029	-0.184	-0.308	-0.453	-0.532	-0.608	-0.682
DCP10	.300	0.434	0.348	0.258	0.202	-0.001	-0.146	-0.251	-0.360	-0.438	-0.515	-0.596
DCP11	.399	0.406	0.343	0.247	0.147	-0.033	-0.259	-0.260	-0.383	-0.471	-0.528	-0.589
DCP12	.501	0.338	0.279	0.196	0.093	-0.028	-0.217	-0.290	-0.401	-0.428	-0.482	-0.550
DCP13	.600	0.324	0.270	0.194	0.069	-0.063	-0.112	-0.203	-0.341	-0.405	-0.451	-0.502
DCP14	.701	0.330	0.281	0.225	0.146	0.060	-0.005	-0.101	-0.200	-0.247	-0.295	-0.337
DCP15	.800	-0.161	-0.274	-0.382	-0.412	-0.423	-0.316	0.197	0.405	0.027	-0.025	-0.072
DCP16	.900	-0.358	-0.467	-0.506	-0.245	-0.090	-0.021	0.016	0.096	0.552	0.400	0.147
DCP17	.969	-0.124	-0.038	-0.012	-0.018	-0.013	-0.006	0.036	0.032	0.166	0.343	0.309

ALPHA		-5.577	-6.159	-6.665	-7.137	-7.733	-8.454	-9.078	-9.631
CN		-0.548	-0.620	-0.680	-0.734	-0.795	-0.854	-0.909	-0.964
CM		0.039	0.058	0.071	0.080	0.092	0.104	0.113	0.124
DCP 1	.010	-2.100	-2.260	-2.208	-2.354	-2.433	-2.346	-2.495	-2.502
DCP 2	.020	-1.856	-1.927	-2.000	-2.069	-2.137	-2.208	-2.261	-2.322
DCP 3	.030	-1.661	-1.736	-1.814	-1.880	-1.949	-2.025	-2.094	-2.163
DCP 4	.049	-1.292	-1.375	-1.457	-1.531	-1.606	-1.686	-1.763	-1.837
DCP 5	.074	-0.985	-1.070	-1.164	-1.240	-1.333	-1.422	-1.506	-1.584
DCP 6	.099	-0.857	-0.943	-1.033	-1.107	-1.194	-1.276	-1.358	-1.438
DCP 7	.149	-0.802	-0.882	-0.960	-1.038	-1.112	-1.189	-1.264	-1.335
DCP 8	.200	-0.764	-0.832	-0.909	-0.978	-1.052	-1.129	-1.201	-1.268
DCP 9	.250	-0.734	-0.806	-0.873	-0.934	-1.005	-1.073	-1.140	-1.199
DCP10	.300	-0.645	-0.712	-0.780	-0.840	-0.908	-0.972	-1.040	-1.102
DCP11	.399	-0.632	-0.692	-0.748	-0.808	-0.866	-0.928	-0.990	-1.049
DCP12	.501	-0.600	-0.671	-0.727	-0.774	-0.830	-0.888	-0.941	-0.996
DCP13	.600	-0.546	-0.598	-0.650	-0.701	-0.759	-0.823	-0.877	-0.930
DCP14	.701	-0.380	-0.449	-0.518	-0.575	-0.631	-0.683	-0.723	-0.764
DCP15	.800	-0.109	-0.144	-0.171	-0.211	-0.255	-0.294	-0.337	-0.402
DCP16	.900	-0.118	-0.150	-0.200	-0.264	-0.336	-0.399	-0.435	-0.477
DCP17	.969	0.040	-0.234	-0.333	-0.304	-0.344	-0.380	-0.401	-0.426

M = 0.849 Rn = 11.0 x 10⁶

ALPHA		-1.900	-1.359	-0.668	-0.086	0.824	1.301	1.737	2.370	2.898	3.573	4.422
CN		-0.162	-0.127	-0.036	0.026	0.104	0.181	0.247	0.310	0.384	0.479	0.584
CM		0.007	0.017	0.009	0.016	0.008	-0.005	-0.018	-0.023	-0.045	-0.077	-0.113
DCP 1	.010	-1.609	-1.542	-1.391	-1.267	-1.013	-0.800	-0.623	-0.498	-0.419	-0.277	-0.032
DCP 2	.020	-1.337	-1.244	-1.099	-0.910	-0.825	-0.688	-0.560	-0.370	-0.240	-0.102	0.023
DCP 3	.030	-1.107	-1.021	-0.876	-0.770	-0.623	-0.408	-0.287	-0.145	-0.042	0.083	0.195
DCP 4	.049	-0.703	-0.591	-0.462	-0.306	-0.094	-0.005	0.089	0.215	0.309	0.398	0.485
DCP 5	.074	-0.288	-0.260	-0.179	-0.096	-0.008	0.113	0.234	0.366	0.448	0.536	0.622
DCP 6	.099	-0.122	-0.058	0.029	0.115	0.295	0.399	0.466	0.557	0.621	0.695	0.773
DCP 7	.149	-0.041	0.031	0.126	0.293	0.376	0.476	0.534	0.624	0.684	0.749	0.819
DCP 8	.200	-0.089	-0.006	0.085	0.269	0.342	0.426	0.492	0.582	0.647	0.718	0.783
DCP 9	.250	-0.148	-0.028	0.103	0.236	0.332	0.434	0.503	0.587	0.650	0.712	0.781
DCP10	.300	-0.083	-0.004	0.184	0.252	0.355	0.448	0.507	0.581	0.639	0.693	0.753
DCP11	.399	-0.201	-0.051	0.142	0.241	0.343	0.412	0.462	0.533	0.583	0.642	0.706
DCP12	.501	-0.204	-0.044	0.092	0.187	0.281	0.347	0.400	0.471	0.519	0.575	0.633
DCP13	.600	-0.082	-0.067	0.056	0.191	0.277	0.339	0.385	0.460	0.508	0.558	0.616
DCP14	.701	0.024	0.053	0.151	0.225	0.284	0.340	0.423	0.504	0.545	0.608	0.665
DCP15	.800	-0.182	-0.426	-0.435	-0.354	-0.311	-0.219	-0.072	-0.047	0.133	0.440	0.806
DCP16	.900	-0.060	-0.087	-0.159	-0.522	-0.500	-0.403	-0.265	-0.227	-0.100	0.018	0.173
DCP17	.969	0.015	-0.025	-0.036	-0.008	-0.056	-0.099	-0.307	-0.424	-0.368	-0.240	-0.153

ALPHA		4.942	5.317	5.989	6.448	7.271	7.916	8.463	8.975
CN		0.670	0.749	0.812	0.870	0.926	0.982	1.038	1.092
CM		-0.142	-0.168	-0.182	-0.191	-0.200	-0.208	-0.217	-0.225
DCP 1	.010	0.063	0.255	0.386	0.552	0.643	0.780	0.922	1.075
DCP 2	.020	0.145	0.263	0.388	0.523	0.649	0.771	0.898	1.026
DCP 3	.030	0.296	0.398	0.498	0.605	0.713	0.824	0.928	1.025
DCP 4	.049	0.577	0.662	0.756	0.845	0.934	1.024	1.114	1.201
DCP 5	.074	0.700	0.778	0.866	0.964	1.053	1.136	1.217	1.298
DCP 6	.099	0.848	0.920	0.994	1.070	1.154	1.233	1.315	1.387
DCP 7	.149	0.882	0.944	1.017	1.091	1.162	1.232	1.299	1.371
DCP 8	.200	0.844	0.899	0.968	1.038	1.108	1.179	1.248	1.317
DCP 9	.250	0.840	0.898	0.964	1.026	1.091	1.161	1.229	1.291
DCP10	.300	0.812	0.866	0.924	0.989	1.051	1.112	1.175	1.234
DCP11	.399	0.765	0.817	0.875	0.942	0.999	1.064	1.125	1.183
DCP12	.501	0.688	0.742	0.798	0.858	0.914	0.974	1.036	1.093
DCP13	.600	0.672	0.723	0.781	0.836	0.893	0.949	1.001	1.056
DCP14	.701	0.743	0.794	0.844	0.889	0.939	0.989	1.034	1.081
DCP15	.800	0.875	0.920	0.960	1.007	1.045	1.080	1.121	1.152
DCP16	.900	0.497	0.764	0.796	0.821	0.853	0.882	0.916	0.946
DCP17	.969	-0.098	0.042	0.208	0.251	0.269	0.279	0.297	0.317

43

AIRFOIL NLR 7223-62   STEADY FORCES AND MOMENTS

FLOOR AND CEILING WITH 4.9% POROSITY

M = 0.898   Rn = 3.6 x 10^6

ALPHA		-4.757	-4.148	-3.615	-3.094	-2.258	-1.626	-0.976	-0.517	-0.074	0.721	1.276
CN		-0.460	-0.391	-0.321	-0.253	-0.180	-0.104	-0.033	0.041	0.124	0.197	0.259
CM		0.041	0.031	0.020	0.008	-0.005	-0.019	-0.032	-0.047	-0.063	-0.076	-0.085
DCP 1	.010	-1.743	-1.641	-1.552	-1.478	-1.432	-1.377	-1.288	-1.276	-1.159	-0.990	-0.778
DCP 2	.020	-1.610	-1.505	-1.413	-1.329	-1.274	-1.214	-1.157	-1.063	-0.934	-0.822	-0.719
DCP 3	.030	-1.415	-1.325	-1.241	-1.156	-1.071	-0.995	-0.918	-0.836	-0.785	-0.685	-0.510
DCP 4	.049	-1.059	-0.967	-0.867	-0.785	-0.693	-0.628	-0.528	-0.446	-0.369	-0.202	-0.082
DCP 5	.074	-0.804	-0.703	-0.599	-0.504	-0.415	-0.328	-0.245	-0.160	-0.090	-0.006	0.074
DCP 6	.099	-0.662	-0.555	-0.455	-0.361	-0.262	-0.178	-0.100	-0.004	0.062	0.119	0.215
DCP 7	.149	-0.631	-0.519	-0.409	-0.286	-0.199	-0.103	-0.033	0.049	0.140	0.262	0.347
DCP 8	.200	-0.625	-0.530	-0.424	-0.316	-0.187	-0.080	-0.003	0.052	0.133	0.282	0.345
DCP 9	.250	-0.609	-0.526	-0.443	-0.347	-0.244	-0.133	-0.045	0.017	0.158	0.244	0.306
DCP10	.300	-0.507	-0.424	-0.345	-0.271	-0.170	-0.072	0.010	0.077	0.214	0.271	0.333
DCP11	.399	-0.527	-0.452	-0.362	-0.245	-0.203	-0.116	-0.042	0.070	0.194	0.253	0.317
DCP12	.501	-0.485	-0.416	-0.343	-0.290	-0.253	-0.152	-0.035	0.091	0.163	0.222	0.278
DCP13	.600	-0.441	-0.386	-0.333	-0.266	-0.186	-0.119	-0.027	0.054	0.149	0.223	0.275
DCP14	.701	-0.321	-0.257	-0.196	-0.141	-0.077	0.003	0.062	0.119	0.186	0.248	0.315
DCP15	.800	-0.045	0.002	0.052	0.107	0.167	0.211	0.252	0.316	0.379	0.444	0.485
DCP16	.900	-0.092	-0.055	-0.007	0.035	0.090	0.140	0.181	0.215	0.273	0.320	0.352
DCP17	.969	-0.311	-0.284	-0.263	-0.225	-0.184	-0.150	-0.124	-0.088	-0.063	-0.011	0.022

ALPHA		1.900	2.660	3.179	3.720	4.313
CN		0.327	0.400	0.470	0.536	0.610
CM		-0.096	-0.109	-0.119	-0.130	-0.145
DCP 1	.010	-0.685	-0.545	-0.298	-0.146	0.026
DCP 2	.020	-0.559	-0.421	-0.268	-0.118	0.042
DCP 3	.030	-0.353	-0.202	-0.068	0.055	0.183
DCP 4	.049	0.017	0.139	0.273	0.381	0.490
DCP 5	.074	0.175	0.311	0.414	0.504	0.613
DCP 6	.099	0.341	0.444	0.538	0.616	0.704
DCP 7	.149	0.424	0.508	0.596	0.670	0.766
DCP 8	.200	0.420	0.506	0.600	0.656	0.737
DCP 9	.250	0.373	0.476	0.563	0.641	0.722
DCP10	.300	0.410	0.494	0.574	0.643	0.717
DCP11	.399	0.389	0.452	0.510	0.598	0.661
DCP12	.501	0.340	0.409	0.475	0.541	0.614
DCP13	.600	0.335	0.388	0.464	0.521	0.580
DCP14	.701	0.369	0.429	0.503	0.564	0.631
DCP15	.800	0.533	0.607	0.654	0.709	0.766
DCP16	.900	0.405	0.477	0.522	0.574	0.651
DCP17	.969	0.064	0.078	0.082	0.097	0.120

M = 0.901   Rn = 7.2 x 10⁶

ALPHA		-0.407	-1.316	-2.126	-3.051	-4.140	-5.028	-6.238	-7.077	-7.855
CN		0.073	-0.037	-0.164	-0.283	-0.390	-0.492	-0.585	-0.682	-0.766
CM		-0.050	-0.029	-0.007	0.013	0.030	0.048	0.064	0.075	0.044
DCP 1	.010	-1.265	-1.404	-1.537	-1.805	-1.952	-1.871	-1.961	-2.088	-2.177
DCP 2	.020	-0.985	-1.159	-1.310	-1.429	-1.543	-1.673	-1.780	-1.904	-2.019
DCP 3	.030	-0.742	-0.942	-1.0?	-1.206	-1.338	-1.470	-1.588	-1.729	-1.838
DCP 4	.044	-0.416	-0.570	-0.7??	-0.865	-1.004	-1.147	-1.260	-1.406	-1.522
DCP 5	.074	-0.074	-0.170	-0.313	-0.512	-0.685	-0.841	-0.988	-1.133	-1.260
DCP 6	.099	0.248	-0.029	-0.131	-0.322	-0.518	-0.695	-0.853	-1.014	-1.133
DCP 7	.144	0.111	0.004	-0.156	-0.343	-0.518	-0.671	-0.796	-0.935	-1.052
DCP 8	.200	0.1?7	0.006	-0.167	-0.365	-0.522	-0.655	-0.783	-0.909	-1.015
DCP 9	.250	0.081	-0.0?0	-0.208	-0.375	-0.506	-0.625	-0.734	-0.855	-0.960
DCP10	.300	0.118	0.012	-0.165	-0.311	-0.419	-0.543	-0.651	-0.766	-0.862
DCP11	.359	-0.140	-0.006	-0.215	-0.307	-0.451	-0.556	-0.640	-0.751	-0.831
DCP12	.501	0.105	-0.067	-0.262	-0.315	-0.419	-0.518	-0.609	-0.710	-0.798
DCP13	.600	0.061	-0.052	-0.15?	-0.300	-0.367	-0.464	-0.570	-0.653	-0.727
DCP14	.701	0.130	0.056	-0.074	-0.177	-0.243	-0.325	-0.452	-0.544	-0.621
DCP15	.800	0.026	0.035	0.144	0.054	0.007	-0.067	-0.135	-0.202	-0.259
DCP16	.900	0.248	0.0??	0.119	0.025	-0.050	-0.104	-0.150	-0.246	-0.353
DCP17	.969	-?.?6?	0.156	-0.156	-0.258	-0.313	-0.366	-0.412	-0.371	-0.???

ALPHA		...	...	0.124	...	...	1.357	1.762	2.405	...	4.166
CN		...	...	...	...	...	0.256	...	0.377	3.44	...	0.562
CM		...	...	...	...	-0.069	-0.079	-0.092	-0.103	...	...	-0.032
DCP 1	.010	-1.462	-1.414	-1.160	-1.2?3	-1.?42	-0.924	-0.749	-0.608	-0.447	.253	-0.174
DCP 2	.020	-0.935	-1.145	-1.323	-0.946	-0.818	-0.751	-0.631	-0.462	-0.305	-0.151	-0.114
DCP 3	.030	-1.234	-1.254	-1.061	-0.790	-0.701	-0.585	-0.454	-0.261	-0.128	-0.003	?.020
DCP 4	.044	-1.666	-0.566	-0.451	-0.404	-0.243	-0.121	-0.026	0.091	0.205	0.314	0.412
DCP 5	.074	-0.236	-0.153	-0.045	-0.046	0.013	0.103	0.178	0.276	0.374	0.470	0.564
DCP 6	.099	-0.086	-0.038	0.024	0.053	0.131	0.140	0.305	0.421	0.509	0.550	0.679
DCP 7	.144	-0.067	0.008	0.088	0.148	0.185	0.354	0.414	0.443	0.574	0.653	0.727
DCP 8	.200	-0.091	0.008	0.070	0.121	0.206	0.320	0.401	0.471	0.554	0.631	0.702
DCP 9	.250	-0.116	-0.012	0.032	0.093	0.234	0.300	0.387	0.470	0.558	0.626	0.692
DCP10	.300	-0.088	0.009	0.068	0.124	0.243	0.313	0.402	0.488	0.552	0.616	0.678
DCP11	.349	-0.148	-0.066	0.030	0.171	0.221	0.292	0.375	0.439	0.497	0.583	0.624
DCP12	.501	-0.211	-0.073	0.077	0.110	0.180	0.244	0.321	0.380	0.444	0.507	0.624
DCP13	.600	-0.127	-0.053	0.009	0.065	0.180	0.254	0.318	0.369	0.430	0.486	0.562
DCP14	.701	0.003	0.059	0.096	0.156	0.210	0.268	0.341	0.406	0.472	0.533	0.545
DCP15	.800	0.207	0.232	0.261	0.346	0.413	0.467	0.520	0.560	0.630	0.672	0.712
DCP16	.900	0.138	0.173	0.200	0.247	0.296	0.341	0.389	0.443	0.497	0.530	0.578
DCP17	.969	-0.162	-0.133	-0.099	-0.062	-0.022	0.005	0.035	0.065	0.080	0.060	0.070

AIRFOIL NLR 7223-62   STEADY FORCES AND MOMENTS

FLOOR AND CEILING WITH 4.9% POROSITY

M = 0.899   Rn = 11.0 x 10^6

ALPHA		-1.918	-1.337	-0.692	0.194	0.655	1.047	1.728	2.370	2.949	3.730
CN		-0.117	-0.050	0.015	0.078	0.151	0.222	0.297	0.364	0.423	0.485
CM		-0.016	-0.029	-0.041	-0.054	-0.068	-0.080	-0.093	-0.103	-0.113	-0.121
DCP 1	.010	-1.501	-1.476	-1.420	-1.357	-1.324	-1.031	-0.811	-0.562	-0.658	-0.344
DCP 2	.020	-1.268	-1.204	-1.120	-0.993	-0.855	-0.787	-0.690	-0.522	-0.373	-0.226
DCP 3	.030	-1.069	-0.998	-0.896	-0.796	-0.?21	-0.635	-0.441	-0.293	-0.166	-0.040
DCP 4	.049	-0.693	-0.605	-0.514	-0.426	-0.324	-0.138	-0.050	0.058	0.160	0.270
DCP 5	.074	-0.263	-0.233	-0.201	-0.145	-0.086	-0.018	0.055	0.194	0.319	0.423
DCP 6	.099	-0.132	-0.073	-0.005	0.040	0.118	0.161	0.325	0.407	0.484	0.571
DCP 7	.149	-0.038	0.020	0.080	0.137	0.184	0.334	0.413	0.488	0.557	0.632
DCP 8	.200	-0.088	-0.014	0.048	0.106	0.240	0.299	0.370	0.451	0.526	0.603
DCP 9	.250	-0.150	-0.035	0.020	0.083	0.207	0.282	0.364	0.452	0.525	0.601
DCP10	.300	-0.099	-0.008	0.059	0.124	0.227	0.299	0.385	0.466	0.531	0.590
DCP11	.399	-0.167	-0.088	0.029	0.161	0.200	0.280	0.359	0.426	0.479	0.544
DCP12	.501	-0.225	-0.089	0.053	0.090	0.166	0.236	0.310	0.367	0.416	0.480
DCP13	.600	-0.113	-0.058	-0.017	0.064	0.170	0.240	0.311	0.359	0.412	0.472
DCP14	.701	-0.006	0.061	0.096	0.144	0.199	0.252	0.334	0.389	0.451	0.511
DCP15	.800	0.215	0.239	0.290	0.348	0.409	0.469	0.517	0.572	0.617	0.657
DCP16	.900	0.143	0.182	0.218	0.246	0.303	0.351	0.598	0.446	0.493	0.523
DCP17	.969	-0.160	-0.131	-0.099	-0.056	-0.017	0.015	0.047	0.092	0.118	0.121

ALPHA		-0.206	-1.198	-2.179	-3.204	-4.058	-4.944	-5.810	-6.617
CN		0.064	-0.037	-0.147	-0.264	-0.377	-0.472	-0.558	-0.640
CM		-0.050	-0.030	-0.012	0.010	0.028	0.044	0.059	0.071
DCP 1	.010	-1.290	-1.573	-1.633	-1.778	-1.845	-1.889	-2.020	-2.064
DCP 2	.020	-1.039	-1.168	-1.332	-1.426	-1.563	-1.676	-1.780	-1.889
DCP 3	.030	-0.830	-0.967	-1.120	-1.226	-1.350	-1.473	-1.578	-1.641
DCP 4	.049	-0.440	-0.569	-0.736	-0.851	-0.992	-1.115	-1.230	-1.350
DCP 5	.074	-0.113	-0.190	-0.253	-0.363	-0.561	-0.754	-0.904	-1.049
DCP 6	.099	0.036	-0.045	-0.144	-0.280	-0.498	-0.677	-0.815	-0.950
DCP 7	.149	0.118	0.033	-0.063	-0.306	-0.511	-0.659	-0.777	-0.893
DCP 8	.200	0.087	-0.001	-0.135	-0.358	-0.505	-0.622	-0.730	-0.846
DCP 9	.250	0.061	-0.021	-0.203	-0.365	-0.493	-0.604	-0.704	-0.810
DCP10	.300	0.098	-0.004	-0.154	-0.297	-0.400	-0.522	-0.624	-0.724
DCP11	.399	0.151	-0.072	-0.216	-0.287	-0.432	-0.533	-0.614	-0.702
DCP12	.501	0.081	-0.029	-0.249	-0.305	-0.414	-0.493	-0.580	-0.676
DCP13	.600	0.039	-0.065	-0.149	-0.269	-0.383	-0.449	-0.537	-0.614
DCP14	.701	0.128	0.063	-0.027	-0.161	-0.233	-0.303	-0.395	-0.492
DCP15	.800	0.327	0.241	0.211	0.122	0.024	-0.069	-0.124	-0.163
DCP16	.900	0.237	0.183	0.132	0.031	-0.034	-0.088	-0.125	-0.166
DCP17	.969	-0.067	-0.126	-0.182	-0.247	-0.311	-0.391	-0.444	-0.459

MEASURED DRAG COEFFICIENTS

Airfoil: NLR7223-62   Test: BSWT567

M = 0.6 Re = 10×10^6		M = 0.7 Re = 11×10^6		M = 0.75 Re = 11.4×10^6		M = 0.8 Re = 11.7×10^6	
α	c_d	α	c_d	α	c_d	α	c_d
- 2.0	0.0092	-2.06	0.0088	-2.15	0.0093	-2.04	0.0159
- 1.98	0.0081	-1.33	0.0073	-2.10	0.0108	-1.01	0.0102
- 1.91	0.0082	-1.12	0.0083	-1.6	0.0070	-1.01	0.0100
0.58	0.0077	1.01	0.0083	-1.24	0.0083	-0.03	0.0107
0.71	0.0075	1.95	0.0104	-1.01	0.0082	-0.02	0.0099
1.07	0.0069	3.12	0.01367	0.15	0.0076	0.76	0.0120
2.10	0.0070	3.95	0.0228	0.91	0.0096	0.93	0.014
2.10	0.0076	5.05	0.0416	0.96	0.0089		
3.03	0.0082			1.12	0.0099		
4.07	0.0082			1.69	0.0158		
4.11	0.0081			1.99	0.0160		
5.06	0.0118			2.72	0.0223		
5.74	0.0176			2.87	0.0255		
5.79	0.0179						
6.02	0.0179						
7.04	0.0290						
7.95	0.0453						
9.01	0.0560						
10.09	0.0803						

AIRFOIL NLR 7223-62   STEADY FORCES AND MOMENTS

M = 0.201 Rn = 3.2×10^6

SOLID FLOOR AND CEILING

ALPHA		-7.887	-7.305	-6.652	-6.069	-5.505	-4.914	-4.284	-3.728	-3.102	-2.506	-1.847
CN		-0.459	-0.437	-0.469	-0.403	-0.357	-0.294	-0.252	-0.180	-0.147	-0.075	-0.022
CM		-0.044	-0.031	-0.032	-0.033	-0.032	-0.033	-0.026	-0.033	-0.025	-0.026	-0.026
DCP 1	.010	-2.418	-2.518	-5.307	-4.764	-4.360	-3.826	-3.544	-2.931	-2.504	-2.162	-1.682
DCP 2	.020	-2.362	-2.697	-3.459	-3.165	-2.860	-2.590	-2.429	-2.160	-1.835	-1.492	-1.292
DCP 3	.030	-2.218	-2.837	-2.476	-2.232	-2.034	-1.832	-1.593	-1.403	-1.123	-0.954	-0.654
DCP 4	.049	-2.737	-2.131	-2.139	-1.889	-1.733	-1.490	-1.410	-1.193	-0.579	-0.642	-0.651
DCP 5	.074	-2.026	-1.602	-1.463	-1.298	-1.207	-0.969	-0.865	-0.752	-0.633	-0.407	-0.255
DCP 6	.099	-1.451	-1.058	-1.025	-0.862	-0.740	-0.666	-0.450	-0.345	-0.240	-0.131	0.041
DCP 7	.149	-1.114	-0.928	-0.866	-0.800	-0.695	-0.570	-0.513	-0.421	-0.301	-0.152	-0.091
DCP 8	.200	-0.851	-0.700	-0.644	-0.547	-0.515	-0.378	-0.323	-0.269	-0.243	-0.115	0.009
DCP 9	.250	-0.574	-0.617	-0.568	-0.472	-0.406	-0.296	-0.305	-0.158	-0.133	-0.034	0.021
DCP10	.300	-0.453	-0.404	-0.442	-0.417	-0.352	-0.326	-0.203	-0.131	-0.087	0.008	0.036
DCP11	.399	-0.277	-0.332	-0.345	-0.269	-0.224	-0.229	-0.100	-0.150	-0.038	0.053	0.047
DCP12	.501	-0.197	-0.230	-0.281	-0.239	-0.217	-0.158	-0.156	-0.016	-0.085	0.015	0.026
DCP13	.600	-0.075	-0.096	-0.071	-0.055	-0.032	-0.005	0.035	0.129	0.121	0.121	0.174
DCP14	.701	-0.001	-0.057	-0.073	-0.032	-0.017	0.012	0.031	0.105	0.089	0.056	0.122
DCP15	.800	-0.005	-0.018	-0.029	0.034	0.037	0.056	0.039	0.042	0.038	0.060	0.046
DCP16	.900	0.036	0.009	-0.111	-0.056	-0.079	-0.045	-0.089	-0.095	-0.093	-0.051	-0.060
DCP17	.969	0.009	-0.013	0.078	-0.017	0.016	0.040	-0.082	0.011	-0.018	-0.041	0.010

ALPHA		-1.285	-0.712	-0.068	0.572	1.104	1.696	2.357	2.943	3.521	4.186	4.801
CN		0.021	0.082	0.144	0.195	0.265	0.312	0.371	0.454	0.528	0.568	0.618
CM		-0.022	-0.021	-0.023	-0.020	-0.020	-0.020	-0.018	-0.022	-0.024	-0.015	-0.016
DCP 1	.010	-1.310	-0.898	-0.577	-0.178	0.280	0.664	0.994	1.477	1.863	2.240	2.542
DCP 2	.020	-1.053	-0.705	-0.420	-0.179	0.212	0.473	0.741	1.123	1.440	1.814	1.921
DCP 3	.030	-0.501	-0.223	0.053	0.294	0.508	0.745	1.099	1.280	1.596	1.917	2.145
DCP 4	.049	-0.345	-0.259	-0.073	0.175	0.401	0.615	0.745	1.065	1.255	1.456	1.713
DCP 5	.074	-0.153	0.053	0.236	0.368	0.511	0.720	0.888	1.085	1.254	1.431	1.616
DCP 6	.099	0.192	0.256	0.474	0.614	0.747	0.832	1.062	1.201	1.320	1.534	1.627
DCP 7	.149	-0.003	0.088	0.237	0.293	0.478	0.579	0.620	0.782	0.955	1.016	1.057
DCP 8	.200	0.009	0.203	0.265	0.351	0.386	0.502	0.684	0.692	0.800	0.947	0.974
DCP 9	.250	0.114	0.150	0.233	0.301	0.467	0.448	0.502	0.633	0.678	0.716	0.789
DCP10	.300	0.096	0.085	0.178	0.303	0.328	0.379	0.468	0.565	0.615	0.689	0.698
DCP11	.399	0.082	0.207	0.187	0.209	0.331	0.321	0.361	0.480	0.557	0.534	0.622
DCP12	.501	0.046	0.084	0.153	0.157	0.218	0.206	0.228	0.320	0.389	0.374	0.471
DCP13	.600	0.143	0.251	0.249	0.252	0.305	0.333	0.351	0.348	0.443	0.473	0.464
DCP14	.701	0.152	0.195	0.161	0.198	0.183	0.210	0.269	0.291	0.374	0.331	0.342
DCP15	.800	0.069	0.058	0.110	0.117	0.143	0.154	0.170	0.207	0.223	0.197	0.205
DCP16	.930	-0.056	-0.126	-0.011	-0.045	-0.044	-0.003	-0.017	0.000	-0.040	-0.002	-0.002
DCP17	.969	-0.036	-0.029	-0.081	-0.030	-0.058	-0.014	-0.056	0.019	-0.019	-0.057	-0.035

M = 0.201 Rn = 3.2 x 10⁶

ALPHA		5.351	5.960	6.575	7.194	7.748	8.380	9.013	9.610	10.164	10.773	11.381
CN		0.701	0.752	0.809	0.860	0.912	0.585	1.014	1.101	1.145	1.192	1.251
CM		-0.017	-0.018	-0.014	-0.015	-0.011	-0.005	-0.011	-0.007	-0.007	-0.004	-0.001
DCP 1	.010	2.959	3.329	3.651	4.043	4.475	4.916	5.291	5.867	5.548	5.933	6.010
DCP 2	.020	2.337	2.659	2.943	3.050	3.560	3.848	3.999	4.380	4.750	5.008	5.210
DCP 3	.030	2.426	2.626	2.822	3.134	3.368	3.672	3.846	4.152	4.405	4.609	4.925
DCP 4	.049	1.899	2.149	2.342	2.519	2.724	3.099	3.002	3.461	3.657	3.871	3.586
DCP 5	.074	1.724	1.982	2.095	2.223	2.420	2.714	2.721	2.941	3.075	3.251	3.473
DCP 6	.099	1.749	1.887	2.049	2.191	2.318	2.387	2.530	2.768	2.898	3.022	3.233
DCP 7	.149	1.291	1.359	1.460	1.537	1.662	1.831	1.818	1.964	2.117	2.255	2.354
DCP 8	.200	1.050	1.163	1.252	1.392	1.417	1.493	1.642	1.678	1.681	1.824	1.950
DCP 9	.250	0.935	1.006	1.097	1.120	1.217	1.290	1.337	1.492	1.494	1.632	1.704
DCP10	.300	0.871	0.868	1.007	0.990	1.051	1.109	1.139	1.231	1.315	1.332	1.397
DCP11	.399	0.676	0.724	0.762	0.828	0.826	0.992	0.940	1.076	1.037	1.090	1.194
DCP12	.501	0.539	0.529	0.540	0.586	0.630	0.686	0.704	0.736	0.825	0.818	0.893
DCP13	.600	0.545	0.488	0.585	0.613	0.624	0.685	0.640	0.745	0.753	0.740	0.707
DCP14	.701	0.376	0.415	0.410	0.385	0.514	0.500	0.476	0.515	0.488	0.504	0.555
DCP15	.800	0.191	0.233	0.224	0.327	0.259	0.260	0.318	0.282	0.318	0.299	0.266
DCP16	.900	0.016	0.066	0.054	0.036	-0.024	-0.002	0.035	0.005	0.001	0.051	0.031
DCP17	.969	-0.057	-0.020	-0.063	-0.094	-0.052	-0.094	-0.020	-0.049	0.019	-0.018	-0.009

ALPHA		11.972	12.537	13.173	13.812	14.384	14.972	15.547	16.743	17.570	19.126	19.702
CN		1.280	1.336	1.368	1.305	1.377	1.297	1.315	1.227	1.097	1.173	1.107
CM		-0.004	-0.006	-0.004	0.010	-0.001	-0.010	-0.066	-0.081	-0.118	-0.143	-0.114
DCP 1	.010	6.119	6.433	6.696	6.627	7.124	6.802	5.171	5.108	2.370	1.805	1.868
DCP 2	.020	5.472	5.799	6.003	5.908	6.240	5.964	4.446	4.259	2.113	1.642	1.791
DCP 3	.030	5.102	5.358	5.573	5.462	5.823	5.558	3.681	3.520	2.176	1.842	1.751
DCP 4	.049	4.220	4.340	4.481	4.255	4.324	3.993	3.935	3.683	3.065	3.564	3.586
DCP 5	.074	3.577	3.718	3.811	3.696	3.735	3.248	3.250	2.865	2.413	2.738	2.742
DCP 6	.099	3.257	3.367	3.364	3.324	3.414	2.923	2.719	2.440	1.561	2.222	2.241
DCP 7	.149	2.376	2.505	2.547	2.478	2.473	2.207	1.588	1.772	1.609	1.762	1.804
DCP 8	.200	1.971	2.011	2.054	2.089	2.122	1.994	1.873	1.655	1.445	1.343	1.374
DCP 9	.250	1.705	1.765	1.803	1.714	1.858	1.788	1.716	1.489	1.250	1.309	1.201
DCP10	.300	1.446	1.465	1.522	1.512	1.559	1.544	1.647	1.347	1.218	1.155	1.192
DCP11	.399	1.149	1.270	1.255	1.204	1.282	1.287	1.482	1.306	1.232	1.194	1.147
DCP12	.501	0.854	0.896	1.012	0.892	0.938	0.967	1.061	0.990	0.997	1.151	0.589
DCP13	.600	0.762	0.749	0.839	0.768	0.832	0.763	0.921	0.972	1.067	1.105	0.989
DCP14	.701	0.555	0.606	0.503	0.476	0.558	0.491	0.681	0.739	0.785	0.572	0.838
DCP15	.800	0.392	0.307	0.371	0.257	0.317	0.295	0.536	0.516	0.680	0.831	0.733
DCP16	.900	0.057	0.157	0.076	0.026	0.064	0.143	0.198	0.382	0.370	0.502	0.347
DCP17	.969	-0.080	-0.034	-0.024	-0.031	-0.044	-0.006	0.120	0.106	0.115	0.092	0.081

AIRFOIL NLR 7223-62 STEADY FORCES AND MOMENTS

M = 0.301 Rn = 4.8 x 10⁶

SOLID FLOOR AND CEILING

ALPHA		-9.574	-8.588	-8.371	-7.793	-7.229	-6.615	-5.573	-5.411	-4.848	-4.194	-3.575
CN		-3.637	-0.590	-0.580	-0.526	-0.494	-0.502	-0.459	-0.405	-0.351	-0.287	-0.231
CM		-0.024	-0.035	-0.027	-0.025	-0.025	-0.031	-0.027	-0.027	-0.025	-0.025	-0.023
DCP 1	.010	-3.211	-3.502	-2.301	-2.470	-2.601	-5.201	-5.021	-4.690	-4.220	-3.655	-3.172
DCP 2	.020	-2.488	-2.272	-2.456	-2.775	-2.996	-3.502	-3.271	-3.038	-2.719	-2.373	-2.164
DCP 3	.030	-2.180	-2.128	-3.396	-3.265	-2.809	-2.685	-2.486	-2.205	-2.053	-1.745	-1.539
DCP 4	.049	-1.950	-2.038	-2.365	-2.243	-2.155	-2.031	-1.869	-1.641	-1.451	-1.284	-1.120
DCP 5	.074	-1.888	-1.998	-1.846	-1.747	-1.630	-1.480	-1.347	-1.183	-1.046	-0.871	-0.690
DCP 6	.099	-1.533	-1.639	-1.505	-1.346	-1.267	-1.163	-1.053	-0.896	-0.763	-0.634	-0.462
DCP 7	.149	-1.413	-1.578	-1.278	-1.118	-1.011	-0.929	-0.834	-0.740	-0.593	-0.491	-0.408
DCP 8	.200	-1.293	-1.342	-0.563	-0.999	-0.892	-0.757	-0.677	-0.640	-0.539	-0.440	-0.347
DCP 9	.250	-1.259	-1.076	-3.968	-0.795	-0.667	-0.624	-0.563	-0.518	-0.455	-0.385	-0.268
DCP10	.300	-0.958	-0.827	-0.757	-0.591	-0.533	-0.506	-0.470	-0.376	-0.325	-0.272	-0.199
DCP11	.399	-0.663	-0.454	-0.488	-0.346	-0.325	-0.379	-0.342	-0.282	-0.240	-0.185	-0.158
DCP12	.501	-0.396	-0.274	-0.312	-0.278	-0.296	-0.307	-0.248	-0.231	-0.213	-0.128	-0.130
DCP13	.600	-0.201	-0.129	-0.198	-3.184	-0.172	-0.190	-0.150	-0.120	-0.097	-0.086	-0.034
DCP14	.701	0.003	0.031	-0.040	-0.031	-0.035	0.016	-0.003	0.018	0.048	0.057	0.097
DCP15	.800	-3.001	0.021	-0.005	-0.015	-0.011	-0.036	-0.008	-0.033	-0.009	0.005	0.025
DCP16	.900	-0.048	-0.035	-0.081	-0.072	-0.078	-0.083	-0.134	-0.101	-0.108	-0.092	-0.086
DCP17	.969	0.009	0.027	3.027	-0.001	-0.032	0.015	-0.000	0.022	-3.006	0.018	-0.040

ALPHA		-2.596	-2.416	-1.798	-1.187	-0.580	-0.030	0.636	1.248	1.810	2.409	3.067
CN		-0.171	-0.119	-0.047	0.006	0.071	0.125	0.186	0.244	0.305	0.380	0.444
CM		-0.020	-0.018	-0.020	-0.020	-0.018	-0.018	-0.017	-0.018	-0.014	-0.018	-0.015
DCP 1	.010	-2.610	-2.135	-1.721	-1.275	-0.886	-0.489	-0.134	0.288	0.748	1.085	1.489
DCP 2	.020	-1.807	-1.518	-1.172	-0.899	-0.592	-0.290	0.008	0.270	0.667	0.576	1.279
DCP 3	.030	-1.272	-1.043	-0.765	-0.537	-0.281	-0.057	0.217	0.468	0.748	1.012	1.303
DCP 4	.049	-0.863	-0.695	-0.495	-0.285	-0.042	0.135	0.334	0.559	0.765	1.005	1.207
DCP 5	.074	-0.567	-0.379	-0.166	-0.040	0.115	0.303	0.466	0.631	0.796	1.010	1.182
DCP 6	.099	-0.324	-0.195	-0.067	0.079	0.209	0.346	0.527	0.655	0.808	0.932	1.120
DCP 7	.149	-0.262	-0.186	-0.057	0.012	0.165	0.268	0.376	0.463	0.581	0.725	0.818
DCP 8	.200	-0.267	-0.178	-0.077	0.021	0.080	0.209	0.275	0.368	3.414	0.567	0.668
DCP 9	.250	-0.215	-0.148	-0.030	0.001	0.110	0.180	3.264	0.286	0.395	3.501	0.581
DCP10	.300	-0.136	-0.091	-0.001	3.051	0.143	0.170	0.252	3.319	0.387	0.469	0.541
DCP11	.399	-0.105	-0.052	-0.002	0.050	0.117	0.152	0.189	0.259	0.326	0.382	0.445
DCP12	.501	-3.070	-0.040	0.005	0.037	0.085	0.104	0.166	0.188	0.250	0.267	0.327
DCP13	.600	-0.025	0.006	0.040	0.073	0.126	3.122	0.167	0.165	0.230	0.278	0.304
DCP14	.701	0.104	0.110	0.166	0.190	0.194	0.220	0.237	0.259	0.272	0.303	0.364
DCP15	.800	0.056	0.048	0.062	0.066	0.098	0.114	0.130	0.151	0.152	0.177	0.178
DCP16	.900	-0.121	-3.114	-0.087	-0.061	-0.107	-0.061	-0.094	-0.038	-3.085	-0.005	-0.073
DCP17	.969	-0.010	-0.006	-3.019	-0.040	-0.023	-0.028	-0.004	-0.020	-0.042	-0.030	-0.024

M = 0.301   Rn = 4.8 x 10^6   SOLID FLOOR AND CEILING

ALPHA		3.628	4.230	4.656	5.501	6.035	6.638	7.341	7.857	8.460	9.042	9.670
CN		0.590	0.552	0.618	0.682	0.745	0.797	0.862	0.912	0.568	1.028	1.081
CM		-0.014	-0.011	-0.010	-0.009	-0.011	-0.008	-0.008	-0.006	-0.002	-0.001	-0.002
DCP 1	.010	1.893	2.252	2.64C	3.041	3.430	3.8C4	4.198	4.707	5.122	5.388	5.542
DCP 2	.020	1.583	1.921	2.220	2.501	2.829	3.119	3.469	3.738	4.131	4.373	4.600
DCP 3	.030	1.584	1.814	2.111	2.412	2.583	2.842	3.162	3.395	3.670	3.508	4.146
DCP 4	.049	1.454	1.674	1.853	2.139	2.355	2.553	2.757	2.581	3.237	3.405	3.572
DCP 5	.074	1.323	1.524	1.683	1.895	2.016	2.218	2.408	2.558	2.710	2.934	3.065
DCP 6	.099	1.298	1.378	1.537	1.720	1.840	1.942	2.152	2.262	2.396	2.551	2.681
DCP 7	.149	0.933	1.044	1.191	1.242	1.382	1.511	1.607	1.687	1.838	1.932	1.993
DCP 8	.200	0.719	0.822	0.935	1.041	1.107	1.219	1.262	1.365	1.406	1.557	1.648
DCP 9	.250	0.660	0.717	0.798	0.892	0.575	1.035	1.114	1.171	1.271	1.338	1.426
DCP10	.300	0.599	0.661	0.715	0.782	0.845	0.920	0.970	1.045	1.C99	1.158	1.200
DCP11	.399	0.496	0.555	0.616	0.655	0.732	0.748	0.791	0.823	0.862	0.932	1.017
DCP12	.501	0.362	0.359	0.461	0.462	0.530	0.546	0.623	0.635	0.665	0.721	0.776
DCP13	.600	0.331	0.357	0.374	0.449	0.445	0.480	0.519	0.553	0.596	0.580	0.605
DCP14	.701	0.349	0.370	0.377	0.417	0.449	0.447	0.477	0.465	0.490	0.508	0.521
DCP15	.800	0.186	0.188	0.205	0.217	0.243	0.258	0.271	0.249	0.27C	0.301	0.295
DCP16	.900	-0.050	-0.046	-0.042	-0.054	-0.025	-0.050	-0.C18	0.026	-0.022	-0.046	-0.011
DCP17	.969	-0.012	-0.026	-0.042	-0.033	-0.047	-0.006	-0.050	-0.036	-0.051	-0.018	-0.030

ALPHA		10.274	10.865	11.447	12.126	12.626	13.226	13.818	14.505	15.011	15.641	16.245
CN		1.125	1.172	1.202	1.251	1.267	1.268	1.196	1.234	1.170	1.127	1.227
CM		0.003	0.004	0.C07	0.007	0.009	0.011	0.003	-0.005	-0.074	-0.066	-0.07C
DCP 1	.010	5.559	6.355	6.779	7.273	7.692	7.777	7.C 8	6.659	4.798	4.681	4.840
DCP 2	.020	4.900	5.147	5.305	5.443	5.520	5.794	5.662	5.338	4.097	4.205	4.189
DCP 3	.030	4.402	4.645	4.804	5.025	5.094	5.232	5.081	4.725	3.675	3.775	3.166
DCP 4	.049	3.805	3.581	4.090	4.228	4.355	4.358	3.901	4.176	3.287	3.257	3.601
DCP 5	.074	3.188	3.357	3.472	3.590	3.603	3.641	3.178	3.461	2.536	2.425	2.901
DCP 6	.099	2.816	2.940	2.578	3.141	3.184	3.120	2.736	2.995	2.129	2.036	2.399
DCP 7	.149	2.116	2.258	2.284	2.325	2.384	2.40C	2.192	2.206	1.694	1.674	2.005
DCP 8	.200	1.692	1.743	1.842	1.876	1.901	1.944	1.814	1.912	1.503	1.512	1.797
DCP 9	.250	1.468	1.534	1.591	1.628	1.692	1.645	1.637	1.607	1.559	1.408	1.606
DCP10	.300	1.269	1.331	1.433	1.391	1.421	1.420	1.380	1.433	1.385	1.404	1.483
DCP11	.399	1.036	1.035	1.070	1.125	1.118	1.110	1.125	1.122	1.318	1.172	1.230
DCP12	.501	0.799	0.793	0.813	0.884	0.856	0.816	0.846	0.884	1.040	1.011	1.045
DCP13	.600	0.629	0.625	0.654	0.677	0.649	0.665	0.620	0.664	0.884	0.808	0.929
DCP14	.701	0.522	0.572	0.544	0.550	0.518	0.548	0.454	0.485	0.724	0.692	0.737
DCP15	.800	0.285	0.295	0.299	0.279	0.293	0.272	0.255	0.312	0.524	0.472	0.483
DCP16	.900	-0.013	0.008	0.000	0.014	0.056	0.042	0.083	0.119	0.194	0.242	0.192
DCP17	.969	-0.059	-0.061	-0.053	-0.016	-0.001	-0.015	0.039	0.051	0.065	0.039	0.140

AIRFOIL NLR 7223-62 STEADY FORCES AND MOMENTS

M = 0.301 Rn = 4.8 x 10⁶   SOLID FLOOR AND CEILING

ALPHA		16.852	17.410	18.003	18.617	19.242	19.792
CN		1.007	1.003	1.038	0.966	1.011	0.990
CM		-0.101	-0.091	-0.090	-0.095	-0.102	-0.093
DCP 1	.010	4.031	3.909	3.914	3.568	3.615	3.725
DCP 2	.020	3.691	3.642	3.662	3.389	3.242	3.289
DCP 3	.030	3.789	3.666	3.091	3.322	2.934	2.065
DCP 4	.049	2.034	2.087	2.497	1.858	1.909	2.229
DCP 5	.074	1.414	1.455	1.768	1.430	1.546	1.751
DCP 6	.099	1.315	1.428	1.628	1.371	1.470	1.643
DCP 7	.149	1.205	1.318	1.496	1.254	1.391	1.490
DCP 8	.200	1.215	1.231	1.422	1.253	1.363	1.382
DCP 9	.250	1.276	1.285	1.368	1.272	1.351	1.265
DCP10	.300	1.174	1.258	1.250	1.202	1.244	1.192
DCP11	.399	1.149	1.188	1.124	1.103	1.097	1.091
DCP12	.501	1.060	1.029	0.955	0.912	1.080	0.558
DCP13	.600	0.917	0.816	0.830	0.831	0.895	0.785
DCP14	.701	0.787	0.710	0.736	0.741	0.696	0.686
DCP15	.800	0.543	0.495	0.528	0.534	0.550	0.568
DCP16	.900	0.244	0.264	0.290	0.257	0.302	0.290
DCP17	.969	0.104	0.100	0.112	0.123	0.121	0.094

M = 0.400   Rn = 2.3 × 10⁶

SOLID FLOOR AND CEILING

DATA TYPE	X/C											
ALPHA		-8.284	-7.801	-7.278	-6.785	-6.234	-5.727	-5.209	-4.697	-4.145	-3.661	-3.107
CN		-0.555	-0.587	-0.542	-0.503	-0.462	-0.448	-0.395	-0.372	-0.303	-0.245	-0.194
CM		-0.010	-0.016	-0.027	-0.036	-0.046	-0.036	-0.036	-0.034	-0.029	-0.027	-0.020
DCP 1	.010	-2.265	-2.365	-2.194	-2.263	-2.362	-2.477	-2.569	-3.293	-3.663	-3.220	-2.746
DCP 2	.020	-2.243	-2.401	-2.211	-2.313	-2.366	-2.427	-2.440	-2.800	-2.473	-2.084	-1.759
DCP 3	.030	-2.294	-2.491	-1.958	-1.965	-2.007	-2.051	-2.188	-2.246	-1.802	-1.597	-1.354
DCP 4	.049	-1.763	-1.758	-1.863	-1.960	-2.053	-2.032	-2.081	-2.023	-1.334	-1.147	-0.989
DCP 5	.074	-1.565	-1.559	-1.707	-1.752	-1.865	-1.768	-1.715	-1.554	-0.977	-0.763	-0.616
DCP 6	.099	-1.326	-1.365	-1.465	-1.540	-1.580	-1.505	-1.214	-1.019	-0.656	-0.553	-0.355
DCP 7	.149	-1.357	-1.353	-1.414	-1.364	-1.455	-1.273	-0.958	-0.690	-0.637	-0.519	-0.398
DCP 8	.200	-1.129	-1.125	-1.137	-1.017	-0.864	-0.724	-0.556	-0.454	-0.430	-0.333	-0.216
DCP 9	.250	-1.065	-1.047	-1.005	-0.834	-0.695	-0.600	-0.436	-0.441	-0.406	-0.337	-0.237
DCP10	.300	-0.919	-0.877	-0.767	-0.644	-0.497	-0.467	-0.409	-0.357	-0.341	-0.268	-0.179
DCP11	.349	-0.651	-0.583	-0.516	-0.361	-0.345	-0.333	-0.255	-0.257	-0.226	-0.149	-0.120
DCP12	.501	-0.347	-0.344	-0.278	-0.277	-0.160	-0.163	-0.208	-0.175	-0.156	-0.109	-0.102
DCP13	.600	-0.226	-0.200	-0.131	-0.101	-0.064	-0.070	-0.054	-0.064	-0.048	-0.006	-0.045
DCP14	.701	-0.076	-0.026	0.001	0.051	0.077	0.001	0.022	0.024	0.075	0.069	0.060
DCP15	.800	0.010	0.010	0.092	0.074	0.083	0.082	0.074	0.066	0.092	0.076	0.060
DCP16	.900	-0.093	-0.090	-0.065	-0.067	-0.055	-0.073	-0.062	-0.113	-0.117	-0.101	-0.103
DCP17	.969	-0.052	-0.038	-0.088	-0.014	0.031	-0.014	-0.024	-0.001	-0.031	-0.044	-0.030

DATA TYPE	X/C											
ALPHA		-2.584	-2.071	-1.534	-1.014	-0.486	0.073	0.554	1.092	1.636	2.137	2.649
CN		-0.133	-0.073	-0.008	0.045	0.113	0.171	0.214	0.262	0.345	0.404	0.453
CM		-0.023	-0.020	-0.019	-0.018	-0.020	-0.017	-0.008	-0.012	-0.013	-0.008	-0.003
DCP 1	.010	-2.192	-1.760	-1.334	-0.896	-0.514	-0.121	0.317	0.678	1.077	1.443	1.672
DCP 2	.020	-1.534	-1.443	-1.074	-0.754	-0.462	-0.214	0.122	0.439	0.742	1.006	1.380
DCP 3	.030	-1.092	-0.834	-0.607	-0.349	-0.068	0.175	0.444	0.683	0.945	1.235	1.516
DCP 4	.049	-0.803	-0.577	-0.413	-0.156	0.006	0.263	0.457	0.663	0.881	1.099	1.351
DCP 5	.074	-0.462	-0.260	-0.047	0.034	0.228	0.398	0.547	0.754	0.936	1.106	1.254
DCP 6	.099	-0.254	-0.069	0.095	0.212	0.336	0.484	0.672	0.780	0.934	1.153	1.237
DCP 7	.149	-0.240	-0.151	-0.057	0.033	0.173	0.269	0.368	0.453	0.592	0.741	0.854
DCP 8	.200	-0.162	-0.045	0.056	0.107	0.244	0.305	0.413	0.463	0.572	0.608	0.757
DCP 9	.250	-0.203	-0.056	0.025	0.042	0.155	0.217	0.276	0.346	0.462	0.539	0.563
DCP10	.300	-0.137	-0.062	0.026	0.077	0.156	0.237	0.281	0.336	0.364	0.441	0.533
DCP11	.349	-0.059	-0.034	0.045	0.088	0.126	0.223	0.250	0.314	0.345	0.381	0.459
DCP12	.501	-0.042	-0.031	0.031	0.059	0.122	0.143	0.173	0.217	0.305	0.337	0.332
DCP13	.600	0.037	0.072	0.066	0.158	0.180	0.216	0.200	0.239	0.256	0.249	0.324
DCP14	.701	0.103	0.127	0.136	0.163	0.170	0.193	0.200	0.245	0.264	0.310	0.301
DCP15	.800	0.063	0.114	0.127	0.115	0.163	0.127	0.130	0.147	0.175	0.149	0.157
DCP16	.900	-0.061	-0.112	-0.094	-0.115	-0.073	-0.111	-0.137	-0.071	-0.076	-0.090	-0.131
DCP17	.969	-0.072	-0.061	-0.051	-0.046	-0.065	-0.016	-0.060	-0.076	-0.064	-0.072	-0.064

AIRFOIL NLR 7223-62 STEADY FORCES AND MOMENTS

SOLID FLOOR AND CEILING

M = 0.400 Rn = 2.3 x 10⁶

DATA TYPE	X/C											
ALPHA		3.169	3.708	4.237	4.722	5.286	5.792	6.287	6.818	7.369	7.848	8.391
CN		0.530	0.594	0.651	0.717	0.768	0.825	0.861	0.914	0.950	1.009	1.050
CM		-0.005	-0.004	-0.003	-0.004	-0.003	0.002	0.006	0.008	0.013	0.014	0.016
DCP 1	.010	2.248	2.654	3.021	3.424	3.744	4.205	4.566	5.047	5.541	6.021	6.257
DCP 2	.020	1.711	2.023	2.267	2.663	2.810	3.328	3.794	3.894	4.205	5.151	5.673
DCP 3	.030	1.777	2.094	2.354	2.631	2.905	3.062	3.215	3.459	3.597	3.761	4.023
DCP 4	.044	1.573	1.757	1.956	2.259	2.450	2.663	2.859	3.072	3.219	3.361	3.436
DCP 5	.074	1.453	1.645	1.749	2.022	2.157	2.377	2.476	2.644	2.761	2.921	2.956
DCP 6	.099	1.410	1.561	1.775	1.869	2.016	2.205	2.271	2.393	2.523	2.620	2.675
DCP 7	.149	0.937	1.024	1.150	1.300	1.368	1.505	1.547	1.672	1.762	1.846	1.870
DCP 8	.200	0.873	0.976	1.071	1.168	1.213	1.338	1.372	1.485	1.465	1.554	1.649
DCP 9	.250	0.721	0.731	0.872	0.937	1.032	1.102	1.135	1.201	1.250	1.327	1.374
DCP10	.300	0.551	0.674	0.753	0.780	0.823	0.938	0.972	1.025	1.076	1.112	1.108
DCP11	.349	0.513	0.583	0.632	0.660	0.722	0.760	0.810	0.834	0.875	0.943	0.930
DCP12	.501	0.361	0.437	0.468	0.501	0.579	0.570	0.603	0.635	0.627	0.685	0.704
DCP13	.600	0.317	0.377	0.349	0.433	0.472	0.492	0.465	0.531	0.515	0.545	0.532
DCP14	.731	0.337	0.364	0.338	0.404	0.394	0.415	0.372	0.424	0.444	0.435	0.447
DCP15	.800	0.235	0.205	0.208	0.242	0.240	0.246	0.225	0.197	0.243	0.202	0.164
DCP16	.900	-0.083	-0.057	-0.062	-0.060	-0.054	-0.067	-0.055	-0.058	-0.046	-0.026	-0.035
DCP17	.964	-0.042	-0.038	-0.094	-0.037	-0.068	-0.047	-0.061	-0.073	-0.105	-0.085	-0.059

DATA TYPE	X/C											
ALPHA		8.891	9.426	9.917	10.446	10.957	11.511	12.008	12.543	13.067	13.598	14.061
CN		1.063	1.057	1.004	1.015	1.006	0.998	0.961	0.961	0.926	0.933	0.942
CM		0.018	0.016	-0.005	-0.014	-0.046	-0.052	-0.063	-0.062	-0.060	-0.076	-0.081
DCP 1	.010	6.352	6.057	4.955	4.974	4.414	4.241	2.244	2.194	2.316	2.053	2.075
DCP 2	.020	5.846	5.704	4.161	4.041	3.485	3.404	1.833	1.770	1.702	1.639	1.626
DCP 3	.030	4.530	4.723	3.801	3.995	3.714	3.548	1.862	1.812	1.745	1.616	1.732
DCP 4	.044	3.451	3.451	2.864	2.751	2.459	2.411	2.935	2.855	2.125	2.605	2.709
DCP 5	.074	3.009	2.930	2.425	2.296	2.010	1.952	2.560	2.501	2.614	2.576	2.616
DCP 6	.099	2.654	2.736	2.235	2.214	1.812	1.762	2.264	2.242	2.332	2.510	2.467
DCP 7	.149	1.972	2.013	1.765	1.854	1.508	1.572	1.427	1.459	1.469	1.492	1.587
DCP 8	.200	1.713	1.707	1.713	1.747	1.613	1.514	1.339	1.255	1.146	1.226	1.120
DCP 9	.250	1.373	1.371	1.440	1.465	1.411	1.374	1.168	1.121	1.051	1.013	1.023
DCP10	.300	1.162	1.117	1.246	1.313	1.239	1.177	1.331	1.040	0.974	0.977	0.926
DCP11	.349	0.952	0.935	1.050	1.068	1.202	1.265	1.034	1.009	0.908	0.937	0.915
DCP12	.501	0.704	0.707	0.811	0.878	0.804	0.942	0.918	0.865	0.746	0.805	0.816
DCP13	.600	0.572	0.545	0.534	0.625	0.755	0.668	0.838	0.750	0.762	0.765	0.806
DCP14	.731	0.429	0.368	0.421	0.364	0.479	0.502	0.721	0.717	0.738	0.662	0.705
DCP15	.800	0.233	0.252	0.237	0.316	0.308	0.374	0.565	0.556	0.547	0.545	0.615
DCP16	.900	-0.044	-0.002	0.050	0.076	0.107	0.150	0.103	0.144	0.185	0.194	0.231
DCP17	.964	-0.074	-0.060	-0.043	-0.012	0.010	0.001	0.015	0.014	0.004	0.002	0.000

M = 0.400   Rn = 2.3 x 10^6 SOLID FLOOR AND CEILING

DATA TYPE	x/c					
ALPHA		14.642	15.137	15.494	16.116	16.709
CN		0.981	0.958	0.987	0.978	0.983
CM		-3.066	-0.085	-0.054	-0.087	-0.091
DCP 1	.010	2.025	2.009	1.662	1.683	1.720
DCP 2	.020	1.722	1.662	1.702	1.714	1.770
DCP 3	.030	1.762	1.807	1.661	1.760	1.682
DCP 4	.047	2.647	2.476	2.477	2.652	2.466
DCP 5	.074	2.522	2.472	2.513	2.556	2.478
DCP 6	.095	2.615	2.575	2.612	2.649	2.547
DCP 7	.144	1.572	1.616	1.707	1.599	1.708
DCP 8	.200	1.286	1.164	1.244	1.162	1.158
DCP 9	.250	1.116	1.066	1.208	1.142	1.176
DCP10	.300	1.038	0.974	1.044	1.037	1.043
DCP11	.345	1.001	0.948	1.007	1.021	1.024
DCP12	.501	0.820	0.862	0.892	0.857	0.863
DCP13	.600	0.805	0.768	0.745	0.770	0.782
DCP14	.701	0.754	0.737	0.750	0.724	0.756
DCP15	.800	0.610	0.637	0.647	0.597	0.611
DCP16	.900	0.246	0.226	0.305	0.262	0.268
DCP17	.969	0.017	-0.005	0.149	0.060	0.059

AIRFOIL NLR 7223-62 STEADY FORCES AND MOMENTS

M = 0.399 Rn = 4.7 x 10^6

SOLID FLOOR AND CEILING

ALPHA		-9.581	-9.015	-8.378	-7.817	-7.257	-6.653	-6.015	-5.456	-4.836	-4.258	-3.558
CN		-0.628	-0.605	-0.598	-0.535	-0.495	-0.486	-0.444	-0.414	-0.356	-0.303	-0.238
CM		-0.013	-0.023	-0.037	-0.042	-0.035	-0.033	-0.036	-0.025	-0.025	-0.023	-0.021
DCP 1	.010	-3.087	-3.234	-3.125	-2.635	-3.142	-4.793	-4.576	-4.816	-4.414	-3.547	-3.335
CCP 2	.020	-2.475	-2.410	-2.714	-2.616	-3.244	-3.545	-3.212	-2.977	-2.616	-2.438	-2.135
DCP 3	.030	-2.146	-2.155	-2.213	-3.150	-3.157	-3.071	-2.578	-2.606	-2.095	-1.664	-1.603
DCP 4	.049	-1.734	-1.866	-2.257	-2.452	-2.325	-2.035	-1.923	-1.676	-1.482	-1.282	-1.114
DCP 5	.074	-1.652	-1.787	-2.039	-2.198	-1.874	-1.461	-1.385	-1.206	-1.042	-0.845	-0.682
DCP 6	.099	-1.455	-1.575	-1.815	-1.668	-1.411	-1.169	-1.085	-0.953	-0.840	-0.685	-0.524
DCP 7	.149	-1.317	-1.403	-1.501	-1.265	-1.033	-0.883	-0.791	-0.726	-0.602	-0.510	-0.433
DCP 8	.200	-1.227	-1.241	-1.313	-0.902	-0.731	-0.675	-0.674	-0.585	-0.517	-0.415	-0.307
DCP 9	.250	-1.141	-1.194	-0.986	-0.807	-0.640	-0.606	-0.541	-0.526	-0.441	-0.351	-0.273
DCP10	.300	-1.032	-0.877	-0.724	-0.578	-0.466	-0.480	-0.442	-0.400	-0.325	-0.292	-0.197
DCP11	.355	-0.663	-0.520	-0.487	-0.349	-0.351	-0.363	-0.319	-0.311	-0.230	-0.227	-0.155
DCP12	.501	-0.433	-0.371	-0.291	-0.254	-0.282	-0.287	-0.257	-0.233	-0.201	-0.167	-0.115
DCP13	.600	-0.255	-0.197	-0.116	-0.117	-0.138	-0.161	-0.124	-0.121	-0.133	-0.090	-0.053
DCP14	.701	-0.055	-0.036	0.003	0.048	0.003	0.001	-0.033	0.014	0.017	0.041	0.065
DCP15	.800	-0.015	-0.001	0.013	-0.005	0.022	-0.001	0.048	-0.016	0.004	0.015	0.023
DCP16	.900	-0.032	-0.035	-0.033	-0.037	-0.052	-0.072	-0.076	-0.066	-0.099	-0.081	-0.105
DCP17	.965	-0.054	-0.035	-0.033	-0.015	0.010	-0.008	0.010	-0.025	-0.036	-0.029	-0.035

ALPHA		-3.020	-2.418	-1.806	-1.164	-0.552	0.031	1.231	1.814	2.431	3.091	3.646
CN		-0.176	-0.116	-0.052	0.004	0.075	0.125	0.263	0.326	0.387	0.455	0.515
CM		-0.018	-0.019	-0.016	-0.014	-0.015	-0.012	-0.014	-0.012	-0.011	-0.011	-0.008
DCP 1	.010	-2.732	-2.253	-1.810	-1.315	-0.865	-0.446	0.325	0.727	1.088	1.455	1.927
DCP 2	.020	-1.821	-1.512	-1.177	-0.896	-0.574	-0.227	0.361	0.711	1.052	1.358	1.655
DCP 3	.030	-1.310	-1.094	-0.824	-0.564	-0.275	-0.059	0.512	0.764	1.043	1.338	1.600
DCP 4	.049	-0.875	-0.677	-0.468	-0.226	-0.036	0.165	0.650	0.873	1.093	1.314	1.580
DCP 5	.074	-0.526	-0.346	-0.169	0.019	0.183	0.345	0.718	0.890	1.085	1.276	1.447
DCP 6	.099	-0.362	-0.241	-0.072	0.078	0.235	0.346	0.657	0.816	0.979	1.139	1.324
DCP 7	.149	-0.282	-0.158	-0.050	0.068	0.186	0.298	0.514	0.660	0.756	0.855	0.977
DCP 8	.200	-0.246	-0.166	-0.044	0.048	0.133	0.253	0.426	0.504	0.617	0.731	0.814
DCP 9	.250	-0.184	-0.120	-0.020	0.054	0.126	0.215	0.345	0.466	0.535	0.624	0.697
DCP10	.300	-0.155	-0.071	-0.018	0.068	0.133	0.194	0.340	0.408	0.465	0.556	0.615
DCP11	.399	-0.113	-0.072	0.025	0.068	0.115	0.169	0.274	0.348	0.413	0.449	0.506
DCP12	.501	-0.080	-0.038	-0.033	0.032	0.094	0.117	0.222	0.264	0.295	0.251	0.377
DCP13	.600	-0.016	0.025	0.047	0.066	0.096	0.125	0.217	0.261	0.266	0.311	0.334
DCP14	.701	0.080	0.110	0.133	0.161	0.178	0.190	0.259	0.267	0.307	0.320	0.338
DCP15	.800	0.032	0.045	0.050	0.062	0.086	0.098	0.122	0.138	0.124	0.174	0.172
DCP16	.900	-0.135	-0.101	-0.113	-0.111	-0.084	-0.106	-0.086	-0.073	-0.072	-0.074	-0.049
DCP17	.969	-0.053	-0.034	-0.040	-0.052	-0.052	-0.061	-0.045	-0.082	-0.044	-0.065	-0.095

M = 0.399 Rn = 4.7 x 10⁶

SOLID FLOOR AND CEILING

ALPHA		4.233	4.892	5.471	6.070	6.652	7.302	7.847	8.458	9.065	9.675	10.266
CN		0.582	0.650	0.700	0.756	0.823	0.879	0.937	0.984	1.039	1.054	1.075
CM		-0.006	-0.008	-0.006	-0.001	-0.003	-0.001	0.002	0.005	0.005	0.015	0.020
DCP 1	.010	2.357	2.718	3.106	3.528	3.534	4.378	5.055	5.645	6.071	6.222	6.346
DCP 2	.020	2.053	2.363	2.639	2.998	3.152	3.496	3.719	3.837	4.263	5.098	5.585
DCP 3	.030	1.908	2.196	2.445	2.696	2.937	3.239	3.482	3.696	3.843	4.001	4.336
DCP 4	.049	1.821	2.023	2.226	2.501	2.726	2.910	3.163	3.362	3.473	3.566	3.652
DCP 5	.074	1.646	1.847	2.009	2.195	2.393	2.557	2.701	2.858	3.024	3.080	3.122
DCP 6	.099	1.454	1.626	1.754	1.911	2.052	2.206	2.356	2.457	2.585	2.657	2.688
DCP 7	.149	1.126	1.250	1.330	1.475	1.584	1.670	1.774	1.890	1.982	2.023	2.110
DCP 8	.200	0.904	1.004	1.138	1.156	1.279	1.364	1.440	1.528	1.608	1.623	1.656
DCP 9	.250	0.775	0.832	0.930	1.012	1.080	1.153	1.245	1.300	1.381	1.407	1.441
DCP10	.300	0.683	0.753	0.811	0.868	0.925	0.995	1.054	1.115	1.166	1.183	1.201
DCP11	.399	0.591	0.631	0.645	0.705	0.764	0.812	0.876	0.877	0.943	0.971	0.965
DCP12	.501	0.435	0.466	0.482	0.543	0.592	0.623	0.637	0.700	0.753	0.730	0.734
DCP13	.600	0.355	0.430	0.446	0.426	0.502	0.516	0.562	0.554	0.560	0.566	0.561
DCP14	.701	0.340	0.385	0.391	0.414	0.439	0.466	0.466	0.464	0.483	0.445	0.419
DCP15	.800	0.190	0.210	0.204	0.203	0.223	0.220	0.218	0.235	0.244	0.213	0.185
DCP16	.900	-0.065	-0.055	-0.019	-0.055	-0.046	-0.037	-0.036	-0.023	-0.026	-0.036	-0.032
DCP17	.969	-0.074	-0.075	-0.070	-0.062	-0.068	-0.066	-0.065	-0.080	-0.067	-0.073	-0.059

ALPHA		10.855	11.524	12.044	12.631	13.228	13.881	14.427	15.106	15.651	16.515	17.468
CN		1.074	1.037	1.057	1.054	1.038	1.056	1.029	1.012	1.052	1.101	1.099
CM		0.024	0.035	-0.008	-0.024	-0.040	-0.053	-0.045	-0.055	-0.061	-0.065	-0.087
DCP 1	.010	6.130	3.572	3.217	2.812	2.724	2.448	2.525	2.573	2.607	4.127	4.384
DCP 2	.020	5.637	3.535	3.254	2.880	2.760	2.416	2.502	2.605	2.697	3.222	2.911
DCP 3	.030	4.734	4.087	3.627	3.337	3.057	2.825	3.025	3.128	3.106	2.132	1.711
DCP 4	.049	3.754	3.793	3.706	3.455	3.140	3.094	2.854	2.613	2.711	2.644	2.555
DCP 5	.074	3.126	3.114	3.042	2.920	2.710	2.641	2.515	2.295	2.444	2.471	2.534
DCP 6	.099	2.635	2.657	2.623	2.491	2.283	2.382	2.258	2.110	2.340	2.165	2.331
DCP 7	.149	2.387	2.046	1.992	1.924	1.831	1.793	1.843	1.722	1.515	1.864	1.933
DCP 8	.200	1.703	1.736	1.767	1.664	1.616	1.534	1.561	1.566	1.571	1.564	1.632
DCP 9	.250	1.471	1.551	1.533	1.544	1.575	1.606	1.543	1.564	1.466	1.391	1.319
DCP10	.300	1.217	1.258	1.471	1.426	1.427	1.383	1.376	1.363	1.344	1.245	1.167
DCP11	.399	0.976	0.952	1.064	1.136	1.172	1.164	1.137	1.095	1.116	1.172	1.127
DCP12	.501	0.706	0.712	0.745	0.791	0.852	1.006	0.601	0.868	0.881	1.022	0.952
DCP13	.600	0.503	0.498	0.582	0.663	0.594	0.726	0.684	0.706	0.715	0.871	0.880
DCP14	.701	0.385	0.376	0.432	0.471	0.532	0.539	0.555	0.545	0.586	0.747	0.782
DCP15	.800	0.192	0.196	0.243	0.265	0.355	0.365	0.346	0.365	0.435	0.570	0.584
DCP16	.900	-0.021	0.036	0.033	0.046	0.126	0.140	0.140	0.163	0.234	0.235	0.246
DCP17	.969	-0.064	-0.023	0.016	-0.032	0.034	0.011	0.014	0.040	0.065	0.035	0.053

AIRFOIL NLR 7223-62 STEADY FORCES AND MOMENTS

$M = 0.399$ $Rn = 4.7 \times 10^6$ SOLID FLOOR AND CEILING

ALPHA		18.344	18.647	19.215	19.863
CN		1.075	1.058	1.045	1.032
CM		-0.087	-0.087	-3.C88	-0.C92
DCP 1	.013	4.227	3.834	3.645	3.215
DCP 2	.020	2.942	2.906	2.776	2.679
DCP 3	.033	1.660	1.682	1.706	1.695
DCP 4	.049	2.470	2.606	2.445	2.281
DCP 5	.074	2.442	2.349	2.208	2.244
DCP 6	.099	2.193	2.172	2.160	2.128
DCP 7	.149	2.C57	1.967	1.581	1.923
DCP 8	.203	1.686	1.693	1.617	1.555
DCP 9	.250	1.243	1.253	1.237	1.265
DCP10	.300	1.108	1.106	1.137	1.082
DCP11	.399	1.032	1.011	1.024	1.C59
DCP12	.501	0.942	3.917	0.517	0.904
DCP13	.60C	C.832	0.806	3.824	0.831
DCP14	.701	0.802	0.773	0.747	3.761
DCP15	.800	0.657	3.608	0.597	0.589
DCP16	.903	3.214	0.274	3.265	0.294
DCP17	.969	3.054	0.C7C	0.079	0.060

M = 0.400   Rn = 6.3 x 10^6

SOLID FLOOR AND CEILING

ALPHA		-9.588	-9.002	-8.486	-7.861	-7.241	-6.700	-6.094	-5.440	-4.878	-4.290	-3.665
CN		-0.684	-3.661	-0.615	-0.547	-0.526	-0.500	-0.470	-0.435	-0.384	-0.323	-0.268
CM		-0.016	-0.025	-3.036	-0.039	-3.038	-0.036	-0.034	-3.028	-0.025	-0.023	-0.019
DCP 1	.010	-2.006	-2.162	-2.247	-2.696	-4.038	-4.916	-5.153	-5.191	-4.784	-4.165	-3.545
DCP 2	.020	-1.886	-2.089	-2.130	-2.848	-3.475	-3.712	-3.447	-3.041	-2.844	-2.583	-2.305
DCP 3	.030	-3.220	-3.244	-3.190	-3.338	-3.243	-3.200	-3.071	-2.613	-2.148	-1.924	-1.685
DCP 4	.049	-2.200	-2.222	-2.538	-2.510	-2.325	-2.050	-1.912	-1.746	-1.545	-1.352	-1.162
DCP 5	.074	-1.967	-1.973	-2.276	-2.072	-1.715	-1.515	-1.311	-1.242	-1.100	-0.918	-0.739
DCP 6	.099	-1.807	-1.857	-1.875	-1.578	-1.355	-1.179	-1.100	-0.962	-0.824	-0.705	-0.555
DCP 7	.149	-1.589	-1.584	-1.356	-1.128	-1.092	-0.911	-0.840	-0.753	-0.691	-3.547	-0.437
DCP 8	.233	-1.169	-1.142	-1.025	-0.944	-0.796	-0.779	-0.707	-0.631	-0.586	-0.466	-0.374
DCP 9	.250	-1.193	-1.214	-1.100	-3.815	-0.742	-0.637	-0.582	-0.521	-0.464	-0.374	-0.303
DCP10	.300	-1.030	-0.990	-3.923	-0.617	-3.538	-0.499	-0.456	-0.434	-0.358	-0.311	-0.243
DCP11	.399	-3.760	-0.650	-0.495	-0.414	-0.371	-0.359	-0.361	-0.332	-0.292	-0.231	-0.195
DCP12	.501	-0.475	-3.347	-0.316	-0.292	-0.311	-0.297	-0.279	-0.255	-0.210	-3.186	-0.147
DCP13	.600	-0.236	-0.196	-3.143	-0.145	-3.137	-0.149	-0.130	-3.130	-0.103	-0.079	-0.057
DCP14	.701	-0.035	-0.055	0.010	0.013	0.005	-0.009	0.020	0.006	0.024	0.038	0.054
DCP15	.800	-0.038	3.006	0.002	0.023	0.002	-0.008	3.001	0.012	-0.017	-3.030	0.012
DCP16	.900	-0.023	-0.075	-0.049	-0.046	-0.064	-0.053	-0.072	-0.114	-0.105	-0.105	-3.123
DCP17	.969	-3.016	0.002	0.016	-3.002	0.004	-3.008	-0.022	-0.036	-0.019	-0.019	-0.040

ALPHA		-3.046	-2.492	-1.882	-1.198	-0.666	-0.065	0.583	1.181	1.767	2.388	2.998
CN		-0.203	-0.142	-0.073	-0.011	0.052	0.115	0.186	0.250	0.316	3.371	0.437
CM		-0.016	-0.016	-3.016	-0.018	-0.014	-0.013	-0.016	-0.014	-0.013	-0.010	-3.010
DCP 1	.010	-2.928	-2.411	-1.930	-1.483	-0.998	-0.575	-0.186	0.229	0.641	1.018	1.432
DCP 2	.020	-2.010	-1.679	-1.330	-1.021	-0.693	-3.347	-0.032	3.264	0.639	0.546	1.255
DCP 3	.030	-1.428	-1.167	-0.890	-3.630	-0.362	-0.115	0.181	0.467	0.720	1.012	1.271
DCP 4	.049	-0.921	-3.713	-0.515	-0.309	-0.055	0.158	0.356	3.584	0.839	1.023	1.290
DCP 5	.074	-0.575	-0.403	-3.215	-0.035	0.135	3.322	0.512	0.701	0.869	1.053	1.234
DCP 6	.099	-3.401	-0.248	-0.094	0.047	0.206	0.336	0.508	0.692	0.805	0.981	1.142
DCP 7	.149	-0.325	-0.204	-0.077	0.010	3.146	0.258	0.375	3.481	0.631	0.727	0.830
DCP 8	.200	-0.285	-0.192	-0.089	-0.028	0.089	0.194	0.276	0.371	0.479	0.553	0.679
DCP 9	.250	-3.219	-0.155	-0.063	-0.011	0.091	0.170	0.245	0.351	0.433	0.497	0.574
DCP10	.300	-0.165	-0.098	-0.043	0.058	0.106	0.176	0.251	0.333	0.399	0.481	0.542
DCP11	.399	-0.134	-0.072	0.004	3.040	0.084	0.146	0.222	0.272	3.344	0.394	0.425
DCP12	.501	-0.105	-3.095	-0.015	0.026	0.067	0.126	0.165	0.193	0.245	0.273	0.341
DCP13	.600	-0.023	0.006	3.031	0.071	0.095	3.144	0.168	0.218	0.250	0.274	3.292
DCP14	.701	0.091	0.104	0.136	3.152	0.172	0.194	0.244	0.245	0.268	0.290	0.318
DCP15	.800	0.016	0.033	0.037	0.068	0.077	0.089	0.112	3.131	0.144	0.129	0.145
DCP16	.900	-0.137	-0.118	-0.115	-0.092	-0.098	-0.120	-0.090	-0.082	-0.083	-0.086	-0.071
DCP17	.969	-3.036	-0.032	-0.041	-0.029	-0.045	-0.037	-3.044	-0.047	-0.068	-0.060	-0.050

AIRFOIL NLR 7223-62   STEADY FORCES AND MOMENTS

M = 0.400   Rn = 6.3 x 10⁶ ... $M = 0.400$ $Rn = 6.3 \times 10^6$

SOLID FLOOR AND CEILING

ALPHA		3.583	4.166	4.834	5.368	6.013	6.590	7.225	7.812	8.358	9.020	9.601
CN		0.500	0.576	0.643	0.694	0.763	0.831	0.887	0.944	1.000	1.033	1.063
CM		-0.008	-0.010	-0.010	-0.007	-0.006	-0.005	-0.001	0.000	0.002	0.006	0.011
DCP 1	.010	1.846	2.262	2.668	3.063	3.470	3.912	4.492	5.103	5.780	6.216	6.439
DCP 2	.020	1.593	1.958	2.260	2.566	2.915	3.277	3.568	3.871	4.001	4.106	4.817
DCP 3	.030		1.664	2.156	2.422	2.672	2.586	3.283	3.510	3.736	3.906	4.014
DCP 4	.049	1.538	1.759	2.013		2.483	2.727	2.951	3.172	3.359	3.521	3.606
DCP 5	.074	.411	1.514	1.613	1.956		2.378	2.549	2.707	2.881	3.000	3.056
DCP 6	.099	.300	1.446	1.632	1.857	1.917	2.087	2.225	2.345	2.318	2.599	2.667
DCP 7	.149	1.908	1.285	1.224	1.295	.449	1.578	1.677	1.787	1.843	1.947	2.030
DCP 8	.200	0.790	0.86			1.150	1.265	1.350	1.407	1.526	1.574	1.617
DCP 9	.250	0.665				0.974	1.076	1.163	1.216	1.292	1.365	1.418
DCP10	.300	0.556			0.607		.89	0.944	1.024	1.074	1.120	1.190
DCP11	.395	0.509						0.778	0.811	0.871	0.907	0.955
DCP12	.501	0.346						2.602	0.823	0.647	0.709	0.701	0.731
DCP13	.600	0.336						0.496	0.526	0.556	0.574	0.595
DCP14	.701							0.461	0.460	0.498	0.487	0.479
DCP15	.800						0.217	0.229	0.230	0.267	0.262	0.246	0.236
DCP16	.900	-0.073	-0.05			-0.044	-0.022	-0.064	-0.043	-0.030	-0.010	-0.058
DCP17	.969	-0.070	-0.05		-0.283	-0.067	-0.030	-0.060	-0.075	-0.063	-0.077	-0.069

ALPHA		10.191	10.837	11.408	11.997	12.602	13.271	13.778	14.417	15.046	15.583	16.154
CN		1.091	1.092	1.081	1.075	1.035	1.020	1.012	1.037	1.035	1.023	1.040
CM		0.016	0.023	0.026	0.022	0.014	-0.009	-0.028	-0.036	-0.049	-0.055	-0.061
DCP 1	.010	6.498	6.339	6.184	5.952	5.640	4.741	4.863	4.670	4.655	4.120	4.211
DCP 2	.020	5.512	5.713	5.570	5.280	4.988	4.469	4.126	4.044	4.097	3.452	3.597
DCP 3	.030	4.338	4.788	4.996	4.962	4.715	4.235	3.943	3.660	3.357	3.128	3.228
DCP 4	.049	3.669	3.840	3.963	3.958	3.674	3.677	3.230	3.361	3.148	3.095	2.920
DCP 5	.074	3.139	3.140	3.146	3.125	2.950	2.795	2.487	2.527	2.521	2.383	2.211
DCP 6	.099	2.740	2.737	2.741	2.695	2.592	2.334	2.079	2.178	2.107	2.126	2.037
DCP 7	.149	2.073	2.108	2.082	2.105	1.956	1.775	1.698	1.736	1.704	1.714	1.717
DCP 8	.200	1.673	1.695	1.683	1.721	1.619	1.521	1.460	1.534	1.442	1.452	1.487
DCP 9	.250	1.424	1.430	1.415	1.386	1.318	1.309	1.328	1.382	1.257	1.276	1.396
DCP10	.300	1.263	1.248	1.215	1.213	1.234	1.185	1.222	1.199	1.154	1.141	1.192
DCP11	.395	0.587	0.582	0.951	0.953	0.914	0.936	1.015	0.977	1.015	1.026	1.011
DCP12	.501	0.738	0.720	0.711	0.685	0.658	0.731	0.738	0.797	0.791	0.843	0.906
DCP13	.600	0.575	0.545	0.529	0.495	0.479	0.557	0.626	0.660	0.765	0.732	0.760
DCP14	.701	0.440	0.428	0.355	0.354	0.370	0.476	0.495	0.543	0.607	0.585	0.628
DCP15	.800	0.214	0.195	0.198	0.191	0.247	0.287	0.344	0.376	0.442	0.472	0.519
DCP16	.900	-0.022	-0.053	-0.022	0.042	0.047	0.093	0.166	0.172	0.176	0.190	0.161
DCP17	.969	-0.046	-0.057	-0.037	-0.019	-0.023	0.007	0.017	0.070	0.055	0.055	0.043

AIRFOIL NLR 7223-62   STEADY FORCES AND MOMENTS

M = 0.400   Rn = 6.3 x 10^6 SOLID FLOOR AND CEILING

ALPHA		16.758	17.395	17.568	18.578	19.211	19.757
CN		1.022	1.033	1.007	0.974	1.018	1.003
CM		-0.065	-0.075	-0.070	-0.081	-0.095	-0.092
DCP 1	.010	3.689	3.702	3.516	3.499	3.505	3.523
DCP 2	.020	3.414	3.309	3.258	3.080	2.971	2.816
DCP 3	.030	3.055	2.632	2.855	2.770	2.470	2.225
DCP 4	.049	2.637	2.512	2.395	2.096	2.059	2.140
DCP 5	.074	2.120	2.225	1.970	1.750	1.815	1.849
DCP 6	.099	2.018	1.561	1.860	1.638	1.714	1.793
DCP 7	.149	1.664	1.668	1.764	1.495	1.564	1.628
DCP 8	.200	1.489	1.506	1.448	1.349	1.449	1.477
DCP 9	.250	1.372	1.394	1.384	1.322	1.306	1.311
DCP10	.300	1.224	1.234	1.242	1.183	1.247	1.145
DCP11	.399	1.077	1.101	1.050	1.100	1.150	1.054
DCP12	.501	0.892	0.928	0.872	0.931	0.980	0.928
DCP13	.600	0.704	0.747	0.784	0.780	0.868	0.857
DCP14	.701	0.639	0.650	0.634	0.626	0.711	0.748
DCP15	.800	0.477	0.504	0.470	0.517	0.553	0.569
DCP16	.900	0.203	0.248	0.216	0.226	0.257	0.231
DCP17	.969	0.064	0.082	0.045	0.068	0.076	0.072

AIRFOIL NLR 7223-62 STEADY FORCES AND MOMENTS

M = 0.401 Rn = 7.0 x 10^6

SOLID FLOOR AND CEILING

ALPHA		-9.448	-8.826	-8.289	-7.706	-7.127	-6.434	-5.927	-5.336	-4.725	-4.092	-3.543
CN		-0.665	-0.626	-0.579	-0.529	-0.499	-0.496	-0.461	-0.409	-0.363	-0.308	-0.248
CM		-0.021	-0.331	-0.038	-0.039	-0.036	-0.035	-0.029	-0.028	-0.024	-0.020	-0.019
DCP 1	.010	-2.061	-2.199	-2.391	-2.558	-4.161	-5.116	-5.086	-5.077	-4.577	-3.946	-3.320
DCP 2	.020	-1.987	-2.122	-2.438	-3.244	-3.580	-3.656	-3.316	-2.935	-2.777	-2.533	-2.221
DCP 3	.030	-3.147	-3.208	-3.351	-3.198	-3.204	-3.126	-2.858	-2.281	-2.073	-1.838	-1.602
DCP 4	.049	-2.163	-2.415	-2.581	-2.476	-2.234	-2.012	-1.828	-1.671	-1.521	-1.320	-1.090
DCP 5	.074	-1.953	-2.006	-2.212	-2.075	-1.536	-1.447	-1.317	-1.184	-1.017	-0.840	-0.696
DCP 6	.099	-1.820	-1.910	-1.701	-1.476	-1.213	-1.132	-1.020	-0.912	-0.768	-0.629	-0.497
DCP 7	.149	-1.631	-1.468	-1.218	-1.108	-0.953	-0.929	-0.827	-0.721	-0.637	-0.519	-0.420
DCP 8	.200	-1.116	-1.046	-0.995	-0.821	-0.746	-0.746	-0.668	-0.605	-0.510	-0.473	-0.352
DCP 9	.250	-1.205	-1.121	-0.967	-0.798	-0.666	-0.590	-0.563	-0.503	-0.459	-0.397	-0.283
DCP10	.300	-1.015	-3.858	-3.718	-0.469	-0.536	-0.486	-0.447	-0.389	-0.333	-0.289	-0.212
DCP11	.399	-0.660	-0.563	-0.408	-3.393	-0.360	-0.377	-0.346	-0.302	-0.256	-0.226	-0.168
DCP12	.501	-3.421	-0.362	-0.348	-0.303	-0.264	-0.295	-0.270	-0.232	-0.204	-0.167	-0.150
DCP13	.600	-0.237	-0.154	-0.144	-0.159	-0.184	-0.162	-0.139	-0.123	-0.119	-0.090	-0.068
DCP14	.701	-0.029	-0.024	-0.014	3.011	0.016	0.007	-0.018	0.022	0.025	0.039	0.084
DCP15	.800	-0.023	0.018	3.016	0.011	0.010	-0.008	-0.023	-0.030	-0.018	-0.011	0.009
DCP16	.900	-0.035	-0.048	-0.021	-0.025	-0.061	-0.053	-0.084	-0.076	-0.092	-0.094	-0.108
DCP17	.969	-3.017	-0.030	-0.011	-0.025	0.008	-0.020	-0.013	-0.011	-0.025	-0.048	-0.042

ALPHA		-2.942	-2.305	-1.655	-1.101	-0.495	0.144	0.741	1.212	1.518	2.562	3.151
CN		-0.183	-0.120	-0.059	0.009	0.073	0.137	0.194	0.259	0.324	0.392	0.452
CM		-0.019	-0.017	-0.015	-0.018	-0.016	-0.016	-0.014	-0.014	-0.013	-0.012	-0.010
DCP 1	.010	-2.739	-2.213	-1.740	-1.311	-0.881	-0.475	-0.066	0.355	0.740	1.118	1.535
DCP 2	.020	-1.924	-1.580	-1.277	-0.924	-0.609	-0.296	0.011	0.342	0.654	0.588	1.294
DCP 3	.030	-1.356	-1.071	-0.802	-3.545	-0.302	-0.021	0.247	0.517	0.776	1.099	1.358
DCP 4	.049	-0.895	-0.701	-0.461	-0.233	-0.014	0.178	0.400	0.628	0.859	1.070	1.332
DCP 5	.074	-0.517	-0.351	-0.155	0.003	0.189	0.373	0.543	0.710	0.900	1.111	1.261
DCP 6	.099	-0.359	-0.213	-0.052	0.095	0.235	0.406	0.547	0.698	0.845	1.030	1.188
DCP 7	.149	-0.292	-0.183	-0.060	0.036	0.153	0.272	0.370	0.496	0.607	0.737	0.848
DCP 8	.200	-3.266	-0.141	-3.081	0.034	0.151	0.230	0.318	0.391	0.512	0.613	0.679
DCP 9	.250	-3.216	-3.138	-0.041	0.016	3.103	0.191	0.263	0.344	0.444	0.518	0.616
DCP10	.300	-0.134	-0.067	-0.002	0.059	0.152	0.199	0.260	0.337	0.412	0.500	0.545
DCP11	.399	-3.115	-0.071	-0.013	0.059	0.119	0.182	0.232	0.293	0.341	0.381	0.452
DCP12	.501	-0.097	-0.045	-0.004	0.034	0.072	0.118	0.157	0.203	0.247	0.309	0.342
DCP13	.600	-0.023	0.033	3.023	3.084	0.100	0.144	0.182	0.206	0.229	0.267	0.301
DCP14	.701	0.098	0.110	0.137	0.153	3.188	0.210	0.213	0.249	0.277	3.305	0.327
DCP15	.800	0.022	0.029	0.042	0.071	0.084	0.098	0.104	0.132	0.139	0.158	0.159
DCP16	.900	-0.106	-0.111	-0.104	-0.072	-0.080	-0.068	-0.069	-0.064	-0.058	-0.069	-0.062
DCP17	.969	-0.027	-0.047	-0.037	-0.035	-0.047	-0.046	-0.055	-0.067	-0.056	-0.058	-0.066

M = 0.401   Rn = 7.0 x 10^6

SOLID FLOOR AND CEILING

ALPHA		3.724	4.365	4.573	5.566	6.117	6.785	7.400	7.563	8.562	9.191	9.747
CN		0.524	0.578	0.643	0.701	0.761	0.825	0.878	0.941	0.994	1.036	1.056
CM		-3.013	-0.009	-0.009	-0.007	-0.004	-0.005	0.000	0.000	0.004	0.006	0.011
DCP 1	.010	1.952	2.308	2.721	3.091	3.512	3.566	4.475	5.232	5.880	6.311	6.454
DCP 2	.020	1.663	1.572	2.274	2.580	2.890	3.296	3.551	3.870	3.983	4.128	4.752
DCP 3	.030	1.629	1.903	2.216	2.408	2.624	3.004	3.261	3.524	3.733	3.925	4.012
DCP 4	.049	1.567	1.795	2.018	2.244	2.476	2.717	2.942	3.156	3.348	3.498	3.554
DCP 5	.074	1.454	1.622	1.820	1.994	2.193	2.383	2.541	2.692	2.875	2.995	3.050
DCP 6	.099	1.339	1.475	1.634	1.786	1.939	2.102	2.239	2.371	2.488	2.608	2.690
DCP 7	.149	0.566	1.089	1.235	1.311	1.439	1.537	1.632	1.764	1.866	1.938	1.977
DCP 8	.200	0.791	0.894	0.975	1.059	1.157	1.243	1.342	1.404	1.505	1.595	1.619
DCP 9	.250	0.696	0.757	0.846	0.918	0.993	1.098	1.135	1.223	1.296	1.362	1.391
DCP10	.300	0.637	0.684	0.748	0.817	0.881	0.940	1.011	1.065	1.114	1.157	1.198
DCP11	.399	0.497	0.545	0.611	0.671	0.712	0.757	0.804	0.852	0.912	0.938	0.974
DCP12	.501	0.383	0.408	0.461	0.510	0.546	0.599	0.613	0.643	0.685	0.721	3.703
DCP13	.600	0.361	0.389	0.404	0.433	0.461	0.492	0.528	0.541	0.568	0.570	0.571
DCP14	.701	0.354	0.356	0.395	0.408	0.419	0.448	0.431	0.467	0.484	0.483	0.468
DCP15	.800	0.189	0.207	0.208	0.211	0.234	0.245	0.245	0.262	0.256	0.249	0.258
DCP16	.900	-0.037	-0.046	-0.036	-0.052	-0.055	-0.033	-0.041	-0.015	-0.038	-0.006	-0.046
DCP17	.969	-0.058	-0.076	-0.075	-0.061	-0.074	-0.055	-0.073	-0.068	-0.065	-0.078	-0.078

ALPHA		10.391	10.998	11.622	12.183	12.724	13.441	13.994	14.575	15.174	15.840	16.344
CN		1.067	1.074	1.066	1.030	1.016	0.962	0.977	1.028	0.995	0.958	0.964
CM		0.018	0.021	0.023	0.027	0.010	-0.025	-3.030	-0.049	-0.048	-0.056	-0.056
DCP 1	.010	6.473	6.236	6.036	5.834	5.255	4.840	5.040	4.945	4.172	4.211	4.411
DCP 2	.020	5.358	5.585	5.542	5.392	4.983	4.072	4.180	3.858	3.972	3.621	3.674
DCP 3	.030	4.256	4.688	4.935	4.917	4.653	4.066	3.832	3.242	3.331	3.379	3.307
DCP 4	.049	3.615	3.773	3.878	3.855	3.644	3.017	3.126	3.187	2.819	2.296	2.409
DCP 5	.074	3.103	3.110	3.084	3.031	2.883	2.381	2.421	2.655	2.287	1.981	1.917
DCP 6	.099	2.690	2.703	2.643	2.575	2.455	1.927	1.995	2.142	1.979	1.732	1.758
DCP 7	.149	2.033	2.055	2.011	1.587	1.906	1.522	1.547	1.654	1.637	1.458	1.521
DCP 8	.200	1.653	1.672	1.651	1.622	1.592	1.345	1.405	1.337	1.411	1.428	1.373
DCP 9	.250	1.434	1.421	1.401	1.352	1.328	1.274	1.245	1.215	1.321	1.282	1.271
DCP10	.300	1.198	1.232	1.190	1.195	1.154	1.165	1.077	1.137	1.098	1.149	1.175
DCP11	.399	0.566	0.952	0.574	0.886	0.901	0.927	0.951	1.017	0.992	0.992	1.026
DCP12	.501	0.726	0.737	0.706	0.643	0.656	0.768	0.731	0.823	0.787	0.835	0.820
DCP13	.600	0.557	0.543	0.519	0.475	0.472	0.572	0.622	0.695	0.686	0.670	0.655
DCP14	.701	0.431	0.420	0.382	0.319	0.373	0.494	0.532	0.580	0.585	0.626	0.567
DCP15	.800	0.207	0.196	0.183	0.182	0.255	0.334	0.337	0.472	0.455	0.410	0.435
DCP16	.900	-0.041	-0.030	0.001	0.007	0.074	0.140	0.155	0.207	0.162	0.179	0.191
DCP17	.969	-0.070	-0.075	-0.065	-0.030	-0.008	-0.021	0.034	0.047	0.045	0.022	0.049

AIRFOIL NLR 7223-62   STEADY FORCES AND MOMENTS

M = 0.401   Rn = 7.0 x 10^6 SOLID FLOOR AND CEILING

ALPHA		17.010	17.585	18.177	18.756	19.325
CN		0.585	0.980	0.962	0.577	0.931
CM		-0.062	-0.069	-0.074	-0.083	-3.C83
DCP 1	.010	3.588	3.699	3.447	3.268	3.121
DCP 2	.020	3.429	3.115	2.997	2.871	2.696
DCP 3	.030	3.C99	2.751	2.784	2.468	2.582
DCP 4	.049	2.403	2.488	2.157	2.236	1.842
DCP 5	.074	1.997	2.076	1.936	1.846	1.657
DCP 6	.099	1.910	1.897	1.711	1.825	1.576
DCP 7	.149	1.544	1.530	1.509	1.502	1.421
DCP 8	.200	1.395	1.378	1.405	1.363	1.304
DCP 9	.250	1.382	1.280	1.307	1.242	1.223
DCP10	.300	1.160	1.149	1.201	1.149	1.177
DCP11	.399	1.067	1.046	1.C28	1.12C	1.047
DCP12	.501	0.859	0.856	0.866	3.912	0.515
DCP13	.600	0.680	0.753	0.701	0.805	0.774
DCP14	.701	0.579	0.633	0.60°	3.665	0.638
DCP15	.800	0.464	0.469	0.506	0.510	3.484
DCP16	.900	0.233	0.223	0.227	0.218	3.217
DCP17	.969	0.039	0.048	0.086	3.072	0.C64

M = 0.500   Rn = 7.9 x 10⁶

SOLID FLOOR AND CEILING

ALPHA		-9.525	-9.001	-8.421	-7.811	-7.252	-6.656	-6.024	-5.435	-4.858	-4.274	-3.558
CN		-0.676	-0.648	-0.616	-0.569	-0.526	-0.491	-0.442	-0.409	-0.368	-0.318	-0.259
CM		-0.008	-0.022	-0.036	-0.042	-0.044	-0.042	-0.039	-0.032	-0.025	-0.024	-0.021
DCP 1	.010	-2.275	-2.391	-2.888	-2.937	-3.432	-3.882	-3.810	-3.797	-3.521	-3.695	-3.773
DCP 2	.020	-2.150	-2.382	-2.626	-3.191	-3.334	-3.437	-3.270	-2.970	-2.939	-2.757	-2.171
DCP 3	.030	-2.668	-2.896	-3.088	-3.119	-3.107	-3.038	-2.809	-2.622	-2.590	-2.057	-1.700
DCP 4	.049	-2.104	-2.219	-2.417	-2.480	-2.476	-2.425	-2.288	-2.110	-1.850	-1.295	-1.131
DCP 5	.074	-1.834	-1.913	-2.161	-2.106	-1.905	-1.766	-1.555	-1.395	-1.134	-0.875	-0.732
DCP 6	.099	-1.800	-1.856	-1.729	-1.725	-1.557	-1.377	-1.122	-0.938	-0.842	-0.711	-0.551
DCP 7	.149	-1.494	-1.489	-1.437	-1.267	-1.152	-0.940	-0.798	-0.724	-0.612	-0.526	-0.436
DCP 8	.200	-1.137	-1.127	-1.301	-0.944	-0.853	-0.737	-0.695	-0.609	-0.544	-0.457	-0.368
DCP 9	.250	-1.123	-1.176	-1.036	-0.899	-0.742	-0.654	-0.556	-0.517	-0.441	-0.385	-0.308
DCP10	.300	-0.952	-0.862	-0.688	-0.656	-0.546	-0.475	-0.433	-0.383	-0.343	-0.298	-0.208
DCP11	.399	-0.727	-0.591	-0.478	-0.429	-0.349	-0.346	-0.303	-0.279	-0.262	-0.216	-0.154
DCP12	.501	-0.455	-0.426	-0.339	-0.292	-0.274	-0.262	-0.236	-0.221	-0.195	-0.189	-0.143
DCP13	.600	-0.339	-0.192	-0.172	-0.144	-0.144	-0.138	-0.110	-0.127	-0.108	-0.077	-0.056
DCP14	.701	-0.090	-0.063	0.009	0.029	0.036	0.015	0.029	0.041	0.041	0.032	0.065
DCP15	.800	-0.056	-0.056	-0.013	0.016	0.015	0.041	0.013	0.010	0.012	0.004	0.005
DCP16	.900	-0.077	-0.041	-0.051	-0.019	-0.035	-0.044	-0.033	-0.075	-0.082	-0.081	-0.122
DCP17	.969	-0.000	-0.010	-0.002	-0.026	-0.015	0.006	-0.005	-0.018	-0.017	-0.033	-0.024

ALPHA		-3.047	-2.452	-1.851	-1.162	-0.620	0.010	0.680	1.186	1.801	2.458	3.015
CN		-0.198	-0.137	-0.070	-0.007	0.059	0.128	0.196	0.262	0.327	0.401	0.472
CM		-0.021	-0.017	-0.017	-0.016	-0.016	-0.016	-0.015	-0.013	-0.010	-0.012	-0.010
DCP 1	.010	-3.198	-2.551	-1.966	-1.538	-1.072	-0.680	-0.276	0.162	0.605	0.817	1.397
DCP 2	.020	-2.014	-1.686	-1.371	-1.050	-0.709	-0.363	-0.044	0.333	0.665	0.991	1.322
DCP 3	.030	-1.462	-1.217	-0.943	-0.673	-0.425	-0.138	0.165	0.451	0.738	1.053	1.346
DCP 4	.049	-0.922	-0.656	-0.485	-0.265	-0.032	0.175	0.419	0.663	0.911	1.159	1.430
DCP 5	.074	-0.552	-0.365	-0.186	-0.015	0.164	0.385	0.576	0.757	0.956	1.172	1.377
DCP 6	.099	-0.415	-0.263	-0.095	0.048	0.208	0.359	0.552	0.715	0.882	1.061	1.240
DCP 7	.149	-0.328	-0.187	-0.071	0.033	0.162	0.284	0.402	0.543	0.648	0.756	0.897
DCP 8	.200	-0.277	-0.194	-0.088	-0.001	0.114	0.234	0.303	0.400	0.514	0.626	0.732
DCP 9	.250	-0.227	-0.140	-0.052	0.017	0.101	0.200	0.291	0.371	0.461	0.554	0.632
DCP10	.300	-0.142	-0.076	-0.034	0.061	0.121	0.203	0.259	0.351	0.424	0.510	0.578
DCP11	.399	-0.121	-0.054	-0.004	0.063	0.118	0.184	0.235	0.294	0.354	0.428	0.488
DCP12	.501	-0.081	-0.060	-0.007	0.031	0.071	0.113	0.179	0.205	0.258	0.296	0.345
DCP13	.600	-0.018	0.002	0.038	0.056	0.095	0.133	0.181	0.211	0.232	0.297	0.318
DCP14	.701	0.080	0.105	0.133	0.162	0.165	0.194	0.230	0.255	0.263	0.308	0.338
DCP15	.830	0.021	0.028	0.050	0.058	0.073	0.090	0.114	0.113	0.126	0.143	0.174
DCP16	.900	-0.107	-0.118	-0.110	-0.098	-0.081	-0.078	-0.092	-0.091	-0.077	-0.076	-0.087
DCP17	.969	-0.027	-0.042	-0.049	-0.052	-0.040	-0.037	-0.060	-0.048	-0.070	-0.072	-0.063

AIRFOIL NLR 7223-62   STEADY FORCES AND MOMENTS

M = 0.500   Rn = 7.9 x 10^6

SOLID FLOOR AND CEILING

ALPHA		3.624	4.265	4.861	5.426	6.048	6.661	7.251	7.833	8.529	9.054	9.685
CN		0.542	0.610	0.671	0.734	0.795	0.862	0.927	0.973	1.005	1.037	1.086
CM		-0.009	-0.007	-0.006	-0.002	-0.032	0.002	0.004	0.013	0.019	0.025	0.025
DCP 1	.010	1.872	2.285	2.692	3.103	3.613	4.350	4.850	4.891	5.018	5.135	4.903
DCP 2	.020	1.698	2.043	2.369	2.709	2.836	3.757	4.425	4.830	5.008	5.152	5.031
DCP 3	.030	1.657	1.562	2.268	2.570	2.805	2.830	4.106	4.457	4.732	4.888	4.507
DCP 4	.049	1.715	1.564	2.226	2.485	2.750	3.051	2.726	4.125	4.425	4.625	4.688
DCP 5	.074	1.586	1.786	1.994	2.181	2.385	2.585	2.720	2.454	2.868	3.417	3.218
DCP 6	.099	1.414	1.611	1.702	1.858	2.072	2.219	2.348	2.344	2.284	2.453	2.575
DCP 7	.149	1.040	1.163	1.274	1.405	1.516	1.620	1.727	1.787	1.826	1.833	1.912
DCP 8	.200	0.825	0.921	1.022	1.123	1.210	1.295	1.375	1.424	1.484	1.503	1.786
DCP 9	.250	0.731	0.821	0.874	0.965	1.044	1.122	1.195	1.233	1.285	1.305	1.622
DCP10	.300	0.648	0.727	0.798	0.856	0.927	0.577	1.033	1.082	1.117	1.135	1.404
DCP11	.399	0.530	0.586	0.649	0.704	0.761	0.812	0.855	0.878	0.858	0.910	0.550
DCP12	.501	0.394	0.443	0.494	0.518	0.556	0.601	0.638	0.660	0.674	0.672	0.683
DCP13	.600	0.361	0.391	0.401	0.437	0.481	0.490	0.525	0.530	0.534	0.534	0.489
DCP14	.701	0.357	0.365	0.393	0.432	0.437	0.440	0.460	0.445	0.442	0.418	0.356
DCP15	.800	0.176	0.192	0.201	0.204	0.220	0.220	0.246	0.224	0.197	0.194	0.165
DCP16	.900	-0.071	-0.065	-0.065	-0.057	-0.056	-0.051	-0.047	-0.055	-0.055	-0.044	0.036
DCP17	.969	-0.068	-0.064	-0.063	-0.073	-0.077	-0.072	-0.075	-0.074	-0.081	-0.074	-0.052

ALPHA		10.272	10.886	11.445	12.043	12.681	13.258	13.650	14.465	15.113	15.624	16.230
CN		1.073	1.033	0.585	0.576	0.548	0.545	0.565	0.548	0.577	0.992	0.977
CM		0.014	0.013	-0.001	-0.009	-0.017	-0.032	-0.031	-0.038	-0.046	-0.055	-0.064
DCP 1	.010	4.704	4.662	4.452	4.332	4.241	4.124	4.025	3.885	3.551	3.609	3.731
DCP 2	.020	4.647	4.622	4.268	3.890	3.743	3.488	3.315	3.320	2.955	2.831	2.550
DCP 3	.030	4.891	4.849	4.552	3.707	3.525	3.360	3.216	3.123	2.941	2.815	2.668
DCP 4	.049	4.105	3.444	3.060	2.916	2.700	2.440	2.526	2.309	2.412	2.466	2.153
DCP 5	.074	3.071	2.795	2.483	2.447	2.128	2.072	2.129	1.951	2.078	2.143	1.979
DCP 6	.099	2.433	2.442	2.254	2.181	2.073	1.567	2.012	1.945	2.030	2.045	1.843
DCP 7	.149	1.878	1.891	1.812	1.866	1.723	1.711	1.775	1.721	1.769	1.730	1.675
DCP 8	.200	1.786	1.675	1.517	1.562	1.546	1.474	1.543	1.533	1.536	1.520	1.581
DCP 9	.250	1.688	1.564	1.477	1.415	1.387	1.339	1.439	1.421	1.437	1.407	1.363
DCP10	.300	1.377	1.281	1.215	1.243	1.255	1.169	1.284	1.194	1.307	1.237	1.252
DCP11	.399	1.032	1.046	1.014	1.058	0.954	0.564	1.068	0.948	1.043	1.065	1.084
DCP12	.501	0.691	0.713	0.706	0.724	0.744	0.826	0.715	0.748	0.785	0.845	0.834
DCP13	.600	0.502	0.453	0.465	0.491	0.572	0.627	0.617	0.637	0.676	0.712	0.707
DCP14	.701	0.376	0.361	0.396	0.373	0.431	0.433	0.454	0.467	0.530	0.587	0.611
DCP15	.800	0.183	0.187	0.240	0.237	0.264	0.324	0.318	0.308	0.382	0.412	0.437
DCP16	.900	0.004	0.030	0.038	0.069	0.067	0.082	0.082	0.144	0.113	0.158	0.159
DCP17	.969	0.035	-0.005	-0.026	0.021	-0.026	0.012	0.008	0.007	-0.004	-0.006	0.037

$M = 0.500$ $Rn = 7.9 \times 10^6$ SOLID FLOOR AND CEILING

ALPHA		16.510	17.450	18.013
CN		0.570	0.580	0.576
CM		-0.070	-0.077	-0.080
DCP 1	.010	3.363	3.411	2.837
DCP 2	.020	2.537	2.884	2.751
DCP 3	.030	2.721	2.788	2.778
DCP 4	.049	2.042	1.965	2.026
DCP 5	.074	1.562	1.855	1.724
DCP 6	.059	1.823	1.725	1.735
DCP 7	.149	1.613	1.612	1.581
DCP 8	.200	1.465	1.344	1.421
CCP 9	.250	1.332	1.354	1.401
DCP10	.300	1.217	1.260	1.205
DCP11	.399	1.117	1.112	1.127
DCP12	.501	0.878	0.921	0.927
DCP13	.600	0.741	0.771	0.827
DCP14	.701	0.587	0.664	0.635
DCP15	.633	0.462	0.457	0.448
DCP16	.930	0.195	0.200	0.203
DCP17	.969	0.001	0.030	0.050

M = 0.597 Rn = 3.1 x 10⁶

SOLID FLOOR AND CEILING

α		-8.428	-7.926	-7.413	-6.906	-6.365	-5.870	-5.329	-4.862	-4.304	-3.775	-2.702
CN		-0.642	-0.640	-0.617	-0.585	-0.563	-0.536	-0.498	-0.451	-0.394	-0.340	-0.233
CM		0.013	0.008	-0.001	-0.013	-0.026	-0.034	-0.041	-0.044	-0.034	-0.032	-0.025
CP 1	.010	-2.372	2.448	-2.514	-2.528	-2.541	-2.599	-2.599	-2.588	-2.641	-2.798	-2.923
CP 2	.020	-2.379	-2.393	-2.410	-2.349	-2.415	-2.443	-2.448	-2.476	-2.528	-2.656	-2.555
CP 3	.030	-2.658	-2.715	-2.718	-2.687	-2.673	-2.633	-2.619	-2.505	-2.423	-2.360	-1.862
CP 4	.049	-1.584	-1.577	-1.597	-1.612	-1.755	-1.813	-1.846	-1.846	-1.940	-1.858	-0.950
CP 5	.074	-1.426	-1.408	-1.410	-1.426	-1.562	-1.649	-1.642	-1.435	-1.649	-1.376	-0.583
CP 6	.099	-1.291	-1.294	-1.293	-1.322	-1.457	-1.450	-1.453	-1.483	-1.309	-0.910	-0.410
CP 7	.149	-1.243	-1.271	-1.264	-1.289	-1.325	-1.351	-1.373	-1.273	-0.984	-0.646	-0.390
CP 8	.200	-1.110	-1.149	-1.156	-1.128	-1.159	-1.125	-1.118	-0.953	-0.610	-0.443	-0.264
CP 9	.250	-1.086	-1.119	-1.083	-1.082	-1.060	-1.004	-0.958	-0.693	-0.417	-0.395	-0.249
CP10	.300	-0.899	-0.920	-0.897	-0.918	-0.792	-0.737	-0.589	-0.491	-0.363	-0.312	-0.196
CP11	.399	-0.665	-0.628	-0.681	-0.570	-0.543	-0.496	-0.368	-0.302	-0.258	-0.245	-0.135
CP12	.501	-0.540	-0.517	-0.446	-0.428	-0.324	-0.248	-0.218	-0.179	-0.202	-0.153	-0.094
CP13	.600	-0.359	-0.387	-0.280	-0.197	-0.172	-0.124	-0.104	-0.066	-0.091	-0.082	-0.016
CP14	.701	-0.113	-0.105	-0.093	-0.016	0.038	0.044	0.072	0.087	0.077	0.066	0.094
CP15	.800	-0.101	-0.086	-0.078	0.012	0.032	0.051	0.075	0.062	0.049	0.015	0.041
CP16	.900	-0.178	-0.134	-0.100	-0.097	-0.070	-0.033	-0.056	-0.044	-0.044	-0.064	-0.091
CP17	.969	-0.079	-0.049	-0.086	-0.065	-0.026	-0.050	-0.037	0.001	-0.020	-0.034	-0.035

α		-2.206	-1.644	-1.129	-0.597	-0.071	0.451	0.988	1.514	2.026	2.543	3.076
CN		-0.140	-0.079	-0.006	0.061	0.126	0.201	0.269	0.346	0.419	0.490	0.565
CM		-0.022	-0.017	-0.016	-0.013	-0.008	-0.008	-0.005	-0.005	-0.001	0.000	0.000
CP 1	.010	-2.517	-2.006	-1.563	-1.072	-0.682	-0.105	0.334	0.759	1.226	1.602	1.985
CP 2	.020	-2.196	-1.604	-1.092	-0.777	-0.305	-0.058	0.272	0.616	0.962	1.304	1.617
CP 3	.030	-1.964	-0.991	-0.701	-0.303	-0.073	0.217	0.576	0.822	1.150	1.458	1.742
CP 4	.049	-0.753	-0.545	-0.287	-0.073	0.204	0.442	0.708	0.989	1.259	1.601	1.897
CP 5	.074	-0.399	-0.197	0.012	0.227	0.417	0.633	0.856	1.084	1.331	1.608	1.899
CP 6	.099	-0.268	-0.092	0.080	0.272	0.426	0.630	0.875	1.025	1.221	1.460	1.723
CP 7	.149	-0.240	-0.120	0.003	0.134	0.271	0.410	0.559	0.733	0.899	0.928	0.925
CP 8	.200	-0.168	-0.072	0.025	0.144	0.255	0.370	0.468	0.557	0.701	0.806	0.935
CP 9	.250	-0.142	-0.064	0.031	0.118	0.219	0.292	0.404	0.484	0.592	0.691	0.787
CP10	.300	-0.115	-0.035	0.036	0.117	0.203	0.272	0.352	0.440	0.510	0.602	0.666
CP11	.399	-0.074	-0.021	0.047	0.102	0.170	0.243	0.287	0.357	0.414	0.491	0.568
CP12	.501	-0.058	-0.009	0.059	0.100	0.129	0.197	0.226	0.267	0.329	0.367	0.416
CP13	.600	0.021	0.029	0.073	0.107	0.142	0.166	0.194	0.231	0.273	0.301	0.343
CP14	.701	0.124	0.154	0.178	0.188	0.195	0.228	0.261	0.289	0.286	0.334	0.344
CP15	.800	0.050	0.062	0.054	0.071	0.059	0.069	0.083	0.097	0.108	0.120	0.153
CP16	.900	-0.088	-0.150	-0.125	-0.147	-0.144	-0.139	-0.136	-0.116	-0.130	-0.121	-0.117
CP17	.969	-0.039	-0.037	-0.062	-0.059	-0.086	-0.069	-0.095	-0.074	-0.089	-0.098	-0.094

M = 0.597 Rn = 3.1×10^6

SOLID FLOOR AND CEILING

ALPHA		3.600	4.131	4.662	5.172	5.687	6.215	6.740	7.235	7.798	8.301	8.818
CN		0.622	0.694	0.772	0.835	0.872	0.908	0.928	0.914	0.955	0.947	0.937
CM		0.004	0.008	0.013	0.018	0.025	0.026	0.025	0.026	0.022	0.006	-0.006
CCP 1	.010	2.139	2.407	2.944	3.277	3.472	3.715	3.648	3.225	3.527	3.921	3.771
CCP 2	.020	1.903	2.165	2.405	2.830	3.050	3.242	3.397	3.462	3.567	3.539	3.454
CCP 3	.033	1.985	2.147	2.372	2.749	3.014	3.211	3.344	3.400	3.448	3.391	3.175
CCP 4	.049	2.140	2.352	2.518	2.659	2.924	3.083	3.153	3.085	3.397	3.013	2.733
CCP 5	.074	2.228	2.485	2.654	2.758	2.919	2.929	2.959	2.877	2.872	2.617	2.376
CCP 6	.099	2.019	2.293	2.519	2.656	2.729	2.804	2.729	2.576	2.570	2.326	2.226
CCP 7	.149	0.979	1.389	2.011	2.259	2.176	2.257	1.992	2.003	2.131	1.926	1.912
CCP 8	.200	0.996	1.032	1.118	1.492	1.658	1.780	1.798	1.817	1.894	1.767	1.688
CCP 9	.250	0.850	0.909	0.942	0.997	1.194	1.276	1.488	1.481	1.587	1.456	1.372
CCP10	.300	0.737	0.782	0.827	0.842	0.922	1.016	1.124	1.182	1.231	1.198	1.242
CCP11	.305	0.546	0.657	0.690	0.719	0.711	0.757	0.826	0.817	0.891	0.922	0.967
CCP12	.501	0.449	0.489	0.503	0.541	0.530	0.556	0.574	0.572	0.613	0.675	0.674
CCP13	.600	0.367	0.397	0.413	0.417	0.406	0.412	0.427	0.368	0.370	0.473	0.502
CCP14	.701	0.363	0.359	0.383	0.370	0.345	0.305	0.283	0.285	0.290	0.352	0.400
CCP15	.800	0.146	0.149	0.156	0.160	0.137	0.136	0.124	0.141	0.163	0.181	0.184
CCP16	.900	-0.121	-0.113	-0.100	-0.091	-0.089	-0.065	-0.052	-0.088	-0.054	-0.090	0.018
CCP17	.965	-0.099	-0.096	-0.109	-0.082	-0.092	-0.095	-0.100	-0.133	-0.085	-0.095	-0.035

ALPHA		9.363	10.402	10.906	11.442	11.936	12.492	12.981	13.511	14.035	15.420
CN		0.936	0.927	0.912	0.849	0.848	0.867	0.895	0.920	0.924	0.991
CM		-0.029	-0.063	-0.068	-0.066	-0.061	-0.067	-0.070	-0.072	-0.070	-0.082
CCP 1	.010	3.536	2.403	2.177	1.972	1.995	1.993	2.034	2.025	2.047	1.997
CCP 2	.020	3.014	2.174	1.991	1.712	1.694	1.574	1.713	1.727	1.726	1.809
CCP 3	.030	2.926	2.237	1.870	1.772	1.709	1.718	1.742	1.755	1.769	1.796
CCP 4	.049	2.642	2.461	2.794	2.661	2.605	2.605	2.563	2.646	2.652	2.451
CCP 5	.074	2.397	2.493	2.459	2.467	2.405	2.438	2.417	2.476	2.504	2.407
CCP 6	.099	2.208	2.282	2.248	2.213	2.237	2.264	2.262	2.277	2.462	2.448
CCP 7	.149	1.677	1.479	1.393	1.259	1.339	1.386	1.570	1.601	1.671	1.894
CCP 8	.200	1.444	1.156	1.169	1.057	1.008	1.070	1.093	1.162	1.139	1.362
CCP 9	.250	1.274	1.075	1.062	1.024	0.990	1.032	1.341	1.075	1.079	1.298
CCP10	.300	1.127	1.028	0.983	0.870	0.889	0.925	0.978	0.962	0.990	1.008
CCP11	.305	1.065	0.980	0.926	0.934	0.850	0.857	0.894	0.907	0.917	1.044
CCP12	.501	0.795	0.824	0.876	0.734	0.731	0.749	0.793	0.783	0.818	0.894
CCP13	.600	0.663	0.751	0.661	0.679	0.658	0.670	0.721	0.733	0.706	0.787
CCP14	.701	0.612	0.633	0.636	0.638	0.641	0.635	0.654	0.682	0.663	0.720
CCP15	.800	0.379	0.482	0.550	0.556	0.530	0.543	0.564	0.544	0.557	0.562
CCP16	.900	0.055	0.133	0.140	0.171	0.147	0.196	0.152	0.193	0.170	0.229
CCP17	.965	-0.087	-0.128	-0.067	-0.049	-0.052	-0.059	-0.044	-0.001	-0.017	-0.012

AIRFOIL NLR 7223-62   STEADY FORCES AND MOMENTS

M = 0.597 Rn = 6.2 x

SOLID FLOOR AND CEILING

ALPHA		-9.491	-9.090	-8.374	-7.767	-7.170	-6.568	-5.963	-5.377	-4.776	-4.176	-3.539
CN		-0.747	-0.675	-0.656	-0.611	-0.582	-0.514	-0.482	-0.449	-0.380	-0.337	-0.279
CM		0.707	-0.004	-0.018	-0.074	-0.033	-0.046	-0.044	-0.041	-0.038	-0.032	-0.029
CP 1	.010	-3.175	-3.249	-3.295	-3.406	-3.700	-3.598	-3.029	-2.892	-3.168	-3.362	-3.323
CP 2	.020	-2.511	-2.535	-2.411	-2.322	-2.051	-2.200	-2.570	-2.633	-2.858	-2.988	-2.898
CP 3	.030	-2.702	-2.732	-2.519	-2.373	-1.887	-2.058	-2.330	-2.447	-2.611	-2.535	-2.269
CP 4	.049	-2.491	-2.083	-2.387	-2.542	-2.455	-2.478	-2.285	-1.979	-2.111	-1.889	-1.749
CP 5	.074	-2.026	-1.833	-2.072	-2.016	-2.078	-2.015	-1.896	-1.689	-1.566	-1.115	-0.895
CP 6	.099	-1.800	-1.628	-1.768	-1.689	-1.588	-1.748	-1.614	-1.480	-1.132	-0.801	-0.592
CP 7	.149	-1.362	-1.465	-1.360	-1.358	-1.402	-1.300	-1.216	-1.117	-0.714	-0.556	-0.465
CP 8	.200	-1.273	-1.247	-1.156	-1.290	-1.095	-0.940	-0.904	-0.880	-0.584	-0.472	-0.405
CP 9	.250	-1.205	-1.128	-1.143	-1.038	-0.827	-0.759	-0.669	-0.598	-0.444	-0.403	-0.322
CP10	.300	-0.947	-0.843	-0.836	-0.793	-0.697	-0.582	-0.450	-0.440	-0.342	-0.286	-0.239
CP11	.399	-0.671	-0.579	-0.653	-0.545	-0.548	-0.382	-0.347	-0.301	-0.258	-0.214	-0.178
CP12	.501	-0.507	-0.416	-0.435	-0.315	-0.394	-0.246	-0.253	-0.198	-0.190	-0.165	-0.144
CP13	.600	-0.422	-0.328	-0.264	-0.165	-0.295	-0.099	-0.104	-0.092	-0.079	-0.082	-0.061
CP14	.701	-0.234	-0.174	-0.060	0.037	0.068	0.079	0.040	0.068	0.057	0.076	0.081
CP15	.800	-0.156	-0.132	-0.007	-0.005	0.043	0.061	0.082	0.031	0.045	0.023	0.033
CP16	.900	-0.153	-0.081	-0.050	-0.020	-0.047	-0.032	-0.032	-0.044	-0.075	-0.088	-0.078
CP17	.969	-0.021	-0.049	-0.062	-0.056	-0.018	-0.002	-0.015	0.003	-0.015	-0.028	-0.014

ALPHA		-2.976	-2.332	-1.729	-1.152	-0.540	0.103	0.678	1.288	1.911	2.471	3.763
CN		-0.216	-0.146	-0.079	-0.002	0.070	0.143	0.216	0.292	0.360	0.438	0.501
CM		-0.025	-0.021	-0.018	-0.017	-0.015	-0.014	-0.012	-0.011	-0.011	-0.009	-0.003
CP 1	.010	-3.149	-2.787	-2.245	-1.502	-1.104	-0.650	-0.197	0.185	0.625	1.023	1.794
CP 2	.020	-2.740	-1.853	-1.342	-1.066	-0.710	-0.390	-0.009	0.335	0.686	1.017	1.687
CP 3	.030	-1.674	-1.250	-1.035	-0.748	-0.444	-0.138	0.182	0.484	0.894	1.108	1.714
CP 4	.049	-0.966	-0.757	-0.531	-0.387	-0.026	0.220	0.495	0.765	1.045	1.337	1.561
CP 5	.074	-0.601	-0.392	-0.205	0.004	0.229	0.443	0.632	0.886	1.137	1.369	1.949
CP 6	.099	-0.464	-0.297	-0.174	0.057	0.254	0.451	0.628	0.874	1.030	1.255	1.765
CP 7	.149	-0.339	-0.222	-0.084	0.046	0.182	0.319	0.471	0.637	0.751	0.829	1.115
CP 8	.200	-0.301	-0.213	-0.005	0.021	0.135	0.248	0.330	0.480	0.593	0.601	0.927
CP 9	.250	-0.243	-0.155	-0.074	0.026	0.121	0.221	0.317	0.419	0.514	0.616	0.787
CP10	.300	-0.175	-0.121	-0.023	0.078	0.141	0.234	0.309	0.386	0.469	0.558	0.707
CP11	.399	-0.122	-0.061	-0.006	0.057	0.127	0.192	0.250	0.326	0.379	0.459	0.567
CP12	.501	-0.096	-0.051	-0.015	0.053	0.089	0.143	0.188	0.235	0.285	0.338	0.428
CP13	.600	-0.033	-0.004	0.024	0.066	0.119	0.247	0.190	0.217	0.270	0.247	0.279
CP14	.701	0.102	0.124	0.140	0.171	0.196	0.227	0.245	0.269	0.292	0.315	0.366
CP15	.800	0.042	0.051	0.050	0.071	0.070	0.088	0.118	0.117	0.134	0.136	0.164
CP16	.900	-0.103	-0.117	-0.113	-0.126	-0.118	-0.107	-0.132	-0.105	-0.092	-0.096	-0.094
CP17	.969	-0.037	-0.046	-0.041	-0.055	-0.055	-0.069	-0.072	-0.075	-0.065	-0.082	-0.092

M = 0.597 Rn = 6.2 x 10⁶   SOLID FLOOR AND CEILING

ALPHA		4.311	4.921	5.566	6.153	6.760	7.360	7.971	8.576	9.788	10.338	10.937
CN		0.655	0.722	0.807	0.867	0.922	0.925	0.948	0.953	0.965	0.936	0.965
CM		0.001	0.004	0.007	0.014	0.020	0.025	0.030	0.029	0.014	0.002	-0.005
CP 1	.010	2.183	2.546	2.968	3.240	3.426	3.500	3.633	3.607	3.802	3.793	3.766
CP 2	.020	1.988	2.248	2.530	2.977	3.222	3.325	3.437	3.557	3.678	3.635	3.692
CP 3	.030	1.947	2.136	2.351	2.785	3.014	3.132	3.267	3.372	3.446	3.176	3.316
CP 4	.049	2.220	2.392	2.512	2.770	3.007	3.110	3.253	3.310	3.195	2.811	2.828
CP 5	.074	2.270	2.490	2.648	2.784	2.980	3.103	3.155	3.077	2.683	2.452	2.570
CP 6	.099	2.143	2.467	2.740	2.866	3.000	3.013	2.976	2.732	2.434	2.293	2.329
CP 7	.149	1.317	1.447	2.133	2.486	2.626	2.434	2.703	2.353	2.099	2.033	1.990
CP 8	.200	0.992	1.014	1.020	1.335	1.552	1.744	1.975	1.945	1.852	1.649	1.588
CP 9	.250	0.877	0.921	0.936	0.974	1.244	1.236	1.400	1.493	1.514	1.370	1.535
CP10	.300	0.784	0.827	0.973	0.867	0.905	0.992	1.118	1.239	1.254	1.238	1.317
CP11	.395	0.639	0.674	0.720	0.745	0.750	0.743	0.797	0.870	1.002	0.915	0.992
CP12	.501	0.466	0.503	0.549	0.552	0.569	0.540	0.554	0.542	0.617	0.706	0.692
CP13	.600	0.376	0.415	0.455	0.447	0.457	0.433	0.437	0.380	0.440	0.445	0.505
CP14	.701	0.345	0.389	0.424	0.430	0.409	0.374	0.317	0.207	0.358	0.361	0.364
CP15	.800	0.176	0.163	0.188	0.198	0.191	0.171	0.142	0.134	0.150	0.197	0.235
CP16	.900	-0.095	-0.078	-0.092	-0.067	-0.086	-0.091	-0.106	-0.096	-0.017	0.005	0.020
CP17	.969	-0.130	-0.097	-0.078	-0.091	-0.091	-0.073	-0.101	-0.091	-0.078	0.077	-0.050

ALPHA		11.607	12.130	12.717	13.413	14.581	15.198	15.760	16.078
CN		0.947	0.937	0.975	0.970	0.896	0.955	0.918	0.964
CM		-0.051	-0.047	-0.043	-0.171	-0.077	-0.084	-0.075	-0.082
CP 1	.010	2.646	2.373	2.120	1.964	1.832	1.832	1.817	1.704
CP 2	.020	2.480	2.934	2.041	1.928	1.721	1.748	1.733	1.787
CP 3	.030	2.496	2.701	2.145	1.995	1.747	1.750	1.730	1.730
CP 4	.049	3.173	2.681	2.870	2.763	2.630	2.614	2.630	2.683
CP 5	.074	2.657	2.392	2.571	2.554	2.424	2.510	2.472	2.543
CP 6	.099	2.300	2.011	2.335	2.316	2.192	2.275	2.240	2.262
CP 7	.149	1.566	1.521	1.420	1.370	1.476	1.440	1.640	1.770
CP 8	.200	1.255	1.302	1.149	1.385	1.350	1.350	1.083	1.187
CP 9	.250	1.243	1.316	1.119	1.063	1.017	1.073	1.055	1.113
CP10	.300	1.134	1.191	1.007	0.997	0.943	1.030	0.985	1.040
CP11	.395	1.004	1.050	0.975	0.949	0.914	1.010	0.913	0.954
CP12	.501	0.811	0.866	0.837	0.841	0.787	0.847	0.874	0.848
CP13	.600	0.705	0.608	0.753	0.740	0.737	0.782	0.737	0.730
CP14	.701	0.575	0.517	0.620	0.717	0.680	0.710	0.687	0.714
CP15	.800	0.420	0.393	0.450	0.537	0.563	0.506	0.526	0.476
CP16	.900	0.136	0.125	0.165	0.147	0.312	0.218	0.215	0.230
CP17	.969	-0.031	-0.008	0.033	0.031	-0.023	0.031	-0.010	0.001

AIRFOIL NLR 7223-62   STEADY FORCES AND MOMENTS

M = 0.609   Rn = 9.1 x 10⁶

SOLID FLOOR AND CEILING

ALPHA		-8.219	-7.709	-7.234	-6.686	-6.201	-5.692	-5.147	-4.626	-4.113	-3.579	-3.096
CN		-0.643	-0.655	-0.632	-0.577	-0.577	-0.523	-0.466	-0.442	-0.385	-0.340	-0.283
CM		0.004	-0.020	-0.031	-0.041	-0.046	-0.045	-0.049	-0.044	-0.038	-0.034	-0.029
DCP 1	.010	-2.995	-2.931	-3.118	-3.233	-3.346	-3.440	-3.242	-3.074	-3.213	-3.422	-3.420
DCP 2	.020	-2.692	-2.657	-2.575	-3.096	-3.044	-2.905	-2.900	-2.731	-2.913	-2.936	-2.870
DCP 3	.030	-2.442	-2.634	-3.036	-2.687	-2.934	-2.751	-2.320	-2.635	-2.640	-2.531	-2.265
DCP 4	.049	-1.876	-2.485	-2.285	-2.154	-2.426	-2.493	-2.342	-2.275	-2.150	-1.842	-1.368
DCP 5	.074	-1.887	-1.911	-1.685	-1.735	-2.025	-1.555	-1.868	-1.795	-1.448	-1.114	-0.796
DCP 6	.099	-1.425	-1.666	-1.735	-1.741	-1.807	-1.677	-1.641	-1.441	-1.092	-0.794	-0.602
DCP 7	.149	-1.020	-1.258	-1.474	-1.519	-1.376	-1.178	-1.116	-1.023	-0.733	-0.591	-0.484
DCP 8	.200	-0.990	-1.242	-1.191	-1.076	-1.064	-0.927	-0.802	-0.684	-0.560	-0.490	-0.409
DCP 9	.250	-0.976	-1.116	-1.018	-0.941	-0.922	-0.811	-0.639	-0.563	-0.477	-0.405	-0.332
DCP10	.300	-0.850	-1.025	-0.805	-0.710	-0.647	-0.636	-0.489	-0.430	-0.345	-0.305	-0.250
DCP11	.359	-0.778	-0.584	-0.547	-0.454	-0.458	-0.336	-0.295	-0.297	-0.264	-0.211	-0.184
DCP12	.501	-0.524	-0.357	-0.345	-0.319	-0.282	-0.259	-0.218	-0.212	-0.200	-0.168	-0.139
DCP13	.600	-0.323	-0.219	-0.194	-0.165	-0.174	-0.077	-0.360	-0.067	-0.074	-0.084	-0.053
DCP14	.701	-0.068	-0.056	-0.058	0.057	0.076	0.071	0.082	0.075	0.065	0.071	0.092
DCP15	.800	-0.066	-0.025	0.037	0.037	0.045	0.055	0.051	0.042	0.035	0.037	0.037
DCP16	.900	-0.161	-0.094	-0.081	-0.015	-0.025	-0.031	-0.022	-0.052	-0.063	-0.076	-0.093
DCP17	.969	-0.083	-0.024	-0.015	-0.014	0.007	-0.001	0.001	-0.009	-0.022	-0.019	-0.036

ALPHA		-2.571	-2.027	-1.490	-0.964	-0.444	0.079	0.572	1.135	1.651	2.181	2.693
CN		-0.215	-0.153	-0.079	-0.005	0.069	0.140	0.218	0.292	0.368	0.448	0.523
CM		-0.026	-0.020	-0.019	-0.018	-0.016	-0.014	-0.014	-0.012	-0.011	-0.010	-0.008
DCP 1	.010	-3.367	-2.945	-2.225	-1.531	-1.010	-0.545	-0.086	0.327	0.760	1.182	1.600
DCP 2	.020	-2.698	-1.654	-1.480	-1.118	-0.760	-0.395	-0.035	0.316	0.682	1.030	1.378
DCP 3	.030	-1.605	-1.273	-1.026	-0.716	-0.417	-0.114	0.196	0.519	0.835	1.155	1.467
DCP 4	.049	-0.563	-0.783	-0.548	-0.308	-0.045	0.204	0.466	0.740	1.031	1.333	1.652
DCP 5	.074	-0.611	-0.416	-0.212	-0.008	0.210	0.433	0.669	0.887	1.130	1.376	1.652
DCP 6	.099	-0.449	-0.289	-0.113	0.061	0.260	0.443	0.634	0.824	1.034	1.248	1.474
DCP 7	.149	-0.367	-0.247	-0.103	0.013	0.157	0.290	0.429	0.579	0.718	0.860	1.005
DCP 8	.200	-0.321	-0.205	-0.106	0.009	0.123	0.242	0.351	0.463	0.586	0.650	0.812
DCP 9	.250	-0.254	-0.169	-0.077	0.014	0.118	0.217	0.309	0.412	0.512	0.607	0.732
DCP10	.300	-0.180	-0.111	-0.024	0.053	0.125	0.210	0.298	0.382	0.460	0.556	0.621
DCP11	.399	-0.119	-0.066	0.005	0.064	0.126	0.190	0.268	0.331	0.392	0.460	0.516
DCP12	.501	-0.097	-0.070	-0.010	0.044	0.090	0.140	0.186	0.241	0.291	0.347	0.392
DCP13	.600	-0.035	0.001	0.043	0.077	0.120	0.141	0.187	0.222	0.260	0.301	0.338
DCP14	.701	0.111	0.121	0.146	0.171	0.202	0.218	0.248	0.272	0.301	0.325	0.349
DCP15	.800	0.035	0.037	0.051	0.058	0.078	0.089	0.112	0.114	0.130	0.157	0.165
DCP16	.900	-0.103	-0.128	-0.121	-0.096	-0.107	-0.104	-0.098	-0.090	-0.093	-0.084	-0.078
DCP17	.969	-0.025	-0.037	-0.047	-0.042	-0.056	-0.061	-0.066	-0.067	-0.070	-0.076	-0.074

M = 0.609   Rn = 9.1 x 10^6

ALPHA		3.233	3.897	4.273	4.765	5.317	5.836	6.363	6.842	7.372	7.909	8.427
CN		0.600	0.684	0.733	0.804	0.886	0.924	0.954	0.974	0.982	1.000	0.998
CM		-0.004	0.001	0.001	0.036	0.013	0.021	0.025	0.028	0.032	0.010	-0.003
DCP 1	.010	2.023	2.482	2.783	3.225	3.481	3.635	3.778	3.653	3.655	3.534	3.562
DCP 2	.023	1.709	2.065	2.266	2.615	3.036	3.237	3.395	3.490	3.614	3.601	3.647
DCP 3	.030	1.763	2.063	2.214	2.462	2.915	3.124	3.294	3.385	3.498	3.503	3.572
DCP 4	.049	1.568	2.280	2.430	2.505	2.831	3.023	3.185	3.275	3.399	3.410	3.470
DCP 5	.074	1.942	2.372	2.535	2.658	2.845	3.035	3.151	3.246	3.323	3.276	3.176
DCP 6	.099	1.777	2.286	2.587	2.751	2.910	3.062	3.126	3.153	3.091	2.880	2.650
DCP 7	.149	1.125	1.167	1.237	1.822	2.561	2.633	2.536	2.263	2.273	1.779	1.635
DCP 8	.200	0.910	1.020	1.032	1.125	1.165	1.405	1.564	1.755	1.838	1.501	1.455
DCP 9	.250	0.798	0.894	0.937	0.954	0.995	1.127	1.248	1.436	1.401	1.485	1.456
DCP10	.300	0.735	0.785	0.832	0.866	0.862	0.844	0.995	1.109	1.161	1.361	1.246
DCP11	.399	0.590	0.651	0.695	0.732	0.762	0.773	0.783	0.801	0.837	0.992	1.027
DCP12	.501	0.429	0.478	0.518	0.547	0.575	0.571	0.566	0.573	0.582	0.664	0.729
DCP13	.600	0.364	0.414	0.431	0.444	0.465	0.464	0.448	0.439	0.394	0.514	0.557
DCP14	.701	0.373	0.390	0.404	0.404	0.415	0.395	0.375	0.353	0.323	0.356	0.386
DCP15	.800	0.177	0.179	0.185	0.200	0.199	0.191	0.172	0.165	0.140	0.157	0.192
DCP16	.900	-0.076	-0.085	-0.078	-0.059	-0.063	-0.075	-0.071	-0.092	-0.066	0.002	0.068
DCP17	.969	-0.085	-0.092	-0.082	-0.091	-0.080	-0.090	-0.084	-0.079	-0.105	-0.046	-0.035

ALPHA		8.949	9.469	9.972	10.465	10.989	11.547	12.041	12.587	13.091	13.586	14.116
CN		0.991	0.943	0.985	0.994	0.932	0.946	0.885	0.900	0.972	0.981	1.056
CM		-0.015	-0.007	-0.037	-0.026	-0.032	-0.036	-0.048	-0.056	-0.055	-0.071	-0.054
DCP 1	.010	3.542	3.544	3.714	3.684	4.077	3.582	4.071	3.567	3.370	3.622	3.270
DCP 2	.023	3.668	3.683	3.674	3.641	3.654	3.085	3.636	3.470	2.734	3.124	2.578
DCP 3	.030	3.624	3.632	3.715	3.665	3.517	2.940	3.231	3.059	3.047	2.937	2.563
DCP 4	.049	3.514	3.176	3.435	3.091	2.442	2.486	2.207	2.398	2.155	2.654	2.740
DCP 5	.074	3.057	2.544	2.743	2.605	1.730	2.081	1.572	1.575	1.941	1.710	2.442
DCP 6	.099	2.500	2.214	2.386	2.395	1.634	1.975	1.439	1.501	1.893	1.661	2.349
DCP 7	.149	1.463	1.745	1.362	1.601	1.533	1.735	1.298	1.303	1.705	1.422	1.896
DCP 8	.200	1.372	1.472	1.215	1.380	1.401	1.440	1.289	1.286	1.560	1.430	1.638
DCP 9	.250	1.335	1.332	1.198	1.329	1.226	1.297	1.174	1.237	1.483	1.298	1.501
DCP10	.300	1.200	1.152	1.128	1.241	1.136	1.254	1.091	1.072	1.278	1.240	1.396
DCP11	.399	0.977	0.957	0.955	1.055	0.979	1.036	1.051	0.972	1.066	1.131	1.155
DCP12	.501	0.765	0.681	0.813	0.810	0.814	0.776	0.847	0.828	0.775	0.515	0.834
DCP13	.600	0.630	0.534	0.665	0.605	0.591	0.650	0.646	0.735	0.697	0.768	0.735
DCP14	.701	0.469	0.378	0.492	0.502	0.462	0.494	0.499	0.582	0.586	0.654	0.586
DCP15	.800	0.276	0.248	0.386	0.312	0.315	0.322	0.361	0.374	0.418	0.435	0.434
DCP16	.900	0.074	0.044	0.171	0.094	0.085	0.086	0.115	0.116	0.135	0.179	0.154
DCP17	.969	-0.028	-0.035	0.045	-0.049	-0.065	-0.050	-0.042	0.024	-0.010	0.047	-0.016

AIRFOIL NLR 7223-62   STEADY FORCES AND MOMENTS

M = 0.609   Rn = 9.1 x 10⁶   SOLID FLOOR AND CEILING

ALPHA		14.666	15.169	15.649	16.176	16.720
CN		1.061	1.C81	1.063	1.C83	1.C86
CM		-0.07C	-).C78	-).C83	-).087	-).C90
DCP 1	.013	3.492	3.375	3.617	3.125	3.249
DCP 2	.020	2.630	3.030	3.340	2.411	2.935
DCP 3	.030	2.554	2.593	1.563	3.028	3.114
DCP 4	.049	2.377	2.563	2.484	2.530	2.426
DCP 5	.074	2.173	2.242	2.185	2.190	2.189
DCP 6	.099	2.098	2.138	2.211	2.178	2.002
DCP 7	.149	1.833	1.855	1.972	1.855	1.758
DCP 8	.200	1.644	1.646	1.803	1.604	1.623
DCP 9	.253	1.480	1.446	1.194	1.390	1.541
DCP10	.303	1.334	1.301	1.C85	1.292	1.370
DCP11	.399	1.188	1.158	1.C75	1.122	1.045
DCP12	.531	).964	1.020	0.927	1.032	0.525
DCP13	.600	0.773	).845	0.824	).857	).825
DCP14	.701	0.664	0.672	0.757	0.746	0.757
DCP15	.803	).482	0.495	0.605	).562	0.601
DCP16	.900	0.179	).224	).235	0.254	0.309
DCP17	.969	).024	0.022	).026	).017	0.C61

M = 0.705   Rn = 10.0 x 10⁶

ALPHA		-9.601	-8.983	-9.442	-7.961	-7.245	-6.641	-6.104	-5.490	-4.832	-4.278	-3.652
CN		-0.871	-0.892	-0.702	-0.762	-0.734	-0.684	-0.645	-0.578	-0.534	-0.469	-0.357
CM		0.234	0.026	-0.025	0.011	0.004	-0.028	-0.046	-0.053	-0.051	-0.045	-0.038
CP 1	.010	-1.917	-2.010	-3.136	-3.137	-3.257	-3.215	-3.271	-3.100	-3.154	-3.058	-2.957
CP 2	.020	-2.798	-2.846	-2.879	-2.932	-2.977	-3.102	-3.120	-3.051	-3.014	-2.897	-2.772
CP 3	.030	-2.530	-2.489	-2.671	-2.790	-2.204	-2.827	-2.801	-2.716	-2.786	-2.672	-2.537
CP 4	.049	-2.190	-2.255	-2.346	-2.730	-2.681	-2.622	-2.595	-2.505	-2.470	-2.289	-2.122
CP 5	.074	-1.747	-1.836	-1.867	-2.438	-2.378	-2.323	-2.288	-2.189	-2.100	-1.967	-1.784
CP 6	.099	-1.656	-1.640	-1.708	-2.300	-2.188	-2.090	-2.100	-2.071	-1.935	-1.793	-1.607
CP 7	.149	-1.410	-1.417	-1.444	-1.704	-1.885	-1.475	-1.333	-1.763	-1.750	-1.612	-0.385
CP 8	.200	-0.707	-0.717	-1.118	-1.005	-1.016	-0.872	-1.100	-1.021	-1.276	-0.631	-0.324
CP 9	.250	-0.680	-0.733	-1.112	-0.909	-0.710	-0.962	-1.097	-0.745	-0.691	-0.337	-0.298
CP 10	.300	-0.618	-0.709	-0.960	-0.777	-0.613	-0.881	-0.917	-0.494	-0.346	-0.243	-0.242
CP 11	.399	-0.616	-0.610	-0.790	-0.551	-0.512	-0.491	-0.622	-0.477	-0.212	-0.221	-0.194
CP 12	.501	-0.586	-0.570	-0.467	-0.519	-0.519	-0.444	-0.385	-0.318	-0.179	-0.190	-0.158
CP 13	.600	-0.426	-0.378	-0.343	-0.444	-0.464	-0.244	-0.136	-0.111	-0.102	-0.099	-0.072
CP 14	.701	-0.225	-0.242	-0.134	-0.182	-0.194	-0.231	0.087	0.101	0.076	0.077	0.094
CP 15	.800	-0.239	-0.187	-0.068	-0.252	-0.196	0.011	0.097	0.098	0.029	0.018	0.021
CP 16	.900	-0.342	-0.353	-0.135	-0.246	-0.201	-0.270	-0.043	-0.038	-0.111	-0.133	-0.125
CP 17	.969	-0.144	-0.118	-0.020	-0.122	-0.090	-0.068	-0.004	-0.024	-0.031	-0.038	-0.026

ALPHA		-3.037	-2.465	-1.858	-1.188	-0.584	-0.021	0.604	1.257	1.810	2.401	3.066
CN		-0.270	-0.183	-0.104	-0.024	0.059	0.143	0.230	0.302	0.395	0.492	0.580
CM		-0.233	-0.030	-0.025	-0.021	-0.019	-0.016	-0.015	-0.013	-0.010	-0.005	-0.004
CP 1	.010	-2.814	-2.586	-2.360	-1.998	-1.270	-0.754	-0.329	0.081	0.428	0.769	1.087
CP 2	.020	-2.598	-2.367	-2.058	-1.547	-0.940	-0.537	-0.175	0.158	0.470	0.761	1.072
CP 3	.030	-2.339	-2.083	-1.680	-0.873	-0.583	-0.257	0.055	0.351	0.615	0.858	1.083
CP 4	.049	-1.913	-1.593	-0.576	-0.419	-0.142	0.136	0.416	0.690	0.858	1.159	1.083
CP 5	.074	-1.482	-0.318	-0.244	-0.052	0.186	0.418	0.729	0.942	1.133	1.332	1.356
CP 6	.099	-0.468	-0.249	-0.164	0.017	0.239	0.472	0.745	1.066	1.272	1.450	1.533
CP 7	.149	-0.300	-0.265	-0.139	0.005	0.150	0.327	0.513	0.489	1.206	1.463	1.633
CP 8	.200	-0.314	-0.249	-0.137	-0.007	0.120	0.248	0.388	0.518	0.510	1.360	1.625
CP 9	.250	-0.173	-0.208	-0.106	0.001	0.108	0.223	0.335	0.450	0.506	0.515	1.575
CP 10	.300	-0.207	-0.136	-0.050	0.024	0.130	0.226	0.320	0.418	0.487	0.504	1.107
CP 11	.399	-0.155	-0.090	-0.030	0.048	0.125	0.199	0.277	0.346	0.408	0.457	0.546
CP 12	.501	-0.112	-0.068	-0.017	0.032	0.087	0.148	0.203	0.259	0.314	0.349	0.464
CP 13	.600	-0.033	0.009	0.030	0.077	0.114	0.158	0.202	0.233	0.280	0.310	0.333
CP 14	.701	0.124	0.156	0.172	0.191	0.219	0.245	0.277	0.297	0.324	0.336	0.359
CP 15	.800	0.040	0.052	0.059	0.072	0.081	0.094	0.106	0.118	0.128	0.142	0.157
CP 16	.900	-0.110	-0.110	-0.118	-0.129	-0.121	-0.133	-0.131	-0.128	-0.122	-0.122	-0.106
CP 17	.969	-0.025	-0.021	-0.025	-0.039	-0.051	-0.057	-0.061	-0.070	-0.071	-0.082	-0.073

AIRFOIL NLR 7223-62 STEADY FORCES AND MOMENTS

M = 0.705   Rn = 10.0 x 10⁶

SOLID FLOOR AND CEILING

ALPHA		3.609	4.231	4.871	5.490	6.061	6.648	7.290	7.854	8.447	9.099	9.720
CN		0.673	0.782	0.835	0.825	0.848	0.867	0.893	0.921	0.930	0.891	0.875
CM		-0.001	-0.001	0.002	0.008	0.007	0.002	-0.001	-0.005	-0.006	-0.027	-0.035
CP 1	.010	1.374	1.614	1.836	1.598	2.111	2.260	2.381	2.464	2.575	2.647	2.680
CP 2	.020	1.252	1.453	1.611	1.723	1.833	1.970	2.131	2.231	2.367	2.457	2.404
CP 3	.030	1.277	1.424	1.556	1.660	1.740	1.587	2.030	2.146	2.260	2.357	2.401
CP 4	.049	1.569	1.668	1.773	1.854	1.902	1.966	2.076	2.174	2.270	2.345	2.379
CP 5	.074	1.692	1.805	1.925	1.999	2.034	2.089	2.165	2.234	2.329	2.396	2.422
CP 6	.099	1.707	1.902	2.008	2.077	2.115	2.157	2.221	2.279	2.355	2.410	2.411
CP 7	.149	1.776	1.886	1.981	2.042	2.086	2.131	2.175	2.218	2.271	2.119	1.575
CP 8	.200	1.719	1.824	1.919	1.985	2.021	2.069	2.118	2.119	1.968	1.187	1.053
CP 9	.250	1.666	1.776	1.875	1.936	1.827	1.696	1.570	1.544	1.387	1.143	0.973
CP 10	.300	0.902	1.668	1.686	1.195	1.193	1.199	1.243	1.248	1.270	0.992	0.932
CP 11	.399	0.439	0.730	0.978	0.965	0.959	1.000	0.952	0.998	1.048	0.946	0.916
CP 12	.501	0.372	0.343	0.510	0.630	0.617	0.661	0.718	0.738	0.792	0.752	0.686
CP 13	.600	0.349	0.315	0.264	0.308	0.439	0.450	0.503	0.535	0.485	0.608	0.648
CP 14	.701	0.363	0.347	0.286	0.212	0.240	0.270	0.303	0.321	0.318	0.422	0.473
CP 15	.800	0.165	0.159	0.139	0.095	0.112	0.097	0.122	0.121	0.167	0.271	0.327
CP 16	.900	-0.099	-0.106	-0.114	-0.126	-0.114	-0.106	-0.118	-0.070	-0.047	0.060	0.101
CP 17	.969	-0.070	-0.069	-0.089	-0.079	-0.076	-0.091	-0.060	-0.049	-0.082	-0.001	0.007

ALPHA		10.290	10.818	11.511	12.116	12.619	13.264	13.880	14.469	15.090	15.656	17.507
CN		0.913	0.931	0.968	0.929	0.945	0.970	0.990	1.003	1.036	1.048	1.097
CM		-0.036	-0.044	-0.039	-0.049	-0.052	-0.054	-0.057	-0.064	-0.070	-0.073	-0.109
CP 1	.010	2.770	2.848	2.920	2.929	2.998	3.073	3.078	3.141	3.199	3.226	2.702
CP 2	.020	2.600	2.692	2.787	2.783	2.867	2.954	2.980	3.041	3.116	3.173	2.564
CP 3	.030	2.591	2.578	2.660	2.679	2.755	2.843	2.876	2.942	2.994	3.006	2.839
CP 4	.049	2.472	2.543	2.541	2.636	2.709	2.753	2.776	2.767	2.769	2.709	1.891
CP 5	.074	2.408	2.561	2.346	2.607	2.622	2.647	2.661	2.843	2.600	2.529	1.863
CP 6	.099	2.473	2.468	2.192	2.461	2.477	2.456	2.487	2.444	2.400	2.324	1.754
CP 7	.149	2.056	1.990	1.912	1.907	1.971	2.080	2.133	2.171	2.176	2.195	1.671
CP 8	.200	1.135	1.133	1.634	1.055	1.038	1.056	1.100	1.042	1.137	1.147	1.743
CP 9	.250	1.071	1.042	1.436	1.014	0.976	1.051	1.054	1.076	1.099	1.148	1.723
CP 10	.300	0.990	0.982	1.229	0.906	0.934	0.958	1.000	0.969	1.035	1.092	1.463
CP 11	.399	0.930	0.950	0.951	0.905	0.907	0.868	0.914	0.938	0.977	1.024	1.256
CP 12	.501	0.745	0.771	0.782	0.713	0.684	0.842	0.769	0.743	0.908	0.893	0.931
CP 13	.600	0.638	0.595	0.588	0.671	0.700	0.705	0.677	0.731	0.908	0.781	0.854
CP 14	.701	0.503	0.574	0.564	0.620	0.559	0.591	0.643	0.691	0.718	0.778	0.839
CP 15	.800	0.330	0.381	0.377	0.431	0.555	0.455	0.565	0.569	0.573	0.562	0.664
CP 16	.900	0.120	0.184	0.066	0.176	0.208	0.225	0.233	0.270	0.268	0.270	0.347
CP 17	.969	-0.019	0.005	0.005	0.016	-0.019	0.055	-0.022	0.014	0.010	0.015	0.027

AIRFOIL NLR 7223-62   STEADY FORCES AND MOMENTS

M = 0.705   Rn = 10.0 x 10^6 SOLID FLOOR AND CEILING

ALPHA		18.140	18.696	19.276	19.903
CN		1.068	1.138	1.180	1.199
CM		-0.115	-0.123	-0.136	-0.146
CP 1	.010	2.527	2.659	2.721	2.643
CP 2	.020	2.467	2.607	2.634	2.635
CP 3	.030	2.855	2.692	2.630	2.598
CP 4	.049	1.774	1.785	1.924	1.865
CP 5	.074	1.661	1.774	1.741	1.789
CP 6	.099	1.591	1.659	1.699	1.707
CP 7	.145	1.490	1.577	1.642	1.596
CP 8	.200	1.696	1.734	1.759	1.767
CP 9	.250	1.774	1.787	1.818	1.802
CP10	.300	1.506	1.613	1.617	1.637
CP11	.399	1.101	1.361	1.427	1.404
CP12	.501	0.913	1.079	1.155	1.182
CP13	.600	0.883	1.003	1.050	1.056
CP14	.701	0.854	0.843	0.878	0.941
CP15	.800	0.717	0.699	0.706	0.754
CP16	.900	0.381	0.297	0.373	0.411
CP17	.969	-0.076	0.007	0.075	0.118

FORCED PITCHING OSCILLATION   AIRFOIL   NLF 1

TUNER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	22.09	0.195	0.210	2.61	0.0	0.05	12095.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.MAX	AERO DAMP	TDR	FST DAMP
75.2 (246.6)	14163 (295.8)	0.35E 07	-0.040	0.320	2.62	-0.00125	0.764	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		0.050	2.607	0	0.059	357	0.081	218	0.020	130	0.015	35	0.021	46	0.013	199	0.035	33	0.009	346
CN		0.139	0.169	359	0.009	282	0.008	167	0.005	232	0.002	229	0.004	68	0.002	161	0.017	10	0.002	74
CM		-0.024	0.010	300	0.001	46	0.001	331	0.002	50	0.002	4	0.001	268	0.001	79	0.005	202	0.000	355
CP 1	.010	-0.482	1.727	346	0.024	343	0.014	158	0.012	229	0.017	274	0.098	198	0.013	10	0.028	323	0.017	31
CP 2	.020	-0.311	0.909	349	0.032	292	0.007	259	0.006	355	0.001	155	0.010	67	0.001	284	0.027	345	0.013	36
CP 3	.030	0.046	0.741	349	0.020	293	0.004	197	0.002	126	0.001	236	0.014	38	0.004	62	0.014	332	0.007	44
CP 4	.040	0.308	0.633	349	0.010	310	0.012	146	0.007	308	0.006	197	0.005	207	0.004	67	0.017	343	0.002	13
CP 5	.074	0.126	0.502	350	0.010	306	0.009	167	0.004	222	0.005	308	0.004	357	0.004	67	0.011	349	0.010	48
CP 6	.099	0.350	0.426	352	0.004	8	0.011	146	0.003	329	0.008	241	0.005	0	0.004	101	0.009	139	0.014	17
CP 7	.149	0.241	0.323	354	0.009	284	0.007	158	0.005	301	0.007	232	0.007	55	0.004	754	0.018	0	0.005	5
CP 8	.200	0.231	0.242	350	0.004	1	0.018	154	0.007	91	0.010	331	0.004	47	0.004	61	0.014	332	0.009	20
CP 9	.250	0.205	0.223	347	0.090	46	0.012	149	0.014	254	0.005	306	0.006	355	0.005	48	0.323	357	0.001	251
CP10	.300	0.211	0.188	358	0.003	371	0.009	165	0.003	367	0.006	299	0.007	704	0.004	84	0.013	27	0.005	146
CP11	.355	0.204	0.150	9	0.011	284	0.011	278	0.001	77	0.004	115	0.004	49	0.011	177	0.019	0	0.007	223
CP12	.401	0.129	0.113	19	0.006	313	0.015	141	0.006	203	0.010	129	0.011	66	0.006	63	0.022	5	0.003	252
CP13	.600	0.192	0.702	14	0.008	317	0.012	183	0.017	302	0.011	284	0.012	66	0.007	121	0.027	18	0.010	359
CP14	.731	0.203	0.057	29	0.004	114	0.037	212	0.012	249	0.005	170	0.004	226	0.015	277	0.015	25	0.009	105
CP15	.800	0.150	0.739	38	0.012	203	0.001	77	0.006	192	0.003	152	0.013	156	0.006	255	0.022	78	0.005	156
CP16	.900	-0.053	0.015	85	0.005	799	0.010	110	0.008	334	0.008	62	0.010	47	0.004	350	0.010	18	0.004	56
CP17	.969	0.023	0.214	199	0.018	235	0.034	111	0.008	250	0.017	250	0.012	247	0.023	196	0.021	6	0.012	206

FORCED PITCHING OSCILLATION   AIRFOIL   NLF 1

TUNER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	22.09	0.182	0.210	2.61	0.0	2.45	12091.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.MAX	AERO DAMP	TDR	FST DAMP
71.9 (235.8)	13205 (275.8)	0.36E 07	-0.534	0.540	5.03	-0.00113	0.663	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		2.449	2.609	0	0.059	357	0.062	220	0.014	130	0.018	357	0.022	33	0.014	127	0.004	199	0.010	331
CN		0.348	0.185	356	0.003	300	0.002	99	0.001	206	0.001	258	0.001	309	0.001	177	0.004	9	0.001	99
CM		-0.029	0.008	299	0.001	89	0.001	49	0.002	359	0.001	193	0.001	112	0.001	117	0.001	146	0.001	190
CP 1	.010	0.979	1.787	345	0.078	52	0.013	18	0.008	256	0.017	194	0.014	78	0.011	80	0.022	356	0.307	169
CP 2	.020	0.897	0.996	348	0.013	16	0.012	80	0.007	63	0.015	241	0.010	79	0.058	99	0.017	36	0.013	199
CP 3	.030	0.444	0.841	348	0.010	16	0.012	52	0.002	12	0.007	205	0.007	52	0.008	169	0.014	99	0.005	146
CP 4	.049	0.731	0.693	349	0.002	291	0.014	53	0.003	244	0.002	351	0.006	82	0.307	160	0.021	69	0.005	290
CP 5	.074	0.727	0.561	349	0.004	370	0.006	172	0.005	69	0.009	260	0.003	117	0.099	151	0.008	19	0.006	147
CP 6	.099	0.874	0.453	352	0.003	70	0.009	80	0.007	214	0.004	274	0.004	341	0.009	88	0.010	72	0.097	199
CP 7	.149	0.627	0.349	351	0.007	291	0.013	85	0.008	340	0.007	226	0.000	46	0.001	137	0.013	17	0.011	139
CP 8	.200	0.564	0.284	356	0.011	103	0.014	56	0.007	199	0.009	261	0.004	108	0.001	157	0.010	33	0.012	131
CP 9	.250	0.440	0.756	355	0.007	107	0.008	165	0.004	299	0.002	245	0.010	199	0.009	177	0.007	161	0.004	244
CP10	.300	0.457	0.203	358	0.007	350	0.006	157	0.009	314	0.002	143	0.007	289	0.005	165	0.004	7	0.008	107
CP11	.355	0.391	0.164	5	0.006	268	0.014	159	0.009	227	0.002	329	0.007	326	0.006	166	0.007	319	0.015	750
CP12	.501	0.267	0.116	6	0.004	342	0.004	331	0.005	194	0.005	209	0.002	248	0.004	27	0.015	74	0.010	315
CP13	.600	0.301	0.087	10	0.004	119	0.006	750	0.014	19	0.007	218	0.004	205	0.099	169	0.012	337	0.004	287
CP14	.731	0.276	0.064	23	0.008	291	0.004	60	0.005	86	0.008	319	0.103	313	0.081	305	0.005	155	0.001	333
CP15	.800	0.169	0.041	26	0.009	277	0.003	207	0.009	361	0.008	118	0.005	42	0.038	183	0.010	327	0.003	106
CP16	.900	-0.068	0.017	47	0.008	196	0.008	168	0.010	179	0.002	136	0.007	274	0.017	397	0.006	261	0.008	16
CP17	.969	0.012	0.004	169	0.009	9	0.007	336	0.013	295	0.006	360	0.007	283	0.007	199	0.005	88	0.008	49

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNER HZ 7.9	TORQUE HZ 22.99	K 0.168	MACH NO 0.399	DEL.ALPHA 7.6C	DEL.H 0.0	ALPHA.0 4.95	TEST POINT 12001.3	CYCLES ANALYSED 70
V 69.2 (227.1)	Q 12334 (257.6)	PH 0.37E 07	C(H)IN) -0.997	C(H)MAX) 0.778	ALPHA.MAX 7.99	AERO DAMP -0.00164	TH0 0.991	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	K/C	OFS 0	OFS 1 PHI	OFS 2 PHI	OFS 3 PHI	OFS 4 PHI	OFS 5 PHI	OFS 6 PHI	OFS 7 PHI	OFS 8 PHI	OFS 9 PHI
ALPHA		4.950	7.657 7	0.061 4	0.061 710	0.021 172	0.018 11	0.026 99	0.012 151	0.007 122	0.010 0

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNER HZ 7.0	TORQUE HZ 22.92	K 0.172	MACH NO 0.199	DEL.ALPHA 7.60	DEL.H 0.0	ALPHA.0 7.62	TEST POINT 12001.4	CYCLES ANALYSED 20
V 67.9 (222.7)	Q 11893 (288.4)	PH 0.37E 07	C(H)IN) -0.021	C(H)MAX) 1.009	ALPHA.MAX 10.06	AERO DAMP -0.00139	TH0 0.779	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	K/C	OFS 0	OFS 1 PHI	OFS 2 PHI	OFS 3 PHI	OFS 4 PHI	OFS 5 PHI	OFS 6 PHI	OFS 7 PHI	OFS 8 PHI	OFS 9 PHI
ALPHA		7.622	7.655 0	0.066 0	0.066 727	0.022 127	0.021 20	0.028 41	0.012 157	0.007 113	0.010 344

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	0.0	22.99	0.174	0.197	7.56	0.0	14.86	12093.7	25

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AER0 DAMP	T20	EXT DAMP
	67.3	11735	3.32E 07	-0.151	1.612	17.46	0.30457	-2.522	0.0
	(220.7)	(245.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		14.862	2.556 3	0.101 6	0.081 234	0.036 124	0.030 4	0.025 81	0.318 155	0.304 17	0.012 355
CN		1.193	0.404 42	0.193 256	0.049 129	0.031 345	0.010 249	0.036 65	0.002 153	0.019 11	0.003 248
CM		-0.021	0.053 147	0.034 4	0.020 258	0.015 133	0.035 18	0.034 257	0.001 141	0.036 216	0.001 326
CP 1	.010	5.407	1.725 82	0.781 15	0.352 321	0.266 224	0.174 138	0.094 53	0.073 327	0.094 280	0.038 176
CP 2	.070	4.735	1.591 79	0.595 357	0.217 286	0.164 217	0.124 135	0.095 45	0.063 328	0.088 282	0.032 173
CP 3	.033	4.479	1.526 71	0.673 333	0.272 226	0.162 147	0.123 45	0.077 336	0.043 215	0.034 205	0.033 12
CP 4	.149	3.503	1.729 89	0.516 11	0.179 296	0.030 187	0.039 234	0.036 162	0.025 120	0.029 1	0.015 7
CP 5	.234	2.961	1.172 81	0.421 344	0.128 238	0.041 125	0.033 271	0.012 75	0.205 247	0.023 316	0.007 114
CP 6	.209	2.704	1.029 72	0.365 321	0.174 213	0.066 125	0.021 15	0.017 346	0.016 266	0.011 319	0.004 253
CP 7	.149	2.157	0.861 54	0.319 282	0.109 180	0.088 97	0.035 355	0.032 333	0.020 228	0.028 279	0.021 82
CP 8	.209	1.891	0.743 42	0.294 271	0.142 171	0.084 77	0.024 17	0.035 318	0.011 241	0.032 308	0.006 350
CP 9	.253	1.615	0.596 37	0.241 246	0.135 161	0.086 15	0.095 340	0.024 325	0.001 129	0.054 107	0.027 244
CP10	.300	1.446	0.546 78	0.236 244	0.176 136	0.085 26	0.052 284	0.033 211	0.027 143	0.015 35	0.036 313
CP11	.300	1.184	0.447 74	0.180 228	0.113 126	0.03C 6	0.053 265	0.030 175	0.033 72	0.053 13	0.024 276
CP12	.501	0.864	0.357 18	0.157 212	0.103 106	0.074 338	0.035 236	0.025 146	0.009 74	0.023 9	0.021 206
CP13	.600	0.688	0.286 17	0.144 203	0.088 97	0.071 324	0.027 271	0.022 112	0.023 305	0.013 0	0.016 157
CP14	.701	0.542	0.223 13	0.117 193	0.078 74	0.074 303	0.037 242	0.023 62	0.014 286	0.015 42	0.007 125
CP15	.803	0.331	0.171 351	0.103 171	0.064 47	0.059 306	0.023 175	0.030 44	0.034 274	0.019 56	0.010 66
CP16	.900	0.299	0.141 326	0.073 160	0.045 44	0.038 278	0.017 135	0.015 19	0.033 255	0.030 17	0.009 24
CP17	.949	0.250	0.079 333	0.042 189	0.025 30	0.025 277	0.008 318	0.038 26	0.004 7	0.015 28	0.007 153

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	0.0	22.94	0.173	0.199	7.54	0.0	17.37	12033.4	25

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AER0 DAMP	T20	EXT DAMP
	67.6	11870	3.32E 07	-0.256	1.909	19.49	0.00054	-0.398	0.0
	(221.9)	(247.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		17.374	2.538 3	0.054 31	0.031 176	0.027 11	0.018 291	0.021 78	0.037 115	0.034 349	0.011 302
CN		1.191	0.438 63	0.127 353	0.077 204	0.055 207	0.024 127	0.019 52	0.034 133	0.034 183	0.035 157
CM		-0.264	0.107 174	0.043 117	0.024 54	0.020 113	0.011 260	0.038 175	0.033 111	0.031 115	0.002 334
CP 1	.010	4.252	1.076 136	0.597 130	0.337 105	0.171 90	0.360 70	0.143 44	0.111 15	0.247 15	0.053 349
CP 2	.070	3.721	1.785 119	0.307 127	0.234 94	0.060 96	0.114 79	0.396 79	0.346 7	0.131 337	0.014 350
CP 3	.033	3.570	1.655 117	0.296 83	0.211 32	0.095 112	0.007 268	0.018 357	0.015 123	0.032 217	0.007 136
CP 4	.149	3.166	1.137 125	0.480 97	0.184 14	0.084 347	0.306 76	0.037 51	0.033 313	0.041 319	0.011 132
CP 5	.234	2.620	1.024 111	0.346 63	0.166 356	0.088 315	0.009 175	0.021 12	0.017 243	0.041 196	0.013 149
CP 6	.209	2.303	0.909 100	0.297 52	0.167 351	0.095 299	0.016 259	0.011 340	0.024 241	0.043 292	0.015 150
CP 7	.149	1.956	0.775 77	0.222 44	0.218 330	0.141 275	0.048 216	0.016 233	0.032 238	0.053 177	0.033 133
CP 8	.209	1.717	0.686 70	0.264 27	0.207 331	0.161 276	0.076 238	0.021 144	0.033 133	0.034 166	0.026 128
CP 9	.300	1.566	0.617 59	0.251 8	0.171 315	0.158 244	0.094 190	0.072 150	0.048 123	0.053 85	0.039 39
CP10	.300	1.473	0.563 47	0.229 350	0.154 299	0.125 229	0.057 178	0.064 125	0.035 75	0.038 63	0.015 356
CP11	.300	1.290	0.494 45	0.227 346	0.171 290	0.115 211	0.047 169	0.070 123	0.015 60	0.023 47	0.032 291
CP12	.501	0.692	0.451 18	0.228 335	0.135 271	0.137 196	0.066 132	0.051 74	0.032 7	0.024 332	0.024 233
CP13	.600	0.513	0.385 29	0.184 318	0.116 241	0.103 178	0.054 111	0.052 34	0.043 316	0.025 330	0.039 208
CP14	.701	0.615	0.343 18	0.165 297	0.113 241	0.097 156	0.068 85	0.062 3	0.032 285	0.025 243	0.020 141
CP15	.803	0.489	0.297 1	0.154 285	0.095 214	0.081 130	0.054 57	0.048 336	0.034 257	0.014 201	0.021 111
CP16	.900	0.278	0.193 6	0.109 290	0.053 214	0.059 112	0.048 46	0.040 327	0.019 198	0.018 195	0.010 45
CP17	.949	0.095	0.298 7	0.061 201	0.032 136	0.033 125	0.019 18	0.018 337	0.037 68	0.014 33	0.004 127

FORCED PITCHING OSCILLATION · AIRFOIL · NLR 1

FREC WT	DRIVE WT	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYZED
0.0	23.92	0.172	0.291	0.53	0.0	19.82	12901.0	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TMD	CYC DAMP
68.2	12099	0.375 07	-0.162	1.229	19.85	-0.33532	0.974	0.0
(223.9)	(252.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	DEG 0	DEG 1 PHI	DEG 2 PHI	DEG 3 PHI	DEG 4 PHI	DEG 5 PHI	DEG 6 PHI	DEG 7 PHI	DEG 8 PHI	DEG 9 PHI
ALPHA		19.822	0.521 2	0.053 74	0.256 214	0.021 192	0.032 74	0.008 63	0.013 170	0.002 27	0.012 356
CN		0.905	0.194 26	0.040 222	0.043 197	0.024 91	0.002 234	0.013 85	0.007 175	0.009 351	0.003 225
CM		-0.101	0.047 277	0.006 304	0.007 252	0.006 253	0.001 170	0.002 241	0.002 147	0.004 190	0.001 47
CP 1	.012	1.657	0.152 132	0.071 208	0.052 215	0.007 356	0.004 6	0.011 168	0.004 336	0.015 202	0.008 260
CP 2	.020	1.555	0.174 136	0.040 222	0.043 197	0.020 173	0.014 185	0.036 245	0.036 304	0.019 211	0.009 240
CP 3	.030	1.648	0.123 197	0.048 241	0.005 245	0.002 32	0.003 19	0.015 307	0.015 44	0.013 175	0.014 143
CP 4	.040	2.994	0.614 148	0.216 91	0.153 169	0.070 119	0.003 87	0.023 98	0.034 87	0.031 304	0.015 143
CP 5	.014	2.305	0.464 146	0.307 92	0.177 172	0.347 119	0.009 181	0.017 177	0.011 84	0.003 351	0.007 201
CP 6	.100	1.565	0.272 115	0.320 91	0.359 151	0.119 124	0.017 222	0.335 245	0.011 242	0.002 12	0.006 201
CP 7	.160	1.500	0.318 68	0.309 30	0.053 156	0.070 110	0.020 176	0.013 84	0.017 91	0.005 50	0.002 14
CP 8	.200	1.272	0.218 81	0.341 131	0.372 163	0.012 146	0.002 215	0.011 168	0.013 211	0.014 232	0.016 140
CP 9	.200	1.148	0.240 76	0.348 125	0.360 145	0.020 171	0.016 208	0.017 332	0.019 163	0.022 304	0.001 165
CP10	.100	1.191	0.232 77	0.074 137	0.044 141	0.015 81	0.010 339	0.026 249	0.035 156	0.023 120	0.035 308
CP11	.300	1.069	0.242 68	0.076 179	0.053 114	0.013 34	0.007 125	0.036 235	0.027 316	0.011 314	0.019 170
CP12	.521	0.918	0.248 68	0.366 114	0.052 125	0.043 171	0.006 217	0.009 133	0.014 156	0.001 47	0.010 187
CP13	.600	0.834	0.347 62	0.054 137	0.339 179	0.027 104	0.036 311	0.036 136	0.013 153	0.013 133	0.010 256
CP14	.701	0.773	0.333 66	0.027 110	0.038 84	0.335 54	0.006 17	0.014 49	0.013 95	0.012 146	0.006 232
CP15	.802	0.627	0.202 50	0.098 56	0.035 48	0.031 56	0.002 248	0.013 4	0.013 32	0.012 4	0.006 184
CP16	.900	0.378	0.114 43	0.012 187	0.011 56	0.014 67	0.003 235	0.033 88	0.012 121	0.010 4	0.009 200
CP17	.060	0.091	0.059 60	0.019 174	0.320 36	0.023 117	0.020 30	0.015 99	0.014 98	0.022 0	0.010 27

FORCED PITCHING OSCILLATION · AIRFOIL · NLR 1

FREC WT	DRIVE WT	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYZED
0.0	22.95	0.111	0.329	2.58	0.0	0.97	12705.1	23

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TMD	CYC DAMP
105.4	28776	0.505 07	-0.026	0.391	2.64	-0.00085	0.713	0.0
(345.9)	(60)							

HARMONIC ANALYSIS

DATA TYPE	X/C	DEG 0	DEG 1 PHI	DEG 2 PHI	DEG 3 PHI	DEG 4 PHI	DEG 5 PHI	DEG 6 PHI	DEG 7 PHI	DEG 8 PHI	DEG 9 PHI
ALPHA		0.067	2.503 2	0.358 7	0.067 210	0.022 134	0.025 78	0.021 47	0.015 201	0.036 108	0.006 337
CN		0.118	0.213 356	0.032 207	0.032 143	0.001 248	0.000 44	0.002 142	0.001 246	0.003 175	0.002 231
CM		-0.047	0.037 328	0.001 315	0.003 273	0.000 97	0.001 177	0.001 312	0.001 70	0.001 21	0.000 31
CP 1	.012	-0.510	1.508 347	0.333 0	0.015 156	0.006 182	0.035 182	0.006 17	0.014 245	0.015 158	0.017 277
CP 2	.020	-0.363	1.171 348	0.051 388	0.030 234	0.015 278	0.002 268	0.013 11	0.001 72	0.015 175	0.003 329
CP 3	.030	-0.351	0.043 349	0.021 303	0.007 164	0.006 304	0.002 241	0.006 19	0.002 259	0.006 232	0.003 7
CP 4	.040	0.092	0.746 348	0.917 133	0.035 156	0.004 137	0.002 166	0.004 85	0.001 178	0.008 181	0.005 156
CP 5	.014	0.217	0.521 353	0.013 302	0.017 146	0.001 108	0.004 175	0.001 70	0.003 118	0.005 158	0.003 308
CP 6	.100	0.318	0.650 351	0.013 309	0.004 173	0.001 347	0.035 169	0.009 35	0.035 112	0.033 134	0.002 271
CP 7	.160	0.333	0.508 351	0.013 277	0.036 183	0.002 111	0.005 82	0.035 11	0.034 334	0.035 178	0.004 258
CP 8	.200	0.303	0.318 353	0.023 274	0.003 153	0.007 341	0.005 174	0.004 147	0.003 304	0.006 234	0.006 334
CP 9	.200	0.345	0.371 353	0.033 71	0.034 54	0.004 171	0.002 292	0.035 143	0.011 7	0.037 116	0.038 175
CP10	.100	0.178	0.321 355	0.003 300	0.031 82	0.004 269	0.004 197	0.035 154	0.035 155	0.004 75	0.002 240
CP11	.300	0.174	0.303 350	0.031 347	0.031 267	0.004 253	0.005 49	0.005 154	0.007 360	0.012 174	0.003 282
CP12	.521	0.117	0.165 1	0.004 133	0.036 92	0.002 136	0.023 204	0.005 153	0.003 326	0.002 271	0.035 177
CP13	.600	0.150	0.127 6	0.007 123	0.051 188	0.002 185	0.004 302	0.035 175	0.037 137	0.014 248	0.002 127
CP14	.701	0.150	0.047 167	0.001 71	0.002 347	0.001 222	0.004 155	0.001 247	0.001 113	0.035 205	
CP15	.802	0.094	0.047 15	0.001 171	0.002 187	0.002 339	0.003 343	0.003 112	0.002 243	0.035 176	0.032 233
CP16	.900	-0.078	0.015 8	0.002 324	0.002 304	0.001 266	0.005 40	0.034 112	0.000 264	0.034 308	0.001 314
CP17	.060	-0.033	0.013 175	0.003 198	0.004 174	0.003 249	0.000 336	0.006 173	0.007 244	0.003 334	0.003 310

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

FREQ HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.O	TEST POINT	CYCLES ANALYSED
3.3	33.96	3.113	3.393	7.6C	3.3	7.53	17995.2	33

103.1 (338.2)	27747. (579.5)						

HARMONIC ANALYSIS

DATA TYPE	X/C	BEC 0	BEC 1 PHI	BEC 2 PHI	BEC 3 PHI	BEC 4 PHI	BEC 5 PHI	BEC 6 PHI	BEC 7 PHI	BEC 8 PHI	BEC 9 PHI

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

100.8 (330.6)	26665. (556.9)		

HARMONIC ANALYSIS

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TIMER H2	NOTUE H2	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	77.04	0.117	0.704	2.61	0.0	7.48	12095.4	70

V	Q	QN	CM(MIN)	CM(MAX)	ALPHA.NMAX	AERO DAMP	TPD	EXT DAMP
99.6	26095.	0.48E 07	-0.316	1.365	10.12	-0.00125	1.336	0.7
(326.6)	(545.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	BFC 0	BFC 1 PHI	BFC 2 PHI	BFC 3 PHI	BFC 4 PHI	BFC 5 PHI	BFC 6 PHI	BFC 7 PHI	BFC 8 PHI	BFC 9 PHI
ALPHA		9.477	7.607 0	0.062 5	0.057 331	0.324 120	0.073 71	0.019 132	0.011 174	0.025 174	0.013 343
CN		0.453	0.721 356	0.039 38	0.037 358	0.092 247	0.092 178	0.032 157	0.003 116	0.005 312	0.001 261
CM		-0.002	0.009 200	0.031 270	0.092 104	0.000 96	0.001 337	0.001 337	0.001 197	0.004 358	0.001 171
NCP 1	.010	4.181	1.338 346	0.127 59	0.056 318	0.092 183	0.013 301	0.008 208	0.016 89	0.036 312	0.005 74
NCP 2	.020	3.444	1.306 350	0.031 5	0.016 314	0.093 61	0.037 240	0.010 50	0.015 44	0.042 326	0.007 75
NCP 3	.030	3.174	1.371 349	0.076 324	0.316 335	0.035 120	0.034 179	0.005 35	0.011 85	0.020 314	0.003 98
NCP 4	.040	2.835	1.466 357	0.010 352	0.032 237	0.010 212	0.001 230	0.006 309	0.007 20	0.025 329	0.013 110
NCP 5	.014	2.436	1.475 357	0.014 4	0.031 247	0.034 179	0.007 76	0.000 219	0.004 31	0.018 311	0.006 98
NCP 6	.080	2.156	1.560 351	0.011 3	0.031 247	0.006 168	0.002 304	0.031 252	0.003 43	0.020 315	0.009 68
NCP 7	.140	1.656	1.410 357	0.011 4	0.006 344	0.006 238	0.004 233	0.005 53	0.006 50	0.017 322	0.036 45
NCP 8	.230	1.332	3.311 355	0.212 77	0.036 170	0.001 240	0.006 35	0.007 100	0.038 88	0.027 333	0.009 112
NCP 9	.253	1.280	3.243 356	0.090 61	0.030 13	0.005 230	0.034 165	0.005 162	0.002 287	0.011 179	0.003 227
NCP10	.370	0.884	3.216 356	0.037 47	0.025 17	0.002 243	0.002 104	0.003 265	3.037 276	0.013 194	0.036 223
NCP11	.400	0.410	3.189 3	0.036 73	0.011 7	0.002 277	0.003 113	3.001 134	0.036 307	0.018 181	0.035 254
NCP12	.501	3.597	3.143 4	3.007 56	0.009 362	0.003 321	0.005 177	0.004 47	0.007 307	0.017 185	0.006 274
NCP13	.600	3.509	0.119 11	0.000 49	0.013 340	0.001 346	3.007 169	3.001 189	0.030 59	0.015 180	0.033 243
NCP14	.701	3.442	3.070 14	0.007 38	0.030 358	0.004 277	0.002 307	0.035 175	0.036 295	0.010 181	0.031 256
NCP15	.800	3.220	3.344 20	0.000 94	0.036 6	0.007 262	0.006 168	3.001 331	0.006 319	0.015 173	0.001 269
NCP16	.900	-3.043	3.324 29	3.001 332	0.030 14	0.002 119	0.004 196	3.038 142	0.006 247	0.018 172	0.001 324
NCP17	.960	-0.063	0.036 94	0.007 47	0.009 358	0.006 131	0.006 270	3.035 322	0.007 279	0.010 215	0.003 340

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TIMER H2	NOTUE H2	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	77.00	0.118	0.291	2.60	0.0	9.94	12095.5	27

V	Q	QN	CM(MIN)	CM(MAX)	ALPHA.MAX	AERO DAMP	TPD	EXT DAMP
99.3	26037.	0.48E 07	-0.308	1.270	12.64	-0.00133	1.049	0.3
(325.9)	(543.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	BFC 0	BFC 1 PHI	BFC 2 PHI	BFC 3 PHI	BFC 4 PHI	BFC 5 PHI	BFC 6 PHI	BFC 7 PHI	BFC 8 PHI	BFC 9 PHI
ALPHA		9.919	2.804 0	0.068 14	0.063 339	0.022 110	0.027 12	0.011 70	0.014 149	0.012 102	0.004 344
CN		1.060	3.105 2	0.015 5	0.036 257	0.031 227	0.001 356	0.092 147	0.001 88	0.007 74	0.001 131
CM		0.005	0.011 307	0.033 213	0.031 108	0.001 139	0.000 144	0.001 7	0.000 62	0.003 272	0.001 324
NCP 1	.010	5.885	1.422 351	0.207 269	0.169 161	0.027 165	0.028 135	0.012 111	0.012 357	0.013 267	0.036 105
NCP 2	.020	4.596	3.896 352	0.079 44	0.073 338	0.005 338	0.001 71	3.032 212	0.006 83	0.014 337	0.003 162
NCP 3	.030	4.101	3.945 351	0.041 3	0.007 366	0.003 151	0.001 121	0.034 47	0.003 149	0.039 322	0.003 210
NCP 4	.040	3.847	3.757 354	0.049 20	0.037 340	0.002 72	0.003 333	1.007 85	0.005 371	0.017 344	0.003 94
NCP 5	.074	3.371	3.505 354	0.035 17	0.036 345	0.002 151	0.032 26	0.008 70	0.005 67	0.015 74	0.004 350
NCP 6	.080	2.807	3.407 356	0.031 10	0.012 273	0.006 181	0.005 144	3.034 48	0.036 337	0.004 140	0.032 335
NCP 7	.140	2.315	3.377 357	0.079 344	0.011 271	0.001 225	0.034 207	0.001 188	0.007 97	0.037 325	0.035 15
NCP 8	.230	1.633	3.337 1	0.010 340	0.036 341	0.001 199	0.005 248	0.007 107	0.001 97	0.033 340	0.031 331
NCP 9	.253	1.371	3.265 1	0.310 0	0.317 292	0.004 188	0.031 305	0.034 74	0.011 67	0.036 211	
NCP10	.370	1.314	3.230 1	0.021 12	0.036 374	0.001 89	0.005 58	0.032 332	0.001 147	0.012 56	0.004 7
NCP11	.400	0.968	3.164 10	0.019 19	0.034 242	0.002 330	0.004 77	0.001 139	0.001 100	0.012 80	0.031 108
NCP12	.501	3.734	3.124 15	0.027 17	0.035 269	0.032 191	0.032 229	3.036 147	0.035 44	0.007 86	0.004 185
NCP13	.600	3.646	3.096 24	0.019 4	0.031 259	0.002 103	0.002 1	0.003 192	0.002 313	0.015 67	0.004 126
NCP14	.701	3.495	3.051 37	0.015 14	0.036 266	0.005 201	0.006 2	3.032 142	0.031 133	0.030 65	0.004 117
NCP15	.800	3.354	3.376 41	0.039 17	0.036 275	0.006 278	0.005 34	3.033 243	0.001 339	0.011 96	0.033 39
NCP16	.900	-0.025	3.227 48	0.013 16	0.031 291	0.002 70	0.034 251	0.006 145	0.007 339	0.011 97	0.034 153
NCP17	.965	-0.060	3.213 14	0.002 36	0.035 277	0.004 7	0.004 171	0.034 34	0.039 86	0.013 84	0.035 252

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

104.8   28412.
(343.9)   (593.4)

HARMONIC ANALYSIS

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

101.7   27100.
(333.5)   (566.0)

HARMONIC ANALYSIS

FORCED PITCHING OSCILLATION

TUNNEL MF	TOTAL MF	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.O	TEST POINT	CYCLES ANALYSED
9.0	22.99	0.117	5.794	7.51	5.9	17.99	12997.5	20

V	Q	QH	C(MEAN)	C(MAX)	ALPHA.NMAX	ATOT DAMP	TAU	TOT DAMP
99.8 (327.6)	26267. (548.6)	3.495 37	-3.162	1.794	17.65	-3.395%	4.035	5.7

HARMONIC ANALYSIS

DATA TYPE	K.F.	DEG 0	DEG 1 PHI	DEG 2 PHI	DEG 3 PHI	DEG 4 PHI	DEG 5 PHI	DEG 6 PHI	DEG 7 PHI	DEG 8 PHI	DEG 9 PHI

(Remaining tabular data illegible due to scan degradation)

FORCED PITCHING OSCILLATION

TUNNEL MF	TOTAL MF	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.O	TEST POINT	CYCLES ANALYSED
9.0	22.96	0.118	5.797	7.56	5.7	18.90	12997.4	20

V	Q	QH	C(MEAN)	C(MAX)	ALPHA.NMAX	ATOT DAMP	TAU	TOT DAMP
99.1 (325.1)	25937. (541.7)	3.494 37	-3.165	1.790	17.05	-3.395%	4.750	5.7

HARMONIC ANALYSIS

(Remaining tabular data illegible due to scan degradation)

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.45	0.216	0.314	2.82	0.0	0.10	12099.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
107.2 (351.6)	29978. (626.1)	0.51E 07	-0.026	0.286	3.00	-0.00082	0.725	0.0

HARMONIC ANALYSIS

DATA TYPE	R/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.102	2.621 0	0.079 358	0.091 262	0.006 127	0.029 85	0.024 51	0.015 184	0.011 170	0.011 356
CN		0.102	0.190 2	0.003 9	0.005 8	0.005 327	0.002 197	0.002 41	0.002 211	0.005 148	0.003 255
CM		-0.013	0.013 293	0.001 288	0.001 254	0.002 159	0.000 110	0.001 295	0.001 102	0.001 337	0.001 86
DCP 1	.010	-0.489	1.350 344	0.042 353	0.012 187	0.007 330	0.026 164	0.021 349	0.008 162	0.014 74	0.005 176
DCP 2	.020	-0.281	1.020 350	0.023 292	0.020 319	0.004 328	0.005 203	0.005 339	0.011 140	0.010 130	0.003 34
DCP 3	.030	-0.069	0.857 349	0.021 301	0.014 309	0.006 177	0.008 217	0.004 3	0.010 164	0.004 71	0.005 28
DCP 4	.049	0.145	0.697 350	0.013 336	0.016 340	0.010 190	0.007 176	0.002 210	0.007 178	0.001 148	0.008 6
DCP 5	.074	0.244	0.562 351	0.010 350	0.009 321	0.007 177	0.009 141	0.001 285	0.002 93	0.002 40	0.005 23
DCP 6	.099	0.219	0.484 352	0.009 1	0.010 336	0.006 197	0.006 149	0.002 227	0.005 149	0.004 91	0.003 120
DCP 7	.149	0.228	0.440 355	0.006 344	0.008 337	0.003 181	0.002 266	0.004 72	0.006 189	0.006 132	0.003 233
DCP 8	.200	0.167	0.286 3	0.008 347	0.004 85	0.006 7	0.011 178	0.005 294	0.003 214	0.007 124	0.004 166
DCP 9	.250	0.143	0.250 2	0.002 178	0.008 346	0.008 304	0.005 72	0.007 37	0.004 150	0.002 117	0.002 168
DCP10	.300	0.153	0.210 2	0.004 352	0.010 351	0.003 340	0.002 207	0.009 6	0.003 174	0.007 138	0.006 201
DCP11	.399	0.137	0.170 12	0.006 77	0.012 13	0.009 317	0.005 247	0.004 18	0.004 208	0.006 192	0.004 244
DCP12	.501	0.098	0.131 19	0.002 20	0.005 64	0.005 326	0.009 172	0.001 317	0.001 303	0.007 176	0.006 298
DCP13	.600	0.100	0.104 27	0.003 182	0.004 326	0.007 308	0.004 254	0.007 66	0.002 249	0.004 146	0.005 233
DCP14	.701	0.183	0.069 34	0.001 182	0.006 39	0.005 16	0.003 331	0.007 193	0.000 62	0.009 157	0.006 295
DCP15	.800	0.075	0.046 46	0.007 26	0.003 89	0.008 352	0.003 263	0.003 104	0.004 281	0.004 173	0.003 212
DCP16	.900	-0.075	0.024 74	0.004 124	0.005 132	0.008 286	0.002 87	0.004 164	0.003 241	0.007 147	0.007 243
DCP17	.969	-0.034	0.012 159	0.001 109	0.001 5	0.021 358	0.004 333	0.007 35	0.004 293	0.006 87	0.009 322

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.46	0.222	0.306	2.75	0.0	2.49	12099.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
104.1 (341.7)	28561. (596.5)	0.50E 07	-0.022	0.515	5.14	-0.00088	0.718	0.0

HARMONIC ANALYSIS

DATA TYPE	R/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.488	2.754 0	0.070 28	0.095 240	0.017 305	0.031 26	0.023 44	0.022 175	0.017 263	0.015 338
CN		0.328	0.191 1	0.002 92	0.003 342	0.009 336	0.001 274	0.003 4	0.002 192	0.004 350	0.001 278
CM		-0.008	0.013 292	0.001 33	0.001 190	0.003 161	0.001 98	0.001 143	0.000 53	0.002 193	0.000 15
DCP 1	.010	0.999	1.302 341	0.032 34	0.023 38	0.013 347	0.012 68	0.019 336	0.004 47	0.003 38	0.005 69
DCP 2	.020	0.866	1.042 348	0.019 17	0.010 269	0.008 308	0.004 161	0.006 42	0.013 91	0.008 253	0.005 349
DCP 3	.030	0.912	0.886 348	0.013 17	0.007 265	0.005 340	0.001 141	0.001 38	0.006 99	0.004 253	0.002 234
DCP 4	.049	0.961	0.717 349	0.009 61	0.008 270	0.004 323	0.003 148	0.010 123	0.005 135	0.005 321	0.006 357
DCP 5	.074	0.906	0.575 350	0.009 38	0.005 221	0.001 243	0.001 262	0.004 83	0.004 68	0.003 53	0.002 4
DCP 6	.099	0.882	0.474 352	0.014 51	0.008 297	0.008 253	0.004 156	0.001 36	0.006 60	0.004 302	0.003 81
DCP 7	.149	0.647	0.357 355	0.007 55	0.004 91	0.007 266	0.002 91	0.004 21	0.006 97	0.006 176	0.004 107
DCP 8	.200	0.515	0.296 1	0.010 84	0.004 214	0.005 284	0.006 48	0.001 95	0.008 92	0.006 309	0.005 110
DCP 9	.250	0.430	0.249 0	0.003 133	0.005 5	0.016 330	0.007 253	0.007 1	0.011 180	0.005 238	0.005 297
DCP10	.300	0.410	0.237 3	0.005 230	0.005 241	0.010 344	0.005 129	0.002 307	0.006 213	0.008 302	0.006 326
DCP11	.399	0.331	0.165 14	0.001 93	0.009 16	0.015 350	0.010 286	0.005 66	0.013 235	0.009 2	0.004 208
DCP12	.501	0.244	0.131 18	0.007 80	0.010 286	0.015 348	0.002 44	0.007 43	0.007 263	0.005 323	0.001 217
DCP13	.600	0.209	0.136 23	0.010 90	0.001 198	0.011 358	0.004 226	0.002 327	0.001 193	0.001 285	0.001 174
DCP14	.701	0.269	0.077 40	0.006 218	0.004 9	0.008 351	0.003 251	0.037 18	0.003 108	0.005 13	0.001 286
DCP15	.800	0.115	0.047 49	0.005 217	0.008 48	0.009 315	0.002 57	0.006 312	0.001 251	0.011 25	0.005 16
DCP16	.900	-0.067	0.018 62	0.005 241	0.006 310	0.015 333	0.005 233	0.009 240	0.003 232	0.009 26	0.001 240
DCP17	.969	0.053	0.012 164	0.011 240	0.011 34	0.001 228	0.007 343	0.007 359	0.005 70	0.010 356	0.006 165

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.43	0.226	0.301	2.77	0.0	4.98	12099.3	20

V	Q	RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
102.4	27689.	0.49E 07	-0.019	0.754	7.62	-0.00098	0.829	0.0
(335.9)	(578.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.975	2.774 0	0.070 6	0.072 256	0.011 150	0.037 47	0.013 46	0.018 175	0.010 252	0.014 350
CN		0.569	0.192 1	0.005 29	0.004 5	0.012 268	0.002 134	0.001 314	0.004 208	0.004 307	0.000 128
CM		-0.003	0.014 291	0.000 67	0.002 206	0.003 100	0.001 327	0.001 79	0.001 37	0.001 133	0.001 190
DCP 1	.010	2.588	1.301 343	0.026 44	0.022 206	0.023 229	0.011 8	0.014 35	0.006 120	0.019 230	0.001 130
DCP 2	.020	2.106	1.026 349	0.027 24	0.009 235	0.025 259	0.005 278	0.007 22	0.008 150	0.007 249	0.007 185
DCP 3	.030	1.964	0.875 348	0.024 20	0.003 259	0.018 258	0.002 109	0.010 36	0.005 169	0.004 252	0.002 273
DCP 4	.049	1.847	0.731 350	0.014 32	0.005 339	0.019 234	0.008 178	0.002 99	0.005 120	0.001 312	0.008 157
DCP 5	.074	1.622	0.585 350	0.014 35	0.008 277	0.015 252	0.004 242	0.003 197	0.005 121	0.007 305	0.003 234
DCP 6	.099	1.470	0.471 353	0.013 52	0.001 233	0.013 224	0.002 244	0.003 80	0.003 96	0.008 333	0.001 193
DCP 7	.149	1.091	0.378 355	0.019 20	0.005 299	0.013 246	0.003 104	0.007 295	0.004 222	0.007 293	0.006 230
DCP 8	.200	0.884	0.289 2	0.005 343	0.005 330	0.013 265	0.005 202	0.003 53	0.001 139	0.008 309	0.000 294
DCP 9	.250	0.727	0.254 2	0.008 12	0.002 314	0.013 276	0.007 112	0.006 167	0.008 200	0.012 331	0.002 98
DCP10	.300	0.668	0.214 4	0.004 33	0.005 326	0.009 258	0.003 71	0.007 332	0.005 224	0.001 279	0.003 137
DCP11	.399	0.541	0.171 16	0.007 67	0.006 14	0.017 277	0.006 36	0.005 358	0.002 268	0.001 214	0.001 354
DCP12	.501	0.398	0.135 23	0.007 26	0.007 10	0.011 268	0.006 126	0.003 292	0.003 219	0.001 236	0.004 162
DCP13	.600	0.325	0.108 29	0.008 44	0.009 21	0.011 286	0.006 189	0.003 335	0.009 218	0.010 325	0.001 2
DCP14	.701	0.347	0.073 37	0.003 102	0.008 56	0.011 322	0.004 126	0.006 213	0.005 250	0.004 275	0.001 26
DCP15	.800	0.166	0.054 54	0.003 23	0.007 61	0.012 262	0.002 341	0.001 129	0.006 159	0.002 321	0.004 139
DCP16	.900	-0.051	0.025 89	0.011 250	0.009 334	0.012 244	0.004 190	0.003 269	0.006 235	0.009 301	0.012 1
DCP17	.969	-0.053	0.008 131	0.000 217	0.000 266	0.019 279	0.003 129	0.003 282	0.003 163	0.003 21	0.004 255

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.46	0.228	0.299	2.81	0.0	7.48	12099.4	20

V	Q	RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
101.3	27210.	0.49E 07	-0.018	0.999	10.41	-0.00107	0.900	0.0
(332.4)	(568.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.483	2.809 0	0.084 358	0.064 260	0.039 140	0.035 56	0.013 42	0.017 197	0.013 45	0.009 44
CN		0.806	0.192 5	0.009 42	0.003 20	0.007 205	0.002 26	0.001 273	0.002 124	0.008 83	0.002 131
CM		0.002	0.016 288	0.001 271	0.001 291	0.002 24	0.000 260	0.000 65	0.001 334	0.003 271	0.001 355
DCP 1	.010	4.004	1.196 344	0.126 41	0.082 305	0.028 216	0.016 306	0.013 358	0.008 107	0.016 282	0.002 301
DCP 2	.020	3.363	1.054 349	0.021 24	0.020 314	0.003 102	0.001 334	0.006 339	0.011 139	0.011 265	0.003 206
DCP 3	.030	3.022	0.898 349	0.023 0	0.014 335	0.008 36	0.005 11	0.003 340	0.005 78	0.003 238	0.004 334
DCP 4	.049	2.745	0.742 350	0.023 38	0.011 343	0.005 270	0.006 24	0.005 287	0.007 136	0.006 15	0.004 68
DCP 5	.074	2.345	0.584 351	0.017 26	0.004 356	0.004 302	0.004 38	0.001 358	0.010 97	0.005 352	0.005 85
DCP 6	.099	2.056	0.482 353	0.012 36	0.002 339	0.001 166	0.006 351	0.002 10	0.002 160	0.002 347	0.004 105
DCP 7	.149	1.549	0.360 355	0.016 5	0.005 343	0.004 224	0.010 342	0.002 217	0.006 94	0.002 11	0.006 23
DCP 8	.200	1.235	0.287 1	0.012 13	0.005 332	0.010 222	0.001 126	0.008 190	0.010 167	0.004 124	0.010 145
DCP 9	.250	1.030	0.254 4	0.009 30	0.005 338	0.010 185	0.001 87	0.001 98	0.005 98	0.013 78	0.012 54
DCP10	.300	0.925	0.216 7	0.008 44	0.007 11	0.006 143	0.002 46	0.003 31	0.005 349	0.009 40	0.001 156
DCP11	.399	0.747	0.177 19	0.009 56	0.007 65	0.005 198	0.007 91	0.004 235	0.001 322	0.013 84	0.003 283
DCP12	.501	0.555	0.131 24	0.004 67	0.003 70	0.012 221	0.005 13	0.009 330	0.004 35	0.015 99	0.003 207
DCP13	.600	0.431	0.112 35	0.009 65	0.007 35	0.014 204	0.003 23	0.009 92	0.001 43	0.017 78	0.005 169
DCP14	.701	0.427	0.079 48	0.006 69	0.008 63	0.006 211	0.005 162	0.004 223	0.003 185	0.012 95	0.000 288
DCP15	.800	0.205	0.058 57	0.004 132	0.007 168	0.009 211	0.006 255	0.004 346	0.007 151	0.010 108	0.005 56
DCP16	.900	-0.0??	0.029 65	0.009 50	0.004 114	0.005 202	0.008 61	0.011 232	0.009 155	0.007 38	0.009 183
DCP17	.969	-0.057	0.007 135	0.003 22	0.006 259	0.010 189	0.007 273	0.001 110	0.004 344	0.012 114	0.002 341

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.50	0.230	0.297	2.76	0.0	9.93	12099.5	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
100.9	27019.	0.49E 07	-0.011	1.195	12.43	-0.00116	0.976	0.0
(331.0)	(564.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		9.927	2.757 0	0.065 16	0.071 249	0.012 292	0.033 41	0.020 47	0.019 158	0.007 279	0.013 336
CN		1.013	0.185 10	0.008 344	0.002 29	0.014 305	0.002 236	0.004 324	0.003 85	0.001 351	0.002 239
CM		0.010	0.017 289	0.001 188	0.001 245	0.005 143	0.001 93	0.001 128	0.001 204	0.001 197	0.001 28
DCP 1	.010	5.493	1.284 349	0.257 260	0.110 144	0.044 196	0.008 48	0.017 139	0.010 295	0.028 166	0.009 207
DCP 2	.020	4.464	0.929 352	0.056 49	0.023 329	0.022 237	0.006 207	0.008 245	0.008 163	0.012 210	0.003 227
DCP 3	.030	3.996	0.874 351	0.033 6	0.010 309	0.010 228	0.008 120	0.001 150	0.007 117	0.005 174	0.002 272
DCP 4	.049	3.553	0.701 352	0.040 18	0.011 287	0.010 213	0.008 140	0.004 40	0.009 159	0.003 252	0.010 133
DCP 5	.074	2.985	0.558 353	0.026 9	0.007 277	0.010 222	0.007 209	0.000 320	0.004 232	0.004 236	0.001 54
DCP 6	.099	2.580	0.456 356	0.021 359	0.001 41	0.014 224	0.008 165	0.001 110	0.006 177	0.007 264	0.004 281
DCP 7	.149	1.944	0.352 359	0.010 6	0.006 292	0.007 223	0.006 34	0.001 83	0.010 192	0.005 350	0.005 64
DCP 8	.200	1.564	0.280 7	0.013 343	0.002 229	0.009 260	0.012 179	0.005 25	0.002 156	0.014 224	0.002 245
DCP 9	.250	1.303	0.250 6	0.007 316	0.009 338	0.014 282	0.001 134	0.004 288	0.003 186	0.007 5	0.009 294
DCP10	.300	1.145	0.203 11	0.007 9	0.004 314	0.015 291	0.003 240	0.008 323	0.006 121	0.006 329	0.008 289
DCP11	.399	0.915	0.164 24	0.008 22	0.009 343	0.025 331	0.006 300	0.013 334	0.011 73	0.003 82	0.006 284
DCP12	.501	0.689	0.134 31	0.004 86	0.007 20	0.016 296	0.003 313	0.005 43	0.006 17	0.005 117	0.001 209
DCP13	.600	0.516	0.100 46	0.007 317	0.011 38	0.014 316	0.005 216	0.003 339	0.003 72	0.001 150	0.002 195
DCP14	.701	0.471	0.087 57	0.008 347	0.005 86	0.018 331	0.004 251	0.011 310	0.003 292	0.003 2	0.008 231
DCP15	.800	0.235	0.062 71	0.008 15	0.010 107	0.021 321	0.002 321	0.004 275	0.005 9	0.004 350	0.003 176
DCP16	.900	-0.021	0.035 53	0.007 297	0.007 181	0.024 311	0.003 315	0.005 296	0.011 66	0.010 16	0.006 132
DCP17	.969	-0.068	0.018 72	0.001 347	0.007 321	0.016 324	0.005 189	0.006 282	0.007 344	0.003 327	0.007 241

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.49	0.229	0.298	2.77	0.0	12.42	12099.6	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
101.0	27119.	0.49E 07	-0.089	1.392	14.86	0.00103	-0.863	0.0
(331.4)	(566.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.425	2.768 0	0.112 349	0.077 236	0.026 147	0.033 58	0.021 44	0.011 198	0.006 96	0.006 348
CN		1.064	0.325 28	0.049 211	0.038 76	0.032 303	0.017 217	0.012 136	0.007 25	0.004 56	0.007 297
CM		-0.005	0.032 152	0.031 341	0.014 230	0.009 95	0.002 11	0.002 207	0.003 162	0.001 231	0.002 93
DCP 1	.010	5.134	1.306 66	0.823 2	0.383 302	0.114 213	0.054 63	0.060 15	0.078 297	0.055 221	0.024 147
DCP 2	.020	4.095	1.166 89	0.883 24	0.468 295	0.247 222	0.124 195	0.136 146	0.108 62	0.038 325	0.027 230
DCP 3	.030	3.522	1.209 90	0.763 13	0.235 291	0.168 271	0.189 207	0.136 149	0.088 96	0.080 54	0.075 351
DCP 4	.049	3.690	0.783 36	0.183 342	0.068 222	0.044 137	0.016 27	0.012 247	0.019 140	0.010 73	0.018 294
DCP 5	.074	3.049	0.649 42	0.160 338	0.056 198	0.023 108	0.013 335	0.011 203	0.005 107	0.007 150	0.009 310
DCP 6	.099	2.621	0.609 44	0.155 319	0.061 169	0.013 55	0.010 285	0.015 154	0.009 34	0.014 250	0.008 255
DCP 7	.149	1.968	0.564 43	0.160 297	0.075 154	0.024 358	0.006 133	0.004 270	0.003 299	0.003 184	0.005 37
DCP 8	.200	1.644	0.557 33	0.177 262	0.077 117	0.014 312	0.005 189	0.012 54	0.015 341	0.027 200	0.007 28
DCP 9	.250	1.429	0.577 21	0.231 233	0.114 104	0.054 12	0.039 286	0.033 146	0.003 111	0.004 26	0.009 82
DCP10	.300	1.299	0.550 12	0.243 221	0.122 112	0.079 8	0.043 243	0.006 60	0.014 202	0.017 76	0.005 304
DCP11	.399	1.047	0.448 14	0.205 211	0.113 102	0.088 354	0.042 239	0.014 190	0.014 126	0.020 65	0.014 298
DCP12	.501	0.769	0.322 11	0.152 184	0.088 75	0.084 317	0.040 208	0.017 165	0.018 78	0.019 345	0.007 302
DCP13	.600	0.544	0.215 14	0.137 152	0.076 45	0.078 288	0.039 171	0.015 117	0.019 23	0.015 261	0.006 292
DCP14	.701	0.475	0.161 20	0.119 139	0.062 21	0.062 248	0.004 118	0.017 115	0.022 16	0.005 91	0.014 289
DCP15	.800	0.281	0.118 353	0.090 131	0.037 18	0.035 231	0.005 294	0.020 149	0.022 339	0.006 101	0.014 263
DCP16	.900	0.038	0.071 316	0.043 140	0.033 22	0.025 218	0.001 321	0.020 57	0.019 287	0.016 54	0.004 240
DCP17	.969	-0.026	0.036 294	0.015 101	0.025 353	0.017 216	0.013 95	0.013 315	0.007 308	0.006 197	0.002 324

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.46	0.229	0.298	2.68	0.0	14.90	12099.7	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
100.9 (330.9)	27095. (565.9)	0.49E 07	-0.205	1.719	17.53	0.00075	-0.626	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		14.904	2.683 0	0.158 34	0.155 295	0.060 81	0.043 86	0.018 20	0.007 271	0.018 239	0.008 97
CN		1.099	0.422 55	0.139 329	0.071 221	0.024 148	0.031 93	0.012 14	0.010 44	0.007 20	0.001 71
CM		-0.029	0.004 177	0.043 80	0.024 353	0.014 303	0.014 243	0.007 155	0.004 160	0.002 59	0.002 301
DCP 1	.010	4.480	1.809 130	0.985 78	0.265 61	0.162 21	0.073 331	0.032 300	0.033 281	0.066 223	0.042 181
DCP 2	.020	3.929	1.680 134	0.875 71	0.138 53	0.247 60	0.180 13	0.056 345	0.061 356	0.041 282	0.002 117
DCP 3	.030	3.362	1.544 132	0.573 68	0.176 111	0.204 56	0.102 44	0.105 34	0.078 2	0.052 11	0.065 345
DCP 4	.049	3.486	0.969 107	0.490 46	0.161 340	0.081 316	0.051 312	0.052 231	0.022 149	0.010 167	0.011 219
DCP 5	.074	2.929	0.876 97	0.367 22	0.083 294	0.066 326	0.037 293	0.034 211	0.023 133	0.008 148	0.008 119
DCP 6	.099	2.549	0.821 90	0.327 4	0.067 285	0.048 312	0.021 289	0.033 224	0.032 155	0.009 174	0.020 175
DCP 7	.149	2.027	0.765 72	0.292 349	0.106 291	0.084 279	0.055 219	0.048 172	0.042 132	0.028 94	0.014 84
DCP 8	.200	1.694	0.713 65	0.261 351	0.136 292	0.061 261	0.033 225	0.023 164	0.017 128	0.017 121	0.016 53
DCP 9	.250	1.466	0.712 53	0.288 336	0.198 270	0.090 193	0.037 174	0.041 136	0.024 94	0.032 78	0.033 1
DCP10	.300	1.322	0.691 47	0.295 332	0.196 256	0.068 203	0.063 170	0.036 95	0.005 33	0.032 58	0.026 321
DCP11	.399	1.095	0.612 43	0.259 327	0.185 245	0.052 216	0.088 164	0.043 78	0.019 613	0.054 54	0.017 291
DCP12	.501	0.847	0.517 33	0.215 304	0.159 211	0.064 170	0.105 127	0.064 43	0.001 78	0.048 2	0.019 253
DCP13	.600	0.633	0.434 25	0.187 280	0.157 185	0.075 148	0.112 95	0.062 13	0.044 24	0.065 308	0.030 204
DCP14	.701	0.557	0.350 15	0.154 253	0.125 158	0.069 107	0.099 50	0.050 323	0.034 343	0.046 237	0.020 96
DCP15	.800	0.364	0.282 359	0.134 245	0.090 147	0.072 97	0.079 27	0.038 294	0.022 312	0.032 187	0.018 89
DCP16	.900	0.117	0.171 352	0.107 249	0.066 130	0.050 90	0.056 2	0.035 267	0.020 264	0.035 146	0.015 95
DCP17	.969	0.016	0.064 351	0.052 270	0.030 135	0.023 82	0.027 29	0.013 304	0.014 293	0.010 160	0.007 84

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.54	0.230	0.298	2.67	0.0	17.38	12099.8	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
101.0 (331.4)	27229. (568.7)	0.49E 07	-0.223	1.662	19.09	-0.00168	1.407	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		17.381	2.666 0	0.062 76	0.081 63	0.051 156	0.020 313	0.010 76	0.005 70	0.016 94	0.004 265
CN		1.075	0.404 70	0.111 16	0.065 338	0.031 260	0.008 226	0.004 71	0.001 263	0.008 94	0.004 309
CM		-0.065	0.082 197	0.038 146	0.022 112	0.013 44	0.007 12	0.002 296	0.001 280	0.004 287	0.001 251
DCP 1	.010	3.800	1.657 154	0.612 147	0.276 165	0.116 183	0.098 196	0.051 172	0.070 180	0.027 148	0.016 157
DCP 2	.020	3.351	1.547 150	0.305 140	0.265 173	0.097 151	0.114 203	0.063 160	0.050 224	0.037 186	0.018 299
DCP 3	.030	2.880	1.380 135	0.261 171	0.173 147	0.076 172	0.048 183	0.045 218	0.035 205	0.022 235	0.014 346
DCP 4	.049	3.002	1.017 130	0.290 106	0.088 86	0.032 105	0.063 94	0.049 73	0.026 65	0.029 37	0.035 6
DCP 5	.074	2.474	0.863 114	0.176 93	0.082 49	0.015 229	0.032 62	0.024 76	0.005 79	0.014 353	0.019 341
DCP 6	.099	2.144	0.790 101	0.158 81	0.098 38	0.013 263	0.028 29	0.028 67	0.009 350	0.007 308	0.006 265
DCP 7	.149	1.782	0.682 61	0.188 63	0.132 22	0.034 347	0.032 29	0.033 57	0.013 42	0.023 24	0.018 338
DCP 8	.200	1.546	0.625 78	0.229 66	0.128 25	0.048 15	0.031 28	0.024 50	0.010 14	0.014 21	0.018 315
DCP 9	.250	1.387	0.611 70	0.231 43	0.134 4	0.073 350	0.032 342	0.031 2	0.015 308	0.013 310	0.031 240
DCP10	.300	1.298	0.592 65	0.230 32	0.141 4	0.075 336	0.032 344	0.020 315	0.009 296	0.017 342	0.012 283
DCP11	.399	1.162	0.507 60	0.231 16	0.151 2	0.075 323	0.052 329	0.051 305	0.014 303	0.019 310	0.021 282
DCP12	.501	0.959	0.506 49	0.209 358	0.125 336	0.087 280	0.045 280	0.033 262	0.016 271	0.027 208	0.009 236
DCP13	.600	0.741	0.429 40	0.180 339	0.119 310	0.092 247	0.054 226	0.044 174	0.020 176	0.033 165	0.017 150
DCP14	.701	0.654	0.366 29	0.160 325	0.108 283	0.084 223	0.059 192	0.033 137	0.011 121	0.036 100	0.020 89
DCP15	.800	0.477	0.280 20	0.134 312	0.094 260	0.073 194	0.044 155	0.022 58	0.007 247	0.033 93	0.013 47
DCP16	.900	0.204	0.150 20	0.082 308	0.051 253	0.049 165	0.025 143	0.023 65	0.019 68	0.015 53	0.015 333
DCP17	.969	0.044	0.081 42	0.038 298	0.033 276	0.026 183	0.022 138	0.021 93	0.011 66	0.011 51	0.000 351

FORCED PITCHING OSCILLATION   AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.51	0.228	0.300	2.71	0.0	19.89	12099.9	20

V	Q	RN	C(M(MIN)	C(M(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
101.5	27488.	0.49E 07	-0.196	1.383	20.35	-0.00444	3.744	0.0
(332.9)	(574.1)							

HARMONIC ANALYSES

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		19.891	2.713 0	0.040 331	0.075 160	0.029 147	0.028 359	0.009 344	0.015 189	0.013 154	0.010 346
CM		1.018	0.314 86	0.033 118	0.031 72	0.003 351	0.014 293	0.006 331	0.004 356	0.003 202	0.002 195
CR		-0.097	0.075 233	0.010 252	0.008 202	0.003 186	0.004 86	0.003 125	0.001 131	0.001 29	0.001 247
DCP 1	.010	2.679	1.342 176	0.203 265	0.105 213	0.054 314	0.017 41	0.015 189	0.015 56	0.019 200	0.040 311
DCP 2	.020	2.248	0.732 171	0.311 300	0.101 80	0.052 330	0.086 107	0.064 218	0.026 134	0.054 265	0.050 18
DCP 3	.030	1.803	0.333 128	0.095 240	0.035 27	0.021 18	0.010 181	0.064 262	0.018 315	0.004 348	0.008 121
DCP 4	.049	2.630	0.668 148	0.079 218	0.023 195	0.050 280	0.026 318	0.010 260	0.011 70	0.021 355	0.013 323
DCP 5	.074	2.165	0.463 122	0.062 210	0.033 103	0.015 347	0.025 339	0.013 356	0.010 49	0.013 273	0.012 235
DCP 6	.099	1.879	0.398 105	0.071 185	0.042 102	0.006 111	0.017 338	0.005 45	0.008 40	0.011 278	0.014 214
DCP 7	.149	1.600	0.344 88	0.073 121	0.048 85	0.019 136	0.007 338	0.008 117	0.009 336	0.005 172	0.006 76
DCP 8	.200	1.409	0.363 100	0.097 133	0.062 160	0.014 190	0.007 242	0.003 169	0.007 140	0.004 13	0.002 83
DCP 9	.250	1.290	0.368 97	0.050 135	0.046 112	0.021 220	0.003 291	0.009 236	0.020 33	0.021 178	0.014 239
DCP10	.300	1.223	0.386 93	0.051 148	0.058 100	0.024 208	0.019 316	0.015 115	0.011 316	0.012 108	0.025 208
DCP11	.399	1.126	0.427 89	0.069 130	0.067 92	0.019 175	0.030 312	0.026 57	0.013 346	0.012 71	0.026 208
DCP12	.501	0.977	0.415 78	0.078 110	0.068 70	0.019 107	0.034 307	0.028 28	0.008 228	0.007 10	0.013 112
DCP13	.600	0.808	0.401 70	0.068 93	0.052 46	0.020 53	0.030 275	0.027 0	0.005 65	0.005 174	0.018 50
DCP14	.701	0.765	0.381 60	0.056 62	0.042 16	0.024 7	0.012 287	0.025 292	0.007 20	0.013 201	0.009 8
DCP15	.800	0.588	0.308 51	0.036 30	0.031 341	0.030 338	0.016 248	0.029 279	0.006 324	0.006 240	0.004 244
DCP16	.900	0.263	0.195 48	0.017 19	0.023 347	0.017 343	0.007 211	0.009 237	0.007 215	0.008 238	0.002 19
DCP17	.949	0.061	0.084 54	0.002 157	0.009 351	0.006 301	0.016 209	0.019 221	0.008 343	0.010 237	0.002 339

FORCED PITCHING OSCILLATION   AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.49	0.230	0.300	2.71	0.0	9.92	12191.1	20

V	Q	RN	C(M(MIN)	C(M(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
108.8	29940.	0.49E 07	-0.198	1.119	3.16	-0.00081	3.744	0.0
(356.8)	(625.3)							

HARMONIC ANALYSES

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		9.921	2.713 0	0.137 320	0.114 190	0.029 97	0.015 317	0.026 71	0.029 86	0.025 156	0.010 315
CM		0.118	0.104 14	0.011 70	0.035 262	0.033 191	0.033 294	0.032 329	0.031 136	0.033 427	0.041 9
CR		-0.010	0.033 204	0.033 245	0.037 119	0.033 247	0.031 155	0.031 124	0.031 331	0.031 104	0.031 163

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

(table of harmonic analysis data — illegible due to image degradation)

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

HARMONIC ANALYSIS

(table of harmonic analysis data — illegible due to image degradation)

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

| 101.4 | 26621. |
| (332.6) | (556.0) |

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

| 101.2 | 26607. |
| (332.1) | (555.7) |

CONTENTS

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TIMER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	68.29	0.344	0.299	3.07	0.0	17.36	12191.A	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDO	EXT DAMP
100.9	26526.	0.49E 07	-0.268	1.954	20.51	0.00294	-2.531	0.0
(331.2)	(554.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		17.357	3.099	0	0.289	347	0.086	149	0.023	144	0.002	85	0.015	5	0.003	49	0.003	73	0.006	131
CN		1.248	0.525	33	0.154	285	0.065	204	0.015	83	0.009	186	0.015	121	0.003	50	0.003	77	0.002	81
CM		-0.080	0.114	149	0.054	76	0.014	329	0.013	236	0.007	164	0.001	13	0.002	118	0.003	110	0.001	4
CP 1	.010	3.202	2.136	116	0.446	72	0.521	116	0.374	74	0.132	29	0.080	323	0.081	271	0.028	185	0.013	56
CP 2	.020	3.713	1.994	114	0.301	31	0.435	121	0.261	56	0.110	62	0.035	67	0.068	96	0.060	47	0.023	33
CP 3	.030	3.204	1.779	115	0.187	67	0.345	134	0.128	88	0.147	91	0.092	131	0.094	92	0.091	97	0.065	83
CP 4	.040	3.402	1.247	91	0.529	20	0.126	312	0.140	322	0.126	255	0.028	191	0.040	257	0.046	205	0.033	200
CP 5	.074	2.914	1.140	77	0.302	356	0.090	292	0.122	331	0.098	228	0.044	179	0.037	200	0.040	141	0.033	83
CP 6	.100	2.568	1.300	67	0.337	341	0.398	279	0.097	299	0.073	217	0.027	190	0.022	193	0.009	126	0.015	136
CP 7	.149	2.134	1.050	48	0.352	330	0.158	268	0.086	272	0.092	217	0.052	155	0.021	116	0.006	71	0.014	37
CP 8	.200	1.833	0.945	48	0.421	332	0.133	259	0.084	292	0.114	219	0.049	162	0.022	138	0.023	119	0.006	175
CP 9	.250	1.668	0.954	35	0.450	318	0.176	246	0.119	243	0.096	177	0.071	144	0.044	82	0.030	49	0.013	5
CP10	.300	1.529	0.880	29	0.436	307	0.167	243	0.116	215	0.079	158	0.069	113	0.055	72	0.034	5	0.016	303
CP11	.390	1.357	0.822	75	0.405	331	0.194	237	0.151	182	0.076	132	0.054	82	0.027	72	0.026	54	0.029	338
CP12	.521	1.088	0.692	8	0.324	244	0.169	204	0.155	125	0.094	78	0.070	17	0.051	322	0.032	235	0.013	175
CP13	.600	0.904	0.619	352	0.327	334	0.144	172	0.163	89	0.097	22	0.051	321	0.051	267	0.027	153	0.028	140
CP14	.701	0.760	0.532	334	0.299	292	0.124	127	0.130	16	0.080	319	0.037	221	0.004	243	0.015	103	0.006	19
CP15	.800	0.554	0.387	322	0.266	177	0.090	91	0.106	1	0.042	275	0.033	161	0.006	227	0.017	347	0.009	170
CP16	.900	0.221	0.155	317	0.135	148	0.010	83	0.068	344	0.045	261	0.020	126	0.001	355	0.004	278	0.012	118
CP17	.960	0.377	0.388	332	0.089	161	0.053	42	0.028	302	0.017	354	0.030	241	0.031	105	0.021	304	0.015	213

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TIMER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	68.29	0.346	0.297	3.00	0.0	19.01	12131.S	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDO	EXT DAMP
100.6	26368.	0.49E 07	-0.279	1.769	22.30	-0.00106	1.633	0.0
(330.0)	(550.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		19.014	3.005	0	0.337	324	0.138	315	0.023	148	0.043	45	0.018	67	0.009	316	0.003	183	0.006	64
CN		1.125	0.496	53	0.119	353	0.357	261	0.015	174	0.006	1	0.026	159	0.003	77	0.006	338	0.003	150
CM		-0.110	0.122	233	0.030	132	0.013	63	0.025	334	0.001	329	0.001	278	0.002	315	0.002	74	0.001	184

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.03	0.085	0.404	2.63	0.0	0.00	12103.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
138.1	49020.	0.64E 07	-0.322	0.360	2.75	-0.00070	3.778	0.0
(453.2)	(1023.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.002	2.631 2	0.348 3	0.057 213	0.036 135	0.022 30	0.011 2	0.013 160	0.015 132	0.010 23
CN		0.119	0.242 353	0.005 357	0.001 143	0.001 192	0.001 183	0.001 299	0.001 52	0.000 108	0.001 127
CM		-0.015	0.006 305	0.000 164	0.000 312	0.000 267	0.000 81	0.000 198	0.000 277	0.001 290	0.000 351
DCP 1	.010	-0.594	1.649 347	0.061 33	0.017 122	0.005 178	0.007 207	0.003 246	0.003 298	0.012 262	0.002 44
DCP 2	.020	-0.365	1.241 350	0.025 352	0.009 140	0.011 194	0.006 242	0.002 234	0.004 314	0.013 288	0.003 70
DCP 3	.030	-0.377	1.039 350	0.019 313	0.003 117	0.037 197	0.004 249	0.002 243	0.004 316	0.006 290	0.002 156
DCP 4	.049	0.143	0.951 350	0.016 324	0.002 43	0.003 204	0.003 179	0.002 355	0.003 24	0.007 287	0.003 130
DCP 5	.074	0.274	0.697 350	0.012 335	0.031 192	0.001 271	0.001 138	0.004 357	0.001 23	0.036 296	0.004 127
DCP 6	.099	0.356	0.593 351	0.013 350	0.000 191	0.001 209	0.000 113	0.002 326	0.002 347	0.007 287	0.002 121
DCP 7	.149	0.247	0.479 351	0.010 13	0.007 318	0.007 235	0.003 144	0.004 336	0.003 57	0.006 315	0.001 185
DCP 8	.200	0.197	0.357 354	0.009 348	0.007 133	0.004 133	0.003 133	0.004 278	0.003 356	0.011 291	0.001 57
DCP 9	.250	0.176	0.315 353	0.003 334	0.001 257	0.003 178	0.003 155	0.001 191	0.002 71	0.003 52	0.001 88
DCP10	.300	0.182	0.268 352	0.005 358	0.001 109	0.001 102	0.002 157	0.002 306	0.001 209	0.002 60	0.001 86
DCP11	.399	0.164	0.211 354	0.006 358	0.001 238	0.003 190	0.003 339	0.004 275	0.001 355	0.004 148	0.003 92
DCP12	.501	0.118	0.164 359	0.004 349	0.004 179	0.002 249	0.002 217	0.002 219	0.002 154	0.002 147	0.001 277
DCP13	.600	0.146	0.134 1	0.004 88	0.003 177	0.002 247	0.001 284	0.001 277	0.002 131	0.006 114	0.003 315
DCP14	.701	0.296	0.386 2	0.003 18	0.002 157	0.002 324	0.001 207	0.002 232	0.001 249	0.002 142	0.002 140
DCP15	.800	0.084	0.054 9	0.002 317	0.002 67	0.001 164	0.002 159	0.003 19	0.004 34	0.005 93	0.002 126
DCP16	.900	-0.096	0.013 4	0.000 302	0.002 70	0.001 45	0.002 150	0.002 146	0.002 48	0.002 124	0.004 169
DCP17	.969	-0.045	0.009 158	0.002 276	0.001 26	0.004 115	0.006 343	0.007 24	0.002 190	0.004 78	0.001 325

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.06	0.086	0.404	2.63	0.0	2.47	12103.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
136.2	47957.	0.64E 07	-0.020	0.616	5.01	-0.00070	0.769	0.0
(446.7)	(1001.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.424	2.626 0	0.064 2	0.063 218	0.028 143	0.032 33	0.014 39	0.017 172	0.012 297	0.010 359
CN		0.369	0.245 353	0.005 6	0.003 256	0.001 233	0.001 294	0.001 75	0.003 118	0.005 345	0.000 151
CM		-0.011	0.006 311	0.000 254	0.001 33	0.000 75	0.001 103	0.000 233	0.001 294	0.002 143	0.000 182
DCP 1	.010	1.043	1.586 347	0.028 353	0.038 283	0.000 111	0.002 238	0.003 43	0.004 189	0.013 71	0.006 161
DCP 2	.020	0.993	1.275 350	0.026 338	0.009 292	0.001 227	0.002 273	0.002 85	0.005 213	0.014 82	0.004 201
DCP 3	.030	0.994	1.095 350	0.023 355	0.010 302	0.001 240	0.001 124	0.001 87	0.004 222	0.030 63	0.003 166
DCP 4	.049	1.324	0.994 350	0.017 340	0.005 273	0.003 80	0.005 69	0.005 153	0.001 242	0.008 71	0.001 185
DCP 5	.074	0.994	0.719 350	0.013 337	0.007 298	0.006 52	0.003 58	0.001 161	0.001 186	0.006 89	0.005 190
DCP 6	.099	0.370	0.605 351	0.014 350	0.005 304	0.002 110	0.004 22	0.004 138	0.002 219	0.004 85	0.004 176
DCP 7	.149	0.308	0.453 351	0.007 347	0.004 276	0.035 222	0.005 94	0.007 177	0.001 297	0.007 107	0.002 149
DCP 8	.200	0.570	0.372 354	0.008 6	0.011 301	0.004 76	0.003 145	0.001 333	0.001 315	0.010 71	0.001 123
DCP 9	.250	0.500	0.316 353	0.008 9	0.003 230	0.001 320	0.001 69	0.002 74	0.002 74	0.008 140	0.000 289
DCP10	.300	0.462	0.263 354	0.000 24	0.003 252	0.003 180	0.000 229	0.006 20	0.002 13	0.006 305	0.001 278
DCP11	.399	0.384	0.212 358	0.007 21	0.003 210	0.001 226	0.004 299	0.004 68	0.001 137	0.010 327	0.000 31
DCP12	.501	0.286	0.161 358	0.004 37	0.005 212	0.004 234	0.006 287	0.000 89	0.006 92	0.007 301	0.002 153
DCP13	.600	0.272	0.122 1	0.004 358	0.003 225	0.003 155	0.003 264	0.002 157	0.003 87	0.008 334	0.001 14
DCP14	.701	0.295	0.084 2	0.002 29	0.001 199	0.001 286	0.002 293	0.004 36	0.006 124	0.006 343	0.002 295
DCP15	.800	0.134	0.049 10	0.003 67	0.001 91	0.002 346	0.004 157	0.001 41	0.004 132	0.006 353	0.003 274
DCP16	.900	-0.085	0.018 14	0.001 11	0.006 239	0.003 273	0.005 327	0.001 279	0.005 141	0.012 312	0.006 48
DCP17	.969	-0.049	0.011 191	0.002 1	0.002 333	0.002 162	0.002 295	0.004 93	0.006 89	0.006 345	0.001 37

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.12	0.087	0.409	2.63	0.0	4.89	12103.3	20

V	Q.	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
134.7	47090	0.63E 07	-0.015	0.968	7.55	-0.00088	3.951	0.0
(441.9)	(983.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		4.890	2.632	0	0.060	7	0.050	228	0.031	124	0.024	37	0.016	69	0.017	177	0.004	92	0.013	19
CN		0.626	0.244	354	0.005	24	0.002	24	0.001	225	0.001	233	0.000	242	0.001	171	0.003	16	0.001	81
CM		-0.006	0.008	310	0.001	258	0.001	193	0.000	70	0.000	20	0.000	92	0.003	291	0.001	222	0.000	270
DCP 1	.010	2.727	1.642	347	0.050	279	0.026	145	0.005	49	0.003	227	0.007	67	0.006	140	0.009	266	0.002	113
DCP 2	.020	2.234	1.295	350	0.022	327	0.007	116	0.003	240	0.005	141	3.037	70	0.002	152	0.008	293	0.002	24
DCP 3	.030	2.126	1.086	350	0.019	356	0.008	148	0.003	102	0.005	149	0.006	69	0.004	157	0.007	310	0.002	293
DCP 4	.049	1.977	0.923	350	0.015	333	0.001	295	0.001	156	0.001	218	0.003	113	0.005	224	0.005	265	0.001	131
DCP 5	.074	1.763	0.732	350	0.012	351	0.004	316	0.000	70	0.002	255	0.003	82	0.002	311	0.003	312	0.002	155
DCP 6	.099	1.617	0.603	351	0.009	8	0.004	2	0.001	183	0.001	226	0.004	104	0.004	266	0.002	290	0.002	162
DCP 7	.149	1.184	0.464	351	0.014	24	0.004	114	0.005	254	0.004	243	0.001	109	0.005	195	0.004	340	0.001	204
DCP 8	.200	0.960	0.367	354	0.006	21	0.002	349	0.002	194	0.004	333	0.002	156	0.005	272	0.003	291	0.003	270
DCP 9	.250	0.823	0.309	354	0.007	12	0.002	17	0.002	108	0.002	236	0.004	126	0.004	98	0.002	17	0.002	47
DCP10	.300	0.775	0.259	355	0.007	48	0.002	51	0.003	115	0.002	223	0.003	233	0.001	115	0.003	25	0.002	70
DCP11	.399	0.603	0.205	359	0.007	48	0.002	343	0.001	93	0.002	294	0.003	274	0.002	181	0.006	40	0.002	47
DCP12	.501	0.453	0.160	0	0.006	39	0.003	309	0.003	308	0.003	182	0.001	10	0.002	98	0.004	5	0.003	63
DCP13	.600	0.394	0.119	4	0.008	24	0.002	27	0.001	81	0.001	37	0.001	265	0.002	325	0.005	26	0.001	168
DCP14	.701	0.380	0.081	7	0.004	59	0.004	35	0.002	246	0.002	248	0.003	332	0.001	44	0.004	17	0.003	337
DCP15	.800	0.186	0.045	13	0.005	92	0.005	19	0.004	213	0.003	61	0.001	159	0.001	170	0.004	35	0.004	90
DCP16	.900	-0.064	0.019	22	0.003	348	0.002	324	0.002	309	0.002	210	0.004	273	0.003	102	0.002	13	0.002	210
DCP17	.969	-0.062	0.005	193	0.004	124	0.005	68	0.001	198	0.002	216	0.002	207	0.004	293	0.010	69	0.005	107

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.01	0.088	0.396	2.63	0.0	7.39	12103.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
133.3	46319.	0.63E 07	-0.009	1.087	10.02	-0.00114	1.216	0.0
(437.3)	(967.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.386	2.634	0	0.060	14	0.051	233	0.023	119	0.024	27	0.013	70	0.015	177	0.001	63	0.010	0
CN		0.873	0.222	358	0.021	28	0.011	291	0.002	132	0.001	252	0.002	127	0.001	293	0.004	45	0.001	87
CM		0.002	0.012	321	0.003	221	0.002	133	0.003	254	0.000	27	0.000	306	0.001	91	0.001	206	0.000	126
DCP 1	.010	4.705	2.342	349	0.080	207	0.144	324	0.097	234	0.021	180	0.026	197	0.024	109	0.011	88	0.013	82
DCP 2	.020	3.569	1.398	353	0.119	300	0.141	177	0.131	77	0.053	347	0.016	21	0.029	334	0.023	226	0.015	152
DCP 3	.030	3.293	0.974	351	0.074	43	0.036	323	0.014	78	0.010	341	0.008	239	0.004	132	0.012	109	0.003	82
DCP 4	.049	2.895	0.817	352	0.074	46	0.032	331	0.017	234	0.004	91	0.035	83	0.035	58	0.034	20
DCP 5	.074	2.502	0.659	352	0.048	37	0.015	374	0.005	235	0.001	188	0.002	78	0.006	74	0.001	26
DCP 6	.099	2.213	0.541	354	0.035	34	0.014	114	0.004	171	0.002	196	0.002	47	0.004	99	0.003	87	0.001	57
DCP 7	.149	1.651	0.413	354	0.024	19	0.007	295	0.002	136	0.003	331	0.004	73	0.001	291	0.005	91	0.000	227
DCP 8	.200	1.333	0.340	358	0.021	24	0.003	204	0.002	154	0.001	5	0.001	122	0.001	318	0.005	149	0.005	108
DCP 9	.250	1.117	0.286	357	0.019	22	0.009	274	0.003	167	0.004	52	0.003	167	0.001	174	0.005	31	0.005	58
DCP10	.300	1.001	0.231	357	0.019	19	0.013	272	0.002	85	0.001	68	0.003	121	0.001	234	0.003	34	0.002	34
DCP11	.399	0.813	0.185	7	0.021	33	0.011	297	0.005	114	0.001	137	0.002	133	0.001	55	0.005	51	0.001	150
DCP12	.501	0.612	0.137	7	0.021	31	0.009	240	0.003	207	0.001	139	0.001	323	0.005	46	0.002	141
DCP13	.600	0.505	0.035	16	0.021	42	0.012	299	0.002	226	0.002	121	0.000	88	0.001	58	0.002	0	0.004	107
DCP14	.701	0.452	0.052	27	0.023	35	0.011	285	0.001	144	0.001	231	0.001	139	0.004	272	0.005	47	0.001	302
DCP15	.800	0.219	0.031	42	0.018	46	0.012	297	0.002	234	0.002	191	0.035	43	0.035	285	0.035	29	0.001	329
DCP16	.900	-0.056	0.011	45	0.011	20	0.010	272	0.003	50	0.003	291	0.035	212	0.001	264	0.006	344	0.001	312
DCP17	.969	-0.067	0.003	64	0.007	11	0.005	112	0.002	38	0.005	219	0.004	47	0.002	208	0.038	91	0.001	293

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ 0.0	DRIVE HZ 23.34	K 0.088	MACH NO 0.395	DEL.ALPHA 2.64	DEL.H 0.0	ALPHA.0 9.87	TEST POINT 12133.5	CYCLES ANALYSED 20
V 132.8 (435.6)	Q 46070. (962.2)	RN 0.63E 07	CN(MIN) -0.032	CN(MAX) 1.214	ALPHA.NMAX 11.96	AERO DAMP -0.00167	TDP 1.478	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		5.868	2.641 0	0.066 16	0.049 274	0.014 106	0.025 7	0.005 232	0.011 141	0.015 56	0.008 350
CN		1.015	0.115 42	0.072 28	0.016 263	0.003 157	0.004 236	0.004 141	0.003 69	0.007 43	0.002 341
CM		0.011	0.014 105	0.007 108	0.006 355	0.004 262	0.001 183	0.001 223	0.002 59	0.002 211	0.001 65
DCP 1	.010	5.777	0.500 342	0.766 84	0.166 61	0.023 14	0.074 125	0.013 47	0.009 45	0.012 3	0.018 287
DCP 2	.020	4.551	0.820 9	0.270 66	0.328 16	0.122 311	0.102 352	0.050 345	0.058 342	0.022 25	0.021 351
DCP 3	.030	4.377	0.725 16	0.269 18	0.114 340	0.134 299	0.084 256	0.055 239	0.038 213	0.024 167	0.011 168
DCP 4	.049	3.470	0.346 22	0.248 46	0.084 332	0.071 278	0.054 230	0.029 203	0.019 193	0.022 140	0.015 148
DCP 5	.074	2.922	0.226 25	0.213 53	0.072 328	0.049 252	0.032 192	0.017 132	0.006 63	0.028 107	0.004 159
DCP 6	.099	2.540	0.175 32	0.193 55	0.044 332	0.040 249	0.020 190	0.009 183	0.005 103	0.009 96	0.003 110
DCP 7	.149	1.947	0.335 29	0.145 22	0.064 278	0.032 204	0.010 177	0.014 170	0.021 109	0.020 47	0.037 336
DCP 8	.200	1.590	0.232 31	0.126 11	0.044 267	0.024 193	0.014 161	0.019 129	0.023 65	0.014 15	0.005 245
DCP 9	.250	1.342	0.191 34	0.110 9	0.060 249	0.028 162	0.006 102	0.013 120	0.016 55	0.013 350	0.006 251
DCP10	.300	1.158	0.152 39	0.088 8	0.039 240	0.017 194	0.002 208	0.011 113	0.013 12	0.004 7	0.002 155
DCP11	.399	0.925	0.118 54	0.072 14	0.030 233	0.016 139	0.009 311	0.009 167	0.005 56	0.007 48	0.003 167
DCP12	.501	0.684	0.095 70	0.062 17	0.023 228	0.016 89	0.005 313	0.001 71	0.001 334	0.007 53	0.002 14
DCP13	.600	0.531	0.085 100	0.052 19	0.022 235	0.016 72	0.008 304	0.003 167	0.002 170	0.006 57	0.003 299
DCP14	.701	0.413	0.092 125	0.032 23	0.024 171	0.020 61	0.007 284	0.003 148	0.003 290	0.004 30	0.002 336
DCP15	.800	0.223	0.051 101	0.018 321	0.019 154	0.012 60	0.003 135	0.005 34	0.006 346	0.007 50	0.003 242
DCP16	.900	-0.025	0.045 26	0.030 254	0.015 141	0.001 230	0.003 158	0.007 11	0.005 139	0.012 26	0.008 248
DCP17	.969	-0.051	0.031 4	0.019 276	0.007 156	0.004 129	0.006 69	0.002 276	0.001 357	0.000 337	0.004 189

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ 0.0	DRIVE HZ 23.03	K 0.085	MACH NO 0.405	DEL.ALPHA 2.52	DEL.H 0.0	ALPHA.0 12.43	TEST POINT 12105.1	CYCLES ANALYSED 20
V 137.3 (450.4)	Q 48675. (1010.6)	RN 0.64E 07	CN(MIN) -0.049	CN(MAX) 1.200	ALPHA.NMAX 12.13	AERO DAMP -0.00115	TDP 1.264	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.432	2.521 0	0.055 30	0.060 127	0.046 115	0.027 197	0.027 290	0.053 248	0.042 209	0.007 56
CN		1.014	0.145 104	0.016 107	0.028 90	0.014 84	0.010 312	0.007 290	0.004 224	0.007 192	0.002 89
CM		-0.008	0.035 193	0.009 93	0.007 157	0.003 163	0.004 100	0.002 109	0.002 350	0.001 20	0.000 180
DCP 1	.010	5.348	1.176 194	0.172 103	0.115 241	0.021 176	0.034 359	0.050 27	0.091 353	0.036 277	0.022 100
DCP 2	.020	4.436	0.872 162	0.249 130	0.110 234	0.028 168	0.034 263	0.043 17	0.060 357	0.034 301	0.017 72
DCP 3	.030	3.899	0.538 140	0.325 175	0.219 162	0.175 160	0.086 175	0.027 183	0.034 290	0.031 278	0.012 313
DCP 4	.049	3.217	0.568 151	0.225 108	0.121 137	0.096 135	0.004 53	0.044 267	0.048 248	0.021 245	0.013 253
DCP 5	.074	2.662	0.561 152	0.168 95	0.115 121	0.083 98	0.026 40	0.012 281	0.023 243	0.013 197	0.006 176
DCP 6	.099	2.331	0.514 146	0.124 80	0.105 115	0.055 68	0.020 319	0.014 259	0.028 249	0.016 208	0.009 221
DCP 7	.149	1.841	0.380 121	0.071 70	0.121 134	0.043 73	0.022 89	0.004 268	0.014 218	0.014 174	0.010 153
DCP 8	.200	1.555	0.304 106	0.048 62	0.099 89	0.020 76	0.022 81	0.002 47	0.016 160	0.021 130	0.011 95
DCP 9	.250	1.364	0.253 93	0.028 41	0.074 65	0.015 44	0.027 3	0.039 272	0.034 195	0.007 133	0.009 58
DCP10	.300	1.178	0.213 94	0.006 14	0.063 66	0.024 78	0.023 3	0.031 312	0.009 212	0.016 138	0.008 104
DCP11	.399	0.961	0.179 72	0.021 280	0.044 49	0.011 55	0.024 329	0.008 313	0.015 241	0.010 160	0.005 40
DCP12	.501	0.740	0.146 61	0.022 253	0.033 77	0.010 44	0.023 290	0.005 298	0.008 274	0.005 165	0.007 37
DCP13	.600	0.589	0.117 59	0.038 246	0.027 3	0.005 61	0.027 290	0.010 277	0.010 186	0.010 241	0.006 159
DCP14	.701	0.462	0.085 57	0.040 246	0.022 340	0.003 243	0.020 267	0.009 303	0.011 187	0.004 242	0.002 56
DCP15	.800	0.278	0.097 20	0.015 247	0.020 326	0.011 31	0.014 263	0.013 296	0.004 194	0.006 205	0.003 30
DCP16	.900	0.045	0.106 6	0.014 8	0.011 290	0.013 359	0.005 244	0.007 262	0.003 90	0.011 200	0.004 278
DCP17	.969	-0.010	0.051 0	0.011 18	0.007 282	0.002 328	0.004 235	0.005 336	0.004 137	0.004 227	0.006 267

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.19	0.087	0.430	2.49	0.0	14.85	12105.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
134.9	47138.	0.63E 07	-0.086	1.174	14.00	-0.00193	2.090	0.0
(442.7)	(984.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		14.846	2.494	0	0.053	10	0.029	202	0.014	114	0.014	316	0.017	281	0.034	2	0.012	277	0.011	340
CN		1.019	0.115	95	0.025	159	0.012	220	0.006	159	0.004	211	0.004	172	0.002	191	0.005	211	0.004	53
CM		-0.035	0.348	194	0.010	191	0.003	205	0.004	279	0.002	297	0.001	225	0.000	176	0.002	64	0.000	203
DCP 1	.010	4.689	1.274	191	0.098	305	0.024	149	0.044	303	0.057	285	0.053	223	0.019	231	0.029	130	0.015	357
DCP 2	.020	3.977	0.974	180	0.175	248	0.266	307	0.018	338	0.065	300	0.020	290	0.022	288	0.035	123	0.042	23
DCP 3	.030	3.600	0.813	174	0.267	221	0.167	284	0.090	324	0.047	338	0.021	339	0.013	198	0.014	141	0.038	42
DCP 4	.049	2.653	0.781	165	0.087	207	0.067	279	0.029	267	0.012	313	0.014	171	0.011	149	0.012	273	0.008	80
DCP 5	.074	2.427	0.592	157	0.095	236	0.037	231	0.050	241	0.031	247	0.021	193	0.002	331	0.008	185	0.008	114
DCP 6	.099	2.162	0.441	145	0.101	230	0.009	173	0.035	225	0.030	233	0.030	166	0.008	181	0.012	116	0.022	28
DCP 7	.149	1.769	0.395	125	0.127	197	0.024	240	0.027	262	0.027	250	0.012	161	0.020	174	0.012	152	0.009	306
DCP 8	.200	1.528	0.229	110	0.106	177	0.029	240	0.021	252	0.032	264	0.001	154	0.036	189	0.013	144	0.030	162
DCP 9	.250	1.365	0.203	86	0.095	142	0.032	247	0.013	186	0.031	227	0.018	195	0.034	121	0.007	102	0.009	100
DCP10	.300	1.199	0.186	70	0.076	141	0.029	235	0.014	199	0.025	223	0.014	195	0.026	145	0.002	226	0.006	62
DCP11	.395	1.018	0.185	51	0.049	125	0.036	238	0.036	158	0.011	135	0.013	219	0.013	266	0.012	228	0.012	112
DCP12	.501	0.797	0.177	43	0.037	190	0.022	164	0.016	88	0.008	159	0.011	177	0.010	14	0.009	179	0.009	49
DCP13	.600	0.636	0.164	34	0.026	64	0.015	136	0.015	100	0.007	167	0.010	137	0.003	93	0.013	259	0.003	207
DCP14	.721	0.527	0.160	23	0.027	35	0.013	120	0.023	86	0.007	152	0.004	6	0.005	91	0.006	279	0.004	217
DCP15	.800	0.378	0.136	25	0.034	29	0.012	56	0.012	141	0.004	148	0.009	52	0.002	158	0.006	204	0.002	17
DCP16	.900	0.134	0.095	19	0.026	32	0.033	95	0.009	96	0.006	57	0.009	22	0.005	294	0.009	205	0.002	141
DCP17	.969	0.138	0.044	21	0.011	34	0.007	24	0.005	88	0.002	23	0.005	60	0.002	251	0.006	212	0.002	166

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.96	0.088	0.396	2.51	0.0	17.31	12105.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
133.5	46358.	0.63E 07	-0.104	1.137	16.19	-0.00199	2.133	0.0
(438.1)	(968.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		17.312	2.526	0	0.061	17	0.034	215	0.013	149	0.021	24	0.017	7	0.013	73	0.006	151	0.002	51
CN		0.991	0.118	94	0.016	174	0.012	203	0.009	163	0.002	314	0.006	223	0.004	310	0.002	296	0.002	316
CM		-0.072	0.334	201	0.003	316	0.002	96	0.001	35	0.000	98	0.002	16	0.001	108	0.001	20	0.000	222
DCP 1	.010	3.920	0.725	192	0.160	305	0.068	47	0.045	237	0.035	15	0.015	54	0.034	224	0.029	293	0.053	33
DCP 2	.020	3.331	0.618	172	0.054	271	0.040	32	0.026	293	0.034	43	0.017	229	0.009	23	0.018	289	0.026	28
DCP 3	.030	2.967	0.697	183	0.091	355	0.034	249	0.018	164	0.040	9	0.021	292	0.014	13	0.007	290	0.031	20
DCP 4	.049	2.270	0.401	159	0.358	238	0.054	137	0.036	147	0.028	155	0.014	337	0.017	133	0.034	9	0.020	168
DCP 5	.074	1.911	0.433	139	0.068	196	0.029	141	0.032	147	0.016	191	0.014	297	0.026	35	0.013	175	0.022	305
DCP 6	.099	1.755	0.337	174	0.068	186	0.023	169	0.017	145	0.019	222	0.015	236	0.007	49	0.012	2	0.015	243
DCP 7	.149	1.536	0.260	112	0.047	180	0.005	113	0.024	137	0.039	274	0.013	189	0.010	251	0.012	155	0.009	267
DCP 8	.200	1.412	0.213	107	0.027	187	0.012	136	0.012	181	0.011	16	0.006	305	0.011	104	0.009	120	0.007	244
DCP 9	.250	1.332	0.188	91	0.074	176	0.018	71	0.007	144	0.009	18	0.010	239	0.014	137	0.014	86	0.006	345
DCP10	.300	1.214	0.164	83	0.017	190	0.012	20	0.023	78	0.037	17	0.013	157	0.013	174	0.007	309	0.005	27
DCP11	.395	1.075	0.148	68	0.013	165	0.009	265	0.002	278	0.008	281	0.008	333	0.016	157	0.007	333	0.007	255
DCP12	.501	0.897	0.133	54	0.018	178	0.012	242	0.005	179	0.009	374	0.003	157	0.007	120	0.004	128	0.005	167
DCP13	.600	0.751	0.132	44	0.023	169	0.011	249	0.010	170	0.002	18	0.009	237	0.002	62	0.006	179	0.002	41
DCP14	.701	0.640	0.122	35	0.016	157	0.005	238	0.008	172	0.005	212	0.012	233	0.007	298	0.009	252	0.004	143
DCP15	.800	0.482	0.116	29	0.011	158	0.005	298	0.005	232	0.003	323	0.014	179	0.004	283	0.004	302	0.004	34
DCP16	.900	0.278	0.074	35	0.006	114	0.008	323	0.007	214	0.003	200	0.017	211	0.004	269	0.030	159	0.002	189
DCP17	.969	0.061	0.027	47	0.006	91	0.008	271	0.005	175	0.004	179	0.008	231	0.005	337	0.006	237	0.003	288

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	27.99	0.088	0.394	2.54	0.0	19.84	12105.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDW	EXT DAMP
132.7	46037.	0.63E 07	-0.127	1.799	19.88	-0.00239	2.555	0.0
(435.9)	(961.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		15.841	2.544 0	0.060 15	0.051 217	0.008 87	0.024 22	0.010 93	0.014 123	0.013 102	0.037 9
CN		1.978	0.111 94	0.016 153	0.026 113	0.002 304	0.003 334	0.007 359	0.003 342	0.006 125	0.004 259
CM		-0.096	0.023 271	0.005 262	0.002 240	0.002 304	0.031 197	0.031 150	0.031 157	0.030 179	0.037 45
OCP 1	.010	3.264	0.437 182	0.036 213	0.048 355	0.035 355	0.029 55	0.008 120	0.038 214	0.017 105	0.035 57
OCP 2	.020	2.695	0.616 175	0.060 128	0.025 318	0.022 11	0.012 318	0.003 344	0.023 138	0.019 146	0.029 95
OCP 3	.030	2.347	0.676 169	0.043 263	0.036 137	0.005 258	0.026 334	0.036 106	0.034 344	0.017 142	0.014 195
OCP 4	.049	1.898	0.271 138	0.069 258	0.046 145	0.020 276	0.018 243	0.015 23	0.009 128	0.024 153	0.017 317
OCP 5	.074	1.698	0.234 111	0.060 217	0.017 145	0.022 229	0.009 316	0.012 13	0.012 83	0.021 131	0.003 93
OCP 6	.099	1.434	0.230 104	0.043 205	0.016 169	0.018 205	0.011 255	0.018 91	0.005 239	0.013 127	0.002 300
OCP 7	.149	1.480	0.192 97	0.034 197	0.011 227	0.008 218	0.017 266	0.013 72	0.006 101	0.013 139	0.003 298
OCP 8	.200	1.362	0.159 91	0.025 216	0.037 207	0.014 303	0.009 344	0.010 347	0.009 8	0.014 168	0.032 20
OCP 9	.250	1.256	0.151 99	0.045 164	0.016 143	0.011 251	0.005 260	0.012 342	0.007 15	0.009 85	0.036 342
OCP10	.300	1.207	0.139 97	0.034 157	0.014 116	0.011 188	0.008 182	0.017 326	0.036 322	0.009 143	0.008 289
OCP11	.399	1.132	0.133 91	0.031 149	0.010 117	0.008 159	0.007 138	0.005 351	0.007 279	0.036 142	0.011 272
OCP12	.501	0.942	0.120 40	0.023 132	0.013 54	0.005 18	0.308 51	0.036 16	0.002 334	0.000 117	0.006 351
OCP13	.600	0.812	0.109 65	0.020 102	0.035 95	0.013 348	0.013 11	0.011 48	0.034 16	0.013 36	0.037 246
OCP14	.701	0.722	0.103 40	0.025 77	0.036 59	0.029 10	0.006 14	0.003 264	0.005 235	0.037 66	0.008 230
OCP15	.800	0.570	0.091 40	0.025 70	0.007 112	0.005 76	0.010 343	0.010 348	0.003 156	0.004 310	0.014 226
OCP16	.900	0.252	0.363 62	0.010 58	0.007 42	0.005 38	0.004 245	0.038 297	0.004 324	0.008 284	0.007 188
OCP17	.960	0.073	0.028 73	0.033 124	0.034 16	0.033 309	0.001 162	0.005 164	0.032 105	0.004 314	0.005 121

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	45.67	0.168	0.409	2.84	0.0	0.02	12107.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDW	EXT DAMP
138.8	49379.	0.65E 07	-0.028	0.356	2.99	-0.00074	3.846	0.0
(455.3)	(1031.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.022	2.840 0	0.088 350	0.179 351	0.034 98	0.021 77	0.010 131	0.011 127	0.009 189	0.011 342
CN		0.123	0.225 357	0.005 1	0.004 312	0.009 117	0.002 271	0.031 267	0.003 172	0.001 44	0.032 76
CM		-0.014	0.012 296	0.001 240	0.001 278	0.031 305	0.001 133	0.000 119	0.003 47	0.000 297	0.000 252
OCP 1	.010	-0.581	1.503 343	0.054 18	0.026 242	0.023 94	0.009 143	0.002 256	0.004 51	0.005 78	0.004 299
OCP 2	.020	-0.346	1.196 348	0.026 342	0.032 266	0.028 122	0.005 205	0.005 240	0.002 151	0.012 15	0.005 4
OCP 3	.030	-0.073	0.998 347	0.023 304	0.014 267	0.018 129	0.001 166	0.003 317	0.004 336	0.034 310	0.031 294
OCP 4	.049	0.163	0.916 348	0.020 302	0.019 289	0.017 98	0.003 185	0.033 157	0.004 32	0.004 7	0.034 63
OCP 5	.074	0.279	0.671 348	0.015 323	0.014 290	0.016 96	0.004 175	0.004 267	0.003 177	0.007 313	0.032 67
OCP 6	.099	0.356	0.567 350	0.012 324	0.014 293	0.018 97	0.008 207	0.001 262	0.004 241	0.005 324	0.001 80
OCP 7	.149	0.251	0.421 351	0.010 11	0.015 249	0.015 131	0.004 158	0.002 277	0.001 305	0.001 325	0.002 143
OCP 8	.200	0.208	0.344 359	0.011 347	0.007 307	0.017 101	0.002 142	0.005 260	0.004 40	0.004 356	0.006 349
OCP 9	.250	0.190	0.295 355	0.011 331	0.007 331	0.009 129	0.005 276	0.003 83	0.004 142	0.036 65	0.002 169
OCP10	.300	0.182	0.248 356	0.003 26	0.031 337	0.009 141	0.003 274	0.003 143	0.001 274	0.033 99	0.001 278
OCP11	.399	0.173	0.196 7	0.003 65	0.001 355	0.007 131	0.006 320	0.001 115	0.002 111	0.005 177	0.002 102
OCP12	.501	0.123	0.141 11	0.005 21	0.031 344	0.007 118	0.004 186	0.002 162	0.003 128	0.002 181	0.007 111
OCP13	.600	0.137	0.117 18	0.002 42	0.034 343	0.002 154	0.004 215	0.002 143	0.005 30	0.003 117	0.003 42
OCP14	.701	0.221	0.041 71	0.005 85	0.004 9	0.008 118	0.004 328	0.036 316	0.005 6	0.037 249	0.003 42
OCP15	.800	0.303	0.050 32	0.006 7	0.031 43	0.005 99	0.003 312	0.003 274	0.007 227	0.003 73	0.004 5
OCP16	.900	-0.089	0.016 68	0.001 42	0.007 46	0.011 171	0.003 331	0.007 312	0.002 270	0.003 278	0.003 89
OCP17	.960	-0.041	0.015 181	0.006 1	0.031 265	0.008 124	0.005 316	0.005 98	0.003 72	0.034 119	0.002 276

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNER HZ 0.0	DRIVE HZ 45.70	K 0.171	MACH NO 0.404	DEL.ALPHA 2.84	DEL.H 0.0	ALPHA.0 2.42	TEST POINT 12107.2	CYCLES ANALYSED 23
	V 136.5 (447.7)	Q 48287. (1008.5)	RN 0.64E 07	CN(MIN) -0.324	CN(MAX) 0.593	ALPHA.NMAX 5.31	AERO DAMP -2.00075	TDP 3.850	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.418	2.837 0	0.087 357	0.096 261	0.324 50	0.035 64	0.013 61	0.014 195	0.009 299	0.007 352
CN		0.372	0.228 357	0.007 17	0.035 330	0.007 2	0.001 64	0.001 183	0.001 274	0.002 288	0.001 42
CM		-0.011	0.012 294	0.001 244	0.001 271	0.002 173	0.001 196	0.000 255	0.002 114	0.001 130	0.000 216
CP 1	.013	1.254	1.519 343	0.031 352	0.022 279	0.011 3	0.007 188	0.002 36	0.006 108	0.002 148	0.006 332
CP 2	.020	0.919	1.219 348	0.029 345	0.016 296	0.010 9	0.005 170	0.004 166	0.004 237	0.006 170	0.005 5
CP 3	.030	1.036	1.245 347	0.022 332	0.015 292	0.038 16	0.006 204	0.002 73	0.005 196	0.003 62	0.004 53
CP 4	.049	1.040	0.895 348	0.016 323	0.013 311	0.007 65	0.004 217	0.002 185	0.007 183	0.002 309	0.001 28
CP 5	.074	1.004	0.647 348	0.015 316	0.011 291	0.009 38	0.001 178	0.004 141	0.004 103	0.002 24	0.002 30
CP 6	.099	0.976	0.576 349	0.016 K	0.016 328	0.001 138	0.008 133	0.002 333	0.006 235	0.006 202	0.003 69
CP 7	.145	0.711	0.422 357	0.008 318	0.006 4	0.005 78	0.006 104	0.005 141	0.001 58	0.005 106	0.003 353
CP 8	.200	0.579	0.356 357	0.007 5	0.006 286	0.010 46	0.006 113	0.005 214	0.003 283	0.004 8	0.005 171
CP 9	.253	0.503	0.305 355	0.011 25	0.009 336	0.004 324	0.002 158	0.002 250	0.002 323	0.004 230	0.002 357
CP10	.300	0.456	0.247 356	0.011 6	0.012 316	0.008 339	0.003 155	0.004 133	0.002 277	0.002 317	0.003 4
CP11	.399	0.390	0.199 7	0.013 32	0.009 339	0.011 359	0.004 61	0.004 244	0.005 4	0.005 264	0.005 107
CP12	.501	0.287	0.152 17	0.008 52	0.002 333	0.008 4	0.002 260	0.003 53	0.001 178	0.005 230	0.001 311
CP13	.600	0.266	0.115 16	0.005 64	0.006 344	0.012 330	0.005 336	0.005 313	0.007 263	0.001 207	0.002 40
CP14	.701	0.288	0.091 23	0.004 27	0.006 21	0.005 355	0.004 31	0.002 37	0.005 216	0.004 36	0.002 52
CP15	.800	0.140	0.064 31	0.005 68	0.003 76	0.014 23	0.007 147	0.005 151	0.004 27	0.005 283	0.005 331
CP16	.900	-0.074	0.023 44	0.007 68	0.006 18	0.006 330	0.008 82	0.001 174	0.004 191	0.004 11	0.001 71
CP17	.969	-0.062	0.016 148	0.036 328	0.007 248	0.011 350	0.001 343	0.002 69	0.007 0	0.005 287	0.005 153

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNER HZ 0.0	DRIVE HZ 45.67	K 0.172	MACH NO 0.399	DEL.ALPHA 2.84	DEL.H 0.0	ALPHA.0 4.94	TEST POINT 12107.3	CYCLES ANALYSED 20
	V 135.0 (442.3)	Q 47320. (988.3)	RN 0.64E 07	CN(MIN) -0.024	CN(MAX) 0.870	ALPHA.NMAX 7.94	AERO DAMP -0.00075	TDP 0.824	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.939	2.837 0	0.076 357	0.065 257	0.079 102	0.028 70	0.013 67	0.014 200	0.012 175	0.010 84
CN		0.629	0.228 357	0.005 22	0.002 314	0.016 113	0.001 241	0.001 43	0.001 280	0.001 186	0.002 89
CM		-0.036	0.012 302	0.001 273	0.000 311	0.005 280	0.001 31	0.000 261	0.000 110	0.001 358	0.001 294
CP 1	.010	2.739	1.582 343	0.050 270	0.013 146	0.021 98	0.006 233	0.007 331	0.010 273	0.004 222	0.006 84
CP 2	.020	2.242	1.232 348	0.022 331	0.005 256	0.019 142	0.002 203	0.010 10	0.011 201	0.002 310	0.003 7
CP 3	.030	2.139	1.242 348	0.021 351	0.010 313	0.010 100	0.005 169	0.012 15	0.009 264	0.009 328	0.004 236
CP 4	.049	2.001	0.891 348	0.016 331	0.012 300	0.017 160	0.002 135	0.000 73	0.007 253	0.007 357	0.003 113
CP 5	.074	1.771	0.722 349	0.013 352	0.010 305	0.014 158	0.001 21	0.003 374	0.002 3	0.004 332	0.001 82
CP 6	.099	1.612	0.574 351	0.012 18	0.005 311	0.018 178	0.002 138	0.002 192	0.005 47	0.005 348	0.004 22
CP 7	.145	1.187	0.451 351	0.014 20	0.004 310	0.011 161	0.001 307	0.001 151	0.001 234	0.001 277	0.001 45
CP 8	.200	0.971	0.350 358	0.004 4	0.007 348	0.015 175	0.002 334	0.004 71	0.001 288	0.002 21	0.005 27
CP 9	.250	0.829	0.288 357	0.009 14	0.004 1	0.018 86	0.003 76	0.001 23	0.007 303	0.001 126	0.001 219
CP10	.300	0.735	0.245 359	0.008 14	0.005 241	0.017 99	0.005 325	0.002 171	0.001 307	0.001 101	0.004 37
CP11	.399	0.610	0.195 9	0.006 14	0.003 147	0.024 112	0.001 11	0.002 239	0.001 83	0.007 188	0.002 226
CP12	.501	0.454	0.149 11	0.002 353	0.002 293	0.018 114	0.007 284	0.001 147	0.001 239	0.001 162	0.003 114
CP13	.600	0.394	0.117 17	0.006 23	0.004 296	0.018 96	0.003 244	0.037 67	0.001 112	0.006 200	0.003 55
CP14	.701	0.378	0.074 26	0.007 96	0.002 345	0.018 106	0.003 297	0.002 222	0.004 240	0.003 116	0.004 127
CP15	.800	0.189	0.045 37	0.004 104	0.004 171	0.017 114	0.005 167	0.002 335	0.001 49	0.001 319	0.001 129
CP16	.900	-0.063	0.018 54	0.009 18	0.004 158	0.022 96	0.004 215	0.001 272	0.001 272	0.001 213	0.006 123
CP17	.969	-0.064	0.013 201	0.007 188	0.001 264	0.020 93	0.004 174	0.005 7	0.006 335	0.003 186	0.004 19

101

FORCED PITCHING OSCILLATION   AIRFOIL   NLF 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYZED
7.0	45.67	0.174	0.396	7.43	0.0	7.40	12197.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
133.6	46578.	7.63E 07	-0.716	1.982	19.27	-7.30109	1.147	0.0
(438.2)	(972.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.396	2.899	0	0.177	1	0.056	264	0.027	60	0.029	65	0.013	59	0.013	304	0.003	156	0.013	47
CN		0.872	0.711	4	0.016	0	0.007	274	0.013	157	0.001	357	0.001	141	0.001	317	0.002	104	0.002	110
CM		0.002	0.018	307	0.002	189	0.002	330	0.005	166	0.030	231	0.000	159	0.001	277	0.003	218	0.006	330
DCP 1	.010	4.677	1.982	344	0.081	274	0.142	310	0.077	214	0.016	202	0.028	177	0.011	117	0.008	124	0.034	48
DCP 2	.020	3.553	1.760	351	0.135	278	0.145	166	0.141	65	0.056	325	0.021	13	0.035	303	0.007	319	0.035	147
DCP 3	.030	3.196	0.992	350	0.256	38	0.036	324	0.014	70	0.015	288	0.011	253	0.013	133	0.007	128	0.036	44
DCP 4	.049	2.991	2.782	351	0.066	99	0.036	175	0.006	357	0.010	196	0.005	172	0.034	211	0.038	117	0.038	44
DCP 5	.074	2.850	0.462	342	0.339	90	0.015	318	0.001	94	0.004	212	0.032	154	0.003	315	0.005	153	0.031	23
DCP 6	.099	2.209	0.531	354	0.033	27	0.211	325	0.005	73	0.004	173	0.003	188	0.007	91	0.006	176	0.037	97
DCP 7	.149	1.651	0.409	355	0.022	0	0.236	263	0.004	65	0.003	148	0.004	263	0.002	277	0.004	117	0.037	53
DCP 8	.200	1.338	0.327	7	0.015	40	0.035	295	0.007	113	0.004	375	0.002	66	0.005	225	0.006	170	0.033	190
DCP 9	.250	1.117	0.275	7	0.016	6	0.005	336	0.017	333	0.001	243	0.002	87	0.001	181	0.009	36	0.036	122
DCP10	.302	0.998	0.275	4	0.015	340	0.036	153	0.014	327	0.001	281	0.034	145	0.034	338	0.002	44	0.033	72
DCP11	.399	0.916	0.195	16	0.016	12	0.035	159	0.020	4	0.000	87	0.034	251	0.004	2	0.007	147	0.031	110
DCP12	.501	0.639	0.147	71	0.012	17	0.033	48	0.015	359	0.002	95	0.001	293	0.032	227	0.002	351	0.031	68
DCP13	.602	0.494	0.137	17	0.014	77	0.033	163	0.017	351	0.003	84	0.004	214	0.003	39	0.031	221	0.034	354
DCP14	.701	0.445	0.070	54	0.018	22	0.004	127	0.015	339	0.004	170	0.001	17	0.001	86	0.001	53	0.005	218
DCP15	.800	0.225	0.055	77	0.013	4	0.004	154	0.018	357	0.002	330	0.004	93	0.001	357	0.001	148	0.037	154
DCP16	.900	-0.041	0.032	93	0.036	344	0.012	275	0.020	336	0.033	241	0.003	170	0.004	26	0.004	39	0.002	35
DCP17	.969	-0.365	0.008	116	0.009	308	0.017	176	0.014	7	0.005	126	0.005	327	0.009	1	0.002	96	0.006	104

FORCED PITCHING OSCILLATION   AIRFOIL   NLF 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.60	0.175	0.394	2.79	0.0	9.89	12107.9	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
132.9	46214.	0.63E 07	-0.015	1.297	12.20	-0.00120	1.319	0.0
(435.9)	(965.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		9.892	7.793	0	0.118	17	0.110	258	0.031	181	0.041	62	0.021	56	0.013	235	0.005	252	0.008	28
CN		0.994	0.736	46	0.046	322	0.009	153	0.011	280	0.003	170	0.001	210	0.002	206	0.003	359	0.002	23
CM		0.007	0.018	259	0.016	59	0.009	279	0.001	74	0.007	209	0.001	84	0.000	98	0.001	145	0.001	288
DCP 1	.010	9.411	0.676	13	0.692	91	0.193	8	0.280	98	0.104	34	0.063	309	0.049	212	0.026	182	0.020	185
DCP 2	.020	4.270	0.880	30	0.347	28	0.232	1	0.190	319	0.052	357	0.125	340	0.081	294	0.033	263	0.006	279
DCP 3	.030	3.809	0.644	31	0.333	40	0.230	343	0.200	295	0.133	245	0.073	211	0.046	202	0.037	179	0.015	189
DCP 4	.049	3.369	0.569	40	0.301	15	0.147	288	0.059	242	0.061	241	0.050	204	0.033	161	0.020	154	0.017	122
DCP 5	.074	7.812	0.430	49	0.343	16	0.100	274	0.011	204	0.029	255	0.036	185	0.027	170	0.016	118	0.020	50
DCP 6	.099	2.490	0.448	46	0.229	354	0.105	245	0.006	170	0.042	228	0.051	135	0.021	46	0.007	83	0.020	28
DCP 7	.149	1.916	0.441	38	0.252	327	0.083	216	0.013	346	0.045	199	0.037	112	0.015	107	0.037	63	0.039	338
DCP 8	.200	1.562	0.388	40	0.154	322	0.059	252	0.023	306	0.052	194	0.037	96	0.005	1	0.009	73	0.019	322
DCP 9	.250	1.323	0.355	37	0.127	302	0.037	177	0.021	232	0.035	122	0.028	19	0.012	296	0.015	343	0.011	233
DCP10	.300	1.150	0.338	39	0.111	298	0.040	176	0.015	177	0.024	79	0.020	333	0.008	197	0.012	302	0.006	187
DCP11	.399	0.976	0.257	50	0.090	290	0.031	151	0.009	256	0.016	91	0.012	356	0.005	273	0.009	316	0.005	209
DCP12	.501	0.687	0.215	49	0.071	284	0.041	123	0.007	346	0.010	41	0.008	292	0.004	254	0.005	280	0.004	123
DCP13	.600	0.527	0.178	65	0.059	280	0.036	99	0.010	316	0.011	14	0.017	250	0.008	146	0.000	7	0.002	245
DCP14	.701	0.414	0.153	86	0.042	274	0.036	48	0.017	273	0.008	29	0.009	271	0.004	12	0.007	242	0.004	120
DCP15	.800	0.229	0.101	74	0.044	247	0.036	78	0.008	269	0.005	23	0.005	255	0.007	257	0.003	11	0.006	61
DCP16	.900	-0.015	0.071	23	0.043	219	0.018	59	0.010	283	0.008	309	0.004	143	0.001	176	0.005	244	0.006	86
DCP17	.969	-0.052	0.037	359	0.018	219	0.005	7	0.010	142	0.004	271	0.004	174	0.004	265	0.009	42	0.006	71

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.3	45.56	0.168	0.474	7.67	0.0	12.47	12109.1	70

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TAU	EXT DAMP
138.1	48809.	0.64E 07	-0.094	1.339	15.95	-0.00121	1.373	0.0
(453.2)	(1019.4)							

HARMONIC ANALYSIS

DATA TYPE	K/C	BFS 0	BFS 1	PHI	BFS 2	PHI	BFS 3	PHI	BFS 4	PHI	BFS 5	PHI	BFS 6	PHI	BFS 7	PHI	BFS 8	PHI	BFS 9	PHI
ALPHA		17.466	2.669	0	0.078	58	0.168	39	0.042	112	0.008	37	0.011	142	0.011	70	0.012	161	0.017	277
CN		1.015	0.269	78	0.058	43	0.037	0	0.004	154	0.010	227	0.009	337	0.006	96	0.001	201	0.002	192
CM		-0.015	0.349	202	0.016	94	0.012	105	0.007	30	0.009	38	0.003	147	0.003	147	0.003	141	0.003	147
DCP 1	.010	5.767	1.051	169	0.402	100	0.159	300	0.055	284	0.025	245	0.070	375	0.082	290	0.024	345	0.029	325
DCP 2	.020	4.101	0.820	172	0.487	115	0.031	149	0.047	276	0.071	259	0.047	295	0.043	309	0.025	329	0.038	334
DCP 3	.033	3.549	0.602	150	0.515	190	0.317	118	0.157	120	0.097	179	0.086	193	0.053	219	0.036	227	0.024	270
DCP 4	.049	3.208	0.686	172	0.345	75	0.090	67	0.085	109	0.061	125	0.026	147	0.017	211	0.032	254	0.032	254
DCP 5	.074	2.669	0.656	121	0.283	68	0.053	61	0.071	85	0.037	82	0.011	99	0.007	180	0.024	200	0.019	207
DCP 6	.099	2.248	0.421	114	0.274	68	0.093	137	0.103	67	0.040	74	0.027	94	0.019	99	0.024	160	0.032	136
DCP 7	.149	1.875	0.543	57	0.144	37	0.121	76	0.043	99	0.023	47	0.015	119	0.002	112	0.023	110	0.021	113
DCP 8	.200	1.449	0.455	67	0.102	34	0.138	51	0.051	12	0.010	346	0.039	215	0.011	119	0.024	140	0.028	108
DCP 9	.250	1.348	0.476	77	0.080	35	0.119	35	0.029	347	0.034	343	0.074	337	0.009	347	0.017	291	0.009	68
DCP10	.300	1.159	0.390	67	0.054	43	0.090	346	0.024	339	0.007	244	0.042	244	0.014	337	0.023	114	0.017	235
DCP11	.399	0.989	0.354	65	0.040	5	0.085	350	0.016	291	0.034	285	0.012	242	0.007	220	0.008	13	0.009	315
DCP12	.501	0.766	0.308	56	0.090	371	0.068	311	0.026	342	0.032	257	0.021	176	0.023	151	0.018	61	0.034	214
DCP13	.600	0.613	0.252	43	0.099	278	0.054	317	0.033	298	0.031	231	0.020	191	0.029	117	0.020	356	0.013	214
DCP14	.701	0.479	0.195	52	0.051	253	0.046	294	0.034	182	0.029	201	0.021	155	0.022	60	0.011	309	0.032	230
DCP15	.800	0.295	0.163	37	0.043	271	0.044	294	0.031	187	0.021	170	0.007	174	0.018	56	0.011	203	0.036	88
DCP16	.900	0.065	0.149	14	0.031	293	0.032	242	0.020	187	0.009	153	0.019	128	0.013	356	0.009	282	0.031	308
DCP17	.965	-0.008	0.065	4	0.014	330	0.018	346	0.019	203	0.010	186	0.011	199	0.007	321	0.013	277	0.004	38

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.62	0.173	0.394	7.65	0.0	14.89	12109.2	70

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TAU	EXT DAMP
134.6	47009.	0.63E 07	-0.141	1.425	15.45	-0.00138	1.577	0.0
(441.6)	(981.8)							

HARMONIC ANALYSIS

DATA TYPE	K/C	BFS 0	BFS 1	PHI	BFS 2	PHI	BFS 3	PHI	BFS 4	PHI	BFS 5	PHI	BFS 6	PHI	BFS 7	PHI	BFS 8	PHI	BFS 9	PHI
ALPHA		14.895	2.651	0	0.012	141	0.091	121	0.031	41	0.032	7	0.003	111	0.022	145	0.003	178	0.017	323
CN		1.029	0.350	78	0.075	86	0.033	47	0.014	19	0.005	12	0.035	1	0.003	67	0.004	18	0.001	199
CM		-0.041	0.369	196	0.023	187	0.014	162	0.010	159	0.002	128	0.002	153	0.001	35	0.002	184	0.000	8
DCP 1	.010	4.855	1.391	171	0.388	245	0.173	170	0.069	41	0.303	67	0.029	34	0.030	156	0.027	200	0.027	207
DCP 2	.020	3.817	1.155	157	0.360	170	0.091	128	0.077	52	0.059	34	0.031	126	0.034	114	0.034	320	0.020	276
DCP 3	.030	3.347	1.039	172	0.539	169	0.174	148	0.138	260	0.097	289	0.022	17	0.039	41	0.024	7	0.019	112
DCP 4	.049	3.020	0.965	144	0.278	129	0.153	159	0.030	147	0.047	275	0.002	44	0.036	34	0.033	12	0.002	154
DCP 5	.074	2.410	0.777	133	0.153	127	0.117	139	0.063	145	0.017	171	0.011	136	0.023	83	0.030	62	0.012	41
DCP 6	.099	2.157	0.670	121	0.163	139	0.115	114	0.036	188	0.015	155	0.013	81	0.017	19	0.018	70	0.008	88
DCP 7	.149	1.749	0.453	98	0.107	128	0.099	137	0.067	152	0.017	79	0.015	127	0.024	307	0.024	134	0.010	337
DCP 8	.200	1.506	0.433	88	0.106	117	0.007	102	0.064	117	0.011	65	0.006	339	0.024	235	0.014	118	0.003	1
DCP 9	.250	1.353	0.389	77	0.160	135	0.071	41	0.046	68	0.017	129	0.007	375	0.030	241	0.037	148	0.010	10
DCP10	.300	1.214	0.381	66	0.153	67	0.060	59	0.036	70	0.015	61	0.013	166	0.019	190	0.009	139	0.006	57
DCP11	.399	1.748	0.360	50	0.131	70	0.066	64	0.042	45	0.015	88	0.015	99	0.003	198	0.014	121	0.015	320
DCP12	.501	0.892	0.333	47	0.116	57	0.077	74	0.056	5	0.010	24	0.015	8	0.034	161	0.011	57	0.017	220
DCP13	.600	0.676	0.295	41	0.090	16	0.064	10	0.048	1	0.014	351	0.024	18	0.009	336	0.021	23	0.008	209
DCP14	.701	0.559	0.277	30	0.085	1	0.044	343	0.036	323	0.014	313	0.011	311	0.032	251	0.017	358	0.007	170
DCP15	.800	0.392	0.241	71	0.077	354	0.042	332	0.035	332	0.014	290	0.010	254	0.034	301	0.013	345	0.033	145
DCP16	.900	0.149	0.146	77	0.066	353	0.046	319	0.034	306	0.013	241	0.008	290	0.004	166	0.010	277	0.011	60
DCP17	.964	0.028	0.053	37	0.027	5	0.023	313	0.020	334	0.003	276	0.039	13	0.014	172	0.034	35	0.012	223

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
7.0	45.65	0.174	0.395	2.67	0.0	17.26	12109.7	70

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TPD	EXT DAMP
133.6	46477.	0.63E 07	-0.134	1.268	17.65	-0.00235	7.615	0.0
(438.4)	(970.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RFS 0	RFS 1 PHI	RFS 2 PHI	RFS 3 PHI	RFS 4 PHI	RFS 5 PHI	RFS 6 PHI	RFS 7 PHI	RFS 8 PHI	RFS 9 PHI
ALPHA		17.264	2.673 0	0.244 11	0.041 197	0.045 133	0.012 18	0.007 4	0.015 174	0.009 107	0.008 225
CN		1.021	0.306 49	0.079 58	0.011 115	0.007 65	0.007 299	0.001 331	0.003 74	0.003 14	0.032 133
CM		-0.074	0.252 217	0.011 197	0.001 248	0.002 258	0.001 60	0.000 247	0.002 279	0.001 314	0.001 190
CP 1	.010	4.148	0.007 188	0.116 796	0.105 84	0.023 14	0.010 14	0.050 67	0.009 94	0.025 156	0.034 303
CP 2	.020	3.335	0.060 105	0.098 105	0.044 49	0.040 41	0.039 5	0.037 41	0.023 69	0.012 39	0.037 189
CP 3	.030	2.028	0.043 170	0.062 347	0.016 172	0.034 32	0.020 122	0.015 299	0.010 118	0.006 260	0.030 172
CP 4	.040	2.369	0.077 150	0.059 184	0.047 77	0.020 15	0.013 299	0.037 67	0.004 291	0.020 222	0.022 211
CP 5	.074	1.943	0.435 123	0.048 186	0.038 49	0.011 257	0.007 331	0.012 0	0.007 335	0.005 241	0.014 203
CP 6	.099	1.811	0.348 112	0.067 164	0.013 139	0.017 264	0.017 313	0.079 351	0.002 318	0.004 127	0.038 118
CP 7	.149	1.611	0.302 91	0.064 118	0.035 123	0.010 175	0.030 225	0.018 271	0.009 323	0.003 329	0.016 73
CP 8	.200	1.471	0.293 84	0.049 124	0.038 123	0.009 296	0.014 358	0.036 13	0.007 349	0.020 45	0.007 174
CP 9	.250	1.378	0.266 85	0.060 101	0.012 97	0.010 162	0.014 107	0.011 190	0.015 156	0.012 19	0.016 314
CP10	.300	1.738	0.303 74	0.076 97	0.018 198	0.034 25	0.024 153	0.032 215	0.014 349	0.029 65	0.330 204
CP11	.399	1.110	0.274 73	0.071 76	0.019 127	0.013 97	0.012 219	0.007 263	0.005 206	0.023 311	0.014 134
CP12	.501	0.972	0.278 63	0.062 34	0.017 63	0.015 68	0.009 278	0.011 95	0.014 135	0.017 274	0.018 120
CP13	.600	0.765	0.25 45	0.045 17	0.034 36	0.014 139	0.004 299	0.015 63	0.017 86	0.009 253	0.014 43
CP14	.701	0.650	0.22 44	0.047 358	0.004 279	0.004 40	0.016 271	0.004 331	0.008 50	0.007 189	0.017 350
CP15	.800	0.507	0.18 49	0.038 357	0.007 116	0.012 77	0.019 261	0.001 23	0.011 146	0.017 139	0.011 303
CP16	.900	0.715	0.135 47	0.032 353	0.035 43	0.010 17	0.014 292	0.005 291	0.007 41	0.013 58	0.005 228
CP17	.969	0.050	0.058 67	0.007 17	0.002 97	0.008 99	0.002 173	0.005 51	0.001 353	0.006 129	0.010 38

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
7.0	45.54	0.175	0.393	2.71	0.0	19.87	12109.4	70

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TPD	EXT DAMP
132.6	45927.	0.63E 07	-0.156	1.255	19.67	-0.00309	7.357	0.0
(435.2)	(959.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RFS 0	RFS 1 PHI	RFS 2 PHI	RFS 3 PHI	RFS 4 PHI	RFS 5 PHI	RFS 6 PHI	RFS 7 PHI	RFS 8 PHI	RFS 9 PHI
ALPHA		19.871	2.709 0	0.069 6	0.048 200	0.038 161	0.027 30	0.010 24	0.011 184	0.014 129	0.005 343
CN		1.012	0.708 84	0.009 69	0.010 156	0.013 227	0.009 88	0.012 116	0.006 99	0.007 176	0.001 160
CM		-0.996	0.252 233	0.008 205	0.003 215	0.002 47	0.003 254	0.004 289	0.001 273	0.002 133	0.001 54
CP 1	.010	9.374	0.882 191	0.084 74	0.025 66	0.041 174	0.026 242	0.015 341	0.016 3	0.017 223	0.030 175
CP 2	.020	2.836	0.801 171	0.095 63	0.071 209	0.045 159	0.012 307	0.007 40	0.009 288	0.009 224	0.011 211
CP 3	.070	2.489	0.747 149	0.138 266	0.035 73	0.321 266	0.301 136	0.032 153	0.021 7	0.012 146	0.011 269
CP 4	.049	2.000	0.537 138	0.075 230	0.071 198	0.542 238	0.025 242	0.018 373	0.021 356	0.021 31	0.013 89
CP 5	.074	1.755	0.273 108	0.061 184	0.053 179	0.040 275	0.017 94	0.017 169	0.006 312	0.009 209	0.017 340
CP 6	.099	1.693	0.242 99	0.070 184	0.030 184	0.029 211	0.022 89	0.009 83	0.008 313	0.036 64	
CP 7	.149	1.562	0.236 89	0.040 161	0.039 160	0.026 233	0.011 179	0.007 166	0.011 118	0.003 759	0.008 215
CP 8	.200	1.410	0.217 91	0.032 196	0.032 272	0.020 256	0.015 96	0.013 81	0.016 127	0.007 167	0.011 180
CP 9	.250	1.347	0.250 88	0.027 197	0.023 227	0.011 254	0.005 91	0.011 171	0.001 3	0.009 275	0.008 82
CP10	.300	1.252	0.251 81	0.012 177	0.024 203	0.013 242	0.010 42	0.015 76	0.012 153	0.007 759	0.006 33
CP11	.399	1.154	0.272 82	0.023 69	0.024 166	0.011 238	0.011 147	0.010 144	0.017 111	0.010 217	0.008 60
CP12	.501	0.977	0.274 72	0.036 58	0.035 127	0.010 248	0.025 84	0.018 159	0.014 126	0.015 168	0.018 60
CP13	.600	0.828	0.257 65	0.027 48	0.020 76	0.016 176	0.018 130	0.020 149	0.008 94	0.017 163	0.006 358
CP14	.701	0.779	0.233 57	0.031 38	0.013 19	0.006 208	0.024 82	0.025 118	0.010 38	0.018 174	0.004 314
CP15	.800	0.567	0.195 56	0.032 16	0.017 11	0.009 210	0.012 72	0.026 100	0.003 162	0.004 160	0.016 229
CP16	.900	0.758	0.159 60	0.011 358	0.017 6	0.015 266	0.012 2	0.013 56	0.001 259	0.005 115	0.016 212
CP17	.969	0.067	0.076 68	0.010 1	0.032 233	0.016 210	0.007 325	0.010 60	0.011 41	0.007 183	0.009 237

	REDUCED WG	MOTVE WG	K	MACH NO	REL.ALPHA	REL.W	ALPHA.0	TEST POINT	CYCLES ANALYSED
	7.0	68.99	0.252	0.497	3.15	0.0	0.96	12111.1	70

	V	Q	RN	CNEMINI	CNEMAXI	ALPHA.NMAX	AERO DAMP	THR	EXT DAMP
	138.2	48953.	0.84E 07	-0.035	0.340	3.25	-0.390E-8	7.789	0.0
	(453.3)	(1022.4)							

HARMONIC ANALYSIS

DATA TYPE	K/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.257	7.147 0	0.136 308	0.098 191	0.022 113	0.012 216	0.026 57	0.009 52	0.004 189	0.008 87
CN		0.212	7.772 5	0.017 331	0.004 267	0.037 217	0.007 214	0.001 120	7.032 77	0.003 326	0.001 300
CM		-0.016	7.017 291	0.001 238	0.001 212	0.001 76	0.000 303	0.000 294	0.003 294	0.000 312	0.003 178
CP 1	.010	-1.117	1.580 342	0.047 299	0.050 181	0.010 95	0.026 150	0.007 259	0.023 318	0.011 82	0.039 132
CP 2	.020	-0.564	1.197 350	0.053 304	0.026 279	0.011 179	0.012 206	0.007 53	0.013 07	0.003 315	0.035 111
CP 3	.030	-0.385	1.090 349	0.051 286	0.029 279	0.010 172	0.012 272	0.034 85	0.003 173	0.005 267	0.004 183
CP 4	.045	0.161	0.821 351	0.037 298	0.021 291	0.004 161	0.008 263	0.009 80	0.004 318	0.003 176	0.001 310
CP 5	.114	0.292	0.670 351	0.029 299	0.032 250	0.004 71	0.006 108	0.007 358	0.004 356	0.007 306	0.004 166
CP 6	.099	0.344	0.572 353	0.023 335	0.015 247	0.004 80	0.009 187	0.004 65	0.001 6	0.004 317	0.002 37
CP 7	.149	0.347	0.420 356	0.011 346	0.011 241	0.006 198	0.007 239	0.001 353	0.004 56	0.004 280	0.004 253
CP 8	.200	0.149	0.343 5	0.010 330	0.011 268	0.007 270	0.003 150	0.004 68	0.004 58	0.004 359	0.002 184
CP 9	.250	0.181	0.291 7	0.018 331	0.017 273	0.006 158	0.007 110	0.004 145	0.003 116	0.003 178	0.003 310
CP10	.302	0.195	0.251 4	0.013 326	0.006 238	0.003 216	0.004 350	0.004 149	0.003 69	0.003 130	0.008 376
CP11	.399	0.162	0.237 29	0.012 343	0.003 342	0.004 136	0.005 266	0.006 291	0.004 81	0.003 315	0.003 362
CP12	.501	0.170	0.197 76	0.008 347	0.004 274	0.004 216	0.009 338	0.005 174	0.006 122	0.006 321	0.005 279
CP13	.600	0.159	0.114 76	0.010 335	0.006 319	0.007 208	0.001 151	0.003 212	0.001 259	0.006 161	0.004 85
CP14	.701	0.212	0.091 41	0.006 91	0.003 91	0.006 268	0.007 151	0.003 356	0.002 347	0.003 109	0.003 22
CP15	.800	0.086	0.063 58	0.008 33	0.006 11	0.001 11	0.005 115	0.003 356	0.002 58	0.006 109	0.003 22
CP16	.950	-0.005	0.036 77	0.003 18	0.008 35	0.003 239	0.000 237	0.007 57	0.005 195	0.005 217	0.006 167
CP17	.969	-0.367	0.018 102	0.008 196	0.006 197	0.002 79	0.010 118	0.001 311	0.003 150	0.004 1	0.003 359

	REDUCED WG	MOTVE WG	K	MACH NO	REL.ALPHA	REL.W	ALPHA.0	TEST POINT	CYCLES ANALYSED
	7.0	68.97	0.256	0.499	3.14	0.0	7.45	12111.7	70

	V	Q	RN	CNEMINI	CNEMAXI	ALPHA.NMAX	AERO DAMP	THR	EXT DAMP
	136.4	48144.	0.84E 07	-0.028	0.505	5.73	-0.390E-8	7.754	0.0
	(447.5)	(1005.5)							

HARMONIC ANALYSIS

DATA TYPE	K/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.486	7.141 0	0.127 296	0.077 201	0.014 120	0.011 99	2.390 85	0.005 50	7.025 169	0.007 127
CN		0.367	0.777 4	0.011 323	0.001 355	0.007 282	0.001 197	0.002 156	0.001 121	0.001 293	0.001 185
CM		-0.011	0.017 292	0.002 216	0.001 225	0.001 121	0.001 68	0.001 71	0.000 308	0.000 54	0.000 0
CP 1	.010	0.745	1.480 344	0.068 285	0.072 250	0.028 139	0.008 26	0.001 11	0.002 145	0.008 56	0.002 355
CP 2	.020	0.826	1.223 350	0.050 293	0.004 275	0.010 187	0.007 100	0.007 95	0.001 319	0.007 67	0.005 151
CP 3	.010	1.009	1.046 349	0.043 287	0.011 293	0.005 158	0.004 98	0.004 72	0.034 357	0.001 217	0.005 125
CP 4	.049	1.058	0.861 350	0.034 296	0.007 185	0.007 158	0.006 158	0.005 53	0.004 11	0.007 298	0.001 146
CP 5	.114	1.012	0.691 350	0.032 290	0.006 240	0.002 55	0.000 157	0.004 98	0.007 277	0.004 8	0.003 133
CP 6	.099	0.976	0.580 353	0.023 317	0.012 299	0.007 214	0.012 109	0.002 51	0.001 300	0.011 301	0.007 235
CP 7	.149	0.706	0.425 356	0.022 283	0.004 140	0.001 200	0.008 90	0.010 94	0.001 43	0.008 63	0.004 267
CP 8	.200	0.569	0.358 4	0.017 339	0.005 110	0.004 354	0.003 24	0.003 98	0.001 291	0.004 314	0.004 231
CP 9	.250	0.591	0.300 2	0.012 313	0.001 4	0.004 255	0.007 270	0.003 94	0.004 156	0.004 357	0.007 136
CP10	.300	0.461	0.252 321	0.015 321	0.004 151	0.001 194	0.002 84	0.002 176	0.001 316	0.001 168	0.004 117
CP11	.399	0.385	0.208 70	0.010 343	0.001 289	0.004 292	0.005 288	0.002 125	0.002 196	0.003 213	0.000 152
CP12	.401	0.289	0.159 75	0.011 345	0.004 2	0.004 319	0.006 165	0.006 181	0.004 184	0.001 261	0.002 0
CP13	.600	0.262	0.124 33	0.007 4	0.004 8	0.002 267	0.005 243	0.006 277	0.005 174	0.001 71	0.005 219
CP14	.701	0.291	0.088 41	0.007 341	0.003 111	0.007 316	0.004 231	0.004 157	0.013 96	0.004 243	0.027 169
CP15	.800	0.139	0.060 53	0.013 74	0.006 114	0.005 351	0.004 271	0.002 274	0.004 290	0.003 246	0.002 247
CP16	.900	-0.083	0.022 77	0.007 35	0.012 71	0.001 300	0.004 199	0.001 205	0.005 147	0.001 102	0.001 91
CP17	.969	-0.062	0.006 193	0.005 275	0.001 214	0.005 192	0.002 328	0.005 235	0.002 351	0.004 160	0.003 100

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TOWER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
7.0	69.56	0.267	0.399	3.1C	5.0	4.97	12111.3	70

Q	Q	PN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AFP3 DAMP	TNO	FXT DAMP
135.0	47320.	7.66E 07	-0.026	0.851	8.04	-0.00070	0.788	0.0
(443.0)	(988.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	BFS 0	BFS 1	PHI	BFS 2	PHI	BFS 3	PHI	BFS 4	PHI	BFS 5	PHI	BFS 6	PHI	BFS 7	PHI	BFS 8	PHI	BFS 9	PHI
ALPHA		4.974	3.193	3	0.134	311	0.071	214	0.009	161	0.024	127	0.023	69	0.006	17	0.034	287	0.033	203
CN		0.690	0.715	5	0.014	344	0.002	144	0.003	258	0.008	213	0.013	11	0.037	157	0.034	317	0.032	277
CM		-0.097	0.019	302	0.002	231	0.002	140	0.001	67	0.002	69	0.002	215	0.001	391	0.001	185	0.031	43
PCP 1	.010	2.350	1.614	341	0.121	256	0.054	142	0.007	321	0.013	63	0.004	327	0.010	237	0.012	194	0.004	111
PCP 2	.020	2.254	1.225	349	0.353	294	0.023	143	0.005	244	0.010	175	3.337	312	0.519	195	0.008	193	3.053	304
PCP 3	.290	2.147	1.036	349	0.041	305	0.016	297	0.001	293	0.007	102	0.009	333	0.004	244	0.001	250	0.004	161
PCP 4	.049	2.010	0.878	350	0.042	295	0.011	240	0.003	241	0.008	114	0.003	28	0.035	297	0.011	149	0.002	333
PCP 5	.034	1.779	0.752	351	0.026	308	0.010	258	0.003	238	0.006	126	3.303	42	0.036	342	0.006	129	0.002	260
PCP 6	.099	1.615	0.572	354	0.032	317	0.006	197	0.006	363	0.005	170	0.003	94	0.006	343	0.003	354	0.007	320
PCP 7	.149	1.184	0.441	356	0.021	337	0.007	260	0.006	278	0.005	185	0.004	47	0.002	11	0.003	333	0.003	141
PCP 8	.200	0.943	0.345	4	0.019	336	0.008	253	0.002	166	0.002	261	0.004	234	0.005	343	0.002	80	0.002	217
PCP 9	.250	0.892	0.288	3	0.022	335	0.006	284	0.002	227	0.010	212	0.006	41	0.003	344	0.006	344	0.005	339
PCP10	.300	0.736	0.276	5	0.016	337	0.003	255	0.005	249	0.002	318	0.002	251	0.034	322	0.035	359	0.031	261
PCP11	.399	0.676	0.139	350	0.049	24	0.017	46	0.011	3	0.076	192	0.118	352	0.001	149	0.020	290	0.023	334
PCP12	.501	0.459	0.154	31	0.013	14	0.006	292	0.001	59	0.007	327	0.007	19	0.003	129	0.003	322	0.004	111
PCP13	.600	0.374	0.141	43	0.007	252	0.017	19	0.013	177	0.024	310	0.028	195	3.321	274	0.018	70	0.021	234
PCP14	.701	0.179	0.083	49	0.003	353	0.007	355	0.010	279	0.001	178	0.003	193	0.008	73	0.033	16	0.010	141
PCP15	.900	0.107	0.060	68	0.007	45	0.006	319	0.005	210	0.002	334	0.004	83	0.038	352	0.006	330	0.037	325
PCP16	.900	-0.344	0.029	101	0.006	96	0.035	276	0.007	292	0.003	317	0.034	64	0.004	146	0.003	66	0.002	167
PCP17	.949	-0.344	0.015	151	0.003	326	0.002	153	0.002	77	0.007	267	0.005	393	0.007	290	0.006	351	0.001	344

Q	Q	PN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AFP3 DAMP	TNO	FXT DAMP
134.0	46846.	0.63E 07	-0.021	1.103	11.63	-0.00004	1.354	0.0
(439.8)	(978.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	BFS 0	BFS 1	PHI	BFS 2	PHI	BFS 3	PHI	BFS 4	PHI	BFS 5	PHI	BFS 6	PHI	BFS 7	PHI	BFS 8	PHI	BFS 9	PHI
ALPHA		7.493	3.117	3	0.102	315	0.130	198	0.013	151	0.027	64	0.015	56	0.012	149	0.001	230	0.037	291
CN		0.865	0.772	17	0.073	341	0.037	337	0.002	349	3.037	260	0.002	19	0.032	131	0.003	113	0.001	331
CM		0.001	0.024	293	0.003	185	0.003	11	0.001	128	0.001	59	0.000	248	0.031	315	0.000	317	0.000	78
PCP 1	.010	4.252	1.995	344	3.104	287	0.139	298	0.008	199	0.017	149	0.025	165	0.007	67	0.036	344	0.009	1
PCP 2	.020	3.574	1.149	352	0.218	270	0.192	166	0.143	63	0.045	327	0.029	26	0.054	302	0.033	217	0.005	109
PCP 3	.030	3.193	0.961	351	0.032	337	0.015	261	0.021	66	0.026	307	0.023	232	3.015	114	0.005	47	3.035	9
PCP 4	.040	2.902	0.759	351	0.051	15	0.021	247	0.009	170	0.006	68	0.031	213	0.008	342	0.012	390	0.009	242
PCP 5	.034	2.601	0.652	355	0.019	359	0.010	268	0.007	188	0.004	178	0.003	73	0.032	144	0.004	28	0.004	270
PCP 6	.050	2.109	0.542	358	0.036	347	0.009	275	0.002	93	0.003	314	0.034	358	3.033	49	0.032	25	0.000	47
PCP 7	.149	1.459	0.497	7	0.026	343	0.007	240	0.007	219	0.002	95	0.005	17	0.034	30	0.007	78	0.003	16
PCP 8	.200	1.330	0.347	11	0.020	337	0.004	185	0.001	167	0.005	194	0.031	144	0.000	304	0.005	174	0.002	91
PCP 9	.250	1.116	0.302	8	0.015	331	0.000	239	0.008	258	0.003	213	0.006	3	0.003	141	0.037	149	0.003	348
PCP10	.300	0.897	0.245	11	0.017	350	0.005	239	0.006	64	0.001	238	0.005	341	0.007	75	0.035	326	0.001	297
PCP11	.355	0.811	0.204	29	0.022	351	0.036	276	0.006	43	0.005	249	0.003	189	0.033	85	0.001	162	3.036	44
PCP12	.521	0.611	0.185	39	0.01	354	0.036	256	0.002	285	0.004	363	0.004	342	0.003	204	0.032	183	0.002	237
PCP13	.600	0.495	0.127	48	0.017	9	0.009	256	0.005	319	0.006	289	0.008	189	0.001	75	0.001	299	0.001	9
PCP14	.701	0.444	0.133	66	0.024	355	0.007	198	0.002	8	0.008	243	0.006	11	0.008	178	0.034	253	0.004	331
PCP15	.900	0.722	0.081	78	0.023	346	0.005	213	0.008	311	0.003	177	0.014	23	0.007	86	0.017	93	0.004	175
PCP16	.900	-0.094	0.049	78	0.005	372	0.005	113	0.008	308	0.002	251	0.006	118	0.017	162	0.034	178	0.004	247
PCP17	.949	-0.069	0.017	75	0.037	9	0.091	73	0.006	237	0.007	68	0.032	293	0.035	18	0.003	162	0.033	317

FORCED PITCHING OSCILLATION   AIRFOIL   NLR I

POWER HZ	POINT HZ	K	MACH NO	DEL.ALPHA	DEL.W	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.91	0.262	0.994	3.07	0.0	0.96	12111.5	29

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TPO	EXT DAMP
133.2	46315.	0.49E 07	-0.019	1.936	12.86	-0.00041	1.094	0.0
(437.1)	(967.3)			HARMONIC ANALYSIS				

DATA TYPE	K/C	BFS 0	BFS 1 PHI	BFS 2 PHI	BFS 3 PHI	BFS 4 PHI	BFS 5 PHI	BFS 6 PHI	BFS 7 PHI	BFS 8 PHI	BFS 9 PHI
ALPHA		9.969	9.072 0	9.194 992	0.078 174	0.027 120	0.009 109	0.017 75	0.001 117	0.006 96	0.010 301
CN		0.479	0.318 96	0.045 268	0.009 47	0.008 281	0.007 279	0.004 174	0.004 98	0.004 131	0.001 35
CM		0.006	0.025 248	0.018 11	0.006 716	0.002 213	0.002 42	0.001 290	0.001 246	0.001 114	0.000 222
CCP 1	.010	4.495	0.926 12	0.674 61	0.176 370	0.184 56	0.125 910	0.051 169	0.013 286	0.039 191	0.054 66
CCP 2	.020	4.178	1.093 26	0.996 10	0.139 332	0.152 921	0.092 905	0.111 299	0.074 296	0.350 267	0.339 213
CCP 3	.030	7.679	0.782 91	0.436 74	0.279 304	0.155 251	0.106 215	0.081 191	0.062 157	0.078 192	0.046 191
CCP 4	.049	3.145	0.809 27	1.260 345	0.104 219	0.026 292	0.075 227	0.048 160	0.093 141	0.045 110	0.036 53
CCP 5	.074	2.431	0.678 93	0.209 329	0.091 234	0.029 314	0.059 197	0.039 121	0.020 47	0.028 47	0.014 331
CCP 6	.099	2.475	0.623 93	0.190 322	0.055 198	0.049 275	0.090 171	0.097 79	0.029 95	0.004 14	0.025 272
CCP 7	.149	1.880	0.543 28	0.139 291	0.021 117	0.067 247	0.071 123	0.035 159	0.005 191	0.015 349	0.022 306
CCP 8	.200	1.999	0.489 91	0.124 277	0.093 114	0.092 239	0.043 104	0.021 317	0.014 124	0.014 174	0.014 324
CCP 9	.250	1.911	0.484 27	0.150 269	0.099 148	0.092 166	0.048 42	0.028 179	0.012 208	0.013 201	0.016 83
CCP10	.300	1.146	0.406 27	0.118 251	0.041 114	0.009 191	0.020 396	0.017 217	0.011 76	0.010 243	0.016 163
CCP11	.349	0.926	0.947 98	0.101 246	0.903 93	0.008 131	0.028 352	0.020 236	0.009 109	0.004 222	0.008 151
CCP12	.501	0.679	0.797 44	0.095 276	0.099 61	0.011 16	0.097 296	0.019 155	0.007 71	0.036 150	0.039 296
CCP13	.600	0.521	0.249 54	0.067 213	0.042 44	0.010 350	0.030 299	0.021 114	0.007 915	0.032 108	0.095 239
CCP14	.701	0.420	0.213 69	0.044 198	0.131 6	0.094 225	0.013 231	0.006 114	0.008 83	0.008 373	0.006 56
CCP15	.800	0.719	0.118 95	0.056 177	1.522 359	0.014 12	0.015 203	0.005 93	0.035 96	0.008 261	0.037 62
CCP16	.900	-0.329	0.394 25	0.041 143	0.314 336	0.007 285	0.017 54	0.036 6	0.054 74	0.033 4	0.001 279
CCP17	.949	-0.761	0.031 7	0.027 178	0.096 191	0.015 322	0.004 197	0.004 275	0.009 141	0.007 128	0.008 11

FORCED PITCHING OSCILLATION   AIRFOIL   NLR I

POWER HZ	POINT HZ	K	MACH NO	DEL.ALPHA	DEL.W	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.46	0.291	0.697	3.04	0.0	0.88	12111.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TPO	EXT DAMP
138.8	49092.	0.66E 07	-0.521	1.289	12.61	-0.35070	3.914	3.3
(455.4)	(1025.3)			HARMONIC ANALYSIS				

DATA TYPE	K/C	BFS 0	BFS 1 PHI	BFS 2 PHI	BFS 3 PHI	BFS 4 PHI	BFS 5 PHI	BFS 6 PHI	BFS 7 PHI	BFS 8 PHI	BFS 9 PHI
ALPHA		5.877	3.074 3	0.795 117	0.075 184	0.011 129	0.009 134	0.019 96	0.094 74	0.011 95	0.032 2
CN		0.469	0.380 97	0.091 277	0.011 79	0.005 298	0.007 219	0.007 143	0.003 198	0.005 79	0.001 281
CM		0.002	0.022 248	0.010 15	0.008 279	0.001 217	0.002 89	0.001 266	0.003 398	0.001 158	0.002 70
CCP 1	.010	4.861	3.794 16	0.645 69	0.112 399	0.739 66	0.173 393	0.038 165	0.119 307	0.369 197	0.047 70
CCP 2	.020	3.998	3.996 26	0.350 15	0.132 941	0.151 370	0.101 915	0.124 796	0.077 251	0.097 349	0.320 746
CCP 3	.030	7.556	3.717 99	0.422 79	0.282 913	0.194 259	0.119 210	0.065 195	0.359 170	0.077 125	0.021 158
CCP 4	.049	3.196	3.785 31	0.286 368	0.131 941	0.010 244	0.074 237	0.056 164	0.073 165	0.318 139	0.046 44
CCP 5	.074	2.795	0.616 93	0.227 997	0.085 715	0.079 374	0.070 220	0.059 114	0.025 109	0.040 71	0.043 8
CCP 6	.099	2.409	0.690 94	0.217 329	0.071 238	1.048 291	0.090 183	0.051 88	0.314 194	0.351 65	0.048 725
CCP 7	.149	1.861	0.552 79	0.192 295	0.065 140	0.044 216	0.094 119	0.053 17	0.019 5	0.031 121	0.025 798
CCP 8	.200	1.509	0.481 91	0.139 290	0.011 166	0.044 275	0.050 111	0.326 119	0.016 113	0.029 19	0.021 287
CCP 9	.250	1.300	3.43? 27	0.129 249	0.041 128	0.020 199	0.394 53	0.072 915	0.017 777	0.014 195	0.011 92
CCP10	.300	1.115	0.391 27	0.125 295	0.044 117	0.015 86	0.033 358	0.023 215	0.013 55	0.004 108	0.007 101
CCP11	.349	0.987	0.322 98	0.116 294	3.048 136	0.028 68	0.023 947	0.013 223	0.007 1	0.016 718	0.015 77
CCP12	.501	0.677	0.779 42	0.995 229	0.047 63	0.014 944	0.022 292	0.017 187	0.007 96	0.012 79	0.017 314
CCP13	.600	0.511	0.225 93	0.066 716	0.098 49	0.006 192	0.017 266	0.009 147	0.006 171	0.015 22	0.012 231
CCP14	.701	0.425	0.191 68	0.044 200	0.041 19	0.074 215	0.011 257	0.009 74	0.011 202	0.074 114	0.039 614
CCP15	.800	0.235	0.134 99	0.049 189	0.031 19	0.010 18	0.019 214	0.099 48	0.006 129	0.015 108	0.008 197
CCP16	.900	-0.022	0.062 74	0.044 163	0.014 2	0.014 977	0.017 180	0.006 100	0.017 303	0.039 148	0.031 203
CCP17	.949	-0.048	0.071 356	0.019 174	0.034 7	0.034 992	0.001 124	0.003 18	0.017 163	0.032 943	0.035 204

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.50	0.256	0.402	2.94	0.0	12.39	12113.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
136.2	48038.	0.64E 07	-0.152	1.512	15.53	0.00021	-0.236	0.0
(447.0)	(1003.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.392	2.942 0	0.292 352	0.116 163	0.033 137	0.010 17	0.018 43	0.005 115	0.008 189	0.005 130
CN		1.041	0.404 48	0.083 315	0.049 192	0.020 76	0.003 307	0.005 41	0.001 281	0.003 141	0.007 70
CM		-0.021	0.062 141	0.033 51	0.022 341	0.009 233	0.003 156	0.002 148	0.002 0	0.002 253	0.002 175
DCP 1	.010	4.842	0.793 132	0.602 76	0.163 247	0.167 183	0.040 239	0.091 203	0.041 128	0.022 184	0.057 130
DCP 2	.020	4.016	0.973 89	0.597 56	0.066 43	0.172 164	0.154 147	0.063 181	0.083 202	0.032 197	0.023 265
DCP 3	.030	3.366	0.967 119	0.700 65	0.158 43	0.181 84	0.137 49	0.033 85	0.078 99	0.035 101	0.046 126
DCP 4	.049	3.163	0.898 90	0.478 28	0.037 337	0.080 44	0.022 8	0.049 75	0.037 11	0.026 189	0.053 125
DCP 5	.074	2.679	0.822 84	0.387 12	0.025 291	0.056 355	0.019 194	0.055 52	0.046 353	0.007 58	0.030 49
DCP 6	.099	2.424	0.803 76	0.335 2	0.026 3	0.069 334	0.012 223	0.041 28	0.035 315	0.015 145	0.043 65
DCP 7	.149	1.974	0.757 59	0.242 338	0.037 318	0.048 279	0.011 45	0.027 331	0.018 344	0.025 329	0.015 328
DCP 8	.200	1.610	0.683 56	0.215 336	0.065 313	0.060 252	0.008 284	0.028 291	0.032 254	0.006 244	0.015 267
DCP 9	.250	1.389	0.632 46	0.180 311	0.059 271	0.045 218	0.020 214	0.019 198	0.010 171	0.008 176	0.020 177
DCP10	.300	1.242	0.579 38	0.150 300	0.066 247	0.022 160	0.035 235	0.024 152	0.015 81	0.011 245	0.025 126
DCP11	.399	1.043	0.555 40	0.167 298	0.126 236	0.058 141	0.017 249	0.031 144	0.021 73	0.004 297	0.013 109
DCP12	.501	0.793	0.468 34	0.140 281	0.129 208	0.056 108	0.015 144	0.032 76	0.024 355	0.016 239	0.011 118
DCP13	.600	0.632	0.373 32	0.117 253	0.133 183	0.062 73	0.016 52	0.026 27	0.027 294	0.022 173	0.019 42
DCP14	.701	0.514	0.287 23	0.121 220	0.111 151	0.057 40	0.015 359	0.021 326	0.030 215	0.031 117	0.023 1
DCP15	.800	0.328	0.234 5	0.110 209	0.093 137	0.037 40	0.020 355	0.023 307	0.028 163	0.018 53	0.017 352
DCP16	.900	0.056	0.152 350	0.075 227	0.077 120	0.038 8	0.017 322	0.013 236	0.019 116	0.020 358	0.011 228
DCP17	.969	-0.009	0.060 346	0.034 256	0.048 143	0.025 37	0.012 293	0.013 338	0.009 188	0.008 25	0.008 12

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.49	0.259	0.397	2.91	0.0	14.84	12113.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
134.4	46985.	0.63E 07	-0.190	1.639	17.09	-0.00040	0.548	0.0
(441.0)	(981.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		14.840	2.909 0	0.163 56	0.142 197	0.019 162	0.015 72	0.011 15	0.018 189	0.010 149	0.001 344
CN		1.194	0.409 57	0.116 0	0.037 264	0.017 252	0.015 191	0.011 24	0.004 277	0.004 268	0.004 333
CM		-0.042	0.091 148	0.040 126	0.018 57	0.007 30	0.008 344	0.005 224	0.002 315	0.000 49	0.001 144
DCP 1	.010	4.347	1.322 168	0.268 86	0.099 321	0.106 327	0.060 22	0.057 17	0.037 57	0.029 34	0.015 90
DCP 2	.020	3.074	1.287 150	0.562 100	0.112 310	0.156 287	0.055 38	0.041 32	0.051 92	0.038 86	0.013 146
DCP 3	.030	3.238	1.315 148	0.469 106	0.252 191	0.157 181	0.075 265	0.051 264	0.039 3	0.029 0	0.013 59
DCP 4	.049	3.113	1.344 118	0.290 70	0.132 126	0.026 193	0.024 220	0.047 290	0.024 331	0.052 5	0.027 345
DCP 5	.074	2.669	0.920 105	0.181 45	0.121 103	0.014 243	0.039 142	0.023 299	0.076 294	0.025 108	0.012 202
DCP 6	.099	2.409	0.859 97	0.166 57	0.172 79	0.017 191	0.021 92	0.050 265	0.024 239	0.023 291	0.011 320
DCP 7	.149	1.959	0.735 73	0.126 45	0.087 25	0.019 258	0.024 187	0.025 194	0.007 274	0.024 267	0.010 265
DCP 8	.200	1.678	0.695 67	0.156 47	0.086 15	0.035 17	0.006 56	0.017 32	0.013 349	0.006 311	0.011 327
DCP 9	.250	1.443	0.628 57	0.173 30	0.090 334	0.030 1	0.025 24	0.024 329	0.010 313	0.008 278	0.017 222
DCP10	.300	1.290	0.612 51	0.198 19	0.070 309	0.037 37	0.034 2	0.031 1	0.024 323	0.041 233	0.017 96
DCP11	.399	1.104	0.573 47	0.224 15	0.102 304	0.055 333	0.055 280	0.018 159	0.029 296	0.030 198	0.020 66
DCP12	.501	0.874	0.518 37	0.214 357	0.130 272	0.056 290	0.056 236	0.027 101	0.026 261	0.027 124	0.012 358
DCP13	.600	0.697	0.469 29	0.192 316	0.107 249	0.052 246	0.065 213	0.024 85	0.034 201	0.029 79	0.007 224
DCP14	.701	0.564	0.390 18	0.174 302	0.096 220	0.044 207	0.055 159	0.025 44	0.025 134	0.021 15	0.009 317
DCP15	.800	0.406	0.378 8	0.162 290	0.073 210	0.054 185	0.051 125	0.032 13	0.019 80	0.018 307	0.004 303
DCP16	.900	0.174	0.189 10	0.110 286	0.054 202	0.030 163	0.043 118	0.023 3	0.009 63	0.021 238	0.003 345
DCP17	.969	1.316	0.072 28	0.358 298	0.029 221	0.023 194	0.012 155	0.012 28	0.015 61	0.007 300	0.009 277

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	68.41	0.261	0.395	2.95	0.0	17.46	12113.4	20

J	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AER) DAMP	TOR	EXT DAMP
133.6	46497.	0.63E 07	-0.201	1.485	18.85	-0.00233	2.610	0.0
(438.4)	(971.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		17.456	2.953 0	0.010 200	0.070 220	0.014 104	0.026 33	0.011 113	0.009 188	0.008 161	0.004 340
CN		1.044	0.356 79	0.052 24	0.019 93	0.017 299	0.006 351	0.005 247	0.000 324	0.007 113	0.001 198
CM		-0.077	0.096 216	0.026 167	0.010 174	0.006 96	0.003 168	0.002 48	0.001 193	0.002 318	0.001 85
DCP 1	.010	3.317	1.316 18	.044 341	0.132 34	0.091 67	0.054 146	0.013 173	0.010 131	0.003 254	0.013 145
DCP 2	.020	3.307	1.129 1	0.128 129	0.086 335	0.090 69	0.046 104	0.018 135	0.028 158	0.015 32	0.007 116
DCP 3	.030	2.903	1.102 15	0.052 204	0.170 314	0.050 2	0.002 316	0.029 131	0.019 226	0.014 184	0.005 106
DCP 4	.049	2.497	0.803 1	0.165 180	0.089 117	0.092 7	0.063 313	0.052 273	0.061 209	0.047 120	0.040 73
DCP 5	.074	2.103	0.595 112	0.119 197	0.340 91	0.018 208	0.012 87	0.008 17	0.012 157	0.003 152	0.022 257
DCP 6	.099	1.602	0.554 35	0.148 14	0.021 34	0.318 272	0.017 339	0.024 58	0.030 95	0.019 129	0.007 181
DCP 7	.149	1.603	0.492 72	0.111 142	0.013 229	0.074 169	0.037 282	0.022 248	0.013 78	0.017 62	0.012 74

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA			1.593 0	0.064 13	0.053 219	0.021 122	0.026 69	0.012 93	0.015 190	0.013 121	0.012 2
CN		0.121	0.245 153	0.041 34	0.004 119	0.003 230	0.001 306	0.001 62	0.002 165	0.001 158	0.001 9
CM		-0.015	0.004 276	0.001 92	0.001 126	0.001 215	0.001 323	0.000 39	0.000 131	0.001 309	0.000 339
DCP 1	.010	-0.698	1.562 348	0.147 52	0.069 143	0.040 233	0.017 317	0.007 46	0.007 115	0.015 298	0.012 350
DCP 2	.020	-0.398	1.152 350	0.076 30	0.040 124	0.026 219	0.020 309	0.013 42	0.018 129	0.012 275	0.013 330
DCP 3	.030	-0.108	0.974 350	0.061 21	0.033 130	0.024 237	0.020 332	0.013 86	0.013 147	0.014 299	0.013 2
DCP 4	.049	0.188	0.801 350	0.046 15	0.028 117	0.020 208	0.015 307	0.010 74	0.011 133	0.009 273	0.011 321
DCP 5	.074	0.321	0.671 350	0.041 33	0.022 122	0.017 232	0.014 333	0.010 91	0.007 153	0.010 309	0.008 25
DCP 6	.099	0.385	0.567 351	0.036 35	0.018 125	0.015 224	0.010 329	0.010 84	0.008 155	0.009 308	0.007 32
DCP 7	.149	0.270	0.409 351	0.031 40	0.014 81	0.015 219	0.008 314	0.007 32	0.007 149	0.008 257	0.004 330
DCP 8	.200	0.214	0.343 353	0.020 46	0.012 119	0.007 216	0.007 304	0.007 5	0.007 168	0.004 259	0.004 305
DCP 9	.250	0.208	0.350 352	0.007 357	0.002 85	0.000 356	0.001 248	0.001 42	0.002 237	0.003 114	0.002 115
DCP10	.300	0.207	0.296 352	0.006 18	0.003 305	0.003 219	0.001 141	0.001 312	0.001 174	0.004 118	0.002 113
DCP11	.399	0.173	0.238 356	0.005 24	0.004 311	0.002 207	0.002 187	0.002 297	0.001 129	0.003 113	0.000 153
DCP12	.501	0.127	0.181 358	0.003 28	0.001 305	0.002 314	0.001 224	0.001 353	0.000 339	0.003 119	0.002 348
DCP13	.600	0.135	0.136 0	0.004 49	0.002 197	0.002 346	0.002 176	0.002 150	0.002 355	0.005 138	0.001 54
DCP14	.301	0.212	0.097 10	0.004 38	0.001 258	0.001 13	0.001 154	0.001 179	0.003 286	0.004 151	0.003 204
DCP15	.800	0.087	0.054 4	0.004 45	0.001 225	0.003 18	0.002 97	0.002 172	0.002 272	0.003 141	0.001 183
DCP16	.900	-0.103	0.011 7	0.001 133	0.004 359	0.001 62	0.003 153	0.001 293	0.001 168	0.004 111	0.003 123
DCP17	.949	-0.051	0.011 176	0.002 257	0.001 343	0.002 151	0.003 137	0.001 44	0.002 77	0.005 144	0.001 93

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.00	0.072	0.503	2.61	0.0	2.49	12115.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TPD	EXT DAMP
167.4	72859	0.795 07	-0.319	2.682	4.14	-0.30069	2.929	0.0
(549.1)	(1521.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.477	2.614 0	0.059 2	0.042 230	0.021 128	0.323 31	0.004 44	0.013 188	0.013 36	0.008 34
CN		0.404	0.274 353	0.005 336	0.000 168	0.001 218	0.001 313	0.031 65	0.001 165	0.004 53	0.002 129
CM		-0.010	0.007 317	0.000 249	0.000 296	0.000 202	0.001 174	0.000 49	0.000 338	0.001 210	0.000 320
DCP 1	.010	1.042	1.602 349	0.037 331	0.014 205	0.008 218	0.007 0	0.005 241	0.010 124	0.007 42	0.002 49
DCP 2	.020	0.975	1.386 350	0.021 330	0.002 162	0.002 267	0.002 11	0.002 76	0.002 113	0.002 79	0.004 102
DCP 3	.030	1.049	1.217 350	0.023 337	0.002 146	0.001 270	0.001 71	0.004 43	0.001 200	0.006 80	0.005 89
DCP 4	.040	1.189	1.038 350	0.025 289	0.002 242	0.001 64	0.001 289	0.002 96	0.002 179	0.005 63	0.001 107
DCP 5	.074	1.146	0.826 350	0.018 294	0.003 246	0.002 35	0.001 179	0.001 59	0.002 127	0.004 73	0.003 117
DCP 6	.093	1.079	0.699 350	0.012 342	0.010 337	0.011 227	0.009 117	0.007 31	0.004 250	0.004 86	0.002 102
DCP 7	.140	0.787	0.505 351	0.011 289	0.002 150	0.008 70	0.001 147	0.006 194	0.002 219	0.007 108	0.003 193
DCP 8	.200	0.626	0.412 354	0.006 345	0.001 258	0.001 81	0.003 351	0.002 153	0.002 53	0.004 88	0.002 108
DCP 9	.260	0.561	0.351 352	0.005 22	0.001 83	0.003 289	0.001 259	0.001 109	0.001 255	0.004 21	0.002 73
DCP10	.365	0.512	0.291 353	0.007 9	0.000 255	0.003 177	0.002 312	0.002 13	0.001 252	0.003 15	0.003 115
DCP11	.365	0.416	0.234 357	0.005 17	0.002 162	0.001 244	0.003 323	0.001 108	0.002 133	0.004 38	0.003 143
DCP12	.501	0.313	0.180 359	0.004 12	0.002 152	0.001 244	0.003 336	0.001 77	0.002 169	0.004 52	0.003 152
DCP13	.600	0.278	0.138 1	0.002 35	0.001 17	0.002 182	0.002 217	0.031 59	0.001 121	0.004 22	0.002 47
DCP14	.701	0.313	0.091 1	0.002 15	0.003 77	0.001 158	0.001 269	0.001 170	0.003 183	0.003 85	0.003 143
DCP15	.800	0.144	0.054 5	0.002 337	0.001 50	0.001 359	0.003 299	0.007 71	0.002 123	0.005 53	0.001 82
DCP16	.900	-0.089	0.014 355	0.001 123	0.001 275	0.002 339	0.004 343	0.002 271	0.002 214	0.002 11	0.006 179
DCP17	.969	-0.065	0.010 169	0.003 289	0.004 188	0.001 143	0.001 293	0.000 350	0.001 55	0.007 47	0.001 53

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.97	0.070	0.497	2.61	0.0	4.98	12115.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TPD	EXT DAMP
166.5	72294.	0.785 07	-0.013	2.955	7.65	-0.00092	1.197	0.0
(546.2)	(1509.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.978	2.627 0	0.065 0	0.053 218	0.028 115	0.026 41	0.013 35	0.020 183	0.012 77	0.010 23
CN		0.687	0.267 354	0.008 14	0.002 117	0.001 4	0.001 174	0.001 37	0.031 76	0.001 39	0.001 244
CM		-0.003	0.010 325	0.002 239	0.001 180	0.000 152	0.000 125	0.000 137	0.002 298	0.001 254	0.000 203
DCP 1	.010	2.908	1.062 349	0.106 251	0.036 40	0.043 235	0.055 128	0.039 5	0.013 43	0.027 349	0.009 226
DCP 2	.020	2.579	1.682 350	0.224 250	0.115 150	0.029 31	0.044 154	0.060 42	0.025 296	0.024 17	0.040 267
DCP 3	.030	2.433	1.399 350	0.142 258	0.129 151	0.110 51	0.050 108	0.029 35	0.067 290	0.067 196	0.047 81
DCP 4	.040	2.351	0.992 350	0.086 52	0.061 325	0.031 217	0.008 129	0.002 211	0.048 125	0.051 1	0.043 258
DCP 5	.074	2.096	0.813 350	0.033 36	0.019 333	0.015 228	0.010 140	0.007 33	0.004 281	0.002 123	0.006 48
DCP 6	.093	1.788	0.660 351	0.030 35	0.002 53	0.005 315	0.005 131	0.032 144	0.034 58	0.002 174	0.035 45
DCP 7	.140	1.296	0.490 352	0.026 40	0.004 132	0.004 229	0.002 241	0.002 38	0.031 73	0.031 46	0.002 38
DCP 8	.200	1.046	0.386 352	0.013 31	0.002 153	0.001 346	0.002 235	0.001 153	0.001 344	0.002 58	0.003 60
DCP 9	.250	0.917	0.329 355	0.013 29	0.001 327	0.002 16	0.002 64	0.031 37	0.002 111	0.003 70	0.002 107
DCP10	.300	0.830	0.272 356	0.013 32	0.001 74	0.001 271	0.002 43	0.001 85	0.001 318	0.001 32	0.002 111
DCP11	.365	0.652	0.217 358	0.011 38	0.002 64	0.002 4	0.001 132	0.003 17	0.001 318	0.004 63	0.001 33
DCP12	.501	0.491	0.167 0	0.010 43	0.001 21	0.002 267	0.002 243	0.002 237	0.002 244	0.001 345	0.001 345
DCP13	.600	0.412	0.124 2	0.009 43	0.001 14	0.002 348	0.001 138	0.031 150	0.001 135	0.004 34	0.001 304
DCP14	.701	0.407	0.070 4	0.008 43	0.001 344	0.001 342	0.002 33	0.002 298	0.033 111	0.003 93	0.031 118
DCP15	.800	0.192	0.033 14	0.007 47	0.002 54	0.001 6	0.002 95	0.031 70	0.002 117	0.004 44	0.001 349
DCP16	.900	-0.072	0.015 29	0.006 22	0.002 115	0.002 38	0.003 128	0.032 47	0.031 85	0.003 63	0.001 62
DCP17	.965	-0.073	0.007 177	0.001 246	0.001 351	0.001 301	0.002 295	0.002 323	0.002 84	0.004 75	0.002 314

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	22.97	0.071	0.494	2.63	0.0	7.45	12115.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
165.4	71586.	0.78E 07	-0.007	1.183	10.09	-0.00128	1.698	0.0
(542.5)	(1495.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.453	2.635	0	0.069	26	0.057	220	0.020	158	0.025	33	0.004	108	0.006	125	0.017	137	0.005	349
CN		0.927	0.208	6	0.042	9	0.017	225	0.009	87	0.003	349	0.004	33	0.004	303	0.005	166	0.003	130
CM		0.012	0.019	332	0.001	145	0.004	335	0.003	221	0.001	107	0.000	342	0.000	166	0.001	330	0.000	318
DCP 1	.010	4.449	1.130	349	0.508	59	0.107	311	0.011	140	0.075	108	0.034	0	0.027	110	0.012	55	0.003	336
DCP 2	.020	4.041	1.430	353	0.351	60	0.234	327	0.052	70	0.001	287	0.083	31	0.015	147	0.013	22	0.031	77
DCP 3	.030	3.847	1.452	354	0.141	44	0.228	331	0.023	65	0.109	313	0.048	39	0.049	286	0.047	15	0.021	212
DCP 4	.049	3.587	1.251	356	0.106	21	0.189	342	0.131	244	0.033	357	0.050	223	0.048	325	0.063	200	0.017	335
DCP 5	.074	2.736	0.643	8	0.202	351	0.062	232	0.071	279	0.078	185	0.007	248	0.064	179	0.046	107	0.026	53
DCP 6	.099	2.308	0.419	8	0.170	9	0.116	235	0.073	163	0.051	122	0.046	63	0.027	10	0.015	312	0.008	207
DCP 7	.149	1.712	0.324	3	0.076	20	0.037	235	0.026	151	0.022	101	0.023	46	0.018	345	0.014	285	0.012	224
DCP 8	.200	1.435	0.381	4	0.080	308	0.074	194	0.043	105	0.023	42	0.017	355	0.015	286	0.011	184	0.002	161
DCP 9	.250	1.265	0.357	0	0.083	278	0.082	166	0.049	69	0.020	355	0.014	329	0.016	271	0.017	179	0.012	115
DCP10	.300	1.079	0.259	3	0.051	296	0.053	170	0.036	66	0.019	338	0.006	296	0.009	254	0.013	153	0.006	83
DCP11	.399	0.843	0.172	11	0.026	344	0.025	175	0.025	59	0.017	313	0.007	192	0.002	66	0.006	177	0.007	128
DCP12	.501	0.621	0.102	23	0.035	32	0.008	217	0.010	44	0.008	277	0.005	173	0.004	359	0.005	191	0.003	101
DCP13	.600	0.491	0.064	45	0.038	34	0.010	246	0.005	39	0.003	269	0.003	71	0.005	332	0.005	166	0.003	127
DCP14	.701	0.425	0.053	109	0.045	44	0.012	264	0.006	86	0.003	297	0.002	345	0.001	0	0.005	158	0.001	196
DCP15	.800	0.198	0.040	112	0.025	36	0.008	214	0.006	66	0.001	319	0.004	64	0.001	302	0.004	141	0.001	218
DCP16	.990	-0.061	0.019	41	0.016	269	0.014	137	0.010	5	0.004	177	0.003	56	0.003	339	0.004	143	0.003	156
DCP17	.969	-0.074	0.010	11	0.014	258	0.011	153	0.003	50	0.001	357	0.002	59	0.003	255	0.006	113	0.002	37

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	22.97	0.069	0.505	2.53	0.0	9.92	12117.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
169.4	74080	0.79E 07	-0.024	1.205	13.66	-0.00142	1.910	0.0
(555.8)	(1547.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		9.924	2.537	0	0.396	44	0.050	238	0.036	177	0.039	58	0.041	19	0.039	133	0.012	151	0.009	14
CN		0.991	0.195	84	0.058	64	0.025	67	0.021	72	0.010	355	0.008	319	0.004	202	0.004	428	0.003	280
CM		0.006	0.020	219	0.015	94	0.003	141	0.005	139	0.001	99	0.001	59	0.001	6	0.001	292	0.001	329
DCP 1	.010	4.425	1.429	175	0.337	90	0.073	120	0.073	103	0.058	45	0.014	29	0.014	39	0.011	189	0.015	122
DCP 2	.020	4.491	1.440	191	0.496	99	0.099	87	0.099	103	0.091	46	0.039	6	0.022	22	0.015	308	0.005	322
DCP 3	.030	4.322	1.347	192	0.543	131	0.143	78	0.084	86	0.108	30	0.069	353	0.036	349	0.045	289	0.023	253
DCP 4	.049	3.618	1.651	177	0.495	90	0.296	164	0.126	109	0.017	171	0.096	86	0.058	133	0.036	114	0.017	7
DCP 5	.074	2.691	0.376	129	0.473	96	0.179	133	0.149	98	0.147	171	0.094	246	0.042	274	0.048	296	0.061	350
DCP 6	.099	2.340	0.245	116	0.274	70	0.120	52	0.119	64	0.041	61	0.039	94	0.042	150	0.017	162	0.030	183
DCP 7	.149	1.912	0.178	78	0.118	51	0.071	74	0.049	158	0.079	349	0.076	331	0.011	261	0.007	289	0.036	245
DCP 8	.200	1.537	0.190	63	0.138	55	0.075	39	0.073	31	0.054	8	0.047	4	0.016	340	0.029	21	0.071	356
DCP 9	.250	1.379	0.220	52	0.136	37	0.073	20	0.066	2	0.055	347	0.045	333	0.027	326	0.018	340	0.033	301
DCP10	.300	1.176	0.197	48	0.081	23	0.050	26	0.057	355	0.045	331	0.032	301	0.013	267	0.014	314	0.019	265
DCP11	.399	0.940	0.148	50	0.041	359	0.023	41	0.033	344	0.023	313	0.015	262	0.037	184	0.003	191	0.005	213
DCP12	.501	0.684	0.129	63	0.026	329	0.017	76	0.028	326	0.013	237	0.008	237	0.009	197	0.036	254	0.009	192
DCP13	.600	0.510	0.079	42	0.020	293	0.011	113	0.017	290	0.003	203	0.007	203	0.012	151	0.001	110	0.004	189
DCP14	.701	0.423	0.070	114	0.025	266	0.039	115	0.009	276	0.005	120	0.011	254	0.039	195	0.008	114	0.006	60
DCP15	.800	0.226	0.054	57	0.033	270	0.003	115	0.010	284	0.005	105	0.002	215	0.006	146	0.001	81	0.001	252
DCP16	.900	-0.019	0.025	11	0.023	252	0.013	345	0.005	300	0.003	284	0.005	121	0.003	273	0.004	143	0.006	116
DCP17	.969	-0.040	0.045	6	0.030	201	0.039	313	0.002	319	0.007	353	0.001	251	0.005	259	0.001	156	0.002	289

111

112

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TIMER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.91	0.070	0.500	2.46	0.0	12.45	12117.2	20

V _	Q	RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDB	EXT DAMP
167.6	72912.	0.78E 07	-0.052	1.172	11.02	-0.00191	2.551	0.0
(549.8)	(1522.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		12.447	2.465	0	0.067	17	0.034	218	0.010	129	0.013	17	0.040	2	0.019	175	0.013	50	0.008	65
CN		1.016	0.108	117	0.028	219	0.018	160	0.011	233	0.033	237	0.010	281	0.005	204	0.003	90	0.033	92
CM		-0.013	0.042	196	0.003	274	0.004	263	0.031	320	0.001	301	0.003	34	0.001	218	0.031	238	0.000	8
DCP 1	.010	4.205	0.671	178	0.043	255	0.061	239	0.011	335	0.009	310	0.018	322	0.047	233	0.036	74	0.015	236
DCP 2	.020	4.075	1.010	178	0.138	270	0.134	271	0.016	271	0.025	17	0.047	256	0.031	97	0.005	308
DCP 3	.030	3.393	1.057	181	0.295	274	0.215	239	0.057	291	0.062	245	0.070	335	0.035	7	0.020	293
DCP 4	.040	3.231	0.913	175	0.357	271	0.133	7	0.020	289	0.057	2	0.033	77	0.043	183	0.028	222	0.012	171
DCP 5	.074	2.510	0.630	163	0.193	249	0.025	327	0.017	295	0.024	12	0.030	0	0.017	160	0.028	181	0.035	264
DCP 6	.099	2.230	0.375	152	0.080	224	0.043	143	0.034	279	0.035	76	0.021	223	0.012	246	0.010	164	0.026	76
DCP 7	.149	1.833	0.213	133	0.052	109	0.052	129	0.039	233	0.013	191	0.016	274	0.014	278	0.009	43	0.004	84
DCP 8	.200	1.622	0.245	136	0.066	207	0.035	205	0.026	261	0.036	68	0.028	215	0.018	17	0.012	131	0.014	67
DCP 9	.250	1.465	0.218	122	0.042	162	0.030	201	0.023	218	0.015	254	0.021	344	0.037	145	0.034	290	0.010	74
DCP10	.300	1.270	0.162	114	0.054	155	0.040	144	0.034	196	0.018	233	0.025	333	0.012	272	0.003	93	0.006	100
DCP11	.359	1.024	0.141	70	0.036	148	0.030	163	0.020	184	0.025	319	0.026	258	0.015	152	0.011	41	0.001	231
DCP12	.501	0.758	0.136	52	0.015	199	0.023	126	0.015	172	0.030	166	0.017	228	0.005	42	0.035	217	0.013	172
DCP13	.602	0.571	0.128	39	0.023	234	0.022	120	0.031	6	0.009	129	0.011	232	0.004	201	0.009	120	0.009	112
DCP14	.701	0.440	0.114	33	0.023	260	0.011	57	0.035	256	0.005	124	0.009	221	0.003	97	0.011	59	0.036	350
DCP15	.802	0.275	0.125	22	0.032	26	0.015	40	0.001	304	0.036	67	0.009	126	0.007	241	0.032	228	0.033	140
DCP16	.900	0.350	0.099	13	0.000	50	0.012	98	0.007	206	0.008	62	0.035	235	0.004	333	0.030	70	0.036	244
DCP17	.949	-0.011	0.043	21	0.008	120	0.035	93	0.002	249	0.005	351	0.032	333	0.011	193	0.035	73	0.032	294

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TIMER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.91	0.070	0.498	2.49	0.0	14.90	12117.3	20

V _	Q	RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDB	EXT DAMP
166.7	72443.	0.78E 07	-0.074	1.278	14.50	-0.00194	2.589	0.0
(546.9)	(1513.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		14.905	2.490	0	0.064	17	0.021	217	0.033	197	0.007	106	0.003	162	0.028	23	0.021	191	0.004	127
CN		0.992	0.073	85	0.009	168	0.004	147	0.003	324	0.009	93	0.001	304	0.001	220	0.008	198	0.002	328
CM		-0.044	0.033	201	0.003	272	0.002	355	0.003	103	0.002	222	0.001	93	0.001	73	0.002	324	0.001	18
DCP 1	.010	3.518	0.427	160	0.014	302	0.042	70	0.015	93	0.012	46	0.016	302	0.003	339	0.006	290	0.020	215
DCP 2	.020	3.394	0.410	156	0.062	279	0.075	68	0.023	144	0.019	343	0.017	55	0.010	23	0.007	78	0.010	288
DCP 3	.030	3.216	0.554	172	0.114	244	0.065	41	0.059	106	0.017	276	0.024	54	0.027	29	0.036	16	0.010	183
DCP 4	.040	2.670	0.388	169	0.053	212	0.116	16	0.044	131	0.008	128	0.007	269	0.027	233	0.013	214	0.010	91
DCP 5	.074	2.194	0.195	162	0.040	224	0.014	350	0.017	127	0.012	292	0.005	265	0.013	257	0.008	209	0.018	64
DCP 6	.099	2.013	0.148	161	0.045	198	0.011	352	0.018	80	0.034	148	0.021	146	0.024	173	0.012	235	0.015	63
DCP 7	.149	1.755	0.096	144	0.031	179	0.018	127	0.015	47	0.012	148	0.009	265	0.006	203	0.022	195	0.023	25
DCP 8	.200	1.529	0.100	126	0.029	235	0.021	200	0.012	72	0.014	97	0.012	36	0.033	184	0.021	211	0.009	225
DCP 9	.250	1.471	0.121	122	0.011	196	0.023	186	0.010	349	0.018	142	0.033	31	0.036	129	0.010	247	0.015	196
DCP10	.300	1.262	0.118	107	0.005	14	0.023	178	0.005	8	0.028	116	0.008	200	0.018	59	0.014	244	0.030	291
DCP11	.359	1.071	0.132	76	0.018	92	0.024	154	0.008	326	0.017	133	0.013	141	0.011	47	0.017	214	0.014	302
DCP12	.501	0.831	0.125	48	0.010	119	0.014	152	0.017	297	0.016	30	0.002	270	0.009	8	0.008	196	0.011	227
DCP13	.600	0.652	0.125	35	0.014	121	0.012	163	0.013	292	0.008	57	0.006	71	0.007	228	0.004	165	0.006	77
DCP14	.701	0.524	0.120	29	0.009	131	0.033	132	0.013	267	0.008	74	0.025	279	0.004	268	0.005	161	0.004	52
DCP15	.800	0.369	0.119	23	0.007	89	0.005	250	0.010	284	0.009	56	0.006	271	0.005	222	0.010	125	0.002	206
DCP16	.900	0.122	0.086	22	0.008	137	0.001	12	0.002	271	0.009	8	0.004	312	0.032	235	0.011	133	0.007	183
DCP17	.949	0.017	0.036	32	0.002	305	0.003	43	0.004	217	0.005	351	0.009	318	0.007	240	0.003	179	0.003	143

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.93	0.070	0.496	2.51	0.0	17.57	12117.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
165.9	71916.	0.78E 07	-0.101	1.073	16.71	-0.00155	2.054	0.0
(544.2)	(1502.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		17.570	2.515	0	0.060	19	0.010	213	0.009	98	0.017	21	0.005	76	0.014	93	0.029	231	0.016	290
CN		1.004	0.766	92	0.071	331	0.038	191	0.025	178	0.003	330	0.001	111	0.004	19	0.004	213	0.002	351
CM		-0.071	0.025	292	0.032	222	0.002	58	0.000	347	0.001	225	0.001	78	0.000	53	0.003	55	0.002	107
DCP 1	.010	3.581	0.230	157	0.047	323	0.034	54	0.032	250	0.003	304	0.012	124	0.039	95	0.070	61	0.044	92
DCP 2	.020	3.143	0.266	156	0.042	132	0.349	65	0.021	253	0.016	310	0.009	37	0.026	64	0.025	152
DCP 3	.033	2.860	0.347	171	0.005	120	0.017	266	0.015	149	0.047	19	0.010	121	0.012	35	0.018	169	0.018	87
DCP 4	.049	2.310	0.309	158	0.048	312	0.011	229	0.036	288	0.005	264	0.036	113	0.019	339	0.018	211	0.011	91
DCP 5	.074	1.955	0.229	155	0.035	232	0.037	124	0.017	147	0.002	47	0.016	148	0.023	17	0.019	157	0.016	54
DCP 6	.099	1.817	0.170	155	0.015	353	0.045	128	0.027	101	0.013	1	0.013	4	0.016	44	0.017	88	0.019	57
DCP 7	.149	1.649	0.139	148	0.007	277	0.035	151	0.009	149	0.009	279	0.014	316	0.014	29	0.010	111	0.015	134
DCP 8	.200	1.459	0.102	128	0.011	269	0.014	193	0.006	129	0.003	192	0.011	119	0.019	40	0.007	189	0.010	69
DCP 9	.250	1.376	0.120	114	0.018	167	0.035	163	0.014	164	0.011	240	0.011	59	0.019	4	0.011	55	0.009	50
DCP10	.333	1.240	0.100	103	0.012	193	0.035	197	0.010	196	0.010	263	0.011	71	0.012	51	0.009	95	0.007	356
DCP11	.350	1.101	0.090	83	0.001	59	0.010	211	0.020	230	0.011	119	0.006	164	0.011	261	0.004	90	0.012	260
DCP12	.501	0.912	0.087	52	0.004	250	0.010	211	0.009	165	0.004	54	0.007	295	0.000	276	0.016	295	0.006	297
DCP13	.600	0.754	0.103	35	0.005	174	0.011	210	0.010	115	0.007	335	0.004	193	0.004	227	0.018	286	0.004	94
DCP14	.701	0.644	0.103	76	0.012	41	0.006	261	0.007	77	0.007	47	0.004	178	0.007	98	0.019	236	0.035	326
DCP15	.802	0.478	0.134	25	0.010	65	0.034	293	0.020	339	0.003	20	0.001	114	0.007	29	0.013	184	0.012	279
DCP16	.900	0.189	0.064	29	0.014	3	0.003	191	0.004	288	0.004	108	0.001	237	0.004	318	0.011	202	0.007	203
DCP17	.969	0.241	0.019	45	0.004	335	0.003	254	0.007	300	0.001	144	0.034	199	0.002	53	0.036	179	0.007	301

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.52	0.135	0.510	2.83	0.0	-0.21	12119.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
171.2	75454	0.80E 07	-0.227	0.377	2.96	-0.00065	0.900	0.0
(561.6)	(1575.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		-0.008	2.832	0	0.074	346	0.130	238	0.026	92	0.023	52	0.015	58	0.015	150	0.024	185	0.011	2
CN		0.122	0.252	353	0.005	346	0.004	282	0.004	101	0.001	321	0.001	100	0.001	191	0.003	193	0.001	265
CM		-0.016	0.010	297	0.001	341	0.001	185	0.000	258	0.000	127	0.000	77	0.000	0	0.031	29	0.000	113
DCP 1	.010	-0.861	1.766	342	0.123	32	0.034	170	0.021	148	0.011	112	0.020	75	0.002	316	0.003	353	0.001	190
DCP 2	.020	-0.399	1.304	346	0.032	338	0.017	243	0.017	113	0.002	157	0.003	123	0.002	23	0.003	66	0.004	225
DCP 3	.033	-0.116	1.398	346	0.028	298	0.015	251	0.013	113	0.004	237	0.002	147	0.002	0	0.000	284	0.004	199
DCP 4	.049	0.177	0.909	347	0.024	391	0.012	241	0.012	100	0.003	144	0.001	253	0.006	71	0.003	22	0.002	5
DCP 5	.074	0.309	0.754	347	0.017	316	0.014	266	0.009	94	0.003	210	0.001	23	0.002	73	0.002	317	0.002	141
DCP 6	.099	0.371	0.636	348	0.016	319	0.010	266	0.011	104	0.003	206	0.031	90	0.003	100	0.002	69	0.002	125
DCP 7	.149	0.262	0.459	349	0.016	14	0.016	288	0.008	128	0.001	176	0.002	187	0.004	59	0.001	38	0.002	252
DCP 8	.200	0.207	0.341	355	0.011	337	0.002	252	0.009	106	0.005	87	0.002	45	0.005	77	0.004	82	0.001	250
DCP 9	.250	0.203	0.336	352	0.007	339	0.006	243	0.003	12	0.001	279	0.001	126	0.005	138	0.004	155	0.001	170
DCP10	.300	0.188	0.278	352	0.006	319	0.006	269	0.003	68	0.000	298	0.002	100	0.004	170	0.003	119	0.003	111
DCP11	.350	0.170	0.224	1	0.006	10	0.005	296	0.004	88	0.003	346	0.004	83	0.002	202	0.004	177	0.001	189
DCP12	.501	0.129	0.168	4	0.002	6	0.005	300	0.002	88	0.004	327	0.001	116	0.002	134	0.004	170	0.002	337
DCP13	.600	0.138	0.127	8	0.001	258	0.003	327	0.002	66	0.001	170	0.002	98	0.001	193	0.005	226	0.001	50
DCP14	.701	0.212	0.090	12	0.000	241	0.002	316	0.001	16	0.001	85	0.004	289	0.002	148	0.005	229	0.002	210
DCP15	.800	0.089	0.051	20	0.003	33	0.002	18	0.004	121	0.003	324	0.002	238	0.001	344	0.007	204	0.004	311
DCP16	.900	-0.099	0.015	54	0.003	174	0.002	358	0.002	23	0.002	313	0.001	237	0.002	111	0.005	192	0.002	316
DCP17	.969	-0.048	0.013	183	0.002	109	0.001	76	0.004	165	0.005	212	0.033	77	0.002	209	0.004	239	0.003	220

114

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ 0.0	DRIVE HZ 45.59	K 0.137	MACH NO 0.505	DEL.ALPHA 2.82	DEL.H 0.0	ALPHA.0 2.47	TEST POINT 12119.7	CYCLES ANALYSED 23
V 169.3 (555.5)	Q 74315. (1552.1)	RN 0.79E 07	CNMIN) -0.024	CN(MAX) 0.646	ALPHA.NMAX 5.37	AERO DAMP -0.00066	TDP 0.908	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.473	2.824 0	0.074 1	0.053 241	0.038 115	0.026 49	0.017 99	0.018 187	0.021 233	0.006 37
CN		0.396	0.254 353	0.005 354	0.002 240	0.004 169	0.001 121	0.001 136	0.001 190	0.001 281	0.001 199
CM		-0.011	0.011 331	0.001 252	0.000 49	0.000 65	0.000 16	0.000 7	0.001 27	0.001 92	0.000 339
DCP 1	.010	0.887	1.587 341	0.344 338	0.036 277	0.012 183	0.012 326	0.002 241	0.005 128	0.010 249	0.013 271
DCP 2	.020	0.974	1.314 346	0.022 327	0.006 276	0.015 137	0.003 88	0.004 41	0.003 63	0.000 65	0.003 298
DCP 3	.030	1.069	1.155 346	0.020 302	0.004 279	0.010 128	0.001 86	0.001 120	0.001 56	0.002 294	0.002 303
DCP 4	.049	1.175	0.984 346	0.021 292	0.035 286	0.013 134	0.001 271	0.002 12	0.002 46	0.003 72	0.002 302
DCP 5	.074	1.131	0.782 347	0.015 290	0.008 291	0.010 121	0.003 28	0.001 17	0.003 105	0.003 41	0.003 305
DCP 6	.099	1.064	0.661 348	0.010 336	0.010 306	0.017 178	0.011 98	0.003 2	0.004 228	0.002 151	0.002 20
DCP 7	.149	0.770	0.473 349	0.011 304	0.009 97	0.014 162	0.007 75	0.007 126	0.002 124	0.006 89	0.004 169
DCP 8	.200	0.616	0.390 354	0.011 12	0.001 298	0.012 144	0.001 164	0.001 146	0.001 127	0.005 158	0.002 251
DCP 9	.250	0.549	0.339 352	0.009 0	0.003 312	0.004 145	0.003 291	0.003 151	0.003 166	0.003 305	0.001 137
DCP10	.300	0.490	0.276 353	0.007 9	0.003 261	0.006 175	0.002 157	0.001 175	0.003 184	0.004 249	0.001 167
DCP11	.399	0.409	0.220 1	0.005 69	0.002 307	0.004 223	0.002 162	0.001 96	0.003 257	0.005 287	0.001 241
DCP12	.501	0.309	0.166 6	0.003 36	0.003 373	0.001 242	0.001 83	0.004 144	0.001 347	0.005 256	0.003 157
DCP13	.600	0.274	0.126 9	0.004 19	0.001 316	0.003 118	0.003 29	0.002 151	0.003 347	0.001 303	0.001 236
DCP14	.701	0.308	0.085 12	0.006 353	0.002 247	0.002 216	0.003 230	0.002 138	0.004 146	0.003 224	0.001 271
DCP15	.800	0.130	0.049 72	0.004 39	0.001 244	0.002 198	0.002 147	0.003 277	0.001 177	0.004 177	0.002 53
DCP16	.900	-0.084	0.012 29	0.003 67	0.004 219	0.006 212	0.001 229	0.002 74	0.001 179	0.005 209	0.003 167
DCP17	.965	-0.062	0.011 175	0.004 162	0.002 180	0.004 25	0.000 166	0.001 233	0.004 245	0.007 197	0.002 178

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ 0.0	DRIVE HZ 45.53	K 0.138	MACH NO 0.507	DEL.ALPHA 2.82	DEL.H 0.0	ALPHA.0 4.93	TEST POINT 12119.3	CYCLES ANALYSED 20
V 168.2 (551.9)	Q 73635. (1537.9)	RN 0.79E 07	CNMIN) -0.019	CN(MAX) 0.92.	ALPHA.NMAX 7.89	AERO DAMP -0.00083	TDP 1.299	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.934	2.824 0	0.074 355	0.048 243	0.035 110	0.031 54	0.013 29	0.009 189	0.020 113	0.003 9
CN		0.271	0.249 354	0.008 2	0.001 347	0.001 73	0.003 114	0.002 41	0.001 315	0.005 122	0.001 84
CM		-0.004	0.015 309	0.002 319	0.000 222	0.001 89	0.000 39	0.000 309	0.001 232	0.001 300	0.000 81
DCP 1	.010	2.794	1.889 340	0.129 226	0.027 311	0.035 189	0.069 82	0.029 126	0.013 137	0.024 308	0.018 166
DCP 2	.020	2.506	1.601 346	0.214 248	0.119 140	0.047 41	0.050 122	0.075 15	0.042 269	0.014 324	0.047 234
DCP 3	.030	2.358	1.326 346	0.167 250	0.169 140	0.164 38	0.001 290	0.004 47	0.062 261	0.002 160	0.077 55
DCP 4	.049	2.175	0.906 347	0.127 49	0.130 313	0.042 202	0.050 106	0.027 4	0.002 149	0.015 148	0.027 279
DCP 5	.074	1.965	0.789 347	0.023 15	0.023 342	0.005 151	0.000 172	0.009 36	0.002 318	0.002 57	0.092 119
DCP 6	.099	1.746	0.634 349	0.026 18	0.007 313	0.008 87	0.007 49	0.004 92	0.004 54	0.005 76	0.005 349
DCP 7	.149	1.269	0.469 349	0.026 28	0.003 341	0.007 72	0.002 198	0.002 101	0.001 300	0.001 358	0.002 42
DCP 8	.200	1.022	0.171 354	0.013 77	0.034 328	0.009 60	0.001 166	0.001 256	0.003 52	0.001 254	0.002 192
DCP 9	.250	0.892	0.307 354	0.014 19	0.005 316	0.004 196	0.002 91	0.003 214	0.002 78	0.006 97	0.001 54
DCP10	.300	0.777	0.255 355	0.013 17	0.003 320	0.001 262	0.001 94	0.002 77	0.001 114	0.004 101	0.001 37
DCP11	.399	0.640	0.203 4	0.012 25	0.002 352	0.001 40	0.003 128	0.003 45	0.001 191	0.005 117	0.002 96
DCP12	.521	0.488	0.157 8	0.008 17	0.001 92	0.003 251	0.003 135	0.001 143	0.001 86	0.005 117	0.001 176
DCP13	.600	0.408	0.116 13	0.007 22	0.003 58	0.002 291	0.003 92	0.002 117	0.002 69	0.007 124	0.002 30
DCP14	.701	0.396	0.072 21	0.005 37	0.002 20	0.002 249	0.002 176	0.002 149	0.001 42	0.007 123	0.002 262
DCP15	.800	0.189	0.044 38	0.006 29	0.001 32	0.003 244	0.002 151	0.001 92	0.007 335	0.006 127	0.003 194
DCP16	.900	-0.068	0.015 55	0.004 1	0.004 161	0.001 39	0.000 20	0.004 62	0.002 19	0.006 105	0.001 21
DCP17	.965	-0.072	0.012 181	0.005 207	0.003 8	0.002 337	0.001 64	0.002 339	0.002 46	0.004 148	0.002 2

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.54	0.138	0.501	2.47	0.0	7.45	17119.4	23

V	Q	RN	C(M(MIN)	C(M(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
167.5	73199.	0.79E 07	-0.211	1.159	10.29	-3.00109	1.447	0.0
(549.4)	(1528.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.446	2.830	0	0.093	10	0.090	256	3.015	308	0.037	61	0.013	40	3.012	259	0.005	198	0.006	29
CN		2.996	0.324	13	3.337	318	3.314	141	3.012	355	0.034	270	3.034	356	3.034	123	3.007	160	3.037	14
CM		0.919	3.322	312	0.094	76	3.034	293	3.034	197	0.091	19	3.033	165	3.093	264	3.031	52	0.009	43
CP 1	.010	4.171	1.193	340	3.424	41	3.151	278	1.998	77	0.343	33	3.347	344	3.307	30	3.039	152	3.033	49
CP 2	.020	3.462	1.464	345	3.208	41	3.737	318	3.079	139	0.386	343	3.039	36	3.024	268	0.061	98	0.315	61
CP 3	.037	3.603	1.475	354	3.066	170	3.274	299	3.055	299	0.130	320	3.037	295	3.005	309	3.037	15	3.373	291
CP 4	.040	3.316	1.763	7	3.214	12	3.253	323	3.276	227	0.307	65	3.136	241	3.344	114	0.277	338	3.353	124
CP 5	.074	2.658	3.497	11	3.273	342	3.134	344	3.347	240	0.393	194	3.061	147	3.065	199	3.087	89	3.057	50
CP 6	.090	2.259	3.498	7	3.176	339	3.138	237	0.071	127	0.033	91	3.333	50	3.331	27	3.021	342	3.324	314
CP 7	.140	1.661	3.362	4	3.353	325	3.251	143	3.039	66	3.271	348	3.311	331	3.003	347	3.336	186	3.007	154
CP 8	.200	1.397	3.411	6	3.107	265	3.389	142	3.057	52	3.076	352	3.084	391	3.311	310	3.317	119	3.316	43
CP 9	.250	1.227	3.380	359	3.117	239	3.113	117	3.081	12	3.346	284	3.337	217	3.327	136	3.315	34	3.314	353
CP10	.300	1.337	3.388	3	3.374	253	3.349	118	3.05C	3	3.378	257	3.317	148	3.014	95	3.038	354	3.004	325
CP11	.300	3.921	3.194	71	3.337	287	3.034	115	3.078	345	3.014	236	3.038	140	3.006	76	3.013	112	3.006	214
CP12	.501	3.638	3.143	34	3.324	314	3.377	130	3.324	353	3.315	231	3.036	64	3.033	297	3.033	297	3.031	170
CP13	.600	3.475	3.113	59	3.335	353	3.339	125	3.014	327	3.008	179	3.035	6	3.037	65	0.034	358	0.037	178
CP14	.701	3.417	3.100	90	3.037	353	3.397	151	3.011	320	0.007	181	3.036	317	3.033	134	3.333	194	3.331	125
CP15	.800	0.107	3.174	64	3.374	378	3.014	134	3.010	341	3.331	308	3.33	297	3.034	12	3.337	324	3.032	342
CP16	.900	-0.253	3.227	49	3.019	236	3.717	40	3.003	264	0.307	46	3.032	283	3.003	316	0.005	177	3.301	78
CP17	.965	-0.076	3.038	12	0.016	213	3.338	83	3.331	276	3.393	343	3.032	114	3.033	357	3.333	83	3.035	287

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.54	0.138	0.502	2.77	0.0	9.90	12171.1	23

V	Q	RN	C(M(MIN)	C(M(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
170.4	74880.	0.79E 07	-0.345	1.290	11.77	-3.00117	1.493	0.0
(559.0)	(1563.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		9.905	2.713	2	3.135	59	3.347	338	3.135	107	3.319	91	3.017	56	3.033	133	0.019	184	3.038	178
CN		3.074	3.199	75	3.293	19	3.036	334	3.026	254	0.013	178	3.032	213	3.034	145	3.003	115	3.013	248
CM		0.904	3.029	274	3.029	97	3.034	53	3.007	32	3.133	334	3.020	213	3.031	211	3.023	19	3.131	171
CP 1	.010	4.716	3.345	162	3.467	82	3.149	17	3.041	352	3.378	333	3.022	355	3.039	302	3.017	367	3.314	138
CP 2	.020	4.337	3.364	167	3.645	91	3.191	33	3.018	283	3.357	42	3.065	13	3.049	322	3.024	286	3.034	321
CP 3	.037	4.347	3.349	172	3.440	97	3.146	40	3.338	85	3.378	41	3.047	343	3.011	7	3.035	23	3.035	340
CP 4	.040	3.353	3.360	135	3.307	90	3.192	344	3.061	355	3.017	330	0.014	42	3.077	31	0.388	86	3.026	183
CP 5	.074	2.603	3.570	137	3.305	76	3.192	61	3.143	174	3.172	149	3.094	164	3.135	303	3.368	234	3.074	263
CP 6	.090	3.368	3.394	99	3.311	43	3.152	8	3.374	4	3.340	19	3.343	66	3.049	37	3.029	53	3.036	130
CP 7	.140	1.806	3.340	74	3.336	33	3.152	339	3.074	329	0.031	377	3.016	311	3.009	348	3.037	33	3.037	243
CP 8	.200	1.538	3.357	66	3.315	14	3.131	316	3.383	104	3.347	348	3.320	349	3.027	283	3.315	393	3.375	235
CP 9	.251	1.347	3.347	56	3.212	356	3.113	309	3.096	275	3.371	234	3.340	217	3.043	293	3.029	192	3.029	383
CP10	.300	1.130	3.313	55	3.155	349	3.375	337	3.077	281	3.038	207	3.028	167	3.029	167	3.013	179	3.317	149
CP11	.300	3.800	3.249	65	3.133	343	3.333	339	3.349	263	3.333	195	3.016	135	3.033	146	3.023	87	3.034	71
CP12	.501	3.678	3.214	68	3.387	329	3.371	273	3.047	237	3.036	193	3.034	133	3.011	105	3.006	119	0.007	37
CP13	.600	0.529	3.170	75	3.074	309	3.370	212	3.031	226	3.321	190	3.037	81	3.013	33	3.303	294	3.037	6
CP14	.701	3.434	3.147	86	3.373	291	3.312	177	3.370	212	3.019	134	3.035	36	3.036	357	3.005	191	3.038	324
CP15	.800	3.238	3.113	95	3.368	262	3.311	177	3.330	177	3.012	47	3.007	393	3.055	13	3.034	133	3.035	315
CP16	.900	-3.315	3.388	18	3.342	263	3.331	353	3.317	164	3.397	26	3.037	3	3.033	274	3.335	182	3.039	274
CP17	.963	-3.353	3.366	13	0.019	274	3.338	278	3.011	189	3.006	135	3.037	40	3.003	4	3.031	17	3.036	344

115

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.58	0.138	0.501	7.64	0.0	17.44	12121.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
168.1	73467.	0.79E 07	-0.069	1.313	11.85	-0.08179	7.446	0.0
(551.6)	(1534.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.444	2.639 0	0.048 348	0.128 174	0.043 116	0.032 30	0.007 50	0.018 275	0.005 188	0.008 354
CN		1.314	0.223 97	0.052 134	0.031 114	0.012 117	0.004 60	0.006 305	0.007 286	0.003 32	0.002 53
CM		-0.039	0.051 207	0.007 225	0.039 176	0.004 243	0.003 201	0.001 154	0.001 126	0.001 268	0.000 40
DCP 1	.010	4.425	0.912 170	0.371 143	0.069 161	0.027 266	0.014 278	0.006 113	0.013 15	0.020 187	0.012 31
DCP 2	.020	4.144	1.122 175	0.073 132	0.179 199	0.039 294	0.057 243	0.030 331	0.020 302	0.023 310	0.010 89
DCP 3	.035	3.926	1.133 183	0.095 178	0.288 294	0.037 276	0.089 222	0.055 357	0.019 261	0.039 348	0.021 187
DCP 4	.049	3.302	1.159 171	0.311 250	0.121 140	0.093 288	0.043 27	0.013 75	0.034 78	0.031 123	0.016 101
DCP 5	.074	2.632	0.830 146	0.236 210	0.036 192	0.051 7	0.013 47	0.015 334	0.029 360	0.030 333	0.012 323
DCP 6	.099	2.204	0.994 123	0.163 154	0.132 152	0.032 278	0.014 241	0.019 335	0.035 250	0.017 32	0.028 341
DCP 7	.149	1.846	0.413 97	0.113 130	0.126 119	0.063 154	0.031 155	0.017 243	0.011 248	0.030 268	0.006 168
DCP 8	.200	1.604	0.408 99	0.169 146	0.118 140	0.064 106	0.016 247	0.028 304	0.020 306	0.016 7	0.000 328
DCP 9	.250	1.479	0.420 82	0.187 119	0.132 115	0.057 149	0.020 224	0.031 232	0.017 284	0.009 327	0.012 70
DCP10	.300	1.267	0.353 76	0.140 120	0.098 101	0.039 147	0.028 165	0.016 306	0.012 232	0.008 316	0.007 56
DCP11	.399	0.909	0.300 75	0.088 114	0.052 73	0.045 121	0.009 87	0.007 131	0.009 293	0.012 135	0.031 180
DCP12	.501	0.739	0.244 67	0.051 97	0.036 14	0.033 83	0.024 42	0.013 33	0.002 336	0.012 143	0.015 85
DCP13	.600	0.563	0.199 62	0.016 97	0.025 355	0.018 65	0.014 21	0.009 334	0.009 251	0.010 39	0.032 305
DCP14	.701	0.443	0.165 55	0.009 259	0.023 344	0.014 23	0.017 338	0.005 339	0.011 348	0.007 352	0.011 290
DCP15	.800	0.276	0.168 38	0.016 17	0.022 375	0.018 33	0.008 9	0.014 321	0.036 350	0.002 229	0.002 140
DCP16	.900	0.045	0.125 21	0.032 30	0.011 343	0.006 355	0.008 1	0.005 288	0.006 309	0.002 100	0.006 188
DCP17	.969	-0.018	0.054 24	0.020 45	0.011 46	0.006 12	0.004 276	0.002 250	0.006 316	0.005 46	0.006 13

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.57	0.139	0.498	7.64	0.0	14.89	12121.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
166.8	72539.	0.79E 07	-0.392	1.720	13.96	-0.00210	2.570	0.0
(547.2)	(1515.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		14.886	2.643 0	0.047 346	0.033 246	0.052 133	0.017 35	0.009 45	0.014 182	0.013 213	0.002 340
CN		1.006	0.167 89	0.038 135	0.015 220	0.011 177	0.003 150	0.002 332	0.001 103	0.001 281	0.001 253
CM		-0.047	0.045 213	0.011 251	0.002 308	0.002 296	0.002 276	0.001 11	0.000 40	0.001 224	0.002 192
DCP 1	.010	3.713	0.308 158	0.072 281	0.008 350	0.008 227	0.008 348	0.007 89	0.018 71	0.013 80	0.022 127
DCP 2	.020	3.471	0.456 155	0.114 283	0.011 113	0.010 161	0.020 354	0.019 123	0.023 187	0.007 88	0.013 161
DCP 3	.035	3.342	0.716 173	0.253 259	0.122 340	0.034 154	0.040 275	0.031 23	0.013 152	0.021 233	0.024 97
DCP 4	.049	2.646	0.623 156	0.134 210	0.060 272	0.027 187	0.007 201	0.007 51	0.018 198	0.009 314	0.023 259
DCP 5	.074	2.178	0.491 145	0.092 191	0.062 258	0.040 170	0.004 226	0.020 17	0.010 78	0.024 305	0.015 280
DCP 6	.099	1.994	0.359 117	0.084 185	0.062 240	0.039 205	0.023 154	0.005 261	0.028 88	0.012 244	0.017 249
DCP 7	.149	1.731	0.288 115	0.106 150	0.058 240	0.022 234	0.017 312	0.011 78	0.013 1	0.017 177	0.039 235
DCP 8	.200	1.517	0.329 110	0.095 185	0.025 293	0.008 183	0.019 7	0.011 137	0.012 18	0.009 289	0.010 250
DCP 9	.250	1.437	0.251 99	0.085 149	0.039 230	0.021 255	0.012 277	0.011 253	0.012 171	0.012 773	0.008 277
DCP10	.300	1.275	0.237 94	0.078 149	0.048 188	0.016 209	0.014 213	0.017 323	0.034 285	0.008 141	0.014 169
DCP11	.399	1.046	0.228 79	0.042 120	0.027 217	0.019 151	0.027 192	0.012 333	0.011 355	0.015 16	0.008 230
DCP12	.501	0.955	0.212 60	0.065 117	0.015 159	0.008 157	0.010 145	0.015 267	0.009 747	0.014 266	0.012 184
DCP13	.600	0.680	0.193 45	0.042 107	0.014 151	0.012 180	0.021 121	0.009 296	0.036 164	0.012 142	0.014 102
DCP14	.701	0.549	0.196 43	0.043 72	0.003 127	0.013 142	0.018 62	0.007 149	0.011 147	0.011 90	0.018 67
DCP15	.800	0.378	0.173 38	0.037 56	0.003 195	0.010 113	0.000 49	0.002 787	0.004 724	0.005 43	0.013 341
DCP16	.900	0.135	0.110 41	0.026 48	0.005 73	0.004 59	0.011 12	0.013 139	0.005 354	0.010 346	0.016 324
DCP17	.969	0.015	0.047 48	0.018 44	0.004 123	0.006 181	0.003 160	0.006 155	0.005 46	0.021 268	0.008 316

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.60	0.140	0.497	7.67	0.0	17.60	12121.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
166.2	77304.	0.79E 07	-0.112	1.157	17.41	-0.00181	7.448	0.0
(545.2)	(1510.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		17.596	7.666	0	0.066	18	0.024	231	0.058	55	0.033	30	0.005	62	0.017	207	0.008	200	0.018	5
CN		1.012	0.132	85	0.013	30	0.036	204	0.006	44	0.007	70	0.003	254	0.004	223	0.003	192	0.034	147
CM		-0.064	0.036	222	0.005	217	0.001	328	0.001	111	0.001	214	0.001	5	0.002	53	0.001	332	0.001	268
DCP 1	.010	3.651	0.176	151	0.058	46	0.354	26	0.007	301	0.022	40	0.024	28	0.076	174	0.033	322	0.013	258
DCP 2	.020	3.181	0.342	151	0.085	83	0.067	72	0.011	6	0.027	11	0.012	64	0.019	126	0.039	266	0.005	318
DCP 3	.030	2.820	0.441	167	0.066	66	0.043	177	0.012	0	0.034	48	0.015	168	0.015	67	0.019	270	0.027	204
DCP 4	.040	2.411	0.328	144	0.054	307	0.021	731	0.033	72	0.012	250	0.010	337	0.001	170	0.013	0	0.015	40
DCP 5	.074	2.059	0.202	139	0.083	254	0.014	210	0.041	107	0.035	174	0.004	115	0.039	168	0.003	151	0.003	3
DCP 6	.109	1.917	0.150	171	0.091	249	0.040	207	0.023	84	0.009	111	0.003	287	0.013	258	0.013	125	0.023	218
DCP 7	.145	1.497	0.143	117	0.012	239	0.041	230	0.028	98	0.025	137	0.018	258	0.019	65	0.013	335	0.016	162
DCP 8	.200	1.448	0.153	129	0.032	204	0.011	330	0.020	68	0.026	107	0.016	174	0.005	73	0.004	272	0.010	304
DCP 9	.250	1.340	0.144	110	0.014	257	0.012	277	0.008	78	0.015	156	0.039	124	0.036	152	0.007	732	0.008	140
DCP10	.300	1.249	0.183	96	0.013	167	0.036	251	0.010	79	0.013	33	0.039	68	0.006	230	0.035	706	0.008	130
DCP11	.390	1.106	0.202	81	0.025	73	0.013	158	0.024	22	0.017	54	0.009	307	0.017	247	0.038	266	0.008	180
DCP12	.531	0.899	0.183	69	0.021	54	0.034	114	0.015	39	0.015	57	0.009	221	0.013	144	0.011	157	0.023	133
DCP13	.600	0.749	0.146	58	0.022	20	0.003	190	0.018	305	0.015	27	0.012	222	0.008	222	0.017	203	0.018	100
DCP14	.701	0.637	0.157	47	0.019	17	0.013	230	0.018	274	0.001	177	0.003	124	0.017	233	0.035	103	0.035	4
DCP15	.800	0.473	0.141	41	0.010	78	0.007	150	0.390	290	0.007	224	0.036	51	0.004	247	0.036	75	0.001	289
DCP16	.900	0.191	0.105	49	0.021	28	0.011	149	0.005	169	0.005	148	0.036	169	0.014	296	0.005	147	0.004	300
DCP17	.965	0.034	0.046	58	0.015	3	0.034	50	0.007	104	0.002	347	0.002	336	0.007	1	0.007	117	0.001	288

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	69.74	0.211	0.498	1.12	0.0	-0.02	12123.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
166.6	73932.	0.80E 07	-0.131	0.150	7.23	-0.00061	7.844	0.0
(546.5)	(1544.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		-0.318	1.119	0	0.002	315	0.003	232	0.018	152	0.002	161	0.036	64	0.003	173	0.007	216	0.004	256
CN		0.112	0.244	358	0.007	332	0.035	250	0.002	220	0.001	241	0.003	125	0.002	200	0.001	107	0.001	154
CM		-0.015	0.016	296	0.001	254	0.001	98	0.001	69	0.000	155	0.001	333	0.001	43	0.000	250	0.000	332
DCP 1	.010	-0.034	1.003	339	0.078	7	0.010	131	0.015	98	0.014	173	0.035	48	0.005	304	0.003	60	0.013	121
DCP 2	.020	-0.043	1.015	346	0.045	300	0.010	185	0.011	167	0.013	163	0.034	74	0.001	246	0.001	101	0.002	147
DCP 3	.030	-0.163	1.151	345	0.041	279	0.012	195	0.009	162	0.004	162	0.001	97	0.005	290	0.002	103	0.003	116
DCP 4	.040	0.140	0.914	347	0.040	277	0.013	212	0.006	118	0.007	161	0.005	48	0.008	340	0.002	275	0.007	0
DCP 5	.074	0.290	0.756	347	0.020	283	0.038	236	0.004	102	0.035	107	0.004	47	0.002	4	0.001	174	0.033	145
DCP 6	.099	0.358	0.611	349	0.014	285	0.005	246	0.005	136	0.004	183	0.009	41	0.003	352	0.002	254	0.002	227
DCP 7	.149	0.247	0.451	351	0.013	346	0.013	274	0.003	162	0.007	241	0.007	101	0.007	16	0.006	247	0.002	358
DCP 8	.200	0.195	0.394	350	0.013	307	0.004	276	0.004	185	0.002	183	0.003	125	0.005	28	0.002	14	0.003	188
DCP 9	.250	0.181	0.325	355	0.007	321	0.007	262	0.001	246	0.002	179	0.002	6	0.004	274	0.004	174	0.035	79
DCP10	.300	0.193	0.271	357	0.010	336	0.006	266	0.004	217	0.005	200	0.004	135	0.004	274	0.001	145	0.007	288
DCP11	.390	0.169	0.220	11	0.008	347	0.034	258	0.038	210	0.005	265	0.003	97	0.004	274	0.003	110	0.002	110
DCP12	.571	0.114	0.166	16	0.011	13	0.004	191	0.004	260	0.003	298	0.004	180	0.001	44	0.001	56	0.004	297
DCP13	.600	0.128	0.174	73	0.007	27	0.003	256	0.003	274	0.003	344	0.007	119	0.033	249	0.002	90	0.001	109
DCP14	.701	0.203	0.085	93	0.033	53	0.005	274	0.002	246	0.004	332	0.007	169	0.005	287	0.002	192	0.002	106
DCP15	.800	0.093	0.052	43	0.006	63	0.007	307	0.006	266	0.002	90	0.004	137	0.003	357	0.004	44	0.002	114
DCP16	.900	-0.103	0.021	74	0.001	344	0.017	296	0.035	195	0.001	122	0.002	155	0.008	249	0.001	86	0.004	119
DCP17	.965	-0.051	0.020	193	0.003	135	0.004	221	0.003	35	0.003	269	0.003	193	0.035	103	0.004	75	0.001	314

117

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
3.0	69.09 *	0.212	0.496	3.13	0.0	2.50	12123.7	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TPO	EXT DAMP
165.9	73616.	0.80E 07	-0.028	0.649	5.74	-0.00067	0.424	3.0
(544.2)	(1537.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RFS 0	RFS 1 PHI	RFS 2 PHI	RFS 3 PHI	RFS 4 PHI	RFS 5 PHI	RFS 6 PHI	RFS 7 PHI	RFS 8 PHI	RFS 9 PHI
ALPHA		2.490	3.132 0	0.100 317	0.093 144	0.017 178	0.029 53	0.024 91	0.013 18*	0.005 210	0.009 227
CN		0.395	0.244 158	0.008 334	0.091 174	0.002 218	0.002 147	0.002 96	0.008 114	0.003 *	0.001 291
CM		-0.009	0.018 296	0.002 233	0.003 14	0.000 127	0.001 23	0.000 23	0.002 324	0.009 164	0.000 184
XCP 1	.010	1.033	1.647 339	0.028 245	0.025 171	0.035 314	0.009 357	0.013 92	1.017 138	0.011 917	0.009 242
XCP 2	.020	0.966	1.373 346	0.041 290	0.035 129	0.005 158	0.011 43	0.013 143	0.027 357	0.003 9	0.007 292
XCP 3	.030	1.064	1.150 345	0.041 275	0.005 113	0.002 185	0.008 58	0.002 284	0.014 92	0.003 55	0.002 339
XCP 4	.049	1.172	0.981 346	0.040 271	0.004 156	0.004 136	0.003 68	0.003 31	0.012 129	0.008 85	0.002 293
XCP 5	.074	1.193	0.779 347	0.031 277	0.003 185	0.002 138	0.008 68	0.003 373	0.015 126	0.005 68	0.004 251
XCP 6	.099	1.066	0.651 348	0.024 317	0.011 271	0.016 174	0.012 81	0.003 321	0.010 74	0.003 36	0.003 297
XCP 7	.145	0.766	0.470 351	0.019 292	0.003 185	0.010 166	0.004 21	0.018 135	0.005 19	0.006 72	0.004 123
XCP 8	.200	0.616	0.386 350	0.015 356	0.000 174	0.003 167	0.003 185	0.002 297	0.016 113	0.008 345	0.006 912
XCP 9	.250	0.561	0.324 357	0.011 342	0.004 116	0.000 161	0.002 135	0.003 177	0.020 88	0.003 304	0.006 761
XCP10	.300	0.492	0.272 358	0.010 341	0.003 112	0.004 245	0.003 106	0.007 91	0.017 119	0.007 18	0.004 259
XCP11	.399	0.416	0.217 11	0.008 7	0.003 267	0.005 284	0.002 197	0.005 126	0.011 170	0.003 998	0.001 76
XCP12	.501	0.300	3.166 16	0.009 6	0.003 121	0.002 237	0.003 235	0.005 134	3.011 153	0.002 353	0.001 303
XCP13	.600	0.268	0.130 26	0.009 73	0.002 154	0.002 285	0.006 155	0.002 262	3.008 125	0.005 315	0.002 254
XCP14	.701	0.197	0.005 94	0.007 15	0.002 167	0.002 224	0.003 186	0.004 16	3.013 164	0.004 147	0.007 95
XCP15	.800	0.119	0.054 51	0.009 48	0.001 233	0.002 *	0.003 221	3.005 249	1.004 89	0.002 147	0.001 195
XCP16	.900	-0.089	0.025 81	0.003 97	0.001 144	0.002 238	0.006 191	0.001 197	3.013 88	0.004 155	0.001 250
XCP17	.985	-0.363	0. 16 179	0.001 506	0.004 283	0.004 13	3.007 355	0.004 133	3.018 242	0.004 133	0.006 230

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
3.0	69.99	0.219	0.496	3.14	0.7	4.96	12123.7	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TPO	EXT DAMP
164.9	73008.	0.49E 07	-0.174	0.927	8.78	-0.30974	1.311	0.3
(541.0)	(1524.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RFS 0	RFS 1 PHI	RFS 2 PHI	RFS 3 PHI	RFS 4 PHI	RFS 5 PHI	RFS 6 PHI	RFS 7 PHI	RFS 8 PHI	RFS 9 PHI
ALPHA		4.940	3.056 0	0.909 317	0.139 178	0.017 107	0.013 68	3.020 68	3.336 971	3.004 291	3.007 242
CN		0.664	0.545 390	0.009 328	0.034 291	0.009 164	0.002 75	0.003 38	0.099 169	0.001 65	0.001 172
CM		-0.009	0.020 288	0.007 311	0.001 104	0.001 31	3.000 329	0.001 225	3.002 346	3.203 177	3.001 326
RFS 1	.010	2.678	1.847 336	0.171 219	0.021 174	0.050 178	0.062 67	3.005 134	3.009 243	3.024 360	0.074 191
RFS 2	.020	2.493	1.597 345	0.243 241	0.160 195	0.095 25	3.042 115	3.587 4	3.072 264	3.319 153	3.045 215
RFS 3	.030	7.336	1.323 344	0.178 241	0.175 197	3.151 27	0.101 282	0.031 163	3.333 253	3.376 119	3.081 27
RFS 4	.049	2.162	7.919 346	0.094 35	0.092 209	3.077 186	0.047 60	0.008 134	3.019 119	0.037 118	0.048 219
RFS 5	.074	1.941	0.789 347	0.079 340	0.013 271	3.010 196	0.009 108	3.014 57	3.015 299	3.311 190	0.035 164
RFS 6	.099	1.735	0.620 350	0.027 354	0.036 215	3.094 207	0.008 76	3.031 49	3.012 195	3.397 66	3.007 323
RFS 7	.145	1.250	0.443 351	0.023 1	0.035 218	0.007 172	0.003 141	0.001 129	3.035 345	0.002 315	0.303 224
RFS 8	.200	1.012	0.362 1	0.017 356	0.036 247	3.004 160	0.004 75	3.031 115	3.021 171	3.002 69	3.001 79
RFS 9	.250	0.879	0.308 348	0.016 359	0.011 237	0.005 150	0.005 78	3.005 123	3.029 123	3.003 356	3.095 258
RFS10	.300	0.777	0.258 3	0.012 358	0.009 213	0.001 98	0.001 194	0.004 128	3.377 168	3.034 62	3.031 215
RFS11	.399	0.641	0.211 15	0.013 346	0.036 250	3.002 181	0.001 33	0.004 105	3.019 156	3.002 4	0.034 44
RFS12	.501	0.478	0.165 21	0.019 5	0.004 253	3.006 170	0.005 241	0.005 87	3.017 174	0.000 977	0.001 119
RFS13	.600	0.398	0.122 91	0.007 17	3.001 167	3.002 169	0.002 3	0.009 341	3.012 144	3.001 71	3.007 151
RFS14	.701	3.391	3.099 42	0.009 1	0.034 293	3.003 233	0.004 147	0.003 19	3.013 191	0.031 171	0.002 107
RFS15	.800	0.197	3.059 56	0.007 1	0.004 971	0.004 246	0.002 67	0.004 94	3.008 164	3.003 314	0.004 166
RFS16	.903	-3.070	3.023 71	0.036 315	0.034 120	3.005 177	0.031 116	0.036 43	3.009 77	3.334 14	3.033 274
RFS17	.969	-3.371	3.009 173	0.999 111	0.034 127	3.002 187	0.005 63	3.035 90	3.013 255	3.001 174	3.098 145

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

FREQ HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	60.04	0.719	0.494	5.17	0.0	7.48	12129.4	29

V	Q	RN	CHI MENS	FN(MAX)	ALPHA.NMAX	AERO DAMP	TAU	TAU DAMP
164.7	72883	3.89E 07	-0.016	1.170	10.41	-3.30103	1.757	0.3
(540.2)	(1522.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	REG 0	REG 1	PHI	REG 2	PHI	REG 3	PHI	REG 4	PHI	REG 5	PHI	REG 6	PHI	REG 7	PHI	REG 8	PHI	REG 9	PHI
ALPHA		7.478	1.126	0	0.144	359	0.199	156	0.015	162	0.010	96	0.015	176	0.095	162	0.056	109	0.199	301
CN		0.996	0.754	17	0.196	290	0.312	194	0.038	209	0.052	178	0.136	187	0.098	66	0.133	917	0.331	256
CM		0.711	0.524	208	0.094	44	0.095	248	0.057	198	0.091	135	0.099	9	0.092	246	0.091	196	0.031	67

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

FREQ HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	60.13	0.712	0.495	7.09	0.0	9.94	12129.1	29

V	Q	RN	CHI MENS	FN(MAX)	ALPHA.NMAX	AERO DAMP	TAU	TAU DAMP
165.7	73592.	3.89E 07	-0.177	1.343	17.49	-0.39062	9.061	0.3
(543.7)	(1537.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	REG 0	REG 1	PHI	REG 2	PHI	REG 3	PHI	REG 4	PHI	REG 5	PHI	REG 6	PHI	REG 7	PHI	REG 8	PHI	REG 9	PHI
ALPHA		9.997	7.000	3	0.156	76	0.177	147	0.048	157	0.012	78	0.095	42	0.099	188	0.917	249	0.004	6

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNER HZ	DRIVE HZ	K	MACH NO	MEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	69.19	0.214	0.492	7.91	0.0	12.49	12125.2	20

V	Q	RN	C(NMIN)	C(NMAX)	ALPHA.NMAX	AERO DAMP	TAB	EXT DAMP
164.6	72979.	0.80E 07	-0.133	1.471	15.76	-0.00124	1.741	0.0
(540.1)	(1524.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		12.486	2.912	0	0.144	53	0.091	233	0.027	156	0.018	67	0.012	33	0.012	227	0.002	96	0.002	85
CN		1.039	0.360	72	0.062	40	0.043	352	0.016	274	0.002	135	0.004	135	0.001	84	0.005	148	0.004	192
CM		-0.017	0.074	252	0.017	127	0.020	174	0.006	53	0.002	302	0.001	136	0.000	274	0.001	194	0.000	48
CP 1	.010	4.345	0.864	195	0.347	78	0.047	151	0.044	111	0.018	163	0.007	143	0.021	87	0.010	255	0.018	145
CP 2	.020	4.245	0.464	195	0.240	78	0.154	171	0.012	340	0.096	215	0.013	163	0.046	207	0.016	170	0.020	214
CP 3	.030	3.734	1.251	165	0.333	108	0.144	141	0.065	347	0.100	210	0.049	267	0.066	197	0.051	272	0.047	217
CP 4	.049	3.290	1.151	140	0.145	177	0.139	151	0.102	238	0.085	291	0.057	226	0.055	273	0.024	325	0.018	259
CP 5	.074	2.635	0.954	117	0.277	195	0.164	155	0.117	266	0.075	279	0.049	341	0.045	51	0.011	95	0.040	156
CP 6	.099	2.322	0.716	110	0.718	65	0.195	194	0.045	144	0.073	16	0.056	219	0.023	345	0.046	270	0.027	267
CP 7	.149	1.953	0.478	83	0.194	57	0.237	58	0.030	34	0.051	101	0.049	143	0.031	112	0.025	173	0.023	160
CP 8	.200	1.550	0.500	79	0.175	61	0.162	48	0.038	67	0.051	48	0.022	119	0.017	97	0.020	112	0.015	117
CP 9	.250	1.350	0.576	68	0.166	44	0.149	18	0.055	14	0.055	17	0.045	47	0.026	31	0.036	56	0.014	42
CP10	.300	1.175	0.464	41	0.111	41	0.128	6	0.046	356	0.041	341	0.039	1	0.021	323	0.020	340	0.013	321
CP11	.399	0.879	0.475	66	0.079	54	0.111	357	0.012	312	0.018	344	0.012	355	0.009	14	0.020	354	0.009	297
CP12	.501	0.757	0.420	54	0.061	7	0.138	357	0.030	276	0.014	238	0.015	108	0.011	254	0.007	316	0.007	115
CP13	.600	0.602	0.371	49	0.046	325	0.093	301	0.006	299	0.028	142	0.021	286	0.014	291	0.002	163	0.006	156
CP14	.701	0.496	0.318	47	0.047	293	0.000	278	0.011	243	0.018	146	0.010	215	0.006	86	0.007	330	0.006	229
CP15	.803	0.311	0.174	26	0.054	351	0.048	257	0.022	209	0.013	193	0.007	196	0.002	273	0.001	195	0.008	214
CP16	.900	0.054	0.189	13	0.075	313	0.052	259	0.035	187	0.010	106	0.009	197	0.007	121	0.010	23	0.006	19
CP17	.969	-0.017	0.082	19	0.046	340	0.024	276	0.030	240	0.009	117	0.030	196	0.024	333	0.033	8	0.007	106

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNER HZ	DRIVE HZ	K	MACH NO	MEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	69.18	0.215	0.491	2.93	0.0	14.96	12125.3	20

V	Q	RN	C(NMIN)	C(NMAX)	ALPHA.NMAX	AERO DAMP	TAB	EXT DAMP
164.0	72596.	0.80E 07	-0.133	1.400	15.21	-0.00165	7.236	0.0
(537.9)	(1516.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		14.958	2.926	0	0.051	190	0.041	195	0.032	72	0.031	351	0.005	90	0.019	176	0.002	1	0.007	327
CN		1.025	0.351	75	0.062	73	0.013	109	0.010	8	0.004	23	0.004	167	0.001	117	0.001	166	0.007	170
CM		-0.014	0.074	210	0.025	202	0.005	218	0.004	179	0.002	5	0.002	161	0.001	335	0.002	306		
CP 1	.010	3.095	0.922	195	0.108	263	0.028	237	0.041	301	0.052	315	0.025	336	0.015	61	0.025	356	0.023	108
CP 2	.020	3.965	0.968	161	0.185	246	0.013	115	0.035	313	0.094	22	0.025	55	0.014	11	0.023	113	0.019	223
CP 3	.030	3.447	1.295	171	0.276	234	0.022	27	0.067	264	0.077	16	0.040	103	0.026	164	0.020	131	0.041	223
CP 4	.049	2.961	0.869	140	0.200	219	0.128	313	0.087	29	0.073	110	0.052	193	0.015	210	0.007	272	0.007	340
CP 5	.074	2.416	0.593	119	0.153	176	0.038	230	0.046	316	0.024	355	0.033	67	0.000	352	0.028	11	0.036	349
CP 6	.099	2.188	0.493	109	0.162	148	0.035	261	0.046	246	0.037	274	0.012	41	0.011	67	0.019	5	0.019	336
CP 7	.149	1.821	0.420	95	0.180	137	0.052	192	0.021	131	0.033	243	0.018	169	0.004	9	0.006	268	0.036	92
CP 8	.200	1.561	0.454	96	0.149	145	0.088	201	0.012	260	0.026	347	0.022	292	0.005	204	0.017	67	0.001	334
CP 9	.250	1.439	0.441	83	0.179	100	0.074	153	0.026	134	0.003	353	0.007	242	0.005	291	0.008	291	0.009	126
CP10	.300	1.272	0.433	71	0.147	87	0.072	123	0.016	111	0.016	165	0.016	333	0.003	254	0.009	229	0.034	143
CP11	.399	1.074	0.452	65	0.146	72	0.068	108	0.034	101	0.024	145	0.004	270	0.008	197	0.021	252	0.034	174
CP12	.501	0.930	0.413	54	0.143	52	0.060	44	0.035	22	0.011	58	0.015	136	0.009	116	0.017	168	0.019	77
CP13	.600	0.636	0.354	48	0.112	38	0.031	52	0.024	1	0.009	34	0.004	272	0.007	314	0.018	91	0.014	335
CP14	.701	0.507	0.291	38	0.090	18	0.010	4	0.023	320	0.005	30	0.039	196	0.007	73	0.056	148	0.004	335
CP15	.800	0.358	0.260	33	0.094	359	0.017	346	0.016	345	0.002	170	0.010	149	0.001	84	0.007	255	0.011	151
CP16	.900	0.159	0.184	33	0.062	351	0.018	335	0.013	326	0.012	26	0.013	149	0.039	280	0.004	51	0.010	145
CP17	.969	0.007	0.085	47	0.037	7	0.011	320	0.011	338	0.003	49	0.038	141	0.005	314	0.011	169	0.032	159

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TIMER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	69.18	0.215	0.491	7.96	0.0	17.59	2125.4	20

V	Q	RN	C(MEANS)	C(MEAN)	ALPHA.NMAX	AERO DAMP	TPD	EXT DAMP
163.6 (536.8)	72515. (1514.5)	6.80E 07	-0.194	1.310	17.78	-0.00177	2.499	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	PFS 0	PFS 1 PHI	PFS 2 PHI	PFS 3 PHI	PFS 4 PHI	PFS 5 PHI	PFS 6 PHI	PFS 7 PHI	PFS 8 PHI	PFS 9 PHI

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

121

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TIMER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	23.12	0.060	0.593	2.65	0.0	2.45	12127.2	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
	196.0	103412.	0.95E 07	-0.018	0.701	5.18	-0.00085	1.175	0.0
	(643.1)	(2159.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.449	2.651 0	0.059 5	0.060 215	0.025 127	0.018 79	0.008 18	0.022 194	0.015 89	0.016 20
CN		0.414	0.200 352	0.008 19	0.003 330	0.002 212	0.001 310	0.000 124	0.033 118	0.002 67	0.001 346
CM		-0.007	0.010 325	0.002 243	0.003 49	0.000 198	0.000 109	0.000 233	0.001 209	0.001 234	0.000 224
CP 1	.010	0.850	1.646 347	0.045 25	0.016 359	0.012 66	0.003 159	0.005 251	0.005 221	0.012 164	0.007 154
CP 2	.020	0.891	1.352 349	0.045 42	0.019 330	0.004 195	0.001 51	0.032 265	0.004 261	0.007 165	0.003 208
CP 3	.030	0.891	1.174 349	0.044 45	0.021 329	0.007 208	0.001 52	0.034 222	0.001 269	0.035 179	0.003 317
CP 4	.040	1.273	1.213 349	0.017 359	0.034 325	0.016 217	0.002 71	0.036 219	0.031 306	0.035 170	0.002 324
CP 5	.074	1.336	1.053 349	0.053 264	0.007 343	0.020 219	0.006 114	0.036 351	0.001 179	0.001 185	0.005 277
CP 6	.099	1.336	1.015 350	0.136 256	0.039 153	0.004 198	0.012 128	0.018 16	0.035 266	0.035 162	0.002 304
CP 7	.149	0.775	0.463 351	0.057 52	0.024 319	0.004 162	0.016 313	0.023 237	0.014 114	0.032 22	0.008 272
CP 8	.200	0.533	0.416 353	0.037 50	0.014 330	0.005 216	0.002 82	0.001 260	0.001 261	0.002 166	0.002 247
CP 9	.250	0.570	0.363 352	0.019 42	0.004 310	0.003 218	0.001 97	0.002 35	0.001 61	0.003 10	0.001 207
CP10	.300	0.514	0.305 352	0.014 37	0.003 295	0.003 215	0.001 7	0.002 43	0.001 99	0.003 19	0.002 15
CP11	.399	0.432	0.244 357	0.010 46	0.002 296	0.001 191	0.000 184	0.002 58	0.002 82	0.004 55	0.001 85
CP12	.501	0.318	0.183 359	0.009 40	0.002 273	0.000 127	0.001 294	0.002 55	0.002 99	0.002 41	0.001 70
CP13	.600	0.273	0.137 0	0.009 39	0.002 252	0.002 295	0.002 304	0.002 71	0.002 73	0.002 64	0.001 13
CP14	.701	0.213	0.088 3	0.008 39	0.001 313	0.001 30	0.002 297	0.002 356	0.002 141	0.002 55	0.001 45
CP15	.900	0.133	0.043 10	0.007 47	0.002 289	0.001 348	0.002 249	0.001 171	0.001 154	0.001 50	0.002 13
CP16	.900	-0.037	0.009 17	0.003 63	0.002 255	0.000 33	0.002 351	0.002 219	0.004 142	0.001 51	0.002 147
CP17	.969	-0.071	0.015 177	0.001 4	0.001 155	0.002 37	0.002 240	0.002 73	0.001 138	0.001 82	0.002 99

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TIMER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	23.12	0.060	0.592	2.70	0.0	4.90	12127.3	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
	195.2	102526.	0.94E 07	-0.212	0.976	7.43	-0.00121	1.483	0.0
	(640.4)	(2141.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.900	2.704 0	0.074 4	0.070 221	0.032 107	0.026 16	0.011 292	0.009 83	0.003 112	0.011 341
CN		0.694	0.270 356	0.020 0	0.007 256	0.006 199	0.004 117	0.001 245	0.001 146	0.001 228	0.002 108
CM		0.006	0.019 333	0.003 240	0.000 99	0.001 243	0.001 143	0.000 231	0.000 106	0.000 164	0.000 128
CP 1	.010	2.257	1.363 350	0.161 49	0.051 313	0.009 161	0.012 336	0.011 207	0.011 322	0.017 196	0.014 114
CP 2	.020	2.190	1.226 350	0.053 0	0.013 292	0.040 236	0.021 142	0.019 225	0.019 118	0.002 233	0.017 101
CP 3	.030	2.124	1.073 351	0.046 327	0.016 179	0.038 233	0.031 136	0.013 223	0.021 115	0.003 26	0.013 103
CP 4	.040	2.267	0.910 350	0.073 33	0.067 157	0.032 292	0.032 129	0.004 12	0.008 98	0.010 14	0.001 105
CP 5	.074	2.261	0.903 350	0.005 44	0.024 179	0.028 44	0.017 128	0.017 14	0.006 61	0.007 348	0.003 56
CP 6	.099	2.230	1.005 350	0.124 54	0.053 314	0.050 50	0.002 184	0.030 22	0.007 304	0.006 323	0.003 128
CP 7	.149	1.644	0.595 351	0.161 266	0.157 325	0.212 229	0.053 174	0.054 210	0.016 134	0.035 182	0.024 105
CP 8	.200	1.061	0.432 1	0.103 290	0.076 179	0.015 174	0.027 129	0.019 44	0.004 333	0.004 302	0.009 248
CP 9	.250	0.910	0.339 356	0.052 279	0.064 162	0.033 79	0.015 55	0.016 359	0.004 289	0.004 297	0.003 266
CP10	.300	0.765	0.277 9	0.023 333	0.049 153	0.046 50	0.025 313	0.007 244	0.003 219	0.002 178	0.001 110
CP11	.399	0.629	0.165 5	0.039 52	0.009 314	0.002 163	0.001 39	0.003 294	0.003 209	0.003 184	0.003 62
CP12	.501	0.469	0.130 7	0.027 45	0.006 305	0.003 162	0.001 18	0.001 300	0.001 118	0.001 345	0.001 44
CP13	.600	0.389	0.091 13	0.025 45	0.007 337	0.004 181	0.001 65	0.001 62	0.001 39	0.002 348	0.001 135
CP14	.701	0.370	0.043 33	0.023 48	0.007 337	0.005 197	0.002 94	0.001 33	0.001 117	0.001 349	0.002 123
CP15	.800	0.162	0.025 47	0.013 44	0.006 297	0.005 192	0.001 91	0.001 93	0.000 158	0.001 314	0.001 132
CP16	.900	-0.096	0.012 41	0.003 347	0.004 285	0.003 166	0.001 193	0.001 163	0.001 233	0.002 315	0.001 272
CP17	.969	-0.082	0.007 174	0.004 267	0.002 197	0.001 132	0.001 322	0.000 257	0.001 203	0.001 13	0.002 65

TUNER HZ	DRIVE HZ	K	MACH NO	REL.ALPHA	REL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
7.0	73.18	0.061	0.591	7.67	0.3	7.43	12127.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
194.7	102478.	3.94E 07	0.332	1.065	8.59	-0.00146	7.76?	0.3
(638.9)	(2140.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	REG 0	REG 1	PHI	REG 2	PHI	REG 3	PHI	REG 4	PHI	REG 5	PHI	REG 6	PHI	REG 7	PHI	REG 8	PHI	REG 9	PHI
ALPHA		7.425	7.623	0	0.094	28	0.266	217	0.027	97	0.036	35	0.074	341	0.030	203	0.017	172	0.313	42
CN		0.968	0.139	20	0.266	50	0.019	51	0.013	12	0.035	6	0.035	337	0.003	270	0.003	310	0.031	243
CM		0.018	0.315	317	0.005	92	0.091	347	0.031	61	0.001	134	0.031	27	0.039	359	0.090	338	0.300	260
PR 1	.215	1.285	0.644	356	0.176	67	0.034	110	0.013	182	0.036	315	0.013	182	0.019	270	0.007	234	0.037	241
PR 2	.025	1.508	0.761	357	0.197	58	0.019	37	0.037	42	0.027	134	0.021	237	0.009	241	0.032	187	0.011	275
PR 3	.050	2.036	0.736	357	0.177	56	0.021	79	0.034	36	0.025	133	0.013	233	0.007	165	0.013	191	0.009	271
PR 4	.140	2.060	0.532	358	0.127	67	0.072	355	0.030	0	0.010	144	0.011	7	0.030	167	0.013	183	0.035	120
PR 5	.074	2.843	0.336	357	0.200	70	0.112	0	0.234	343	0.019	335	0.020	324	0.016	222	0.015	172	0.007	90
PR 6	.099	2.732	0.091	215	0.292	83	0.081	78	0.065	54	0.054	8	0.035	311	0.013	288	0.311	274	0.030	233
PR 7	.140	2.544	0.268	16	0.476	66	0.025	144	0.075	56	0.009	127	0.036	37	0.030	135	0.316	153	0.025	285
PR 8	.203	1.421	0.463	15	0.112	50	0.003	4	0.043	41	0.070	346	0.012	30	0.002	208	0.009	30	0.037	80
PR 9	.256	1.198	0.333	13	0.062	28	0.077	4	0.053	8	0.043	330	0.021	341	0.317	311	0.311	269	0.036	214
PR10	.303	0.996	0.250	20	0.036	347	0.048	4	0.041	334	0.349	371	0.020	337	0.021	286	0.016	291	0.017	265
PR11	.395	0.775	0.127	28	0.019	6	0.013	37	0.035	296	0.009	277	0.012	341	0.006	307	0.005	343	0.009	217
PR12	.521	0.555	0.071	43	0.025	44	0.098	56	0.035	281	0.012	163	0.003	235	0.004	209	0.033	272	0.035	176
PR13	.603	0.411	0.056	121	0.020	58	0.000	123	0.007	5	0.002	73	0.001	286	0.004	209	0.005	150	0.034	76
PR14	.731	0.354	0.090	139	0.034	65	0.017	174	0.005	57	0.001	35	0.002	281	0.032	165	0.034	142	0.034	44
PR15	.830	0.162	0.045	112	0.012	17	0.035	147	0.001	75	0.001	161	0.037	162	0.033	161	0.005	147	0.034	44
PR16	.900	-0.092	0.025	44	0.007	316	0.032	357	0.007	216	0.002	130	0.001	118	0.007	87	0.001	117	0.032	247
PR17	.965	-0.094	0.007	41	0.005	284	0.032	305	0.002	270	0.001	203	0.002	145	0.031	222	0.033	238	0.033	193

TUNER HZ	DRIVE HZ	K	MACH NO	REL.ALPHA	REL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
7.0	73.07	0.060	0.594	2.47	3.0	0.93	12120.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
196.7	103977.	3.94E 07	-0.331	1.342	0.11	-3.00110	1.463	0.0
(645.4)	(2171.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	REG 0	REG 1	PHI	REG 2	PHI	REG 3	PHI	REG 4	PHI	REG 5	PHI	REG 6	PHI	REG 7	PHI	REG 8	PHI	REG 9	PHI
ALPHA		2.034	2.473	3	0.090	36	0.333	737	0.019	121	0.012	11	0.013	194	0.011	197	0.020	165	0.037	46
CN		0.051	0.344	100	0.035	124	0.012	190	0.034	144	0.035	203	0.033	100	0.033	115	0.033	178	0.037	203
CM		0.035	0.333	195	0.038	97	0.032	169	0.032	63	0.031	336	0.333	223	0.071	338	0.331	388	0.331	175
PR 1	.013	1.463	0.308	11	0.270	68	0.036	138	0.016	330	0.005	274	0.006	156	0.011	307	0.039	370	0.030	68
PR 2	.030	1.543	0.306	12	0.097	48	0.011	47	0.037	132	0.333	97	0.003	146	0.031	241	0.031	715	0.034	124
PR 3	.035	2.177	0.133	142	0.345	133	0.342	47	0.021	96	0.316	41	0.038	17	0.037	1	0.017	285	0.019	201
PR 4	.049	2.073	0.114	177	0.211	93	0.075	149	0.044	120	0.001	201	0.029	141	0.017	146	0.036	51	0.002	206
PR 5	.174	2.497	0.355	176	0.117	99	0.134	191	0.016	141	0.044	222	0.323	232	0.013	215	0.037	130	0.315	283
PR 6	.099	2.542	0.427	173	0.035	297	0.034	195	0.046	241	0.320	275	0.022	349	0.023	289	0.012	299	0.315	305
PR 7	.140	2.081	0.407	157	0.134	347	0.058	330	0.041	64	0.011	75	0.015	47	0.034	100	0.038	336	0.319	224
PR 8	.223	1.620	0.176	122	0.307	111	0.043	165	0.013	170	0.010	212	0.013	217	0.039	282	0.037	277	0.311	219
PR 9	.257	1.430	0.119	174	0.058	90	0.045	130	0.022	182	0.012	203	0.036	196	0.034	4	0.004	261	0.036	202
PR10	.300	1.149	0.174	51	0.351	85	0.037	172	0.001	333	0.013	271	0.014	274	0.311	36	0.036	134	0.337	63
PR11	.399	0.873	0.161	39	0.033	23	0.019	134	0.012	95	0.012	159	0.012	179	0.033	136	0.013	191	0.335	70
PR12	.521	0.659	0.133	29	0.021	284	0.035	230	0.034	147	0.304	274	0.033	65	0.035	194	0.038	167	0.331	197
PR13	.603	0.484	0.708	35	0.034	347	0.313	273	0.037	246	0.316	193	0.331	111	0.037	171	0.034	161	0.334	71
PR14	.731	0.375	0.343	41	0.345	243	0.314	276	0.036	233	0.031	117	0.032	44	0.036	115	0.030	51	0.035	323
PR15	.800	0.199	0.082	28	0.035	347	0.095	117	0.204	164	0.005	102	0.032	25	0.004	110	0.032	74	0.330	315
PR16	.900	-0.074	0.383	11	0.037	270	0.033	147	0.034	58	0.034	139	0.001	118	0.034	93	0.032	338	0.031	336
PR17	.949	-0.063	0.033	4	0.035	318	0.033	275	0.033	317	0.003	286	0.032	246	0.031	218	0.037	148	0.333	28

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	33.06	0.060	0.593	2.44	0.0	12.49	12131.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TOP	EXT DAMP
196.5	103900.	0.95E 07	-0.059	1.051	12.73	-0.00142	2.219	0.0
(644.7)	(2170.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.499	2.437 0	0.365 2	0.026 199	0.019 172	0.016 74	0.019 129	0.026 202	0.021 8	0.008 88
CN		0.972	0.372 42	0.005 133	0.008 68	0.005 206	0.003 222	0.006 63	0.004 235	0.004 31	0.004 253
CM		-0.025	0.034 195	0.004 266	0.001 193	0.000 65	0.001 79	0.002 220	0.001 325	0.002 133	0.001 180

The remainder of the page consists of extensive harmonic-analysis data rows (CP01–CP17 and related entries) that are too faint and degraded to transcribe reliably.

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TIMER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.84	0.119	0.591	2.94	0.0	0.01	12133.1	20

V	Q	RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TPD	EXT DAMP
196.7	104240.	0.95E 07	-0.328	2.405	2.78	-0.00072	1.112	0.0
(645.3)	(2177.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		2.914	2.942	3	0.093	359	0.262	242	0.027	92	0.023	50	0.016	74	0.022	192	0.002	195	0.007	286
CN		2.126	2.276	352	0.035	334	0.032	331	0.003	357	0.001	61	0.001	94	0.002	103	0.001	44	0.001	216
CM		-0.315	0.312	302	0.021	240	0.022	354	0.001	117	0.000	297	0.000	280	0.000	283	0.002	282	0.000	62
CP 1	.010	-0.901	1.965	339	0.166	39	0.043	91	0.027	25	0.017	65	0.036	139	0.019	87	0.004	336	0.032	292
CP 2	.020	-0.451	1.717	345	0.047	261	0.024	336	0.018	48	0.015	284	0.025	351	0.027	67	0.021	117	0.016	184
CP 3	.030	-0.171	1.154	344	0.021	264	0.014	295	0.015	35	0.006	49	0.006	121	0.001	174	0.002	48	0.001	161
CP 4	.040	0.179	1.310	345	0.034	255	0.036	274	0.010	50	0.003	91	0.002	73	0.001	79	0.001	277	0.001	52
CP 5	.074	0.344	0.862	344	0.027	258	0.039	292	0.010	60	0.003	293	0.004	93	0.001	165	0.001	70	0.003	158
CP 6	.050	0.407	0.727	346	0.020	267	0.005	277	0.008	63	0.001	261	0.002	47	0.001	199	0.002	333	0.002	186
CP 7	.140	0.279	0.519	346	0.020	333	0.024	291	0.026	79	0.002	69	0.003	117	0.001	104	0.002	357	0.001	254
CP 8	.200	0.211	0.430	351	0.007	313	0.003	306	0.005	127	0.002	55	0.002	166	0.001	177	0.001	15	0.002	187
CP 9	.250	0.207	0.368	349	0.006	331	0.014	337	0.003	340	0.001	159	0.003	221	0.001	82	0.002	5	0.002	339
CP10	.300	0.213	0.317	346	0.013	346	0.013	315	0.002	320	0.001	337	0.002	62	0.003	101	0.001	67	0.002	180
CP11	.350	0.177	0.243	350	0.008	7	0.002	321	0.002	223	0.001	74	0.001	179	0.002	124	0.001	35	0.002	271
CP12	.501	0.133	0.184	2	0.005	27	0.003	243	0.003	7	0.001	179	0.001	9	0.001	171	0.001	5	0.002	209
CP13	.600	0.147	0.115	5	0.004	39	0.001	320	0.004	323	0.002	232	0.001	58	0.002	119	0.001	89	0.002	245
CP14	.701	0.277	0.092	5	0.003	25	0.001	178	0.003	268	0.001	199	0.002	119	0.001	170	0.001	99	0.001	162
CP15	.802	0.199	0.049	19	0.001	1	0.001	162	0.004	301	0.002	35	0.001	224	0.002	40	0.002	91	0.002	242
CP16	.900	-0.111	0.014	74	0.001	78	0.000	310	0.003	348	0.002	119	0.002	72	0.002	66	0.002	270	0.002	167
CP17	.960	-0.255	0.021	179	0.002	295	0.002	272	0.008	302	0.002	326	0.001	293	0.002	217	0.002	114	0.004	344

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TIMER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.82	0.119	0.591	2.94	0.0	2.49	12133.2	20

V	Q	RN	CM(MIN)	CN(MAX)	ALPHA.PMAX	AERO DAMP	TPD	EXT DAMP
195.6	103541.	0.95E 07	-0.072	2.690	5.41	-0.00079	1.255	0.0
(641.7)	(2162.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		2.492	2.956	2	0.074	353	0.262	235	0.051	93	0.031	58	0.012	16	0.016	187	0.002	48	0.004	232
CN		2.422	2.275	351	0.238	8	0.004	246	0.001	119	0.001	123	0.030	332	0.001	75	0.001	112	0.001	122
CM		-0.074	0.314	307	0.002	319	0.000	75	0.001	134	0.000	8	0.000	65	0.001	314	0.000	243	0.000	271
CP 1	.010	0.874	1.632	340	0.050	49	0.016	279	0.010	93	0.009	17	0.005	233	0.004	72	0.004	234	0.009	240
CP 2	.020	0.916	1.306	344	0.026	37	0.021	315	0.008	48	0.001	70	0.004	4	0.002	43	0.003	243	0.001	242
CP 3	.030	1.073	1.135	342	0.010	38	0.024	39	0.001	91	0.001	72	0.002	13	0.002	36	0.001	237	0.001	50
CP 4	.040	1.297	1.103	343	0.005	17	0.037	338	0.012	160	0.002	30	0.001	213	0.002	25	0.001	249	0.003	0
CP 5	.074	1.265	1.022	343	0.055	247	0.011	117	0.011	177	0.009	72	0.010	322	0.001	326	0.005	264	0.002	158
CP 6	.050	1.319	1.075	344	0.011	240	0.008	128	0.006	61	0.011	47	0.009	354	0.001	302	0.002	260	0.001	50
CP 7	.140	0.790	0.424	349	0.067	28	0.017	306	0.011	150	0.006	103	0.013	165	0.012	58	0.010	280	0.007	177
CP 8	.200	0.650	0.308	351	0.034	38	0.014	330	0.008	149	0.002	94	0.002	349	0.001	173	0.003	345	0.001	96
CP 9	.250	0.687	0.340	350	0.010	15	0.005	119	0.003	121	0.003	102	0.001	17	0.002	343	0.002	350	0.002	148
CP10	.300	0.591	0.297	351	0.015	11	0.005	294	0.002	150	0.001	124	0.001	21	0.002	274	0.002	303	0.002	112
CP11	.350	0.433	0.234	0	0.012	22	0.001	334	0.002	70	0.001	158	0.001	35	0.002	287	0.002	318	0.001	85
CP12	.501	0.275	0.116	3	0.010	23	0.002	257	0.002	276	0.003	127	0.001	6	0.001	33	0.001	85	0.001	87
CP13	.600	0.287	0.179	2	0.008	30	0.001	205	0.001	120	0.001	143	0.002	319	0.001	166	0.001	48	0.002	47
CP14	.701	0.322	0.092	14	0.008	23	0.002	330	0.001	324	0.010	135	0.001	270	0.001	101	0.001	43	0.001	52
CP15	.400	0.134	0.042	30	0.006	46	0.002	264	0.002	221	0.002	191	0.002	6	0.001	234	0.000	130		
CP16	.900	-0.100	0.015	67	0.004	27	0.001	257	0.005	335	0.001	168	0.002	224	0.004	158	0.001	324	0.001	213
CP17	.960	-0.275	0.016	189	0.002	326	0.001	177	0.002	320	0.001	159	0.001	313	0.002	28	0.001	72	0.002	232

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNER HZ 0.0	DRIVE HZ 45.75	K 0.120	MACH NO 0.599	DEL.ALPHA 2.98	DEL.H 0.0	ALPHA.0 5.00	TEST POINT 12133.3	CYCLES ANALYSED 20
V 194.5 (638.2)	Q 102445 (2139.7)	PN 0.94E 07	CN(MIN) -0.015	CN(MAX) 1.001	ALPHA.NMAX 8.03	AERO DAMP -0.00107	TDR 1.645	EXT DAMP 0.3

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		5.004	2.980 0	0.093 8	0.094 251	0.077 119	0.032 66	0.007 55	0.007 215	0.005 166	0.002 337
CN		0.702	0.266 357	0.020 319	0.037 195	0.008 144	0.034 82	0.031 241	0.002 174	0.002 75	0.002 2
CM		0.015	0.022 315	0.001 195	0.031 353	0.002 265	0.001 93	0.000 135	0.000 17	0.000 231	0.000 186
DCP 1	.010	2.301	1.294 347	0.133 16	0.047 139	0.015 219	0.006 271	0.014 155	0.007 137	0.010 174	0.006 237
DCP 2	.020	2.215	1.022 346	0.023 321	0.016 335	0.048 204	0.020 108	0.018 177	0.020 63	0.001 188	0.014 30
DCP 3	.030	2.158	1.072 345	0.035 277	0.037 143	0.046 202	0.029 97	0.012 179	0.071 60	0.004 280	0.012 20
DCP 4	.040	2.297	0.909 345	0.042 31	0.043 132	0.010 191	0.032 97	0.036 345	0.012 44	0.013 135	0.002 340
DCP 5	.074	2.276	0.905 345	0.066 42	0.019 150	0.020 22	0.017 90	0.019 329	0.007 26	0.011 301	0.003 346
DCP 6	.100	2.247	0.997 348	0.131 50	0.056 300	0.041 45	0.006 350	0.027 314	0.337 236	0.009 325	0.003 226
DCP 7	.140	1.633	0.933 357	0.108 249	0.131 241	0.101 194	0.049 91	0.050 144	0.022 73	0.023 111	0.009 19
DCP 8	.200	1.091	0.466 0	0.124 266	0.085 151	0.010 91	0.029 99	0.022 3	0.012 267	0.006 199	0.005 163
DCP 9	.250	0.933	0.347 355	0.062 264	0.069 126	0.028 30	0.016 356	0.010 293	0.014 196	0.007 122	0.006 72
DCP10	.300	0.782	0.236 1	0.121 274	0.051 114	0.064 9	0.024 250	0.007 197	0.010 165	0.012 70	0.011 333
DCP11	.350	0.634	0.174 15	0.021 26	0.004 271	0.037 107	0.002 277	0.002 213	0.004 116	0.004 55	0.003 308
DCP12	.501	0.478	0.136 20	0.026 18	0.004 252	0.037 125	0.032 219	0.001 95	0.001 41	0.002 345	0.001 256
DCP13	.600	0.394	0.102 33	0.023 16	0.006 254	0.008 121	0.002 319	0.002 65	0.001 162	0.001 73	0.002 76
DCP14	.701	0.278	0.065 55	0.023 12	0.008 249	0.008 126	0.001 51	0.000 283	0.001 157	0.000 169	0.001 80
DCP15	.800	0.163	0.043 69	0.013 355	0.004 211	0.008 111	0.002 14	0.002 256	0.002 189	0.003 5	0.001 54
DCP16	.900	-0.002	0.019 62	0.007 299	0.006 178	0.005 117	0.002 116	0.001 247	0.001 190	0.002 136	0.001 0
DCP17	.965	-0.082	0.008 180	0.007 254	0.003 189	0.007 117	0.002 223	0.001 17	0.001 167	0.001 37	0.002 340

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNER HZ 0.0	DRIVE HZ 45.81	K 0.120	MACH NO 0.598	DEL.ALPHA 2.80	DEL.H 0.0	ALPHA.0 7.51	TEST POINT 12133.4	CYCLES ANALYSED 20
V 193.7 (635.5)	Q 99399. (2077.0)	PN 0.93E 07	CN(MIN) -0.013	CN(MAX) 1.152	ALPHA.NMAX 9.34	AERO DAMP -0.00123	TDR 1.984	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.537	2.901 2	0.107 44	0.042 315	0.121 144	0.015 55	0.010 336	0.012 253	0.013 152	0.012 229
CN		0.864	0.178 34	0.003 25	0.012 299	0.008 170	0.003 244	0.003 215	0.000 59	0.002 336	0.006 182
CM		0.012	0.020 278	0.013 105	0.007 6	0.004 299	0.001 76	0.001 272	0.002 126	0.001 41	0.001 357
DCP 1	.010	2.220	0.698 353	0.170 43	0.047 170	0.011 157	0.010 60	0.022 213	0.005 289	0.012 54	0.005 219
DCP 2	.020	2.066	0.822 357	0.170 42	0.014 222	0.031 67	0.035 118	0.007 218	0.004 112	0.011 163	0.002 254
DCP 3	.030	2.009	0.737 354	0.197 42	0.060 339	0.026 101	0.051 118	0.016 8	0.004 126	0.018 158	0.004 353
DCP 4	.040	2.958	0.654 359	0.192 55	0.139 334	0.040 262	0.031 161	0.017 70	0.017 97	0.006 39	0.005 70
DCP 5	.074	2.714	0.161 16	0.340 65	0.227 337	0.095 247	0.015 156	0.019 284	0.024 157	0.018 67	0.008 37
DCP 6	.100	2.655	0.113 119	0.417 63	0.172 333	0.007 226	0.047 340	0.047 263	0.022 162	0.011 259	0.020 145
DCP 7	.140	1.957	0.412 30	0.566 57	0.063 132	0.074 50	0.063 89	0.017 335	0.019 201	0.013 107	0.002 107
DCP 8	.200	1.380	0.404 28	0.177 16	0.130 329	0.012 306	0.018 329	0.015 297	0.007 172	0.016 10	0.007 357
DCP 9	.250	1.100	0.396 22	0.145 354	0.145 301	0.040 224	0.043 286	0.026 215	0.007 246	0.014 112	0.019 232
DCP10	.300	1.011	0.330 29	0.141 338	0.112 298	0.055 331	0.046 245	0.018 188	0.334 101	0.022 195	0.019 155
DCP11	.350	0.747	0.197 42	0.277 335	0.044 241	0.018 169	0.017 232	0.026 144	0.015 88	0.017 21	0.007 284
DCP12	.501	0.574	0.151 54	0.261 330	0.036 225	0.018 138	0.038 172	0.016 135	0.015 2	0.012 269	0.013 179
DCP13	.600	0.441	0.174 74	0.051 342	0.028 233	0.017 115	0.036 117	0.010 42	0.011 205	0.034 193	0.007 184
DCP14	.701	0.374	0.112 102	0.037 345	0.019 170	0.015 90	0.032 270	0.007 39	0.017 284	0.036 196	0.006 181
DCP15	.800	0.169	0.080 86	0.031 334	0.020 168	0.014 90	0.004 352	0.004 215	0.001 272	0.002 260	0.007 196
DCP16	.900	-0.071	0.050 45	0.029 305	0.015 181	0.013 110	0.032 326	0.004 334	0.004 282	0.004 191	0.035 147
DCP17	.965	-0.081	0.017 46	0.014 299	0.005 213	0.008 110	0.002 290	0.000 123	0.003 283	0.004 153	0.002 107

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	45.77	0.118	0.594	2.62	0.0	9.94	12135.1	20

V	Q	RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TOO	EXT DAMP
196.9 (646.2)	104318. (2179.2)	0.055 07	-0.045	1.133	9.37	-0.00163	2.553	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	REC 0	REC 1	PHI	REC 2	PHI	REC 3	PHI	REC 4	PHI	REC 5	PHI	REC 6	PHI	REC 7	PHI	REC 8	PHI	REC 9	PHI
ALPHA		9.942	2.624	0	0.096	34	0.153	171	0.019	276	0.031 345		0.009 173		0.023 175		0.005 82		0.005 316	
CN		0.034	0.155 102		0.035 99		0.025 102		0.023 330		0.004 327		0.034 274		0.035 346		0.033 302		0.032 77	
CM		0.005	0.036 216		0.007 104		0.037 194		0.034 107		0.032 124		0.032 57		0.031 81		0.001 330		0.031 209	
MCP 1	.010	2.573	0.264	21	0.062 87		0.013 70		0.005 2		0.016 318		0.004 186		0.029 189		0.029 244		0.009 122	
MCP 2	.022	2.597	0.270 27		0.123 102		0.059 94		0.035 46		0.029 354		0.011 117		0.002 262		0.011 325		0.012 256	
MCP 3	.032	2.190	0.061 117		0.274 99		0.044 87		0.065 101		0.048 33		0.016 0		0.013 82		0.028 19		0.374 336	
MCP 4	.040	2.913	0.336 173		0.274 102		0.266 116		0.054 112		0.035 131		0.013 87		0.033 102		0.035 125		0.013 87	
MCP 5	.074	2.606	0.651 172		0.231 95		0.169 165		0.074 103		0.044 151		0.020 81		0.018 189		0.007 166		0.028 155	
MCP 6	.099	2.474	0.770 167		0.099 87		0.183 166		0.014 165		0.031 173		0.032 276		0.013 180		0.024 178		0.012 177	
MCP 7	.149	2.391	0.708 152		0.278 227		0.023 124		0.021 280		0.050 314		0.033 335		0.022 336		0.028 354		0.012 157	
MCP 8	.200	1.597	0.331 111		0.134 96		0.080 143		0.027 100		0.010 2		0.011 78		0.035 204		0.034 279		0.028 204	
MCP 9	.250	1.389	0.374 83		0.128 72		0.251 130		0.013 82		0.039 120		0.013 322		0.007 324		0.018 303		0.012 144	
MCP10	.300	1.151	0.375 67		0.138 89		0.067 115		0.014 180		0.021 176		0.010 104		0.009 338		0.017 126		0.011 45	
MCP11	.350	0.871	0.310 57		0.069 77		0.055 54		0.013 345		0.013 83		0.005 263		0.013 187		0.037 252		0.005 25	
MCP12	.521	0.643	0.196 59		0.038 17		0.041 47		0.024 333		0.011 348		0.014 332		0.032 224		0.032 307		0.032 166	
MCP13	.600	0.488	0.162 66		0.032 265		0.033 42		0.020 308		0.013 324		0.007 187		0.029 293		0.002 92		0.009 302	
MCP14	.721	0.343	0.123 74		0.037 264		0.020 250		0.014 283		0.010 260		0.037 241		0.038 274		0.036 195		0.034 42	
MCP15	.800	0.206	0.113 69		0.024 370		0.025 346		0.014 265		0.007 314		0.036 283		0.006 304		0.005 195		0.038 76	
MCP16	.900	-0.029	0.093 33		0.015 313		0.013 325		0.005 263		0.013 295		0.037 318		0.007 178		0.036 128		0.034 85	
MCP17	.965	-0.062	0.046 35		0.005 21		0.013 354		0.023 153		0.036 294		0.033 268		0.035 194		0.034 156		0.034 36	

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	45.97	0.118	0.591	2.57	0.0	12.51	12135.2	20

V	Q	RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TOO	EXT DAMP
195.7 (642.4)	103643. (2165.1)	0.055 07	-0.075	1.118	11.58	-0.00196	2.946	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	REC 0	REC 1	PHI	REC 2	PHI	REC 3	PHI	REC 4	PHI	REC 5	PHI	REC 6	PHI	REC 7	PHI	REC 8	PHI	REC 9	PHI
ALPHA		12.505	2.577	0	0.377 18		0.073 217		0.042 45		0.021 36		0.026 107		0.011 213		0.038 87		0.011 2	
CN		0.080	0.143 87		0.317 192		0.037 131		0.035 285		0.003 61		0.003 54		0.031 333		0.004 240		0.001 100	
CM		-0.029	0.344 217		0.004 260		0.033 243		0.031 188		0.032 214		0.032 233		0.031 122		0.031 42		0.032 209	
MCP 1	.010	3.530	0.131 134		0.095 88		0.036 214		0.026 146		0.019 272		0.012 219		0.034 144		0.039 264		0.038 173	
MCP 2	.022	3.531	0.190 145		0.112 89		0.043 224		0.021 195		0.039 259		0.021 191		0.033 51		0.017 231		0.031 226	
MCP 3	.032	3.330	0.133 149		0.390 86		0.341 216		0.017 316		0.031 246		0.039 193		0.016 277		0.014 232		0.012 294	
MCP 4	.040	2.912	0.433 170		0.389 201		0.281 198		0.054 327		0.006 223		0.027 213		0.013 339		0.017 330		0.039 246	
MCP 5	.074	2.535	0.481 150		0.156 269		0.219 70		0.032 293		0.014 58		0.039 5		0.033 3		0.012 139		0.035 317	
MCP 6	.099	2.292	0.733 142		0.114 263		0.222 144		0.007 66		0.022 179		0.019 287		0.027 339		0.033 189		0.015 1	
MCP 7	.149	1.751	0.278 112		0.099 262		0.021 121		0.041 261		0.032 344		0.010 237		0.018 186		0.005 107		0.038 20	
MCP 8	.200	1.436	0.333 119		0.367 226		0.329 210		0.017 267		0.009 352		0.015 161		0.031 193		0.032 52		0.034 336	
MCP 9	.250	1.335	0.322 121		0.074 290		0.032 233		0.008 286		0.016 130		0.016 217		0.015 77		0.039 148		0.035 285	
MCP10	.300	1.208	0.193 134		0.057 191		0.033 105		0.008 182		0.010 166		0.038 175		0.033 333		0.011 71		0.011 40	
MCP11	.350	1.027	0.235 83		0.359 152		0.033 197		0.039 147		0.034 153		0.024 118		0.023 104		0.034 354		0.016 260	
MCP12	.521	0.791	0.212 62		0.040 105		0.015 157		0.013 235		0.007 28		0.039 12		0.015 346		0.004 245			
MCP13	.600	0.623	0.218 47		0.067 102		0.036 81		0.038 105		0.007 282		0.039 341		0.016 315		0.011 280		0.034 189	
MCP14	.721	0.483	0.181 35		0.017 57		0.016 49		0.013 76		0.017 49		0.016 7		0.006 267		0.037 290		0.038 121	
MCP15	.800	0.312	0.158 37		0.014 146		0.012 72		0.008 320		0.012 43		0.006 18		0.037 148		0.033 262		0.011 107	
MCP16	.900	0.391	0.115 32		0.311 332		0.036 2		0.007 314		0.034 2		0.018 333		0.037 263		0.004 192		0.014 76	
MCP17	.969	-0.010	0.060 32		0.013 8		0.005 147		0.010 309		0.033 191		0.034 359		0.013 284		0.011 241		0.006 182	

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TIMED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	45.99	0.120	0.599	2.67	0.0	14.95	12135.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TAP	EXT DAMP
194.7	101832.	0.965 07	-0.281	1.147	15.47	-0.00155	7.444	0.0
(638.8)	(2126.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	REG 0	REG 1 PHI	REG 2 PHI	REG 3 PHI	REG 4 PHI	REG 5 PHI	REG 6 PHI	REG 7 PHI	REG 8 PHI	REG 9 PHI
ALPHA		14.951	2.623 0	0.095 10	0.046 236	0.065 87	0.013 17	0.007 129	0.003 145	0.004 141	0.029 119
CN		1.015	0.131 68	0.012 337	0.036 44	0.008 101	0.004 229	0.034 331	0.034 96	0.033 3	0.033 329
CW		-0.047	0.036 214	0.032 299	0.031 224	0.032 274	0.000 276	0.001 159	0.002 265	0.001 195	0.000 132
DCP 1	.010	3.544	0.031 149	0.043 299	0.076 145	0.014 291	0.005 131	0.021 234	0.011 243	0.005 143	0.004 320
DCP 2	.020	3.443	0.123 163	0.037 246	0.047 193	0.032 273	0.010 67	0.016 269	0.036 150	0.009 260	0.009 66
DCP 3	.030	2.773	0.181 159	0.011 346	0.037 359	0.006 284	0.061 5	0.012 299	0.021 333	0.021 339	0.011 124
DCP 4	.045	2.726	0.224 140	0.078 243	0.079 50	0.043 122	0.013 294	0.030 55	0.018 39	0.012 88	0.013 159
DCP 5	.074	2.395	0.217 94	0.067 260	0.022 35	0.013 56	0.019 229	0.033 257	0.004 315	0.013 112	0.004 267
DCP 6	.099	2.117	0.187 101	0.078 266	0.002 224	0.017 13	0.024 212	0.027 177	0.022 165	0.038 95	0.004 156
DCP 7	.149	1.791	0.118 97	0.037 195	0.010 291	0.004 132	0.013 143	0.020 192	0.004 67	0.009 354	0.011 1
DCP 8	.200	1.566	0.150 97	0.023 158	0.012 355	0.012 171	0.001 323	0.017 247	0.008 298	0.020 79	0.006 2
DCP 9	.252	1.421	0.154 156	0.022 173	0.017 95	0.002 229	0.004 320	0.011 156	0.007 125	0.018 205	
DCP10	.300	1.261	0.172 75	0.024 192	0.011 139	0.004 43	0.014 255	0.007 5	0.001 125	0.012 264	0.005 334
DCP11	.390	1.109	0.179 62	0.019 158	0.025 117	0.015 147	0.020 221	0.013 336	0.011 233	0.007 243	0.012 324
DCP12	.501	0.879	0.170 63	0.008 158	0.012 41	0.014 104	0.011 245	0.030 313	0.004 91	0.030 340	0.032 327
DCP13	.600	0.682	0.171 47	0.026 299	0.006 26	0.010 137	0.014 219	0.003 337	0.010 141	0.008 182	0.010 135
DCP14	.701	0.559	0.164 19	0.002 261	0.002 326	0.007 54	0.009 42	0.007 41	0.011 51	0.007 58	0.030 345
DCP15	.800	0.302	0.142 17	0.037 106	0.035 42	0.005 97	0.033 65	0.036 267	0.007 81	0.031 88	0.011 342
DCP16	.900	0.115	0.309 38	0.008 170	0.007 326	0.005 87	0.012 72	0.005 176	0.013 36	0.008 23	0.006 274
DCP17	.965	-0.007	0.044 56	0.007 196	0.032 197	0.013 82	0.005 57	0.034 139	0.009 55	0.012 335	0.032 165

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TIMED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	44.62	0.177	0.594	3.18	0.0	-0.32	12137.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TAP	EXT DAMP
197.0	104575.	0.965 07	-0.333	0.396	3.33	-0.00067	1.397	0.0
(646.3)	(2184.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	REG 0	REG 1 PHI	REG 2 PHI	REG 3 PHI	REG 4 PHI	REG 5 PHI	REG 6 PHI	REG 7 PHI	REG 8 PHI	REG 9 PHI
ALPHA		-0.025	3.150 0	0.120 335	0.170 233	0.032 153	0.023 42	0.020 79	0.032 237	0.010 237	0.039 185
CN		0.124	0.268 353	0.009 288	0.004 253	0.003 219	0.001 74	0.003 45	0.001 347	0.001 60	0.001 94
CW		-0.016	0.317 291	0.001 330	0.001 90	0.001 97	0.010 240	0.000 274	0.001 141	0.000 129	0.000 267
DCP 1	.010	-0.077	1.000 335	0.117 15	0.047 101	0.012 153	0.010 15	0.005 4	0.026 346	0.009 97	0.011 129
DCP 2	.020	-0.053	1.300 342	0.078 248	0.026 280	0.013 213	0.014 296	0.028 341	0.025 41	0.026 111	0.031 182
DCP 3	.030	-0.176	1.144 341	0.057 247	0.316 270	0.023 146	0.012 46	0.034 89	0.005 291	0.003 144	0.001 259
DCP 4	.045	-0.175	1.005 342	0.059 241	0.007 233	0.005 225	0.005 72	0.001 356	0.001 307	0.002 254	0.004 302
DCP 5	.074	0.330	0.954 347	0.046 246	0.017 234	0.036 171	0.032 345	0.004 74	0.002 174	0.004 70	0.032 268
DCP 6	.099	0.431	0.721 344	0.035 251	0.035 227	0.035 201	0.003 33	0.034 357	0.001 151	0.001 127	0.031 273
DCP 7	.149	0.278	0.517 146	0.019 291	0.008 242	0.036 182	0.001 247	0.024 74	0.002 253	0.031 353	0.004 271
DCP 8	.200	0.312	0.425 353	0.017 270	0.031 268	0.007 211	0.006 336	0.035 71	0.005 7	0.011 78	0.011 15
DCP 9	.250	0.232	0.342 357	0.013 281	0.010 250	0.007 294	0.001 88	0.005 24	0.002 39	0.001 117	0.002 102
DCP10	.300	0.197	0.301 357	0.011 294	0.004 237	0.006 196	0.002 130	0.003 3	0.001 271	0.001 147	0.002 94
DCP11	.390	0.177	0.219 5	0.009 322	0.007 353	0.005 214	0.031 134	0.001 7	0.001 349	0.012 20	0.004 92
DCP12	.501	0.151	0.183 10	0.007 351	0.036 338	0.001 270	0.035 110	0.035 44	0.001 327	0.031 335	0.001 253
DCP13	.600	0.144	0.135 18	0.006 358	0.004 251	0.002 237	0.031 149	0.035 48	0.001 373	0.001 265	0.032 122
DCP14	.701	0.227	0.001 74	0.005 349	0.001 271	0.004 263	0.003 263	0.002 51	0.001 36	0.002 335	0.001 64
DCP15	.800	0.085	0.056 42	0.005 10	0.001 179	0.002 255	0.002 53	0.002 94	0.002 341	0.001 289	0.004 88
DCP16	.900	-0.112	0.019 98	0.004 128	0.001 244	0.004 302	0.002 244	0.031 237	0.031 268	0.001 141	0.004 279
DCP17	.965	-0.056	0.003 167	0.002 216	0.001 237	0.001 164	0.003 68	0.032 264	0.002 29	0.032 27	0.005 122

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TURB HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
2.0	69.90	0.179	0.592	5.14	0.0	2.44	12137.2	20

V	Q	RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
196.2	104073.	0.95E 07	-0.026	0.689	5.80	-0.00072	1.152	0.0
(643.8)	(2173.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		2.441	5.139	2	0.098	310	0.116	193	0.015	76	0.006	317	0.010	130	0.003	156	0.006	180	0.008	129
CN		0.422	0.265	353	0.008	324	0.037	246	0.001	166	0.002	144	0.001	41	0.002	116	0.001	79
CM		-0.008	0.023	103	0.003	195	0.031	81	0.000	219	0.000	1	0.000	141	0.001	29	0.000	267
CP 1	.010	0.775	1.572	335	0.011	198	0.026	167	0.029	251	0.017	36	0.039	256	0.039	152	0.006	17	0.035	233
CP 2	.020	0.010	1.294	347	0.007	70	0.023	255	0.004	263	0.005	95	0.001	193	0.001	189	0.001	133	0.002	327
CP 3	.030	1.014	1.121	341	0.014	41	0.020	269	0.007	201	0.004	57	0.000	279	0.002	246	0.002	93	0.033	302
CP 4	.049	1.241	1.201	341	0.019	203	0.024	270	0.016	181	0.017	44	0.035	187	0.003	341	0.003	218	0.036	331
CP 5	.074	1.335	1.211	341	0.077	272	0.002	193	0.015	190	0.014	59	0.011	294	0.003	167	0.033	185	0.003	151
CP 6	.099	1.339	0.966	341	0.150	271	0.049	126	0.006	117	0.013	131	0.010	333	0.032	233	0.032	353	0.032	62
CP 7	.145	0.793	0.435	349	0.047	74	0.033	272	0.010	162	0.009	212	0.015	139	0.013	73	0.004	269	0.006	131
CP 8	.200	0.467	0.201	356	0.024	20	0.019	266	0.006	173	0.001	117	0.001	167	0.002	275	0.001	131	0.001	49
CP 9	.252	0.540	0.342	352	0.017	345	0.011	243	0.003	154	0.002	43	0.001	127	0.001	69	0.010	129	0.003	224
CP10	.320	0.510	0.286	354	0.014	335	0.039	231	0.002	188	0.002	212	0.000	139	0.001	146	0.003	292	0.002	327
CP11	.365	0.432	0.227	7	0.012	358	0.006	257	0.002	31	0.002	195	0.001	176	0.002	57	0.002	13	0.005	73
CP12	.521	0.373	0.177	13	0.012	345	0.026	276	0.001	305	0.004	167	0.003	337	0.001	232	0.003	23	0.013	36
CP13	.600	0.245	0.129	71	0.012	356	0.008	261	0.002	95	0.003	191	0.001	12	0.002	49	0.001	317	0.001	89
CP14	.701	0.114	0.096	31	0.014	359	0.008	210	0.002	105	0.001	177	0.001	358	0.001	98	0.001	255	0.001	137
CP15	.802	0.116	0.049	34	0.010	10	0.004	274	0.032	22	0.002	323	0.002	184	0.001	251	0.002	272	0.001	113
CP16	.900	-0.102	0.016	44	0.008	351	0.005	214	0.001	54	0.001	124	0.004	265	0.002	277	0.001	146	0.002	27
CP17	.969	-0.072	0.021	180	0.005	43	0.001	298	0.001	263	0.003	163	0.002	67	0.001	117	0.002	216	0.002	204

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TURB HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
2.0	68.95	0.179	0.591	5.15	0.0	4.96	12137.3	20

V	Q	RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
195.6	103699.	0.95E 07	-0.333	0.999	9.25	-0.00095	1.533	0.0
(641.8)	(2165.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		4.930	5.151	2	0.132	350	0.146	175	0.006	95	0.005	38	0.017	134	0.011	179	0.009	142	0.006	249
CN		0.698	0.267	356	0.029	247	0.014	169	0.003	29	0.003	148	0.002	147	0.001	156	0.001	56	0.002	282
CM		0.035	0.027	113	0.003	164	0.000	73	0.002	175	0.001	33	0.001	113	0.001	126	0.000	311	0.001	70
CP 1	.010	0.217	1.304	335	0.110	37	0.036	247	0.074	161	0.006	117	0.016	138	0.004	167	0.011	68	0.034	299
CP 2	.020	2.234	1.227	347	0.008	195	0.027	147	0.045	190	0.022	78	0.021	147	0.002	26	0.001	217	0.015	330
CP 3	.030	1.143	1.177	341	0.031	218	0.007	147	0.043	196	0.002	73	0.014	141	0.001	33	0.005	136	0.011	333
CP 4	.049	1.276	0.919	341	0.017	59	0.047	133	0.003	196	0.001	65	0.005	273	0.012	345	0.010	177	0.001	254
CP 5	.074	1.764	0.914	341	0.067	55	0.017	148	0.026	356	0.017	73	0.019	296	0.037	353	0.017	134	0.015	112
CP 6	.099	1.232	0.907	341	0.099	9	0.057	258	0.052	38	0.008	331	0.018	294	0.013	124	0.007	297	0.004	147
CP 7	.145	1.570	0.534	351	0.247	260	0.127	136	0.166	164	0.056	46	0.045	163	0.027	78	0.004	29	0.010	263
CP 8	.200	1.094	0.487	3	0.195	253	0.134	142	0.327	16	0.030	67	0.011	334	0.032	334	0.012	163	0.010	81
CP 9	.252	0.928	0.351	356	0.068	322	0.074	133	0.251	343	0.019	246	0.013	194	0.036	125	0.033	121	0.005	71
CP10	.320	0.776	0.247	4	0.022	324	0.055	97	0.061	319	0.046	195	0.026	86	0.014	322	0.002	310	0.003	76
CP11	.365	0.435	0.199	73	0.026	71	0.039	242	0.006	297	0.008	141	0.002	31	0.001	134	0.002	4	0.001	290
CP12	.521	0.472	0.155	39	0.021	358	0.010	241	0.003	21	0.003	189	0.003	341	0.003	133	0.001	187	0.001	280
CP13	.600	0.392	0.171	42	0.018	351	0.038	274	0.002	17	0.004	217	0.003	129	0.003	311	0.032	169	0.032	371
CP14	.701	0.376	0.091	66	0.024	346	0.012	211	0.007	46	0.001	152	0.002	6	0.003	323	0.001	125	0.002	227
CP15	.802	0.163	0.066	73	0.014	319	0.006	192	0.004	11	0.004	215	0.003	19	0.035	355	0.003	167	0.002	186
CP16	.902	-0.091	0.026	78	0.010	273	0.033	155	0.004	347	0.035	149	0.031	344	0.033	111	0.003	41	0.036	278
CP17	.969	-0.083	0.008	183	0.034	227	0.002	44	0.001	251	0.032	345	0.032	49	0.032	150	0.001	125	0.032	233

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ C.C	DRIVE HZ 64.96	K 0.180	MACH NO 0.597	DEL.ALPHA 3.04	DEL.H 0.0	ALPHA.0 7.46	TEST POINT 12117.4	CYCLES ANALYSED 22
V 195.0 (639.7)	Q 103321. (2157.9)	RN 0.95E 07	CN(MIN) -0.079	CN(MAX) 1.728	ALPHA.NMAX 10.23	AERO DAMP -0.00087	TDP 1.386	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.457	3.036 0	0.332 27	0.178 166	0.046 136	0.013 351	0.013 27	0.009 196	0.006 206	0.013 244
CN		0.444	0.277 36	0.085 324	0.029 211	0.003 142	0.003 119	0.003 96	0.002 184	0.004 261	0.003 261
CM		0.039	0.025 257	0.021 76	0.011 379	0.003 183	0.001 207	0.001 93	0.001 329	0.001 184	0.001 48
CP 1	.010	3.023	0.777 349	0.157 51	0.035 167	0.006 142	0.009 121	0.008 281	0.013 52	0.004 219	0.011 167
CP 2	.020	2.971	0.937 358	0.199 59	0.032 170	0.033 79	0.010 118	0.023 49	0.017 129	0.005 261	0.010 132
CP 3	.030	2.817	0.856 357	0.092 46	0.078 108	0.014 123	0.027 71	0.034 5	0.019 162	0.004 73	0.010 115
CP 4	.040	2.775	0.513 4	0.177 40	0.154 105	0.075 203	0.014 103	0.029 44	0.019 321	0.018 321	0.008 180
CP 5	.074	2.635	0.312 33	0.339 33	0.209 283	0.089 173	0.030 306	0.033 144	0.034 27	0.021 293	0.001 179
CP 6	.099	2.543	0.307 72	0.430 77	0.160 263	0.025 178	0.025 280	0.049 147	0.309 3	0.024 125	0.029 352
CP 7	.149	1.797	0.780 63	0.378 32	0.042 31	0.090 25	0.015 147	0.026 276	0.016 349	0.025 95	0.028 73
CP 8	.200	1.361	0.604 31	0.216 325	0.068 290	0.036 291	0.017 220	0.002 313	0.018 22	0.002 306	0.023 255
CP 9	.250	1.188	0.518 22	0.227 297	0.136 243	0.063 216	0.034 170	0.015 107	0.011 185	0.017 57	0.014 273
CP10	.300	1.021	0.431 22	0.209 288	0.113 270	0.068 184	0.043 137	0.032 49	0.015 58	0.016 23	0.011 317
CP11	.399	0.790	0.306 38	0.149 288	0.094 187	0.031 111	0.027 89	0.028 74	0.018 294	0.011 195	0.007 133
CP12	.521	0.576	0.247 46	0.101 289	0.060 161	0.018 54	0.014 47	0.015 321	0.012 207	0.009 74	0.010 283
CP13	.600	0.440	0.203 62	0.083 287	0.051 150	0.020 16	0.006 11	0.009 301	0.011 105	0.007 58	0.006 254
CP14	.701	0.178	0.167 79	0.060 284	0.040 117	0.022 343	0.006 337	0.008 233	0.011 113	0.010 345	0.004 223
CP15	.400	0.172	0.117 67	0.054 265	0.030 105	0.011 337	0.010 338	0.012 234	0.009 85	0.005 327	0.003 224
CP16	.900	-0.073	0.070 30	0.042 242	0.021 85	0.003 336	0.005 287	0.003 121	0.001 171	0.002 347	0.005 179
CP17	.965	-0.085	0.025 36	0.070 256	0.011 49	0.001 199	0.003 20	0.004 190	0.373 172	0.039 13	0.037 229

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ 0.0	DRIVE HZ 64.62	K 0.177	MACH NO 0.597	DEL.ALPHA 2.91	DEL.H 0.0	ALPHA.0 9.94	TEST POINT 12139.1	CYCLES ANALYSED 20
V 196.9 (646.0)	Q 104379. (2180.0)	RN 0.95E 07	CN(MIN) -0.079	CN(MAX) 1.277	ALPHA.NMAX 11.56	AERO DAMP -0.00139	TDP 2.236	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		9.943	3.007 3	0.233 63	0.053 228	0.017 175	0.012 49	0.014 253	0.014 205	0.014 171	0.033 308
CN		0.941	0.354 75	0.062 37	0.027 42	0.009 304	0.007 177	0.003 193	0.005 149	0.004 146	0.004 71
CM		0.000	0.050 319	0.016 111	0.009 131	0.007 76	0.004 16	0.001 4	0.002 343	0.001 134	0.001 216
CP 1	.010	3.429	3.245 27	0.139 58	0.242 355	0.026 324	0.009 332	0.017 234	0.004 342	0.017 189	0.002 274
CP 2	.020	3.407	0.793 39	0.175 75	0.065 70	0.017 330	0.019 332	0.020 245	0.005 154	0.035 282	0.006 297
CP 3	.030	3.151	0.176 67	0.271 78	0.308 5	0.007 131	0.041 79	0.034 311	0.021 246	0.024 159	0.011 279
CP 4	.040	2.975	0.769 146	0.318 80	0.032 121	0.105 88	0.045 77	0.030 48	0.017 353	0.021 97	0.025 332
CP 5	.074	2.648	0.524 149	0.345 67	0.131 145	0.173 61	0.039 157	0.047 62	0.034 269	0.017 61	0.016 339
CP 6	.099	2.518	0.717 147	0.241 55	0.160 147	0.055 57	0.060 179	0.074 67	0.029 121	0.016 16	0.019 134
CP 7	.149	2.176	0.778 170	0.079 105	0.147 99	0.037 181	0.012 154	0.037 192	0.017 183	0.021 187	0.016 172
CP 8	.200	1.555	0.555 42	0.149 91	0.114 91	0.037 311	0.009 187	0.011 244	0.029 114	0.018 349	0.009 279
CP 9	.250	1.359	0.488 63	0.149 50	0.047 54	0.013 42	0.008 38	0.008 225	0.013 117	0.002 189	0.015 132
CP10	.300	1.131	0.466 50	0.159 58	0.006 41	0.027 27	0.024 191	3.18 158	0.009 159	0.037 165	0.024 108
CP11	.399	0.888	0.369 56	0.097 7	0.007 16	0.040 359	0.019 329	0.011 12	0.007 356	0.004 313	0.011 86
CP12	.501	0.667	0.391 54	0.063 352	0.043 352	0.037 359	0.023 274	0.014 232	0.016 246	0.012 177	0.013 351
CP13	.600	0.538	0.342 60	0.063 319	0.037 332	0.040 269	0.023 224	0.017 224	0.011 125	0.001 227	0.010 112
CP14	.701	0.411	0.293 55	0.056 285	0.024 298	0.029 244	0.033 197	0.014 189	0.011 157	0.012 195	0.009 38
CP15	.400	0.321	0.192 50	0.056 290	0.029 285	0.029 217	0.021 145	0.004 44	0.004 117	0.005 147	0.005 22
CP16	.900	-0.018	0.133 24	0.047 290	0.028 281	0.016 239	0.018 162	0.010 174	0.007 4	0.004 150	0.008 269
CP17	.969	-0.066	0.040 38	0.021 350	0.022 321	0.011 243	0.009 190	0.007 44	0.004 242	0.006 52	0.006 49

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DFL.ALPHA	DFL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	66.84	0.179	0.589	2.88	0.0	12.50	12139.2	70

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
195.4	103364.	0.95E 07	-0.045	1.266	17.56	-0.00155	7.479	0.0
(641.0)	(2158.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		12.504	2.875	0	0.023	336	0.016	190	0.043	86	0.019	353	0.010	141	0.011	114	0.010	155	0.007	318
CN		0.000	0.221	78	0.027	190	0.015	46	0.007	112	0.001	144	0.006	197	0.002	355	0.002	280	0.003	102
CM		-0.028	0.058	215	0.004	228	0.007	190	0.002	260	0.001	311	0.003	266	0.001	98	0.001	306	0.002	307
DCP 1	.010	3.592	0.009	124	0.091	55	0.033	167	0.010	58	0.015	163	0.007	266	0.011	197	0.003	82	0.006	43
DCP 2	.020	3.534	0.166	123	0.170	84	0.026	172	0.045	107	0.005	55	0.015	145	0.013	69	0.003	77	0.009	34
DCP 3	.332	3.242	0.311	151	0.190	79	0.067	175	0.042	69	0.031	221	0.021	115	0.007	41	0.006	46	0.011	292
DCP 4	.349	2.933	0.471	154	0.034	15	0.118	170	0.038	294	0.041	198	0.033	317	0.016	189	0.021	138	0.011	353
DCP 5	.374	2.640	0.559	148	0.092	265	0.073	118	0.055	264	0.005	47	0.026	296	0.021	57	0.014	104	0.014	154
DCP 6	.099	2.414	0.490	136	0.130	243	0.026	77	0.008	206	0.019	316	0.008	354	0.026	116	0.024	200	0.009	300
DCP 7	.149	1.793	0.328	94	0.095	192	0.033	96	0.018	232	0.018	344	0.029	221	0.015	11	0.012	247	0.006	309
DCP 8	.200	1.411	0.260	108	0.058	166	0.028	233	0.025	155	0.015	197	0.006	297	0.014	120	0.019	7	0.010	270
DCP 9	.250	1.393	0.215	104	0.060	158	0.013	180	0.033	166	0.012	141	0.021	223	0.013	30	0.016	313	0.005	157
DCP10	.300	1.738	0.315	92	0.099	145	0.036	154	0.005	110	0.006	291	0.003	175	0.021	2	0.017	315	0.008	176
DCP11	.399	1.055	0.152	74	0.099	110	0.050	176	0.027	171	0.026	42	0.025	201	0.025	277	0.014	329	0.012	65
DCP12	.501	0.899	0.134	57	0.055	89	0.047	66	0.017	90	0.001	319	0.337	131	0.004	123	0.033	29	0.010	264
DCP13	.600	0.621	0.176	49	0.050	41	0.036	32	0.016	41	0.023	232	0.027	135	0.003	224	0.008	214	0.011	65
DCP14	.701	0.497	0.253	19	0.027	42	0.034	11	0.013	145	0.026	142	0.020	56	0.034	236	0.012	146	0.010	113
DCP15	.800	0.330	0.217	36	0.034	18	0.027	145	0.007	38	0.024	163	0.008	71	0.035	139	0.011	151	0.014	153
DCP16	.900	0.084	0.158	31	0.024	17	0.026	147	0.011	139	0.014	73	0.015	95	0.002	355	0.005	67	0.008	111
DCP17	.969	-0.009	0.075	46	0.078	17	0.014	147	0.015	240	0.009	174	0.013	36	0.015	333	0.021	56	0.017	160

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DFL.ALPHA	DFL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	66.92	0.180	0.597	2.91	0.0	14.96	12139.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
194.5	102823.	0.95E 07	-0.102	1.191	14.18	-0.00141	2.247	0.0
(638.2)	(2147.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		14.962	2.907	0	0.095	200	0.097	185	0.033	102	0.026	1	0.015	219	0.029	184	0.015	104	0.011	341
CN		1.090	0.182	68	0.072	121	0.021	209	0.007	108	0.003	196	0.032	161	0.001	180	0.001	355	0.007	350
CM		-0.048	0.050	217	0.019	236	0.007	159	0.003	317	0.002	4	0.001	13	0.001	67	0.001	123	0.003	166
DCP 1	.010	3.489	0.298	152	0.050	209	0.071	145	0.021	304	0.026	333	0.019	222	0.010	231	0.016	198	0.007	137
DCP 2	.020	3.474	0.154	157	0.017	210	0.067	191	0.026	259	0.020	18	0.007	278	0.025	323	0.014	264	0.017	159
DCP 3	.330	2.999	0.490	156	0.091	279	0.031	321	0.018	49	0.021	321	0.034	114	0.319	248	0.015	194	0.030	167
DCP 4	.349	2.756	0.510	143	0.128	256	0.065	13	0.033	106	0.033	335	0.016	55	0.032	145	0.010	209	0.014	272
DCP 5	.374	2.406	0.725	110	0.135	276	0.356	340	0.036	78	0.012	357	0.010	353	0.014	77	0.010	104	0.011	285
DCP 6	.099	2.091	0.207	116	0.083	191	0.028	339	0.024	83	0.016	297	0.010	297	0.016	126	0.026	170	0.011	335
DCP 7	.149	1.725	0.148	98	0.087	164	0.042	292	0.004	33	0.010	116	0.006	41	0.029	84	0.010	0	0.010	308
DCP 8	.200	1.516	0.203	96	0.066	186	0.031	235	0.035	352	0.017	13	0.018	188	0.014	84	0.033	213	0.015	13
DCP 9	.250	1.413	0.239	86	0.066	148	0.025	241	0.010	342	0.017	72	0.013	119	0.012	136	0.016	135	0.008	115
DCP10	.300	1.255	0.241	75	0.059	115	0.051	222	0.011	291	0.024	288	0.001	322	0.015	319	0.005	45	0.006	292
DCP11	.399	1.091	0.268	66	0.063	111	0.042	216	0.036	247	0.012	251	0.008	338	0.015	272	0.017	22	0.017	83
DCP12	.501	0.870	0.242	52	0.053	88	0.047	186	0.025	140	0.023	153	0.014	71	0.013	202	0.014	4	0.014	56
DCP13	.600	0.685	0.235	43	0.042	79	0.034	187	0.021	150	0.014	161	0.003	94	0.035	51	0.026	302	0.033	7
DCP14	.701	0.564	0.220	40	0.035	44	0.032	176	0.017	97	0.007	158	0.005	223	0.001	223	0.015	236	0.010	321
DCP15	.800	0.391	0.195	39	0.030	40	0.025	175	0.012	104	0.009	196	0.015	236	0.011	247	0.010	104	0.013	314
DCP16	.900	0.122	0.145	41	0.029	16	0.016	151	0.010	151	0.005	255	0.006	235	0.004	207	0.011	105	0.007	279
DCP17	.969	-0.003	0.060	52	0.010	77	0.039	190	0.002	289	0.003	325	0.013	149	0.002	81	0.005	300	0.008	329

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
3.0	23.09	0.052	0.686	7.68	0.0	-0.92	12141.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO.DAMP	TDP	EXT.DAMP
225.2	129133.	0.19E 08	-0.033	0.480	7.68	-0.00100	1.784	0.0
(738.7)	(2697.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		-0.018	7.658 0	0.061 10	0.056 201	0.010 123	0.027 26	0.039 77	0.013 186	0.028 194	0.015 349
CN		0.147	0.337 351	0.005 296	0.003 136	0.002 74	0.001 295	0.002 227	0.001 225	0.001 196	0.001 356
CM		-0.018	0.013 329	0.001 352	0.001 144	0.000 220	0.000 53	0.000 79	0.000 134	0.001 40	0.000 141
CP 1	.012	-1.215	1.780 346	0.251 25	0.139 312	0.067 13	0.009 103	0.032 14	0.026 88	0.011 118	0.019 91
CP 2	.020	-0.749	1.606 347	0.143 52	0.021 568	0.047 32	0.050 107	0.022 176	0.015 105	0.029 148	0.015 279
CP 3	.030	-0.456	1.461 347	0.214 56	0.063 127	0.003 108	0.052 112	0.053 185	0.020 255	0.014 149	0.036 237
CP 4	.040	-0.028	1.252 347	0.146 56	0.135 191	0.135 209	0.071 282	0.023 353	0.022 251	0.050 334	0.058 42
CP 5	.074	0.385	0.882 348	0.139 248	0.064 319	0.010 13	0.008 311	0.004 345	0.010 72	0.017 138	0.010 21:
CP 6	.090	0.534	0.900 348	0.056 247	0.082 371	0.010 246	0.010 91	0.015 198	0.007 111	0.035 124	0.037 65
CP 7	.145	0.451	0.840 348	0.145 245	0.054 133	0.015 264	0.055 117	0.044 7	0.015 222	0.076 5	0.032 241
CP 8	.200	0.291	0.615 351	0.118 250	0.139 144	0.105 40	0.080 298	0.049 191	0.009 86	0.073 161	0.012 68
CP 9	.250	0.204	0.391 352	0.046 48	0.032 339	0.013 203	0.004 72	0.002 144	0.001 68	0.037 241	0.002 2
CP10	.300	0.211	0.237 351	0.025 45	0.017 335	0.006 209	0.003 75	0.002 274	0.001 241	0.001 191	0.002 345
CP11	.350	0.192	0.280 355	0.011 48	0.005 310	0.003 227	0.002 105	0.002 193	0.001 317	0.004 224	0.002 352
CP12	.501	0.147	0.213 356	0.006 46	0.004 315	0.002 242	0.001 74	0.002 252	0.003 165	0.001 194	0.001 330
CP13	.630	0.162	0.149 358	0.003 51	0.003 345	0.001 342	0.000 131	0.001 223	0.001 294	0.003 201	0.002 6
CP14	.701	0.252	0.094 0	0.004 67	0.002 338	0.001 26	0.002 218	0.001 207	0.002 272	0.002 717	0.002 323
CP15	.803	0.088	0.339 9	0.001 141	0.001 350	0.002 34	0.002 274	0.002 274	0.002 300	0.004 235	0.001 302
CP16	.900	-0.127	0.010 147	0.007 234	0.002 34	0.002 40	0.002 221	0.003 296	0.002 296	0.005 207	0.002 327
CP17	.965	-0.257	0.029 176	0.005 212	0.001 62	0.001 29	0.002 240	0.001 215	0.001 352	0.002 246	0.002 293

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
3.0	23.13	0.053	0.684	2.66	0.0	2.43	12141.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO.DAMP	TDP	EXT.DAMP
224.3	128659.	0.19E 08	-0.019	0.542	5.22	-0.00124	2.238	0.0
(735.8)	(2687.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.431	2.657 0	0.074 22	0.061 231	0.039 111	0.076 40	0.009 14	0.027 206	0.014 142	0.010 344
CN		0.477	0.336 352	0.020 335	0.014 232	0.010 119	0.004 3	0.001 347	0.001 276	0.001 224	0.001 18
CM		-0.006	0.013 320	0.003 149	0.002 39	0.001 303	0.000 216	0.000 28	0.003 62	0.000 320	0.000 68
CP 1	.012	0.494	1.290 345	0.116 36	0.061 178	0.010 293	0.006 279	0.000 19	0.005 311	0.007 275	0.004 151
CP 2	.020	0.618	1.280 349	0.105 45	0.019 170	0.006 22	0.004 169	0.002 88	0.003 170	0.008 308	0.001 13
CP 3	.030	0.739	1.005 348	0.100 48	0.014 170	0.008 21	0.003 161	0.002 93	0.002 141	0.006 308	0.001 322
CP 4	.040	1.058	0.920 348	0.105 50	0.011 183	0.010 24	0.004 135	0.001 76	0.003 114	0.006 299	0.002 10
CP 5	.074	1.205	0.741 348	0.092 46	0.013 166	0.036 226	0.004 275	0.003 162	0.004 217	0.005 301	0.001 241
CP 6	.090	1.341	0.750 348	0.109 51	0.028 156	0.005 5	0.012 113	0.010 178	0.002 243	0.002 260	0.005 228
CP 7	.145	1.270	0.871 347	0.120 54	0.061 330	0.078 33	0.014 161	0.045 354	0.017 83	0.013 283	0.030 39
CP 8	.200	1.089	0.876 349	0.015 38	0.142 316	0.015 82	0.089 289	0.023 27	0.058 247	0.033 344	0.018 227
CP 9	.240	0.971	0.897 348	0.166 242	0.098 318	0.131 208	0.019 310	0.002 178	0.018 62	0.055 148	0.031 40
CP10	.300	0.711	0.609 356	0.131 271	0.124 189	0.091 152	0.082 72	0.025 332	0.011 35	0.038 280	0.035 338
CP11	.390	0.459	0.277 1	0.049 273	0.089 153	0.051 49	0.005 3	0.018 17	0.016 277	0.008 204	0.002 167
CP12	.501	0.304	0.123 9	0.038 41	0.010 163	0.019 42	0.015 296	0.008 193	0.004 113	0.002 350	0.001 119
CP13	.600	0.268	0.081 16	0.045 51	0.014 335	0.003 211	0.003 187	0.001 167	0.001 223	0.001 51	0.000 8
CP14	.701	0.317	0.044 25	0.032 48	0.011 296	0.005 187	0.002 94	0.001 324	0.002 224	0.000 92	0.000 36
CP15	.800	0.120	0.031 23	0.011 48	0.008 278	0.005 149	0.001 355	0.001 225	0.001 167	0.001 194	0.001 320
CP16	.900	-0.125	0.013 19	0.004 342	0.008 269	0.003 152	0.001 150	0.001 219	0.001 260	0.002 125	0.002 226
CP17	.969	-0.078	0.013 188	0.002 289	0.005 281	0.003 154	0.002 344	0.002 140	0.001 161	0.001 84	0.001 335

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.11	0.051	0.684	2.60	0.0	4.96	12141.1	20

V	Q	RN	CNMIN)	CNMAX)	ALPHA.NMAX	AERO DAMP	TOR	EXT DAMP
223.7	128338.	0.10E 08	-0.024	0.981	6.67	-0.00202	3.604	0.0
(733.9)	(2680.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		-.063	2.595 0	0.072 39	0.064 236	0.057 97	0.054 29	0.035 279	0.041 177	0.039 190	0.070 70
CN		0.727	0.294 11	0.064 58	0.021 14	0.014 331	0.007 279	0.001 258	0.004 221	0.004 138	0.036 92
CM		0.007	0.014 286	0.005 172	0.003 157	0.003 112	0.003 36	0.002 321	0.001 312	0.002 274	0.001 222
DCP 1	.010	1.541	0.824 356	0.120 23	0.031 75	0.011 236	0.005 180	0.011 244	0.009 264	0.004 13	0.010 345
DCP 2	.025	1.509	0.722 358	0.087 6	0.002 262	0.016 248	0.017 164	0.005 351	0.004 240	0.007 99	0.007 8
DCP 3	.033	1.492	0.610 358	0.076 353	0.011 708	0.014 233	0.016 161	0.005 19	0.002 736	0.006 89	0.038 10
DCP 4	.140	1.699	0.468 359	0.069 70	0.005 174	0.008 199	0.008 131	0.036 319	0.002 306	0.001 47	0.005 6
DCP 5	.074	1.781	0.431 358	0.069 28	0.005 194	0.008 212	0.005 134	0.006 331	0.002 328	0.001 3	0.004 13
DCP 6	.099	1.905	0.396 358	0.067 56	0.009 38	0.005 235	0.004 127	0.006 330	0.002 273	0.000 35	0.003 19
DCP 7	.147	1.893	0.366 357	0.062 34	0.012 24	0.006 267	0.004 153	0.005 319	0.001 290	0.000 40	0.002 7
DCP 8	.270	1.898	0.363 359	0.070 47	0.022 60	0.013 273	0.010 256	0.006 296	0.001 119	0.004 99	0.004 92
DCP 9	.350	1.451	0.328 352	0.454 60	0.147 115	0.020 193	0.080 296	0.037 215	0.065 250	0.025 227	0.029 61
DCP10	.320	1.337	0.467 19	0.240 61	0.134 61	0.128 31	0.080 49	0.031 4	0.017 351	0.006 207	0.004 199
DCP11	.350	0.721	0.358 11	0.017 356	0.089 359	0.046 7	0.041 322	0.020 347	0.008 295	0.005 123	0.014 46
DCP12	.501	0.493	0.210 27	0.063 316	0.044 352	0.052 295	0.035 264	0.022 292	0.021 224	0.017 182	0.007 112
DCP13	.600	0.368	0.395 47	0.046 343	0.020 293	0.031 265	0.027 216	0.018 196	0.022 166	0.019 124	0.016 91
DCP14	.701	0.318	0.073 128	0.028 30	0.007 214	0.011 249	0.021 187	0.018 129	0.012 96	0.013 82	0.011 17
DCP15	.800	0.122	0.044 114	0.025 25	0.003 263	0.008 244	0.013 180	0.010 115	0.008 80	0.007 43	0.006 337
DCP16	.900	-0.118	0.026 70	0.022 348	0.005 297	0.010 248	0.013 174	0.010 116	0.007 72	0.006 91	0.001 298
DCP17	.969	-0.091	0.015 139	0.010 351	0.003 129	0.004 296	0.002 143	0.002 34	0.002 187	0.004 114	0.002 271

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	22.45	0.051	0.686	2.47	0.0	7.42	12143.1	20

V	Q	RN	CNMIN)	CNMAX)	ALPHA.NMAX	AERO DAMP	TOR	EXT DAMP
225.3	129267.	0.10E 08	-0.017	1.009	9.64	-0.00185	3.318	0.0
(739.3)	(2699.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.423	2.475 0	0.096 28	0.041 220	0.018 83	0.017 328	0.007 101	0.014 310	0.021 270	0.014 344
CN		0.882	0.117 31	0.022 136	0.007 273	0.010 219	0.007 139	0.002 55	0.003 342	0.003 334	0.004 354
CM		-0.001	0.013 236	0.003 24	0.001 33	0.002 325	0.002 331	0.001 272	0.000 168	0.001 118	0.001 138
DCP 1	.010	2.147	0.576 359	0.078 84	0.008 27	0.009 108	0.019 0	0.004 74	0.010 251	0.007 40	0.005 324
DCP 2	.020	2.086	0.577 2	0.040 76	0.018 16	0.013 115	0.011 22	0.005 79	0.004 312	0.004 73	0.003 61
DCP 3	.030	2.000	0.541 2	0.025 71	0.024 6	0.011 116	0.013 13	0.006 71	0.006 322	0.004 105	0.003 48
DCP 4	.049	2.095	0.400 3	0.007 24	0.010 12	0.004 202	0.010 6	0.002 0	0.006 334	0.003 97	0.004 30
DCP 5	.074	2.134	0.346 3	0.007 23	0.002 28	0.004 194	0.007 15	0.001 324	0.005 333	0.002 86	0.002 7
DCP 6	.099	2.223	0.292 4	0.011 46	0.001 240	0.009 223	0.005 61	0.003 342	0.004 311	0.002 95	0.002 18
DCP 7	.149	2.129	0.197 8	0.064 72	0.031 331	0.028 227	0.016 126	0.007 34	0.004 314	0.003 10	0.004 283
DCP 8	.200	1.985	0.073 46	0.147 79	0.066 348	0.061 243	0.022 131	0.010 34	0.002 299	0.006 48	0.007 352
DCP 9	.250	1.632	0.263 140	0.040 200	0.066 113	0.049 225	0.010 110	0.020 136	0.012 258	0.009 91	0.006 110
DCP10	.300	1.349	0.169 109	0.154 200	0.097 272	0.043 311	0.005 296	0.020 319	0.020 10	0.023 54	0.013 36
DCP11	.399	0.972	0.117 33	0.050 106	0.031 217	0.025 237	0.011 173	0.001 255	0.007 132	0.011 277	0.007 67
DCP12	.501	0.635	0.201 29	0.077 102	0.035 106	0.022 187	0.016 170	0.004 83	0.010 33	0.013 304	0.010 12
DCP13	.600	0.430	0.156 27	0.021 122	0.012 126	0.026 155	0.017 154	0.001 108	0.009 311	0.010 296	0.012 312
DCP14	.701	0.321	0.066 46	0.036 256	0.010 10	0.013 81	0.002 143	0.009 95	0.006 289	0.005 246	0.002 298
DCP15	.800	0.141	0.053 33	0.031 247	0.008 35	0.003 79	0.007 89	0.003 42	0.002 33	0.006 323	0.004 269
DCP16	.900	-0.094	0.053 25	0.004 228	0.009 350	0.004 164	0.005 127	0.002 117	0.002 196	0.001 338	0.005 306
DCP17	.969	-0.092	0.013 49	0.002 225	0.008 308	0.003 95	0.004 174	0.000 223	0.003 172	0.001 326	0.002 328

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.44	3.051	0.685	2.47	0.0	9.96	12143.2	25

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
224.5 (736.6)	128774. (2689.5)	0.10E 08	-0.048	1.041	11.09	-0.00094	1.675	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI

(table data illegible)

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.68	0.052	0.685	2.46	0.0	12.50	12143.3	25

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
223.6 (733.6)	128185. (2677.2)	0.10E 08	-0.091	1.110	14.69	-0.00122	7.179	0.0

HARMONIC ANALYSIS

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.17	0.101	0.696	2.83	0.0	2.43	12145.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
227.3 (745.8)	127898. (2671.2)	0.10E 08	-0.023	0.813	5.15	-0.00100	1.824	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.428	2.833 0	0.098 14	0.095 245	0.025 113	0.031 48	0.002 332	0.011 237	0.011 150	0.008 331
CN		0.474	0.326 346	0.006 253	0.005 148	0.004 26	0.003 267	0.003 16	0.002 231	0.002 48	0.001 217
CM		-0.007	0.016 296	0.003 84	0.002 311	0.001 130	0.000 57	0.000 227	0.000 81	0.000 160	0.000 1
DCP 1	.010	0.495	1.283 336	0.112 27	0.011 146	0.008 182	0.003 4	0.007 335	0.009 0	0.006 74	0.004 29
DCP 2	.020	0.624	1.065 341	0.104 38	0.011 139	0.005 305	0.003 100	0.004 43	0.004 70	0.004 130	0.002 340
DCP 3	.030	0.751	0.878 341	0.099 38	0.008 142	0.005 319	0.003 100	0.002 25	0.003 54	0.003 111	0.001 306
DCP 4	.049	1.076	0.801 340	0.104 37	0.007 165	0.007 331	0.006 78	0.003 45	0.004 38	0.004 111	0.000 351
DCP 5	.074	1.219	0.727 339	0.076 35	0.007 163	0.008 200	0.005 234	0.003 51	0.002 99	0.003 105	0.001 142
DCP 6	.099	1.357	0.732 339	0.107 39	0.025 127	0.004 263	0.012 63	0.011 111	0.003 165	0.004 88	0.004 150
DCP 7	.149	1.250	0.854 338	0.125 48	0.058 266	0.074 357	0.026 109	0.036 290	0.036 23	0.016 150	0.021 306
DCP 8	.200	0.912	0.800 341	0.020 90	0.126 289	0.016 48	0.076 240	0.025 339	0.050 191	0.032 274	0.025 137
DCP 9	.250	0.546	0.871 337	0.153 206	0.100 280	0.126 150	0.022 243	0.086 90	0.012 284	0.047 34	0.021 257
DCP10	.300	0.3	0.657 343	0.253 223	0.118 109	0.036 94	0.049 0	0.008 288	0.021 267	0.015 132	0.003 21
DCP11	.399	0.455	0.276 359	0.061 227	0.083 97	0.043 327	0.003 48	0.021 279	0.015 161	0.004 45	0.004 115
DCP12	.501	0.297	0.136 21	0.036 19	0.008 99	0.016 311	0.011 197	0.007 61	0.003 301	0.002 271	0.001 200
DCP13	.600	0.269	0.101 29	0.036 20	0.010 241	0.002 242	0.002 170	0.003 340	0.001 277	0.002 192	0.002 200
DCP14	.701	0.322	0.067 37	0.024 13	0.008 225	0.001 246	0.000 265	0.002 112	0.001 332	0.002 280	0.001 307
DCP15	.800	0.124	0.039 36	0.005 0	0.005 203	0.002 319	0.001 167	0.000 207	0.003 292	0.002 0	0.000 129
DCP16	.900	-0.125	0.009 25	0.005 249	0.006 196	0.004 318	0.001 241	0.001 56	0.001 334	0.001 4	0.001 237
DCP17	.969	-0.074	0.015 192	0.004 268	0.004 210	0.002 356	0.000 188	0.002 96	0.002 320	0.001 0	0.003 165

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.49	0.131	0.703	2.66	0.0	7.42	12147.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
229.7 (753.7)	129688. (2708.6)	0.10E 08	-0.062	1.116	8.39	-0.00200	3.707	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.417	2.658 0	0.095 18	0.326 188	0.112 68	0.020 17	0.008 213	0.010 161	0.006 121	0.016 357
CN		0.866	0.144 45	0.063 61	0.003 37	0.017 62	0.005 12	0.006 318	0.001 345	0.004 203	0.003 117
CM		-0.010	0.034 281	0.006 194	0.003 115	0.004 220	0.003 148	0.003 109	0.001 104	0.002 28	0.000 93
DCP 1	.010	2.277	0.669 359	0.103 43	0.317 82	0.029 47	0.003 32	0.004 62	0.005 287	0.006 54	0.001 246
DCP 2	.020	2.047	0.652 4	0.077 25	0.321 43	0.020 46	0.010 26	0.005 21	0.001 35	0.001 105	0.001 38
DCP 3	.030	1.974	0.613 4	0.082 10	0.025 27	0.023 42	0.013 10	0.004 15	0.003 357	0.003 71	0.002 80
DCP 4	.049	2.083	0.668 5	0.047 352	0.006 75	0.015 26	0.008 2	0.006 276	0.005 298	0.001 134	0.005 324
DCP 5	.074	2.121	0.608 6	0.049 5	0.002 46	0.005 48	0.006 45	0.005 298	0.006 279	0.002 150	0.001 356
DCP 6	.099	2.140	0.621 9	0.068 31	0.019 321	0.013 230	0.016 119	0.008 346	0.008 275	0.005 197	0.002 15
DCP 7	.149	2.074	0.192 24	0.137 50	0.057 323	0.024 213	0.014 104	0.006 317	0.006 207	0.004 105	0.002 26
DCP 8	.200	1.580	0.178 122	0.200 69	0.063 4	0.016 62	0.021 347	0.006 295	0.010 258	0.008 155	
DCP 9	.250	1.557	0.384 123	0.349 134	0.070 84	0.060 119	0.017 132	0.039 66	0.035 85	0.024 5	0.028 35
DCP10	.300	1.298	0.329 95	0.177 126	0.101 173	0.042 158	0.030 165	0.022 185	0.030 114	0.023 116	0.031 148
DCP11	.399	0.940	0.239 46	0.130 76	0.037 143	0.030 109	0.007 288	0.014 344	0.009 338	0.008 272	0.011 133
DCP12	.501	0.646	0.333 35	0.140 62	0.031 92	0.044 77	0.026 115	0.004 22	0.004 343	0.022 244	0.007 183
DCP13	.600	0.484	0.254 41	0.067 32	0.024 7	0.049 60	0.031 30	0.019 23	0.006 116	0.016 122	0.010 81
DCP14	.701	0.375	0.172 51	0.038 323	0.034 309	0.024 4	0.032 325	0.025 321	0.016 321	0.009 263	0.014 334
DCP15	.830	0.185	0.139 41	0.036 302	0.019 278	0.013 356	0.021 309	0.023 269	0.015 268	0.015 197	0.007 274
DCP16	.900	-0.062	0.112 26	0.030 317	0.027 288	0.011 307	0.014 291	0.020 241	0.008 231	0.007 172	0.008 228
DCP17	.969	-0.077	0.034 37	0.011 357	0.015 306	0.014 34	0.017 313	0.006 247	0.007 358	0.008 258	0.002 32

135

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	45.26	0.101	0.701	2.62	0.0	9.93	12147.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
228.8	129253.	0.10E 08	-0.055	1.084	11.04	-0.00121	2.232	0.0
(750.6)	(2699.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		9.932	2.619 0	0.101 24	0.046 228	0.070 145	0.007 334	0.004 73	0.008 249	0.015 160	0.011 335
CN		0.929	0.139 51	0.022 66	0.005 67	0.002 152	0.003 239	0.002 144	0.003 317	0.002 34	0.000 201
CM		-0.019	0.031 210	0.001 181	0.002 128	0.002 298	0.002 39	0.001 325	0.001 133	0.001 228	0.000 74
DCP 1	.010	2.710	0.394 2	0.061 58	0.007 241	0.017 183	0.003 165	0.005 1	0.006 92	0.003 9	0.003 194
DCP 2	.020	2.475	0.450 6	0.081 77	0.001 22	0.012 230	0.007 215	0.004 49	0.004 86	0.003 308	0.003 191
DCP 3	.030	2.388	0.461 4	0.061 72	0.011 163	0.010 208	0.004 202	0.006 25	0.001 303	0.001 168	0.002 57
DCP 4	.049	2.379	0.359 6	0.075 67	0.015 337	0.014 229	0.008 205	0.004 119	0.004 40	0.004 323	0.004 155
DCP 5	.074	2.311	0.201 19	0.136 70	0.043 348	0.013 289	0.016 260	0.007 167	0.006 93	0.007 313	0.009 176
DCP 6	.099	2.254	0.114 91	0.175 67	0.034 5	0.027 21	0.019 282	0.000 156	0.005 234	0.002 257	0.008 148
DCP 7	.149	2.063	0.228 121	0.090 55	0.061 109	0.025 30	0.012 72	0.011 31	0.003 345	0.002 311	0.005 158
DCP 8	.200	1.549	0.340 135	0.023 117	0.075 126	0.007 246	0.026 100	0.009 123	0.014 85	0.005 57	0.006 41
DCP 9	.250	1.453	0.145 107	0.049 234	0.020 232	0.030 282	0.017 351	0.008 218	0.011 263	0.007 53	0.008 104
DCP10	.300	1.272	0.149 70	0.017 309	0.030 96	0.014 277	0.007 338	0.011 212	0.006 8	0.006 351	0.012 309
DCP11	.399	1.060	0.195 72	0.016 227	0.006 36	0.019 190	0.009 317	0.007 332	0.016 262	0.006 63	0.008 75
DCP12	.501	0.788	0.213 54	0.019 141	0.002 282	0.016 146	0.003 264	0.009 335	0.004 49	0.005 205	0.013 348
DCP13	.600	0.556	0.217 36	0.015 73	0.006 284	0.009 128	0.017 212	0.012 134	0.002 98	0.003 89	0.011 203
DCP14	.701	0.416	0.184 21	0.017 21	0.017 334	0.012 95	0.012 212	0.009 172	0.005 3	0.008 354	0.004 236
DCP15	.800	0.228	0.149 13	0.021 42	0.013 290	0.006 64	0.004 255	0.009 130	0.009 319	0.009 99	0.005 119
DCP16	.900	-0.033	0.093 13	0.018 36	0.010 302	0.005 103	0.007 189	0.007 101	0.008 301	0.004 327	0.004 234
DCP17	.969	-0.086	0.027 25	0.015 73	0.008 17	0.003 31	0.007 218	0.006 241	0.008 303	0.004 278	0.006 297

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	45.34	0.102	0.697	2.61	0.0	12.45	12147.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
227.0	127759	0.10E 08	-0.090	1.164	13.82	-0.00120	2.197	0.0
(744.9)	(2668.)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.446	2.606 0	0.085 12	0.039 222	0.018 267	0.041 10	0.013 163	0.010 134	0.009 174	0.010 5
CN		1.040	0.121 49	0.012 178	0.001 271	0.009 269	0.010 22	0.005 219	0.001 215	0.003 241	0.004 215
CM		-0.056	0.035 236	0.004 337	0.002 191	0.003 27	0.003 161	0.001 7	0.001 25	0.001 4	0.001 27
DCP 1	.010	3.032	0.296 359	0.028 81	0.004 42	0.007 287	0.006 311	0.001 162	0.004 156	0.000 12	0.003 57
DCP 2	.020	2.630	0.313 8	0.039 66	0.008 181	0.008 333	0.003 340	0.006 56	0.003 234	0.006 325	0.002 213
DCP 3	.030	2.577	0.127 42	0.112 71	0.023 104	0.025 10	0.005 82	0.020 27	0.009 293	0.009 328	0.010 236
DCP 4	.049	2.614	0.180 20	0.066 69	0.012 89	0.009 317	0.004 27	0.005 169	0.007 88	0.006 327	0.005 21
DCP 5	.074	2.435	0.104 97	0.037 73	0.049 141	0.009 178	0.016 79	0.003 279	0.009 29	0.006 242	0.012 33
DCP 6	.099	2.255	0.213 143	0.027 238	0.057 164	0.025 225	0.007 147	0.011 250	0.007 42	0.007 242	0.006 338
DCP 7	.149	1.964	0.182 136	0.101 227	0.047 251	0.034 287	0.015 313	0.019 272	0.009 314	0.015 52	0.007 264
DCP 8	.200	1.558	0.136 123	0.083 223	0.052 260	0.030 354	0.003 10	0.003 300	0.015 324	0.004 231	0.009 191
DCP 9	.250	1.537	0.169 88	0.014 230	0.010 150	0.033 342	0.030 61	0.010 175	0.007 185	0.012 275	0.007 218
DCP10	.300	1.331	0.157 71	0.006 180	0.018 330	0.020 333	0.014 79	0.006 218	0.013 120	0.016 7	0.005 100
DCP11	.399	1.075	0.168 39	0.031 32	0.015 102	0.022 336	0.029 69	0.007 141	0.004 52	0.008 321	0.009 150
DCP12	.501	0.879	0.183 40	0.009 236	0.011 354	0.017 237	0.020 37	0.011 278	0.005 297	0.021 221	0.020 231
DCP13	.600	0.740	0.174 33	0.014 171	0.016 22	0.014 216	0.018 39	0.019 250	0.002 115	0.021 206	0.011 262
DCP14	.701	0.636	0.169 26	0.025 153	0.007 7	0.015 193	0.018 312	0.008 180	0.005 207	0.006 96	0.001 125
DCP15	.800	0.445	0.156 21	0.017 144	0.008 86	0.017 204	0.016 334	0.014 162	0.010 196	0.005 11	0.008 220
DCP16	.900	0.111	0.110 20	0.023 162	0.008 327	0.016 192	0.016 318	0.004 123	0.004 258	0.010 120	0.006 131
DCP17	.969	-0.026	0.036 51	0.014 165	0.005 281	0.013 229	0.003 307	0.004 42	0.002 32	0.004 241	0.002 88

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.88	0.153	0.702	3.17	0.0	-0.02	12149.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
229.8	129655.	0.10E 08	-0.039	0.441	3.13	-0.00084	1.568	0.0
(754.1)	(2707.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		-0.019	3.169 0	0.120 306	0.091 198	0.030 91	0.015 22	0.011 55	0.007 185	0.014 240	0.006 97
CN		0.140	0.299 347	0.004 338	0.005 190	0.001 86	0.001 177	0.001 170	0.001 337	0.001 227	0.003 67
CM		-0.018	0.022 294	0.000 221	0.001 93	0.000 111	0.001 315	0.000 280	0.001 20	0.000 67	0.001 240
DCP 1	.010	-0.901	1.718 329	0.083 356	0.099 263	0.061 317	0.024 339	0.023 264	0.024 301	0.006 338	0.007 257
DCP 2	.020	-0.724	1.515 335	0.155 24	0.009 353	0.029 352	0.050 36	0.028 94	0.006 45	0.018 61	0.015 107
DCP 3	.030	-0.428	1.371 335	0.212 31	0.075 93	0.024 128	0.043 49	0.056 108	0.036 166	0.005 151	0.030 114
DCP 4	.049	0.072	1.145 335	0.145 35	0.118 96	0.134 153	0.097 214	0.073 271	0.032 327	0.005 261	0.027 297
DCP 5	.074	0.385	0.840 336	0.037 193	0.065 263	0.018 332	0.009 351	0.003 62	0.001 82	0.007 64	0.005 78
DCP 6	.099	0.531	0.856 337	0.049 198	0.049 269	0.013 168	0.010 14	0.007 121	0.008 355	0.006 143	0.004 353
DCP 7	.149	0.449	0.793 337	0.153 211	0.057 88	0.022 242	0.046 47	0.041 273	0.021 108	0.017 253	0.025 101
DCP 8	.200	0.232	0.468 346	0.069 235	0.073 120	0.074 352	0.073 229	0.061 104	0.035 349	0.012 234	0.003 290
DCP 9	.250	0.209	0.376 347	0.036 2	0.036 235	0.014 119	0.006 20	0.001 37	0.002 222	0.004 85	0.004 213
DCP10	.300	0.213	0.327 348	0.023 350	0.021 227	0.007 98	0.004 30	0.001 245	0.002 200	0.002 61	0.003 202
DCP11	.399	0.191	0.265 1	0.012 6	0.013 252	0.004 140	0.004 103	0.001 82	0.003 209	0.002 95	0.004 4
DCP12	.501	0.147	0.199 6	0.007 15	0.008 261	0.002 205	0.003 110	0.003 266	0.001 161	0.002 242	0.005 6
DCP13	.600	0.163	0.145 15	0.005 357	0.007 253	0.001 178	0.002 131	0.001 142	0.001 174	0.003 225	0.006 45
DCP14	.701	0.253	0.094 24	0.007 14	0.006 263	0.001 195	0.004 138	0.001 91	0.003 227	0.002 226	0.004 57
DCP15	.800	0.088	0.062 48	0.002 45	0.002 274	0.002 284	0.003 150	0.001 286	0.001 216	0.001 131	0.004 100
DCP16	.900	-0.126	0.026 110	0.005 157	0.003 319	0.000 232	0.002 276	0.001 214	0.004 189	0.002 80	0.003 115
DCP17	.969	-0.057	0.030 174	0.003 159	0.002 103	0.001 137	0.004 103	0.001 179	0.002 350	0.007 277	0.000 63

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.97	0.153	0.700	3.12	0.0	2.42	12149.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
228.8	129176.	0.10E 08	-0.030	0.806	5.44	-0.00089	1.670	0.0
(750.8)	(2697.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.421	3.122 0	0.134 332	0.129 170	0.037 79	0.012 322	0.013 125	0.008 11	0.009 167	0.011 256
CN		0.477	0.336 344	0.005 245	0.008 139	0.006 22	0.005 218	0.002 347	0.003 170	0.002 314	0.003 157
CM		-0.007	0.022 285	0.002 64	0.001 302	0.001 122	0.000 68	0.000 151	0.000 320	0.000 116	0.000 199
DCP 1	.010	0.677	1.227 328	0.116 356	0.042 98	0.002 122	0.006 78	0.004 59	0.003 215	0.003 112	0.003 117
DCP 2	.020	0.624	1.008 335	0.105 14	0.029 120	0.003 216	0.007 68	0.002 194	0.002 301	0.003 92	0.002 116
DCP 3	.030	0.745	0.848 334	0.101 15	0.021 120	0.003 199	0.006 65	0.002 121	0.002 307	0.002 30	0.002 89
DCP 4	.049	1.071	0.775 334	0.104 17	0.023 130	0.004 280	0.007 59	0.005 166	0.005 314	0.004 16	0.002 113
DCP 5	.074	1.213	0.703 334	0.077 13	0.021 135	0.010 156	0.007 169	0.003 173	0.002 271	0.004 11	0.004 106
DCP 6	.099	1.349	0.707 334	0.105 22	0.036 121	0.004 248	0.012 45	0.009 116	0.006 241	0.007 19	0.007 114
DCP 7	.149	1.247	0.619 332	0.130 32	0.053 218	0.067 327	0.036 73	0.036 225	0.038 325	0.023 85	0.026 212
DCP 8	.200	0.955	0.776 336	0.025 84	0.126 264	0.022 33	0.081 200	0.034 290	0.050 131	0.040 211	0.025 59
DCP 9	.250	0.974	0.866 331	0.180 185	0.102 297	0.146 110	0.332 220	0.096 34	0.025 224	0.053 319	0.033 179
DCP10	.300	0.731	0.614 340	0.246 207	0.126 34	0.048 42	0.053 292	0.006 149	0.019 195	0.011 52	0.007 170
DCP11	.399	0.453	0.262 8	0.051 223	0.078 77	0.046 294	0.008 169	0.012 230	0.014 108	0.004 321	0.002 350
DCP12	.501	0.303	0.156 35	0.044 2	0.006 186	0.009 261	0.005 162	0.003 18	0.001 226	0.003 239	0.001 47
DCP13	.600	0.277	0.124 42	0.037 6	0.014 225	0.002 192	0.000 308	0.001 186	0.001 204	0.002 265	0.002 348
DCP14	.701	0.325	0.066 51	0.021 0	0.010 208	0.001 86	0.000 225	0.001 161	0.001 81	0.002 292	0.001 237
DCP15	.800	0.125	0.050 53	0.003 0	0.005 216	0.004 317	0.002 260	0.001 62	0.002 16	0.001 296	0.002 146
DCP16	.900	-0.123	0.009 48	0.003 166	0.005 145	0.004 0	0.002 142	0.003 264	0.002 270	0.000 59	0.002 151
DCP17	.969	-0.076	0.018 190	0.005 195	0.005 161	0.004 293	0.001 329	0.003 348	0.002 189	0.003 354	0.002 347

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	69.11	0.154	0.699	2.97	0.0	4.96	12149.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
228.2	128716	0.10E 08	-0.044	1.075	8.07	-0.00094	1.742	0.0
(748.6)	(2688.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		4.957	2.969	0	0.333	7	0.095	176	0.052	115	0.017	24	0.010	226	0.002	313	0.015	147	0.008	285
CN		0.712	0.333	6	0.028	317	0.010	182	0.001	139	0.006	289	0.000	304	0.003	15	0.004	279	0.003	177
CM		-0.005	0.029	236	0.018	48	0.002	285	0.002	237	0.003	100	0.002	353	0.002	243	0.002	97	0.000	356
DCP 1	.010	1.673	1.058	337	0.127	30	0.012	36	0.013	111	0.002	112	0.004	297	0.001	25	0.007	250	0.005	143
DCP 2	.020	1.472	0.917	344	0.062	32	0.028	118	0.014	147	0.010	98	0.004	324	0.004	10	0.005	302	0.002	167
DCP 3	.030	1.473	0.782	343	0.032	22	0.036	117	0.012	148	0.013	83	0.004	319	0.005	7	0.006	268	0.002	185
DCP 4	.049	1.679	0.624	344	0.056	33	0.036	108	0.007	89	0.004	74	0.004	305	0.002	195	0.003	199	0.003	162
DCP 5	.074	1.756	0.582	344	0.072	34	0.031	102	0.006	86	0.003	95	0.001	225	0.002	167	0.003	220	0.003	192
DCP 6	.099	1.880	0.524	345	0.069	37	0.018	99	0.006	46	0.002	250	0.001	239	0.002	170	0.001	208	0.001	202
DCP 7	.149	1.850	0.490	344	0.076	30	0.023	96	0.008	139	0.009	222	0.003	282	0.003	343	0.001	104	0.000	96
DCP 8	.200	1.430	0.570	354	0.207	36	0.157	130	0.078	195	0.062	268	0.022	330	0.018	3	0.005	101	0.012	18
DCP 9	.250	1.263	0.743	10	0.284	14	0.035	188	0.019	20	0.120	51	0.032	80	0.014	174	0.035	107	0.040	101
DCP10	.300	1.045	0.665	10	0.213	11	0.159	292	0.100	299	0.013	188	0.017	334	0.048	323	0.032	290	0.037	228
DCP11	.399	0.737	0.465	13	0.081	255	0.070	271	0.004	148	0.044	247	0.010	243	0.020	199	0.005	208	0.009	205
DCP12	.501	0.530	0.344	16	0.122	244	0.052	205	0.034	155	0.028	147	0.021	58	0.007	97	0.009	13	0.005	335
DCP13	.600	0.396	0.231	28	0.112	236	0.051	156	0.041	106	0.027	36	0.022	327	0.008	218	0.011	284	0.011	180
DCP14	.701	0.341	0.149	59	0.075	222	0.047	96	0.028	29	0.033	304	0.026	211	0.018	102	0.009	310	0.003	85
DCP15	.800	0.137	0.099	52	0.047	214	0.027	50	0.008	322	0.017	275	0.018	161	0.018	29	0.014	251	0.005	86
DCP16	.900	-0.106	0.054	5	0.041	202	0.020	37	0.010	354	0.020	247	0.014	130	0.011	22	0.010	248	0.003	126
DCP17	.969	-0.088	0.013	12	0.025	241	0.005	25	0.007	91	0.009	298	0.004	206	0.005	117	0.005	44	0.009	300

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	68.71	0.153	0.699	2.83	0.0	7.43	12151.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
228.7	128827.	0.10E 08	-0.084	1.202	9.59	-0.00160	2.977	0.0
(750.3)	(2690.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.431	2.833	0	0.259	40	0.058	195	0.034	130	0.014	12	0.004	156	0.013	191	0.027	151	0.007	309
CN		0.871	0.298	42	0.018	21	0.012	313	0.063	155	0.008	335	0.003	193	0.003	140	0.003	68	0.002	50
CM		-0.017	0.053	223	0.017	93	0.004	101	0.001	302	0.003	116	0.003	14	0.002	312	0.002	234	0.001	235
DCP 1	.010	2.265	0.782	353	0.145	84	0.021	261	0.013	97	0.005	110	0.006	341	0.004	109	0.006	26	0.008	246
DCP 2	.020	2.043	0.777	0	0.087	105	0.040	329	0.012	160	0.007	31	0.009	42	0.004	253	0.007	102	0.004	310
DCP 3	.030	1.981	0.719	358	0.054	116	0.040	336	0.006	149	0.012	325	0.007	69	0.005	301	0.005	50	0.003	235
DCP 4	.049	2.095	0.563	359	0.039	137	0.020	322	0.008	203	0.008	311	0.000	234	0.003	304	0.002	203	0.002	275
DCP 5	.074	2.133	0.497	0	0.034	117	0.017	296	0.013	174	0.004	331	0.002	240	0.001	268	0.001	178	0.002	276
DCP 6	.099	2.193	0.407	6	0.043	65	0.034	256	0.022	156	0.006	10	0.005	249	0.002	245	0.003	183	0.002	260
DCP 7	.149	2.053	0.289	28	0.116	24	0.056	240	0.015	142	0.009	158	0.004	95	0.002	19	0.003	256	0.003	245
DCP 8	.200	1.529	0.331	98	0.203	33	0.036	328	0.038	282	0.019	216	0.007	184	0.013	191	0.015	84	0.010	322
DCP 9	.250	1.526	0.513	101	0.051	41	0.112	41	0.038	96	0.042	332	0.039	328	0.011	205	0.031	266	0.008	197
DCP10	.300	1.294	0.470	84	0.188	117	0.063	159	0.006	334	0.040	69	0.037	64	0.023	66	0.019	342	0.004	48
DCP11	.399	0.889	0.436	46	0.113	86	0.009	78	0.037	239	0.004	95	0.005	259	0.021	318	0.027	181	0.017	52
DCP12	.501	0.655	0.442	38	0.058	26	0.037	24	0.028	101	0.021	82	0.009	140	0.009	230	0.009	147	0.005	254
DCP13	.600	0.506	0.368	39	0.078	311	0.060	346	0.019	43	0.043	0	0.017	348	0.013	314	0.009	49	0.006	79
DCP14	.701	0.421	0.256	41	0.121	271	0.042	280	0.009	200	0.040	300	0.026	232	0.018	197	0.007	115	0.013	134
DCP15	.800	0.221	0.208	30	0.101	258	0.024	248	0.016	169	0.022	248	0.027	172	0.023	106	0.019	17	0.003	233
DCP16	.900	-0.038	0.168	15	0.079	266	0.031	221	0.004	57	0.016	232	0.021	176	0.020	111	0.013	31	0.006	43
DCP17	.969	-0.064	0.056	17	0.029	273	0.018	241	0.006	58	0.012	272	0.009	204	0.017	148	0.021	68	0.016	141

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	68.80	0.153	0.699	2.88	0.0	9.94	12151.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
228.3	128659.	0.10E 08	-0.062	1.190	11.49	-0.00113	2.107	0.0
(749.1)	(2687.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		9.939	2.885	0	0.154	15	0.015	170	0.051	103	0.019	23	0.003	186	0.007	157	0.024	141	0.007	315
CN		0.944	0.211	52	0.016	43	0.025	32	0.002	28	0.002	205	0.002	254	0.004	37	0.001	180	0.001	174
CM		-0.023	0.042	216	0.005	34	0.005	177	0.002	255	0.002	6	0.001	157	0.001	219	0.000	349	0.001	327
DCP 1	.010	2.704	0.491	356	0.068	80	0.007	120	0.005	246	0.007	338	0.001	105	0.004	24	0.002	47	0.001	104
DCP 2	.020	2.449	0.531	6	0.097	80	0.009	302	0.003	220	0.001	275	0.004	159	0.004	99	0.005	32	0.007	314
DCP 3	.030	2.322	0.475	6	0.124	73	0.023	300	0.011	192	0.004	111	0.005	67	0.005	342	0.001	294	0.002	262
DCP 4	.049	2.376	0.433	5	0.064	61	0.024	311	0.010	127	0.005	118	0.002	171	0.002	332	0.002	117	0.002	338
DCP 5	.074	2.308	0.284	23	0.130	44	0.046	298	0.003	80	0.007	200	0.001	151	0.002	156	0.004	76	0.002	50
DCP 6	.099	2.248	0.210	73	0.176	38	0.026	323	0.040	349	0.024	236	0.007	188	0.010	145	0.004	42	0.001	136
DCP 7	.149	2.063	0.293	102	0.122	27	0.066	69	0.044	318	0.021	30	0.021	260	0.007	353	0.011	207	0.003	348
DCP 8	.200	1.622	0.353	112	0.046	5	0.098	94	0.017	246	0.039	43	0.007	228	0.013	356	0.010	346	0.014	270
DCP 9	.250	1.508	0.300	101	0.092	244	0.030	15	0.014	231	0.008	303	0.003	99	0.004	118	0.014	192	0.007	230
DCP10	.300	1.263	0.235	63	0.035	358	0.049	64	0.009	246	0.008	217	0.015	223	0.004	161	0.008	177	0.013	167
DCP11	.399	1.067	0.302	66	0.006	176	0.042	45	0.020	173	0.008	339	0.015	109	0.010	20	0.014	53	0.002	95
DCP12	.501	0.813	0.307	54	0.034	152	0.052	32	0.013	96	0.003	72	0.003	227	0.012	64	0.019	313	0.011	13
DCP13	.600	0.583	0.279	41	0.013	174	0.046	17	0.017	59	0.018	257	0.002	332	0.009	10	0.012	170	0.007	134
DCP14	.701	0.435	0.224	27	0.014	154	0.023	328	0.005	108	0.017	167	0.003	12	0.006	84	0.004	112	0.008	206
DCP15	.800	0.246	0.186	18	0.009	237	0.016	312	0.013	47	0.019	172	0.006	322	0.010	307	0.006	202	0.004	165
DCP16	.900	-0.029	0.121	23	0.007	317	0.009	308	0.008	25	0.007	158	0.013	344	0.005	161	0.001	23	0.007	53
DCP17	.969	-0.080	0.043	44	0.008	294	0.008	302	0.002	310	0.002	328	0.007	241	0.004	88	0.004	85	0.009	226

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.18	0.166	0.208	4.86	0.0	0.04	12001.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
70.9	12889.	0.33E 07	-0.047	0.519	4.75	-0.00137	0.793	0.0
(232.6)	(269.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		0.043	4.858	0	0.216	4	0.026	241	0.001	10	0.010	340	0.045	127	0.020	221	0.006	335	0.002	23
CN		0.134	0.396	358	0.014	27	0.003	83	0.002	111	0.002	317	0.004	193	0.004	353	0.008	285	0.004	86
CM		-0.024	0.019	296	0.003	315	0.001	315	0.000	26	0.000	136	0.001	88	0.001	235	0.002	99	0.001	265
DCP 1	.010	-0.659	2.872	346	0.178	23	0.031	82	0.011	206	0.012	279	0.018	147	0.007	252	0.018	302	0.013	346
DCP 2	.020	-0.439	2.082	349	0.081	347	0.011	65	0.008	244	0.009	232	0.023	160	0.009	256	0.014	276	0.003	66
DCP 3	.030	0.008	1.749	349	0.059	334	0.001	123	0.002	210	0.003	249	0.017	144	0.003	9	0.008	265	0.004	55
DCP 4	.049	-0.036	1.411	350	0.049	342	0.005	14	0.004	107	0.007	260	0.010	185	0.010	334	0.004	313	0.010	119
DCP 5	.074	0.177	1.143	350	0.041	347	0.010	349	0.005	64	0.003	279	0.014	178	0.005	357	0.007	277	0.012	89
DCP 6	.099	0.394	0.976	352	0.032	358	0.010	356	0.012	68	0.001	136	0.007	208	0.010	359	0.010	273	0.007	141
DCP 7	.149	0.201	0.730	353	0.032	18	0.012	7	0.012	36	0.012	314	0.009	133	0.014	311	0.007	273	0.013	75
DCP 8	.200	0.228	0.592	357	0.025	3	0.010	86	0.007	173	0.005	79	0.007	193	0.011	358	0.008	315	0.002	31
DCP 9	.250	0.148	0.517	357	0.024	23	0.006	9	0.010	100	0.004	332	0.007	236	0.009	322	0.007	333	0.003	356
DCP10	.300	0.230	0.437	358	0.020	23	0.006	146	0.006	107	0.004	228	0.007	155	0.003	53	0.004	9	0.007	76
DCP11	.399	0.244	0.353	5	0.016	45	0.007	222	0.003	149	0.007	322	0.007	162	0.008	318	0.017	266	0.006	60
DCP12	.501	0.133	0.264	11	0.008	46	0.008	108	0.005	180	0.004	6	0.002	114	0.005	31	0.011	272	0.003	184
DCP13	.600	0.156	0.201	16	0.007	84	0.011	127	0.002	40	0.004	120	0.006	183	0.006	295	0.013	302	0.005	177
DCP14	.701	0.205	0.150	20	0.014	108	0.003	64	0.006	103	0.012	352	0.005	237	0.006	162	0.010	300	0.005	73
DCP15	.800	0.113	0.096	29	0.012	119	0.002	213	0.003	307	0.005	318	0.004	280	0.003	88	0.012	293	0.011	48
DCP16	.900	-0.072	0.022	81	0.009	121	0.007	8	0.008	263	0.007	194	0.004	230	0.010	45	0.013	185	0.003	219
DCP17	.969	0.027	0.022	166	0.009	276	0.003	218	0.006	117	0.006	194	0.013	297	0.008	24	0.009	25	0.011	8

139

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.21	0.172	0.202	4.87	0.0	2.47	12001.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
68.6	12209.	0.32E 07	-0.040	0.779	7.40	-0.00146	0.820	0.0
(225.0)	(255.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.469	4.868 0	0.226 4	0.043 266	0.002 246	0.015 37	0.012 88	0.031 195	0.011 134	0.004 26
CN		0.361	0.407 358	0.017 18	0.004 351	0.002 14	0.001 118	0.002 287	0.004 197	0.014 131	0.001 50
CM		-0.017	0.020 293	0.001 290	0.001 143	0.000 109	0.000 117	0.001 110	0.001 349	0.005 319	0.002 216
DCP 1	.010	0.964	2.750 346	0.127 10	0.015 10	0.010 318	0.002 91	0.006 345	0.011 139	0.012 43	0.017 184
DCP 2	.020	0.724	2.153 349	0.088 3	0.027 340	0.008 316	0.007 136	0.006 29	0.001 238	0.018 70	0.011 162
DCP 3	.030	0.989	1.019 349	0.066 355	0.027 336	0.008 355	0.006 172	0.005 206	0.005 163	0.016 56	0.011 225
DCP 4	.049	0.801	1.471 349	0.049 340	0.005 19	0.002 10	0.003 352	0.009 174	0.006 332	0.017 83	0.008 198
DCP 5	.074	0.860	1.178 350	0.042 353	0.009 26	0.003 17	0.000 140	0.004 200	0.004 17	0.011 104	0.006 213
DCP 6	.099	0.964	1.001 351	0.038 3	0.006 55	0.006 44	0.005 72	0.002 235	0.003 216	0.016 106	0.003 291
DCP 7	.149	0.661	0.766 352	0.034 11	0.006 67	0.007 353	0.015 84	0.003 87	0.003 36	0.003 355	0.003 45
DCP 8	.200	0.578	0.623 357	0.020 23	0.003 113	0.005 168	0.008 237	0.008 154	0.005 59	0.005 45	0.012 180
DCP 9	.250	0.427	0.529 357	0.024 19	0.007 357	0.009 331	0.007 55	0.007 30	0.005 197	0.022 105	0.002 331
DCP10	.300	0.494	0.445 358	0.023 15	0.006 7	0.002 286	0.006 160	0.008 43	0.006 87	0.009 143	0.003 289
DCP11	.399	0.450	0.355 7	0.020 31	0.007 319	0.009 112	0.009 251	0.008 331	0.008 161	0.023 144	0.002 148
DCP12	.501	0.272	0.280 11	0.016 28	0.003 316	0.004 113	0.004 20	0.007 196	0.009 158	0.015 170	0.003 63
DCP13	.600	0.259	0.211 16	0.013 34	0.012 326	0.009 17	0.001 215	0.013 240	0.003 146	0.013 167	0.005 323
DCP14	.701	0.270	0.152 21	0.015 35	0.007 107	0.005 24	0.003 131	0.006 338	0.016 169	0.021 129	0.003 94
DCP15	.800	0.141	0.095 29	0.008 87	0.002 297	0.004 238	0.005 290	0.003 45	0.003 159	0.021 124	0.003 346
DCP16	.900	-0.059	0.033 65	0.011 157	0.005 263	0.009 298	0.007 11	0.011 295	0.005 265	0.024 128	0.016 50
DCP17	.969	-0.008	0.030 161	0.008 257	0.009 21	0.010 183	0.011 152	0.010 287	0.006 130	0.015 141	0.008 29

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.21	0.174	0.199	4.87	0.0	4.97	12001.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
67.8	11913.	0.32E 07	-0.035	1.013	9.78	-0.00149	0.830	0.0
(222.4)	(248.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.975	4.873 0	0.226 5	0.040 265	0.004 270	0.016 40	0.006 22	0.027 185	0.004 96	0.005 18
CN		0.600	0.412 358	0.019 14	0.004 87	0.002 39	0.003 349	0.001 290	0.003 32	0.008 11	0.004 216
CM		-0.011	0.020 294	0.002 257	0.001 296	0.001 195	0.001 227	0.000 65	0.001 246	0.002 219	0.001 47
DCP 1	.010	2.621	2.807 346	0.124 321	0.044 137	0.025 72	0.011 284	0.009 58	0.015 302	0.017 307	0.014 180
DCP 2	.020	1.975	2.176 349	0.090 355	0.008 56	0.002 50	0.008 280	0.002 72	0.016 318	0.024 339	0.015 235
DCP 3	.030	2.022	1.856 349	0.083 357	0.007 353	0.007 79	0.001 24	0.002 342	0.009 314	0.019 342	0.004 188
DCP 4	.049	1.497	1.518 349	0.066 355	0.002 321	0.006 72	0.002 233	0.002 307	0.001 139	0.010 349	0.002 121
DCP 5	.074	1.584	1.203 350	0.054 357	0.009 35	0.008 137	0.012 343	0.005 215	0.006 224	0.014 329	0.001 322
DCP 6	.099	1.548	1.012 352	0.042 3	0.007 345	0.007 114	0.007 347	0.004 211	0.006 216	0.013 323	0.006 81
DCP 7	.149	1.093	0.769 353	0.028 351	0.013 358	0.002 139	0.009 354	0.004 25	0.009 235	0.019 315	0.003 117
DCP 8	.200	0.921	0.638 358	0.026 2	0.009 126	0.007 236	0.002 170	0.003 115	0.011 301	0.013 22	0.010 205
DCP 9	.250	0.734	0.534 358	0.021 13	0.008 73	0.006 225	0.011 273	0.004 134	0.007 336	0.011 35	0.010 225
DCP10	.300	0.748	0.448 359	0.017 37	0.004 10	0.001 147	0.005 211	0.002 229	0.008 65	0.008 349	0.007 172
DCP11	.399	0.653	0.365 7	0.021 50	0.006 141	0.006 67	0.004 239	0.009 1	0.009 11	0.011 51	0.006 245
DCP12	.501	0.431	0.276 10	0.021 37	0.007 84	0.004 302	0.004 359	0.004 302	0.008 67	0.006 40	0.002 172
DCP13	.600	0.362	0.208 17	0.019 29	0.006 133	0.001 339	0.010 22	0.006 270	0.005 71	0.017 20	0.001 73
DCP14	.701	0.354	0.141 26	0.019 24	0.011 39	0.005 39	0.011 5	0.002 335	0.007 44	0.003 31	0.009 327
DCP15	.800	0.189	0.089 39	0.009 50	0.002 304	0.004 313	0.005 8	0.002 205	0.004 78	0.011 20	0.008 235
DCP16	.900	-0.037	0.040 35	0.004 238	0.012 135	0.017 45	0.008 170	0.008 135	0.002 297	0.003 22	0.007 183
DCP17	.969	-0.013	0.010 135	0.005 213	0.008 149	0.004 326	0.007 95	0.007 266	0.012 93	0.006 45	0.019 208

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.13	0.175	0.199	4.87	0.0	7.47	12001.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
67.5	11826.	0.32E 07	-0.041	1.225	12.29	-0.00171	0.943	0.0
(221.4)	(247.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.474	4.873	0	0.220	6	0.041	260	0.002	237	0.018	50	0.005	344	0.026	193	0.003	76	0.003	6
CN		0.433	0.401	0	0.017	31	0.006	117	0.004	312	0.001	268	0.003	245	0.002	291	0.011	343	0.005	107
CM		-0.008	0.022	290	0.003	332	0.004	316	0.002	107	0.000	225	0.001	32	0.001	141	0.005	178	0.002	282
DCP 1	.010	4.008	2.412	344	.282	46	0.189	331	0.080	228	0.054	283	0.063	207	0.033	147	0.021	195	0.033	78
DCP 2	.020	3.213	2.115	35.	0.093	358	0.008	357	0.012	228	0.015	303	0.006	247	0.008	213	0.020	221	0.007	68
DCP 3	.030	3.055	1.816	350	0.074	351	0.008	71	0.011	230	0.011	313	0.007	209	0.008	244	0.012	218	0.010	192
DCP 4	.049	2.579	1.499	350	0.070	2	0.011	5	0.014	65	0.002	201	0.007	13	0.008	210	0.013	230	0.007	230
DCP 5	.074	2.281	1.182	351	0.051	0	0.010	29	0.007	71	0.004	252	0.005	334	0.005	172	0.012	268	0.003	173
DCP 6	.099	2.107	0.998	352	0.046	358	0.009	33	0.006	100	0.001	256	0.005	6	0.006	208	0.015	276	0.002	46
DCP 7	.149	1.526	0.767	354	0.038	10	0.002	251	0.019	33	0.009	10	0.005	188	0.005	194	0.010	238	0.002	114
DCP 8	.200	1.276	0.621	359	0.030	14	0.004	284	0.005	9	0.004	264	0.008	331	0.004	22	0.011	262	0.003	316
DCP 9	.250	1.045	0.535	359	0.021	38	0.013	92	0.012	10	0.009	106	0.002	191	0.003	49	0.013	350	0.004	94
DCP10	.300	1.000	0.435	1	0.022	14	0.008	186	0.009	316	0.007	206	0.006	278	0.006	221	0.010	355	0.005	225
DCP11	.399	0.854	0.356	9	0.014	53	0.015	137	0.001	21	0.007	208	0.008	246	0.002	336	0.010	352	0.011	132
DCP12	.501	0.584	0.269	13	0.012	46	0.013	115	0.006	333	0.008	246	0.007	255	0.008	340	0.013	347	0.003	126
DCP13	.600	0.465	0.213	19	0.015	80	0.014	132	0.004	145	0.005	229	0.011	268	0.008	314	0.021	359	0.009	25
DCP14	.701	0.430	0.141	34	0.014	92	0.009	105	0.012	274	0.004	36	0.006	118	0.003	91	0.017	39	0.009	127
DCP15	.800	0.236	0.094	45	0.006	85	0.018	111	0.008	312	0.006	174	0.004	352	0.009	180	0.016	338	0.004	32
DCP16	.900	-0.015	0.051	52	0.012	179	0.011	183	0.015	265	0.011	33	0.010	191	0.020	326	0.027	341	0.021	126
DCP17	.969	-0.009	0.010	85	0.007	222	0.013	144	0.005	52	0.011	3	0.005	73	0.002	183	0.015	357	0.012	73

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.24	0.175	0.199	4.87	0.0	9.95	12001.5	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
67.5	11879.	0.32E 07	-0.026	1.419	14.87	-0.00170	0.941	0.0
(221.6)	(248.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		9.945	4.867	0	0.231	7	0.037	270	0.004	273	0.022	58	0.007	352	0.028	199	0.017	172	0.006	14
CN		1.027	0.378	4	0.031	19	0.004	9	0.004	357	0.002	227	0.006	17	0.005	213	0.016	194	0.002	75
CM		0.000	0.023	293	0.003	228	0.001	171	0.001	122	0.001	41	0.001	212	0.001	40	0.005	30	0.001	239
DCP 1	.010	5.216	2.133	348	0.210	32	0.122	151	0.160	44	0.032	127	0.106	27	0.016	79	0.039	43	0.024	347
DCP 2	.020	4.312	2.040	352	0.094	359	0.021	334	0.009	2	0.007	180	0.010	2	0.013	156	0.023	163	0.008	47
DCP 3	.030	3.984	1.772	351	0.081	346	0.023	320	0.013	11	0.002	59	0.006	330	0.010	157	0.018	151	0.005	231
DCP 4	.049	3.355	1.431	353	0.093	359	0.004	212	0.010	52	0.007	32	0.003	42	0.007	254	0.016	166	0.002	289
DCP 5	.074	2.892	1.133	354	0.073	358	0.006	243	0.002	330	0.002	7	0.005	5	0.003	287	0.020	152	0.003	99
DCP 6	.099	2.598	0.950	355	0.055	5	0.001	62	0.005	44	0.003	218	0.002	69	0.004	222	0.021	136	0.001	216
DCP 7	.149	1.912	0.723	357	0.041	7	0.005	105	0.010	246	0.012	56	0.007	323	0.004	218	0.015	152	0.005	356
DCP 8	.200	1.587	0.602	2	0.030	1	0.001	90	0.006	64	0.003	264	0.004	5	0.009	193	0.024	189	0.010	323
DCP 9	.250	1.312	0.511	2	0.029	21	0.015	15	0.003	206	0.006	246	0.007	261	0.007	188	0.013	212	0.009	113
DCP10	.300	1.210	0.412	4	0.031	22	0.004	37	0.004	279	0.007	292	0.006	305	0.006	295	0.015	190	0.008	130
DCP11	.399	1.007	0.329	13	0.038	33	0.003	354	0.006	317	0.004	246	0.006	31	0.007	256	0.018	181	0.012	181
DCP12	.501	0.713	0.250	19	0.029	32	0.008	4	0.005	352	0.004	238	0.009	8	0.005	219	0.018	216	0.007	68
DCP13	.600	0.537	0.167	27	0.026	29	0.011	8	0.001	265	0.002	116	0.009	39	0.010	145	0.017	228	0.006	62
DCP14	.701	0.474	0.133	42	0.027	32	0.007	338	0.010	328	0.009	221	0.004	122	0.006	196	0.021	209	0.004	269
DCP15	.800	0.254	0.093	55	0.019	36	0.003	40	0.005	353	0.002	224	0.006	37	0.006	146	0.021	204	0.003	1
DCP16	.900	-0.002	0.057	32	0.003	60	0.003	329	0.008	100	0.003	34	0.001	116	0.015	260	0.014	180	0.011	67
DCP17	.969	-0.013	0.012	63	0.007	317	0.004	263	0.011	279	0.007	187	0.019	9	0.006	255	0.019	212	0.005	334

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.11	0.167	0.206	4.84	0.0	12.47	12003.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
70.5	12736.	0.33E 07	-0.107	1.611	17.30	-0.00011	0.064	0.0
(231.3)	(266.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.473	4.838 0	0.253 5	0.044 237	0.008 53	0.015 357	0.024 124	0.031 218	0.008 198	0.003 54
CN		1.122	0.465 30	0.086 268	0.041 87	0.017 311	0.011 172	0.005 17	0.003 307	0.002 278	0.007 103
CM		-0.027	0.024 182	0.036 0	0.020 217	0.006 89	0.003 332	0.002 180	0.000 303	0.002 35	0.002 286
DCP 1	.010	5.132	1.647 37	0.777 357	0.401 228	0.147 188	0.195 148	0.065 349	0.120 236	0.036 191	0.024 44
DCP 2	.020	4.313	1.767 32	0.634 345	0.218 223	0.051 148	0.077 99	0.061 351	0.059 259	0.022 121	0.044 69
DCP 3	.030	4.199	1.685 28	0.586 326	0.283 188	0.152 56	0.065 290	0.030 225	0.016 137	0.023 8	0.010 23
DCP 4	.049	3.065	1.142 51	0.643 3	0.246 260	0.080 173	0.047 129	0.040 62	0.042 326	0.026 293	0.022 138
DCP 5	.074	2.673	1.022 49	0.525 347	0.208 229	0.058 110	0.017 89	0.022 30	0.026 307	0.010 357	0.002 352
DCP 6	.099	2.565	0.948 45	0.428 333	0.172 199	0.058 74	0.013 57	0.026 339	0.021 253	0.014 20	0.004 141
DCP 7	.149	1.979	0.839 33	0.301 296	0.155 149	0.057 11	0.011 28	0.024 270	0.008 113	0.029 36	0.009 44
DCP 8	.200	1.777	0.794 24	0.269 269	0.161 122	0.074 358	0.021 285	0.021 214	0.010 126	0.018 7	0.005 321
DCP 9	.250	1.535	0.702 19	0.211 246	0.141 93	0.059 339	0.028 283	0.043 181	0.029 69	0.019 349	0.017 240
DCP10	.300	1.349	0.590 19	0.175 235	0.129 72	0.060 305	0.031 226	0.012 118	0.012 14	0.004 290	0.006 196
DCP11	.399	1.132	0.479 24	0.149 221	0.109 62	0.052 294	0.026 187	0.017 80	0.013 322	0.013 231	0.022 100
DCP12	.501	0.857	0.388 24	0.138 213	0.100 55	0.033 288	0.025 187	0.015 78	0.011 295	0.007 202	0.014 105
DCP13	.600	0.726	0.306 29	0.118 204	0.081 47	0.023 272	0.016 194	0.015 60	0.008 337	0.010 204	0.006 86
DCP14	.701	0.550	0.219 38	0.105 192	0.065 37	0.022 241	0.015 139	0.022 356	0.005 81	0.006 191	0.017 85
DCP15	.800	0.333	0.146 24	0.097 176	0.052 11	0.014 221	0.016 117	0.016 336	0.005 127	0.007 221	0.007 100
DCP16	.900	0.078	0.116 2	0.060 164	0.023 38	0.008 280	0.021 107	0.004 299	0.007 139	0.006 209	0.009 148
DCP17	.969	0.034	0.065 347	0.033 160	0.018 19	0.009 282	0.006 284	0.018 281	0.018 228	0.008 331	0.006 301

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	22.97	0.172	0.200	4.82	0.0	14.95	12003.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
68.0	11989.	0.32E 07	-0.320	2.216	19.75	0.00094	-0.526	0.0
(223.1)	(250.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		14.954	4.817 0	0.258 13	0.045 288	0.036 253	0.040 109	0.041 347	0.013 181	0.010 133	0.005 234
CN		1.277	0.574 44	0.196 307	0.119 207	0.087 110	0.056 18	0.036 284	0.019 192	0.028 57	0.006 340
CM		-0.052	0.087 176	0.063 52	0.039 333	0.031 241	0.019 147	0.015 49	0.007 326	0.011 235	0.006 138
DCP 1	.010	4.952	2.052 112	1.094 28	0.283 30	0.415 337	0.220 331	0.205 281	0.159 206	0.134 142	0.087 100
DCP 2	.020	4.235	1.854 93	1.015 25	0.157 353	0.150 320	0.073 318	0.120 276	0.111 213	0.102 141	0.078 100
DCP 3	.030	4.167	1.739 84	1.027 17	0.305 310	0.246 253	0.147 159	0.065 92	0.056 49	0.064 348	0.036 288
DCP 4	.049	3.449	1.203 83	0.787 32	0.317 308	0.111 211	0.047 49	0.068 284	0.058 178	0.037 82	0.033 66
DCP 5	.074	3.033	1.144 76	0.686 12	0.278 280	0.118 194	0.036 100	0.011 274	0.026 132	0.038 54	0.026 23
DCP 6	.099	2.853	1.097 70	0.603 357	0.241 263	0.126 194	0.072 115	0.023 48	0.027 94	0.033 39	0.019 351
DCP 7	.149	2.196	0.992 58	0.487 337	0.221 255	0.168 189	0.094 109	0.048 28	0.029 75	0.051 14	0.045 306
DCP 8	.200	1.958	0.916 49	0.415 330	0.245 257	0.195 183	0.097 112	0.050 55	0.030 42	0.074 12	0.037 291
DCP 9	.250	1.713	0.842 39	0.350 311	0.251 236	0.226 151	0.144 76	0.108 10	0.050 303	0.067 307	0.067 209
DCP10	.300	1.574	0.769 35	0.321 299	0.238 223	0.220 136	0.140 52	0.099 345	0.071 279	0.048 251	0.044 155
DCP11	.399	1.345	0.710 33	0.307 285	0.224 210	0.208 121	0.145 42	0.111 330	0.079 256	0.036 173	0.062 120
DCP12	.501	1.029	0.616 28	0.270 269	0.201 192	0.194 100	0.124 13	0.090 295	0.056 224	0.055 135	0.038 78
DCP13	.600	0.864	0.530 24	0.267 252	0.179 170	0.170 78	0.126 348	0.098 264	0.068 182	0.069 89	0.036 20
DCP14	.701	0.687	0.418 19	0.257 238	0.184 151	0.162 53	0.106 319	0.100 221	0.058 133	0.072 67	0.056 332
DCP15	.800	0.442	0.325 7	0.215 230	0.158 137	0.129 31	0.096 298	0.088 196	0.051 99	0.079 30	0.047 279
DCP16	.900	0.149	0.223 3	0.092 227	0.088 136	0.066 14	0.053 281	0.044 196	0.031 130	0.051 25	0.038 299
DCP17	.969	0.066	0.110 350	0.047 254	0.034 125	0.025 39	0.014 286	0.029 199	0.025 33	0.027 21	0.011 310

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	22.96	0.174	0.197	4.81	0.0	17.44	12003.3	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	67.1	11702.	0.32E 07	-0.409	2.446	21.61	0.00045	-0.250	0.0
	(220.1)	(244.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		17.441	4.808 0	0.212 11	0.013 278	0.046 0	0.046 264	0.057 120	0.033 183	0.007 33	0.015 307
CN		1.320	0.647 55	0.106 345	0.111 303	0.129 235	0.099 143	0.048 56	0.016 328	0.015 211	0.008 265
CM		-0.078	0.125 180	0.005 99	0.044 17	0.041 351	0.036 270	0.021 115	0.008 124	0.006 73	0.005 47
DCP 1	.010	4.473	2.591 121	0.510 99	0.692 71	0.176 107	0.231 96	0.256 88	0.171 36	0.140 9	0.115 351
DCP 2	.020	3.987	2.345 110	0.606 83	0.559 55	0.150 332	0.031 214	0.114 105	0.062 65	0.043 34	0.039 25
DCP 3	.030	3.936	2.120 106	0.706 68	0.615 46	0.359 335	0.171 299	0.102 271	0.098 246	0.131 212	0.093 173
DCP 4	.049	3.421	1.565 109	0.806 60	0.317 21	0.233 325	0.145 235	0.098 99	0.050 334	0.031 218	0.029 280
DCP 5	.074	3.008	1.391 99	0.622 48	0.230 16	0.286 311	0.152 224	0.037 103	0.035 281	0.041 217	0.035 209
DCP 6	.099	2.810	1.273 90	0.491 41	0.355 10	0.307 297	0.140 222	0.016 165	0.036 254	0.071 208	0.062 169
DCP 7	.149	2.208	1.142 73	0.362 70	0.359 350	0.278 282	0.148 217	0.032 161	0.062 243	0.079 193	0.047 142
DCP 8	.200	1.980	1.012 66	0.368 25	0.332 346	0.284 290	0.169 229	0.045 195	0.064 230	0.087 194	0.044 144
DCP 9	.250	1.747	0.931 56	0.328 5	0.303 321	0.294 263	0.217 201	0.105 155	0.061 142	0.100 129	0.056 56
DCP10	.300	1.624	0.844 48	0.307 353	0.258 308	0.274 252	0.225 177	0.093 127	0.070 111	0.091 79	0.065 13
DCP11	.399	1.439	0.799 43	0.300 339	0.246 291	0.265 244	0.235 166	0.133 110	0.090 77	0.057 45	0.084 351
DCP12	.501	1.137	0.730 34	0.279 316	0.213 266	0.233 216	0.217 137	0.131 76	0.080 24	0.047 341	0.076 297
DCP13	.600	0.948	0.686 27	0.293 297	0.218 239	0.214 189	0.216 113	0.139 41	0.089 342	0.060 290	0.072 258
DCP14	.701	0.774	0.585 20	0.266 281	0.182 223	0.204 171	0.201 87	0.145 9	0.091 304	0.079 245	0.058 195
DCP15	.800	0.527	0.429 10	0.201 276	0.129 214	0.152 162	0.154 71	0.118 345	0.076 280	0.072 227	0.064 162
DCP16	.900	0.245	0.293 0	0.153 270	0.070 203	0.099 145	0.102 47	0.076 318	0.029 215	0.014 171	0.022 167
DCP17	.949	0.127	0.184 359	0.121 276	0.070 191	0.075 101	0.068 23	0.057 292	0.057 188	0.035 105	0.039 10

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	23.23	0.175	0.199	4.80	0.0	19.94	12003.4	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	67.5	11865.	0.32E 07	-0.383	2.220	22.92	-0.00230	1.275	0.0
	(221.4)	(247.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		19.944	4.796 0	0.205 12	0.025 224	0.029 80	0.061 11	0.044 245	0.022 212	0.012 89	0.003 356
CN		1.280	0.605 60	0.091 39	0.106 21	0.115 318	0.088 242	0.033 167	0.028 77	0.010 329	0.004 322
CM		-0.106	0.126 194	0.044 138	0.032 128	0.035 76	0.027 11	0.017 299	0.012 259	0.004 225	0.003 236
DCP 1	.010	3.335	1.803 113	0.739 140	0.282 145	0.128 167	0.214 231	0.212 189	0.139 157	0.093 152	0.087 137
DCP 2	.020	3.100	1.755 107	0.619 134	0.248 112	0.116 38	0.123 286	0.117 226	0.054 187	0.074 188	0.073 189
DCP 3	.030	3.147	1.589 108	0.606 124	0.387 91	0.259 46	0.096 11	0.040 347	0.078 33	0.054 0	0.031 327
DCP 4	.049	3.096	1.509 123	0.516 105	0.378 106	0.255 38	0.039 335	0.016 341	0.046 45	0.041 326	0.030 299
DCP 5	.074	2.725	1.263 110	0.353 103	0.336 88	0.234 20	0.072 331	0.035 314	0.052 33	0.042 332	0.029 335
DCP 6	.099	2.515	1.092 98	0.306 103	0.301 73	0.233 13	0.098 325	0.040 321	0.069 16	0.046 337	0.036 350
DCP 7	.149	2.012	0.931 78	0.310 94	0.249 57	0.250 13	0.106 307	0.016 304	0.060 16	0.038 349	0.056 328
DCP 8	.200	1.841	0.833 73	0.252 80	0.250 55	0.242 17	0.126 310	0.038 308	0.052 7	0.048 343	0.048 318
DCP 9	.250	1.674	0.769 66	0.197 56	0.234 36	0.239 350	0.173 290	0.068 272	0.040 317	0.052 277	0.061 271
DCP10	.300	1.596	0.742 59	0.180 34	0.220 25	0.238 336	0.195 273	0.105 246	0.049 241	0.054 255	0.036 216
DCP11	.399	1.445	0.737 52	0.161 10	0.179 17	0.219 325	0.195 266	0.094 234	0.049 197	0.049 227	0.049 187
DCP12	.501	1.176	0.697 42	0.144 354	0.153 354	0.184 302	0.175 241	0.092 187	0.067 147	0.031 193	0.038 150
DCP13	.600	0.997	0.701 34	0.108 338	0.144 329	0.191 277	0.175 213	0.113 155	0.084 109	0.030 101	0.029 98
DCP14	.701	0.855	0.619 26	0.191 323	0.142 309	0.184 253	0.163 188	0.117 125	0.091 80	0.040 45	0.052 33
DCP15	.800	0.617	0.476 22	0.126 317	0.120 308	0.140 248	0.123 175	0.113 107	0.097 63	0.064 16	0.053 337
DCP16	.900	0.308	0.304 21	0.076 298	0.064 291	0.066 234	0.062 141	0.062 65	0.037 26	0.020 47	0.014 78
DCP17	.949	0.136	0.186 23	0.077 295	0.057 249	0.068 188	0.061 112	0.057 38	0.048 332	0.018 242	0.021 176

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
3.0	45.86	0.333	0.205	5.21	3.3	3.38	12035.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
70.2	12669.	0.33E 07	-0.076	0.491	5.30	-3.33146	0.073	0.0
(230.3)	(264.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.075	5.208 0	0.284 3	0.066 326	0.028 189	0.036 104	0.025 65	0.015 217	0.030 267	0.011 161
CN		0.143	0.358 16	0.025 48	0.008 72	0.021 61	0.012 288	0.032 322	0.036 273	0.009 254	0.003 142
CM		-0.026	0.040 289	0.004 282	0.003 286	0.012 233	0.003 126	0.002 138	0.002 163	0.004 36	0.001 303
DCP 1	.013	-0.587	2.609 346	0.167 14	0.021 47	0.075 193	0.006 223	0.015 186	0.029 217	0.013 51	0.006 166
DCP 2	.020	-0.437	1.890 152	0.075 353	0.016 345	0.373 211	0.009 239	0.015 209	0.015 217	0.026 8	0.008 221
DCP 3	.033	0.015	1.597 152	0.373 344	0.023 342	0.338 223	0.013 221	0.009 298	0.009 254	0.013 343	0.008 171
DCP 4	.049	-0.061	1.284 353	0.064 0	0.028 325	0.038 202	0.018 266	0.014 36	0.013 139	0.006 327	0.006 256
DCP 5	.074	0.159	1.030 355	0.054 2	0.013 20	0.033 213	0.007 272	0.006 203	0.003 131	0.012 7	0.004 177
DCP 6	.099	0.395	0.883 358	0.044 22	0.011 67	0.031 193	0.014 285	0.032 329	0.037 135	0.012 330	0.004 25
DCP 7	.149	0.213	0.661 4	0.051 30	0.014 29	0.030 193	0.009 298	0.016 126	0.003 61	0.015 316	0.007 152
DCP 8	.200	0.223	0.534 12	0.036 45	0.012 8	0.027 221	0.001 232	0.007 365	0.010 77	0.003 228	
DCP 9	.253	0.175	0.489 13	0.027 33	0.021 63	0.022 31	0.023 270	0.005 115	0.006 26	0.012 354	0.005 151
DCP10	.300	0.220	0.402 16	0.033 64	0.006 66	0.031 41	0.009 284	0.013 105	0.009 231	0.012 292	0.013 87
DCP11	.399	0.259	0.341 13	0.031 92	0.007 90	0.042 52	0.015 260	0.035 343	0.008 332	0.027 295	0.008 127
DCP12	.501	0.144	0.293 43	0.032 56	0.003 129	0.027 48	0.013 272	0.006 272	0.035 332	0.026 255	0.004 214
DCP13	.600	0.187	0.244 51	0.028 46	0.017 61	0.031 69	0.011 254	0.008 291	0.026 264	0.019 246	0.004 43
DCP14	.701	0.221	0.187 59	0.012 128	0.017 138	0.042 52	0.022 319	0.005 301	0.012 292	0.031 186	0.009 240
DCP15	.800	0.118	0.136 71	0.016 98	0.014 119	0.038 59	0.022 296	0.011 11	0.003 16	0.017 153	0.006 205
DCP16	.903	-0.074	0.081 95	0.017 67	0.014 77	0.052 43	0.011 295	0.013 321	0.019 336	0.005 193	0.008 106
DCP17	.969	0.023	0.036 136	0.003 120	0.004 16	0.043 58	0.017 15	0.011 206	0.013 236	0.023 267	0.014 58

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
3.0	46.00	0.344	0.200	5.20	0.0	2.48	12005.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
68.2	12051.	0.32E 07	-0.066	0.698	7.70	-0.00142	0.828	0.0
(223.6)	(251.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.484	5.204 0	0.288 2	0.081 319	0.019 260	0.038 108	0.029 62	0.023 194	0.025 246	0.013 157
CN		0.363	0.365 15	0.024 47	0.011 65	0.022 8	0.001 256	0.001 159	0.001 223	0.010 170	0.005 236
CM		-0.020	0.039 290	0.005 300	0.003 291	0.011 198	0.001 256	0.001 159	0.001 30	0.003 310	0.003 71
DCP 1	.010	0.957	2.499 346	0.159 1	0.031 14	0.043 218	0.015 257	0.010 227	0.009 357	0.034 218	0.013 40
DCP 2	.020	0.686	1.962 352	0.109 3	0.044 352	0.053 227	0.003 153	0.009 228	0.008 178	0.034 253	0.015 61
DCP 3	.030	0.968	1.646 352	0.086 3	0.036 354	0.040 230	0.012 138	0.008 197	0.003 205	0.026 248	0.006 46
DCP 4	.049	0.733	1.323 354	0.074 349	0.031 14	0.032 216	0.003 231	0.004 305	0.010 209	0.016 199	0.011 89
DCP 5	.074	0.814	1.088 355	0.061 8	0.025 354	0.023 207	0.009 146	0.015 193	0.007 51	0.010 151	0.007 9
DCP 6	.099	0.957	0.897 358	0.057 19	0.028 12	0.031 219	0.008 211	0.015 176	0.001 206	0.022 125	0.010 71
DCP 7	.149	0.625	0.680 2	0.036 10	0.014 44	0.027 215	0.013 43	0.006 197	0.013 18	0.006 304	0.014 53
DCP 8	.200	0.557	0.557 12	0.032 38	0.018 97	0.025 221	0.009 270	0.008 284	0.007 207	0.022 278	0.008 69
DCP 9	.250	0.455	0.485 13	0.031 22	0.010 49	0.038 356	0.008 261	0.009 88	0.004 337	0.024 256	0.009 111
DCP10	.300	0.485	0.421 16	0.035 27	0.024 67	0.031 354	0.016 241	0.009 183	0.002 49	0.018 212	0.015 233
DCP11	.399	0.450	0.354 31	0.028 63	0.017 89	0.040 19	0.011 223	0.014 139	0.014 30	0.017 170	0.011 187
DCP12	.501	0.284	0.284 41	0.032 74	0.007 97	0.042 32	0.007 258	0.011 88	0.012 205	0.018 161	0.012 203
DCP13	.600	0.291	0.236 53	0.037 90	0.010 77	0.042 19	0.008 321	0.010 54	0.009 82	0.029 133	0.012 252
DCP14	.701	0.292	0.201 59	0.026 102	0.011 74	0.044 20	0.013 77	0.007 310	0.010 289	0.021 146	0.016 260
DCP15	.800	0.145	0.140 73	0.020 99	0.016 87	0.036 20	0.002 7	0.014 325	0.008 242	0.013 98	0.014 244
DCP16	.900	-0.067	0.066 90	0.010 225	0.010 153	0.039 349	0.012 101	0.013 231	0.011 207	0.014 15	0.004 246
DCP17	.969	0.010	0.016 151	0.007 126	0.003 109	0.026 34	0.015 29	0.008 21	0.012 156	0.017 221	0.009 286

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	46.05	0.349	0.198	5.20	0.0	5.01	12005.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
67.2	11745.	0.32E 07	-0.062	0.960	10.26	-0.00147	0.843	0.0
(220.5)	(245.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		5.006	5.199	0	0.293	3	0.090	308	0.019	190	0.036	96	0.027	63	0.019	215	0.021	244	0.009	140
CN		0.587	0.366	16	0.022	41	0.008	55	0.018	119	0.005	281	0.005	20	0.004	29	0.009	146	0.003	198
CM		-0.012	0.042	292	0.003	297	0.001	311	0.007	337	0.001	106	0.002	182	0.002	212	0.004	292	0.001	15
DCP 1	.010	2.542	2.519	347	0.116	335	0.022	116	0.071	40	0.016	183	0.013	2	0.007	237	0.016	225	0.005	80
DCP 2	.020	1.886	1.942	352	0.108	5	0.019	38	0.072	47	0.013	183	0.024	63	0.019	271	0.014	224	0.004	176
DCP 3	.030	1.998	1.655	352	0.091	5	0.018	359	0.046	47	0.012	186	0.019	30	0.012	262	0.005	325	0.006	182
DCP 4	.049	1.593	1.360	354	0.069	12	0.028	350	0.035	27	0.008	186	0.004	305	0.009	269	0.015	265	0.014	280
DCP 5	.074	1.500	1.079	356	0.063	9	0.016	6	0.039	31	0.004	241	0.005	67	0.003	88	0.009	134	0.002	331
DCP 6	.099	1.518	0.910	359	0.056	16	0.027	33	0.030	32	0.011	178	0.015	356	0.005	137	0.015	95	0.002	338
DCP 7	.149	1.052	0.676	3	0.040	22	0.016	31	0.027	44	0.008	206	0.006	103	0.007	98	0.010	235	0.011	172
DCP 8	.200	0.914	0.577	11	0.035	66	0.020	12	0.041	38	0.009	52	0.009	117	0.007	294	0.009	69	0.014	242
DCP 9	.250	0.746	0.494	13	0.026	32	0.015	50	0.029	129	0.017	260	0.009	149	0.005	136	0.022	235	0.012	144
DCP10	.300	0.731	0.425	19	0.030	33	0.023	54	0.015	121	0.011	344	0.005	93	0.016	355	0.019	200	0.007	68
DCP11	.399	0.656	0.351	34	0.033	62	0.010	55	0.028	136	0.010	339	0.002	103	0.019	66	0.021	230	0.006	16
DCP12	.501	0.418	0.295	42	0.029	84	0.006	82	0.021	168	0.024	254	0.007	345	0.005	225	0.015	173	0.007	230
DCP13	.600	0.375	0.247	52	0.014	49	0.003	24	0.030	148	0.013	273	0.019	356	0.010	52	0.013	147	0.013	218
DCP14	.701	0.353	0.189	61	0.014	56	0.014	153	0.017	160	0.016	284	0.007	318	0.009	315	0.031	103	0.013	183
DCP15	.800	0.173	0.142	78	0.013	102	0.002	140	0.025	142	0.003	255	0.003	159	0.011	19	0.022	77	0.003	27
DCP16	.900	-0.051	0.084	101	0.003	118	0.013	137	0.039	134	0.003	117	0.008	13	0.003	167	0.024	74	0.013	147
DCP17	.969	-0.015	0.031	155	0.010	263	0.012	14	0.024	181	0.006	118	0.017	27	0.015	40	0.026	190	0.022	337

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.99	0.352	0.196	5.20	0.0	7.51	12005.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
66.5	11558.	0.32E 07	-0.069	1.218	12.78	-0.00153	0.672	0.0
(218.3)	(241.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.509	5.200	0	0.305	3	0.088	305	0.014	108	0.040	98	0.026	52	0.025	217	0.022	270	0.010	129
CN		0.823	0.363	18	0.030	44	0.008	44	0.040	113	0.005	293	0.009	313	0.005	234	0.010	224	0.001	154
CM		-0.008	0.043	291	0.004	281	0.003	293	0.012	305	0.001	174	0.003	140	0.001	51	0.003	357	0.000	216
DCP 1	.010	3.974	2.255	346	0.258	39	0.202	330	0.042	223	0.030	252	0.070	191	0.035	129	0.018	122	0.016	108
DCP 2	.020	3.127	1.931	353	0.111	358	0.035	359	0.034	80	0.018	273	0.013	215	0.020	222	0.012	27	0.020	236
DCP 3	.030	3.026	1.674	353	0.094	354	0.026	12	0.029	93	0.002	271	0.008	152	0.018	254	0.014	6	0.011	213
DCP 4	.049	2.480	1.362	355	0.077	5	0.023	11	0.034	62	0.010	226	0.007	339	0.003	320	0.009	314	0.010	242
DCP 5	.074	2.219	1.092	356	0.069	7	0.018	342	0.037	86	0.013	281	0.011	306	0.010	281	0.013	254	0.010	231
DCP 6	.099	2.094	0.912	0	0.063	21	0.016	332	0.045	74	0.003	178	0.010	307	0.009	265	0.018	281	0.016	255
DCP 7	.149	1.492	0.700	2	0.051	23	0.012	22	0.031	57	0.005	10	0.006	225	0.014	199	0.017	280	0.005	32
DCP 8	.200	1.252	0.568	13	0.035	37	0.015	48	0.034	92	0.015	290	0.007	192	0.003	340	0.010	95	0.017	236
DCP 9	.250	1.043	0.486	15	0.041	32	0.008	156	0.039	102	0.009	249	0.017	304	0.012	232	0.027	319	0.007	107
DCP10	.300	0.991	0.418	18	0.035	46	0.020	6	0.040	95	0.011	220	0.009	49	0.005	283	0.021	270	0.012	354
DCP11	.399	0.861	0.354	37	0.039	63	0.003	88	0.056	132	0.011	321	0.009	335	0.004	260	0.026	270	0.013	85
DCP12	.501	0.580	0.284	44	0.034	74	0.011	62	0.043	121	0.011	0	0.019	327	0.007	265	0.026	220	0.011	143
DCP13	.600	0.481	0.245	55	0.022	82	0.008	26	0.052	114	0.012	255	0.029	324	0.007	197	0.039	211	0.009	130
DCP14	.701	0.437	0.202	67	0.021	57	0.021	105	0.039	135	0.006	333	0.007	322	0.005	76	0.028	172	0.008	226
DCP15	.800	0.217	0.149	82	0.017	99	0.016	69	0.087	124	0.009	322	0.016	258	0.004	189	0.024	126	0.005	81
DCP16	.900	-0.024	0.084	88	0.012	41	0.013	160	0.070	117	0.012	127	0.016	309	0.009	210	0.018	111	0.013	11
DCP17	.969	-0.021	0.000	115	0.005	18	0.011	120	0.036	125	0.005	50	0.014	50	0.018	270	0.024	317	0.018	285

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ 0.0	DRIVE HZ 46.03	K 0.353	MACH NO 0.196	DEL.ALPHA 5.20	DEL.H 0.0	ALPHA.0 10.01	TEST POINT 12005.5	CYCLES ANALYSED 20
V 66.4 (217.8)	Q 11515. (240.5)	RN 0.32E 07	CN(MIN) -0.060	CN(MAX) 1.408	ALPHA.NMAX 15.18	AERO DAMP -0.00159	TDR 0.905	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		10.007	5.200 0	0.281 7	0.101 300	0.035 102	0.032 91	0.023 75	0.032 241	0.012 216	0.008 216
CN		1.029	0.354 20	0.033 47	0.006 35	0.046 134	0.004 294	0.001 353	0.006 322	0.009 21	0.001 196
CM		-0.001	0.044 290	0.004 293	0.000 207	0.013 329	0.002 137	0.000 129	0.002 143	0.004 177	0.001 357
DCP 1	.010	5.217	1.956 347	3.246 31	0.109 139	0.186 52	0.066 112	0.099 14	0.022 42	0.021 338	0.004 192
DCP 2	.020	4.278	1.802 354	0.113 13	0.031 323	0.076 100	0.023 173	0.019 49	0.009 193	0.020 138	0.002 127
DCP 3	.030	4.000	1.649 353	0.090 4	0.033 321	0.040 103	0.012 138	0.003 46	0.004 242	0.014 100	0.010 189
DCP 4	.049	3.294	1.331 356	0.087 13	0.026 26	0.036 111	0.007 249	0.001 337	0.008 186	0.009 100	0.006 206
DCP 5	.074	2.856	1.057 358	0.078 18	0.015 15	0.036 106	0.010 162	0.008 288	0.001 229	0.007 29	0.004 354
DCP 6	.399	2.606	0.888 0	0.075 28	0.019 3	0.043 106	0.008 223	0.009 300	0.003 205	0.010 282	0.003 189
DCP 7	.149	1.910	0.669 5	0.062 27	0.013 4	0.035 135	0.007 341	0.004 252	0.002 116	0.020 6	0.008 313
DCP 8	.200	1.503	0.567 16	0.043 48	0.013 20	0.032 116	0.010 162	0.004 20	0.002 76	0.012 142	0.011 125
DCP 9	.250	1.323	0.491 17	0.032 42	0.009 18	0.057 128	0.010 231	0.006 61	0.013 304	0.011 173	0.008 155
DCP10	.300	1.203	0.401 21	0.045 31	0.012 355	0.053 128	0.009 203	0.010 230	0.005 355	0.013 123	0.010 359
DCP11	.399	1.027	0.346 38	0.032 59	0.014 51	0.054 136	0.013 270	0.008 143	0.002 17	0.012 82	0.009 322
DCP12	.501	0.710	0.286 44	0.037 75	0.009 56	0.049 149	0.005 354	0.004 188	0.015 322	0.015 35	0.007 273
DCP13	.600	0.562	0.237 58	0.032 81	0.003 63	0.052 144	0.009 41	0.007 161	0.006 297	0.017 36	0.008 146
DCP14	.701	0.482	0.203 71	0.025 84	0.008 87	0.055 145	0.008 311	0.004 167	0.014 313	0.014 1	0.015 174
DCP15	.800	0.248	0.157 79	0.018 90	0.002 148	0.054 139	0.012 297	0.007 157	0.009 344	0.015 5	0.005 143
DCP16	.900	-0.009	0.086 87	0.009 125	0.006 186	0.049 154	0.008 46	0.019 3	0.013 344	0.045 326	0.003 299
DCP17	.969	-0.017	0.039 104	0.004 1	0.008 324	0.037 139	0.020 276	0.016 305	0.007 244	0.013 124	0.009 0

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ 0.0	DRIVE HZ 46.03	K 0.353	MACH NO 0.196	DEL.ALPHA 5.20	DEL.H 0.0	ALPHA.0 12.48	TEST POINT 12005.6	CYCLES ANALYSED 20
V 66.4 (218.0)	Q 11550. (241.4)	RN 0.32E 07	CN(MIN) -0.040	CN(MAX) 1.571	ALPHA.NMAX 17.74	AERO DAMP -0.00121	TDR 0.689	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.470	5.195 0	0.304 2	0.079 297	0.031 74	0.037 85	0.016 57	0.030 223	0.012 271	0.007 115
CN		1.163	0.410 20	0.034 85	0.006 54	0.036 102	0.007 293	0.002 264	0.007 263	0.007 252	0.005 108
CM		-0.002	0.031 283	0.016 281	0.001 76	0.000 204	0.002 161	0.001 183	0.002 118	0.003 57	0.002 285
DCP 1	.010	5.719	1.580 13	0.675 336	0.354 181	0.135 131	0.024 270	0.110 177	0.030 181	0.038 162	0.017 253
DCP 2	.020	4.097	1.726 7	0.376 347	0.126 184	0.115 74	0.039 275	0.005 185	0.008 270	0.021 123	0.006 303
DCP 3	.030	4.710	1.697 357	0.093 347	0.038 47	0.016 123	0.015 111	0.005 298	0.012 179	0.017 124	0.005 150
DCP 4	.049	3.693	1.383 13	0.251 318	0.111 149	0.009 54	0.043 237	0.019 130	0.014 219	0.010 100	0.016 39
DCP 5	.074	3.169	1.154 14	0.183 300	0.110 121	0.061 14	0.034 200	0.010 116	0.007 251	0.014 68	0.011 358
DCP 6	.099	2.865	0.999 15	0.130 285	0.104 93	0.028 9	0.035 178	0.010 19	0.012 234	0.015 28	0.014 2
DCP 7	.149	2.165	0.819 12	0.063 215	0.092 52	0.014 215	0.015 126	0.003 315	0.020 205	0.026 12	0.010 162
DCP 8	.200	1.879	0.727 7	0.122 165	0.103 25	0.046 184	0.021 120	0.027 204	0.020 165	0.007 169	0.004 330
DCP 9	.250	1.575	0.568 4	0.140 118	0.100 338	0.067 122	0.019 357	0.025 283	0.010 195	0.037 348	0.021 171
DCP10	.300	1.401	0.463 8	0.116 104	0.076 303	0.071 115	0.036 323	0.021 244	0.009 243	0.019 197	0.006 128
DCP11	.399	1.173	0.374 27	0.101 99	0.036 275	0.070 98	0.036 298	0.014 95	0.016 333	0.030 269	0.008 175
DCP12	.501	0.798	0.303 37	0.079 91	0.014 249	0.042 84	0.014 231	0.006 75	0.012 305	0.017 261	0.011 71
DCP13	.600	0.604	0.265 48	0.071 98	0.009 245	0.039 88	0.002 231	0.006 18	0.005 316	0.020 276	0.010 90
DCP14	.701	0.496	0.220 64	0.059 82	0.015 147	0.031 110	0.007 279	0.004 251	0.007 298	0.035 208	0.005 130
DCP15	.800	0.293	0.155 70	0.034 93	0.015 148	0.021 123	0.013 5	0.009 95	0.018 254	0.015 170	0.007 66
DCP16	.900	0.009	0.080 71	0.020 68	0.023 83	0.035 92	0.010 7	0.010 307	0.010 19	0.014 115	0.012 115
DCP17	.969	-0.012	0.035 36	0.011 68	0.007 162	0.031 113	0.008 27	0.005 288	0.020 260	0.035 340	0.008 253

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	46.19	0.351	0.198	5.20	0.0	15.02	12005.7	20

V	Q	RN	C(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
67.1	11779.	0.32E 07	-0.206	1.808	19.60	0.00170	-0.972	0.0
(220.1)	(246.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		15.024	5.196	0	0.311	354	0.039	288	0.038	194	0.026	80	0.013	49	0.019	193	0.010	136	0.010	186
CN		1.225	0.621	5	0.155	147	0.053	342	0.027	286	0.021	355	0.025	195	0.015	41	0.014	269	0.009	308
CM		-0.032	0.054	105	0.065	285	0.031	111	0.003	11	0.009	191	0.005	351	0.005	182	0.008	37	0.002	195
DCP 1	.010	4.694	2.152	58	0.563	354	0.422	333	0.445	241	0.198	204	0.143	106	0.077	339	0.107	309	0.026	233
DCP 2	.020	4.192	2.207	43	0.427	327	0.183	2	0.178	250	0.076	179	0.101	106	0.063	8	0.043	299	0.012	169
DCP 3	.030	4.069	2.181	36	0.569	300	0.104	164	0.102	94	0.144	322	0.106	183	0.049	85	0.062	358	0.063	244
DCP 4	.049	3.520	1.792	33	0.510	302	0.169	168	0.062	84	0.078	29	0.072	270	0.054	165	0.025	31	0.004	207
DCP 5	.074	3.083	1.638	28	0.447	275	0.162	137	0.071	66	0.098	352	0.081	240	0.039	132	0.022	51	0.033	0
DCP 6	.099	2.808	1.486	24	0.361	253	0.114	123	0.097	76	0.125	335	0.083	220	0.047	121	0.036	26	0.020	315
DCP 7	.149	2.257	1.362	12	0.380	220	0.116	117	0.138	38	0.097	302	0.086	216	0.061	112	0.040	44	0.055	319
DCP 8	.200	1.971	1.230	7	0.360	210	0.141	118	0.130	23	0.087	306	0.077	199	0.045	90	0.048	26	0.030	312
DCP 9	.250	1.713	1.072	356	0.390	176	0.183	71	0.188	327	0.116	227	0.076	134	0.062	41	0.058	324	0.042	228
DCP10	.300	1.560	0.920	351	0.400	162	0.197	45	0.187	292	0.083	164	0.064	106	0.067	338	0.029	247	0.020	172
DCP11	.399	1.321	0.742	351	0.408	150	0.211	19	0.166	268	0.086	139	0.062	16	0.038	260	0.029	238	0.036	11
DCP12	.501	0.934	0.529	348	0.352	130	0.162	346	0.136	225	0.109	83	0.075	288	0.015	178	0.012	82	0.025	308
DCP13	.600	0.711	0.376	344	0.306	114	0.169	322	0.087	205	0.099	53	0.079	256	0.035	108	0.057	315	0.019	186
DCP14	.701	0.572	0.257	328	0.289	95	0.177	282	0.071	137	0.099	348	0.061	184	0.048	43	0.065	246	0.021	87
DCP15	.800	0.358	0.168	300	0.215	87	0.175	264	0.070	62	0.072	323	0.048	147	0.044	349	0.063	205	0.026	18
DCP16	.900	0.108	0.069	301	0.124	75	0.100	243	0.066	41	0.045	298	0.054	106	0.023	326	0.045	161	0.011	289
DCP17	.969	.044	0.034	285	0.062	73	0.051	241	0.031	339	0.019	321	0.006	201	0.009	46	0.003	198	0.016	298

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	46.05	0.348	0.199	5.17	0.0	17.50	12005.8	20

V	Q	RN	C(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
67.3	11874.	0.32E 07	-0.351	2.143	22.67	0.00381	-2.189	0.0
(220.8)	(248.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		17.501	5.173	0	0.340	353	0.086	237	0.062	214	0.030	70	0.014	47	0.026	195	0.006	112	0.006	104
CN		1.330	0.751	15	0.182	215	0.060	79	0.040	194	0.026	88	0.015	329	0.010	282	0.005	299	0.005	187
CM		-0.079	0.127	122	0.093	323	0.034	190	0.014	75	0.008	341	0.003	181	0.005	39	0.003	225	0.000	75
DCP 1	.010	4.407	2.628	85	0.600	355	0.366	9	0.081	81	0.284	347	0.158	297	0.152	222	0.124	150	0.074	100
DCP 2	.020	3.986	2.625	71	0.731	346	0.219	315	0.279	180	0.096	70	0.096	9	0.098	300	0.102	225	0.090	160
DCP 3	.030	3.828	2.423	67	0.785	345	0.332	310	0.379	210	0.148	142	0.159	119	0.177	41	0.132	339	0.114	275
DCP 4	.049	3.393	2.148	60	0.813	328	0.272	262	0.330	193	0.200	123	0.101	50	0.084	20	0.078	306	0.042	245
DCP 5	.074	3.005	1.880	53	0.656	314	0.268	248	0.291	177	0.184	105	0.116	36	0.091	2	0.097	278	0.049	201
DCP 6	.099	2.771	1.691	47	0.539	303	0.225	234	0.262	168	0.173	100	0.106	18	0.080	348	0.088	265	0.049	190
DCP 7	.149	2.250	1.553	34	0.552	284	0.279	203	0.228	144	0.182	72	0.095	334	0.074	315	0.067	236	0.025	152
DCP 8	.200	1.988	1.450	29	0.570	276	0.304	185	0.215	146	0.187	56	0.092	315	0.067	303	0.080	189	0.042	145
DCP 9	.250	1.757	1.335	18	0.589	253	0.303	150	0.230	90	0.267	5	0.184	275	0.105	214	0.098	133	0.077	63
DCP10	.300	1.612	1.171	12	0.535	254	0.346	121	0.166	41	0.101	331	0.143	231	0.075	163	0.077	66	0.018	38
DCP11	.399	1.466	1.041	5	0.542	218	0.407	106	0.204	8	0.158	275	0.113	175	0.058	113	0.070	29	0.060	313
DCP12	.501	1.169	0.910	350	0.544	193	0.383	73	0.238	321	0.188	210	0.098	104	0.058	37	0.080	301	0.045	213
DCP13	.600	0.948	0.721	334	0.495	164	0.307	35	0.215	275	0.170	162	0.106	50	0.059	318	0.053	222	0.025	121
DCP14	.701	0.758	0.523	318	0.452	133	0.273	352	0.199	223	0.133	103	0.070	334	0.069	251	0.023	87	0.021	33
DCP15	.800	0.513	0.348	302	0.332	117	0.196	322	0.148	198	0.125	69	0.066	279	0.029	162	0.008	245	0.027	40
DCP16	.900	0.244	0.203	297	0.205	96	0.138	287	0.084	158	0.025	47	0.032	301	0.033	192	0.027	10	0.037	207
DCP17	.969	0.152	0.178	284	0.199	85	0.156	270	0.109	102	0.080	258	0.066	64	0.064	258	0.056		0.021	

147

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.98	0.347	0.199	5.14	0.0	19.91	12005.9	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
67.5	11956.	0.32E 07	-0.386	2.295	25.15	0.00338	-1.950	0.0
(221.6)	(249.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		19.910	5.138 0	0.362 359	0.097 257	0.069 276	0.036 76	0.012 88	0.028 189	0.015 286	0.003 72
CN		1.386	0.751 27	0.204 276	0.062 249	0.050 246	0.007 243	0.017 157	0.008 28	0.011 194	0.011 359
CM		-0.116	0.141 142	0.084 5	0.028 256	0.007 154	0.015 125	0.008 345	0.008 142	0.010 21	0.004 195
DCP 1	.010	3.769	2.339 95	0.715 41	0.230 58	0.069 149	0.130 94	0.134 50	0.124 11	0.113 335	0.098 301
DCP 2	.020	3.590	2.309 85	0.802 23	0.200 342	0.240 257	0.121 180	0.060 141	0.062 07	0.062 81	0.061 17
DCP 3	.030	3.535	2.125 85	0.757 19	0.334 0	0.308 283	0.153 246	0.136 202	0.119 175	0.122 143	0.083 96
DCP 4	.049	3.170	2.039 79	0.729 7	0.241 343	0.360 275	0.161 224	0.089 173	0.099 150	0.070 98	0.013 88
DCP 5	.074	2.853	1.795 68	0.675 354	0.229 313	0.338 264	0.204 200	0.097 160	0.129 132	0.097 91	0.031 67
DCP 6	.099	2.641	1.597 60	0.632 343	0.205 297	0.307 254	0.182 196	0.090 161	0.127 109	0.095 70	0.034 28
DCP 7	.149	2.167	1.402 48	0.630 330	0.206 260	0.251 235	0.170 157	0.073 132	0.088 63	0.050 29	0.042 6
DCP 8	.200	2.034	1.385 44	0.716 326	0.295 255	0.259 229	0.202 149	0.109 104	0.100 72	0.070 9	0.007 348
DCP 9	.250	1.852	1.203 34	0.709 316	0.340 216	0.304 178	0.239 96	0.153 37	0.147 356	0.099 304	0.070 270
DCP10	.300	1.729	1.136 27	0.634 288	0.346 191	0.250 145	0.191 50	0.101 344	0.075 286	0.049 240	0.049 226
DCP11	.399	1.598	1.064 19	0.621 273	0.406 173	0.328 101	0.185 13	0.121 303	0.062 235	0.051 226	0.054 149
DCP12	.501	1.280	0.936 4	0.540 242	0.392 139	0.209 40	0.166 328	0.096 247	0.067 175	0.062 168	0.033 41
DCP13	.600	1.052	0.702 348	0.456 210	0.333 100	0.203 346	0.150 265	0.078 192	0.041 94	0.021 282	0.025 284
DCP14	.701	0.875	0.587 337	0.394 181	0.257 63	0.219 303	0.117 205	0.053 117	0.008 331	0.017 274	0.013 230
DCP15	.800	0.628	0.385 332	0.263 161	0.182 40	0.187 276	0.060 165	0.043 70	0.024 273	0.029 117	0.009 109
DCP16	.900	0.371	0.302 312	0.262 130	0.181 322	0.104 171	0.075 299	0.081 137	0.092 335	0.086 172	0.069 13
DCP17	.949	0.238	0.280 301	0.277 121	0.233 320	0.164 168	0.132 344	0.110 177	0.092 7	0.077 226	0.037 19

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.67	0.483	0.212	5.91	0.0	0.02	12007.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
72.4	13606.	0.34E 07	-0.086	0.552	4.12	-0.00119	0.758	0.0
(237.4)	(280.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.015	5.906 0	0.507 344	0.136 196	0.066 132	0.026 123	0.016 109	0.023 251	0.016 72	0.017 68
CN		0.141	0.357 34	0.036 54	0.022 294	0.001 176	0.015 262	0.000 146	0.003 184	0.006 155	0.001 295
CM		-0.023	0.058 295	0.008 310	0.006 134	0.002 182	0.005 85	0.001 117	0.002 350	0.002 327	0.000 93
DCP 1	.010	-0.534	2.494 348	0.240 1	0.049 131	0.007 165	0.025 155	0.014 92	0.011 304	0.001 182	0.011 251
DCP 2	.020	-0.337	1.791 358	0.168 356	0.011 217	0.026 229	0.019 221	0.009 143	0.016 316	0.014 123	0.010 251
DCP 3	.030	0.049	1.492 358	0.124 349	0.025 231	0.006 163	0.020 193	0.009 231	0.013 76	0.014 141	0.008 203
DCP 4	.049	-0.023	1.218 1	0.094 2	0.018 228	0.003 241	0.016 179	0.003 139	0.001 53	0.009 227	0.004 124
DCP 5	.074	0.160	0.987 3	0.085 5	0.020 249	0.019 159	0.006 231	0.004 167	0.008 295	0.003 156	0.009 172
DCP 6	.099	0.370	0.850 8	0.079 15	0.030 280	0.025 156	0.010 208	0.007 327	0.007 131	0.010 253
DCP 7	.149	0.236	0.655 15	0.073 32	0.022 272	0.011 131	0.014 275	0.019 107	0.015 255	0.007 357	0.010 39
DCP 8	.200	0.252	0.562 27	0.077 42	0.026 291	0.018 272	0.011 272	0.006 1	0.012 121	0.008 245	0.022 190
DCP 9	.250	0.195	0.491 30	0.052 43	0.034 293	0.020 203	0.011 192	0.011 149	0.012 87	0.014 123	0.007 187
DCP10	.300	0.211	0.420 36	0.042 43	0.017 258	0.013 212	0.014 237	0.000 257	0.004 220	0.010 161	0.010 347
DCP11	.399	0.228	0.398 56	0.043 65	0.029 292	0.007 232	0.023 292	0.010 298	0.010 272	0.006 188	0.019 72
DCP12	.501	0.141	0.356 65	0.044 78	0.027 289	0.008 77	0.019 270	0.006 47	0.009 320	0.010 314	0.009 3
DCP13	.600	0.209	0.319 73	0.057 85	0.030 300	0.014 78	0.031 273	0.011 39	0.013 21	0.025 175	0.020 298
DCP14	.701	0.181	0.257 79	0.031 122	0.023 305	0.011 36	0.012 253	0.005 255	0.017 132	0.011 83	0.008 192
DCP15	.800	0.097	0.192 95	0.030 116	0.018 326	0.007 1F	0.015 269	0.012 230	0.016 167	0.014 125	0.010 87
DCP16	.900	-0.073	0.103 108	0.029 127	0.030 294	0.025 31?	0.016 238	0.015 206	0.016 215	0.010 245	0.015 295
DCP17	.949	0.010	0.061 153	0.035 261	0.032 3	0.018 17?	0.021 255	0.027 28	0.016 160	0.024 121	0.024 164

	TUNED HZ 0.0	DRIVE HZ 68.58	K 0.499	MACH NO 0.205	DEL.ALPHA 5.95	DEL.M 0.0	ALPHA.0 2.52	TEST POINT 12007.2	CYCLES ANALYSED 20
	V 50.0 (229.4)	Q 12654. (264.3)	RN 0.33E 07	CN(MIN) -0.088	CN(MAX) 0.759	ALPHA.NMAX 6.64	AERO DAMP -0.00123	TDR 0.757	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.520	5.946 0	0.511 345	0.150 189	0.072 136	0.006 129	0.019 14	0.016 227	0.025 123	0.002 123
CN		0.365	0.356 36	0.048 63	0.011 310	0.006 286	0.006 239	0.008 42	0.003 63	0.004 157	0.003 101
CM		-0.020	0.062 300	0.012 301	0.005 171	0.004 158	0.002 92	0.003 257	0.001 90	0.001 268	0.001 314
DCP 1	.010	0.957	2.371 349	0.238 356	0.064 180	0.019 134	0.028 185	0.008 0	0.018 324	0.012 300	0.021 60
DCP 2	.020	0.756	1.840 358	0.177 3	0.028 228	0.015 226	0.034 184	0.017 353	0.021 45	0.007 132	0.010 16
DCP 3	.030	0.974	1.535 358	0.152 359	0.025 265	0.009 257	0.014 167	0.008 247	0.007 181	0.018 96	0.011 4
DCP 4	.049	0.762	1.284 1	0.116 359	0.023 241	0.019 223	0.018 184	0.016 294	0.028 84	0.013 264	0.010 186
DCP 5	.074	0.812	1.018 4	0.103 8	0.032 222	0.020 176	0.016 248	0.017 313	0.011 58	0.015 193	0.002 264
DCP 6	.099	0.934	0.860 9	0.095 12	0.026 239	0.010 192	0.018 225	0.015 310	0.019 49	0.021 241	0.008 177
DCP 7	.149	0.645	0.656 16	0.083 32	0.027 201	0.012 233	0.010 241	0.014 344	0.019 97	0.008 161	0.015 281
DCP 8	.200	0.581	0.559 29	0.068 38	0.026 259	0.013 237	0.008 94	0.025 7	0.007 34	0.009 60	0.025 71
DCP 9	.250	0.473	0.508 28	0.068 45	0.005 9	0.012 223	0.013 213	0.009 339	0.012 188	0.021 177	0.011 333
DCP10	.300	0.471	0.459 33	0.063 53	0.018 280	0.013 213	0.007 9	0.002 49	0.015 149	0.005 217	0.012 100
DCP11	.399	0.425	0.399 54	0.064 75	0.011 353	0.016 260	0.006 176	0.006 312	0.010 16	0.007 157	0.007 96
DCP12	.501	0.277	0.359 67	0.069 87	0.015 345	0.008 241	0.008 55	0.012 96	0.001 35	0.006 350	0.010 155
DCP13	.600	0.322	0.311 77	0.061 108	0.013 352	0.005 357	0.004 175	0.021 84	0.011 1	0.014 219	0.006 117
DCP14	.701	0.277	0.271 88	0.062 92	0.025 339	0.015 27	0.026 276	0.021 77	0.002 342	0.009 118	0.003 343
DCP15	.800	0.147	0.220 102	0.043 127	0.025 336	0.01: 352	0.034 249	0.016 45	0.006 74	0.013 56	0.038 327
DCP16	.900	-0.051	0.129 127	0.034 102	0.015 356	0.029 341	0.006 188	0.013 70	0.007 328	0.012 169	0.026 176
DCP17	.969	0.007	0.051 169	0.025 202	0.010 344	0.022 286	0.010 291	0.012 248	0.032 222	0.022 26	0.025 18

	TUNED HZ 0.0	DRIVE HZ 68.48	K 0.511	MACH NO 0.201	DEL.ALPHA 5.93	DEL.M 0.0	ALPHA.0 5.05	TEST POINT 12007.3	CYCLES ANALYSED 20
	V 68.3 (224.0)	Q 12099. (252.7)	RN 0.32E 07	CN(MIN) -0.082	CN(MAX) 1.019	ALPHA.NMAX 8.71	AERO DAMP -0.00128	TDR 0.772	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		5.053	5.929 0	0.519 345	0.149 185	0.065 136	0.021 349	0.024 28	0.017 188	0.023 129	0.011 112
CN		0.593	0.372 36	0.050 61	0.021 347	0.011 257	0.003 312	0.004 359	0.005 263	0.004 195	0.002 43
CM		-0.015	0.063 299	0.013 288	0.008 193	0.004 116	0.001 253	0.001 197	0.001 82	0.001 14	0.001 252
DCP 1	.010	2.538	2.450 349	0.218 327	0.092 179	0.037 86	0.032 226	0.014 73	0.021 303	0.011 172	0.012 325
DCP 2	.020	1.940	1.893 358	0.168 4	0.031 226	0.012 105	0.018 231	0.002 176	0.009 314	0.012 27	0.019 10
DCP 3	.030	1.977	1.608 358	0.137 3	0.023 222	0.018 113	0.023 235	0.008 92	0.012 333	0.006 26	0.006 349
DCP 4	.049	1.606	1.321 1	0.112 359	0.024 235	0.022 175	0.017 274	0.004 299	0.009 102	0.006 344	0.012 241
DCP 5	.074	1.483	1.044 4	0.101 4	0.024 237	0.021 187	0.018 265	0.009 93	0.011 26	0.007 104	0.003 160
DCP 6	.099	1.481	0.885 10	0.088 14	0.028 288	0.019 182	0.009 291	0.006 282	0.005 21	0.005 322	0.004 281
DCP 7	.149	1.071	0.697 17	0.082 32	0.014 292	0.013 229	0.010 262	0.015 292	0.017 231	0.001 148	0.005 134
DCP 8	.200	0.916	0.593 29	0.067 44	0.039 293	0.019 236	0.017 313	0.009 297	0.013 163	0.007 264	0.011 57
DCP 9	.250	0.753	0.512 32	0.077 51	0.021 313	0.017 156	0.018 312	0.005 101	0.015 224	0.009 179	0.011 195
DCP10	.300	0.718	0.463 37	0.062 42	0.020 321	0.013 247	0.002 201	0.012 49	0.009 341	0.025 162	0.015 298
DCP11	.399	0.635	0.426 56	0.063 74	0.028 348	0.024 284	0.011 16	0.002 259	0.004 129	0.012 219	0.009 49
DCP12	.501	0.431	0.369 67	0.069 89	0.044 359	0.020 259	0.006 251	0.011 324	0.007 334	0.006 284	0.003 222
DCP13	.600	0.417	0.326 78	0.074 87	0.040 4	0.026 240	0.005 155	0.010 295	0.017 254	0.007 349	0.015 317
DCP14	.701	0.362	0.270 86	0.062 89	0.021 11	0.021 282	0.010 39	0.001 4	0.011 297	0.003 209	0.021 77
DCP15	.800	0.182	0.216 101	0.044 98	0.026 7	0.010 254	0.011 39	0.005 108	0.013 257	0.011 62	0.003 251
DCP16	.900	-0.031	0.130 121	0.026 121	0.032 352	0.015 5	0.012 8	0.026 58	0.011 127	0.014 232	0.030 151
DCP17	.969	-0.006	0.036 139	0.028 127	0.039 62	0.022 352	0.031 179	0.021 291	0.008 304	0.023 169	0.037 4

149

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.50	0.511	0.201	5.93	0.0	7.54	12007.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
68.3 (224.1)	12104. (252.8)	0.32E 07	-0.094	1.241	11.64	-0.00143	0.868	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.542	5.930	0	0.509	344	0.159	186	0.062	129	0.026	353	0.020	12	0.022	192	0.024	114	0.005	198
CN		0.806	0.385	38	0.057	67	0.016	288	0.012	246	0.007	288	0.005	299	0.004	325	0.003	97	0.002	95
CM		-0.010	0.068	294	0.014	296	0.003	118	0.003	58	0.000	349	0.002	138	0.001	115	0.001	225	0.000	222
DCP 1	.010	3.849	2.174	348	0.300	35	0.157	333	0.082	230	0.051	240	0.055	207	0.021	144	0.020	120	0.015	69
DCP 2	.020	3.092	1.903	358	0.173	3	0.012	210	0.021	170	0.030	288	0.022	116	0.019	11	0.010	252	0.012	294
DCP 3	.030	2.932	1.611	358	0.144	2	0.009	187	0.012	163	0.018	282	0.003	46	0.004	105	0.015	192	0.002	222
DCP 4	.049	2.418	1.327	0	0.132	7	0.005	35	0.003	2	0.026	282	0.005	133	0.006	359	0.011	206	0.017	74
DCP 5	.074	2.140	1.062	4	0.107	14	0.006	211	0.004	353	0.021	266	0.004	192	0.010	289	0.018	146	0.012	54
DCP 6	.099	2.012	0.905	9	0.092	22	0.019	293	0.003	354	0.018	271	0.009	108	0.009	352	0.025	153	0.013	77
DCP 7	.149	1.474	0.697	16	0.093	40	0.021	292	0.021	273	0.010	343	0.010	352	0.010	53	0.006	112	0.007	144
DCP 8	.200	1.236	0.596	30	0.076	54	0.008	17	0.001	161	0.018	308	0.012	355	0.016	343	0.005	233	0.011	151
DCP 9	.250	1.029	0.533	33	0.077	48	0.031	245	0.009	270	0.011	300	0.015	297	0.002	359	0.011	32	0.004	84
DCP10	.300	0.946	0.455	39	0.058	50	0.029	238	0.014	255	0.012	259	0.015	249	0.002	78	0.015	28	0.010	130
DCP11	.399	0.815	0.441	59	0.073	76	0.027	286	0.013	275	0.010	37	0.013	256	0.005	350	0.010	75	0.006	211
DCP12	.501	0.574	0.406	66	0.072	93	0.020	291	0.025	258	0.012	287	0.004	145	0.012	282	0.008	216	0.006	234
DCP13	.600	0.507	0.362	76	0.069	98	0.022	285	0.015	231	0.005	262	0.013	73	0.005	276	0.011	168	0.003	289
DCP14	.701	0.422	0.297	86	0.051	87	0.013	298	0.023	232	0.006	261	0.018	280	0.003	159	0.007	292	0.008	20
DCP15	.800	0.225	0.220	97	0.059	107	0.021	303	0.012	219	0.001	38	0.004	293	0.002	67	0.009	64	0.011	6
DCP16	.900	-0.018	0.150	110	0.044	121	0.006	255	0.007	153	0.010	105	0.021	328	0.027	331	0.017	67	0.014	158
DCP17	.969	-0.012	0.077	132	0.025	122	0.018	36	0.014	309	0.010	268	0.011	351	0.018	194	0.009	335	0.011	40

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.15	0.513	0.199	5.93	0.0	10.04	12007.5	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
67.7 (222.1)	11917. (248.9)	0.32E 07	-0.077	1.482	13.68	-0.00148	0.890	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		10.036	5.927	0	0.500	344	0.156	183	0.067	117	0.046	346	0.018	12	0.030	185	0.020	136	0.005	185
CN		1.016	0.386	39	0.063	57	0.021	309	0.009	295	0.010	349	0.008	271	0.006	151	0.002	201	0.006	126
CM		-0.005	0.069	293	0.013	275	0.006	157	0.004	96	0.003	195	0.004	87	0.003	334	0.001	45	0.002	318
DCP 1	.010	5.097	1.942	348	0.287	18	0.143	160	0.166	43	0.029	135	0.080	16	0.031	357	0.032	3	0.015	330
DCP 2	.020	4.206	1.874	358	0.177	8	0.040	262	0.022	60	0.023	276	0.024	7	0.008	111	0.012	161	0.009	142
DCP 3	.030	3.881	1.610	358	0.148	3	0.042	275	0.012	72	0.023	271	0.006	356	0.004	149	0.008	127	0.003	318
DCP 4	.049	3.236	1.323	1	0.128	12	0.015	295	0.015	203	0.014	315	0.019	156	0.010	349	0.012	180	0.002	75
DCP 5	.074	2.789	1.047	4	0.099	21	0.024	243	0.007	230	0.016	236	0.014	148	0.011	45	0.006	175	0.017	120
DCP 6	.099	2.541	0.885	9	0.092	27	0.023	258	0.015	198	0.011	309	0.001	97	0.003	20	0.014	191	0.015	119
DCP 7	.149	1.884	0.697	16	0.088	41	0.018	313	0.017	176	0.013	297	0.004	339	0.005	333	0.002	17	0.013	319
DCP 8	.200	1.562	0.583	28	0.082	51	0.027	283	0.004	196	0.015	331	0.008	195	0.007	269	0.015	168	0.006	327
DCP 9	.250	1.309	0.552	31	0.073	40	0.020	250	0.010	96	0.024	333	0.005	184	0.001	7	0.021	268	0.017	48
DCP10	.300	1.170	0.472	37	0.065	53	0.022	273	0.005	320	0.010	306	0.003	207	0.007	106	0.011	61	0.006	43
DCP11	.399	0.984	0.449	59	0.075	73	0.039	312	0.026	342	0.011	17	0.013	266	0.005	126	0.003	324	0.012	127
DCP12	.501	0.707	0.400	68	0.062	67	0.028	322	0.022	325	0.013	49	0.013	309	0.015	206	0.005	47	0.018	177
DCP13	.600	0.591	0.344	79	0.070	69	0.037	313	0.018	298	0.018	332	0.016	266	0.017	182	0.007	59	0.018	186
DCP14	.701	0.486	0.312	86	0.068	90	0.019	346	0.025	261	0.017	19	0.020	267	0.011	89	0.004	190	0.008	75
DCP15	.800	0.256	0.244	97	0.056	92	0.029	328	0.008	286	0.013	291	0.017	278	0.019	140	0.008	211	0.009	46
DCP16	.900	0.005	0.152	103	0.039	85	0.022	346	0.040	244	0.016	61	0.009	277	0.010	132	0.013	255	0.009	173
DCP17	.969	-0.003	0.060	112	0.016	55	0.011	32	0.020	53	0.029	14	0.010	193	0.010	207	0.006	147	0.017	118

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	67.57	0.506	0.199	5.90	0.0	12.52	12007.6	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
67.7	11937.	0.32E 07	-0.070	1.587	16.55	-0.00130	0.762	0.0
(222.2)	(249.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.520	5.902 0	0.496 343	0.151 184	0.057 120	0.043 334	0.019 60	0.024 161	0.011 103	0.005 261
CN		1.155	0.360 35	0.056 64	0.013 297	0.010 307	0.006 9	0.001 101	0.012 142	0.001 59	0.002 136
CM		-0.002	0.060 294	0.016 279	0.004 129	0.005 129	0.003 266	0.001 215	0.003 325	0.001 163	0.003 42
DCP 1	.010	5.831	1.597 359	0.485 340	0.213 174	0.145 170	0.033 170	0.070 170	0.026 172	0.313 72	0.046 208
DCP 2	.020	4.974	1.737 1	0.291 2	0.049 222	0.035 81	0.038 290	0.004 267	0.016 43	0.010 40	0.005 195
DCP 3	.030	4.614	1.590 358	0.159 2	0.008 234	0.004 304	0.032 262	0.005 56	0.016 1	0.007 163	0.014 337
DCP 4	.049	3.688	1.329 8	0.186 330	0.057 160	0.033 36	0.050 290	0.020 203	0.004 97	0.009 91	0.006 77
DCP 5	.074	3.142	1.069 10	0.119 332	0.036 139	0.016 343	0.022 274	0.019 94	0.007 105	0.016 189	0.013 154
DCP 6	.099	2.642	0.925 12	0.065 336	0.024 53	0.025 257	0.002 321	0.005 277	0.009 45	0.006 169	0.010 109
DCP 7	.149	2.148	0.733 14	0.025 12	0.021 13	0.013 234	0.017 281	0.005 105	0.007 59	0.012 85	0.005 64
DCP 8	.200	1.832	0.656 15	0.085 123	0.059 8	0.015 248	0.037 356	0.016 185	0.015 146	0.018 169	0.017 37
DCP 9	.250	1.515	0.511 25	0.114 73	0.054 298	0.012 131	0.035 333	0.025 180	0.017 124	0.003 234	0.004 29
DCP10	.300	1.350	0.451 31	0.105 73	0.047 279	0.019 67	0.016 352	0.037 324	0.015 95	0.008 137	0.006 123
DCP11	.399	1.117	0.399 53	0.096 64	0.027 276	0.011 9	0.013 77	0.024 327	0.043 152	0.011 316	0.014 161
DCP12	.501	0.803	0.357 64	0.080 64	0.020 262	0.022 317	0.010 98	0.036 204	0.018 174	0.014 291	0.013 144
DCP13	.600	0.638	0.337 76	0.055 83	0.017 269	0.034 311	0.036 101	0.017 42	0.015 208	0.004 75	0.009 355
DCP14	.701	0.507	0.266 85	0.065 79	0.006 330	0.034 297	0.003 226	0.006 90	0.008 161	0.007 84	0.011 282
DCP15	.800	0.262	0.221 97	0.052 96	0.020 356	0.015 316	0.037 349	0.006 73	0.004 143	0.013 19	0.008 336
DCP16	.900	0.036	0.118 112	0.049 95	0.026 251	0.017 261	0.022 111	0.017 202	0.026 114	0.003 346	0.008 175
DCP17	.969	0.000	0.064 91	0.020 34	0.017 105	0.011 60	0.021 57	0.015 31	0.018 348	0.007 176	0.016 110

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	67.31	0.504	0.200	5.90	0.0	15.07	12007.7	20

V	Q	RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
67.9	12018.	0.32E 07	-0.085	1.581	19.50	-0.00023	0.137	0.0
(222.9)	(251.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		15.072	5.897 0	0.397 337	0.116 194	0.065 148	0.063 359	0.021 116	0.007 152	0.020 188	0.012 15
CN		1.219	0.397 11	0.112 86	0.006 273	0.016 326	0.012 237	0.012 73	0.008 176	0.006 333	0.005 156
CM		-0.017	0.035 353	0.041 252	0.013 39	0.003 195	0.000 31	0.003 205	0.004 348	0.002 156	0.001 102
DCP 1	.010	4.957	1.902 52	0.739 343	0.443 263	0.321 193	0.067 135	0.099 305	0.042 252	0.032 207	0.020 190
DCP 2	.020	4.440	1.888 38	0.492 352	0.249 296	0.199 171	0.062 43	0.031 30	0.012 299	0.051 115	0.033 39
DCP 3	.030	4.241	1.860 26	0.255 301	0.117 331	0.093 152	0.019 211	0.071 2	0.061 191	0.026 55	0.045 347
DCP 4	.049	3.719	1.552 22	0.424 308	0.242 157	0.150 43	0.073 293	0.061 213	0.040 107	0.037 57	0.013 353
DCP 5	.074	3.185	1.402 19	0.348 274	0.249 118	0.143 357	0.086 258	0.049 158	0.041 44	0.024 327	0.025 161
DCP 6	.099	2.916	1.298 13	0.274 238	0.218 64	0.115 323	0.063 228	0.033 122	0.035 34	0.032 283	0.043 125
DCP 7	.149	2.335	1.148 1	0.258 181	0.155 68	0.133 328	0.100 219	0.062 113	0.037 26	0.021 296	0.026 144
DCP 8	.200	2.043	0.977 356	0.237 160	0.136 60	0.103 339	0.071 241	0.079 121	0.065 11	0.023 221	0.053 163
DCP 9	.250	1.763	0.779 342	0.320 123	0.135 22	0.114 271	0.049 152	0.054 32	0.037 260	0.029 166	0.033 111
DCP10	.300	1.536	0.577 339	0.296 103	0.109 342	0.074 233	0.054 110	0.037 336	0.047 216	0.022 51	0.007 176
DCP11	.399	1.248	0.347 347	0.337 97	0.137 316	0.053 159	0.050 38	0.011 257	0.037 166	0.022 23	0.014 10
DCP12	.501	0.871	0.164 6	0.234 77	0.111 269	0.035 134	0.064 343	0.027 134	0.012 134	0.012 253	0.013 236
DCP13	.600	0.653	0.096 45	0.198 66	0.086 241	0.046 53	0.045 269	0.023 45	0.008 231	0.017 114	0.017 297
DCP14	.701	0.471	0.097 96	0.167 56	0.085 206	0.064 72	0.037 245	0.023 72	0.019 222	0.032 354	0.019 239
DCP15	.800	0.295	0.152 124	0.120 54	0.076 170	0.040 333	0.023 142	0.021 355	0.023 158	0.025 306	0.007 141
DCP16	.900	0.145	0.122 117	0.070 36	0.047 157	0.027 291	0.026 177	0.001 43	0.036 126	0.022 259	0.009 5
DCP17	.969	0.046	0.051 125	0.033 61	0.024 143	0.002 306	0.023 76	0.017 342	0.011 343	0.032 83	0.013 74

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.74	0.516	0.200	5.96	0.0	17.56	12007.8	20

V	C	RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
67.8	12023.	0.32E 07	-0.260	1.795	23.99	0.00106	-0.637	0.0
(222.6)	(251.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		17.561	5.962 0	0.486 331	0.130 203	0.053 115	0.051 1	0.024 58	0.025 176	0.016 125	0.005 311
CN		1.325	0.562 359	0.133 102	0.036 266	0.034 55	0.016 253	0.017 25	0.011 188	0.009 161	0.007 324
CM		-0.077	0.079 49	0.075 243	0.022 83	0.006 238	0.007 27	0.008 223	0.002 314	0.003 73	0.003 88
DCP 1	.010	4.289	2.481 55	0.357 359	0.285 331	0.286 317	0.231 257	0.147 211	0.100 116	0.118 47	0.106 345
DCP 2	.020	3.986	2.633 45	0.505 332	0.218 237	0.126 86	0.106 6	0.116 274	0.106 188	0.130 108	0.092 37
DCP 3	.030	3.817	2.447 39	0.571 335	0.423 254	0.215 154	0.185 104	0.184 10	0.118 317	0.121 243	0.094 182
DCP 4	.049	3.480	2.173 33	0.586 295	0.215 210	0.191 132	0.125 38	0.079 340	0.080 274	0.053 174	0.043 172
DCP 5	.074	3.045	1.912 25	0.410 277	0.232 198	0.204 102	0.119 24	0.091 324	0.092 254	0.088 145	0.064 86
DCP 6	.099	2.798	1.775 20	0.358 259	0.249 173	0.187 79	0.142 359	0.074 283	0.094 219	0.072 121	0.053 47
DCP 7	.149	2.311	1.621 5	0.384 231	0.241 143	0.179 67	0.145 330	0.085 249	0.093 168	0.075 64	0.081 348
DCP 8	.200	2.035	1.447 3	0.396 220	0.210 132	0.197 49	0.143 312	0.099 213	0.081 116	0.044 53	0.041 325
DCP 9	.250	1.789	1.236 347	0.443 177	0.265 80	0.283 347	0.206 229	0.119 139	0.106 55	0.073 312	0.061 199
DCP10	.300	1.601	1.043 341	0.437 156	0.258 42	0.226 296	0.160 185	0.113 76	0.064 318	0.036 238	0.019 100
DCP11	.399	1.393	0.760 336	0.537 140	0.295 11	0.188 252	0.112 146	0.101 36	0.050 279	0.078 175	0.025 15
DCP12	.501	1.109	0.543 316	0.585 108	0.299 312	0.139 166	0.068 56	0.063 321	0.062 154	0.017 70	0.032 254
DCP13	.600	0.902	0.305 283	0.529 81	0.281 270	0.160 113	0.078 324	0.035 199	0.021 87	0.006 57	0.018 227
DCP14	.701	0.752	0.218 232	0.444 48	0.209 231	0.135 75	0.088 260	0.053 80	0.030 264	0.009 234	0.008 358
DCP15	.800	0.555	0.207 186	0.316 22	0.132 206	0.087 14	0.047 169	0.035 359	0.029 164	0.014 209	0.014 260
DCP16	.900	0.248	0.107 157	0.180 357	0.078 198	0.082 12	0.061 154	0.039 354	0.042 50	0.015 261	0.024 325
DCP17	.969	0.163	0.126 187	0.161 344	0.076 109	0.049 228	0.055 335	0.049 70	0.042 211	0.031 295	0.017 142

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.82	0.520	0.198	5.93	0.0	19.97	12007.9	20

V	Q	RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
67.3	11846.	0.32E 07	-0.314	2.081	25.94	0.00215	-1.284	0.0
(220.9)	(247.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		19.973	5.931 0	0.532 332	0.100 210	0.060 138	0.045 19	0.015 46	0.018 193	0.019 132	0.003 41
CN		1.442	0.654 7	0.058 157	0.031 331	0.034 176	0.008 16	0.019 86	0.004 107	0.013 339	0.011 265
CM		-0.136	0.113 70	0.058 267	0.019 176	0.013 30	0.009 144	0.007 318	0.004 43	0.004 241	0.003 49
DCP 1	.010	3.621	2.723 67	0.629 52	0.237 319	0.138 358	0.237 28	0.170 356	0.137 283	0.154 247	0.125 178
DCP 2	.020	3.413	2.636 62	0.643 44	0.310 315	0.242 258	0.148 161	0.128 89	0.068 42	0.059 331	0.057 305
DCP 3	.030	3.346	2.527 57	0.634 26	0.423 304	0.213 282	0.266 199	0.183 147	0.167 94	0.127 67	0.136 3
DCP 4	.049	3.264	2.292 49	0.581 347	0.378 278	0.247 210	0.126 171	0.170 114	0.118 17	0.118 335	
DCP 5	.074	2.902	2.029 39	0.510 326	0.413 253	0.279 175	0.133 125	0.160 69	0.080 17	0.108 327	0.088 274
DCP 6	.099	2.724	1.852 32	0.457 308	0.367 235	0.270 157	0.152 99	0.138 42	0.064 332	0.089 293	0.068 226
DCP 7	.149	2.307	1.759 20	0.517 286	0.321 214	0.291 136	0.120 62	0.147 4	0.091 297	0.102 219	0.089 147
DCP 8	.200	2.063	1.694 19	0.600 271	0.355 199	0.303 109	0.173 38	0.146 333	0.067 260	0.055 208	0.043 147
DCP 9	.250	1.900	1.552 7	0.651 234	0.405 144	0.354 51	0.210 316	0.146 247	0.089 166	0.067 74	0.077 20
DCP10	.300	1.767	1.363 359	0.594 213	0.385 106	0.299 3	0.186 263	0.114 185	0.077 118	0.067 4	0.075 302
DCP11	.399	1.596	1.052 350	0.610 186	0.422 64	0.261 316	0.126 207	0.079 127	0.047 103	0.055 312	0.038 233
DCP12	.501	1.313	0.766 320	0.587 144	0.415 13	0.252 243	0.107 124	0.050 26	0.028 17	0.020 175	0.021 122
DCP13	.600	1.143	0.529 301	0.522 109	0.371 334	0.225 194	0.065 68	0.028 341	0.021 19	0.015 25	0.031 3
DCP14	.701	0.967	0.353 259	0.428 74	0.273 290	0.131 126	0.043 327	0.016 184	0.010 139	0.006 263	0.033 270
DCP15	.800	0.745	0.268 216	0.302 47	0.196 253	0.093 80	0.035 232	0.002 351	0.034 129	0.016 225	0.017 286
DCP16	.900	0.417	0.254 199	0.235 4	0.077 160	0.061 170	0.094 332	0.080 91	0.054 231	0.043 28	0.036 172
DCP17	.969	0.336	0.393 211	0.344 351	0.229 122	0.188 248	0.144 24	0.112 159	0.089 286	0.072 82	0.016 208

FORCED PITCHING OSCILLATION　　　　AIRFOIL　　NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.12	0.113	0.308	5.14	0.0	0.03	12009.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
104.4	28259.	0.49E 07	-0.039	0.567	5.24	-0.00083	0.702	0.0
(342.5)	(590.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.028	5.136 0	0.238 5	0.050 258	0.004 125	0.007 53	0.029 76	0.034 187	0.041 179	0.004 308
CN		0.126	0.430 355	0.016 0	0.001 178	0.001 85	0.003 274	0.001 76	0.005 208	0.018 205	0.002 42
CM		-0.018	0.013 303	0.001 352	0.001 19	0.000 273	0.001 98	0.001 178	0.002 25	0.007 15	0.001 201
DCP 1	.010	-0.632	3.105 347	0.226 31	0.049 116	0.014 188	0.003 207	0.012 121	0.002 300	0.022 312	0.012 167
DCP 2	.020	-0.331	2.245 350	0.089 349	0.008 358	0.003 259	0.002 253	0.012 144	0.007 347	0.018 324	0.011 187
DCP 3	.030	-0.015	1.868 350	0.072 333	0.008 331	0.004 268	0.003 262	0.006 132	0.002 244	0.013 328	0.006 191
DCP 4	.049	0.106	1.519 350	0.058 332	0.008 333	0.004 252	0.003 225	0.007 129	0.001 56	0.017 327	0.004 212
DCP 5	.074	0.276	1.217 350	0.047 344	0.002 302	0.002 242	0.004 174	0.007 136	0.002 36	0.015 324	0.004 173
DCP 6	.099	0.365	1.053 351	0.040 351	0.010 322	0.001 154	0.005 167	0.003 86	0.001 316	0.015 309	0.006 190
DCP 7	.149	0.231	0.786 352	0.033 4	0.003 3	0.005 31	0.004 305	0.005 164	0.006 301	0.010 300	0.007 153
DCP 8	.200	0.205	0.642 355	0.027 355	0.004 34	0.003 176	0.002 199	0.005 146	0.003 334	0.009 329	0.003 191
DCP 9	.250	0.175	0.559 354	0.027 3	0.001 230	0.003 127	0.004 266	0.001 83	0.008 179	0.027 192	0.004 336
DCP10	.300	0.190	0.466 355	0.019 359	0.002 205	0.005 38	0.006 256	0.003 38	0.006 179	0.019 188	0.002 202
DCP11	.399	0.183	0.374 0	0.012 10	0.004 158	0.004 36	0.009 295	0.003 63	0.009 203	0.030 200	0.004 11
DCP12	.501	0.120	0.283 4	0.009 11	0.006 149	0.001 309	0.003 311	0.001 249	0.006 222	0.024 201	0.003 104
DCP13	.600	0.151	0.219 6	0.008 34	0.003 170	0.004 223	0.004 284	0.003 306	0.008 197	0.027 203	0.005 26
DCP14	.701	0.195	0.155 6	0.004 6	0.003 235	0.002 172	0.002 350	0.003 280	0.007 200	0.028 194	0.006 40
DCP15	.800	0.096	0.093 14	0.001 61	0.003 110	0.003 110	0.004 353	0.003 9	0.009 215	0.027 201	0.005 23
DCP16	.900	-0.061	0.029 23	0.004 220	0.001 297	0.008 51	0.008 229	0.002 359	0.005 222	0.023 186	0.006 12
DCP17	.969	-0.028	0.019 195	0.004 200	0.006 206	0.008 228	0.004 141	0.008 67	0.012 196	0.028 205	0.003 351

FORCED PITCHING OSCILLATION　　　　AIRFOIL　　NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.19	0.115	0.304	5.15	0.0	2.46	12009.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
102.9	27617.	0.49E 07	-0.030	0.790	7.62	-0.00091	0.754	0.0
(337.7)	(576.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.455	5.155 0	0.233 6	0.049 261	0.005 203	0.015 24	0.011 89	0.023 162	0.006 142	0.006 21
CN		0.358	0.434 355	0.019 14	0.002 42	0.002 353	0.001 276	0.001 265	0.001 154	0.004 161	0.003 14
CM		-0.014	0.014 300	0.002 253	0.001 275	0.001 173	0.000 340	0.001 152	0.003 354	0.001 306	0.001 189
DCP 1	.010	1.005	2.898 347	0.118 8	0.007 29	0.003 163	0.011 291	0.013 181	0.004 25	0.007 217	0.015 302
DCP 2	.023	0.850	2.248 350	0.080 356	0.032 323	0.037 28	0.013 302	0.015 197	0.007 112	0.003 227	0.013 309
DCP 3	.030	0.969	1.905 350	0.068 354	0.027 331	0.002 118	0.013 317	0.012 183	0.008 82	0.006 204	0.013 341
DCP 4	.049	0.929	1.571 350	0.055 342	0.015 337	0.002 117	0.007 299	0.004 189	0.002 270	0.008 231	0.005 13
DCP 5	.074	0.942	1.243 350	0.042 346	0.011 324	0.003 205	0.005 299	0.001 172	0.003 251	0.004 212	0.004 284
DCP 6	.099	0.924	1.064 351	0.039 358	0.007 314	0.001 107	0.002 311	0.001 284	0.002 255	0.035 203	0.003 302
DCP 7	.149	0.660	0.802 352	0.033 0	0.003 345	0.003 257	0.004 98	0.003 191	0.003 337	0.006 197	0.004 346
DCP 8	.200	0.553	0.654 355	0.025 1	0.008 1	0.003 1	0.004 337	0.001 277	0.002 82	0.009 221	0.006 69
DCP 9	.250	0.470	0.567 355	0.027 10	0.006 231	0.003 39	0.002 281	0.001 241	0.002 287	0.035 137	0.006 70
DCP10	.300	0.447	0.475 355	0.024 20	0.002 297	0.005 335	0.003 20	0.003 218	0.003 9	0.002 152	0.003 6
DCP11	.399	0.385	0.374 1	0.015 27	0.004 108	0.003 352	0.005 308	0.002 134	0.001 92	0.004 156	0.004 16
DCP12	.531	0.272	0.292 4	0.012 35	0.011 117	0.001 89	0.004 261	0.002 73	0.005 122	0.004 179	0.002 65
DCP13	.600	0.264	0.223 6	0.017 46	0.009 103	0.002 290	0.004 214	0.005 356	0.005 156	0.004 183	0.011 52
DCP14	.701	0.275	0.152 10	0.011 37	0.007 53	0.004 14	0.004 156	0.007 9	0.005 162	0.006 99	0.006 15
DCP15	.830	0.142	0.091 17	0.011 37	0.006 42	0.002 262	0.003 82	0.003 312	0.004 136	0.035 129	0.003 15
DCP16	.900	-0.048	0.017 26	0.005 63	0.008 328	0.007 10	0.003 160	0.005 230	0.007 253	0.005 121	0.007 261
DCP17	.969	-0.034	0.013 181	0.004 343	0.010 176	0.001 321	0.002 294	0.002 247	0.002 244	0.006 144	0.004 328

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ 0.0	DRIVE HZ 23.16	K 0.115	MACH NO 0.302	DEL.ALPHA 5.15	DEL.H 0.0	ALPHA.0 5.01	TEST POINT 12009.3	CYCLES ANALYSED 20
	V 102.1 (335.1)	Q 27273. (569.6)	RN 0.48E 07	CN(MIN) -0.026	CN(MAX) 1.005	ALPHA.NMAX 9.95	AERO DAMP -0.00094	TOR 0.779	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		5.009	5.147 0	0.237 8	0.036 257	0.003 305	0.013 351	0.006 213	0.027 229	0.005 225	0.004 77
CN		0.594	0.426 356	0.022 17	0.005 40	0.003 249	0.002 338	0.001 207	0.005 348	0.006 317	0.003 224
CM		-0.009	0.015 305	0.002 263	0.001 262	0.000 114	0.000 210	0.000 13	0.001 183	0.001 119	0.001 90
DCP 1	.010	2.563	2.774 347	0.144 16	0.066 339	0.050 227	0.020 149	0.009 137	0.004 345	0.024 341	0.005 212
DCP 2	.020	2.096	2.263 350	0.101 356	0.018 355	0.006 236	0.003 147	0.003 120	0.009 337	0.022 342	0.010 187
DCP 3	.030	2.015	1.913 350	0.085 353	0.009 356	0.004 354	0.006 205	0.002 102	0.007 335	0.013 340	0.007 198
DCP 4	.049	1.797	1.569 350	0.067 346	0.011 337	0.001 233	0.005 282	0.007 237	0.010 329	0.012 344	0.012 159
DCP 5	.074	1.642	1.259 351	0.053 355	0.013 355	0.004 201	0.005 301	0.005 223	0.010 332	0.011 332	0.012 181
DCP 6	.099	1.510	1.062 351	0.045 357	0.010 356	0.001 221	0.003 316	0.005 230	0.007 348	0.011 329	0.009 170
DCP 7	.149	1.098	0.790 353	0.030 1	0.008 322	0.008 191	0.010 294	0.005 222	0.007 346	0.014 322	0.003 138
DCP 8	.200	0.905	0.646 356	0.030 6	0.011 24	0.006 216	0.003 79	0.002 59	0.005 358	0.010 313	0.007 192
DCP 9	.250	0.779	0.557 355	0.030 10	0.006 178	0.004 256	0.003 31	0.005 193	0.000 325	0.004 310	0.003 306
DCP10	.300	0.706	0.460 356	0.023 23	0.006 56	0.001 284	0.006 276	0.004 150	0.004 299	0.005 296	0.002 257
DCP11	.399	0.592	0.367 1	0.019 32	0.011 88	0.002 333	0.009 327	0.002 222	0.008 346	0.001 263	0.005 262
DCP12	.501	0.429	0.280 5	0.020 29	0.007 102	0.005 263	0.002 174	0.001 306	0.005 338	0.005 327	0.003 345
DCP13	.600	0.380	0.210 7	0.017 23	0.010 64	0.006 264	0.003 105	0.006 4	0.002 342	0.005 291	0.002 290
DCP14	.701	0.353	0.143 12	0.020 62	0.008 11	0.002 290	0.009 60	0.002 306	0.009 344	0.005 312	0.003 225
DCP15	.800	0.188	0.082 20	0.011 58	0.007 29	0.001 106	0.006 45	0.004 243	0.005 25	0.007 297	0.003 253
DCP16	.900	-0.044	0.031 35	0.004 93	0.004 72	0.005 296	0.009 269	0.008 161	0.007 354	0.004 357	0.004 239
DCP17	.969	-0.043	0.010 219	0.003 31	0.008 185	0.002 166	0.005 173	0.002 132	0.009 26	0.007 299	0.001 203

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ 0.0	DRIVE HZ 23.13	K 0.116	MACH NO 0.300	DEL.ALPHA 5.14	DEL.H 0.0	ALPHA.0 7.48	TEST POINT 12009.4	CYCLES ANALYSED 20
	V 101.6 (333.2)	Q 27019. (564.3)	RN 0.48E 07	CN(MIN) -0.023	CN(MAX) 1.213	ALPHA.NMAX 12.61	AERO DAMP -0.00112	TOR 0.921	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.471	5.140 0	0.247 7	0.051 264	0.003 308	0.012 55	0.013 354	0.020 201	0.006 170	0.006 133
CN		0.816	0.603 358	0.029 21	0.002 336	0.004 101	0.002 22	0.001 51	0.001 335	0.006 325	0.003 200
CM		-0.003	0.018 307	0.002 253	0.001 246	0.001 288	0.001 287	0.001 224	0.000 70	0.001 109	0.000 122
DCP 1	.010	4.060	2.722 348	0.154 331	0.110 167	0.132 64	0.081 324	0.015 261	0.019 302	0.016 5	0.015 211
DCP 2	.020	3.261	2.136 351	0.125 22	0.054 342	0.018 231	0.007 284	0.012 205	0.007 329	0.017 22	0.006 231
DCP 3	.030	3.024	1.861 351	0.094 359	0.015 338	0.009 225	0.005 309	0.009 196	0.004 7	0.006 11	0.010 215
DCP 4	.049	2.634	1.531 351	0.090 11	0.024 329	0.007 232	0.003 41	0.002 306	0.036 37	0.012 18	0.008 186
DCP 5	.074	2.295	1.206 352	0.071 13	0.016 330	0.005 222	0.002 21	0.002 350	0.004 13	0.012 11	0.007 186
DCP 6	.099	2.062	1.016 353	0.060 16	0.014 332	0.006 226	0.004 277	0.004 281	0.005 348	0.014 19	0.008 167
DCP 7	.149	1.512	0.771 354	0.047 14	0.003 320	0.009 141	0.007 349	0.005 173	0.008 349	0.011 359	0.008 190
DCP 8	.200	1.243	0.625 357	0.042 14	0.011 319	0.005 151	0.006 83	0.005 217	0.005 62	0.010 13	0.006 195
DCP 9	.250	1.065	0.537 357	0.030 6	0.007 238	0.006 113	0.004 36	0.001 87	0.003 27	0.007 350	0.001 165
DCP10	.300	0.944	0.434 358	0.033 21	0.000 157	0.006 55	0.004 169	0.001 14	0.003 49	0.005 257	0.005 285
DCP11	.399	0.782	0.347 5	0.031 30	0.002 179	0.004 43	0.002 343	0.004 79	0.001 193	0.009 307	0.005 148
DCP12	.501	0.573	0.261 8	0.023 17	0.003 205	0.007 114	0.003 9	0.004 45	0.005 226	0.008 276	0.005 198
DCP13	.600	0.476	0.194 12	0.021 47	0.005 99	0.007 110	0.005 58	0.004 65	0.002 251	0.010 310	0.003 208
DCP14	.701	0.422	0.123 23	0.024 46	0.002 326	0.005 67	0.004 104	0.003 356	0.003 7	0.003 340	0.001 158
DCP15	.800	0.227	0.069 33	0.011 45	0.005 35	0.001 224	0.003 110	0.002 322	0.004 7	0.003 266	0.004 269
DCP16	.900	-0.026	0.029 42	0.002 0	0.007 10	0.002 287	0.003 173	0.001 32	0.008 217	0.006 264	0.004 127
DCP17	.969	-0.049	0.012 104	0.004 298	0.005 156	0.008 124	0.004 317	0.004 142	0.008 305	0.010 355	0.006 341

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	23.26	0.117	0.300	5.12	3.0	9.99	12009.5	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	101.2	26875.	0.48E 07	-0.092	1.404	15.10	-0.00046	0.390	0.0
	(331.9)	(561.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		9.993	5.121 0	0.266 16	0.062 265	0.012 195	0.332 78	0.037 347	0.031 164	0.013 154	0.007 306
CN		0.943	0.351 22	0.100 339	0.037 174	0.022 34	0.013 310	0.013 230	0.016 138	0.011 72	0.015 313
CM		-0.011	0.019 207	0.026 52	0.021 292	0.013 174	0.305 68	0.004 11	0.003 295	0.002 235	0.004 117
DCP 1	.010	4.408	1.175 22	1.146 38	0.609 314	0.393 244	0.317 179	0.205 108	0.112 30	0.063 261	0.076 184
DCP 2	.020	3.521	0.903 29	1.017 45	0.602 320	0.364 237	0.243 166	0.167 101	0.126 49	0.062 349	0.069 302
DCP 3	.030	3.143	0.757 41	0.987 38	0.558 305	0.255 211	0.388 161	0.116 139	0.105 61	0.117 331	0.089 257
DCP 4	.049	3.074	1.076 12	0.380 16	0.135 279	0.073 172	0.048 76	0.035 352	0.017 264	0.015 186	0.006 116
DCP 5	.074	2.612	0.818 15	0.337 16	0.127 273	0.071 161	0.041 55	0.034 326	0.021 216	0.022 145	0.006 18
DCP 6	.099	2.296	0.680 20	0.316 15	0.125 267	0.077 152	0.045 47	0.033 315	0.023 208	0.015 133	0.006 137
DCP 7	.149	1.710	0.555 24	0.264 2	0.118 241	0.061 130	0.036 22	0.021 299	0.098 216	0.014 162	0.002 296
DCP 8	.200	1.450	0.562 23	0.224 338	0.143 210	0.091 95	0.353 0	0.032 285	0.026 193	0.025 134	0.011 351
DCP 9	.250	1.274	0.564 19	0.216 313	0.159 179	0.105 74	0.063 351	0.053 261	0.053 191	0.043 107	0.035 13
DCP10	.300	1.138	0.502 17	0.193 300	0.150 170	0.096 69	0.364 355	0.063 275	0.057 178	0.036 85	0.024 4
DCP11	.399	0.943	0.415 20	0.146 293	0.124 157	0.082 46	0.349 326	0.068 255	0.043 159	0.026 72	0.021 336
DCP12	.501	0.687	0.302 23	0.092 282	0.101 131	0.076 16	0.350 285	0.035 205	0.034 126	0.023 43	0.025 323
DCP13	.600	0.546	0.228 24	0.089 273	0.086 115	0.063 352	0.038 260	0.033 173	0.022 90	0.016 38	0.021 317
DCP14	.701	0.457	0.152 40	0.050 260	0.072 103	0.063 329	0.021 232	0.015 159	0.015 86	0.009 4	0.022 295
DCP15	.800	0.268	0.116 29	0.061 233	0.063 93	0.042 320	0.013 262	0.003 174	0.009 110	0.006 44	0.026 260
DCP16	.900	0.016	0.085 1	0.044 212	0.022 61	0.017 313	0.014 220	0.016 122	0.009 1	0.005 207	0.009 229
DCP17	.969	-0.032	0.035 350	0.024 222	0.016 62	0.012 297	0.007 164	0.004 133	0.007 29	0.004 135	0.005 230

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	23.22	0.117	0.299	5.08	0.0	12.48	12009.6	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	101.1	26732.	0.48E 07	-0.183	1.691	16.86	-0.00108	0.882	0.0
	(330.8)	(558.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.478	5.084 0	0.239 16	0.016 315	0.052 351	0.039 291	0.071 165	0.025 230	0.016 35	0.013 306
CN		1.045	0.299 52	0.160 16	0.082 302	0.063 219	0.042 143	0.032 70	0.020 359	0.008 46	0.024 293
CM		-0.025	0.054 199	0.038 94	0.021 46	0.020 340	0.013 260	0.011 210	0.006 139	0.001 41	0.005 80
DCP 1	.010	4.584	0.774 143	1.352 81	0.726 40	0.427 357	0.235 333	0.156 341	0.197 307	0.107 253	0.060 216
DCP 2	.020	3.801	0.603 134	1.167 79	0.491 32	0.264 359	0.162 326	0.089 328	0.148 305	0.114 257	0.097 241
DCP 3	.030	3.302	0.745 135	1.062 69	0.246 25	0.236 39	0.205 340	0.092 319	0.136 308	0.120 254	0.075 233
DCP 4	.049	3.323	0.454 61	0.620 61	0.260 6	0.148 313	0.105 261	0.072 203	0.051 153	0.044 106	0.011 21
DCP 5	.074	2.792	0.414 75	0.555 54	0.226 347	0.116 281	0.066 222	0.068 166	0.029 112	0.031 70	0.014 324
DCP 6	.099	2.448	0.427 80	0.511 48	0.213 335	0.111 267	0.055 204	0.038 163	0.028 121	0.031 85	0.012 347
DCP 7	.149	1.880	0.440 64	0.381 29	0.153 313	0.089 247	0.056 186	0.027 122	0.008 64	0.019 89	0.007 335
DCP 8	.200	1.579	0.462 59	0.339 21	0.165 314	0.137 255	0.100 195	0.060 135	0.036 85	0.027 60	0.020 330
DCP 9	.250	1.385	0.488 53	0.305 7	0.175 305	0.159 240	0.127 169	0.072 111	0.044 71	0.044 49	0.032 317
DCP10	.300	1.229	0.457 50	0.277 1	0.174 300	0.162 234	0.116 166	0.079 115	0.052 61	0.047 42	0.046 336
DCP11	.399	1.041	0.424 48	0.223 351	0.152 294	0.144 229	0.102 162	0.081 107	0.044 57	0.042 58	0.062 344
DCP12	.501	0.797	0.365 41	0.159 331	0.109 273	0.118 202	0.090 129	0.073 73	0.043 17	0.032 18	0.061 305
DCP13	.600	0.637	0.303 40	0.126 310	0.081 242	0.094 179	0.076 105	0.057 42	0.043 349	0.016 351	0.052 277
DCP14	.701	0.542	0.244 38	0.118 288	0.069 222	0.085 155	0.062 81	0.053 16	0.043 316	0.021 241	0.031 243
DCP15	.800	0.345	0.205 21	0.104 270	0.065 219	0.075 142	0.039 66	0.047 9	0.044 294	0.025 219	0.025 199
DCP16	.900	0.071	0.148 6	0.064 265	0.047 216	0.041 133	0.028 46	0.040 354	0.026 265	0.020 191	0.018 207
DCP17	.969	-0.003	0.078 357	0.028 282	0.026 243	0.018 147	0.016 94	0.022 353	0.013 270	0.012 191	0.011 180

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	23.24	0.118	0.298	5.05	0.0	15.04	12009.7	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	100.6	26660	0.48E 07	-0.219	1.828	17.82	-0.00164	1.331	0.0
	(330.0)	(556.8)							

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		15.036	5.048 0	0.224 16	0.022 192	0.027 96	0.082 60	0.106 328	0.040 186	0.039 159	0.014 189
CN		1.093	0.324 81	0.149 52	0.078 5	0.061 343	0.058 285	0.046 247	0.036 204	0.027 168	0.013 158
CM		-0.043	0.075 198	0.024 143	0.027 122	0.017 107	0.018 63	0.013 27	0.010 354	0.011 317	0.003 278
DCP 1	.010	4.240	1.989 159	0.989 110	0.543 127	0.403 128	0.213 114	0.172 154	0.166 134	0.076 123	0.090 110
DCP 2	.020	3.642	1.588 155	0.715 102	0.436 125	0.224 114	0.142 108	0.104 151	0.139 143	0.107 138	0.140 134
DCP 3	.030	3.187	1.483 149	0.416 98	0.479 138	0.145 113	0.213 132	0.092 116	0.130 133	0.067 109	0.094 134
DCP 4	.049	3.350	0.878 136	0.564 100	0.293 82	0.192 50	0.123 17	0.088 347	0.051 297	0.019 316	0.017 34
DCP 5	.074	2.808	0.685 128	0.451 84	0.203 66	0.131 33	0.085 347	0.056 327	0.045 279	0.020 299	0.014 333
DCP 6	.099	2.452	0.688 121	0.387 71	0.162 56	0.118 20	0.084 327	0.040 300	0.037 263	0.015 289	0.003 349
DCP 7	.149	1.939	0.587 96	0.263 55	0.173 42	0.103 3	0.095 331	0.063 288	0.039 243	0.020 300	0.014 227
DCP 8	.200	1.617	0.549 92	0.277 60	0.197 36	0.123 7	0.122 333	0.083 296	0.047 264	0.035 294	0.012 255
DCP 9	.250	1.448	0.530 82	0.291 49	0.201 14	0.133 357	0.143 316	0.095 284	0.061 248	0.037 242	0.032 226
DCP10	.300	1.287	0.478 76	0.263 46	0.181 4	0.140 353	0.126 308	0.089 279	0.049 251	0.042 239	0.033 230
DCP11	.399	1.103	0.429 68	0.210 40	0.149 354	0.116 348	0.106 300	0.090 279	0.050 241	0.055 222	0.035 228
DCP12	.501	0.871	0.373 57	0.145 24	0.123 330	0.082 327	0.088 276	0.072 247	0.053 217	0.061 193	0.034 181
DCP13	.600	0.715	0.344 49	0.106 4	0.119 318	0.078 300	0.100 260	0.081 225	0.066 201	0.066 167	0.040 144
DCP14	.701	0.608	0.301 40	0.070 329	0.105 300	0.070 283	0.094 239	0.074 200	0.061 171	0.060 132	0.030 104
DCP15	.800	0.417	0.286 23	0.060 318	0.085 293	0.064 281	0.074 225	0.060 187	0.054 154	0.059 106	0.024 75
DCP16	.900	0.136	0.191 11	0.051 333	0.046 285	0.043 264	0.035 198	0.038 168	0.027 130	0.048 108	0.021 18
DCP17	.969	0.023	0.007 12	0.032 349	0.030 288	0.017 260	0.021 215	0.017 164	0.023 139	0.024 121	0.018 45

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	23.27	0.116	0.290	5.04	0.0	17.51	12009.8	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	100.6	26703.	0.48E 07	-0.214	1.845	17.99	-0.00265	2.154	0.0
	(330.1)	(557.7)							

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		17.512	5.041 0	0.199 4	0.067 238	0.030 189	0.031 142	0.069 112	0.019 236	0.028 34	0.009 56
CN		1.090	0.352 98	0.133 83	0.076 91	0.055 68	0.047 55	0.044 40	0.022 32	0.029 33	0.015 44
CM		-0.057	0.075 236	0.037 236	0.021 195	0.016 199	0.014 167	0.013 182	0.004 169	0.009 183	0.004 169
DCP 1	.010	3.667	2.499 164	0.885 178	0.684 200	0.276 235	0.252 252	0.136 310	0.143 295	0.085 313	0.115 320
DCP 2	.020	3.176	1.920 160	0.476 178	0.424 188	0.190 222	0.144 262	0.129 309	0.140 323	0.131 341	0.113 3
DCP 3	.030	2.780	1.669 193	0.564 206	0.295 180	0.295 220	0.144 268	0.092 260	0.122 302	0.077 334	0.065 344
DCP 4	.049	3.311	0.865 154	0.398 141	0.229 192	0.143 161	0.108 150	0.078 145	0.030 124	0.051 194	0.042 156
DCP 5	.074	2.756	0.826 141	0.286 121	0.162 138	0.099 144	0.085 115	0.066 119	0.075 87	0.030 188	0.029 134
DCP 6	.099	2.418	0.797 129	0.219 115	0.181 124	0.077 109	0.086 100	0.031 83	0.035 84	0.019 155	0.026 115
DCP 7	.149	1.922	0.613 135	0.198 117	0.143 105	0.091 112	0.074 98	0.057 91	0.035 62	0.022 128	0.012 116
DCP 8	.200	1.576	0.598 108	0.269 109	0.177 109	0.147 98	0.116 98	0.065 89	0.038 89	0.051 106	0.023 122
DCP 9	.250	1.435	0.571 99	0.286 97	0.181 100	0.157 80	0.110 93	0.088 73	0.051 87	0.050 71	0.035 105
DCP10	.300	1.291	0.518 91	0.245 88	0.177 97	0.146 80	0.117 85	0.067 77	0.054 77	0.051 82	0.032 101
DCP11	.399	1.119	0.458 82	0.201 76	0.145 85	0.116 74	0.099 73	0.047 72	0.048 69	0.074 73	0.032 81
DCP12	.501	0.991	0.393 69	0.177 56	0.106 62	0.092 44	0.083 46	0.078 42	0.049 39	0.070 33	0.039 59
DCP13	.600	0.746	0.361 58	0.159 45	0.094 41	0.082 22	0.076 24	0.078 16	0.036 5	0.065 11	0.031 32
DCP14	.701	0.636	0.309 46	0.139 36	0.079 11	0.071 7	0.069 359	0.071 359	0.033 335	0.044 345	0.028 354
DCP15	.800	0.463	0.254 31	0.129 29	0.069 356	0.055 8	0.063 341	0.056 337	0.026 296	0.036 322	0.027 317
DCP16	.900	0.184	0.159 25	0.098 10	0.048 355	0.025 354	0.038 330	0.036 320	0.012 303	0.023 334	0.025 294
DCP17	.969	0.041	0.064 31	0.046 25	0.011 14	0.011 3	0.016 334	0.011 334	0.006 299	0.009 346	0.012 321

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	5.0	23.18	0.118	0.298	5.07	0.0	19.95	12009.9	20

			RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	100.4	26607.	3.48E 07	-0.201	1.591	16.52	-0.00417	3.389	0.0
	(329.3)	(555.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		19.946	5.305 0	0.215 4	0.059 245	0.012 251	0.013 6	0.031 298	0.030 193	0.002 105	0.006 21
CN		1.058	3.315 100	0.068 133	0.060 150	0.034 167	0.032 162	0.028 177	0.019 184	0.003 146	0.002 171
CM		-0.065	0.065 294	0.022 242	0.018 274	0.011 294	0.010 307	0.008 335	0.003 349	0.001 241	0.002 349
DCP 1	.015	2.614	1.651 161	0.585 228	0.224 248	0.229 297	0.113 11	0.039 54	0.055 91	0.043 111	0.023 148
DCP 2	.030	2.480	1.197 161	0.464 232	0.193 248	0.159 307	0.067 2	0.02 53	0.021 106	0.045 121	0.018 228
DCP 3	.045	2.276	0.981 155	0.401 227	0.235 283	0.096 325	0.029 19	0.032 59	0.091 154	0.033 192	0.016 213
DCP 4	.060	2.913	0.843 164	0.144 221	0.251 228	0.056 243	0.066 257	0.013 291	0.015 136	0.038 58	0.037 32
DCP 5	.074	2.433	0.616 144	0.117 253	0.187 221	0.026 196	0.061 226	0.034 151	0.017 193	0.029 56	0.033 4
DCP 6	.399	2.119	0.514 126	0.090 229	0.097 213	0.061 202	0.043 732	0.012 155	0.026 154	0.017 69	0.012 62
DCP 7	.149	1.734	0.412 99	0.101 150	0.090 190	0.058 187	0.031 193	0.013 165	0.015 213	0.009 148	0.012 29
DCP 8	.200	1.471	0.408 104	0.132 157	0.116 174	0.053 212	0.058 206	0.040 239	0.027 230	0.010 256	0.008 340
DCP 9	.250	1.367	0.428 104	0.125 148	0.133 157	0.085 192	0.067 188	0.050 218	0.041 218	0.027 265	0.005 343
DCP10	.300	1.255	0.399 98	0.122 141	0.119 149	0.081 190	0.059 192	0.049 212	0.032 210	0.023 250	0.009 298
DCP11	.349	1.147	0.391 94	0.101 130	0.117 139	0.077 167	0.053 187	0.057 201	0.034 214	0.021 253	0.006 239
DCP12	.501	0.959	0.359 84	0.087 102	0.098 125	0.063 161	0.051 162	0.050 171	0.037 180	0.017 214	0.008 247
DCP13	.600	0.812	0.334 74	0.086 74	0.075 136	0.054 127	0.058 138	0.045 162	0.026 153	0.024 140	0.017 189
DCP14	.701	0.712	0.313 65	0.094 60	0.071 98	0.046 109	0.046 116	0.034 147	0.011 130	0.022 90	0.009 144
DCP15	.800	0.455	0.251 62	0.074 52	0.056 90	0.045 96	0.041 116	0.036 142	0.014 189	0.015 28	0.011 117
DCP16	.900	0.247	0.166 62	0.066 39	0.029 62	0.030 72	0.027 97	0.023 126	0.011 129	0.016 6	0.006 101
DCP17	.969	0.072	0.083 71	0.013 60	0.013 95	0.012 80	0.011 117	0.007 131	0.004 122	0.003 228	0.012 204

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	5.0	45.80	0.225	0.535	5.53	0.0	-0.01	12011.1	20

			RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	103.8	27952.	3.44E 07	-0.049	0.494	5.56	-0.00091	0.782	0.0
	(340.4)	(583.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		-0.004	5.529 0	0.305 5	0.105 298	0.044 238	0.043 107	0.038 60	0.023 197	0.012 239	0.009 89
CN		0.116	0.393 3	0.016 41	0.007 12	0.012 235	0.003 245	0.002 248	0.002 7	0.001 137	0.001 189
CM		-0.016	0.027 294	0.004 247	0.001 258	0.005 139	0.000 111	0.001 137	0.001 162	0.001 127	0.000 61
DCP 1	.015	-0.055	2.914 346	0.209 22	0.023 51	0.061 147	0.006 1	0.012 142	0.036 110	0.007 127	0.011 70
DCP 2	.030	-0.365	2.114 350	0.086 356	0.027 342	0.059 165	0.005 338	0.009 150	0.008 301	0.008 173	0.004 199
DCP 4	.250	-0.028	1.754 349	0.382 342	0.029 314	0.039 164	0.009 293	0.004 128	0.005 294	0.006 132	0.006 156
DCP 4	.047	-0.002	1.427 351	0.047 345	0.016 329	0.039 159	0.016 297	0.005 112	0.004 303	0.004 77	0.006 110
DCP 5	.074	0.253	1.136 351	0.044 355	0.013 352	0.034 153	0.035 260	0.006 141	0.005 34	0.006 136	0.004 62
DCP 5	.099	0.169	0.907 353	0.043 6	0.017 341	0.005 162	0.010 263	0.003 127	0.005 342	0.001 119	0.007 152
DCP 7	.149	0.027	0.776 355	0.034 16	0.017 342	0.028 165	0.007 251	0.007 135	0.005 125	0.009 110	0.003 266
DCP 8	.200	0.19	0.599 2	0.026 31	0.012 16	0.003 159	0.006 327	0.004 122	0.005 63	0.006 109	0.007 169
DCP 8	.250	0.155	0.516 1	0.027 14	0.005 33	0.018 247	0.003 153	0.005 22	0.001 254	0.009 113	0.002 110
DCP11	.300	0.108	0.403 3	0.014 38	0.006 7	0.017 247	0.006 343	0.003 20	0.001 213	0.003 134	0.003 165
DCP11	.349	0.101	0.351 16	0.021 60	0.010 23	0.021 266	0.006 354	0.006 53	0.003 200	0.004 161	
DCP12	.501	0.114	0.271 22	0.020 71	0.006 63	0.021 276	0.002 208	0.005 301	0.004 71	0.008 266	0.002 313
DCP13	.601	0.169	0.215 20	0.014 89	0.012 19	0.023 274	0.032 2	0.012 298	0.034 27	0.033 265	0.034 265
DCP14	.701	0.190	0.153 37	0.011 91	0.007 26	0.012 274	0.004 275	0.006 247	0.006 319	0.001 72	0.032 126
DCP15	.800	0.142	0.121 46	0.015 133	0.005 77	0.045 261	0.005 296	0.006 272	0.007 332	0.005 354	0.006 213
DCP16	.900	0.103	0.066 73	0.013 98	0.032 236	0.014 254	0.032 316	0.008 149	0.004 261	0.001 268	0.003 221
DCP17	.969	0.042	0.022 161	0.004 171	0.007 167	0.017 311	0.005 129	0.007 334	0.004 123	0.001 316	0.007 6

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.79	0.227	0.303	5.52	0.0	2.43	12011.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
102.6	27435.	0.49E 07	-0.046	0.742	8.02	-0.00090	0.766	0.0
(336.5)	(573.0)							

HARMONIC ANALYSIS

DATA TYPE	R/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.433	5.524 0	0.314 4	0.109 297	0.017 199	0.036 90	0.031 66	0.029 213	0.014 208	0.009 126
CN		0.349	0.392 3	0.022 27	0.006 12	0.013 178	0.002 344	0.003 118	0.003 270	0.002 147	0.001 212
CM		-0.012	0.027 292	0.003 272	0.002 307	0.005 7	0.002 185	0.001 283	0.001 90	0.001 311	0.001 25
DCP 1	.010	0.981	2.707 344	0.141 0	0.038 335	0.012 69	0.008 238	0.005 124	0.001 274	0.003 176	0.009 29
DCP 2	.020	0.841	2.110 349	0.106 4	0.060 332	0.009 77	0.012 160	0.007 97	0.005 214	0.002 242	0.009 0
DCP 3	.030	0.966	1.775 349	0.082 356	0.049 330	0.007 93	0.001 114	0.006 205	0.008 131	0.002 84	0.008 261
DCP 4	.049	0.910	1.463 350	0.059 352	0.023 350	0.010 68	0.007 208	0.003 2	0.012 253	0.006 209	0.005 16
DCP 5	.074	0.918	1.153 351	0.049 357	0.022 339	0.006 82	0.010 216	0.003 309	0.009 225	0.004 158	0.004 30
DCP 6	.099	0.915	0.984 353	0.048 10	0.019 339	0.011 58	0.004 223	0.004 275	0.004 175	0.007 203	0.003 107
DCP 7	.149	0.651	0.735 355	0.030 5	0.012 11	0.003 198	0.005 48	0.008 84	0.007 90	0.005 138	0.004 25
DCP 8	.200	0.543	0.605 1	0.024 14	0.012 351	0.002 91	0.001 248	0.000 203	0.010 326	0.007 289	0.001 326
DCP 9	.250	0.459	0.521 1	0.032 14	0.007 21	0.018 161	0.004 161	0.003 195	0.004 264	0.001 164	0.005 226
DCP10	.300	0.443	0.437 2	0.028 31	0.012 356	0.020 172	0.001 212	0.004 120	0.005 286	0.002 163	0.004 106
DCP11	.399	0.387	0.349 14	0.028 55	0.008 39	0.021 190	0.003 183	0.009 123	0.004 270	0.008 85	0.005 164
DCP12	.501	0.262	0.270 22	0.021 53	0.009 16	0.013 186	0.005 295	0.005 142	0.001 274	0.003 155	0.004 299
DCP13	.600	0.254	0.208 29	0.013 21	0.006 40	0.011 173	0.009 337	0.006 168	0.011 282	0.004 205	0.006 272
DCP14	.701	0.267	0.154 37	0.017 72	0.011 116	0.019 179	0.005 353	0.004 304	0.003 254	0.007 110	0.004 126
DCP15	.800	0.140	0.170 49	0.010 62	0.003 68	0.015 165	0.008 10	0.006 69	0.006 281	0.003 345	0.004 154
DCP16	.900	-0.070	0.065 62	0.014 98	0.009 151	0.020 198	0.005 76	0.002 199	0.001 296	0.008 200	0.006 204
DCP17	.969	-0.045	0.022 50	0.008 326	0.004 235	0.023 197	0.011 359	0.006 58	0.009 134	0.006 75	0.002 271

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.75	0.230	0.300	5.54	0.0	5.01	12011.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
101.5	26947.	0.48E 07	-0.043	0.972	10.59	-0.00094	0.789	0.0
(332.9)	(562.8)							

HARMONIC ANALYSIS

DATA TYPE	R/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		5.014	5.535 0	0.313 5	0.096 297	0.040 27	0.032 78	0.019 79	0.026 193	0.006 201	0.007 93
CN		0.596	0.388 4	0.024 31	0.009 358	0.011 80	0.003 289	0.002 22	0.002 90	0.001 100	0.003 214
CM		-0.009	0.028 293	0.003 264	0.001 235	0.005 248	0.001 91	0.001 152	0.001 265	0.000 209	0.001 16
DCP 1	.010	2.546	2.603 344	0.137 11	0.075 316	0.049 204	0.007 86	0.007 115	0.007 30	0.007 265	0.004 229
DCP 2	.020	2.110	2.110 350	0.095 3	0.022 325	0.022 201	0.008 13	0.010 172	0.004 6	0.010 208	0.003 264
DCP 3	.030	2.022	1.777 349	0.079 3	0.019 322	0.009 158	0.008 319	0.005 163	0.003 212	0.007 188	0.002 249
DCP 4	.049	1.799	1.471 350	0.060 359	0.023 329	0.014 193	0.008 310	0.009 190	0.003 258	0.009 180	0.006 226
DCP 5	.074	1.629	1.161 351	0.054 4	0.022 332	0.014 205	0.006 328	0.005 172	0.001 238	0.005 182	0.005 214
DCP 6	.099	1.514	0.978 353	0.050 8	0.016 334	0.015 199	0.010 351	0.003 132	0.003 286	0.008 129	0.003 230
DCP 7	.149	1.110	0.719 356	0.035 14	0.020 336	0.011 195	0.008 247	0.007 181	0.001 270	0.007 88	0.007 289
DCP 8	.200	0.912	0.599 2	0.034 27	0.007 348	0.017 181	0.006 348	0.002 213	0.006 246	0.004 306	0.005 228
DCP 9	.250	0.768	0.516 2	0.037 17	0.016 21	0.019 31	0.004 120	0.001 332	0.003 185	0.002 27	0.004 312
DCP10	.300	0.711	0.432 5	0.028 33	0.013 359	0.016 41	0.007 185	0.015 77	0.002 50	0.002 274	0.005 154
DCP11	.399	0.601	0.349 17	0.027 51	0.009 10	0.021 62	0.006 207	0.009 56	0.005 108	0.004 144	0.003 278
DCP12	.501	0.428	0.274 23	0.016 55	0.011 37	0.016 73	0.007 260	0.007 22	0.006 91	0.003 271	0.003 264
DCP13	.600	0.377	0.215 29	0.024 52	0.004 345	0.015 75	0.002 67	0.006 52	0.002 90	0.005 47	0.004 205
DCP14	.701	0.353	0.144 41	0.020 71	0.007 8	0.020 76	0.004 330	0.015 266	0.004 73	0.002 48	0.009 166
DCP15	.800	0.192	0.131 53	0.017 59	0.007 43	0.018 65	0.009 246	0.010 296	0.004 67	0.003 60	0.007 150
DCP16	.900	-0.040	0.044 70	0.009 55	0.004 50	0.013 33	0.009 42	0.005 34	0.008 75	0.001 2	0.010 276
DCP17	.969	-0.051	0.026 154	0.005 283	0.001 37	0.026 113	0.017 270	0.003 90	0.004 141	0.001 284	0.008 183

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	45.79	0.231	0.299	5.53	0.0	7.50	12011.4	20

	V	Q	RN	CM(MIN)	CM(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	101.0	26765.	0.48E 07	-0.039	1.193	13.05	-0.00103	0.862	0.0
	(331.3)	(559.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.503	5.533 0	0.315 6	0.093 293	0.038 37	0.029 66	0.014 81	0.024 204	0.010 253	0.008 124
CN		0.820	0.374 6	0.028 26	0.005 52	0.017 62	0.005 278	0.003 327	0.001 247	0.002 222	0.002 175
CM		-0.004	0.031 243	0.002 262	0.002 295	0.005 227	0.001 107	0.002 139	0.001 234	0.000 331	0.001 330
DCP 1	.010	4.010	2.482 345	0.151 353	0.042 163	0.115 52	0.056 302	0.006 265	0.026 239	0.006 158	0.011 235
DCP 2	.020	3.267	2.025 350	0.115 20	0.057 337	0.015 156	0.016 257	0.002 70	0.013 261	0.006 127	0.006 327
DCP 3	.030	3.036	1.756 350	0.088 359	3.024 345	0.004 100	0.010 258	0.013 166	0.009 221	0.004 155	0.003 234
DCP 4	.049	2.661	1.444 351	0.069 10	0.033 339	0.014 128	0.006 260	0.015 157	0.010 238	0.002 254	0.005 37
DCP 5	.074	2.295	1.136 352	0.066 12	0.022 332	0.014 125	0.006 246	0.008 149	0.003 284	0.013 270	0.00
DCP 6	.099	2.067	0.948 354	0.055 9	0.021 343	0.017 121	0.009 220	0.006 127	0.007 241	0.009 274	0.006 33
DCP 7	.149	1.524	0.715 357	0.049 19	0.011 332	0.018 124	0.009 319	0.006 29	0.009 194	0.008 250	0.004 288
DCP 8	.200	1.248	0.585 4	0.036 20	0.015 26	0.004 120	0.006 264	0.008 244	0.011 266	0.006 174	0.006 206
DCP 9	.250	1.061	0.505 4	0.028 31	0.004 340	0.017 34	0.006 184	0.001 55	0.006 216	0.006 114	0.016 231
DCP10	.300	0.953	0.414 8	0.035 28	0.003 18	0.017 54	0.002 96	0.006 203	0.006 266	0.004 143
DCP11	.399	0.792	0.335 20	0.037 47	0.012 87	0.020 70	0.006 265	0.008 339	0.006 276	0.004 229	0.005 94
DCP12	.501	0.573	0.265 28	0.022 60	0.009 66	0.017 48	0.007 257	0.006 336	0.004 61	0.009 336	0.004 219
DCP13	.600	0.482	0.206 39	0.016 41	0.008 127	0.023 49	0.008 310	0.011 11	0.007 103	0.006 149	0.004 145
DCP14	.701	0.426	0.145 50	0.020 44	0.009 96	0.023 54	0.009 274	0.008 323	0.007 24	0.003 32	0.006 106
DCP15	.800	0.230	0.104 61	0.011 54	0.012 87	0.023 56	0.003 317	0.009 279	0.002 258	0.002 244	0.002 27
DCP16	.900	-0.029	0.053 70	0.006 73	0.010 147	0.011 47	0.005 221	0.006 277	0.009 20	0.006 164	0.006 173
DCP17	.969	-0.057	0.016 122	0.005 289	0.003 304	0.016 48	0.007 348	0.004 104	0.009 156	0.003 146	0.002 288

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	45.76	0.232	0.298	5.51	0.0	10.00	12011.5	20

	V	Q	RN	CM(MIN)	CM(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	100.6	26617.	0.48E 07	-0.067	1.410	15.18	-0.00075	0.630	0.0
	(330.1)	(555.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		10.003	5.505 0	0.340 4	0.105 289	0.036 256	0.030 69	0.019 60	0.022 192	0.005 292	0.004 152
CN		0.947	0.446 20	0.030 228	0.040 34	0.036 297	0.024 165	0.022 46	0.014 277	0.006 156	0.004 443
CM		-0.008	0.021 243	0.027 351	0.016 202	0.012 55	0.006 322	0.004 198	0.005 60	0.003 306	0.002 155
DCP 1	.010	4.385	1.706 16	0.975 11	0.561 270	0.296 161	0.210 105	0.062 357	0.075 192	0.095 111	0.096 50
DCP 2	.020	3.569	1.399 27	0.897 17	0.557 275	0.310 172	0.183 90	0.065 37	0.075 16	0.095 295	0.091 197
DCP 3	.030	3.116	1.247 36	0.862 9	0.432 298	0.133 155	0.114 143	0.102 55	0.113 327	0.063 204	0.067 211
DCP 4	.049	3.117	1.377 6	0.161 351	0.034 261	0.093 55	0.013 326	0.008 290	0.011 119	0.003 103	0.009 240
DCP 5	.074	2.653	1.061 8	0.134 349	0.023 233	0.025 25	0.012 267	0.004 275	0.011 198	0.006 25	0.034 274
DCP 6	.099	2.350	0.942 11	0.128 338	0.023 202	0.006 27	0.008 210	0.004 131	0.010 126	0.010 326	0.010 292
DCP 7	.149	1.746	0.757 16	0.122 312	0.056 151	0.052 10	0.021 244	0.003 67	0.004 206	0.011 15	0.005 228
DCP 8	.200	1.477	0.726 17	0.138 269	0.104 114	0.075 355	0.033 238	0.016 124	0.006 75	0.007 319	0.006 109
DCP 9	.250	1.313	0.715 10	0.195 229	3.159 86	0.067 312	0.044 213	0.023 136	0.031 15	0.026 253	0.004 143
DCP10	.300	1.174	0.628 9	0.192 220	0.146 78	0.085 299	0.050 201	0.043 63	0.030 319	0.023 167	0.014 7
DCP11	.399	0.960	0.496 16	0.145 212	0.132 71	0.086 295	0.060 195	0.042 72	0.027 312	0.029 196	0.007 111
DCP12	.501	0.679	0.361 29	0.114 179	0.115 34	0.074 259	0.066 185	0.062 30	0.040 281	0.029 159	0.015 29
DCP13	.600	0.528	0.292 87	0.087 172	0.102 17	0.060 233	0.080 129	0.011 36	0.033 266	0.026 158	0.017 17
DCP14	.701	0.437	0.227 53	0.066 161	0.072 359	0.059 211	0.017 124	0.022 1	0.029 248	0.016 144	0.010 6
DCP15	.800	0.250	0.138 51	0.069 149	0.064 338	0.065 196	0.013 123	0.015 31	0.026 231	0.019 77	0.018 275
DCP16	.900	0.001	0.070 17	0.094 128	0.033 312	0.013 209	0.011 87	0.011 290	0.016 170	0.007 60	0.015 283
DCP17	.969	-0.046	0.022 17	0.017 164	0.015 311	0.023 213	0.015 40	0.007 306	0.008 107	0.005 8	0.008 40

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ 0.0	DRIVE HZ 45.71	K 0.232	MACH NO 0.297	DEL.ALPHA 5.43	DEL.H 0.0	ALPHA.0 12.49	TEST POINT 12011.6	CYCLES ANALYSED 20
	V 100.4 (329.5)	Q 26530. (554.1)	RN 0.48E 07	CN(MIN) -0.201	CN(MAX) 1.813	ALPHA.NMAX 17.98	AERO DAMP 0.00019	TDR -0.156	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.488	5.428 0	0.415 9	0.173 274	0.070 337	0.042 73	0.010 80	0.024 238	0.006 76	0.006 121
CN		1.044	0.569 35	0.138 268	0.069 169	0.020 105	0.024 359	0.018 277	0.006 251	0.005 284	0.009 215
CM		-0.033	0.067 178	0.057 27	0.026 287	0.012 178	0.010 130	0.009 34	0.005 295	0.003 219	0.002 144
DCP 1	.010	3.968	1.514 90	1.277 36	0.192 17	0.356 349	0.284 295	0.236 266	0.171 223	0.082 194	0.071 124
DCP 2	.020	3.438	1.412 79	1.035 34	0.133 339	0.187 355	0.214 305	0.220 265	0.174 216	0.108 180	0.113 156
DCP 3	.030	3.062	1.220 63	0.932 38	0.200 357	0.231 339	0.228 284	0.156 244	0.139 212	0.110 168	0.079 142
DCP 4	.049	3.129	1.172 50	0.643 18	0.290 292	0.195 214	0.069 152	0.052 142	0.073 98	0.072 26	0.049 328
DCP 5	.074	2.685	1.052 50	0.510 3	0.247 265	0.129 189	0.049 127	0.035 108	0.050 59	0.045 343	0.036 278
DCP 6	.099	2.412	1.039 48	0.442 347	0.185 240	0.102 160	0.051 128	0.033 80	0.042 32	0.031 327	0.020 291
DCP 7	.149	1.890	1.011 41	0.407 321	0.155 223	0.109 163	0.073 109	0.026 61	0.030 37	0.030 338	0.031 277
DCP 8	.200	1.600	0.958 41	0.391 317	0.175 228	0.126 173	0.056 127	0.061 82	0.069 6	0.046 323	0.041 272
DCP 9	.250	1.433	0.975 32	0.395 294	0.193 205	0.123 150	0.066 68	0.077 43	0.079 321	0.045 269	0.051 235
DCP10	.300	1.292	0.867 29	0.372 282	0.196 191	0.126 127	0.062 66	0.080 18	0.083 307	0.067 257	0.079 196
DCP11	.349	1.097	0.765 31	0.310 276	0.178 169	0.138 132	0.111 55	0.105 342	0.084 284	0.072 225	0.069 170
DCP12	.501	0.825	0.629 26	0.265 249	0.164 156	0.109 61	0.096 14	0.118 300	0.088 219	0.066 158	0.060 93
DCP13	.600	0.668	0.503 22	0.254 223	0.150 123	0.096 40	0.099 336	0.109 256	0.090 171	0.066 93	0.049 30
DCP14	.701	0.544	0.366 19	0.225 201	0.151 93	0.112 350	0.077 283	0.085 203	0.057 106	0.047 24	0.039 311
DCP15	.800	0.355	0.266 4	0.196 165	0.113 60	0.097 321	0.057 264	0.070 162	0.045 66	0.027 359	0.028 289
DCP16	.900	0.067	0.153 348	0.089 178	0.068 75	0.052 295	0.036 249	0.039 152	0.039 66	0.024 312	0.022 219
DCP17	.969	-0.011	0.057 347	0.036 186	0.032 77	0.037 256	0.018 244	0.022 151	0.013 58	0.015 345	0.025 325

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ 0.0	DRIVE HZ 45.67	K 0.233	MACH NO 0.296	DEL.ALPHA 5.39	DEL.H 0.0	ALPHA.0 15.03	TEST POINT 12011.7	CYCLES ANALYSED 20
	V 100.0 (328.0)	Q 26358. (550.5)	RN 0.48E 07	CN(MIN) -0.260	CN(MAX) 7.033	ALPHA.NMAX 19.83	AERO DAMP 0.00045	TDR -0.371	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		15.027	5.390 0	0.391 18	0.189 313	0.071 77	0.037 107	0.016 9	0.016 168	0.031 220	0.011 226
CN		1.177	0.608 42	0.130 334	0.069 249	0.034 203	0.012 196	0.013 106	0.004 96	0.008 66	0.014 34
CM		-0.061	0.114 177	0.063 59	0.033 343	0.006 270	0.003 249	0.009 216	0.005 117	0.003 64	0.002 204
DCP 1	.010	4.013	1.980 124	0.967 67	0.349 87	0.426 96	0.365 49	0.213 50	0.149 12	0.078 30	0.054 322
DCP 2	.020	3.352	1.634 113	0.898 63	0.194 69	0.244 101	0.258 51	0.184 43	0.193 16	0.122 10	0.124 351
DCP 3	.030	3.144	1.450 117	0.776 69	0.340 60	0.205 50	0.190 48	0.153 13	0.117 18	0.114 355	0.082 343
DCP 4	.049	3.270	0.933 87	0.716 62	0.241 11	0.136 14	0.167 331	0.151 263	0.091 249	0.074 239	0.082 205
DCP 5	.074	2.867	0.983 74	0.536 17	0.150 335	0.090 354	0.156 302	0.141 250	0.067 203	0.056 191	0.064 164
DCP 6	.099	2.594	1.067 68	0.504 17	0.159 312	0.058 324	0.133 293	0.137 263	0.094 191	0.054 171	0.049 157
DCP 7	.149	2.039	1.071 58	0.436 3	0.267 309	0.164 239	0.070 240	0.084 226	0.080 176	0.061 130	0.046 62
DCP 8	.200	1.723	0.973 57	0.425 11	0.313 308	0.133 236	0.066 247	0.080 215	0.072 181	0.053 143	0.044 122
DCP 9	.250	1.566	0.969 48	0.395 354	0.300 292	0.156 263	0.122 227	0.110 189	0.107 146	0.093 107	0.091 60
DCP10	.300	1.411	0.873 43	0.342 349	0.289 282	0.177 236	0.147 197	0.110 156	0.103 108	0.089 71	0.089 19
DCP11	.399	1.245	0.820 39	0.267 332	0.257 274	0.197 227	0.166 177	0.135 126	0.123 79	0.094 35	0.071 358
DCP12	.501	1.003	0.749 27	0.246 292	0.238 234	0.159 181	0.122 125	0.129 82	0.127 21	0.096 333	0.064 261
DCP13	.600	0.849	0.686 19	0.279 261	0.219 193	0.124 132	0.097 73	0.102 41	0.138 329	0.071 270	0.046 203
DCP14	.701	0.704	0.554 11	0.295 235	0.219 155	0.112 76	0.080 19	0.087 344	0.075 255	0.047 209	0.048 106
DCP15	.800	0.461	0.412 359	0.249 222	0.205 132	0.099 30	0.077 322	0.035 298	0.047 211	0.028 156	0.027 52
DCP16	.900	0.140	0.243 347	0.133 209	0.107 102	0.052 349	0.036 245	0.029 331	0.033 208	0.027 128	0.025 137
DCP17	.969	0.035	0.123 343	0.066 213	0.067 92	0.046 330	0.024 233	0.008 23	0.018 263	0.022 216	0.013 117

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

| | TUNED HZ
0.0 | DRIVE HZ
45.77 | X
0.234 | MACH NO
0.296 | DEL.ALPHA
5.37 | DEL.H
0.0 | ALPHA.0
17.45 | TEST POINT
12011.8 | CYCLES ANALYSED
20 |
| | V
99.8
(327.3) | Q
26286.
(549.0) | RN
0.48E 07 | CN(MIN)
-0.315 | CN(MAX)
2.155 | ALPHA.NMAX
20.86 | AERO DAMP
0.00013 | TDR
-0.111 | EXT DAMP
5.0 |

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		17.454	5.372	0	0.326	21	0.145	357	0.148	149	0.022	191	0.019	15	0.017	177	0.016	314	0.014	187
CN		1.240	0.656	49	0.127	16	0.095	310	0.021	212	0.026	306	0.024	228	0.008	267	0.008	218	0.013	205
CM		-0.080	0.141	182	0.051	98	0.038	47	0.022	321	0.003	326	0.006	326	0.007	221	0.003	232	0.002	5
DCP 1	.010	3.791	2.378	137	0.764	103	0.424	130	0.291	177	0.322	164	0.198	166	0.131	152	0.071	174	0.058	120
DCP 2	.020	3.430	2.033	129	0.687	95	0.327	99	0.084	222	0.210	158	0.153	179	0.204	172	0.142	183	0.155	167
DCP 3	.030	2.964	1.772	127	0.558	120	0.440	100	0.207	160	0.255	126	0.194	139	0.099	143	0.115	138	0.066	167
DCP 4	.049	3.335	1.037	102	0.563	94	0.252	78	0.225	62	0.183	18	0.090	17	0.076	12	0.069	6	0.057	6
DCP 5	.074	2.903	1.078	86	0.324	71	0.194	62	0.184	44	0.195	0	0.101	333	0.058	328	0.056	340	0.055	343
DCP 6	.099	2.631	1.188	78	0.300	51	0.215	37	0.140	35	0.212	357	0.127	322	0.079	296	0.045	313	0.036	309
DCP 7	.149	2.105	1.084	70	0.437	55	0.401	359	0.160	315	0.087	328	0.117	337	0.102	296	0.067	274	0.028	286
DCP 8	.200	1.800	1.103	68	0.457	52	0.376	352	0.158	311	0.063	347	0.107	333	0.080	312	0.066	294	0.057	295
DCP 9	.250	1.646	1.334	58	0.450	37	0.375	334	0.144	306	0.066	324	0.120	297	0.096	280	0.076	255	0.071	243
DCP10	.300	1.440	0.415	53	0.382	34	0.356	335	0.191	295	0.133	292	0.121	257	0.106	241	0.073	221	0.075	200
DCP11	.399	1.336	0.513	44	0.285	19	0.318	326	0.184	281	0.158	276	0.155	235	0.119	208	0.094	198	0.081	189
DCP12	.501	1.122	0.890	31	0.249	336	0.284	286	0.171	229	0.156	216	0.156	183	0.125	135	0.087	122	0.063	95
DCP13	.600	0.954	0.811	21	0.266	303	0.260	248	0.179	181	0.085	171	0.113	147	0.111	87	0.077	61	0.034	359
DCP14	.701	0.779	0.669	11	0.249	270	0.241	209	0.178	137	0.075	96	0.067	84	0.083	21	0.043	3	0.033	287
DCP15	.800	0.528	0.510	2	0.231	255	0.197	181	0.168	108	0.079	48	0.034	17	0.058	321	0.007	324	0.008	166
DCP16	.900	0.196	0.213	355	0.103	245	0.076	173	0.094	69	0.036	28	0.026	21	0.043	326	0.015	290	0.011	180
DCP17	.969	0.050	0.116	356	0.061	226	0.050	142	0.060	71	0.020	297	0.029	142	0.033	37	0.033	333	0.023	248

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

| | TUNED HZ
0.0 | DRIVE HZ
45.75 | X
0.234 | MACH NO
0.295 | DEL.ALPHA
5.35 | DEL.H
0.0 | ALPHA.0
19.94 | TEST POINT
12011.9 | CYCLES ANALYSED
20 |
| | V
99.4
(326.2) | Q
26090.
(544.9) | RN
0.48E 07 | CN(MIN)
-0.346 | CN(MAX)
2.182 | ALPHA.NMAX
22.32 | AERO DAMP
-0.00069 | TDR
0.572 | EXT DAMP
0.0 |

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		19.936	5.352	0	0.241	14	0.086	79	0.144	196	0.013	340	0.009	86	0.014	190	0.022	124	0.008	209
CN		1.250	0.658	54	0.122	50	0.140	355	0.022	274	0.017	22	0.014	350	0.009	297	0.009	348	0.009	307
CM		-0.100	0.149	188	0.047	136	0.045	105	0.019	17	0.005	356	0.005	25	0.005	3	0.001	276	0.002	116
DCP 1	.010	3.406	2.280	138	0.803	160	0.271	149	0.355	221	0.286	241	0.162	247	0.118	244	0.059	264	0.051	246
DCP 2	.020	3.162	1.893	133	0.619	150	0.267	106	0.170	233	0.157	249	0.167	270	0.146	278	0.148	301	0.109	303
DCP 3	.030	2.875	1.561	134	0.634	171	0.241	133	0.222	210	0.149	238	0.121	231	0.109	265	0.098	295	0.062	296
DCP 4	.049	2.995	1.310	116	0.441	131	0.324	108	0.102	133	0.190	120	0.083	94	0.079	130	0.049	132	0.053	153
DCP 5	.074	2.448	1.182	99	0.338	123	0.282	76	0.078	116	0.156	95	0.099	81	0.067	82	0.042	118	0.056	114
DCP 6	.099	2.465	1.101	86	0.331	111	0.285	59	0.106	89	0.169	88	0.152	44	0.088	43	0.026	76	0.056	106
DCP 7	.149	2.041	1.052	73	0.423	88	0.324	38	0.135	31	0.122	56	0.097	31	0.046	47	0.056	52	0.052	42
DCP 8	.200	1.776	0.937	73	0.435	84	0.338	44	0.119	16	0.089	59	0.069	56	0.053	88	0.060	74	0.043	62
DCP 9	.250	1.652	0.941	64	0.456	70	0.388	28	0.167	1	0.121	17	0.095	25	0.087	9	0.071	3	0.042	345
DCP10	.300	1.520	0.876	56	0.402	62	0.389	21	0.194	353	0.149	355	0.105	358	0.086	336	0.066	331	0.045	323
DCP11	.399	1.409	0.919	47	0.318	45	0.370	13	0.182	343	0.169	334	0.126	330	0.098	309	0.079	303	0.072	285
DCP12	.501	1.189	0.910	35	0.274	8	0.326	336	0.151	296	0.131	286	0.122	275	0.100	250	0.085	230	0.065	228
DCP13	.600	1.001	0.856	27	0.271	337	0.302	303	0.159	241	0.098	232	0.089	227	0.061	206	0.058	167	0.030	193
DCP14	.701	0.827	0.716	17	0.240	305	0.267	271	0.160	195	0.096	158	0.055	146	0.047	137	0.039	96	0.015	48
DCP15	.800	0.590	0.518	11	0.176	287	0.193	251	0.166	170	0.104	126	0.053	95	0.027	59	0.024	17	0.004	311
DCP16	.900	0.261	0.289	5	0.088	253	0.079	234	0.076	143	0.045	109	0.036	131	0.034	89	0.022	345	0.013	337
DCP17	.969	0.085	0.143	10	0.062	251	0.047	203	0.070	116	0.035	24	0.025	233	0.045	168	0.036	87	0.041	2

FORCED PITCHING OSCILLATION — AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	69.07	0.333	0.310	5.95	0.0	0.03	12013.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
105.5	28733.	0.50E 07	-0.062	0.485	6.04	-3.00086	0.775	0.0
(346.0)	(600.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.035	5.953 0	0.520 343	0.151 203	0.077 136	0.016 189	0.016 27	0.010 223	0.018 97	0.006 41
CN		0.113	0.367 16	0.038 33	0.006 267	0.002 244	0.005 275	0.001 172	0.003 201	0.003 190	0.002 127
CM		-0.016	0.041 293	0.008 280	0.001 161	0.001 141	0.001 142	0.000 359	0.001 34	0.000 38	0.001 279
DCP 1	.010	-0.452	2.756 344	0.280 357	0.057 134	0.019 97	0.025 154	0.006 190	0.007 315	0.010 92	0.011 127
DCP 2	.020	-0.355	1.991 353	0.169 344	0.032 201	0.004 141	0.013 198	0.006 167	0.009 239	0.004 39	0.007 156
DCP 3	.030	-0.046	1.648 353	0.135 337	0.024 219	0.007 197	0.014 214	0.003 26	0.003 194	0.001 217	0.005 154
DCP 4	.049	0.067	1.336 355	0.108 340	0.026 207	0.008 174	0.011 176	0.007 262	0.006 106	0.006 212	0.007 20
DCP 5	.074	0.243	1.070 356	0.093 350	0.023 197	0.007 165	0.006 186	0.003 355	0.004 77	0.004 171	0.002 138
DCP 6	.099	0.335	0.924 359	0.080 355	0.022 231	0.006 131	0.012 209	0.002 16	0.005 147	0.003 316	0.004 175
DCP 7	.149	0.210	0.687 3	0.068 4	0.013 249	0.007 165	0.007 229	0.003 347	0.005 197	0.004 203	0.003 327
DCP 8	.200	0.186	0.567 14	0.052 26	0.013 286	0.007 257	0.011 296	0.004 151	0.003 86	0.004 193	0.006 180
DCP 9	.250	0.154	0.498 12	0.053 27	0.009 275	0.007 176	0.014 261	0.005 335	0.004 77	0.001 13	0.001 94
DCP10	.300	0.177	0.423 15	0.047 26	0.010 260	0.005 157	0.008 252	0.006 88	0.009 217	0.010 143	0.004 200
DCP11	.399	0.176	0.351 35	0.047 58	0.012 308	0.008 166	0.008 313	0.003 244	0.004 201	0.011 216	0.007 107
DCP12	.501	0.116	0.293 42	0.046 55	0.010 306	0.004 231	0.006 262	0.003 187	0.004 17	0.011 153	0.002 166
DCP13	.600	0.140	0.240 54	0.042 72	0.004 293	0.015 306	0.001 137	0.006 156	0.009 201	0.005 133	0.004 216
DCP14	.701	0.184	0.191 62	0.037 70	0.004 286	0.001 117	0.007 323	0.003 180	0.004 18	0.004 284	0.005 123
DCP15	.800	0.062	0.137 74	0.026 86	0.008 347	0.010 332	0.010 333	0.004 31	0.006 203	0.005 321	0.004 17
DCP16	.900	-0.075	0.079 101	0.020 106	0.005 319	0.006 317	0.005 328	0.004 267	0.012 226	0.002 304	0.004 69
DCP17	.969	-0.031	0.030 176	0.003 197	0.009 154	0.006 94	0.005 221	0.007 174	0.003 141	0.006 197	0.005 176

FORCED PITCHING OSCILLATION — AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	69.14	0.340	0.308	5.96	0.0	2.47	12013.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
103.7	27948.	0.49E 07	-0.056	0.717	7.79	-3.30086	0.763	0.0
(340.1)	(583.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.472	5.955 0	0.508 343	0.168 190	0.069 136	0.026 336	0.014 2	0.025 193	0.014 120	0.001 145
CN		0.335	0.376 15	0.038 33	0.010 261	0.004 258	0.005 311	0.006 244	0.004 199	0.003 93	0.001 60
CM		-0.012	0.041 293	0.007 279	0.002 162	0.002 112	0.001 147	0.000 127	0.001 359	0.001 232	0.001 139
DCP 1	.010	0.884	2.581 344	0.207 340	0.052 172	0.011 110	0.016 196	0.007 111	0.003 264	0.006 306	0.003 279
DCP 2	.020	0.760	2.000 353	0.154 348	0.034 247	0.004 49	0.010 209	0.002 63	0.011 193	0.001 53	0.010 5
DCP 3	.030	0.908	1.669 352	0.132 345	0.028 242	0.009 194	0.014 236	0.006 235	0.014 135	0.003 117	0.006 231
DCP 4	.049	0.875	1.392 354	0.111 343	0.038 223	0.011 147	0.005 328	0.004 260	0.009 158	0.006 146	0.007 71
DCP 5	.074	0.885	1.109 355	0.088 349	0.030 222	0.007 157	0.009 262	0.003 135	0.004 206	0.006 190	0.007 45
DCP 6	.099	0.884	0.936 358	0.074 2	0.025 237	0.003 30	0.011 310	0.000 120	0.008 211	0.005 166	0.006 51
DCP 7	.149	0.621	0.693 3	0.061 2	0.022 226	0.006 207	0.008 2	0.004 94	0.005 322	0.004 136	0.006 21
DCP 8	.200	0.514	0.573 13	0.057 10	0.020 264	0.005 261	0.007 341	0.010 206	0.010 224	0.004 79	0.004 9
DCP 9	.250	0.440	0.516 13	0.054 25	0.017 245	0.010 228	0.008 254	0.005 64	0.009 162	0.008 173	0.006 301
DCP10	.300	0.431	0.437 16	0.054 28	0.011 228	0.006 286	0.012 308	0.005 195	0.007 284	0.005 57	0.004 251
DCP11	.399	0.378	0.370 34	0.056 55	0.006 269	0.005 237	0.006 343	0.006 279	0.003 281	0.005 59	0.002 203
DCP12	.501	0.255	0.299 42	0.046 56	0.004 287	0.009 236	0.003 147	0.004 321	0.009 174	0.005 87	0.002 212
DCP13	.600	0.242	0.243 51	0.035 70	0.014 293	0.009 200	0.006 204	0.003 93	0.006 160	0.007 152	0.013 75
DCP14	.701	0.256	0.186 61	0.031 72	0.013 294	0.019 275	0.008 311	0.007 322	0.013 215	0.005 169	0.007 138
DCP15	.800	0.148	0.139 74	0.024 69	0.006 310	0.007 394	0.002 335	0.009 114	0.001 98	0.006 203	0.006 187
DCP16	.900	-0.056	0.070 101	0.022 121	0.007 53	0.007 9	0.009 327	0.011 247	0.007 23	0.011 47	0.004 118
DCP17	.969	-0.033	0.039 197	0.010 126	0.010 9	0.002 8	0.009 341	0.009 354	0.010 156	0.010 13	0.006 220

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	69.15	0.343	0.303	5.95	0.0	5.02	12013.3	20

	V	Q	RN	CM(MIN)	CM(MAX)	ALPHA.NMAX	AERO DAMP	TDH	EXT DAMP
	102.7	27474.	0.49E 07	-0.054	0.985	10.84	-0.00091	0.796	0.0
	(336.8)	(573.8)							

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		5.020	5.947	0	0.496	342	0.137	191	0.060	129	0.039	334	0.019	59	0.028	193	0.013	117	0.003	206
CN		0.572	0.368	17	0.037	33	0.013	258	0.003	210	0.005	310	0.003	145	0.003	56	0.001	228	0.002	331
CM		-0.008	0.044	294	0.007	277	0.003	115	0.001	136	0.001	167	0.001	320	0.001	196	0.001	121	0.001	128
DCP 1	.010	2.454	2.505	344	0.196	344	0.016	219	0.031	195	0.041	175	0.024	49	0.035	337	0.013	58	0.011	329
DCP 2	.020	2.091	2.025	353	0.163	347	0.045	173	0.002	79	0.020	210	0.013	49	0.008	56	0.012	78	0.005	329
DCP 3	.030	1.930	1.710	352	0.140	346	0.034	175	0.008	54	0.017	236	0.005	1	0.008	340	0.035	9	0.004	346
DCP 4	.049	1.747	1.414	354	0.109	349	0.024	203	0.004	267	0.008	311	0.009	258	0.010	116	0.002	140	0.007	66
DCP 5	.074	1.571	1.116	356	0.087	355	0.016	186	0.002	150	0.006	316	0.006	251	0.004	100	0.006	134	0.006	7
DCP 6	.099	1.443	0.935	359	0.081	0	0.018	192	0.001	246	0.005	359	0.006	241	0.011	76	0.004	146	0.006	70
DCP 7	.149	1.056	0.699	3	0.062	10	0.020	235	0.005	156	0.009	251	0.006	251	0.008	159	0.004	150	0.004	283
DCP 8	.200	0.872	0.574	14	0.056	24	0.017	236	0.007	184	0.009	345	0.004	256	0.009	343	0.004	152	0.004	100
DCP 9	.250	0.735	0.502	14	0.057	27	0.021	273	0.014	191	0.009	265	0.006	116	0.003	113	0.008	121	0.004	308
DCP10	.300	0.645	0.426	17	0.051	35	0.019	248	0.009	202	0.009	204	0.007	78	0.007	116	0.005	180	0.005	63
DCP11	.394	0.563	0.361	37	0.045	62	0.013	251	0.008	186	0.010	341	0.005	117	0.002	154	0.005	169	0.005	31
DCP12	.501	0.414	0.301	45	0.036	56	0.016	274	0.002	295	0.010	351	0.006	219	0.008	46	0.004	286	0.003	297
DCP13	.600	0.353	0.269	56	0.037	70	0.016	274	0.009	192	0.011	306	0.006	106	0.013	41	0.007	334	0.016	242
DCP14	.701	0.344	0.184	67	0.033	62	0.018	300	0.005	277	0.004	263	0.005	17	0.005	296	0.007	286	0.007	176
DCP15	.800	0.176	0.141	60	0.031	77	0.016	306	0.006	356	0.003	234	0.009	146	0.002	323	0.005	226	0.001	316
DCP16	.900	-0.044	0.077	102	0.013	93	0.007	189	0.011	324	0.006	23	0.009	151	0.002	38	0.003	316	0.006	82
DCP17	.969	-0.044	0.028	136	0.006	26	0.015	303	0.008	89	0.006	59	0.007	35	0.002	24	0.004	46	0.035	323

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	69.22	0.344	0.303	5.96	0.0	7.49	12013.4	20

	V	Q	RN	CM(MIN)	CM(MAX)	ALPHA.NMAX	AERO DAMP	TDH	EXT DAMP
	102.4	27416.	0.49E 07	-0.053	1.173	12.51	-0.00102	0.892	0.0
	(336.0)	(572.6)							

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.493	5.939	0	0.517	342	0.117	198	0.065	134	0.028	342	0.023	49	0.021	207	0.037	107	0.036	308
CN		0.786	0.371	20	0.043	34	0.009	285	0.003	306	0.005	307	0.004	192	0.003	324	0.004	171	0.002	117
CM		-0.001	0.048	291	0.007	276	0.002	132	0.001	143	0.001	185	0.001	17	0.002	167	0.001	23	0.001	9
DCP 1	.010	3.877	2.408	345	0.235	335	0.099	180	0.104	59	0.074	291	0.018	246	0.029	221	0.012	195	0.015	195
DCP 2	.020	3.150	1.957	353	0.162	3	0.026	316	0.021	235	0.023	240	0.014	165	0.006	267	0.008	171	0.009	295
DCP 3	.030	2.920	1.697	353	0.141	349	0.009	229	0.013	198	0.006	236	0.013	142	0.005	286	0.009	151	0.007	23
DCP 4	.049	2.562	1.402	355	0.124	354	0.015	240	0.012	225	0.008	295	0.010	166	0.006	266	0.002	99	0.006	47
DCP 5	.074	2.217	1.103	356	0.103	359	0.010	262	0.005	225	0.004	295	0.008	194	0.002	314	0.006	114	0.006	82
DCP 6	.099	1.998	0.928	0	0.091	5	0.011	288	0.009	184	0.010	204	0.003	178	0.001	253	0.002	103	0.006	72
DCP 7	.149	1.442	0.708	4	0.079	13	0.002	262	0.008	142	0.003	279	0.006	152	0.011	152	0.012	155	0.006	108
DCP 8	.200	1.200	0.573	14	0.067	29	0.011	256	0.013	250	0.005	308	0.009	256	0.009	310	0.009	91	0.006	170
DCP 9	.250	1.022	0.505	16	0.055	19	0.009	253	0.006	305	0.004	235	0.004	179	0.002	270	0.002	92	0.009	315
DCP10	.300	0.918	0.426	20	0.060	20	0.006	254	0.010	205	0.006	329	0.005	139	0.001	24	0.003	301	0.013	66
DCP11	.394	0.766	0.361	39	0.051	52	0.011	274	0.013	303	0.003	329	0.004	247	0.002	167	0.013	159	0.006	155
DCP12	.501	0.554	0.306	49	0.051	68	0.011	310	0.003	7	0.011	300	0.004	215	0.002	331	0.003	247	0.006	138
DCP13	.600	0.454	0.264	60	0.042	66	0.014	300	0.002	77	0.011	208	0.008	151	0.003	12	0.005	162	0.007	143
DCP14	.701	0.403	0.218	69	0.040	64	0.022	311	0.004	342	0.001	103	0.008	249	0.007	283	0.005	296	0.005	321
DCP15	.800	0.202	0.184	63	0.032	73	0.010	296	0.006	351	0.006	346	0.002	185	0.012	355	0.001	32	0.009	236
DCP16	.900	-0.035	0.090	94	0.009	125	0.005	17	0.007	270	0.006	96	0.011	206	0.012	355	0.001	95	0.007	216
DCP17	.969	-0.054	0.033	101	0.004	48	0.006	214	0.006	144	0.009	346	0.009	96	0.003	207	0.020	19	0.012	35

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	69.20	0.346	0.301	5.91	0.0	10.01	12013.5	20

	V	G	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	101.9	27195.	0.48E 07	-0.050	1.390	15.70	-0.00077	0.673	0.0
	(334.4)	(568.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		10.006	5.939 0	0.572 339	0.082 191	0.048 131	0.030 24	0.031 106	0.025 194	0.011 140	0.005 250
CN		0.926	0.436 22	0.039 99	0.041 328	0.033 195	0.020 56	0.007 277	0.008 142	0.008 321	0.008 211
CM		-0.001	0.032 271	0.025 311	0.011 146	0.006 349	0.005 194	0.003 66	0.003 326	0.002 177	0.002 84
DCP 1	.010	4.405	1.809 8	0.883 356	0.454 245	0.258 148	0.095 47	0.060 207	0.125 96	0.092 4	0.057 291
DCP 2	.020	3.542	1.526 20	0.841 5	0.514 255	0.329 150	0.150 51	0.030 18	0.060 7	0.076 275	0.039 173
DCP 3	.030	3.134	1.349 29	0.805 353	0.391 237	0.141 145	0.107 120	0.148 41	0.100 314	0.071 248	0.073 187
DCP 4	.049	3.101	1.384 2	0.146 359	0.024 272	0.016 108	0.015 331	0.015 180	0.006 16	0.009 215	0.010 156
DCP 5	.074	2.632	1.096 5	0.115 3	0.005 340	0.003 12	0.015 275	0.027 143	0.009 52	0.011 236	0.009 181
DCP 6	.099	2.336	0.945 9	0.098 1	0.007 294	0.013 263	0.002 258	0.015 106	0.007 289	0.013 202	0.006 131
DCP 7	.149	1.745	0.771 12	0.069 323	0.025 124	0.009 277	0.004 390	0.005 119	0.009 307	0.011 147	0.013 64
DCP 8	.200	1.459	0.714 18	0.079 253	0.073 94	0.033 299	0.007 123	0.013 249	0.008 190	0.008 284	0.003 258
DCP 9	.250	1.282	0.694 10	0.135 191	0.122 43	0.069 258	0.033 106	0.001 302	0.004 57	0.016 267	0.015 160
DCP10	.300	1.160	0.601 7	0.155 171	0.125 26	0.080 253	0.033 125	0.023 332	0.032 161	0.027 351	0.031 206
DCP11	.399	0.935	0.468 26	0.135 161	0.106 17	0.073 242	0.042 100	0.023 317	0.009 191	0.013 352	0.012 192
DCP12	.501	0.655	0.349 36	0.123 126	0.104 337	0.074 197	0.052 59	0.028 289	0.018 146	0.008 271	0.004 152
DCP13	.600	0.491	0.299 51	0.107 111	0.083 314	0.061 167	0.040 41	0.025 243	0.020 131	0.016 339	0.020 245
DCP14	.701	0.408	0.268 61	0.086 116	0.067 299	0.046 157	0.031 7	0.010 228	0.014 147	0.011 323	0.008 114
DCP15	.800	0.218	0.167 65	0.073 105	0.038 282	0.025 141	0.024 350	0.005 214	0.013 143	0.009 344	0.003 305
DCP16	.900	-0.004	0.050 67	0.059 81	0.033 253	0.026 115	0.020 334	0.008 187	0.013 25	0.011 93	0.020 294
DCP17	.969	-0.041	0.021 126	0.025 72	0.010 266	0.014 52	0.011 302	0.008 190	0.016 192	0.016 327	0.009 224

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	69.21	0.347	0.300	5.91	0.0	12.48	12013.6	20

	V	G	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	101.5	27033.	0.48E 07	-0.175	1.698	18.58	0.00042	-0.365	0.0
	(333.1)	(564.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.476	5.914 0	0.659 335	0.051 128	0.043 152	0.029 67	0.021 125	0.016 168	0.011 144	0.008 53
CN		1.043	0.620 19	0.069 197	0.030 90	0.024 19	0.013 238	0.016 277	0.015 171	0.012 69	0.002 297
CM		-0.031	0.047 152	0.063 323	0.022 106	0.008 111	0.011 346	0.006 153	0.002 298	0.005 197	0.003 81
DCP 1	.010	3.694	1.593 64	1.159 16	0.262 355	0.403 300	0.261 226	0.172 181	0.093 130	0.022 96	0.006 323
DCP 2	.020	3.330	1.648 60	0.966 11	0.127 338	0.295 316	0.270 238	0.205 184	0.140 143	0.107 103	0.084 50
DCP 3	.030	2.925	1.535 66	0.899 9	0.194 343	0.306 289	0.159 210	0.139 206	0.150 146	0.084 91	0.106 70
DCP 4	.049	3.076	1.336 35	0.614 59	0.275 252	0.130 163	0.069 122	0.079 70	0.083 348	0.056 264	0.037 189
DCP 5	.074	2.688	1.277 31	0.482 332	0.239 215	0.123 127	0.061 76	0.066 23	0.050 311	0.042 250	0.036 195
DCP 6	.099	2.433	1.258 29	0.407 312	0.193 169	0.086 114	0.057 76	0.060 9	0.041 302	0.054 248	0.046 158
DCP 7	.149	1.886	1.175 24	0.342 282	0.154 178	0.123 124	0.089 36	0.065 325	0.061 254	0.041 185	0.031 120
DCP 8	.200	1.639	1.116 23	0.323 271	0.166 180	0.117 115	0.094 51	0.091 336	0.062 276	0.082 212	0.071 130
DCP 9	.250	1.475	1.125 14	0.347 242	0.202 150	0.142 76	0.121 6	0.117 277	0.085 200	0.092 120	0.073 38
DCP10	.300	1.333	1.005 11	0.338 227	0.178 129	0.130 65	0.136 344	0.119 241	0.083 173	0.105 86	0.059 341
DCP11	.399	1.110	0.810 15	0.316 213	0.195 113	0.138 37	0.155 311	0.126 205	0.082 148	0.092 58	0.069 317
DCP12	.501	0.831	0.623 9	0.306 180	0.193 69	0.145 346	0.172 244	0.107 126	0.058 69	0.069 337	0.050 227
DCP13	.600	0.662	0.465 6	0.319 155	0.173 34	0.113 313	0.156 207	0.092 68	0.040 8	0.054 269	0.024 186
DCP14	.701	0.536	0.267 359	0.297 12	0.143 342	0.074 254	0.123 151	0.043 350	0.028 233	0.018 142	0.019 29
DCP15	.900	0.324	0.153 340	0.248 107	0.129 314	0.047 199	0.074 109	0.067 303	0.016 146	0.030 63	0.021 279
DCP16	.900	0.058	0.071 320	0.128 100	0.074 308	0.047 218	0.062 65	0.043 276	0.008 70	0.017 16	0.022 170
DCP17	.969	-0.020	0.016 354	0.049 103	0.031 306	0.012 275	0.027 112	0.020 338	0.021 239	0.016 352	0.001 282

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	69.13	0.348	0.299	5.86	0.0	15.03	12013.7	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
101.1 (331.7)	26832. (560.4)	0.48E 07	-0.245	1.989	21.27	0.00163	-1.406	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		15.034	5.881	0	0.709	339	0.097	117	0.030	176	0.014	115	0.020	140	0.020	169	0.012	151	0.012	95
CN		1.161	0.887	20	0.032	230	0.043	219	0.012	120	0.010	96	0.014	6	0.015	256	0.003	265	0.002	184
CM		-0.073	0.108	136	0.071	330	0.003	218	0.012	194	0.006	81	0.000	221	0.005	31	0.000	340	0.002	242
DCP 1	.010	3.678	2.197	86	0.547	23	0.618	55	0.296	5	0.292	326	0.138	308	0.108	267	0.031	280	0.028	173
DCP 2	.020	3.206	2.066	81	0.643	19	0.373	57	0.194	5	0.220	338	0.142	321	0.168	289	0.106	247	0.087	220
DCP 3	.030	2.571	1.736	88	0.702	35	0.391	42	0.234	340	0.138	328	0.132	297	0.074	274	0.086	257	0.079	234
DCP 4	.049	3.145	1.271	59	0.653	24	0.228	336	0.208	292	0.192	227	0.105	173	0.079	147	0.079	110	0.070	66
DCP 5	.074	2.763	1.302	49	0.504	358	0.174	307	0.234	261	0.182	187	0.069	136	0.099	110	0.079	54	0.052	9
DCP 6	.099	2.544	1.371	45	0.446	339	0.161	296	0.221	247	0.179	170	0.079	113	0.066	90	0.059	45	0.050	358
DCP 7	.149	2.025	1.190	36	0.409	317	0.230	265	0.186	206	0.159	153	0.097	93	0.057	40	0.042	13	0.047	316
DCP 8	.200	1.727	1.305	37	0.420	315	0.248	250	0.228	212	0.188	138	0.107	91	0.090	36	0.068	3	0.064	283
DCP 9	.250	1.542	1.255	28	0.383	299	0.282	232	0.252	173	0.207	90	0.115	29	0.105	339	0.093	279	0.057	240
DCP10	.300	1.413	1.186	22	0.384	283	0.315	205	0.241	148	0.201	60	0.125	348	0.102	299	0.093	227	0.074	192
DCP11	.399	1.276	1.020	18	0.326	260	0.308	191	0.238	110	0.203	35	0.162	324	0.129	260	0.098	187	0.061	142
DCP12	.501	1.065	0.861	0	0.344	207	0.244	142	0.238	55	0.189	324	0.123	246	0.101	192	0.084	96	0.043	67
DCP13	.600	0.893	0.698	343	0.393	167	0.184	93	0.193	9	0.153	272	0.097	177	0.047	121	0.051	11	0.011	240
DCP14	.701	0.738	0.512	325	0.412	138	0.143	22	0.127	317	0.119	209	0.061	101	0.009	336	0.031	305	0.014	129
DCP15	.800	0.477	0.358	311	0.368	121	0.159	338	0.073	285	0.065	165	0.041	41	0.029	213	0.008	21	0.006	15
DCP16	.900	0.178	0.184	296	0.202	101	0.387	299	0.044	268	0.045	144	0.026	16	0.019	171	0.008	98	0.022	341
DCP17	.969	0.068	0.076	277	0.102	96	0.056	294	0.024	242	0.014	299	0.023	152	0.028	358	0.027	208	0.035	19

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	69.16	0.349	0.299	5.84	0.0	17.51	12013.8	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
100.9 (330.9)	26770. (559.1)	0.48E 07	-0.303	2.144	23.17	0.00179	-1.544	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		17.512	5.815	0	0.714	346	0.127	121	0.031	181	0.019	200	0.007	61	0.018	169	0.013	137	0.017	130
CN		1.268	0.898	29	0.040	312	0.029	228	0.021	219	0.024	202	0.029	100	0.015	344	0.003	53	0.014	11
CM		-0.093	0.139	147	0.086	2	0.007	300	0.012	269	0.007	133	0.033	249	0.006	128	0.003	58	0.004	221
DCP 1	.010	3.662	2.429	105	0.451	85	0.436	86	0.411	79	0.232	79	0.156	59	0.099	43	0.043	50	0.015	322
DCP 2	.020	3.237	2.256	99	0.446	59	0.291	87	0.228	86	0.165	92	0.195	75	0.151	50	0.092	36	0.067	40
DCP 3	.030	2.434	1.763	106	0.581	67	0.395	78	0.144	57	0.182	68	0.118	47	0.082	33	0.052	40	0.057	34
DCP 4	.049	3.253	1.259	82	0.572	40	0.260	54	0.244	353	0.126	305	0.075	324	0.090	283	0.051	267	0.067	251
DCP 5	.074	2.962	1.272	67	0.441	17	0.267	35	0.272	316	0.149	282	0.084	262	0.091	243	0.057	190	0.062	195
DCP 6	.099	2.621	1.328	60	0.416	4	0.231	17	0.295	299	0.182	246	0.079	216	0.106	212	0.059	152	0.054	158
DCP 7	.149	2.089	1.377	51	0.531	352	0.203	305	0.207	208	0.189	238	0.106	182	0.056	168	0.042	114	0.014	126
DCP 8	.200	1.804	1.324	54	0.623	355	0.223	296	0.222	283	0.193	237	0.118	183	0.078	158	0.044	116	0.024	109
DCP 9	.250	1.615	1.274	42	0.626	337	0.294	263	0.282	241	0.221	179	0.162	141	0.105	68	0.085	70	0.072	35
DCP10	.300	1.536	1.176	34	0.600	325	0.332	246	0.290	210	0.223	148	0.153	97	0.107	50	0.065	12	0.072	353
DCP11	.399	1.309	1.097	27	0.489	308	0.355	228	0.287	101	0.213	119	0.166	71	0.144	17	0.077	328	0.076	314
DCP12	.501	1.195	0.995	6	0.390	253	0.292	177	0.246	118	0.178	39	0.112	355	0.110	292	0.041	245	0.010	179
DCP13	.600	0.997	0.859	349	0.408	208	0.214	130	0.197	73	0.151	337	0.052	272	0.052	239	0.033	148	0.017	38
DCP14	.701	0.816	0.669	331	0.407	171	0.169	62	0.123	13	0.109	277	0.031	181	0.011	181	0.015	71	0.009	12
DCP15	.800	0.555	0.451	319	0.360	152	0.161	31	0.085	323	0.072	225	0.032	71	0.029	268	0.005	171	0.008	134
DCP16	.900	0.247	0.188	309	0.227	125	0.070	335	0.033	344	0.051	232	0.014	116	0.024	299	0.027	194	0.028	32
DCP17	.969	0.068	0.095	309	0.120	128	0.076	327	0.027	184	0.054	336	0.049	195	0.030	51	0.051	257	0.047	97

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	69.11	0.349	0.299	5.83	0.0	19.95	12013.9	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
100.9	26755.	0.48E 07	-0.324	2.278	25.01	0.00106	-0.917	0.0
(331.0)	(558.8)							

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		19.954	5.831 0	0.662 352	0.131 149	0.033 176	0.028 176	0.007 60	0.023 166	0.013 155	0.012 109
CN		1.294	0.726 37	0.170 315	0.038 246	0.037 306	0.035 220	0.016 174	0.010 103	0.009 178	0.005 108
CM		-0.114	0.145 165	0.053 47	0.013 351	0.004 309	0.004 296	0.002 25	0.005 253	0.001 142	0.002 303
DCP 1	.010	3.277	2.238 120	0.614 101	0.506 121	0.294 139	0.226 123	0.166 121	0.049 142	0.083 111	0.026 152
DCP 2	.020	3.076	1.921 115	0.533 90	0.318 126	0.162 141	0.184 152	0.188 145	0.127 143	0.128 136	0.069 143
DCP 3	.030	2.760	1.605 111	0.527 107	0.243 121	0.169 100	0.177 154	0.110 142	0.090 141	0.079 161	0.082 186
DCP 4	.049	3.049	1.376 97	0.474 44	0.293 112	0.257 32	0.040 15	0.085 50	0.075 28	0.043 34	0.059 35
DCP 5	.074	2.693	1.327 79	0.381 30	0.236 81	0.266 12	0.104 336	0.091 354	0.099 330	0.045 323	0.065 336
DCP 6	.099	2.492	1.377 67	0.384 23	0.192 58	0.291 0	0.129 311	0.069 338	0.111 323	0.077 279	0.043 264
DCP 7	.149	2.060	1.307 56	0.547 16	0.181 353	0.234 330	0.118 294	0.115 302	0.102 264	0.052 229	0.336 244
DCP 8	.200	1.828	1.265 60	0.662 16	0.239 348	0.243 327	0.168 295	0.117 291	0.105 253	0.043 251	0.050 265
DCP 9	.250	1.695	1.211 47	0.680 356	0.297 307	0.260 285	0.199 243	0.136 213	0.120 177	0.066 166	0.045 142
DCP10	.300	1.571	1.109 41	0.633 348	0.337 290	0.266 260	0.210 211	0.153 169	0.114 133	0.071 125	0.054 86
DCP11	.399	1.483	1.112 35	0.575 336	0.371 273	0.241 240	0.176 200	0.143 153	0.097 119	0.049 115	0.048 62
DCP12	.501	1.279	0.998 16	0.445 285	0.315 226	0.194 170	0.128 128	0.102 76	0.092 37	0.030 346	0.023 342
DCP13	.600	1.060	0.870 4	0.376 257	0.253 182	0.163 118	0.079 67	0.067 8	0.041 358	0.025 240	0.020 166
DCP14	.701	0.850	0.648 352	0.319 217	0.206 131	0.134 49	0.035 351	0.032 275	0.013 340	0.015 159	0.006 122
DCP15	.800	0.625	0.443 343	0.268 185	0.161 100	0.134 10	0.061 262	0.026 151	0.039 332	0.015 228	0.009 84
DCP16	.900	0.310	0.246 339	0.174 155	0.086 36	0.033 335	0.017 346	0.032 231	0.022 127	0.015 303	0.019 142
DCP17	.969	0.154	0.173 328	0.169 151	0.131 18	0.061 238	0.078 74	0.071 285	0.063 157	0.039 9	0.029 244

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.09	0.088	0.396	5.16	0.0	0.05	12017.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
134.3	17558.	0.24E 07	-0.039	0.610	5.00	-0.00088	0.950	0.0
(440.7)	(366.7)							

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.045	5.157 0	0.237 9	0.048 261	0.002 7	0.013 355	0.019 102	0.026 190	0.001 168	0.006 354
CN		0.146	0.462 355	0.013 347	0.001 8	0.001 59	0.002 285	0.001 168	0.001 53	0.003 312	0.002 211
CM		-0.021	0.015 311	0.002 351	0.001 345	0.000 196	0.001 284	0.000 71	0.001 240	0.001 249	0.001 38
DCP 1	.010	-0.639	3.235 348	0.162 22	0.017 85	0.004 49	0.016 272	0.015 135	0.011 266	0.023 270	0.006 3
DCP 2	.020	-0.229	2.302 351	0.094 308	0.017 27	0.044 215	0.070 295	0.035 32	0.005 80	0.032 303	0.017 69
DCP 3	.030	-0.002	1.997 351	0.078 311	0.020 333	0.002 36	0.011 267	0.007 155	0.007 280	0.013 286	0.004 162
DCP 4	.049	0.211	1.643 351	0.058 319	0.009 326	0.004 40	0.015 252	0.003 123	0.005 278	0.014 279	0.004 67
DCP 5	.074	0.333	1.341 351	0.048 334	0.001 51	0.004 104	0.009 265	0.005 104	0.004 304	0.016 257	0.002 316
DCP 6	.099	0.356	1.157 352	0.043 336	0.006 37	0.005 46	0.009 287	0.001 159	0.006 86	0.014 276	0.007 71
DCP 7	.149	0.256	0.863 352	0.032 15	0.020 355	0.009 173	0.002 261	0.008 173	0.002 162	0.013 305	0.001 281
DCP 8	.200	0.218	0.703 355	0.020 352	0.006 12	0.005 84	0.011 302	0.004 76	0.001 343	0.013 279	0.006 276
DCP 9	.250	0.222	0.619 355	0.024 2	0.003 270	0.003 52	0.001 0	0.003 220	0.001 187	0.007 295	0.002 123
DCP10	.300	0.208	0.511 355	0.022 349	0.003 336	0.005 150	0.006 237	0.005 228	0.001 313	0.005 70	0.002 185
DCP11	.399	0.189	0.412 0	0.011 5	0.002 262	0.001 290	0.002 320	0.009 167	0.001 338	0.002 118	0.033 97
DCP12	.501	0.141	0.309 1	0.008 27	0.003 17	0.005 9	0.003 58	0.005 321	0.004 88	0.001 166	0.004 266
DCP13	.600	0.198	0.235 5	0.006 53	0.003 332	0.006 1	0.003 32	0.003 8	0.005 59	0.002 104	0.004 185
DCP14	.701	0.221	0.158 7	0.001 102	0.007 198	0.001 28	0.003 85	0.001 207	0.006 57	0.004 347	0.008 264
DCP15	.800	0.118	0.078 22	0.009 213	0.008 118	0.001 121	0.001 113	0.001 135	0.004 229	0.004 9	0.006 215
DCP16	.900	-0.075	0.022 62	0.010 207	0.004 206	0.002 0	0.005 256	0.002 249	0.004 8	0.006 59	0.007 182
DCP17	.969	-0.042	0.031 169	0.001 294	0.005 137	0.006 169	0.004 149	0.002 122	0.003 146	0.007 86	0.004 35

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED 3.0	DRIVE HZ 23.11	K 0.088	MACH NO 0.395	DEL.ALPHA 5.17	DEL.H 0.0	ALPHA.0 2.47	TEST POINT 12017.2	CYCLES ANALYSED 20
	V 133.4 (437.8)	Q 17376. (362.9)	RN 0.24E 07	CN(MIN) -0.036	CN(MAX) 0.845	ALPHA.NMAX 7.57	AERO DAMP -0.00083	TDR 0.688	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.472	5.168 0	0.238 9	0.043 262	0.004 216	0.022 337	0.017 134	0.024 190	0.001 246	0.006 337
CN		0.383	0.468 355	0.017 1	0.004 334	0.003 192	0.004 267	0.004 236	0.003 28	0.005 331	0.003 71
CM		-0.015	0.014 310	0.001 341	0.001 136	0.001 13	0.000 98	0.001 76	0.001 215	0.003 170	0.001 266
DCP 1	.010	0.996	1.077 348	0.118 7	0.004 23	0.013 84	0.021 284	0.014 171	0.007 131	0.015 171	0.006 34
DCP 2	.020	0.948	2.497 351	0.097 329	0.048 154	0.033 96	0.051 302	0.014 296	0.011 118	0.025 184	0.009 83
DCP 3	.030	1.006	2.034 351	0.071 5	0.059 329	0.015 258	0.018 154	0.012 104	0.004 250	0.013 181	0.002 350
DCP 4	.049	1.064	1.700 351	0.059 331	0.009 314	0.006 90	0.009 277	0.004 125	0.004 202	0.015 195	0.004 15
DCP 5	.074	1.034	1.363 351	0.047 346	0.006 301	0.004 174	0.010 299	0.005 194	0.001 22	0.013 192	0.006 70
DCP 6	.099	0.952	1.163 352	0.050 359	0.017 329	0.003 163	0.015 298	0.010 197	0.004 52	0.017 198	0.009 65
DCP 7	.149	0.785	0.871 352	0.035 1	0.002 353	0.008 47	0.005 200	0.005 31	0.001 338	0.005 212	0.003 191
DCP 8	.200	0.583	0.704 356	0.029 354	0.003 271	0.004 157	0.006 324	0.009 142	0.002 173	0.017 195	0.008 353
DCP 9	.250	0.532	0.614 354	0.027 16	0.006 11	0.006 269	0.004 270	0.002 221	0.006 322	0.006 274	0.004 39
DCP10	.300	0.467	0.508 354	0.023 17	0.003 53	0.004 273	0.003 240	0.003 188	0.007 9	0.006 14	0.006 90
DCP11	.399	0.397	0.417 0	0.018 19	0.004 30	0.004 252	0.007 160	0.008 267	0.003 30	0.012 11	0.001 146
DCP12	.501	0.301	0.316 2	0.012 12	0.007 0	0.003 120	0.003 246	0.005 219	0.003 70	0.010 336	0.003 116
DCP13	.600	0.313	0.227 7	0.005 68	0.002 320	0.019 213	0.014 241	0.016 286	0.005 351	0.023 336	0.006 29
DCP14	.701	0.296	0.155 5	0.031 329	0.005 311	0.004 211	0.002 346	0.005 250	0.006 65	0.009 354	0.005 97
DCP15	.800	0.151	0.091 15	0.003 67	0.003 298	0.003 125	0.008 344	0.005 312	0.001 76	0.006 2	0.004 136
DCP16	.900	-0.069	0.024 38	0.006 240	0.004 300	0.008 143	0.003 316	0.004 202	0.004 334	0.012 334	0.006 69
DCP17	.969	-0.053	0.018 182	0.005 211	0.003 292	0.002 226	0.003 140	0.005 200	0.004 73	0.005 20	0.005 88

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ 0.0	DRIVE HZ 23.07	K 0.088	MACH NO 0.395	DEL.ALPHA 5.16	DEL.H 0.0	ALPHA.0 5.01	TEST POINT 12017.3	CYCLES ANALYSED 20
	V 133.4 (437.6)	Q 17414. (363.7)	RN 0.24E 07	CN(MIN) -0.027	CN(MAX) 1.054	ALPHA.NMAX 10.16	AERO DAMP -0.00101	TDR 1.082	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		5.013	5.161 0	0.233 9	0.039 258	0.007 331	0.021 341	0.018 141	0.021 190	0.004 182	0.006 304
CN		0.612	0.445 357	0.038 15	0.009 284	0.004 117	0.001 308	0.004 215	0.002 281	0.005 281	0.001 351
CM		-0.007	0.018 314	0.004 239	0.001 105	0.001 291	0.000 261	0.001 44	0.001 98	0.001 95	0.001 182
DCP 1	.010	1.681	1.142 349	0.199 319	0.049 199	0.026 218	0.036 148	0.032 76	0.010 6	0.017 348	0.013 262
DCP 2	.020	2.410	2.036 353	0.342 294	0.174 191	0.041 91	0.047 325	0.039 184	0.026 26	0.042 257	0.046 136
DCP 3	.030	2.001	1.920 351	0.140 19	0.013 247	0.048 76	0.054 335	0.029 260	0.016 178	0.019 37	0.019 305
DCP 4	.049	1.895	1.628 351	0.113 19	0.051 329	0.024 261	0.012 215	0.009 153	0.002 21	0.009 307	0.005 175
DCP 5	.074	1.708	1.305 352	0.098 18	0.031 322	0.007 287	0.007 251	0.004 139	0.003 277	0.008 285	0.003 142
DCP 6	.099	1.520	1.110 353	0.085 18	0.027 318	0.002 116	0.006 274	0.003 176	0.003 241	0.007 312	0.003 115
DCP 7	.149	1.142	0.827 353	0.059 16	0.010 333	0.032 297	0.008 263	0.009 222	0.007 243	0.004 220	0.006 255
DCP 8	.200	0.933	0.680 356	0.049 18	0.016 295	0.010 225	0.003 322	0.004 320	0.004 139	0.005 9	0.002 307
DCP 9	.250	0.847	0.563 356	0.044 19	0.007 316	0.004 199	0.002 248	0.003 199	0.004 165	0.007 190	0.001 327
DCP10	.300	0.716	0.476 357	0.042 18	0.009 250	0.036 73	0.004 238	0.004 207	0.004 352	0.005 248	0.001 318
DCP11	.399	0.598	0.380 2	0.040 25	0.012 278	0.007 157	0.003 117	0.006 239	0.003 110	0.003 263	0.003 250
DCP12	.501	0.440	0.291 4	0.035 19	0.011 292	0.005 102	0.002 175	0.002 151	0.006 267	0.002 331	0.006 95
DCP13	.600	0.411	0.209 8	0.031 26	0.010 337	0.008 102	0.005 22	0.002 79	0.002 263	0.005 274	0.006 333
DCP14	.701	0.354	0.128 18	0.031 49	0.010 294	0.002 36	0.004 98	0.005 242	0.006 311	0.005 285	0.005 49
DCP15	.800	0.179	0.074 27	0.026 55	0.005 248	0.002 123	0.001 40	0.009 224	0.001 192	0.010 266	0.006 7
DCP16	.900	-0.054	0.035 63	0.007 319	0.006 262	0.008 107	0.006 312	0.004 258	0.004 294	0.007 302	0.002 255
DCP17	.969	-0.066	0.010 151	0.007 297	0.006 236	0.004 154	0.003 172	0.004 149	0.002 216	0.006 273	0.003 232

167

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.10	0.088	0.394	5.14	0.0	7.48	12017.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
132.9	17333.	0.24E 07	-0.079	1.257	12.31	-0.00065	0.694	0.0
(436.1)	(362.0)							

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.484	5.140 0	0.246 14	0.042 277	0.014 264	0.008 20	0.012 46	0.023 208	0.006 67	0.004 8
CN		0.760	0.330 16	0.144 11	0.066 250	0.035 132	0.018 22	0.006 265	0.001 333	0.007 352	0.004 136
CM		-0.012	0.014 229	0.019 78	0.019 333	0.012 235	0.006 153	0.002 103	0.002 59	0.004 258	0.002 271
DCP 1	.010	3.341	1.609 358	0.925 51	0.463 339	0.177 276	0.094 292	0.132 250	0.104 190	0.044 182	0.029 98
DCP 2	.020	2.891	1.452 9	0.940 43	0.512 329	0.162 283	0.157 293	0.151 238	0.127 190	0.061 139	0.041 79
DCP 3	.030	2.612	1.211 5	0.640 37	0.317 313	0.204 246	0.139 193	0.108 159	0.107 117	0.061 61	0.068 29
DCP 4	.049	2.244	0.760 10	0.716 48	0.386 318	0.184 223	0.064 144	0.031 164	0.071 116	0.069 19	0.055 323
DCP 5	.074	1.997	0.643 14	0.562 40	0.309 304	0.163 204	0.061 115	0.015 162	0.060 91	0.071 348	0.051 262
DCP 6	.099	1.792	0.602 16	0.490 33	0.273 292	0.155 192	0.057 104	0.017 141	0.058 74	0.073 332	0.050 262
DCP 7	.149	1.410	0.581 15	0.334 13	0.225 268	0.123 165	0.057 81	0.028 59	0.054 34	0.058 296	0.036 227
DCP 8	.200	1.189	0.569 15	0.256 2	0.170 252	0.121 154	0.057 66	0.029 35	0.036 351	0.060 285	0.023 207
DCP 9	.250	1.069	0.524 13	0.213 346	0.155 229	0.102 125	0.047 45	0.025 0	0.041 321	0.026 243	0.032 149
DCP10	.300	0.924	0.445 14	0.180 340	0.135 217	0.092 115	0.054 28	0.024 341	0.031 291	0.026 318	0.027 122
DCP11	.399	0.764	0.355 18	0.126 342	0.095 206	0.066 102	0.032 12	0.018 322	0.021 292	0.010 207	0.021 118
DCP12	.501	0.563	0.267 23	0.099 344	0.068 203	0.055 94	0.033 4	0.014 309	0.015 263	0.011 121	0.019 102
DCP13	.600	0.478	0.194 30	0.073 345	0.047 188	0.039 75	0.025 349	0.009 286	0.008 255	0.012 82	0.014 83
DCP14	.701	0.403	0.118 37	0.052 345	0.052 168	0.045 53	0.024 312	0.009 251	0.014 240	0.021 89	0.006 23
DCP15	.800	0.227	0.096 28	0.042 285	0.055 153	0.039 42	0.025 310	0.011 238	0.008 182	0.019 53	0.005 322
DCP16	.900	-0.013	0.086 10	0.053 259	0.043 138	0.023 42	0.012 325	0.010 232	0.019 137	0.023 36	0.003 213
DCP17	.969	-0.055	0.031 4	0.023 246	0.012 146	0.008 16	0.004 21	0.008 261	0.006 158	0.015 36	0.001 314

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.13	0.089	0.393	5.11	0.0	10.00	12017.5	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
132.6	17242.	0.24E 07	-0.145	1.396	13.93	-0.00086	0.919	0.0
(434.8)	(360.1)							

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		10.004	5.113 0	0.235 15	0.021 274	0.024 19	0.089 332	0.071 193	0.041 198	0.012 39	0.014 339
CN		0.871	0.230 48	0.164 24	0.024 333	0.038 311	0.030 230	0.021 161	0.012 103	0.010 67	0.008 2
CM		-0.026	0.044 200	0.031 100	0.009 60	0.015 49	0.013 343	0.009 303	0.007 262	0.008 213	0.005 158
DCP 1	.010	3.760	0.297 56	1.044 70	0.217 89	0.372 65	0.151 22	0.134 51	0.094 3	0.028 40	0.044 349
DCP 2	.020	3.223	0.560 71	1.013 65	0.284 92	0.376 59	0.198 41	0.127 30	0.122 16	0.030 348	0.077 359
DCP 3	.030	2.937	0.414 49	0.657 64	0.221 55	0.236 31	0.207 349	0.134 335	0.120 318	0.086 294	0.074 281
DCP 4	.049	2.434	0.351 119	0.787 67	0.140 40	0.184 40	0.143 336	0.042 312	0.078 323	0.070 260	0.048 260
DCP 5	.074	2.144	0.354 110	0.626 60	0.106 33	0.162 26	0.119 316	0.034 291	0.051 298	0.060 237	0.036 227
DCP 6	.099	1.923	0.352 96	0.516 53	0.088 20	0.155 15	0.108 303	0.042 278	0.054 276	0.061 215	0.031 202
DCP 7	.149	1.531	0.378 68	0.405 37	0.089 0	0.131 349	0.110 276	0.057 241	0.051 223	0.053 187	0.035 164
DCP 8	.200	1.313	0.388 56	0.329 31	0.067 348	0.126 326	0.099 263	0.068 231	0.058 195	0.053 167	0.035 143
DCP 9	.250	1.209	0.421 46	0.290 16	0.094 318	0.111 295	0.091 244	0.073 200	0.054 161	0.049 126	0.035 107
DCP10	.300	1.057	0.382 43	0.242 5	0.075 306	0.096 278	0.075 214	0.056 171	0.045 130	0.036 87	0.026 70
DCP11	.399	0.900	0.346 39	0.175 357	0.044 298	0.072 279	0.061 210	0.048 168	0.038 128	0.023 81	0.024 83
DCP12	.501	0.667	0.301 38	0.131 343	0.034 278	0.056 263	0.059 195	0.042 151	0.033 112	0.025 65	0.026 43
DCP13	.600	0.580	0.268 38	0.109 325	0.023 234	0.041 260	0.049 189	0.038 140	0.033 89	0.034 50	0.033 4
DCP14	.701	0.481	0.183 40	0.087 306	0.023 206	0.038 239	0.038 160	0.036 117	0.031 69	0.032 28	0.035 339
DCP15	.800	0.287	0.158 30	0.080 294	0.034 230	0.049 215	0.044 142	0.034 91	0.023 52	0.031 7	0.026 303
DCP16	.900	0.041	0.148 8	0.064 261	0.015 255	0.029 211	0.033 139	0.027 96	0.024 38	0.023 9	0.024 286
DCP17	.969	-0.024	0.071 7	0.027 267	0.013 272	0.019 223	0.010 174	0.012 113	0.011 43	0.023 24	0.011 303

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.11	0.089	0.393	5.10	0.0	12.47	12017.6	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
132.7 (435.3)	17270. (360.7)	0.24E 07	-0.156	1.420	14.45	-0.00143	1.520	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.475	5.096 0	0.239 14	0.042 207	0.016 52	0.039 91	0.081 7	0.012 252	0.030 204	0.007 182
CN		0.923	0.270 84	0.091 44	0.071 64	0.018 356	0.027 25	0.022 313	0.010 315	0.018 249	0.007 354
CM		-0.039	0.066 198	0.016 130	0.023 158	0.009 117	0.013 129	0.039 93	0.007 85	0.009 54	0.002 74
DCP 1	.010	4.073	0.932 149	0.302 84	0.515 161	0.161 197	0.205 168	0.107 222	0.103 188	0.045 246	0.050 207
DCP 2	.020	3.541	1.036 131	0.247 105	0.485 157	0.214 175	0.272 177	0.155 209	0.126 193	0.043 251	0.057 263
DCP 3	.030	3.123	0.556 124	0.393 93	0.516 129	0.188 136	0.214 136	0.137 134	0.123 151	0.091 156	0.071 164
DCP 4	.049	2.417	1.009 150	0.319 81	0.363 138	0.110 96	0.148 130	0.064 91	0.074 136	0.047 133	0.060 141
DCP 5	.074	2.128	0.847 143	0.267 78	0.305 125	0.082 82	0.134 112	0.051 58	0.058 113	0.026 103	0.055 114
DCP 6	.099	1.913	0.717 134	0.231 72	0.278 115	0.073 75	0.137 99	0.053 60	0.062 88	0.033 84	0.051 95
DCP 7	.149	1.551	0.544 115	0.214 65	0.224 90	0.079 54	0.117 65	0.061 36	0.065 42	0.042 42	0.044 41
DCP 8	.200	1.342	0.453 101	0.213 64	0.176 75	0.086 47	0.101 46	0.069 20	0.052 15	0.036 29	0.040 18
DCP 9	.250	1.248	0.432 87	0.213 51	0.165 52	0.080 12	0.096 20	0.063 351	0.057 344	0.023 322	0.041 352
DCP10	.300	1.112	0.398 77	0.188 41	0.150 36	0.078 352	0.080 357	0.060 332	0.051 328	0.032 307	0.034 316
DCP11	.399	0.960	0.350 64	0.138 30	0.106 22	0.045 328	0.044 354	0.035 333	0.036 335	0.037 319	0.042 328
DCP12	.501	0.740	0.327 55	0.067 341	0.094 29	0.046 277	0.057 22	0.058 283	0.033 351	0.050 251	0.032 13
DCP13	.600	0.645	0.277 45	0.069 335	0.066 7	0.017 288	0.050 336	0.040 291	0.033 286	0.044 255	0.013 265
DCP14	.701	0.538	0.234 39	0.057 309	0.063 351	0.024 291	0.050 312	0.035 276	0.038 253	0.046 218	0.020 213
DCP15	.800	0.348	0.219 29	0.052 322	0.069 336	0.035 293	0.046 281	0.034 254	0.033 218	0.036 216	0.014 187
DCP16	.930	0.101	0.197 13	0.038 328	0.053 329	0.024 299	0.038 272	0.029 242	0.023 218	0.033 207	0.015 178
DCP17	.969	0.003	0.096 7	0.019 355	0.021 309	0.010 345	0.015 288	0.010 255	0.014 237	0.017 227	0.001 170

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.14	0.089	0.394	5.09	0.0	15.02	12017.7	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
132.9 (436.0)	17328. (361.9)	0.24E 07	-0.145	1.388	14.14	-0.00212	2.259	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		15.022	5.094 0	0.224 5	0.040 232	0.013 269	0.034 293	0.071 150	0.051 189	0.002 237	0.007 320
CN		0.953	0.278 96	0.052 156	0.032 98	0.044 138	0.012 145	0.023 141	0.015 145	0.005 336	0.010 160
CM		-0.052	0.071 201	0.026 236	0.012 194	0.016 249	0.007 280	0.007 279	0.006 286	0.002 330	0.004 310
DCP 1	.010	3.979	1.363 160	0.656 251	0.037 313	0.152 261	0.136 347	0.093 93	0.023 69	0.069 81	0.046 191
DCP 2	.020	3.576	1.367 152	0.781 242	0.154 310	0.169 275	0.155 351	0.088 70	0.049 115	0.046 83	0.054 197
DCP 3	.030	3.064	0.919 149	0.365 20C	0.244 216	0.224 258	0.167 311	0.073 354	0.077 33	0.053 53	0.031 112
DCP 4	.049	2.305	1.085 156	0.389 234	0.153 189	0.225 237	0.120 301	0.055 286	0.066 353	0.072 38	0.026 79
DCP 5	.074	2.059	0.883 149	0.335 226	0.123 177	0.188 220	0.100 282	0.059 252	0.050 312	0.070 11	0.025 14
DCP 6	.099	1.890	0.728 141	0.282 216	0.115 169	0.170 208	0.096 268	0.055 233	0.057 301	0.067 3	0.029 16
DCP 7	.149	1.560	0.578 124	0.203 187	0.118 146	0.149 182	0.082 224	0.062 202	0.043 240	0.056 318	0.020 307
DCP 8	.200	1.365	0.506 115	0.174 163	0.132 138	0.134 165	0.087 203	0.063 200	0.058 213	0.044 317	0.023 263
DCP 9	.250	1.282	0.459 102	0.153 135	0.134 115	0.126 139	0.073 165	0.069 186	0.055 184	0.041 234	0.028 230
DCP10	.300	1.145	0.406 93	0.137 122	0.113 100	0.112 119	0.084 146	0.060 142	0.052 165	0.034 212	0.029 194
DCP11	.399	1.009	0.358 78	0.100 102	0.077 78	0.086 107	0.035 134	0.037 126	0.034 157	0.018 240	0.018 192
DCP12	.501	0.807	0.320 63	0.073 89	0.053 55	0.067 98	0.020 138	0.030 121	0.034 146	0.011 194	0.025 176
DCP13	.600	0.681	0.289 50	0.067 84	0.053 14	0.053 86	0.007 145	0.033 117	0.032 132	0.012 170	0.026 137
DCP14	.701	0.573	0.250 39	0.056 65	0.050 351	0.054 70	0.019 112	0.028 84	0.033 89	0.009 76	0.012 123
DCP15	.800	0.402	0.252 29	0.077 46	0.045 348	0.058 67	0.027 53	0.025 48	0.028 73	0.012 56	0.017 82
DCP16	.900	0.156	0.194 18	0.071 42	0.024 17	0.031 60	0.025 79	0.017 48	0.014 63	0.008 36	0.016 109
DCP17	.969	0.028	0.086 20	0.037 45	0.014 13	0.005 359	0.009 108	0.013 131	0.008 42	0.008 76	0.008 135

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.12	0.088	0.394	5.12	0.0	17.51	12017.8	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
133.0	17371.	0.24E 07	-0.136	1.278	14.01	-0.00291	3.104	0.0
(436.4)	(362.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		17.507	5.116 0	0.223 4	0.044 262	0.010 359	0.021 9	0.036 75	0.018 211	0.011 63	0.004 323
CN		0.930	0.248 87	0.074 177	0.042 235	0.020 287	0.012 292	0.010 286	0.011 354	0.015 73	0.006 223
CM		-0.074	0.054 221	0.024 247	0.013 320	0.007 30	0.006 60	0.006 77	0.004 148	0.006 235	0.001 32
DCP 1	.010	3.284	0.755 145	0.382 241	0.240 317	0.176 49	0.095 136	0.050 238	0.042 337	0.028 340	0.033 62
DCP 2	.020	2.896	0.726 136	0.433 229	0.300 317	0.203 53	0.106 122	0.052 201	0.054 328	0.024 37	0.016 85
DCP 3	.030	2.677	0.713 146	0.345 224	0.202 292	0.118 6	0.092 75	0.056 149	0.039 226	0.032 278	0.022 7
DCP 4	.049	1.986	0.534 145	0.380 238	0.197 312	0.101 16	0.045 65	0.029 127	0.023 194	0.021 213	0.016 295
DCP 5	.074	1.825	0.430 131	0.319 228	0.167 295	0.082 359	0.033 52	0.018 98	0.017 168	0.023 209	0.005 213
DCP 6	.099	1.728	0.374 115	0.278 216	0.154 285	0.063 354	0.032 50	0.013 74	0.011 152	0.019 183	0.017 268
DCP 7	.149	1.449	0.359 110	0.251 200	0.144 260	0.066 327	0.033 0	0.023 42	0.013 81	0.026 183	0.024 251
DCP 8	.200	1.286	0.338 108	0.216 199	0.127 251	0.064 303	0.047 346	0.032 43	0.014 75	0.026 161	0.013 234
DCP 9	.250	1.248	0.348 100	0.195 187	0.121 232	0.066 274	0.054 317	0.040 14	0.024 31	0.022 88	0.009 218
DCP10	.300	1.128	0.320 91	0.158 171	0.095 216	0.063 255	0.045 298	0.031 339	0.027 21	0.025 76	0.015 171
DCP11	.399	1.017	0.320 82	0.116 148	0.071 192	0.043 246	0.035 296	0.021 333	0.021 23	0.029 56	0.010 179
DCP12	.501	0.844	0.294 67	0.083 118	0.046 171	0.030 223	0.025 269	0.027 286	0.025 16	0.029 72	0.009 207
DCP13	.600	0.727	0.271 59	0.079 88	0.038 163	0.023 238	0.017 258	0.030 252	0.027 333	0.024 65	0.006 251
DCP14	.701	0.624	0.256 51	0.080 72	0.040 147	0.017 237	0.031 233	0.032 250	0.018 306	0.016 39	0.006 245
DCP15	.800	0.473	0.223 46	0.079 58	0.034 130	0.012 183	0.020 210	0.021 241	0.012 266	0.020 41	0.001 259
DCP16	.900	0.221	0.150 47	0.050 53	0.022 134	0.014 174	0.012 200	0.010 226	0.010 314	0.020 63	0.004 233
DCP17	.969	0.053	0.073 46	0.030 43	0.012 153	0.002 167	0.009 208	0.008 267	0.009 328	0.018 56	0.002 116

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.11	0.089	0.394	5.12	0.0	19.93	12017.9	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
133.0	17352.	0.24E 07	-0.132	1.166	21.38	-0.00286	3.055	0.0
(436.2)	(362.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		19.934	5.125 0	0.231 6	0.045 254	0.010 341	0.016 355	0.026 120	0.035 231	0.014 345	0.009 325
CN		0.956	0.196 62	0.013 144	0.008 141	0.004 242	0.008 342	0.003 152	0.006 304	0.018 3	0.003 80
CM		-0.089	0.039 250	0.002 358	0.004 315	0.002 1	0.001 130	0.001 346	0.001 120	0.005 197	0.001 332
DCP 1	.010	1.703	0.075 86	0.016 165	0.011 76	0.003 43	0.004 118	0.002 222	0.005 233	0.011 309	0.006 137
DCP 2	.020	1.675	0.140 46	0.004 188	0.007 92	0.001 208	0.003 356	0.003 333	0.005 267	0.010 306	0.005 101
DCP 3	.030	1.637	0.169 41	0.001 331	0.006 49	0.005 221	0.001 125	0.003 279	0.007 329	0.005 297	0.009 58
DCP 4	.049	2.437	0.328 111	0.049 171	0.036 322	0.035 4	0.027 45	0.012 146	0.010 282	0.011 281	0.002 245
DCP 5	.074	2.381	0.337 90	0.041 110	0.026 307	0.031 316	0.030 330	0.005 124	0.004 186	0.010 295	0.003 181
DCP 6	.099	2.378	0.386 59	0.119 79	0.041 136	0.027 274	0.028 243	0.005 46	0.003 290	0.018 345	0.008 58
DCP 7	.149	1.588	0.241 28	0.061 114	0.027 241	0.022 228	0.034 18	0.015 30	0.027 310	0.012 271	0.018 30
DCP 8	.200	1.188	0.219 41	0.012 288	0.009 93	0.009 4	0.016 45	0.009 131	0.016 281	0.014 352	0.011 84
DCP 9	.250	1.148	0.229 45	0.016 216	0.007 327	0.012 34	0.005 58	0.011 203	0.008 295	0.026 346	0.008 88
DCP10	.300	1.058	0.214 48	0.014 200	0.003 349	0.007 307	0.006 342	0.007 191	0.006 341	0.024 345	0.005 25
DCP11	.399	0.998	0.217 56	0.017 200	0.006 126	0.003 309	0.012 326	0.001 196	0.007 6	0.028 21	0.004 268
DCP12	.501	0.872	0.220 60	0.017 190	0.011 128	0.012 182	0.010 302	0.004 156	0.004 317	0.023 13	0.007 38
DCP13	.600	0.785	0.232 68	0.018 186	0.013 144	0.011 193	0.012 307	0.003 282	0.010 288	0.022 9	0.006 56
DCP14	.701	0.720	0.209 73	0.023 153	0.020 138	0.007 208	0.005 269	0.003 154	0.007 283	0.023 7	0.006 180
DCP15	.800	0.581	0.187 77	0.011 155	0.023 147	0.008 188	0.004 15	0.009 140	0.004 278	0.014 9	0.008 186
DCP16	.900	0.254	0.134 73	0.008 45	0.006 130	0.001 313	0.007 11	0.004 161	0.002 323	0.018 27	0.008 96
DCP17	.969	0.046	0.064 66	0.004 43	0.015 112	0.004 161	0.004 144	0.004 194	0.001 318	0.021 14	0.003 265

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.12	3.087	0.401	5.15	0.0	0.03	12015.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
135.5	35364.	0.47E 07	-0.030	0.600	5.10	-0.00077	0.833	0.0
(444.6)	(738.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.027	5.152 0	0.241 7	0.044 261	0.007 179	0.009 1	0.027 115	0.025 194	0.036 70	0.036 10
CN		0.127	0.474 354	0.018 356	0.003 0	0.001 295	0.001 278	0.002 199	0.001 77	0.002 13	0.001 243
CM		-0.016	0.013 308	0.001 319	0.001 179	0.000 58	0.000 304	0.001 106	0.001 285	0.001 257	0.000 74
DCP 1	.010	-0.739	3.394 348	0.251 34	0.046 123	0.004 76	0.008 120	0.026 154	0.008 265	0.012 301	0.007 222
DCP 2	.020	-0.305	2.402 351	0.094 327	0.029 323	0.011 15	0.004 108	0.023 171	0.008 298	0.007 303	0.007 262
DCP 3	.030	-0.030	2.030 351	0.077 322	0.014 327	0.000 85	0.002 241	0.012 167	0.005 300	0.005 296	0.006 264
DCP 4	.049	0.171	1.863 351	0.064 324	0.011 350	0.002 322	0.003 285	0.006 175	0.003 339	0.007 269	0.003 153
DCP 5	.074	0.321	1.346 351	0.053 345	0.007 3	0.005 328	0.004 273	0.009 165	0.003 80	0.008 316	0.003 75
DCP 6	.099	0.375	1.186 351	0.042 339	0.010 346	0.001 72	0.006 342	0.007 171	0.003 331	0.007 299	0.004 92
DCP 7	.149	0.246	0.861 352	0.034 351	0.002 353	0.006 43	0.011 313	0.007 155	0.003 305	0.004 295	0.002 45
DCP 8	.200	0.212	0.705 355	0.027 351	0.003 320	0.001 133	0.001 261	0.004 156	0.004 19	0.007 330	0.002 234
DCP 9	.250	0.168	0.622 354	0.027 1	0.004 2	0.004 266	0.006 263	0.006 239	0.002 294	0.000 322	0.003 224
DCP10	.300	0.193	0.521 354	0.023 1	0.003 325	0.001 258	0.003 296	0.003 213	0.001 348	0.002 14	0.002 339
DCP11	.399	0.164	0.414 355	0.020 357	0.003 19	0.001 290	0.003 294	0.001 337	0.003 78	0.004 47	0.003 29
DCP12	.501	0.123	0.319 0	0.013 5	0.005 18	0.002 63	0.001 233	0.000 79	0.001 175	0.002 21	0.004 162
DCP13	.600	0.148	0.243 3	0.010 10	0.003 54	0.000 153	0.002 199	0.003 209	0.007 137	0.003 32	0.002 185
DCP14	.701	0.193	0.187 6	0.006 35	0.004 315	0.002 300	0.004 114	0.004 284	0.005 44	0.004 87	0.005 280
DCP15	.820	0.094	0.097 9	0.005 57	0.002 31	0.001 325	0.001 135	0.001 257	0.003 144	0.004 107	0.003 210
DCP16	.900	-0.086	0.024 19	0.005 196	0.005 0	0.007 240	0.003 108	0.004 265	0.002 7	0.003 16	0.005 15
DCP17	.969	-0.041	0.024 163	0.006 166	0.002 284	0.003 153	0.000 96	0.001 165	0.004 117	0.002 101	0.005 245

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.07	0.087	0.399	5.15	0.0	2.50	12015.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
134.6	35000.	0.47E 07	-0.026	0.845	7.60	-0.00076	0.825	0.0
(441.5)	(731.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.503	5.154 0	0.245 9	0.034 262	0.003 278	0.020 349	0.016 133	0.023 182	0.013 102	0.006 291
CN		0.374	0.472 354	0.020 8	0.006 328	0.002 93	0.003 314	0.002 189	0.002 57	0.004 86	0.003 281
CM		-0.011	0.013 312	0.002 261	0.001 147	0.000 275	0.000 146	0.000 100	0.001 261	0.002 273	0.001 67
DCP 1	.010	1.041	3.157 348	0.123 358	0.029 134	0.012 93	0.023 288	0.014 156	0.006 321	0.004 262	0.003 31
DCP 2	.020	0.928	2.414 351	0.089 358	0.050 336	0.003 336	0.011 293	0.016 177	0.005 80	0.009 31	0.009 272
DCP 3	.030	1.024	2.075 350	0.072 344	0.032 329	0.003 115	0.015 310	0.009 194	0.006 57	0.002 346	0.002 93
DCP 4	.049	1.057	1.728 351	0.059 327	0.017 315	0.001 205	0.009 294	0.007 153	0.005 330	0.009 332	0.004 26
DCP 5	.074	1.035	1.374 351	0.047 339	0.015 338	0.002 140	0.009 294	0.007 166	0.005 292	0.006 312	0.001 277
DCP 6	.099	0.970	1.172 351	0.044 357	0.014 324	0.003 53	0.005 348	0.006 161	0.004 303	0.005 255	0.002 206
DCP 7	.149	0.705	0.870 352	0.032 355	0.004 326	0.002 218	0.004 96	0.008 146	0.002 293	0.005 270	0.003 121
DCP 8	.200	0.584	0.714 355	0.026 356	0.009 330	0.003 188	0.006 321	0.005 183	0.004 307	0.007 338	0.002 344
DCP 9	.250	0.505	0.613 354	0.030 9	0.004 329	0.003 93	0.001 246	0.002 86	0.003 11	0.007 84	0.004 319
DCP10	.300	0.467	0.515 354	0.026 11	0.006 310	0.002 68	0.003 265	0.003 215	0.002 56	0.006 69	0.004 305
DCP11	.399	0.400	0.412 359	0.021 23	0.003 346	0.002 62	0.003 345	0.003 277	0.002 64	0.008 105	0.003 315
DCP12	.501	0.287	0.315 1	0.017 12	0.003 323	0.001 332	0.004 317	0.002 279	0.003 69	0.004 96	0.003 286
DCP13	.600	0.269	0.236 3	0.012 31	0.005 334	0.005 83	0.005 315	0.003 240	0.003 117	0.006 133	0.006 267
DCP14	.701	0.277	0.162 5	0.013 48	0.005 317	0.002 114	0.003 329	0.002 213	0.003 102	0.007 106	0.005 250
DCP15	.500	0.138	0.089 10	0.008 70	0.005 323	0.003 30	0.002 8	0.002 86	0.005 87	0.009 99	0.002 229
DCP16	.900	-0.074	0.024 22	0.006 55	0.008 339	0.006 173	0.003 168	0.003 270	0.007 31	0.008 51	0.006 277
DCP17	.969	-0.050	0.019 170	0.002 275	0.001 107	0.002 30	0.004 330	0.005 111	0.003 130	0.005 77	0.001 345

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.16	0.088	0.398	5.16	0.0	5.03	12015.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
134.3	34909.	0.47E 07	-0.023	1.056	10.20	-0.00089	0.965	0.0
(440.5)	(729.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		5.025	5.159 0	0.236 8	0.038 251	0.007 300	0.019 351	0.005 116	0.019 184	0.011 87	0.002 226
CN		0.010	0.449 356	0.035 17	0.008 276	0.002 156	0.003 21	0.003 284	0.002 69	0.007 49	0.002 202
CM		-0.003	0.017 317	0.004 242	0.001 77	0.000 332	0.001 239	0.001 126	0.001 243	0.002 242	0.001 42
DCP 1	.010	2.851	3.344 349	0.232 298	0.036 195	0.057 228	0.061 148	0.033 65	0.014 344	0.020 13	0.010 311
DCP 2	.020	2.715	2.445 352	0.160 323	0.129 179	0.143 79	0.115 345	0.068 255	0.023 175	0.005 1	0.024 153
DCP 3	.030	2.354	1.980 351	0.131 22	0.089 330	0.009 254	0.003 305	0.007 251	0.008 149	0.017 38	0.007 349
DCP 4	.049	1.928	1.669 351	0.105 15	0.045 328	0.020 243	0.008 222	0.005 200	0.002 268	0.004 54	0.003 100
DCP 5	.074	1.732	1.329 351	0.087 13	0.023 323	0.008 227	0.004 270	0.003 206	0.005 291	0.003 27	0.003 113
DCP 6	.099	1.570	1.118 352	0.076 14	0.017 314	0.005 210	0.001 153	0.003 199	0.003 100	0.004 61	0.005 104
DCP 7	.149	1.146	0.861 353	0.049 12	0.015 309	0.007 202	0.010 316	0.005 268	0.004 250	0.007 354	0.004 71
DCP 8	.200	0.940	0.686 356	0.049 18	0.008 291	0.003 67	0.003 7	0.002 266	0.005 256	0.003 355	0.003 205
DCP 9	.250	0.809	0.584 355	0.043 6	0.006 269	0.004 158	0.002 5	0.000 252	0.005 75	0.007 49	0.004 152
DCP10	.300	0.723	0.484 356	0.039 21	0.009 280	0.001 56	0.002 4	0.001 28	0.005 37	0.009 31	0.003 192
DCP11	.399	0.602	0.382 1	0.035 28	0.008 261	0.001 2	0.001 36	0.004 321	0.006 77	0.008 58	0.003 265
DCP12	.501	0.438	0.295 3	0.027 28	0.007 263	0.001 50	0.005 9	0.006 258	0.003 58	0.006 44	0.005 219
DCP13	.600	0.375	0.211 7	0.026 36	0.009 256	0.003 118	0.005 44	0.002 18	0.007 78	0.007 33	0.007 218
DCP14	.701	0.344	0.132 11	0.030 44	0.010 284	0.001 178	0.004 66	0.009 307	0.003 112	0.011 67	0.001 355
DCP15	.800	0.173	0.073 23	0.022 41	0.008 279	0.004 143	0.005 21	0.005 322	0.001 344	0.012 52	0.004 203
DCP16	.900	-0.067	0.027 33	0.008 45	0.004 232	0.004 222	0.005 51	0.002 162	0.003 85	0.010 82	0.003 215
DCP17	.969	-0.060	0.010 168	0.005 324	0.005 222	0.004 94	0.004 110	0.005 263	0.006 36	0.007 48	0.002 77

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.13	0.088	0.397	5.15	0.0	7.50	12015.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
133.8	34704.	0.47E 07	-0.040	1.208	11.96	-0.00085	0.914	0.0
(439.0)	(724.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.503	5.147 0	0.252 11	0.051 295	0.019 257	0.015 29	0.014 95	0.028 242	0.022 157	0.002 281
CN		0.773	0.334 9	0.119 22	0.043 278	0.017 160	0.002 53	0.001 22	0.002 297	0.008 131	0.004 351
CM		-0.003	0.013 277	0.011 91	0.011 336	0.009 242	0.004 138	0.002 113	0.001 38	0.005 324	0.001 193
DCP 1	.010	3.581	1.750 351	1.053 68	0.783 350	0.405 289	0.104 202	0.045 279	0.087 227	0.046 164	0.023 62
DCP 2	.020	2.890	1.419 2	0.729 49	0.413 336	0.261 271	0.189 214	0.106 175	0.082 162	0.081 111	0.069 64
DCP 3	.030	2.754	1.328 0	0.560 46	0.313 329	0.213 256	0.149 194	0.116 140	0.081 85	0.071 32	0.057 353
DCP 4	.049	2.449	1.028 1	0.527 46	0.284 323	0.151 236	0.078 157	0.032 106	0.022 107	0.049 36	0.045 347
DCP 5	.074	2.161	0.841 3	0.419 40	0.225 309	0.129 215	0.067 127	0.324 65	0.018 56	0.046 7	0.036 304
DCP 6	.099	1.947	0.754 5	0.343 31	0.187 294	0.114 198	0.059 108	0.029 51	0.021 27	0.052 341	0.036 271
DCP 7	.149	1.455	0.640 6	0.254 20	0.141 273	0.087 169	0.053 77	0.011 352	0.011 28	0.030 331	0.018 246
DCP 8	.200	1.210	0.551 10	0.193 12	0.116 263	0.073 164	0.034 81	0.018 41	0.026 354	0.034 304	0.023 217
DCP 9	.250	1.061	0.518 7	0.147 350	0.084 230	0.060 123	0.026 36	0.015 353	0.024 313	0.025 217	0.020 139
DCP10	.300	0.935	0.434 8	0.118 349	0.068 217	0.049 105	0.024 1	0.008 302	0.011 301	0.017 179	0.009 112
DCP11	.399	0.709	0.345 13	0.092 355	0.050 218	0.038 102	0.019 351	0.007 316	0.016 278	0.029 168	0.013 81
DCP12	.501	0.556	0.248 19	0.079 358	0.035 208	0.033 88	0.018 328	0.004 282	0.008 255	0.026 151	0.008 52
DCP13	.600	0.441	0.165 28	0.067 11	0.023 210	0.024 79	0.018 315	0.005 217	0.003 235	0.022 148	0.010 12
DCP14	.701	0.379	0.098 50	0.055 18	0.017 190	0.027 57	0.019 289	0.004 243	0.003 116	0.017 132	0.006 7
DCP15	.800	0.203	0.072 43	0.025 348	0.023 148	0.021 43	0.010 279	0.001 256	0.006 189	0.017 125	0.007 333
DCP16	.900	-0.034	0.059 13	0.030 269	0.019 129	0.011 32	0.003 299	0.006 312	0.005 160	0.014 98	0.006 303
DCP17	.969	-0.053	0.022 12	0.019 269	0.003 184	0.005 122	0.002 223	0.006 330	0.009 168	0.008 134	0.005 301

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
3.0	23.12	0.088	0.397	5.11	0.0	10.00	12015.5	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
133.6	34641.	0.47E 07	-0.097	1.326	13.89	-0.00110	1.184	0.0
(438.2)	(723.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		10.003	5.112 0	0.248 17	0.020 248	0.034 16	0.044 337	0.042 232	0.016 117	0.023 92	0.009 265
CN		0.897	0.233 36	0.134 35	0.032 1	0.032 304	0.016 213	0.010 177	0.012 45	0.009 77	0.005 342
CM		-0.014	0.092 211	0.026 99	0.007 48	0.012 37	0.010 314	0.003 284	0.005 252	0.004 246	0.002 163
DCP 1	.010	4.007	0.146 323	1.304 81	0.224 86	0.544 72	0.281 5	0.062 50	0.106 3	0.023 58	0.057 4
DCP 2	.020	3.251	0.303 37	0.832 77	0.296 64	0.315 49	0.254 3	0.091 354	0.154 6	0.094 329	0.087 348
DCP 3	.030	3.021	0.233 42	0.802 80	0.362 48	0.284 13	0.169 326	0.074 310	0.091 325	0.083 287	0.071 261
DCP 4	.049	2.756	0.293 43	0.681 67	0.184 22	0.125 16	0.109 323	0.037 261	0.049 338	0.049 280	0.030 245
DCP 5	.074	2.421	0.322 44	0.529 59	0.135 15	0.116 5	0.101 302	0.039 244	0.041 299	0.043 227	0.017 196
DCP 6	.099	2.164	0.350 45	0.450 52	0.104 9	0.110 354	0.107 286	0.045 226	0.025 276	0.033 206	0.014 175
DCP 7	.149	1.663	0.380 38	0.316 40	0.087 358	0.104 328	0.080 256	0.030 210	0.018 232	0.011 188	0.020 218
DCP 8	.200	1.381	0.354 38	0.246 41	0.092 3	0.104 322	0.065 256	0.031 228	0.031 205	0.027 176	0.022 160
DCP 9	.250	1.221	0.380 34	0.203 20	0.065 337	0.092 295	0.074 217	0.036 172	0.030 134	0.031 101	0.022 76
DCP10	.300	1.081	0.348 34	0.175 12	0.059 332	0.087 281	0.064 199	0.024 166	0.026 127	0.027 92	0.015 59
DCP11	.399	0.901	0.312 35	0.128 6	0.338 324	0.066 277	0.050 192	0.029 179	0.040 111	0.029 74	0.012 33
DCP12	.501	0.673	0.260 36	0.100 352	0.023 300	0.054 255	0.046 166	0.017 147	0.030 85	0.024 58	0.016 7
DCP13	.600	0.540	0.209 40	0.075 339	0.013 281	0.044 233	0.041 140	0.013 90	0.025 75	0.016 50	0.013 335
DCP14	.701	0.448	0.147 49	0.065 313	0.021 176	0.031 213	0.036 114	0.009 52	0.019 44	0.014 51	0.013 341
DCP15	.800	0.266	0.128 34	0.061 286	0.019 197	0.031 199	0.029 105	0.011 98	0.024 33	0.008 44	0.008 328
DCP16	.900	0.022	0.123 11	0.053 275	0.019 254	0.027 193	0.020 112	0.010 91	0.014 13	0.008 59	0.011 284
DCP17	.969	-0.035	0.052 7	0.022 287	0.011 288	0.014 199	0.006 102	0.005 109	0.006 77	0.010 96	0.003 324

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
3.0	23.14	0.088	0.396	5.05	0.0	12.47	12015.6	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
133.3	34493.	0.47E 07	-0.124	1.399	14.45	-0.00169	1.806	0.0
(437.3)	(720.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.471	5.054 0	0.250 16	0.032 228	0.012 85	0.080 95	0.085 20	0.047 233	0.016 250	0.011 213
CN		0.994	0.204 72	0.083 62	0.062 59	0.011 24	0.026 358	0.011 287	0.012 268	0.011 209	0.008 199
CM		-0.028	0.059 203	0.021 120	0.018 152	0.008 44	0.012 118	0.006 51	0.003 84	0.003 106	0.002 26
DCP 1	.010	4.379	1.265 189	0.818 110	0.543 163	0.210 165	0.181 179	0.036 198	0.098 196	0.036 250	0.040 174
DCP 2	.020	3.456	0.700 169	0.695 108	0.338 150	0.321 132	0.188 166	0.118 194	0.153 205	0.074 218	0.073 230
DCP 3	.030	3.072	0.851 164	0.652 96	0.312 146	0.331 113	0.129 111	0.155 119	0.073 132	0.087 145	0.050 135
DCP 4	.049	2.875	0.585 145	0.361 90	0.289 123	0.093 74	0.087 123	0.048 56	0.037 201	0.031 185	0.048 176
DCP 5	.074	2.518	0.465 134	0.300 89	0.255 106	0.082 62	0.091 92	0.048 36	0.028 118	0.016 66	0.030 114
DCP 6	.099	2.288	0.398 117	0.259 84	0.232 97	0.077 49	0.094 77	0.052 25	0.026 90	0.023 67	0.043 75
DCP 7	.149	1.788	0.335 90	0.207 73	0.177 74	0.052 26	0.080 51	0.039 351	0.019 60	0.021 358	0.013 46
DCP 8	.200	1.471	0.295 87	0.189 75	0.134 70	0.048 53	0.070 41	0.031 17	0.028 7	0.014 348	0.015 47
DCP 9	.250	1.314	0.324 73	0.171 59	0.139 47	0.048 9	0.067 21	0.040 356	0.031 330	0.028 330	0.017 327
DCP10	.300	1.180	0.318 64	0.142 48	0.128 36	0.046 355	0.078 3	0.049 317	0.041 309	0.034 291	0.014 278
DCP11	.399	1.001	0.304 56	0.089 38	0.104 34	0.038 329	0.067 355	0.047 302	0.040 284	0.028 289	0.026 254
DCP12	.501	0.770	0.282 49	0.061 11	0.076 22	0.030 314	0.054 330	0.034 274	0.034 273	0.021 280	0.022 239
DCP13	.600	0.623	0.251 45	0.054 329	0.050 4	0.023 279	0.043 314	0.029 243	0.021 265	0.011 244	0.019 216
DCP14	.701	0.522	0.216 43	0.067 300	0.064 339	0.027 242	0.041 295	0.029 206	0.010 238	0.009 296	0.012 182
DCP15	.800	0.337	0.204 28	0.066 290	0.045 321	0.019 232	0.045 280	0.027 196	0.011 223	0.010 273	0.012 166
DCP16	.900	0.071	0.168 15	0.036 327	0.052 321	0.017 268	0.029 268	0.019 196	0.010 171	0.006 269	0.006 125
DCP17	.969	-0.014	0.077 13	0.016 351	0.028 332	0.007 262	0.013 266	0.010 219	0.005 215	0.001 9	0.011 147

173

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	23.12	0.088	0.396	5.05	0.0	15.03	12015.7	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	133.1	34474.	0.47E 07	-0.531	1.339	14.58	-0.00179	1.909	0.0
	(436.6)	(720.0)							

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		15.032	5.047 0	0.222 7	0.041 230	0.024 207	0.006 274	0.016 117	0.018 152	0.011 133	0.006 290
CN		1.005	0.226 92	0.053 122	0.021 127	0.016 110	0.016 126	0.005 80	0.009 62	0.006 31	0.002 182
CM		-0.049	0.070 197	0.024 217	0.009 175	0.012 214	0.006 250	0.003 255	0.002 257	0.002 289	0.001 333
DCP 1	.010	3.542	2.280 171	0.709 247	0.085 212	0.202 254	0.131 340	0.083 61	0.032 323	0.055 51	0.038 198
DCP 2	.020	3.009	1.602 163	0.576 222	0.241 221	0.232 269	0.120 353	0.066 54	0.052 57	0.046 82	0.037 175
DCP 3	.030	2.783	1.300 163	0.369 207	0.337 192	0.228 245	0.103 264	0.062 338	0.050 28	0.066 73	0.043 130
DCP 4	.049	2.883	0.721 160	0.266 187	0.160 183	0.138 221	0.060 261	0.045 317	0.061 31	0.046 52	0.044 86
DCP 5	.074	2.542	0.568 147	0.246 184	0.110 163	0.127 201	0.040 222	0.036 256	0.031 353	0.043 356	0.036 32
DCP 6	.099	2.318	0.445 128	0.260 185	0.107 136	0.132 193	0.047 231	0.023 322	0.047 319	0.026 3	
DCP 7	.149	1.774	0.474 106	0.148 169	0.086 119	0.087 162	0.036 205	0.023 207	0.009 282	0.032 310	0.003 329
DCP 8	.200	1.434	0.440 112	0.148 144	0.088 122	0.076 153	0.044 184	0.020 235	0.019 257	0.021 307	0.031 317
DCP 9	.250	1.310	0.417 100	0.152 115	0.080 110	0.072 119	0.061 149	0.016 130	0.006 155	0.014 275	0.021 281
DCP10	.300	1.184	0.339 91	0.139 104	0.064 108	0.069 99	0.060 132	0.017 113	0.015 122	0.008 208	0.016 223
DCP11	.399	1.032	0.288 75	0.122 89	0.033 95	0.061 83	0.054 128	0.017 96	0.025 113	0.013 116	0.013 212
DCP12	.501	0.829	0.268 56	0.097 74	0.020 29	0.047 57	0.043 106	0.016 59	0.022 94	0.012 71	0.014 176
DCP13	.600	0.688	0.269 44	0.073 56	0.037 336	0.067 42	0.023 78	0.014 47	0.018 69	0.011 55	0.004 110
DCP14	.701	0.549	0.259 36	0.056 25	0.039 327	0.043 18	0.019 52	0.009 62	0.012 43	0.006 107	0.006 107
DCP15	.800	0.415	0.255 20	0.068 21	0.021 330	0.035 16	0.020 36	0.009 76	0.006 24	0.006 100	0.003 123
DCP16	.900	0.191	0.182 14	0.066 33	0.019 30	0.024 7	0.022 6	0.006 71	0.005 3	0.006 57	0.006 67
DCP17	.969	0.015	0.070 17	0.036 33	0.006 79	0.007 9	0.004 116	0.005 65	0.010 53	0.003 88	0.002 197

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	23.13	0.089	0.396	5.04	0.0	17.51	12015.8	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	133.0	34493.	0.47E 07	-0.143	1.270	14.77	-0.00247	2.635	0.0
	(436.5)	(720.4)							

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		17.510	5.004 0	0.214 4	0.049 264	0.003 242	0.029 49	0.023 39	0.032 182	0.003 254	0.004 347
CN		0.995	0.210 92	0.031 152	0.022 203	0.013 225	0.010 269	0.007 291	0.001 124	0.007 349	0.007 330
CM		-0.070	0.056 212	0.030 228	0.011 294	0.004 326	0.003 29	0.003 64	0.000 187	0.002 153	0.001 122
DCP 1	.010	2.677	1.267 169	0.558 252	0.260 316	0.181 13	0.128 104	0.063 190	0.030 238	0.006 339	0.009 95
DCP 2	.020	2.443	1.013 162	0.488 246	0.261 310	0.127 18	0.088 117	0.053 169	0.046 234	0.025 330	0.007 70
DCP 3	.030	2.380	0.998 161	0.461 250	0.192 309	0.008 340	0.058 59	0.043 141	0.036 252	0.023 252	0.007 285
DCP 4	.049	2.574	0.604 167	0.308 232	0.116 297	0.034 277	0.039 347	0.028 86	0.007 186	0.016 12	0.016 347
DCP 5	.074	2.344	0.432 154	0.254 212	0.128 277	0.031 291	0.043 322	0.039 66	0.011 91	0.004 14	0.016 247
DCP 6	.099	2.183	0.318 130	0.247 201	0.143 264	0.060 261	0.043 309	0.035 9	0.015 135	0.018 61	0.007 309
DCP 7	.149	1.733	0.355 97	0.207 193	0.090 244	0.034 282	0.025 316	0.010 32	0.009 108	0.008 309	0.016 323
DCP 8	.200	1.388	0.355 114	0.160 189	0.051 229	0.044 260	0.035 325	0.012 16	0.010 96	0.015 224	0.020 305
DCP 9	.250	1.318	0.368 103	0.135 168	0.074 191	0.053 229	0.035 279	0.027 329	0.011 54	0.001 47	0.013 317
DCP10	.300	1.210	0.320 97	0.102 153	0.070 179	0.053 207	0.034 257	0.022 322	0.003 11	0.011 47	0.009 32
DCP11	.399	1.067	0.283 82	0.060 104	0.068 164	0.061 201	0.023 252	0.023 308	0.005 63	0.013 48	0.014 29
DCP12	.501	0.875	0.263 65	0.093 70	0.056 151	0.053 201	0.016 223	0.018 275	0.005 340	0.017 356	0.017 358
DCP13	.600	0.730	0.247 53	0.107 54	0.043 135	0.052 193	0.009 205	0.016 262	0.005 200	0.017 350	0.010 9
DCP14	.701	0.626	0.236 38	0.104 42	0.029 98	0.048 72	0.005 158	0.012 221	0.004 206	0.007 334	0.005 276
DCP15	.800	0.485	0.209 34	0.095 41	0.026 76	0.015 109	0.010 106	0.012 220	0.002 300	0.013 286	0.009 251
DCP16	.900	0.206	0.135 38	0.071 34	0.019 69	0.010 105	0.005 228	0.009 202	0.005 71	0.002 284	0.010 270
DCP17	.969	0.040	0.060 44	0.028 50	0.011 105	0.010 117	0.005 155	0.004 179	0.004 338	0.007 348	0.005 235

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUN.O HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	0.0	23.14	0.089	0.396	5.08	0.0	19.94	12015.9	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	132.9	34488.	0.47E 07	-0.160	1.248	19.50	-0.00348	3.711	0.0
	(436.1)	(720.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		19.945	5.001	0	0.218	8	0.046	256	0.008	198	0.024	35	0.012	84	0.034	177	0.018	144	0.009	324
CN		0.999	0.196	85	0.031	118	0.016	113	0.016	83	0.008	137	0.005	1	0.009	119	0.006	131	0.005	296
CM		-0.090	0.048	248	0.010	247	0.006	284	0.004	233	0.002	292	0.002	166	0.002	244	0.001	284	0.001	199
DCP 1	.010	2.123	0.484	257	0.184	265	0.139	43	0.110	136	0.035	247	0.023	77	0.024	185	0.015	308	0.019	42
DCP 2	.020	2.036	0.366	166	0.135	257	0.066	56	0.052	124	0.013	221	0.005	81	0.007	20	0.012	7		
DCP 3	.030	2.039	0.331	137	0.105	247	0.082	332	0.053	78	0.011	218	0.007	11	0.016	202	0.018	248	0.006	317
DCP 4	.049	2.379	0.305	170	0.090	142	0.074	274	0.013	8	0.020	83	0.024	230	0.016	181	0.017	153	0.013	188
DCP 5	.074	2.222	0.218	199	0.108	136	0.056	253	0.015	271	0.014	79	0.006	273	0.025	180	0.023	106	0.007	249
DCP 6	.099	2.135	0.101	121	0.122	129	0.079	237	0.025	265	0.007	162	0.017	22	0.011	139	0.018	130	0.006	327
DCP 7	.149	1.673	0.201	68	0.077	165	0.041	132	0.023	22	0.019	206	0.007	60	0.022	179	0.022	176	0.020	282
DCP 8	.200	1.336	0.233	74	0.024	194	0.019	118	0.021	145	0.003	32	0.004	244	0.008	133	0.007	198	0.013	273
DCP 9	.250	1.285	0.265	81	0.036	158	0.029	143	0.019	107	0.002	129	0.007	62	0.018	133	0.009	159	0.003	249
DCP10	.300	1.191	0.259	70	0.039	149	0.025	127	0.019	119	0.006	229	0.000	50	0.012	96	0.005	115	0.006	255
DCP11	.399	1.094	0.265	63	0.039	135	0.035	106	0.037	121	0.016	185	0.003	39	0.012	149	0.006	128	0.010	255
DCP12	.501	0.933	0.256	60	0.035	112	0.028	89	0.036	86	0.019	143	0.003	27	0.010	156	0.008	63	0.005	212
DCP13	.600	0.806	0.243	77	0.045	88	0.031	97	0.032	65	0.025	120	0.009	24	0.014	98	0.006	144	0.005	105
DCP14	.701	0.711	0.225	72	0.050	72	0.022	101	0.027	47	0.020	103	0.008	332	0.016	74	0.008	125	0.010	328
DCP15	.800	0.545	0.195	72	0.051	64	0.025	125	0.015	27	0.008	114	0.010	345	0.014	56	0.010	125	0.013	349
DCP16	.900	0.243	0.133	70	0.031	55	0.013	96	0.007	317	0.005	346	0.011	332	0.009	41	0.004	103	0.004	354
DCP17	.969	0.056	0.062	78	0.012	77	0.007	75	0.005	301	0.003	30	0.002	345	0.005	317	0.005	18	0.004	295

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	0.0	23.06	0.086	0.403	5.15	0.0	0.33	12019.1	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	136.4	48220.	0.64E 07	-0.029	0.595	5.13	-0.00069	3.754	0.0
	(447.5)	(1007.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		0.003	5.151	0	0.235	8	0.035	264	0.009	195	0.013	20	0.011	68	0.012	216	0.003	277	0.003	255
CN		0.121	0.478	354	0.016	358	0.002	16	0.003	65	0.001	6	0.002	7	0.001	256	0.001	93		
CM		-0.015	0.011	308	0.001	335	0.000	138	0.000	257	0.001	176	0.000	138	0.001	216	0.000	144	0.000	226
DCP 1	.010	-0.756	3.448	348	0.287	34	0.079	123	0.013	168	0.011	142	0.013	190	0.038	256	0.002	37	0.008	79
DCP 2	.020	-0.337	2.438	350	0.094	337	0.020	331	0.012	35	0.009	132	0.007	181	0.005	314	0.004	192	0.003	55
DCP 3	.030	-0.046	2.045	351	0.079	325	0.010	340	0.031	327	0.032	187	0.035	187	0.004	189	0.003	154	0.003	89
DCP 4	.049	0.170	1.676	351	0.062	325	0.005	350	0.033	304	0.002	231	0.002	227	0.003	344	0.006	136	0.003	186
DCP 5	.074	0.327	1.345	351	0.049	338	0.007	22	0.001	292	0.001	241	0.002	238	0.002	56	0.001	99	0.003	120
DCP 6	.099	0.364	1.163	351	0.040	339	0.009	349	0.006	247	0.005	187	0.004	14	0.006	312	0.007	189	0.004	138
DCP 7	.149	0.247	0.869	352	0.033	341	0.002	7	0.003	338	0.001	165	0.003	23	0.001	113	0.002	42	0.001	256
DCP 8	.200	0.200	0.712	355	0.029	355	0.003	356	0.001	186	0.001	252	0.002	107	0.002	136	0.007	199	0.003	196
DCP 9	.250	0.180	0.621	353	0.019	1	0.004	291	0.002	248	0.003	339	0.002	264	0.004	297	0.004	340	0.003	42
DCP10	.300	0.187	0.521	354	0.019	1	0.005	5	0.002	200	0.004	333	0.002	213	0.001	10	0.001	73	0.001	79
DCP11	.399	0.149	0.420	359	0.015	18	0.005	1	0.002	273	0.004	44	0.002	315	0.001	43	0.002	229	0.004	73
DCP12	.501	0.117	0.318	0	0.010	1	0.003	56	0.002	65	0.001	348	0.003	310	0.002	15	0.002	241	0.004	125
DCP13	.600	0.137	0.245	2	0.007	349	0.002	68	0.004	55	0.005	58	0.001	338	0.002	47	0.002	342	0.002	117
DCP14	.701	0.193	0.173	3	0.006	69	0.002	30	0.003	133	0.002	326	0.002	205	0.004	24	0.002	280	0.002	9
DCP15	.800	0.090	0.101	7	0.003	114	0.000	308	0.001	70	0.003	286	0.001	330	0.005	314	0.003	77	0.002	310
DCP16	.900	-0.086	0.031	10	0.003	211	0.003	336	0.002	8	0.002	30	0.001	93	0.003	115	0.003	359	0.002	44
DCP17	.969	-0.042	0.021	180	0.003	165	0.005	204	0.002	119	0.002	322	0.001	190	0.004	34	0.005	265	0.001	167

175

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.06	0.087	0.400	5.16	0.0	2.49	12019.2	20

V	Q	RN	CNMR(N)	CNMR(X)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
135.2	47622.	0.64E 07	-0.022	0.835	7.53	-0.03374	3.78ν	0.0
(443.5)	(994.6)							

HARMONIC ANALYSIS

DATA TYPE	K/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PH.	RES 8 PHI	RES 9 PHI
ALPHA		2.455	5.159 0	0.207 11	0.041 268	0.001 31	0.023 1	3.017 111	3.011 135	0.005 142	0.007 285
CN		0.363	0.477 354	0.018 8	0.002 344	0.001 51	0.002 296	0.002 184	3.000 355	0.000 71	0.001 157
CM		-0.010	0.012 387	0.001 280	0.000 19	3.000 223	3.000 169	0.030 211	3.000 345	0.001 196	0.003 349
DCP 1	.010	1.043	3.170 348	0.126 355	0.039 135	0.015 93	0.021 287	0.011 181	0.000 34.	0.011 177	0.005 350
DCP 2	.020	0.925	2.445 350	0.090 351	0.009 348	3.036 73	0.018 306	3.025 216	3.023 43	0.018 186	0.004 83
DCP 3	.030	1.010	2.080 350	0.075 349	0.021 328	0.005 44	0.013 297	0.009 203	3.036 347	0.011 207	0.006 73
DCP 4	.049	1.053	1.727 350	0.060 351	0.012 330	0.005 243	0.006 300	0.008 190	3.005 33.	0.009 196	0.002 101
DCP 5	.074	1.039	1.370 351	0.049 343	0.009 336	3.004 198	3.004 209	3.035 183	3.005 34.	0.003 212	0.002 318
DCP 6	.099	0.967	1.176 351	0.043 357	0.015 333	0.031 92	0.004 282	0.005 148	3.032 .	0.005 211	0.003 289
DCP 7	.149	0.702	0.875 352	0.032 354	0.005 337	3.002 133	0.006 266	0.008 158	3.025 345	0.005 153	0.002 249
DCP 8	.200	0.546	0.717 354	0.030 11	3.005 2	0.031 245	0.004 278	0.001 3	3.032 25.	0.006 213	0.001 286
DCP 9	.250	0.480	0.620 353	0.027 17	0.002 48	0.004 20	0.002 343	0.004 262	3.003 357	0.002 210	0.003 37
DCP10	.300	0.442	0.516 354	0.021 16	0.004 10	0.302 55	0.002 258	0.002 211	3.032 34	0.002 7	0.005 129
DCP11	.399	0.374	0.415 359	0.018 30	0.002 13	0.001 89	0.002 256	0.003 228	3.031 11.	0.002 79	0.004 103
DCP12	.501	0.273	0.315 0	0.015 35	0.004 326	0.003 355	0.001 325	0.001 52	3.001 27.	0.002 32	0.005 179
DCP13	.600	0.254	0.243 2	0.011 38	3.002 230	0.002 4	3.003 333	0.001 37	3.002 3.	0.004 354	0.001 130
DCP14	.701	0.275	0.165 4	0.013 36	0.002 21	0.002 45	0.002 18	0.001 199	3.002 17.	0.002 342	0.003 90
DCP15	.800	0.135	0.097 8	0.004 60	0.003 148	0.003 111	0.004 330	0.002 282	0.001 39	0.005 29	0.002 97
DCP16	.900	-0.074	3.036 16	0.001 327	0.003 289	3.033 281	0.001 157	3.004 141	3.036 345	0.002 25	0.003 266
DCP17	.969	-0.047	0.016 176	0.000 251	0.002 66	0.007 63	0.003 278	0.003 28	3.001 9.	0.002 205	0.001 209

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.11	0.088	0.398	5.16	0.0	4.98	12019.3	20

V	Q	RN	CNMR(N)	CNMR(X)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
134.2	47105.	0.64E 07	-0.022	1.059	10.14	-0.00009	0.956	0.0
(440.4)	(983.8)							

HARMONIC ANALYSIS

DATA TYPE	K/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.976	5.182 0	0.239 9	0.039 235	0.013 333	0.013 21	0.003 241	2.007 248	0.009 301	0.003 81
CN		0.612	0.456 355	0.036 19	0.007 280	0.002 166	0.002 96	0.001 287	0.021 2	0.006 295	0.002 57
CM		-0.004	0.016 315	0.004 243	0.001 87	0.001 336	0.001 268	0.000 144	0.000 172	0.002 147	0.001 286
DCP 1	.010	2.914	3.464 349	0.280 287	0.061 176	0.061 233	0.087 145	0.055 55	0.026 332	0.008 211	0.028 312
DCP 2	.020	2.203	2.431 351	0.133 344	0.059 194	0.067 83	0.091 347	0.086 253	0.049 166	0.018 134	0.012 51
DCP 3	.030	2.063	2.009 351	0.128 21	0.039 327	0.016 257	0.012 155	0.001 23	0.001 137	0.005 220	0.009 353
DCP 4	.049	1.940	1.684 351	0.099 16	0.040 325	0.014 248	0.007 187	0.004 88	0.004 38	0.012 218	0.003 34
DCP 5	.074	1.749	1.330 351	0.078 11	0.020 315	0.004 256	0.003 233	0.004 175	0.004 297	0.012 213	0.001 46
DCP 6	.099	1.567	1.129 352	0.073 17	0.017 313	0.004 211	0.004 207	0.001 118	0.001 0	0.011 214	0.005 47
DCP 7	.149	1.153	0.845 353	0.054 11	0.012 286	0.002 35	0.003 331	0.000 352	0.001 121	0.012 198	0.004 20
DCP 8	.200	0.934	0.691 356	0.045 20	0.008 287	0.001 44	0.003 341	0.002 317	0.002 297	0.012 191	0.003 77
DCP 9	.250	0.811	0.592 355	0.044 14	0.003 237	0.002 82	0.001 3	0.005 229	0.002 95	0.006 309	0.004 58
DCP10	.300	0.719	0.492 355	0.039 22	0.004 290	0.004 116	0.004 98	0.003 287	0.001 52	0.009 305	0.005 28
DCP11	.399	0.592	0.389 1	0.039 33	0.004 285	0.005 146	0.006 122	0.001 254	0.003 69	0.011 305	0.005 91
DCP12	.501	0.437	0.298 2	0.025 31	0.006 305	0.003 171	0.001 170	0.003 279	0.001 290	0.010 318	0.001 116
DCP13	.600	0.374	0.218 5	0.027 38	0.005 294	0.002 194	0.004 78	0.002 106	0.002 253	0.008 117	0.001 51
DCP14	.701	0.354	0.141 10	0.024 42	0.008 280	0.004 189	0.002 113	0.003 340	0.000 235	0.005 343	0.002 88
DCP15	.800	0.180	0.078 19	0.023 49	0.008 277	0.004 170	0.006 69	0.000 184	0.002 31	0.010 316	0.001 177
DCP16	.900	-0.058	0.027 27	0.011 38	0.003 235	0.003 117	0.001 183	0.002 307	0.007 1	0.009 325	0.007 82
DCP17	.969	-0.060	0.012 157	0.005 336	0.002 165	0.000 132	0.006 92	0.001 359	0.002 228	0.008 316	0.003 270

FORCED PITCHING OSCILLATION

AIRFOIL NLR 1

	TUNED HZ 0.0	DRIVE HZ 23.15	K 0.088	MACH NO 0.398	DEL.ALPHA 5.16	DEL.H 0.0	ALPHA.0 7.48	TEST POINT 12019.4	CYCLES ANALYSED 20
	V 134.0 (439.6)	Q 47009. (981.8)	RN 0.64E 07	CN(MIN) -0.019	CN(MAX) 1.211	ALPHA.NMAX 12.16	AERO DAMP -0.00106	TDR 1.144	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.478	5.161 0	0.234 14	0.029 293	0.023 284	0.020 54	0.009 88	0.017 306	0.001 187	0.005 185
CN		0.760	0.336 8	0.113 24	0.042 274	0.016 152	0.004 8	0.002 104	0.005 22	0.005 61	0.001 194
CM		0.001	0.018 307	0.005 129	0.008 353	0.007 245	0.004 137	0.002 40	0.000 271	0.002 265	0.001 247
DCP 1	.010	3.030	2.150 349	0.841 72	0.726 357	0.414 277	0.127 211	0.033 287	0.097 249	0.094 167	0.047 82
DCP 2	.020	3.081	1.739 358	0.527 42	0.272 336	0.215 280	0.200 212	0.119 195	0.018 110	0.082 127	0.082 67
DCP 3	.030	2.903	1.609 359	0.421 26	0.214 302	0.139 227	0.096 168	0.082 111	0.063 46	0.045 3	0.035 302
DCP 4	.049	2.586	1.261 359	0.372 34	0.168 307	0.087 220	0.053 144	0.038 80	0.027 31	0.020 15	0.025 309
DCP 5	.074	2.263	1.008 0	0.295 24	0.143 292	0.078 194	0.054 112	0.031 45	0.022 1	0.021 344	0.031 269
DCP 6	.099	1.994	0.833 1	0.265 29	0.124 289	0.074 189	0.050 101	0.034 23	0.019 325	0.039 308	0.015 251
DCP 7	.149	1.476	0.636 3	0.205 25	0.100 279	0.059 176	0.032 83	0.019 352	0.002 323	0.007 36	0.012 243
DCP 8	.200	1.204	0.542 7	0.165 18	0.084 267	0.051 161	0.027 65	0.000 342	0.011 50	0.011 334	0.018 239
DCP 9	.250	1.045	0.477 7	0.144 8	0.074 246	0.049 128	0.028 18	0.007 257	0.009 22	0.010 317	0.020 190
DCP10	.300	0.911	0.386 9	0.126 10	0.059 245	0.039 120	0.024 6	0.008 269	0.006 354	0.006 312	0.010 176
DCP11	.399	0.740	0.299 16	0.110 17	0.050 245	0.034 118	0.021 350	0.015 241	0.006 85	0.006 45	0.007 168
DCP12	.501	0.540	0.220 21	0.089 17	0.038 240	0.025 108	0.015 324	0.010 225	0.007 18	0.000 211	0.008 110
DCP13	.600	0.436	0.152 31	0.078 22	0.030 244	0.024 94	0.017 314	0.010 211	0.003 356	0.006 125	0.006 75
DCP14	.701	0.383	0.088 57	0.068 29	0.020 231	0.023 69	0.019 306	0.011 184	0.004 72	0.006 117	0.007 41
DCP15	.800	0.202	0.062 56	0.032 11	0.019 178	0.022 49	0.017 284	0.007 173	0.004 15	0.008 79	0.006 32
DCP16	.900	-0.032	0.053 25	0.026 275	0.025 145	0.012 17	0.004 198	0.005 18	0.004 141	0.012 62	0.002 340
DCP17	.969	-0.052	0.013 13	0.019 276	0.014 166	0.001 46	0.003 71	0.001 182	0.001 196	0.015 82	0.003 341

FORCED PITCHING OSCILLATION

AIRFOIL NLR 1

	TUNED HZ 0.0	DRIVE HZ 23.08	K 0.088	MACH NO 0.396	DEL.ALPHA 5.11	DEL.H 0.0	ALPHA.0 9.96	TEST POINT 12019.5	CYCLES ANALYSED 20
	V 133.4 (437.6)	Q 46750. (976.4)	RN 0.63E 07	CN(MIN) -0.080	CN(MAX) 1.307	ALPHA.NMAX 13.56	AERO DAMP -0.00127	TDR 1.350	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		9.956	5.111 0	0.240 20	0.015 287	0.036 4	0.046 316	0.038 183	0.009 144	0.003 120	0.005 279
CN		0.902	0.231 37	0.135 32	0.020 6	0.031 314	0.017 209	0.009 156	0.011 53	0.004 10	0.001 235
CM		-0.008	0.025 228	0.025 103	0.009 22	0.007 35	0.009 319	0.004 262	0.004 218	0.001 174	0.001 140
DCP 1	.010	4.416	0.880 333	1.319 90	0.419 42	0.264 74	0.220 36	0.047 28	0.103 69	0.118 21	0.023 320
DCP 2	.020	3.567	0.669 11	0.735 76	0.335 50	0.190 13	0.136 14	0.105 326	0.072 0	0.102 334	0.059 291
DCP 3	.030	3.231	0.522 11	0.697 80	0.394 47	0.329 3	0.222 313	0.137 265	0.059 255	0.040 255	0.055 238
DCP 4	.049	2.919	0.499 30	0.645 58	0.211 2	0.106 323	0.086 290	0.050 238	0.004 280	0.031 303	0.050 226
DCP 5	.074	2.492	0.398 38	0.526 53	0.150 358	0.080 336	0.079 295	0.058 239	0.014 266	0.032 248	0.052 188
DCP 6	.099	2.176	0.349 43	0.432 50	0.095 359	0.084 347	0.078 286	0.046 222	0.017 230	0.030 201	0.041 143
DCP 7	.149	1.648	0.344 41	0.318 38	0.080 346	0.073 336	0.066 260	0.037 188	0.001 229	0.021 183	0.030 110
DCP 8	.200	1.350	0.337 39	0.240 35	0.040 351	0.060 332	0.057 249	0.030 177	0.006 104	0.011 140	0.019 82
DCP 9	.250	1.211	0.347 35	0.197 21	0.037 336	0.060 306	0.060 219	0.030 154	0.014 115	0.021 107	0.019 44
DCP10	.300	1.061	0.318 38	0.167 11	0.027 309	0.052 294	0.048 201	0.023 137	0.011 102	0.015 81	0.007 14
DCP11	.399	0.873	0.207 40	0.136 5	0.017 279	0.042 292	0.041 197	0.020 167	0.020 101	0.018 65	0.009 9
DCP12	.501	0.661	0.244 40	0.107 354	0.013 241	0.035 276	0.041 177	0.019 114	0.022 65	0.014 31	0.010 333
DCP13	.600	0.522	0.187 49	0.082 343	0.021 189	0.023 271	0.033 148	0.015 82	0.020 55	0.014 354	0.007 277
DCP14	.701	0.441	0.137 42	0.065 326	0.030 167	0.016 248	0.036 133	0.015 43	0.017 43	0.010 341	0.005 310
DCP15	.800	0.258	0.115 45	0.062 299	0.023 185	0.019 207	0.028 118	0.013 67	0.020 24	0.009 295	0.005 269
DCP16	.900	0.015	0.109 15	0.054 278	0.017 218	0.025 199	0.018 112	0.010 76	0.017 355	0.004 242	0.005 295
DCP17	.969	-0.036	0.053 8	0.032 281	0.010 263	0.011 201	0.007 110	0.009 100	0.010 20	0.004 271	0.005 204

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ 0.0	DRIVE HZ 22.92	K 0.085	MACH NO 0.408	DEL.ALPHA 5.05	DEL.H 0.0	ALPHA.0 12.46	TEST POINT 12021.1	CYCLES ANALYSED 20
	V 137.7 (451.9)	Q 49125. (1026.0)	RN 0.65E 07	CN(MIN) -0.110	CN(MAX) 1.337	ALPHA.NMAX 14.49	AERO DAMP -0.00163	TOR 1.802	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.462	5.047 0	0.230 19	0.039 166	0.029 54	0.028 102	0.068 7	0.041 307	0.043 218	0.023 216
CN		0.961	0.202 75	0.076 49	0.047 74	0.016 38	0.024 357	0.011 294	0.007 280	0.012 225	0.010 227
CM		-0.024	0.051 207	0.022 112	0.011 153	0.008 131	0.008 120	0.006 67	0.003 36	0.005 20	3.003 29
DCP 1	.010	4.591	0.932 194	0.718 106	0.461 175	0.247 165	0.146 207	0.132 187	0.033 232	0.067 220	0.033 169
DCP 2	.020	3.640	3.430 147	0.526 105	0.241 142	0.275 140	0.140 162	0.144 165	0.105 201	0.112 213	0.088 212
DCP 3	.030	3.172	0.642 165	0.731 107	0.309 101	0.218 118	0.198 103	0.119 88	0.065 108	0.065 116	0.035 108
DCP 4	.049	2.871	0.575 143	0.531 83	0.182 101	0.159 88	0.090 62	0.057 66	0.050 55	0.018 11	0.013 138
DCP 5	.074	2.4-1	0.520 132	0.398 71	0.151 107	0.135 69	0.053 46	0.049 62	0.046 42	0.025 25	0.019 45
DCP 6	.099	2.178	0.463 124	0.292 63	0.142 117	0.114 68	0.039 60	0.056 38	0.034 17	0.025 354	0.004 319
DCP 7	.149	1.701	0.373 97	0.195 50	0.125 96	0.071 37	0.044 47	0.044 5	0.027 346	0.023 317	0.004 311
DCP 8	.200	1.437	0.315 86	0.140 56	0.120 86	0.065 38	0.051 31	0.041 357	0.026 342	0.020 320	0.015 281
DCP 9	.250	1.305	0.296 70	0.127 50	0.104 67	0.047 24	0.055 23	0.048 336	0.024 312	0.013 320	0.015 284
DCP10	.300	1.144	0.291 62	0.104 36	0.087 47	0.043 353	0.047 353	0.038 313	0.028 291	0.017 257	0.017 246
DCP11	.399	0.959	0.297 56	0.072 8	0.062 50	0.034 342	0.043 353	0.032 289	0.016 289	0.019 242	0.018 276
DCP12	.501	0.746	0.267 51	0.054 339	0.046 47	0.021 330	0.046 336	0.028 268	0.015 277	0.023 231	0.024 258
DCP13	.600	0.608	0.231 53	0.061 319	0.037 30	0.023 278	0.037 326	0.028 246	0.015 229	0.021 210	0.017 207
DCP14	.701	0.497	0.190 55	0.067 298	0.027 354	0.031 253	0.033 300	0.023 226	0.014 222	0.021 188	0.014 201
DCP15	.800	0.316	0.174 34	0.059 302	0.037 325	0.024 257	0.029 282	0.017 213	0.017 198	0.016 181	0.008 182
DCP16	.900	0.061	0.155 17	0.037 314	0.031 310	0.012 287	0.019 265	0.017 272	0.013 164	0.025 198	0.011 177
DCP17	.969	-0.012	0.075 11	0.016 316	0.019 329	0.008 342	0.010 301	0.010 214	0.003 177	0.016 196	0.003 163

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ 0.0	DRIVE HZ 23.01	K 0.086	MACH NO 0.404	DEL.ALPHA 5.01	DEL.H 0.0	ALPHA.0 15.02	TEST POINT 12021.2	CYCLES ANALYSED 20
	V 136.2 (447.0)	Q 48321. (1009.2)	RN 0.64E 07	CN(MIN) -0.120	CN(MAX) 1.295	ALPHA.NMAX 14.56	AERO DAMP -0.00178	TOR 1.947	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		15.025	5.012 0	0.211 9	0.037 195	0.023 178	0.031 274	0.039 141	0.037 321	0.008 209	0.013 332
CN		0.972	0.242 94	0.042 131	0.014 118	0.025 96	0.012 177	0.015 92	0.014 343	0.004 222	0.002 42
CM		-0.042	0.072 198	0.011 202	0.011 173	0.012 213	0.003 257	0.005 229	0.003 157	0.002 0	0.001 71
DCP 1	.010	4.534	1.693 186	0.159 231	0.173 250	0.164 298	0.055 4	0.051 38	0.068 60	0.026 49	0.033 125
DCP 2	.020	3.639	1.111 165	0.323 167	0.249 244	0.144 283	0.111 358	0.081 65	0.078 41	0.025 71	0.033 111
DCP 3	.030	3.109	1.113 175	0.365 161	0.453 212	0.239 197	0.193 267	0.087 239	0.094 337	0.033 298	0.030 40
DCP 4	.049	2.632	1.151 155	0.232 138	0.222 146	0.115 176	0.045 193	0.035 231	0.015 50	0.031 12	0.026 89
DCP 5	.074	2.226	0.977 145	0.121 167	0.222 146	0.093 192	0.067 194	0.051 215	0.028 295	0.032 304	0.021 9
DCP 6	.099	2.002	0.819 136	0.112 188	0.170 134	0.089 188	0.042 184	0.033 180	0.035 317	0.030 309	0.025 351
DCP 7	.149	1.616	0.554 119	0.093 178	0.101 117	0.060 158	0.035 216	0.026 125	0.012 289	0.015 326	0.008 68
DCP 8	.200	1.417	0.420 107	0.096 158	0.065 120	0.070 138	0.045 208	0.029 111	0.012 244	0.007 339	0.010 66
DCP 9	.250	1.280	0.392 92	0.110 141	0.035 83	0.083 124	0.036 186	0.036 124	0.006 243	0.010 177	0.006 295
DCP10	.300	1.153	0.352 81	0.091 121	0.037 46	0.068 104	0.024 157	0.040 98	0.012 4	0.005 160	0.007 244
DCP11	.399	1.011	0.332 66	0.067 95	0.032 21	0.055 84	0.024 141	0.029 96	0.016 17	0.023 199	0.005 169
DCP12	.501	0.815	0.295 57	0.039 89	0.024 1	0.057 61	0.015 131	0.021 63	0.020 9	0.013 173	0.007 0
DCP13	.600	0.667	0.267 45	0.017 58	0.029 344	0.045 50	0.011 117	0.018 83	0.021 346	0.019 173	0.006 140
DCP14	.701	0.545	0.234 39	0.015 338	0.038 345	0.046 24	0.005 89	0.017 50	0.021 344	0.003 140	0.002 274
DCP15	.800	0.373	0.228 26	0.028 11	0.031 345	0.037 20	0.009 68	0.020 34	0.017 321	0.004 287	0.002 2
DCP16	.900	0.121	0.177 15	0.056 32	0.021 2	0.027 2	0.012 43	0.014 33	0.004 300	0.006 331	0.005 287
DCP17	.969	0.016	0.079 17	0.034 44	0.006 23	0.014 37	0.006 356	0.007 39	0.003 279	0.004 182	0.002 164

FORCED PITCHING OSCILLATION　　　　AIRFOIL　　NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	22.88	0.086	0.402	5.01	0.0	17.51	12021.3	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	135.3 (444.0)	47808. (998.5)	0.64E 07	-0.134	1.258	15.24	-0.00227	2.470	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		17.514	5.007	0	0.200	3	0.044	244	0.023	346	0.018	346	0.021	93	0.035	322	0.002	153	0.015	3.1
CN		0.953	0.251	90	0.042	118	0.034	181	0.013	263	0.006	252	0.009	249	0.006	344	0.007	202	0.007	341
CM		-0.062	0.065	204	0.023	228	0.009	271	0.007	327	0.004	0	0.003	354	0.001	96	0.002	7	0.002	154
DCP 1	.010	3.895	1.657	187	0.332	279	0.180	8	0.085	14	0.064	47	0.019	90	0.011	257	0.014	118	0.008	162
DCP 2	.020	3.263	1.214	173	0.201	246	0.167	306	0.142	7	0.089	79	0.051	160	0.033	210	0.028	227	0.012	231
DCP 3	.030	2.785	1.237	173	0.334	269	0.317	246	0.272	320	0.042	20	0.056	29	0.058	134	0.007	21	0.020	141
DCP 4	.049	2.347	1.011	153	0.285	205	0.176	216	0.064	288	0.025	355	0.021	295	0.010	11	0.030	236	0.017	298
DCP 5	.074	1.982	0.800	137	0.283	205	0.115	223	0.073	288	0.042	334	0.046	321	0.030	13	0.013	190	0.007	264
DCP 6	.099	1.787	0.637	126	0.262	195	0.110	234	0.054	310	0.030	323	0.043	318	0.032	6	0.016	117	0.007	45
DCP 7	.149	1.495	0.435	105	0.162	174	0.093	223	0.057	303	0.019	341	0.019	302	0.011	1	0.003	288	0.003	279
DCP 8	.200	1.345	0.349	96	0.133	158	0.099	214	0.059	281	0.026	308	0.020	302	0.010	341	0.010	186	0.008	245
DCP 9	.250	1.264	0.344	85	0.117	135	0.085	184	0.036	264	0.028	268	0.027	245	0.017	300	0.012	267	0.009	332
DCP10	.300	1.159	0.322	77	0.109	111	0.089	165	0.025	243	0.016	263	0.021	272	0.017	345	0.010	325	0.004	12
DCP11	.399	1.028	0.310	67	0.105	84	0.068	146	0.021	235	0.013	258	0.021	261	0.005	350	0.002	232	0.016	27
DCP12	.501	0.843	0.274	56	0.091	69	0.051	137	0.027	189	0.024	229	0.017	214	0.005	339	0.011	216	0.009	19
DCP13	.600	0.700	0.269	46	0.083	54	0.033	111	0.023	168	0.016	197	0.014	182	0.006	357	0.011	191	0.008	1
DCP14	.701	0.592	0.248	38	0.079	48	0.023	80	0.022	143	0.012	163	0.013	187	0.005	349	0.014	205	0.018	313
DCP15	.800	0.443	0.228	32	0.070	49	0.022	69	0.026	126	0.013	143	0.013	149	0.006	261	0.007	165	0.013	313
DCP16	.900	0.186	0.140	35	0.053	36	0.017	75	0.011	144	0.014	153	0.010	166	0.004	194	0.012	159	0.005	334
DCP17	.969	0.044	0.051	48	0.019	24	0.010	107	0.006	122	0.004	142	0.001	14	0.004	148	0.008	176	0.001	336

FORCED PITCHING OSCILLATION　　　　AIRFOIL　　NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	22.80	0.086	0.401	4.81	0.0	19.93	12021.4	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	135.0 (443.0)	47737. (997.0)	0.64E 07	-0.130	1.137	19.91	-0.00250	2.704	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		19.931	4.814	0	0.135	358	0.034	283	0.037	149	0.028	339	0.017	122	0.010	341	0.029	56	0.011	268
CN		0.939	0.167	89	0.016	53	0.021	132	0.008	232	0.001	240	0.003	149	0.001	5	0.011	24	0.004	127
CM		-0.077	0.044	222	0.011	223	0.004	301	0.002	23	0.001	65	0.001	278	0.001	175	0.005	206	0.001	306
DCP 1	.010	3.162	1.223	187	0.162	8	0.112	319	0.092	62	0.044	108	0.040	221	0.006	176	0.019	271	0.044	115
DCP 2	.020	2.744	0.923	171	0.144	324	0.009	326	0.059	33	0.030	147	0.028	249	0.043	283	0.016	123	0.012	246
DCP 3	.030	2.353	0.883	164	0.360	269	0.099	55	0.048	257	0.087	35	0.031	146	0.038	332	0.028	90	0.017	283
DCP 4	.049	2.055	0.506	154	0.147	247	0.052	174	0.036	273	0.021	145	0.005	317	0.023	156	0.027	317	0.017	66
DCP 5	.074	1.820	0.338	133	0.114	207	0.047	182	0.033	268	0.013	165	0.007	40	0.024	156	0.018	302	0.023	59
DCP 6	.099	1.716	0.275	114	0.070	180	0.042	151	0.012	288	0.015	113	0.005	32	0.031	113	0.011	271	0.015	35
DCP 7	.149	1.504	0.240	88	0.062	131	0.025	122	0.019	338	0.015	83	0.002	53	0.017	113	0.003	189	0.005	11
DCP 8	.200	1.377	0.234	88	0.037	107	0.006	79	0.007	265	0.007	36	0.007	184	0.011	187	0.009	112	0.012	181
DCP 9	.250	1.256	0.210	83	0.031	103	0.038	155	0.018	205	0.009	282	0.005	138	0.008	293	0.004	353	0.007	249
DCP10	.300	1.148	0.199	79	0.023	99	0.031	144	0.018	200	0.013	292	0.033	188	0.002	284	0.001	186	0.007	212
DCP11	.399	1.028	0.211	72	0.038	75	0.038	151	0.013	204	0.007	330	0.004	222	0.014	341	0.012	39	0.006	188
DCP12	.501	0.863	0.193	66	0.035	56	0.032	134	0.019	224	0.006	270	0.007	131	0.003	355	0.016	37	0.010	166
DCP13	.600	0.732	0.196	60	0.040	44	0.024	134	0.039	215	0.010	249	0.033	227	0.032	299	0.017	24	0.012	118
DCP14	.701	0.643	0.183	54	0.054	28	0.017	118	0.036	243	0.006	224	0.036	149	0.033	254	0.018	25	0.007	108
DCP15	.800	0.497	0.172	51	0.047	35	0.013	118	0.002	189	0.007	198	0.032	126	0.002	146	0.021	31	0.003	127
DCP16	.900	0.209	0.118	59	0.024	27	0.008	89	0.007	233	0.002	205	0.036	65	0.038	54	0.021	17	0.007	27
DCP17	.969	0.050	0.056	75	0.005	343	0.006	91	0.005	125	0.004	67	0.003	26	0.033	336	0.019	12	0.001	198

179

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	22.84	0.085	0.405	5.15	0.0	0.02	12023.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
136.6	53458.	0.71E 07	-0.031	0.595	5.14	-0.00070	0.773	0.0
(448.3)	(1116.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.017	5.150 0	0.243 8	0.038 250	0.013 258	0.011 47	0.010 110	0.014 167	0.012 163	0.008 231
CN		0.115	0.480 354	0.018 359	0.001 216	0.002 293	0.000 25	0.001 236	0.002 91	0.005 142	0.002 226
CM		-0.015	0.011 306	0.001 309	0.001 33	0.001 128	0.000 254	0.000 116	0.001 314	0.002 1	0.001 50
DCP 1	.010	-0.776	3.472 347	0.301 38	0.092 126	0.019 188	0.007 168	0.018 170	0.009 301	0.019 28	0.007 66
DCP 2	.020	-0.372	2.448 350	0.091 339	0.016 330	0.012 16	0.005 105	0.010 177	0.006 9	0.019 67	0.003 89
DCP 3	.030	-0.071	2.049 350	0.079 325	0.009 330	0.003 256	0.002 269	0.009 171	0.002 354	0.012 71	0.003 73
DCP 4	.049	0.144	1.673 350	0.064 320	0.006 325	0.002 295	0.001 92	0.007 177	0.006 18	0.015 59	0.004 97
DCP 5	.074	0.310	1.347 350	0.048 342	0.006 324	0.005 17	0.004 288	0.003 201	0.006 357	0.013 66	0.003 28
DCP 6	.099	0.349	1.167 351	0.040 342	0.009 327	0.006 260	0.002 151	0.002 186	0.006 359	0.012 57	0.001 176
DCP 7	.149	0.239	0.871 351	0.032 352	0.002 276	0.000 27	0.001 159	0.001 298	0.004 5	0.014 59	0.003 220
DCP 8	.200	0.190	0.711 354	0.025 351	0.000 142	0.002 255	0.001 297	0.003 236	0.001 301	0.011 73	0.002 156
DCP 9	.250	0.174	0.624 353	0.024 347	0.001 26	0.005 236	0.002 257	0.004 239	0.003 80	0.007 152	0.002 28
DCP10	.300	0.182	0.523 353	0.017 353	0.001 23	0.001 295	0.003 340	0.003 208	0.002 48	0.007 168	0.001 265
DCP11	.399	0.169	0.421 358	0.016 5	0.002 353	0.001 7	0.000 242	0.003 359	0.003 110	0.012 173	0.002 316
DCP12	.501	0.114	0.322 354	0.014 6	0.002 198	0.006 293	0.002 266	0.004 253	0.006 98	0.007 185	0.002 239
DCP13	.600	0.131	0.244 2	0.012 12	0.003 239	0.002 281	0.002 34	0.001 191	0.006 129	0.006 172	0.004 200
DCP14	.701	0.193	0.177 3	0.006 45	0.003 202	0.002 322	0.002 110	0.001 25	0.002 83	0.009 175	0.001 202
DCP15	.800	0.063	0.103 6	0.005 67	0.001 98	0.003 325	0.002 144	0.001 267	0.005 159	0.005 183	0.004 226
DCP16	.900	-0.084	0.030 16	0.001 48	0.002 189	0.003 309	0.003 300	0.001 260	0.002 108	0.011 166	0.006 224
DCP17	.969	-0.043	0.017 183	0.004 189	0.004 211	0.001 268	0.006 85	0.004 268	0.001 225	0.003 96	0.003 287

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.07	0.086	0.403	5.15	0.0	4.22	12023.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
135.8	52501.	0.70E 07	-0.020	0.828	9.35	-0.00060	0.535	0.0
(445.5)	(1096.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.221	5.153 0	0.203 16	0.031 283	0.002 202	0.022 0	0.013 169	0.005 143	0.012 109	0.007 342
CN		0.386	0.447 355	0.017 11	0.005 353	0.000 155	0.002 315	0.001 286	0.002 46	0.002 113	0.001 21
CM		-0.008	0.038 283	0.002 255	0.001 204	0.000 105	0.001 209	0.001 166	0.000 275	0.001 269	0.000 210
DCP 1	.010	1.236	2.764 348	0.128 0	0.041 144	0.031 112	0.025 256	0.020 221	0.015 1	0.007 194	0.000 272
DCP 2	.020	1.072	2.151 352	0.086 343	0.008 171	0.016 127	0.024 259	0.008 275	0.015 352	0.009 182	0.003 244
DCP 3	.030	1.107	1.810 351	0.065 313	0.029 335	0.010 133	0.021 290	0.005 236	0.008 51	0.012 190	0.005 181
DCP 4	.049	1.127	1.526 351	0.061 318	0.014 333	0.013 285	0.005 312	0.010 165	0.004 301	0.007 265	0.001 276
DCP 5	.074	1.099	1.225 352	0.035 337	0.004 300	0.004 303	0.004 70	0.007 139	0.001 324	0.004 219	0.002 21
DCP 6	.099	1.029	1.055 353	0.030 355	0.011 335	0.002 275	0.003 239	0.000 152	0.002 6	0.004 182	0.001 259
DCP 7	.149	0.763	0.792 354	0.023 11	0.006 333	0.003 283	0.003 342	0.006 217	0.002 301	0.006 253	0.004 320
DCP 8	.200	0.632	0.649 357	0.027 15	0.007 336	0.005 59	0.003 285	0.002 302	0.003 334	0.002 245	0.002 122
DCP 9	.250	0.494	0.623 353	0.024 10	0.009 351	0.000 21	0.003 299	0.005 259	0.002 354	0.003 113	0.001 90
DCP10	.300	0.459	0.521 354	0.022 17	0.009 333	0.002 143	0.002 283	0.001 158	0.003 1	0.001 67	0.005 306
DCP11	.399	0.390	0.417 358	0.020 28	0.005 340	0.002 160	0.005 303	0.001 298	0.005 90	0.004 90	0.001 122
DCP12	.501	0.281	0.321 0	0.013 28	0.004 4	0.001 227	0.004 357	0.003 294	0.002 47	0.003 71	0.002 137
DCP13	.600	0.256	0.242 2	0.011 40	0.006 5	0.003 197	0.000 32	0.004 322	0.002 82	0.007 76	0.003 186
DCP14	.701	0.285	0.166 4	0.014 46	0.005 15	0.001 29	0.000 286	0.003 284	0.003 145	0.008 132	0.003 76
DCP15	.800	0.136	0.099 8	0.011 62	0.004 14	0.001 79	0.002 1	0.002 352	0.003 7	0.004 93	0.002 44
DCP16	.900	-0.069	0.034 10	0.004 356	0.002 42	0.004 293	0.004 63	0.001 46	0.002 319	0.002 154	0.006 349
DCP17	.969	-0.052	0.017 164	0.001 104	0.002 95	0.004 92	0.004 333	0.006 15	0.002 95	0.004 90	0.002 18

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.01	0.087	0.398	5.17	0.0	4.99	12023.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
134.2	51940.	0.70E 07	-0.022	1.066	10.13	-0.00087	0.934	0.0
(440.3)	(1084.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		4.990	5.170	0	0.239	12	0.045	249	0.011	315	0.016	36	0.011	10	0.015	179	0.025	233	0.002	141
CN		0.616	0.459	355	0.035	19	0.008	300	0.004	176	0.002	55	0.002	273	0.001	125	0.008	269	0.000	211
CM		-0.005	0.016	316	0.004	236	0.001	111	0.001	332	0.001	215	0.000	94	0.000	14	0.003	82	0.000	221
DCP 1	.010	2.947	3.486	349	0.271	287	0.050	167	0.074	232	0.092	143	0.058	52	0.027	340	0.014	336	0.021	277
DCP 2	.020	2.205	2.449	351	0.131	351	0.044	192	0.073	86	0.091	346	0.086	251	0.053	155	0.021	62	0.008	110
DCP 3	.030	2.063	2.026	351	0.126	21	0.039	337	0.021	247	0.011	149	0.002	273	0.005	89	0.005	38	0.003	15
DCP 4	.049	1.938	1.703	351	0.101	18	0.042	332	0.019	249	0.008	156	0.003	147	0.005	26	0.005	278	0.002	46
DCP 5	.074	1.751	1.336	351	0.078	11	0.028	324	0.009	234	0.001	140	0.002	189	0.001	314	0.005	315	0.001	119
DCP 6	.099	1.574	1.137	352	0.075	19	0.017	324	0.007	213	0.002	113	0.003	219	0.002	26	0.005	297	0.001	241
DCP 7	.149	1.156	0.842	353	0.055	11	0.011	299	0.001	213	0.002	35	0.004	299	0.005	70	0.005	287	0.001	295
DCP 8	.200	0.936	0.696	355	0.049	21	0.005	350	0.002	168	0.003	42	0.003	284	0.004	96	0.005	349	0.001	175
DCP 9	.250	0.812	0.597	354	0.048	17	0.009	268	0.004	131	0.004	305	0.003	262	0.002	244	0.009	234	0.000	51
DCP10	.300	0.729	0.494	355	0.039	17	0.009	269	0.003	131	0.002	40	0.002	239	0.001	300	0.010	247	0.001	203
DCP11	.399	0.603	0.390	0	0.033	27	0.008	300	0.003	151	0.002	27	0.001	258	0.002	178	0.012	270	0.002	190
DCP12	.501	0.445	0.299	2	0.029	35	0.006	289	0.002	143	0.001	80	0.002	312	0.002	119	0.007	286	0.002	173
DCP13	.600	0.373	0.221	5	0.029	39	0.007	278	0.003	146	0.002	120	0.003	294	0.002	121	0.010	276	0.002	147
DCP14	.701	0.359	0.139	9	0.031	44	0.007	318	0.008	182	0.002	33	0.000	284	0.002	218	0.012	252	0.001	275
DCP15	.800	0.177	0.076	16	0.025	43	0.007	303	0.005	162	0.007	33	0.002	245	0.002	322	0.012	257	0.002	341
DCP16	.900	-0.055	0.030	22	0.009	18	0.005	273	0.002	150	0.002	152	0.001	266	0.002	117	0.012	261	0.003	57
DCP17	.969	-0.059	0.014	162	0.007	321	0.003	336	0.003	150	0.004	26	0.003	271	0.002	205	0.009	279	0.002	301

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.11	0.088	0.397	5.16	0.0	7.51	12023.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
133.7	51663.	0.70E 07	-0.018	1.214	12.21	-0.00112	1.201	0.0
(438.5)	(1079.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.508	5.162	0	0.244	15	0.042	280	0.024	264	0.027	81	0.022	34	0.022	255	0.008	269	0.009	149
CN		0.786	0.337	8	0.115	25	0.044	277	0.018	149	0.008	1	0.004	209	0.002	2	0.005	328	0.002	103
CM		0.001	0.020	309	0.005	147	0.008	0	0.007	248	0.005	140	0.003	27	0.001	255	0.001	148	0.001	312
DCP 1	.010	3.882	2.176	349	0.846	71	0.741	356	0.414	274	0.126	206	0.019	277	0.078	251	0.068	178	0.027	51
DCP 2	.020	3.142	1.832	356	0.505	37	0.261	332	0.204	277	0.206	209	0.141	129	0.032	62	0.050	111	0.071	50
DCP 3	.030	2.937	1.665	358	0.392	22	0.187	298	0.104	224	0.068	180	0.071	129	0.057	62	0.054	9	0.039	321
DCP 4	.049	2.615	1.311	359	0.359	31	0.169	299	0.095	204	0.064	124	0.045	49	0.026	338	0.011	320	0.013	323
DCP 5	.074	2.274	1.025	359	0.293	29	0.140	292	0.082	192	0.058	107	0.042	29	0.027	321	0.016	286	0.013	259
DCP 6	.099	2.002	0.834	1	0.257	32	0.116	294	0.065	189	0.044	95	0.034	10	0.021	289	0.005	240	0.003	15
DCP 7	.149	1.481	0.634	3	0.198	27	0.090	286	0.049	177	0.025	72	0.016	330	0.006	221	0.006	29	0.008	300
DCP 8	.200	1.205	0.536	7	0.168	22	0.084	277	0.049	177	0.024	78	0.008	1	0.006	20	0.013	341	0.012	253
DCP 9	.250	1.051	0.469	7	0.147	13	0.072	253	0.047	133	0.029	23	0.018	268	0.008	174	0.006	336	0.004	155
DCP10	.300	0.918	0.377	8	0.129	15	0.061	253	0.039	130	0.026	15	0.012	263	0.003	237	0.004	284	0.007	125
DCP11	.399	0.749	0.300	16	0.111	19	0.053	251	0.034	126	0.025	6	0.013	257	0.001	40	0.007	317	0.008	130
DCP12	.501	0.552	0.221	21	0.091	19	0.040	243	0.031	106	0.023	342	0.015	218	0.005	65	0.007	315	0.007	134
DCP13	.600	0.435	0.151	34	0.085	25	0.034	248	0.026	98	0.020	331	0.014	208	0.006	56	0.005	309	0.006	117
DCP14	.701	0.385	0.087	61	0.077	30	0.023	241	0.025	73	0.025	314	0.015	187	0.006	56	0.005	310	0.004	93
DCP15	.800	0.201	0.064	57	0.037	19	0.018	186	0.022	55	0.021	303	0.010	184	0.001	351	0.002	345	0.001	18
DCP16	.900	-0.030	0.050	28	0.024	287	0.020	159	0.016	39	0.008	270	0.004	163	0.002	324	0.007	345	0.000	278
DCP17	.969	-0.052	0.015	14	0.020	264	0.030	148	0.008	22	0.004	256	0.003	135	0.001	110	0.009	349	0.001	160

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.09	0.088	0.396	5.11	0.0	9.98	12023.5	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
133.1	51217.	0.70E 07	-0.079	1.319	13.88	-0.00120	1.281	0.0
(436.7)	(1069.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		9.976	5.115 0	0.241 23	0.036 277	0.030 27	0.049 334	0.037 228	0.056 119	0.004 184	0.012 283
CN		0.907	0.229 38	0.143 32	0.019 353	0.027 309	0.016 199	0.007 157	0.016 82	0.008 355	0.006 303
CM		-0.009	0.025 226	0.025 99	0.010 6	0.006 47	0.009 321	0.004 266	0.005 249	0.003 158	0.003 134
DCP 1	.010	4.523	0.732 343	1.281 84	0.393 32	0.187 69	0.122 65	0.148 74	0.148 34	0.092 21	0.049 312
DCP 2	.020	3.588	0.175 19	0.814 69	0.330 38	0.205 4	0.118 359	0.105 326	0.085 346	0.086 320	0.056 280
DCP 3	.030	3.245	0.539 16	0.696 73	0.318 43	0.261 11	0.190 330	0.146 288	0.091 269	0.056 234	0.047 234
DCP 4	.049	2.948	0.512 26	0.635 59	0.232 4	0.118 317	0.062 278	0.040 244	0.012 331	0.029 266	0.046 221
DCP 5	.074	2.495	0.384 38	0.545 56	0.184 355	0.082 315	0.061 289	0.059 241	0.019 184	0.016 195	0.031 178
DCP 6	.099	2.172	0.309 47	0.470 54	0.132 348	0.046 329	0.049 305	0.048 244	0.016 178	0.012 166	0.017 162
DCP 7	.149	1.630	0.316 47	0.347 41	0.073 328	0.043 348	0.052 285	0.037 220	0.014 167	0.017 140	0.016 107
DCP 8	.200	1.352	0.329 45	0.269 34	0.053 320	0.043 337	0.047 264	0.029 203	0.016 137	0.009 91	0.010 127
DCP 9	.250	1.207	0.342 39	0.225 21	0.042 301	0.044 312	0.046 235	0.029 163	0.026 123	0.016 97	0.009 48
DCP10	.300	1.067	0.313 38	0.183 12	0.034 280	0.040 294	0.044 209	0.028 150	0.029 101	0.015 53	0.014 6
DCP11	.399	0.894	0.292 40	0.145 2	0.025 235	0.033 296	0.045 195	0.021 127	0.025 103	0.014 43	0.013 2
DCP12	.501	0.668	0.242 41	0.104 353	0.014 202	0.035 289	0.042 178	0.019 106	0.026 89	0.018 15	0.013 333
DCP13	.600	0.525	0.189 48	0.079 342	0.025 161	0.028 285	0.038 159	0.016 89	0.027 83	0.021 353	0.014 321
DCP14	.701	0.448	0.136 62	0.064 326	0.033 158	0.017 265	0.036 137	0.014 61	0.022 66	0.019 325	0.010 294
DCP15	.800	0.260	0.114 41	0.056 295	0.024 163	0.022 227	0.032 118	0.009 64	0.022 59	0.016 313	0.009 287
DCP16	.900	0.021	0.109 13	0.051 271	0.009 216	0.028 208	0.023 109	0.012 75	0.017 24	0.010 299	0.014 280
DCP17	.969	-0.031	0.057 8	0.031 275	0.006 239	0.013 209	0.009 119	0.005 117	0.007 49	0.005 333	0.002 284

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.03	0.086	0.403	5.03	0.0	12.48	12025.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
136.2	53099.	0.71E 07	-0.111	1.362	14.55	-0.00149	1.626	0.0
(446.9)	(1109.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.482	5.033 0	0.244 18	0.045 155	0.048 57	0.009 108	0.058 12	0.059 315	0.034 265	0.013 187
CN		0.960	0.217 84	0.087 47	0.055 75	0.021 5	0.018 340	0.012 311	0.013 268	0.008 243	0.007 183
CM		-0.026	0.052 204	0.022 104	0.012 158	0.009 96	0.009 108	0.005 61	0.005 52	0.003 19	0.002 358
DCP 1	.010	4.758	0.919 188	0.802 98	0.383 158	0.151 173	0.138 219	0.056 247	0.133 264	0.070 236	0.092 222
DCP 2	.020	3.694	0.515 142	0.557 99	0.257 120	0.167 140	0.156 166	0.105 165	0.108 209	0.087 217	0.080 217
DCP 3	.030	3.316	0.478 163	0.590 114	0.396 117	0.249 108	0.196 102	0.131 90	0.076 101	0.064 105	0.053 112
DCP 4	.049	2.850	0.713 144	0.590 81	0.229 94	0.162 70	0.108 58	0.072 31	0.035 50	0.033 28	0.021 96
DCP 5	.074	2.378	0.701 139	0.471 68	0.170 105	0.150 61	0.068 50	0.060 32	0.040 43	0.039 13	0.020 79
DCP 6	.099	2.106	0.637 132	0.366 57	0.155 115	0.130 46	0.035 46	0.053 17	0.020 18	0.026 357	0.008 100
DCP 7	.149	1.644	0.458 112	0.244 45	0.119 102	0.075 19	0.028 61	0.036 352	0.014 45	0.023 342	0.007 69
DCP 8	.200	1.408	0.358 96	0.177 46	0.108 87	0.054 16	0.042 44	0.034 346	0.019 0	0.020 308	0.005 89
DCP 9	.250	1.286	0.338 81	0.142 37	0.103 73	0.046 19	0.050 24	0.031 348	0.027 348	0.013 330	0.013 323
DCP10	.300	1.137	0.313 70	0.114 25	0.088 57	0.052 341	0.042 344	0.039 303	0.030 291	0.024 262	0.015 252
DCP11	.399	0.961	0.295 62	0.079 15	0.071 54	0.061 336	0.039 342	0.027 305	0.029 299	0.024 260	0.017 242
DCP12	.501	0.760	0.264 54	0.053 352	0.061 36	0.032 311	0.041 320	0.027 272	0.029 271	0.020 219	0.008 198
DCP13	.600	0.621	0.226 53	0.043 321	0.048 32	0.029 295	0.034 310	0.023 256	0.024 247	0.016 201	0.013 167
DCP14	.701	0.511	0.179 53	0.064 288	0.029 15	0.036 260	0.029 279	0.020 227	0.028 227	0.015 159	0.011 183
DCP15	.800	0.321	0.174 37	0.061 291	0.034 333	0.028 254	0.032 273	0.011 221	0.021 222	0.010 190	0.012 178
DCP16	.900	0.068	0.163 17	0.035 302	0.036 321	0.013 290	0.029 263	0.008 179	0.015 199	0.009 182	0.007 117
DCP17	.969	-0.005	0.078 14	0.017 321	0.017 324	0.011 318	0.015 272	0.011 252	0.010 169	0.008 244	0.009 145

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.08	0.087	0.400	5.00	0.0	15.03	12025.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
134.6	52266.	0.70E 07	-0.115	1.318	15.04	-0.00176	1.903	0.0
(442.3)	(1091.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		15.029	4.997 0	0.217 7	0.047 183	0.024 213	0.018 298	0.030 156	0.020 272	0.031 37	0.003 133
CN		0.981	0.235 96	0.057 146	0.012 94	0.038 108	0.003 69	0.007 124	0.012 37	0.010 31	0.003 112
CM		-0.042	0.069 198	0.010 204	0.011 178	0.011 219	0.005 239	0.002 211	0.004 213	0.004 231	0.001 257
DCP 1	.010	4.536	1.723 162	0.248 248	0.162 240	0.114 322	0.076 29	0.091 54	0.073 71	0.038 84	0.055 131
DCP 2	.020	3.616	1.142 163	0.421 162	0.242 235	0.115 274	0.093 3	0.078 66	0.056 61	0.030 116	0.026 123
DCP 3	.050	3.216	1.031 171	0.375 159	0.376 213	0.261 201	0.144 275	0.113 270	0.059 336	0.049 340	0.007 116
DCP 4	.069	2.717	1.109 153	0.324 143	0.232 154	0.153 161	0.042 200	0.043 203	0.014 2	0.032 7	0.009 335
DCP 5	.074	2.273	0.939 144	0.189 165	0.189 147	0.116 169	0.039 214	0.057 239	0.018 298	0.029 321	0.008 324
DCP 6	.099	2.027	0.773 136	0.160 186	0.129 129	0.097 167	0.020 259	0.050 183	0.011 299	0.015 332	0.008 296
DCP 7	.149	1.616	0.537 118	0.148 182	0.071 104	0.085 150	0.034 257	0.031 146	0.005 308	0.021 319	0.001 312
DCP 8	.200	1.412	0.410 106	0.133 166	0.045 107	0.085 142	0.027 220	0.023 149	0.007 69	0.017 313	0.005 1
DCP 9	.250	1.306	0.363 96	0.111 136	0.040 77	0.082 125	0.020 178	0.016 133	0.009 217	0.007 235	0.007 215
DCP10	.300	1.173	0.317 85	0.097 128	0.031 63	0.081 111	0.006 147	0.017 133	0.006 149	0.006 165	0.007 183
DCP11	.399	1.011	0.284 69	0.070 119	0.021 40	0.074 98	0.014 114	0.019 99	0.013 78	0.011 104	0.009 183
DCP12	.501	0.815	0.267 55	0.041 111	0.023 2	0.056 77	0.017 100	0.016 78	0.024 67	0.017 69	0.011 98
DCP13	.600	0.667	0.250 47	0.015 126	0.030 356	0.047 62	0.017 67	0.011 36	0.027 45	0.015 52	0.006 120
DCP14	.701	0.551	0.231 40	0.009 299	0.044 351	0.064 42	0.018 50	0.010 5	0.023 32	0.020 43	0.003 14
DCP15	.800	0.379	0.233 27	0.026 24	0.044 348	0.039 28	0.017 43	0.009 342	0.016 26	0.017 39	0.006 95
DCP16	.900	0.127	0.179 18	0.050 40	0.020 16	0.027 16	0.016 32	0.004 57	0.016 354	0.013 18	0.009 70
DCP17	.969	0.018	0.081 18	0.032 41	0.011 49	0.016 17	0.006 19	0.003 108	0.009 350	0.014 40	0.007 12

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.05	0.088	0.397	5.01	0.0	17.46	12025.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
133.7	51538.	0.70E 07	-0.136	1.274	15.19	-0.00235	2.524	0.0
(438.8)	(1076.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		17.465	5.011 0	0.198 2	0.337 251	0.018 339	0.022 355	0.020 100	0.022 267	0.010 248	0.012 331
CN		0.965	0.203 92	0.052 129	0.031 196	0.015 224	0.011 231	0.012 247	0.002 16	0.014 253	0.002 120
CM		-0.064	0.064 206	0.024 236	0.006 263	0.005 328	0.002 20	0.003 30	0.001 96	0.005 46	0.001 197
DCP 1	.010	3.954	1.680 191	0.371 274	0.246 9	0.092 345	0.040 96	0.022 318	0.020 195	0.048 255	0.021 330
DCP 2	.020	3.178	1.415 180	0.187 220	0.197 315	0.082 11	0.091 76	0.012 260	0.028 225	0.028 312	0.018 291
DCP 3	.050	2.812	1.348 171	0.217 264	0.244 244	0.239 335	0.023 8	0.049 35	0.052 161	0.007 705	0.040 213
DCP 4	.069	2.416	1.021 156	0.327 209	0.184 209	0.094 242	0.025 254	0.019 257	0.024 121	0.018 204	0.005 171
DCP 5	.074	2.032	0.744 142	0.318 212	0.098 211	0.078 240	0.022 296	0.027 327	0.024 84	0.005 178	0.015 173
DCP 6	.099	1.831	0.591 129	0.261 205	0.070 229	0.041 231	0.019 267	0.011 337	0.013 63	0.005 235	0.008 145
DCP 7	.149	1.521	0.369 103	0.171 183	0.059 218	0.022 262	0.010 262	0.016 316	0.011 54	0.005 50	0.013 106
DCP 8	.230	1.350	0.332 95	0.140 167	0.065 213	0.037 275	0.021 272	0.027 294	0.016 336	0.012 314	0.002 329
DCP 9	.250	1.261	0.275 85	0.129 136	0.070 200	0.027 230	0.019 234	0.018 265	0.013 31	0.016 331	0.009 186
DCP10	.300	1.164	0.262 78	0.115 115	0.376 192	0.027 219	0.030 234	0.020 245	0.013 356	0.020 285	0.006 131
DCP11	.399	1.030	0.254 64	0.108 97	0.055 184	0.023 205	0.030 230	0.022 239	0.003 12	0.027 301	0.006 192
DCP12	.501	0.856	0.244 53	0.102 80	0.039 165	0.018 205	0.022 226	0.019 244	0.003 290	0.023 271	0.003 139
DCP13	.600	0.717	0.251 48	0.091 74	0.027 144	0.014 188	0.013 216	0.015 233	0.004 329	0.024 257	0.008 64
DCP14	.701	0.608	0.242 39	0.078 63	0.019 102	0.021 156	0.004 187	0.011 225	0.005 290	0.025 222	0.006 ..
DCP15	.800	0.455	0.223 35	0.072 56	0.020 77	0.024 140	0.008 153	0.015 205	0.004 201	0.024 206	0.03 44
DCP16	.900	0.194	0.143 40	0.053 47	0.011 74	0.016 139	0.002 134	0.010 191	0.503 227	0.017 189	0.00 288
DCP17	.969	0.046	0.060 52	0.025 48	0.004 52	0.002 163	0.005 206	0.007 165	0.003 235	0.019 702	0.006 280

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.05	0.088	0.395	5.04	0.0	19.94	12025.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
132.9	50830.	0.69E 07	-0.146	1.189	19.96	-0.00286	3.051	0.0
(436.0)	(1061.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		19.940	5.043 0	0.220 7	0.040 248	0.008 266	0.028 24	0.012 85	0.013 209	0.018 53	0.002 2
CN		0.960	0.172 83	0.032 72	0.024 152	0.003 249	0.002 4	0.005 157	0.002 244	0.009 358	0.003 180
CM		-0.087	0.047 229	0.014 230	0.004 316	0.001 225	0.001 83	0.002 261	0.000 323	0.002 177	0.000 321
DCP 1	.010	3.214	1.524 187	0.020 337	0.159 313	0.116 94	0.021 72	0.085 232	0.037 77	0.035 277	0.013 170
DCP 2	.020	2.710	1.122 176	0.087 302	0.074 207	0.086 58	0.045 175	0.052 189	0.022 290	0.024 179	0.007 349
DCP 3	.030	2.463	1.032 160	0.281 261	0.142 109	0.038 222	0.063 85	0.059 171	0.023 27	0.020 200	0.029 324
DCP 4	.049	1.996	0.340 147	0.120 253	0.014 201	0.031 285	0.008 16	0.014 186	0.025 234	0.020 318	0.005 125
DCP 5	.074	1.714	0.217 90	0.055 181	0.019 171	0.026 256	0.015 58	0.020 176	0.015 259	0.013 342	0.008 98
DCP 6	.099	1.625	0.224 64	0.068 139	0.037 150	0.025 264	0.008 329	0.008 144	0.013 220	0.010 34	0.005 152
DCP 7	.149	1.469	0.224 50	0.068 116	0.029 132	0.024 236	0.007 309	0.003 145	0.004 231	0.009 346	0.005 268
DCP 8	.200	1.333	0.180 66	0.065 108	0.034 175	0.027 216	0.017 356	0.017 204	0.002 314	0.001 3	0.009 183
DCP 9	.250	1.282	0.205 81	0.047 120	0.048 188	0.016 236	0.005 265	0.005 51	0.008 189	0.009 41	0.005 175
DCP10	.300	1.197	0.213 82	0.037 98	0.046 165	0.021 238	0.004 244	0.005 249	0.004 280	0.009 36	0.007 194
DCP11	.399	1.092	0.222 81	0.046 76	0.041 159	0.012 288	0.006 344	0.003 252	0.007 258	0.018 3	0.007 238
DCP12	.501	0.925	0.221 73	0.046 65	0.034 127	0.006 141	0.007 334	0.003 80	0.003 291	0.015 8	0.010 183
DCP13	.600	0.776	0.214 63	0.057 54	0.022 142	0.009 73	0.003 158	0.004 143	0.002 231	0.012 3	0.012 166
DCP14	.701	0.674	0.206 55	0.065 46	0.018 142	0.008 31	0.001 246	0.009 95	0.001 99	0.010 346	0.003 108
DCP15	.830	0.522	0.185 50	0.063 41	0.014 153	0.010 13	0.003 186	0.006 103	0.002 40	0.008 8	0.005 38
DCP16	.900	0.237	0.136 64	0.035 47	0.010 109	0.007 74	0.003 252	0.007 109	0.004 164	0.007 324	0.006 346
DCP17	.969	0.064	0.072 76	0.015 55	0.008 101	0.001 170	0.003 331	0.006 97	0.002 100	0.006 332	0.002 149

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.66	0.169	0.406	5.51	0.0	0.02	12027.1	29

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
137.2	48752.	0.64E 07	-0.035	0.515	5.47	-0.30067	0.746	3.3
(450.1)	(1018.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.017	5.513 0	0.273 6	0.106 302	0.013 180	0.010 30	0.021 71	0.065 269	0.023 134	0.002 332
CN		0.122	0.408 357	0.019 26	0.004 37	0.002 257	0.003 227	0.002 63	0.004 218	0.001 359	0.001 282
CM		-0.014	0.018 278	0.002 295	0.001 206	0.002 74	0.000 104	0.000 300	0.001 12	0.001 115	0.000 335
DCP 1	.010	-0.659	2.027 342	0.231 30	0.341 143	0.036 88	0.018 163	0.038 315	0.013 242	0.011 2	0.002 164
DCP 2	.020	-0.317	2.009 348	0.093 350	0.011 30	0.018 63	0.013 162	0.035 28	0.012 242	0.011 393	0.007 285
DCP 3	.030	-0.026	1.695 348	0.075 342	0.009 48	0.011 59	0.007 168	0.034 10	0.012 242	0.001 48	0.004 343
DCP 4	.049	0.178	1.376 348	0.062 345	0.003 73	0.009 68	0.005 224	0.035 51	0.013 242	0.005 230	0.005 269
DCP 5	.074	0.339	1.115 349	0.049 357	0.008 86	0.008 80	0.003 168	0.007 17	0.008 242	0.004 121	0.004 269
DCP 6	.099	0.384	0.955 350	0.044 356	0.005 106	0.005 69	0.004 214	0.005 74	0.008 242	0.003 147	0.005 264
DCP 7	.149	0.252	0.705 351	0.032 7	0.006 117	0.013 104	0.003 184	0.006 75	0.005 242	0.003 177	0.004 254
DCP 8	.200	0.204	0.571 357	0.026 24	0.006 56	0.004 47	0.004 178	0.004 76	0.009 242	0.004 285	0.007 18
DCP 9	.250	0.173	0.576 355	0.025 22	0.009 353	0.003 205	0.004 228	0.005 133	0.005 242	0.006 129	0.003 8
DCP10	.300	0.183	0.486 356	0.022 21	0.006 339	0.004 256	0.005 217	0.001 14	0.002 272	0.007 108	0.001 20
DCP11	.399	0.179	0.393 6	0.023 45	0.009 1	0.010 309	0.004 219	0.001 34	0.005 242	0.008 62	0.003 319
DCP12	.501	0.112	0.302 13	0.018 49	0.003 29	0.005 256	0.006 268	0.005 193	0.005 242	0.004 43	0.004 162
DCP13	.600	0.131	0.229 15	0.013 65	0.006 10	0.006 228	0.004 238	0.001 336	0.005 242	0.003 332	0.002 215
DCP14	.701	0.187	0.161 19	0.012 66	0.008 38	0.007 239	0.004 344	0.003 57	0.007 242	0.005 307	0.001 133
DCP15	.833	0.086	0.098 29	0.009 74	0.003 98	0.004 263	0.001 260	0.004 162	0.003 184	0.007 310	0.002 97
DCP16	.900	-0.069	0.029 50	0.007 129	0.008 66	0.008 254	0.001 7	0.003 341	0.008 242	0.009 238	0.002 10
DCP17	.969	-0.038	0.023 174	0.003 213	0.005 298	0.005 259	0.005 199	0.005 76	0.003 242	0.004 102	0.006 219

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

		TUNED HZ 3.3	DRIVE HZ 45.67	K 0.171	MACH NO 0.402	DEL.ALPHA 5.52	DEL.M 3.3	ALPHA.0 2.46	TEST POINT 12027.2	CYCLES ANALYSED 20
		V 135.6 (444.9)	Q 47871. (999.8)	PK 0.64E 07	CM(MIN) -0.033	CN(MAX) 0.798	ALPHA.NMAX 7.93	AERO DAMP -3.33376	TDR 3.849	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.460	5.518 0	0.316 4	0.083 297	0.055 349	0.034 83	0.038 56	0.034 144	0.033 238	0.004 3
CN		0.361	0.443 357	0.022 14	0.007 4	0.012 21	0.001 187	0.031 256	0.034 235	0.003 158	0.000 236
CM		-0.007	0.023 295	0.003 275	0.000 264	0.005 185	0.001 297	0.000 339	0.001 3.	0.001 222	0.000 144
DCP 1	.013	1.291	3.023 342	0.158 343	0.018 101	0.016 82	0.019 251	0.009 243	0.038 145	0.018 193	0.002 188
DCP 2	.020	0.931	2.357 348	0.120 341	0.027 344	0.009 105	0.021 289	0.011 216	0.013 141	0.029 160	0.005 282
DCP 3	.030	1.031	2.013 347	5.394 338	3.035 325	0.035 153	0.013 282	0.039 238	0.036 65	5.023 160	0.012 142
DCP 4	.049	1.060	1.652 348	0.075 333	0.017 348	0.016 134	0.007 272	0.009 318	0.037 155	0.002 105	0.005 157
DCP 5	.074	1.053	1.312 348	0.065 349	0.021 10	0.014 145	0.002 210	0.014 0	0.009 143	0.008 78	0.034 152
DCP 6	.399	0.982	1.114 350	0.034 355	0.016 6	0.014 119	0.005 308	0.013 6	0.036 242	0.002 134	0.005 126
DCP 7	.149	0.735	0.826 351	0.042 7	0.009 348	0.015 73	0.005 135	0.003 330	0.003 43	0.004 276	0.002 246
DCP 8	.200	0.579	0.685 357	0.031 11	0.014 1	0.013 124	0.009 243	0.031 353	0.033 134	0.019 222	0.009 258
DCP 9	.253	0.465	0.582 355	0.031 4	0.010 349	0.019 18	0.002 233	0.008 213	0.034 254	0.015 209	0.003 23
DCP10	.300	0.435	0.480 356	0.024 9	0.011 4	0.013 336	0.002 242	0.002 223	0.005 143	0.010 190	0.007 99
DCP11	.399	0.371	0.390 6	0.026 42	0.010 10	0.022 11	0.003 88	0.034 223	0.038 164	0.036 144	0.001 93
DCP12	.501	0.286	0.299 11	0.023 55	0.008 339	0.015 17	0.003 283	0.001 207	0.038 224	0.005 136	0.001 101
DCP13	.600	0.241	0.220 17	0.015 54	0.010 338	0.014 12	0.004 177	0.007 41	0.008 149	0.006 40	0.003 112
DCP14	.731	0.265	0.158 21	0.014 42	0.010 81	0.015 355	0.013 118	0.034 218	0.039 23.	0.003 90	0.001 264
DCP15	.803	0.129	0.096 14	0.011 71	0.003 145	0.020 15	0.002 69	0.003 224	0.009 233	0.009 8	0.003 288
DCP16	.903	-0.075	0.036 56	0.008 55	0.004 21	0.019 15	0.003 203	0.001 141	0.037 13.	0.036 63	0.007 351
DCP17	.969	-0.052	0.024 165	0.032 238	0.008 187	0.018 7	0.009 91	0.034 91	0.035 254	0.036 228	0.005 235

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

		TUNED HZ 3.3	DRIVE HZ 45.71	K 0.173	MACH NO 0.400	DEL.ALPHA 5.50	DEL.M 0.0	ALPHA.0 4.98	TEST POINT 12027.3	CYCLES ANALYSED 20
		V 134.9 (442.5)	Q 47512. (992.3)	PK 0.64E 07	CM(MIN) -0.030	CN(MAX) 0.984	ALPHA.NMAX 10.41	AERO DAMP -3.33377	TDR 3.854	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.978	5.498 0	0.272 10	0.089 333	0.031 263	0.024 65	0.022 86	0.021 213	0.013 44	0.036 212
CN		0.608	0.384 0	0.029 25	0.005 329	0.004 219	0.001 217	0.001 140	0.033 251	0.003 242	0.002 235
CM		-0.006	0.022 286	0.003 219	0.001 41	0.002 72	0.003 61	0.003 345	0.003 71	0.032 35	0.000 55
DCP 1	.013	2.629	2.759 343	0.176 296	0.025 160	0.039 206	0.066 137	0.041 52	0.037 11	0.005 346	0.009 284
DCP 2	.020	2.114	1.937 349	0.108 13	0.023 214	0.086 87	0.352 353	0.051 257	0.033 151	0.017 94	0.006 158
DCP 3	.030	2.021	1.622 348	0.110 32	0.037 345	0.036 240	0.018 163	0.038 57	0.034 151	0.012 75	0.003 153
DCP 4	.049	1.893	1.356 349	0.081 29	0.042 343	0.009 180	0.009 185	0.008 93	0.038 151	0.009 95	0.002 275
DCP 5	.074	1.722	1.078 353	0.069 28	0.023 339	0.035 165	0.039 189	0.003 142	0.033 257	0.010 51	0.004 204
DCP 6	.099	1.547	0.932 351	0.063 31	0.015 346	0.013 96	0.004 201	0.002 230	0.003 153	0.005 55	0.005 165
DCP 7	.149	1.130	0.672 353	0.036 28	0.013 352	0.010 84	0.008 188	0.003 104	0.000 21.	0.010 1	0.001 28
DCP 8	.200	0.922	3.556 359	0.041 39	0.012 356	0.016 124	0.003 317	0.005 161	0.035 261	0.006 233	0.002 291
DCP 9	.253	0.812	3.559 357	0.037 11	0.004 15	0.007 237	0.001 11	0.003 236	0.034 151	0.013 345	0.003 282
DCP10	.300	0.729	0.446 359	0.033 12	0.007 330	0.009 252	0.004 317	0.034 154	0.033 264	0.036 307	0.003 227
DCP11	.399	0.603	0.367 9	0.032 32	0.003 325	0.007 287	0.009 308	0.002 113	0.334 273	0.011 263	0.006 244
DCP12	.501	0.443	0.284 15	0.021 40	0.006 254	0.008 251	0.003 285	0.001 285	0.015 54	0.006 258	0.002 273
DCP13	.600	0.375	0.208 22	0.025 30	0.004 245	0.036 273	0.003 187	0.003 108	0.037 224	0.035 240	0.006 225
DCP14	.701	0.352	0.138 33	0.027 31	0.005 349	0.005 190	0.001 142	0.003 17	0.005 253	0.011 195	0.001 74
DCP15	.800	0.181	0.086 45	0.017 38	0.002 353	0.035 235	0.002 207	0.003 192	0.001 194	0.011 195	0.002 206
DCP16	.933	-0.059	3.339 62	0.038 357	0.006 237	0.009 239	0.004 124	0.333 162	0.034 65	0.009 191	0.002 128
DCP17	.96P	-0.061	0.014 172	0.004 11	0.004 124	0.008 257	0.002 32	0.002 205	0.034 113	0.007 348	0.004 354

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL-ALPHA	DEL-H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.20	0.171	0.399	5.43	0.0	7.46	12027.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
134.2	47224.	0.64E 07	-0.031	1.263	12.65	-0.00095	1.349	0.0
(440.3)	(986.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.465	5.427	0	0.273	15	0.114	291	0.017	333	0.025	72	0.022	107	0.014	273	0.011	156	0.007	240
CN		0.775	0.401	16	0.078	339	0.016	178	0.011	137	0.003	208	0.003	191	0.036	54	0.035	298	0.001	163
CM		0.001	0.327	286	0.013	59	0.011	287	0.001	158	0.002	40	0.001	86	0.003	283	0.001	271	0.001	224
DCP 1	.010	3.542	1.886	354	0.915	48	0.734	325	0.345	227	0.030	29	0.157	225	0.119	113	0.060	334	0.058	191
DCP 2	.020	2.929	1.668	4	0.586	30	0.364	313	0.214	234	0.117	186	0.134	150	0.285	85	0.062	47	0.049	358
DCP 3	.030	2.844	1.670	2	0.419	7	0.249	284	0.179	196	0.107	117	0.053	68	0.042	22	0.032	333	0.033	309
DCP 4	.049	2.585	1.441	2	0.311	356	0.139	258	0.083	145	0.034	53	0.038	142	0.085	5	0.037	305	0.018	243
DCP 5	.074	2.276	1.160	4	0.254	348	0.114	237	0.075	116	0.033	19	0.013	161	0.041	81	0.048	285	0.031	212
DCP 6	.099	1.999	0.972	6	0.220	347	0.094	229	0.060	113	0.020	14	0.007	53	0.032	13	0.038	268	0.021	190
DCP 7	.149	1.476	0.760	9	0.179	341	0.078	213	0.353	99	0.011	359	0.333	125	0.019	334	0.019	228	0.013	149
DCP 8	.200	1.212	0.634	15	0.140	337	0.061	200	0.038	78	0.010	299	0.013	64	0.021	32	0.016	247	0.006	146
DCP 9	.250	1.052	0.588	10	0.104	298	0.068	144	0.037	52	0.018	272	0.006	182	0.003	6	0.002	13	0.007	151
DCP10	.300	0.920	0.483	12	0.079	299	0.058	130	0.023	29	0.016	191	0.007	20	0.005	211	0.005	83	0.005	314
DCP11	.399	0.739	0.381	25	0.062	314	0.050	136	0.016	49	0.012	244	0.006	283	0.008	193	0.005	18	0.001	285
DCP12	.501	0.549	0.303	30	0.048	305	0.040	131	0.008	75	0.008	269	0.007	243	0.012	111	0.009	310	0.005	198
DCP13	.600	0.432	0.235	45	0.050	323	0.036	130	0.333	49	0.011	213	0.305	224	0.012	193	0.009	293	0.008	90
DCP14	.701	0.371	0.176	65	0.047	325	0.028	120	0.006	315	0.007	186	0.005	292	0.010	66	0.004	56	0.008	48
DCP15	.800	0.196	0.128	67	0.023	301	0.030	94	0.039	283	0.008	163	0.032	320	0.009	67	0.004	161	0.008	41
DCP16	.900	-0.036	0.061	43	0.033	228	0.021	60	0.023	182	0.001	245	0.007	164	0.005	357	0.004	51	0.003	357
DCP17	.969	-0.058	0.016	35	0.015	236	0.010	91	0.320	183	0.001	348	0.003	157	0.003	213	0.003	62	0.003	249

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL-ALPHA	DEL-H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.61	0.173	0.398	5.42	0.0	9.80	12027.5	23

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
133.9	47100.	0.64E 07	-0.115	1.438	15.00	-0.00084	0.923	0.0
(439.2)	(983.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		9.797	5.425	0	0.331	25	0.178	324	0.066	103	0.031	69	0.021	85	0.020	223	0.010	83	0.011	258
CN		0.883	0.439	39	0.129	346	0.032	246	0.016	145	0.012	35	0.035	315	0.038	25	0.008	242	0.003	69
CM		-0.011	0.339	224	0.035	76	0.017	340	0.012	288	0.008	203	0.003	120	0.003	61	0.002	10	0.002	228
DCP 1	.010	4.113	1.304	11	1.318	72	0.460	5	0.331	59	0.198	38	0.118	352	0.092	334	0.053	336	0.039	330
DCP 2	.020	3.258	0.871	32	0.795	63	0.347	9	0.188	347	0.139	375	0.092	249	0.062	211	0.034	291	0.049	319
DCP 3	.030	2.986	0.757	42	0.620	56	0.407	348	0.160	301	0.088	209	0.099	280	0.007	211	0.333	210	0.041	249
DCP 4	.049	2.774	0.845	37	0.639	39	0.236	323	0.061	294	0.067	293	0.058	234	0.024	164	0.037	248	0.037	192
DCP 5	.074	2.415	0.757	42	0.521	30	0.190	307	0.051	290	0.077	264	0.059	191	0.043	111	0.036	227	0.040	159
DCP 6	.099	2.132	0.714	44	0.449	21	0.160	293	0.043	283	0.071	246	0.055	161	0.019	71	0.323	226	0.022	136
DCP 7	.149	1.646	0.687	39	0.328	358	0.106	268	0.237	267	0.059	201	0.032	139	0.036	61	0.026	175	0.023	92
DCP 8	.200	1.363	0.629	42	0.266	354	0.061	266	0.038	253	0.050	186	0.022	99	0.035	11	0.006	15	0.006	105
DCP 9	.250	1.175	0.593	35	0.233	335	0.068	245	0.045	221	2.347	151	0.024	85	0.037	6	0.319	46	0.013	342
DCP10	.300	1.046	2.540	14	0.207	322	0.076	220	0.041	181	0.040	110	0.021	42	0.013	24	0.019	0	0.019	315
DCP11	.399	0.866	0.482	40	0.165	320	0.062	222	0.055	182	0.048	106	0.027	42	0.008	.	0.026	300	0.032	176
DCP12	.501	0.654	0.409	41	0.138	327	0.364	237	0.357	149	0.049	63	0.017	348	0.025	321	0.024	278	0.002	142
DCP13	.600	0.522	0.342	47	0.123	243	0.060	182	0.049	126	0.044	43	0.021	138	0.018	211	0.016	250	0.009	84
DCP14	.701	0.442	0.256	52	0.113	278	0.063	153	0.045	98	0.043	18	0.025	294	0.025	203	0.321	193	0.011	79
DCP15	.800	0.295	0.193	43	0.101	256	0.059	198	0.046	79	0.337	347	0.023	259	0.019	23	0.016	173	0.013	31
DCP16	.900	0.012	0.130	22	0.082	243	0.031	140	0.041	81	0.034	326	0.009	228	0.015	223	0.014	154	0.013	46
DCP17	.969	-0.038	0.049	14	0.035	261	0.315	183	0.325	92	0.315	323	0.034	258	0.338	174	0.310	87	0.008	42

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.67	0.170	0.405	5.31	3.0	12.23	12029.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
136.8	48575.	0.64E 07	-0.189	1.631	16.60	-0.33127	1.424	0.0
(448.7)	(1014.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.204	5.313 0	0.271 21	0.136 46	0.165 205	0.323 187	0.333 64	0.329 294	0.027 128	0.017 255
CN		0.995	0.413 58	0.115 4	0.051 306	0.033 209	0.034 193	0.315 114	0.338 195	0.006 62	0.004 236
CM		-0.033	0.075 210	0.034 109	0.019 87	0.014 17	0.013 347	0.006 257	0.003 276	0.004 214	0.002 148
DCP 1	.010	4.370	0.407 156	0.671 100	0.093 130	0.117 122	0.002 203	0.034 311	0.082 366	0.031 346	0.013 242
DCP 2	.020	3.360	0.565 126	0.598 99	0.155 108	0.099 116	0.048 203	0.052 214	0.038 366	0.020 259	0.014 264
DCP 3	.030	3.087	0.665 118	0.569 79	0.072 114	0.112 114	0.045 152	0.043 179	0.053 166	0.037 242	0.029 227
DCP 4	.049	2.879	0.672 94	0.419 57	0.017 77	0.254 105	0.015 190	0.027 170	0.028 23	0.027 178	0.024 210
DCP 5	.074	2.513	0.659 89	0.355 48	0.028 82	0.362 95	0.022 55	0.015 119	0.012 374	0.007 119	0.017 232
DCP 6	.099	2.261	0.650 81	0.318 38	0.017 9	0.354 98	0.335 82	0.335 78	0.023 66	0.022 37	0.009 295
DCP 7	.149	1.769	0.595 68	0.232 23	0.031 15	0.039 35	0.023 341	0.022 31	0.023 366	0.025 255	0.023 197
DCP 8	.200	1.500	0.562 63	0.160 25	0.053 55	0.043 48	0.035 1	0.023 328	0.015 444	0.011 82	0.016 60
DCP 9	.253	1.337	0.615 59	0.246 14	0.141 349	0.394 298	0.059 248	0.036 217	0.013 254	0.006 237	0.020 210
DCP10	.300	1.178	0.570 55	0.200 7	0.146 342	0.092 277	0.060 239	0.041 201	0.035 374	0.013 215	0.023 177
DCP11	.399	1.012	0.546 55	0.168 358	0.124 338	0.074 273	0.076 245	0.039 181	0.012 264	0.014 179	0.019 182
DCP12	.501	0.793	0.480 49	0.138 338	0.097 306	0.070 241	0.084 212	0.043 143	0.021 144	0.029 115	0.008 72
DCP13	.600	0.656	0.436 47	0.132 315	0.083 284	0.070 215	0.082 190	0.045 104	0.024 144	0.032 75	0.013 12
DCP14	.701	0.544	0.368 45	0.136 293	0.087 257	0.081 185	0.074 166	0.345 71	0.019 124	0.033 45	0.019 322
DCP15	.800	0.360	0.312 33	0.133 282	0.096 247	0.081 168	0.066 138	0.034 52	0.022 74	0.028 347	0.013 294
DCP16	.900	0.068	0.208 21	0.080 290	0.086 239	0.051 161	0.045 110	0.024 21	0.014 44	0.015 325	0.008 303
DCP17	.969	-0.012	0.350 18	0.038 336	0.031 241	0.025 145	0.014 124	0.015 37	0.035 355	0.006 16	0.004 324

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	44.95	0.169	0.401	5.18	3.0	14.99	12029.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
135.4	47756.	0.64E 07	-0.202	1.613	17.73	-0.33175	1.944	0.0
(444.1)	(997.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		14.977	5.178 0	0.149 25	0.114 66	0.125 212	0.029 297	0.317 65	0.037 194	0.014 115	0.013 224
CN		1.035	0.429 76	0.102 60	0.042 30	0.324 243	0.011 289	0.015 255	0.037 214	0.008 214	0.004 83
CM		-0.045	0.091 210	0.025 168	0.024 131	0.016 77	0.003 99	0.334 54	0.032 344	0.052 30	0.032 299
DCP 1	.010	4.296	1.822 179	0.711 136	0.152 160	0.084 195	0.038 226	0.105 6	0.064 55	0.042 68	0.061 64
DCP 2	.020	3.304	1.185 160	0.617 136	0.313 167	0.249 201	0.112 222	0.098 306	0.021 294	0.046 41	0.031 118
DCP 3	.030	3.057	1.236 149	0.439 115	0.342 164	0.180 198	0.122 225	0.379 229	0.077 255	0.031 265	0.019 331
DCP 4	.049	2.887	1.037 127	0.330 90	0.212 133	0.111 142	0.036 195	0.044 220	0.039 243	0.025 258	0.005 29
DCP 5	.074	2.532	0.928 116	0.212 87	0.240 122	0.375 131	0.047 163	0.338 236	0.031 174	0.314 263	0.004 297
DCP 6	.099	2.271	0.847 106	0.164 84	0.225 111	0.363 116	0.018 112	0.026 195	0.015 144	0.033 233	0.016 281
DCP 7	.149	1.635	0.714 86	0.134 90	0.204 85	0.072 71	0.038 9	0.018 117	0.033 244	0.013 165	0.037 99
DCP 8	.203	1.558	0.653 84	0.188 95	0.191 73	0.364 77	0.041 16	0.015 75	0.035 144	0.023 168	0.015 97
DCP 9	.253	1.359	0.620 76	0.180 71	0.139 33	0.018 348	0.027 326	0.016 315	0.037 314	0.015 197	0.016 68
DCP10	.300	1.223	0.574 70	0.186 62	0.125 19	0.026 355	0.029 324	0.015 324	0.014 316	0.035 121	0.014 26
DCP11	.399	1.053	0.562 67	0.155 56	0.109 20	0.041 318	0.023 340	0.031 314	0.018 294	0.010 307	0.009 334
DCP12	.501	0.844	0.514 58	0.119 36	0.092 354	0.052 293	0.017 314	0.034 273	0.020 244	0.008 221	0.012 289
DCP13	.600	0.708	0.474 53	0.097 18	0.085 329	0.365 276	0.014 283	0.334 259	0.017 194	0.011 244	0.012 212
DCP14	.701	0.589	0.405 47	0.083 352	0.103 304	0.073 251	0.019 244	0.025 233	0.015 144	0.013 228	0.017 127
DCP15	.800	0.410	0.345 36	0.094 346	0.094 293	0.074 235	0.013 216	0.018 205	0.009 166	0.020 205	0.020 95
DCP16	.900	3.123	0.229 24	0.078 350	0.049 274	0.361 223	0.011 279	0.019 181	0.013 117	0.007 173	0.011 83
DCP17	.969	0.012	0.106 33	0.051 352	0.020 307	0.041 240	0.011 224	0.015 215	0.035 144	0.003 115	0.004 175

FORCED PITCHING OSCILLATION　　　AIRFOIL　　NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.64	0.172	0.400	5.30	0.0	17.47	12029.5	20

V	Q	R0	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
134.9	47521.	0.64E 07	-0.242	1.758	18.48	-0.03225	2.454	0.0
(442.5)	(992.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		17.466	5.300 3	0.190 950	0.127 167	0.001 347	0.066 29	0.014 50	0.061 244	0.007 244	0.001 100
CN		1.051	0.400 77	0.105 73	0.082 87	0.323 52	0.050 37	0.311 22	0.062 .	5.3 191	0.032 18
CM		-0.061	0.132 215	0.343 234	0.327 712	0.374 191	0.014 189	0.032 161	0.335 144	0.039 251	0.001 157
DCP 1	.013	3.872	2.749 165	0.214 277	0.114 274	0.074 274	0.125 71	0.331 144	0.063 144	0.324 232	0.007 203
DCP 2	.020	3.376	1.552 171	0.314 193	0.316 256	0.386 209	0.114 958	0.351 78	0.391 144	0.025 245	0.007 223
DCP 3	.030	2.451	1.347 157	0.312 167	0.962 104	0.190 277	0.075 907	0.117 953	0.005 144	0.031 27	0.016 115
DCP 4	.049	2.055	0.993 107	0.162 234	0.260 175	0.126 254	0.042 254	0.352 354	0.335 54	0.325 123	0.003 97
DCP 5	.074	2.567	0.668 119	0.161 149	0.211 147	7.139 201	0.073 265	0.362 338	0.384 144	0.913 47	0.012 85
DCP 6	.099	2.267	0.781 102	0.171 187	0.167 147	0.073 192	0.019 24	0.313 292	0.044 144	0.011 67	0.016 152
DCP 7	.149	1.814	0.673 86	0.240 141	0.151 117	0.397 143	0.337 97	0.313 3	0.045 47	0.013 29	0.028 311
DCP 8	.200	1.513	0.607 90	0.249 120	0.121 119	0.390 147	2.346 79	0.313 252	0.015 .	0.014 321	0.004 312
DCP 9	.250	1.367	0.613 76	0.244 104	0.139 134	0.091 107	0.063 75	0.035 348	0.02 144	0.018 269	0.011 326
DCP10	.333	1.222	0.572 72	0.222 93	0.194 99	0.303 97	0.383 72	0.311 93	0.011 8.	0.018 194	0.004 243
DCP11	.399	1.085	5.557 67	0.256 79	0.150 49	0.077 84	0.100 77	0.383 92	0.084 54	0.091 170	0.011 107
DCP12	.501	0.897	0.529 59	0.203 56	0.135 74	0.386 64	0.099 55	0.327 85	0.385 54	5.034 195	0.013 86
DCP13	.603	3.748	5.536 53	0.109 42	0.125 56	0.367 58	0.397 32	0.331 31	0.044 14	0.093 102	0.01 32
DCP14	.701	0.626	0.472 49	0.177 23	0.121 32	0.079 0	0.085 358	8.317 335	0.083 144	0.031 63	0.009 327
DCP15	.800	0.474	0.395 41	0.167 13	0.113 16	3.371 338	3.366 337	0.318 322	0.392 244	0.317 29	0.038 273
DCP16	.903	0.167	0.244 41	0.126 1	0.086 12	2.344 333	0.342 334	0.314 332	0.028 244	0.071 5	0.098 242
DCP17	.969	0.042	0.114 48	0.053 0	0.024 13	3.019 316	0.019 322	0.009 241	3.025 244	0.000 271	0.007 51

FORCED PITCHING OSCILLATION　　　AIRFOIL　　NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.56	0.173	0.399	5.32	0.0	19.87	12029.4	20

V	Q	R0	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
134.3	47229.	0.64E 07	-0.203	1.494	19.83	-0.03272	2.999	0.0
(440.5)	(986.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		19.871	5.322 0	0.204 357	0.080 228	0.007 341	0.029 48	0.015 77	0.049 244	0.014 161	0.004 61
CN		1.334	0.366 79	0.353 111	0.037 87	0.337 184	0.106 212	0.339 55	0.331 14	0.001 263	0.003 134
CM		-0.085	0.091 231	0.022 232	0.016 245	0.002 0	0.003 71	0.001 206	0.032 .	0.001 93	0.002 301
DCP 1	.013	3.336	1.700 167	0.429 308	0.399 0	0.102 88	0.074 177	0.348 161	0.047 244	0.323 254	0.013 333
DCP 2	.020	2.863	1.056 170	0.264 288	0.071 311	0.163 48	0.074 165	0.026 111	0.003 244	0.014 348	0.026 332
DCP 3	.030	2.572	1.002 156	0.351 258	0.036 305	0.118 322	0.088 43	0.029 119	0.042 54	0.095 157	0.005 147
DCP 4	.049	2.427	0.726 143	0.284 214	0.350 272	0.332 334	0.310 286	0.353 201	0.338 54	0.322 318	0.013 36
DCP 5	.074	2.139	0.535 117	0.288 196	0.044 280	0.023 273	0.010 195	0.311 236	0.013 144	0.022 262	0.015 153
DCP 6	.099	1.962	0.495 97	0.261 185	0.055 254	0.031 223	0.035 2	0.038 198	0.013 99	5.311 165	0.013 336
DCP 7	.149	1.678	0.451 77	0.192 146	0.333 194	0.332 161	0.008 68	0.313 127	0.011 177	0.011 177	0.003 264
DCP 8	.200	1.484	0.454 79	0.140 134	0.046 163	0.008 82	0.007 310	0.008 80	0.013 54	0.014 157	0.001 120
DCP 9	.250	1.359	0.445 77	0.126 119	0.358 146	3.319 218	3.312 260	0.322 66	0.002 44	0.337 151	0.039 197
DCP10	.333	1.245	0.425 74	0.114 103	0.067 128	0.327 216	0.004 217	0.017 39	0.012 44	0.008 76	0.002 106
DCP11	.399	1.133	0.401 75	0.101 99	0.088 113	3.034 212	0.010 351	0.017 64	0.047 354	0.019 89	0.006 219
DCP12	.501	3.957	0.362 69	0.092 87	3.375 94	7.031 172	3.017 223	3.34 62	3.041 244	0.025 27	0.007 186
DCP13	.603	3.811	0.453 63	0.091 69	0.074 79	7.918 173	0.014 242	0.008 74	3.021 44	0.013 178	0.009 157
DCP14	.701	3.696	0.432 58	0.094 49	0.076 59	.014 99	0.015 186	0.314 53	0.016 174	3.319 277	0.013 119
DCP15	.803	3.545	3.372 56	3.377 54	0.065 45	5.037 12	3.315 203	0.313 53	0.019 144	0.013 246	0.012 90
DCP16	.900	0.240	0.249 57	0.044 38	0.044 35	3.004 29	0.009 134	0.016 325	0.047 466	0.010 189	0.005 54
DCP17	.969	0.068	0.122 65	0.022 40	0.321 30	3.312 281	3.311 241	3.313 2	3.002 .	7.013 252	3.004 253

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	k	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	0.0	45.68	0.186	0.404	5.59	0.0	5.83	12079.1	20

	V	Q	RN	C(HMIN)	C(NMAX)	ALPHA.NMAX	AERO DAMP	TQB	EXT DAMP
	136.2 (446.9)	48926. (1021.8)	0.690 07	-0.024	1.077	11.96	-0.00083	0.035	0.0

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		5.634	5.591 0	0.303 5	0.107 323	0.058 204	0.023 73	0.020 80	0.015 239	0.006 298	0.009 134
CN		0.711	0.375 359	0.095 17	0.006 106	0.006 287	0.002 51	0.009 224	0.001 160	0.003 340	0.004 101
CM		0.006	0.026 282	0.002 251	0.001 48	0.001 260	0.001 49	0.001 39	0.000 247	0.001 508	0.001 100
DCP 1	.010	3.071	2.612 342	0.161 282	0.056 120	0.054 243	0.042 114	0.057 49	0.022 323	0.032 322	0.007 349
DCP 2	.020	2.452	1.893 345	0.134 5	0.034 122	0.013 90	0.063 359	0.043 246	0.038 154	0.027 24	0.016 105
DCP 3	.030	2.549	1.616 345	0.134 17	0.027 73	0.033 269	0.014 57	0.010 178	0.020 343	0.017 96	
DCP 4	.040	2.401	1.362 344	0.133 14	0.025 46	0.044 267	0.016 48	0.001 195	0.011 192	0.017 339	0.018 100
DCP 5	.074	2.167	1.059 343	0.120 12	0.028 116	0.038 269	0.018 29	0.008 195	0.010 213	0.021 325	0.019 112
DCP 6	.090	2.022	0.870 344	0.103 15	0.034 113	0.036 266	0.016 44	0.005 233	0.009 223	0.015 338	0.024 115
DCP 7	.149	1.566	0.652 350	0.058 7	0.022 108	0.019 283	0.007 52	0.007 329	0.009 130	0.015 279	0.023 79
DCP 8	.200	1.339	0.524 357	0.064 5	0.037 119	0.035 284	0.024 55	0.010 238	0.010 227	0.006 346	0.021 111
DCP 9	.250	0.823	0.549 358	0.040 16	0.011 348	0.005 353	0.002 276	0.005 210	0.002 315	0.003 281	0.002 278
DCP10	.300	0.711	0.458 0	0.034 20	0.009 1	0.003 0	0.006 227	0.004 237	0.004 44	0.001 101	0.001 77
DCP11	.399	0.593	0.367 11	0.034 20	0.005 49	0.003 7	0.005 22a	0.011 323	0.003 95	0.000 54	0.004 323
DCP12	.501	0.459	0.283 16	0.024 56	0.004 102	0.006 44	0.004 242	0.007 232	0.003 107	0.002 108	0.003 144
DCP13	.600	0.394	0.218 22	0.023 47	0.006 94	0.004 41	0.002 132	0.005 204	0.004 34	0.003 82	0.001 257
DCP14	.701	0.373	0.140 35	0.025 57	0.003 130	0.004 114	0.001 129	0.007 212	0.001 8	0.005 89	0.002 224
DCP15	.800	0.191	0.094 49	0.012 28	0.007 137	0.002 139	0.003 243	0.004 233	0.003 146	0.002 53	0.003 326
DCP16	.900	-0.057	0.041 63	0.006 5	0.004 269	0.002 161	0.001 290	0.008 217	0.003 159	0.005 240	0.005 205
DCP17	.969	-0.059	0.024 165	0.006 306	0.008 191	0.003 188	0.005 186	0.004 52	0.003 76	0.004 0	0.005 27

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	k	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	0.0	44.70	0.187	0.402	9.57	5.9	7.51	12079.2	20

	V	Q	RN	C(HMIN)	C(NMAX)	ALPHA.NMAX	AERO DAMP	TQB	EXT DAMP
	135.1 (443.2)	47923. (1000.9)	0.68E 07	-0.099	1.273	12.92	-0.30096	1.971	0.9

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		9.512	9.579 0	0.196 8	0.100 295	0.071 257	0.041 40	0.027 44	0.029 178	0.007 289	0.009 122
CN		0.773	0.475 18	0.095 930	0.021 147	0.012 328	0.007 164	0.007 44	0.003 395	0.002 295	0.001 199
CM		-0.002	0.030 282	0.011 52	0.013 271	0.008 196	0.007 396	0.001 113	0.001 315	0.001 296	0.001 104
DCP 1	.010	3.486	7.192 359	0.753 49	0.678 327	0.345 295	0.027 49	0.147 279	1.112 129	0.047 18	0.094 160
DCP 2	.020	2.961	1.675 2	0.479 21	0.284 310	0.149 296	0.133 185	0.106 195	0.067 90	0.079 65	0.072 13
DCP 3	.030	2.427	1.717 1	0.347 9	0.256 293	0.187 208	0.130 139	0.599 76	0.074 12	0.042 118	0.039 300
DCP 4	.040	2.478	1.344 9	0.378 0	0.191 276	0.098 169	0.022 85	0.043 130	0.073 41	0.077 319	0.047 231
DCP 5	.074	2.197	1.135 7	0.312 357	0.161 244	0.108 131	0.045 97	0.012 44	0.042 357	0.044 270	0.091 101
DCP 6	.090	1.956	0.995 9	0.264 341	0.117 219	0.097 110	0.033 7	0.017 71	0.049 329	0.044 233	0.529 131
DCP 7	.149	1.499	0.844 9	0.295 318	0.114 180	0.073 68	0.019 295	0.023 58	0.047 302	0.043 208	0.029 105
DCP 8	.200	1.707	0.604 15	0.144 316	0.085 140	0.049 56	0.008 252	0.024 19	0.042 276	0.029 160	0.017 47
DCP 9	.250	1.262	0.603 12	0.191 299	0.091 146	0.345 20	0.309 267	0.022 314	0.094 204	0.029 97	0.019 354
DCP10	.300	0.911	0.409 15	0.097 294	0.079 132	0.041 1	0.014 232	0.037 270	0.016 167	0.015 47	0.036 299
DCP11	.399	0.750	0.417 26	0.071 305	0.065 127	0.038 351	0.014 219	0.006 317	0.014 147	0.019 48	0.009 269
DCP12	.501	0.563	0.375 39	0.055 395	0.051 116	0.061 192	0.012 219	0.006 193	0.010 99	0.038 996	0.007 192
DCP13	.600	0.453	0.262 49	0.049 312	0.044 181	0.018 115	0.019 166	0.005 69	0.004 84	0.056 292	0.001 395
DCP14	.701	0.388	0.198 44	0.045 321	0.043 46	0.094 507	0.019 137	0.052 173	0.005 42	0.029 282	0.033 174
DCP15	.800	0.197	0.145 44	0.035 273	0.041 81	0.027 293	0.011 120	0.004 232	0.054 993	0.003 245	0.005 27
DCP16	.900	-0.390	0.070 40	0.042 273	0.025 94	0.015 245	0.008 127	0.004 57	0.092 933	0.036 116	0.037 261
DCP17	.969	-0.090	0.110 71	0.021 251	0.019 17	0.097 294	0.091 397	0.009 149	0.031 19	0.094 49	0.004 299

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNER HZ	DRIVE HZ	K	MACH NO	MEL.ALPHA	DEL.P	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	49.71	0.189	0.398	5.51	5.0	15.02	12079.3	70

V	Q	RN	CN(MEAN)	CN(MEAN)	ALPHA.NMAX	AERO DAMP	TPD	FRT DAMP
133.6	47105.	0.449 07	-0.134	1.520	15.49	-5.00071	5.782	5.0
(438.4)	(983.8)							

HARMONIC ANALYSIS

DATA TYPE	K/F	RFS 0	RFS 1 PHI	RFS 2 PHI	RFS 3 PHI	RFS 4 PHI	RFS 5 PHI	RFS 6 PHI	RFS 7 PHI	RFS 8 PHI	RFS 9 PHI
ALPHA		10.029	9.507 9	0.176 19	0.165 324	0.014 230	0.035 85	0.022 29	0.022 182	0.019 116	0.506 172
CN		5.909	0.475 76	0.116 528	0.026 259	0.031 98	0.023 195	0.003 275	0.013 102	5.711 720	0.009 119
CM		-0.019	0.066 213	0.041 60	0.019 329	5.319 268	0.006 160	0.002 121	0.009 76	0.014 931	0.004 246
NCP 1	.017	7.074	1.798 10	1.015 76	0.524 19	0.204 95	0.765 1	0.144 310	0.022 106	0.095 134	0.046 297
NCP 2	.020	3.325	1.109 29	0.729 54	0.259 5	5.160 29	0.256 349	5.181 237	0.117 258	5.545 242	0.047 274
NCP 3	.070	2.934	0.796 47	0.923 56	0.487 148	0.181 100	0.114 336	0.141 271	0.179 316	0.043 165	0.034 217
NCP 4	.049	2.781	0.964 50	0.681 51	0.719 310	0.013 17	0.074 295	0.353 219	0.012 11	0.044 256	0.089 186
NCP 5	.074	2.347	0.877 41	0.538 71	0.181 295	5.392 314	0.090 253	0.765 166	7.015 4	1.759 723	5.061 140
NCP 6	.099	2.144	0.814 43	0.447 13	0.143 286	5.036 324	0.082 241	0.053 195	0.071 306	0.054 707	0.054 117
NCP 7	.149	1.867	0.764 39	0.337 351	0.089 255	0.047 294	0.040 208	0.041 115	0.013 229	5.037 126	0.339 94
NCP 8	.200	1.370	0.727 40	0.242 344	0.095 290	5.057 271	0.039 166	0.011 65	0.013 160	0.016 99	5.029 33
NCP 9	.250	1.218	0.689 96	0.741 573	0.073 273	0.066 203	0.053 141	0.014 09	5.071 98	0.074 146	0.029 354
NCP10	.303	1.087	0.665 99	0.237 357	5.096 256	0.053 158	0.041 96	3.019 94	0.093 28	0.039 116	0.025 268
NCP11	.390	5.893	0.587 56	0.199 292	0.074 143	0.564 151	0.049 63	0.012 89	5.045 99	0.056 104	0.036 217
NCP12	.571	0.714	0.490 56	0.165 281	0.071 181	0.080 128	0.049 31	0.008 19	5.037 345	0.759 253	0.095 163
NCP13	.600	0.566	2.988 47	0.136 265	5.573 156	0.006 102	0.066 358	0.016 311	5.333 291	5.138 707	5.335 120
NCP14	.703	0.471	0.346 44	0.123 246	0.074 126	0.066 76	0.056 325	0.016 260	0.075 360	0.033 157	0.094 74
NCP15	.800	0.701	7.721 33	0.118 230	0.055 126	7.062 64	0.349 178	0.013 291	5.025 710	0.093 138	5.353 47
NCP16	.900	5.075	5.191 11	5.598 270	5.343 144	5.066 52	0.032 295	0.009 299	5.011 195	5.025 106	5.573 9
NCP17	.949	-0.542	0.052 12	0.978 248	5.077 177	0.031 51	0.019 296	0.009 267	5.029 296	0.013 87	5.007 88

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	49.69	0.191	0.396	5.44	5.0	12.52	12079.4	70

V	Q	RN	CN(MEAN)	CN(MEAN)	ALPHA.NMAX	AERO DAMP	TPD	FRT DAMP
132.3	46339.	0.632 57	-0.222	1.786	17.57	-5.00084	5.961	5.0
(434.1)	(967.8)							

HARMONIC ANALYSIS

DATA TYPE	K/F	RFS 0	RFS 1 PHI	RFS 2 PHI	RFS 3 PHI	RFS 4 PHI	RFS 5 PHI	RFS 6 PHI	RFS 7 PHI	RFS 8 PHI	RFS 9 PHI
ALPHA		17.571	9.439 0	0.165 79	0.267 156	5.078 158	0.038 150	0.191 27	3.017 215	0.399 327	5.008 215
CN		1.899	0.492 91	5.129 948	0.953 359	0.028 799	0.092 174	0.026 196	5.016 49	0.019 9	0.096 336
CM		-0.294	0.095 293	0.043 95	0.026 67	0.018 351	0.012 329	0.010 758	5.006 196	0.006 187	0.001 106
NCP 1	.010	4.363	3.750 129	1.139 97	0.285 101	5.140 79	0.091 130	0.067 114	0.099 101	5.043 196	0.038 103
NCP 2	.027	3.665	3.671 88	0.752 82	0.226 76	0.119 77	0.148 92	0.107 71	5.578 64	5.047 90	0.053 91
NCP 3	.070	5.168	0.697 117	5.934 82	0.286 47	0.165 65	0.199 47	0.787 24	5.094 19	5.096 198	5.091 195
NCP 4	.049	2.979	0.806 99	5.608 95	0.096 44	3.124 91	0.029 355	3.035 63	5.058 19	5.024 129	0.036 31
NCP 5	.074	7.556	5.811 81	0.473 61	5.101 51	0.119 7	0.021 298	0.098 90	5.073 346	5.099 341	7.038 73
NCP 6	.099	2.296	5.792 76	0.375 94	5.141 54	0.152 342	0.020 222	0.093 29	5.044 347	5.043 794	0.021 309
NCP 7	.149	1.867	0.770 60	0.273 13	0.134 76	0.125 310	0.019 247	0.029 296	3.013 760	5.017 714	0.019 707
NCP 8	.200	1.950	0.745 58	0.244 14	0.133 7	0.114 802	0.030 263	0.022 215	5.034 108	5.017 313	7.021 244
NCP 9	.290	1.376	0.715 92	0.233 6	5.104 342	5.120 271	0.056 234	7.059 229	5.042 274	0.316 196	5.011 215
NCP10	.390	1.221	0.655 47	0.193 357	5.163 390	5.117 255	0.058 256	0.041 197	5.017 171	0.019 172	5.095 171
NCP11	.399	1.053	0.652 47	0.199 347	5.147 322	5.094 247	0.073 239	0.573 195	0.041 169	0.029 111	5.722 115
NCP12	.501	0.494	0.569 42	5.166 374	0.129 294	5.086 219	0.080 207	5.095 149	7.052 89	0.032 69	0.042 69
NCP13	.600	0.665	0.513 41	5.155 360	0.111 261	0.073 189	0.077 176	0.043 119	0.056 99	0.041 91	5.035 352
NCP14	.703	5.583	0.629 37	5.170 276	0.139 229	5.095 153	0.073 195	0.079 71	1.053 6	5.332 7	5.017 297
NCP15	.890	0.379	5.966 76	5.165 270	0.113 221	5.082 145	0.070 114	0.062 19	0.096 347	5.029 129	5.024 791
NCP16	.900	0.078	5.775 15	5.096 272	5.077 212	5.099 134	0.057 99	0.039 16	0.031 334	5.722 791	5.018 215
NCP17	.949	-0.321	5.393 15	0.043 795	5.041 276	5.024 143	0.024 199	0.024 29	5.012 794	5.009 797	5.009 206

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNNEL HZ	MODEL HZ	X	MACH NO	REL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYZED
0.0	49.68	0.192	0.599	5.36	0.0	15.10	12079.5	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.MAX	AERO DAMP	TAU	FST TEMP
132.0	86228.	0.655 07	-0.270	1.909	18.58	-0.00147	1.598	0.0
(433.1)	(965.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		14.798	5.361	0	0.741	21	0.238	42	0.087	290	0.020	234	0.011	134	0.007	292	0.036	87	0.004	208
CN		1.109	0.595	61	0.063	43	0.079	75	0.064	311	0.033	237	0.015	291	0.012	226	0.011	177	0.006	107
CM		-0.058	0.119	205	0.096	137	0.529	119	0.028	89	0.012	71	0.006	95	0.006	27	0.007	340	0.099	289
CP 1	.010	4.065	1.534	167	0.799	125	0.288	175	0.075	217	0.099	219	0.017	171	0.016	94	0.093	10	0.060	349
CP 2	.025	5.989	1.041	142	0.608	116	0.296	145	0.147	168	0.148	226	0.115	217	0.083	274	0.066	278	0.093	345
CP 3	.099	1.152	1.201	143	0.563	108	0.364	142	0.198	115	0.115	197	0.133	166	0.052	207	0.067	185	0.075	287
CP 4	.048	2.995	1.042	115	0.286	86	0.270	119	0.076	91	0.066	160	0.069	130	0.015	204	0.527	194	0.051	213
CP 5	.074	2.945	0.967	175	0.201	78	0.257	100	0.044	71	0.053	116	0.029	165	0.099	156	0.039	148	0.072	197
CP 6	.099	2.313	0.487	96	0.164	92	0.287	88	0.064	49	0.028	71	0.045	147	0.040	87	0.019	71	0.099	187
CP 7	.149	1.017	0.431	77	0.164	85	0.295	61	0.069	18	0.045	12	0.020	99	0.033	44	0.019	19	0.314	165
CP 8	.200	1.027	0.763	72	0.180	76	0.234	56	0.092	25	0.031	156	0.045	61	0.523	50	0.026	68	0.017	93
CP 9	.250	1.464	0.751	64	0.189	68	0.259	96	0.116	2	0.067	312	0.020	47	0.034	4	0.024	19	0.093	71
CP10	.300	1.308	0.794	58	0.177	62	0.219	74	0.140	349	0.077	287	0.021	349	0.022	342	0.028	74	0.599	361
CP11	.399	1.144	0.786	55	0.124	50	0.180	28	0.164	352	0.085	391	0.068	322	0.045	304	0.521	129	0.058	287
CP12	.501	0.960	0.664	46	0.105	16	0.141	0	0.163	329	0.086	274	0.074	299	0.099	265	0.040	255	0.055	226
CP13	.600	0.778	0.616	42	0.111	342	0.123	324	0.151	296	0.078	252	0.065	265	0.0	27	0.051	215	0.059	161
CP14	.751	0.670	0.560	35	0.127	325	0.193	291	0.155	263	0.089	191	0.049	202	0.0	185	0.054	165	0.051	107
CP15	.800	0.465	0.477	77	0.145	316	0.137	274	0.147	266	0.092	175	0.0	162	0.0	197	0.037	199	0.036	79
CP16	.905	0.199	0.396	17	0.199	316	0.067	269	0.092	229	0.061	151	0.0	186	0.030	347	0.034	124	0.013	41
CP17	.969	0.011	0.125	21	0.095	390	0.095	251	0.040	312	0.071	118	0.006	119	0.011	190	0.009	156	0.015	96

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNNEL HZ	MODEL HZ	X	MACH NO	REL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYZED
0.0	91.68	0.189	0.613	5.66	0.0	4.66	12081.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.MAX	AERO DAMP	TAU	FST TEMP
139.6	50456.	0.665 07	-0.399	0.676	10.95	-0.90082	0.697	0.0
(458.1)	(1053.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		4.960	5.660	0	0.124	1	0.148	4	0.019	279	0.033	81	0.016	68	0.039	274	0.017	297	0.012	132
CN		0.586	0.411	1	0.324	17	0.011	37	0.006	169	0.001	196	0.092	279	0.001	166	0.092	154	0.001	80
CM		-0.056	0.329	296	0.009	346	0.001	304	0.001	215	0.000	175	0.001	96	0.001	205	0.001	186	0.000	251
CP 1	.017	3.680	1.188	147	0.295	270	0.193	47	0.047	197	0.071	137	0.339	3	0.099	307	0.016	208	0.016	107
CP 2	.025	2.076	2.167	149	0.120	9	0.099	4	0.099	65	0.081	290	0.097	106	0.093	110	0.098	317	0.006	182
CP 3	.090	1.663	1.977	149	0.117	10	0.001	453	0.027	340	0.015	199	0.094	147	0.099	320	0.012	306	0.001	706
CP 4	.160	1.860	1.577	149	0.995	5	0.047	565	0.016	297	0.099	166	0.071	216	0.099	267	0.099	112	0.096	171
CP 5	.074	1.618	1.791	199	0.068	1	0.049	966	0.097	271	0.006	218	0.097	261	0.094	367	0.096	329	0.034	141
CP 6	.099	1.481	1.399	352	0.766	6	0.738	6	0.059	316	0.006	210	0.005	151	0.097	313	0.036	337	0.902	116
CP 7	.149	1.096	0.773	353	0.966	996	0.029	3	0.009	312	0.097	267	0.006	295	0.016	275	0.097	116	0.074	357
CP 8	.200	0.887	0.639	0	0.065	36	0.071	18	0.054	329	0.094	266	0.092	166	0.097	306	0.097	306	0.036	237
CP 9	.250	0.783	0.454	350	0.190	36	0.092	47	0.057	347	0.001	129	0.006	195	0.094	290	0.005	351	0.196	79
CP10	.302	0.682	0.444	1	0.093	19	0.049	56	0.007	179	0.001	245	0.007	347	0.009	350	0.091	17	0.051	295
CP11	.399	0.506	0.357	13	0.097	37	0.017	78	0.095	51	0.097	265	0.301	199	0.095	4	0.094	61	0.093	351
CP12	.531	0.436	0.279	19	0.524	97	0.011	91	0.099	24	0.001	11	0.099	279	0.099	73	0.996	70	0.094	60
CP13	.693	0.367	0.217	97	0.025	65	0.004	97	0.507	59	0.001	256	0.097	266	0.009	96	0.005	150	0.005	89
CP14	.751	0.351	0.169	97	0.071	41	0.090	91	0.105	60	0.002	167	0.096	367	0.002	129	0.007	290	0.007	
CP15	.800	0.176	0.096	51	0.017	64	0.139	98	0.002	46	0.007	185	0.091	98	0.095	156	0.092	26		
CP16	.905	-0.097	0.766	69	0.096	90	0.007	179	0.005	7	0.001	66	0.009	206	0.097	950	0.996	64	0.031	129
CP17	.969	-0.099	0.099	174	0.996	937	0.992	294	0.003	6	0.001	270	0.091	176	0.001	190	0.097	179	0.009	107

CONTENTS

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	51.57	0.191	0.409	5.61	0.0	7.47	12081.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TOR	EXT DAMP
137.7	49585.	0.65E 07	-0.035	1.217	12.88	-0.00095	1.073	0.0
(451.8)	(1035.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.467	5.608	0	0.330	4	0.110	348	0.070	257	0.034	74	0.024	76	0.017	23	0.019	337	0.007	126
CN		0.736	0.416	18	0.077	324	0.028	116	0.014	330	0.009	171	0.006	109	0.006	14	0.005	338	0.004	210
CM		-0.091	0.030	279	0.012	45	0.014	271	0.005	139	0.001	329	0.000	85	0.001	295	0.001	233	0.001	91
DCP 1	.010	3.170	2.074	354	0.744	40	0.624	328	0.304	233	0.024	340	0.152	213	0.093	115	0.048	318	0.050	160
DCP 2	.020	2.844	1.942	2	0.473	15	0.272	310	0.165	233	0.098	189	0.100	150	0.068	93	0.067	51	0.062	2
DCP 3	.030	2.733	1.706	1	0.363	1	0.193	291	0.141	206	0.090	133	0.066	95	0.070	26	0.060	329	0.036	289
DCP 4	.049	2.368	1.279	5	0.355	10	0.150	289	0.066	183	0.019	145	0.059	123	0.088	28	0.070	307	0.039	221
DCP 5	.074	2.061	1.076	6	0.285	355	0.103	255	0.052	135	0.007	158	0.047	97	0.069	354	0.044	255	0.026	156
DCP 6	.099	1.871	0.948	8	0.246	340	0.093	213	0.051	99	0.004	262	0.040	89	0.058	334	0.040	236	0.025	143
DCP 7	.149	1.428	0.830	8	0.205	316	0.106	175	0.067	59	0.013	299	0.026	38	0.042	286	0.026	192	0.017	126
DCP 8	.200	1.159	0.673	14	0.155	314	0.082	158	0.045	33	0.020	196	0.024	55	0.027	300	0.020	190	0.022	138
DCP 9	.250	1.010	0.587	13	0.123	294	0.084	130	0.051	8	0.009	195	0.017	375	0.021	203	0.015	58	0.007	295
DCP10	.300	0.880	0.501	14	0.099	285	0.093	116	0.048	356	0.013	229	0.006	244	0.014	157	0.018	27	0.007	310
DCP11	.399	0.711	0.402	27	0.073	299	0.072	119	0.032	344	0.010	166	0.010	284	0.015	142	0.019	32	0.008	282
DCP12	.501	0.536	0.329	32	0.053	290	0.064	107	0.033	334	0.012	183	0.001	200	0.011	105	0.015	25	0.010	271
DCP13	.600	0.425	0.262	44	0.046	295	0.057	96	0.031	319	0.016	164	0.006	147	0.005	107	0.005	354	0.006	298
DCP14	.701	0.363	0.200	64	0.038	302	0.044	91	0.024	284	0.012	124	0.001	167	0.011	34	0.001	287	0.003	161
DCP15	.800	0.181	0.145	66	0.024	263	0.043	76	0.024	289	0.009	149	0.007	149	0.008	26	0.005	265	0.006	203
DCP16	.900	-0.041	0.066	42	0.038	210	0.035	54	0.007	226	0.002	148	0.005	61	0.008	353	0.005	92	0.004	277
DCP17	.969	-0.053	0.024	43	0.020	238	0.015	71	0.003	359	0.004	343	0.009	117	0.009	272	0.003	299	0.006	242

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	51.51	0.192	0.406	5.53	0.0	9.97	12081.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TOR	EXT DAMP
136.4	48823.	0.65E 07	-0.131	1.461	15.40	-0.00067	0.748	0.0
(447.4)	(1019.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		9.972	5.531	0	0.441	18	0.177	327	0.025	269	0.029	76	0.024	11	0.039	172	0.017	292	0.007	135
CN		0.868	0.465	36	0.114	326	0.020	199	0.026	111	0.017	341	0.004	17	0.012	282	0.005	184	0.002	66
CM		-0.017	0.044	214	0.040	58	0.019	321	0.014	269	0.009	157	0.002	165	0.004	71	0.004	305	0.003	185
DCP 1	.010	3.821	1.986	11	0.942	71	0.487	16	0.130	24	0.193	7	0.106	313	0.033	313	0.054	313	0.029	295
DCP 2	.020	3.183	1.124	29	0.678	50	0.236	2	0.133	23	0.168	344	0.140	299	0.094	255	0.049	252	0.048	239
DCP 3	.030	2.804	0.787	44	0.838	55	0.425	350	0.159	301	0.104	297	0.111	257	0.088	203	0.057	176	0.042	187
DCP 4	.049	2.647	0.944	38	0.588	29	0.174	311	0.024	348	0.062	287	0.037	212	0.010	289	0.057	225	0.057	147
DCP 5	.074	2.777	0.862	40	0.491	18	0.129	300	0.054	327	0.084	246	0.040	154	0.016	321	0.034	210	0.041	120
DCP 6	.099	2.050	0.908	42	0.418	8	0.103	287	0.054	328	0.085	234	0.043	142	0.009	258	0.023	159	0.024	97
DCP 7	.149	1.592	0.770	38	0.345	348	0.099	255	0.034	250	0.054	190	0.021	112	0.023	161	0.018	85	0.029	36
DCP 8	.200	1.319	0.711	40	0.282	343	0.086	256	0.048	225	0.051	165	0.020	90	0.011	161	0.025	62	0.014	18
DCP 9	.250	1.165	0.671	35	0.257	324	0.079	232	0.057	203	0.061	136	0.044	61	0.022	2	0.022	350	0.028	309
DCP10	.300	1.048	0.623	31	0.215	308	0.066	214	0.067	177	0.048	91	0.016	51	0.027	38	0.036	326	0.027	243
DCP11	.395	0.892	0.569	34	0.177	297	0.059	204	0.075	165	0.053	73	0.014	52	0.045	19	0.044	298	0.030	211
DCP12	.501	0.678	0.462	36	0.146	294	0.065	184	0.087	130	0.063	24	0.008	336	0.034	328	0.037	251	0.032	159
DCP13	.600	0.534	0.381	40	0.135	266	0.072	156	0.087	109	0.070	351	0.011	16	0.044	294	0.046	185	0.026	95
DCP14	.701	0.450	0.290	45	0.128	246	0.095	118	0.064	66	0.057	315	0.008	344	0.043	246	0.017	132	0.020	23
DCP15	.800	0.263	0.221	34	0.127	231	0.074	109	0.051	58	0.036	301	0.015	335	0.042	220	0.031	96	0.025	349
DCP16	.900	0.014	0.137	15	0.088	224	0.047	119	0.056	41	0.035	291	0.014	264	0.019	168	0.020	67	0.022	330
DCP17	.969	-0.028	0.060	4	0.045	246	0.016	153	0.033	80	0.025	305	0.003	313	0.008	201	0.013	107	0.008	345

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TES. POINT	CYCLES ANALYSED
0.0	51.64	0.194	0.403	5.47	0.0	12.51	12081.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
135.4 (444.2)	48263. (1008.0)	0.64E 07	-0.221	1.724	17.38	-0.00074	0.822	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.513	5.467 0	0.417 31	0.336 350	0.049 126	0.044 122	0.039 34	0.033 214	0.030 268	0.009 220
CN		0.999	0.502 47	0.101 354	0.053 315	0.025 217	0.028 156	0.017 86	0.010 70	0.011 14	0.006 305
CM		-0.037	0.088 201	0.045 88	0.022 53	0.018 339	0.012 298	0.009 241	0.005 196	0.005 156	0.004 87
DCP 1	.010	4.017	0.446 125	1.180 93	0.220 94	0.191 71	0.068 174	0.031 145	0.043 180	0.007 131	0.039 201
DCP 2	.020	3.438	0.627 90	0.801 87	0.269 64	0.124 49	0.107 91	0.059 56	0.026 123	0.019 94	0.016 261
DCP 3	.030	3.048	0.669 110	0.886 81	0.276 39	0.129 48	0.108 51	0.052 8	0.030 92	0.037 35	0.003 348
DCP 4	.049	2.849	0.804 85	0.555 53	0.089 46	0.107 33	0.025 49	0.037 58	0.037 42	0.014 351	0.017 19
DCP 5	.074	2.466	0.808 77	0.432 40	0.105 49	0.130 7	0.036 316	0.003 305	0.032 40	0.010 335	0.014 10
DCP 6	.099	2.227	0.793 70	0.338 31	0.119 54	0.130 358	0.044 319	0.030 309	0.014 341	0.012 252	0.003 261
DCP 7	.149	1.792	0.774 57	0.257 19	0.141 13	0.109 313	0.026 276	0.025 297	0.023 311	0.012 194	0.009 317
DCP 8	.200	1.497	0.721 55	0.232 20	0.162 359	0.092 293	0.015 305	0.036 287	0.023 248	0.004 303	0.019 263
DCP 9	.250	1.327	0.729 48	0.219 3	0.195 337	0.123 264	0.056 232	0.027 234	0.051 207	0.036 170	0.025 124
DCP10	.300	1.185	0.660 44	0.172 357	0.180 331	0.115 258	0.075 216	0.043 179	0.040 165	0.029 124	0.031 96
DCP11	.399	1.028	0.647 44	0.141 341	0.148 331	0.108 256	0.086 219	0.061 163	0.041 142	0.036 101	0.033 76
DCP12	.501	0.812	0.585 40	0.135 315	0.119 299	0.092 220	0.080 182	0.060 131	0.054 100	0.051 49	0.032 5
DCP13	.600	0.667	0.533 38	0.154 292	0.107 264	0.094 185	0.089 154	0.066 94	0.056 69	0.066 16	0.044 312
DCP14	.701	0.570	0.445 35	0.182 272	0.106 224	0.104 150	0.084 113	0.062 56	0.049 14	0.044 318	0.043 274
DCP15	.800	0.367	0.370 24	0.183 261	0.113 203	0.097 126	0.070 82	0.058 20	0.036 328	0.032 280	0.021 218
DCP16	.900	0.084	0.240 8	0.098 256	0.075 197	0.063 108	0.048 62	0.025 18	0.027 310	0.027 285	0.030 206
DCP17	.969	-0.009	0.099 9	0.044 282	0.028 204	0.031 124	0.027 59	0.027 1	0.013 270	0.001 112	0.005 3

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	51.73	0.196	0.400	5.38	0.0	15.07	12081.5	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
134.3 (440.8)	47665. (995.5)	0.64E 07	-0.266	1.866	18.61	-0.00107	1.197	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		15.071	5.376 0	0.284 27	0.312 22	0.078 188	0.023 196	0.029 73	0.025 282	0.022 9	0.016 198
CN		1.078	0.547 55	0.068 31	0.072 8	0.049 305	0.023 273	0.017 259	0.015 208	0.010 165	0.010 69
CM		-0.060	0.121 199	0.038 128	0.033 132	0.021 62	0.010 350	0.006 50	0.005 354	0.006 318	0.007 238
DCP 1	.010	3.754	1.478 159	0.760 127	0.208 180	0.095 176	0.014 249	0.014 247	0.017 29	0.034 330	0.025 259
DCP 2	.020	3.417	1.077 134	0.591 110	0.244 115	0.152 140	0.090 207	0.072 200	0.041 220	0.021 315	0.047 293
DCP 3	.030	3.040	1.103 137	0.563 108	0.297 120	0.161 94	0.092 188	0.087 140	0.040 173	0.036 151	0.018 212
DCP 4	.049	2.912	1.005 109	0.301 90	0.236 103	0.076 65	0.020 158	0.025 177	0.044 191	0.034 172	0.027 178
DCP 5	.074	2.530	0.955 95	0.187 77	0.215 88	0.046 72	0.043 111	0.033 115	0.027 141	0.024 139	0.023 109
DCP 6	.099	2.280	0.907 98	0.153 87	0.256 72	0.048 26	0.023 87	0.030 93	0.011 104	0.018 64	0.014 93
DCP 7	.145	1.870	0.846 69	0.148 85	0.268 51	0.076 14	0.030 12	0.036 19	0.015 204	0.011 83	0.019 107
DCP 8	.200	1.586	0.760 47	0.171 79	0.213 44	0.071 11	0.020 349	0.020 0	0.006 110	0.011 331	0.011 4
DCP 9	.250	1.400	0.752 61	0.180 63	0.245 25	0.146 354	0.071 307	0.029 353	0.036 349	0.042 323	0.031 300
DCP10	.300	1.261	0.689 55	0.165 60	0.215 20	0.153 350	0.070 297	0.048 325	0.032 313	0.035 309	0.027 293
DCP11	.399	1.118	0.693 50	0.114 45	0.176 22	0.166 347	0.084 289	0.060 308	0.053 289	0.029 286	0.031 272
DCP12	.501	0.927	0.683 47	0.098 0	0.131 357	0.149 320	0.081 259	0.072 270	0.055 238	0.042 227	0.035 173
DCP13	.600	0.781	0.651 37	0.124 326	0.127 316	0.129 284	0.080 226	0.077 241	0.063 205	0.062 182	0.062 123
DCP14	.701	0.670	0.578 32	0.153 311	0.144 279	0.144 238	0.091 173	0.047 195	0.053 156	0.042 137	0.058 77
DCP15	.800	0.464	0.497 23	0.167 304	0.167 261	0.143 208	0.078 142	0.040 146	0.034 105	0.034 91	0.045 24
DCP16	.900	0.150	0.309 12	0.118 297	0.083 238	0.083 189	0.056 104	0.003 111	0.019 126	0.038 97	0.044 10
DCP17	.969	0.020	0.141 15	0.062 301	0.047 231	0.041 182	0.033 97	0.025 320	0.007 243	0.023 134	0.010 96

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	52.47	0.191	0.414	5.65	0.0	4.98	12083.1	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	139.9	50696.	0.66E 07	-0.038	0.962	10.47	-0.00077	0.891	0.0
	(458.9)	(1058.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		4.577	5.653	0	0.316	4	0.171	357	0.033	210	0.023	62	0.025	62	0.026	245	0.014	299	0.012	97
CN		0.581	0.400	1	0.028	17	0.010	43	0.003	316	0.001	179	0.002	87	0.002	347	0.004	343	0.001	228
CM		-0.007	0.029	301	0.003	259	0.003	320	0.002	235	0.001	97	0.001	240	0.001	176	0.001	200	0.001	51
DCP 1	.010	2.546	3.193	342	0.242	279	0.013	30	0.079	224	0.074	107	0.030	9	0.017	275	0.021	265	0.006	270
DCP 2	.020	2.012	2.137	349	0.134	10	0.067	2	0.011	21	0.036	317	0.055	217	0.036	125	0.018	331	0.004	65
DCP 3	.030	1.558	1.561	348	0.121	7	0.073	351	0.028	255	0.012	134	0.001	127	0.006	196	0.013	310	0.003	17
DCP 4	.049	1.834	1.560	349	0.094	3	0.058	354	0.022	258	0.008	139	0.002	123	0.005	180	0.002	17	0.002	78
DCP 5	.074	1.602	1.235	350	0.077	2	0.042	359	0.017	254	0.004	114	0.007	175	0.000	139	0.002	220	0.004	231
DCP 6	.099	1.472	1.025	352	0.073	7	0.033	10	0.015	263	0.009	132	0.004	172	0.006	76	0.004	262	0.032	109
DCP 7	.149	1.096	0.771	353	0.051	4	0.028	356	0.010	281	0.007	207	0.007	256	0.006	277	0.005	288	0.004	31
DCP 8	.200	0.882	0.626	0	0.043	23	0.022	31	0.012	303	0.003	230	0.001	268	0.004	341	0.033	345	0.002	351
DCP 9	.250	0.741	0.521	359	0.037	18	0.020	37	0.005	317	0.003	142	0.004	46	0.006	291	0.036	313	0.003	352
DCP10	.300	0.677	0.433	0	0.029	19	0.011	38	0.003	312	0.004	276	0.003	98	0.003	313	0.009	117	0.002	102
DCP11	.399	0.562	0.346	13	0.029	38	0.013	90	0.004	324	0.001	212	0.004	113	0.003	26	0.007	159	0.004	64
DCP12	.501	0.435	0.267	19	0.024	48	0.011	91	0.004	70	0.002	320	0.004	181	0.003	1	0.005	0	0.003	183
DCP13	.600	0.368	0.204	27	0.024	48	0.009	116	0.006	47	0.002	67	0.004	44	0.004	353	0.005	341	0.002	180
DCP14	.731	0.355	0.133	38	0.022	47	0.011	99	0.006	30	0.004	244	0.001	85	0.003	0	0.004	18	0.002	315
DCP15	.800	0.180	0.093	55	0.014	37	0.012	147	0.006	27	0.003	249	0.002	357	0.004	0	0.005	16	0.005	233
DCP16	.900	-0.056	0.098	91	0.009	145	0.003	176	0.006	64	0.003	345	0.009	83	0.003	313	0.005	42	0.007	264
DCP17	.969	-0.058	0.026	168	0.010	228	0.005	154	0.004	158	0.003	183	0.010	33	0.003	120	0.005	16	0.005	175

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	52.81	0.195	0.411	5.62	0.0	7.48	12083.2	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	138.2	49843.	0.65E 07	-0.036	1.192	12.91	-0.00097	1.103	0.0
	(453.4)	(1041.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.478	5.618	0	0.377	3	0.142	339	0.051	271	0.036	75	0.019	54	0.005	160	0.017	303	0.013	114
CN		0.738	0.403	18	0.068	324	0.022	107	0.010	332	0.007	179	0.005	94	0.004	3	0.032	50	0.034	145
CM		-0.001	0.032	282	0.010	46	0.013	263	0.005	125	0.001	335	0.001	324	0.002	244	0.002	208	0.001	21
DCP 1	.010	3.296	2.053	352	0.631	19	0.507	319	0.185	211	0.054	314	0.137	184	0.096	69	0.034	260	0.041	101
DCP 2	.020	2.851	1.708	2	0.426	15	0.240	304	0.118	218	0.073	178	0.080	125	0.055	64	0.054	0	0.047	311
DCP 3	.030	2.746	1.687	0	0.324	358	0.172	286	0.112	188	0.069	120	0.056	66	0.054	332	0.039	253	0.021	207
DCP 4	.049	2.380	1.268	4	0.372	8	0.141	282	0.061	170	0.023	161	0.049	89	0.060	333	0.049	240	0.020	158
DCP 5	.074	2.064	1.068	6	0.261	351	0.106	241	0.066	114	0.015	0	0.025	53	0.048	302	0.052	195	0.032	90
DCP 6	.099	1.861	0.910	8	0.223	342	0.096	216	0.062	95	0.016	310	0.027	86	0.037	304	0.040	197	0.031	96
DCP 7	.149	1.419	0.747	8	0.160	319	0.070	167	0.047	40	0.018	232	0.021	58	0.025	270	0.019	158	0.009	44
DCP 8	.200	1.160	0.655	14	0.130	312	0.058	162	0.028	63	0.009	142	0.016	339	0.029	223	0.020	97	0.006	1
DCP 9	.250	1.018	0.576	12	0.109	291	0.077	121	0.050	6	0.004	188	0.013	321	0.022	187	0.021	52	0.003	281
DCP10	.300	0.878	0.489	15	0.088	289	0.063	113	0.035	356	0.011	194	0.011	298	0.014	191	0.018	49	0.004	290
DCP11	.399	0.715	0.397	26	0.062	291	0.060	107	0.030	339	0.011	208	0.004	337	0.009	130	0.012	25	0.003	167
DCP12	.501	0.534	0.315	34	0.049	293	0.060	96	0.030	327	0.013	211	0.004	142	0.012	82	0.007	353	0.008	160
DCP13	.600	0.425	0.252	47	0.041	297	0.054	90	0.030	318	0.012	172	0.006	121	0.014	60	0.008	343	0.012	166
DCP14	.731	0.369	0.201	46	0.031	311	0.039	78	0.023	294	0.009	178	0.008	193	0.014	67	0.009	353	0.003	145
DCP15	.800	0.187	0.144	68	0.023	263	0.039	66	0.022	269	0.009	123	0.005	171	0.014	26	0.004	37	0.006	179
DCP16	.900	-0.049	0.072	57	0.029	220	0.025	53	0.007	249	0.006	124	0.013	75	0.007	332	0.006	109	0.007	235
DCP17	.969	-0.057	0.017	52	0.020	225	0.012	35	0.009	217	0.005	269	0.012	120	0.007	335	0.001	107	0.001	291

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	52.78	0.197	0.406	5.55	0.0	10.51	12083.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TOR	EXT DAMP
136.7 (448.4)	48996. (1023.3)	0.65E 07	-0.126	1.416	16.01	-0.00053	0.600	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		10.508	5.548 0	0.373 17	0.245 313	0.030 111	0.016 73	0.036 39	0.028 167	0.001 21	0.012 186
CN		0.870	0.454 38	0.094 329	0.012 203	0.025 97	0.013 329	0.007 20	0.011 262	0.008 177	0.003 72
CM		-0.017	0.045 206	0.038 55	0.015 321	0.013 267	0.007 141	0.002 185	0.004 42	0.003 282	0.001 176
DCP 1	.010	3.813	0.862 21	0.985 75	0.371 21	0.141 34	0.088 27	0.045 358	0.030 38	0.012 266	0.017 57
DCP 2	.020	3.211	0.970 39	0.701 59	0.235 10	0.121 22	0.098 1	0.380 330	0.031 294	0.017 257	0.012 13
DCP 3	.030	2.841	0.759 57	0.835 57	0.355 353	0.116 329	0.074 328	0.071 294	0.039 251	0.031 222	0.008 136
DCP 4	.049	2.665	0.882 47	0.569 35	0.152 322	0.056 353	0.046 284	0.023 250	0.006 279	0.020 258	0.014 272
DCP 5	.074	2.287	0.825 49	0.476 23	0.113 309	0.062 336	0.048 252	0.019 204	0.001 170	0.019 227	0.003 175
DCP 6	.099	2.052	0.784 50	0.401 13	0.086 300	0.058 324	0.049 226	0.013 181	0.015 191	0.014 151	0.012 330
DCP 7	.149	1.630	0.788 42	0.325 351	0.082 279	0.060 271	0.059 206	0.022 152	0.012 161	0.018 122	0.008 64
DCP 8	.200	1.350	0.707 44	0.263 349	0.071 286	0.048 256	0.041 202	0.017 190	0.015 154	0.013 169	0.021 89
DCP 9	.250	1.166	0.682 35	0.233 319	0.062 230	0.058 202	0.063 129	0.034 59	0.018 35	0.022 326	0.016 285
DCP10	.300	1.035	0.615 31	0.192 304	0.055 215	0.066 176	0.057 94	0.031 31	0.028 339	0.032 270	0.023 188
DCP11	.399	0.868	0.557 36	0.174 296	0.058 208	0.074 154	0.042 69	0.023 51	0.038 345	0.042 255	0.032 160
DCP12	.501	0.669	0.463 36	0.146 280	0.064 185	0.092 117	0.054 3	0.017 56	0.043 302	0.041 194	0.025 83
DCP13	.600	0.538	0.383 38	0.133 260	0.064 149	0.077 95	0.056 336	0.015 5	0.049 259	0.043 150	0.032 38
DCP14	.701	0.452	0.287 43	0.118 237	0.062 123	0.063 73	0.053 312	0.017 335	0.040 213	0.039 93	0.023 337
DCP15	.800	0.274	0.216 29	0.115 219	0.052 110	0.060 57	0.036 299	0.010 287	0.029 186	0.018 81	0.011 303
DCP16	.900	0.010	0.141 8	0.082 213	0.038 107	0.036 34	0.024 258	0.006 198	0.015 132	0.020 30	0.011 238
DCP17	.969	-0.045	0.045 16	0.029 235	0.017 135	0.019 41	0.013 261	0.002 205	0.016 141	0.013 13	0.005 210

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	52.78	0.197	0.405	5.36	0.0	12.53	12083.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TOR	EXT DAMP
136.1 (446.6)	48737. (1017.9)	0.65E 07	-0.214	1.656	17.50	-0.00057	0.639	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.525	5.359 0	0.379 32	0.303 325	0.058 119	0.022 71	0.030 10	0.037 149	0.012 215	0.019 163
CN		0.992	0.495 46	0.092 353	0.049 299	0.027 184	0.015 106	0.008 70	0.010 27	0.008 310	0.004 201
CM		-0.038	0.084 197	0.043 81	0.023 40	0.017 317	0.008 233	0.002 175	0.004 160	0.005 85	0.004 333
DCP 1	.010	3.973	0.471 110	1.101 92	0.235 95	0.135 76	0.067 156	0.070 95	0.031 20	0.041 261	0.013 215
DCP 2	.020	3.383	0.492 87	0.770 82	0.194 60	0.090 78	0.101 103	0.074 72	0.022 59	0.006 205	0.011 305
DCP 3	.030	2.995	0.715 106	0.874 76	0.253 36	0.115 44	0.083 46	0.055 35	0.022 25	0.005 47	0.010 276
DCP 4	.049	2.825	0.818 82	0.562 53	0.112 31	0.103 11	0.007 349	0.029 29	0.014 330	0.011 311	0.028 226
DCP 5	.074	2.446	0.822 74	0.421 39	0.113 39	0.123 352	0.021 296	0.025 348	0.012 280	0.015 139	0.016 108
DCP 6	.099	2.193	0.804 70	0.341 33	0.126 33	0.104 339	0.019 302	0.005 44	0.023 23	0.006 295	0.009 87
DCP 7	.149	1.766	0.809 55	0.253 9	0.145 5	0.123 301	0.051 254	0.029 214	0.005 185	0.010 101	0.016 316
DCP 8	.200	1.482	0.761 55	0.234 14	0.158 358	0.106 295	0.033 238	0.015 231	0.006 72	0.013 336	0.016 265
DCP 9	.250	1.324	0.699 48	0.203 4	0.177 325	0.114 239	0.041 194	0.022 149	0.019 169	0.028 118	0.016 53
DCP10	.300	1.190	0.638 43	0.175 359	0.170 314	0.103 225	0.040 192	0.030 158	0.032 144	0.038 94	0.028 22
DCP11	.399	1.013	0.600 43	0.130 342	0.138 308	0.097 218	0.054 174	0.034 117	0.031 108	0.046 42	0.026 325
DCP12	.501	0.814	0.566 38	0.129 308	0.116 282	0.105 195	0.067 134	0.035 80	0.044 62	0.051 345	0.033 256
DCP13	.600	0.670	0.523 35	0.154 285	0.098 251	0.100 168	0.067 108	0.037 54	0.049 28	0.055 310	0.033 220
DCP14	.701	0.570	0.433 32	0.170 265	0.105 216	0.096 126	0.057 47	0.026 346	0.034 331	0.041 250	0.027 167
DCP15	.800	0.374	0.368 19	0.171 253	0.116 192	0.102 104	0.063 21	0.032 316	0.034 293	0.038 223	0.029 124
DCP16	.900	0.078	0.229 8	0.090 244	0.071 180	0.054 76	0.040 352	0.012 255	0.017 285	0.024 204	0.025 95
DCP17	.969	-0.017	0.092 7	0.038 267	0.032 183	0.026 83	0.017 14	0.006 205	0.013 312	0.011 248	0.012 147

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	52.80	0.199	0.432	5.38	0.0	15.10	12041.5	32

Y	Q	PN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TR2	EXT AMP
134.9	48038.	0.64E 07	-0.264	1.862	18.62	-0.00101	1.123	0.0
(442.6)	(1003.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		15.095	5.176 0	0.241 40	0.335 22	0.092 165	0.034 230	0.031 80	3.343 247	0.016 30	0.027 192
CN		1.081	0.547 55	0.073 40	0.048 2	0.059 282	0.019 205	0.017 210	0.036 192	0.009 172	0.003 345
CM		-0.061	0.119 198	0.054 123	0.030 103	0.021 49	0.006 339	0.006 21	0.023 302	0.005 289	0.005 177
DCP 1	.010	3.913	1.475 160	0.721 120	0.199 166	0.073 294	0.118 218	0.024 67	0.027 219	0.034 259	0.020 253
DCP 2	.020	3.448	1.037 132	0.599 128	0.221 120	0.066 177	0.145 198	0.070 173	0.055 253	0.040 260	0.076 298
DCP 3	.030	2.993	1.154 138	0.561 103	0.318 128	0.136 84	0.116 166	0.101 119	0.046 161	0.032 139	0.040 224
DCP 4	.040	2.889	1.002 108	0.280 87	0.242 105	0.045 53	0.057 137	0.035 92	0.009 141	0.017 298	0.044 231
DCP 5	.074	2.517	0.950 95	0.204 77	0.233 46	0.048 73	0.046 112	0.018 129	0.037 145	0.015 117	0.034 141
DCP 6	.099	2.266	0.904 87	0.182 70	0.238 68	0.041 0	0.025 89	0.042 123	0.025 96	0.012 248	0.030 147
DCP 7	.149	1.851	0.835 71	0.196 81	0.274 40	0.071 336	0.071 351	0.016 26	0.017 313	0.017 296	0.012 175
DCP 8	.200	1.582	0.796 67	0.205 71	0.265 33	0.097 347	0.026 349	0.043 35	0.029 337	0.000 263	0.013 74
DCP 9	.250	1.472	0.765 58	0.183 65	0.267 21	0.137 332	0.059 294	0.031 308	0.039 308	0.036 275	0.036 262
DCP10	.300	1.282	0.699 59	0.171 58	0.241 9	0.138 318	0.068 274	0.041 258	0.019 266	0.033 258	0.019 253
DCP11	.399	1.128	0.695 50	0.119 53	0.203 14	0.157 326	0.070 273	0.052 276	0.033 265	0.038 258	0.011 217
DCP12	.501	0.922	0.461 43	0.091 15	0.161 349	0.143 292	0.052 240	0.064 243	0.042 200	0.046 185	0.029 122
DCP13	.600	0.776	0.640 37	0.106 327	0.141 315	0.138 259	0.054 201	0.068 212	0.044 165	0.052 147	0.041 67
DCP14	.701	0.677	0.570 33	0.142 306	0.168 279	0.133 225	0.062 157	0.054 168	0.037 117	0.045 104	0.033 358
DCP15	.800	0.469	0.496 22	0.153 303	0.153 256	0.119 230	0.063 129	0.034 117	0.021 65	0.033 70	0.035 333
DCP16	.900	0.152	0.298 12	0.099 288	0.070 235	0.065 180	0.034 79	0.011 147	0.017 45	0.019 23	0.026 306
DCP17	.969	0.028	0.142 12	0.065 291	0.041 271	0.050 161	0.028 79	0.015 340	0.013 308	0.014 106	0.002 309

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	53.38	0.192	0.419	5.68	0.0	4.96	12085.1	70

Y	Q	PN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TR2	EXT DAMP
141.8	51921.	0.66E 07	-0.038	0.951	10.50	-0.00076	0.492	0.0
(465.1)	(1084.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.960	5.478 0	0.345 3	0.173 350	0.030 200	0.024 62	0.012 26	0.020 14	0.017 255	0.013 111
CN		0.568	0.397 1	0.027 17	0.012 22	0.001 9	0.001 240	0.002 287	0.002 297	0.003 5	0.031 98
CM		-0.037	0.074 298	0.003 254	0.002 325	0.001 211	0.000 128	0.001 131	0.001 152	0.001 206	0.000 285
DCP 1	.010	2.534	1.059 342	0.250 276	0.034 25	0.027 238	0.068 98	0.034 249	0.007 273	0.017 282	0.009 268
DCP 2	.020	1.964	1.105 349	0.129 9	0.072 353	0.027 68	0.045 322	2.054 217	0.037 132	0.016 6	0.036 346
DCP 3	.030	1.912	1.011 344	0.110 11	0.043 351	0.016 226	0.013 135	0.003 34	0.004 211	0.005 298	0.001 115
DCP 4	.049	1.793	1.531 349	0.091 5	0.070 349	0.017 215	0.008 147	0.004 132	0.036 212	0.004 242	0.002 127
DCP 5	.074	1.570	1.218 350	0.073 1	0.048 353	0.009 234	0.002 135	0.007 83	0.004 263	0.002 92	0.002 70
DCP 6	.099	1.435	1.210 352	0.060 7	0.039 358	0.008 215	0.002 285	0.003 149	0.001 219	0.002 315	0.002 27
DCP 7	.149	1.060	0.759 351	0.043 6	0.031 6	0.007 184	0.003 253	0.005 287	0.007 169	0.036 233	0.003 138
DCP 8	.200	0.861	0.616 0	0.039 22	0.019 36	0.003 319	0.003 351	0.005 145	0.006 289	0.007 347	0.032 49
DCP 9	.250	0.759	0.514 359	0.034 11	0.031 34	0.004 33	0.001 142	0.008 217	0.006 294	0.002 237	0.001 284
DCP10	.300	0.662	0.497 2	0.031 19	0.017 16	0.006 353	0.005 272	0.003 242	0.005 166	0.002 312	0.001 236
DCP11	.399	0.544	0.347 11	0.028 38	0.012 45	0.003 358	0.002 317	0.036 312	0.005 307	0.007 17	0.001 244
DCP12	.501	0.425	0.264 19	0.025 39	0.011 71	0.003 64	0.002 315	0.004 324	0.006 309	0.008 27	0.034 89
DCP13	.600	0.363	0.200 28	0.023 40	0.009 83	0.004 44	0.002 39	0.005 301	0.036 347	0.004 20	0.005 147
DCP14	.701	0.346	0.142 39	0.010 47	0.007 132	0.002 17	0.005 4	0.004 319	0.005 349	0.006 359	0.003 27
DCP15	.800	0.174	0.093 53	0.015 50	0.036 157	0.003 30	0.001 139	0.002 119	0.031 12	0.002 35	0.032 48
DCP16	.900	-0.054	0.040 73	0.005 58	0.033 238	0.003 40	0.004 240	0.004 311	0.003 296	0.003 212	0.004 144
DCP17	.969	-0.061	0.019 145	0.006 329	0.005 144	0.006 21	0.002 339	0.004 275	0.001 274	0.005 34	0.005 277

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	53.85	0.196	0.415	5.67	0.0	7.47	12085.2	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TOR	EXT DAMP
	139.8	50988.	0.66E 07	-0.039	1.172	13.11	-0.00096	1.193	0.0
	(458.6)	(1064.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.474	5.671 0	0.367 6	0.152 319	0.029 229	0.031 61	0.028 55	0.015 161	0.013 290	0.016 149
CN		0.718	0.405 19	0.066 325	0.024 115	0.009 328	0.006 177	0.002 110	0.004 333	0.001 172	0.005 115
CM		-0.002	0.032 279	0.009 43	0.013 272	0.004 116	0.001 332	0.001 16	0.001 207	0.001 202	0.001 352
DCP 1	.010	2.793	1.940 353	0.654 39	0.566 317	0.216 214	0.017 325	0.110 175	0.077 65	0.043 245	0.052 110
DCP 2	.020	2.774	1.765 2	0.421 16	0.243 303	0.110 214	0.054 171	0.060 116	0.046 54	0.051 356	0.044 316
DCP 3	.030	2.684	1.660 3	0.311 359	0.170 287	0.105 191	0.065 116	0.055 54	0.053 337	0.040 259	0.017 251
DCP 4	.049	2.374	1.354 4	0.317 6	0.144 279	0.055 159	0.015 191	0.063 94	0.058 334	0.048 241	0.009 169
DCP 5	.074	2.025	1.066 8	0.258 350	0.108 253	0.058 120	0.009 31	0.021 38	0.048 295	0.044 195	0.025 86
DCP 6	.099	1.833	0.839 8	0.214 338	0.074 213	0.050 81	0.022 290	0.008 81	0.037 276	0.043 178	0.030 84
DCP 7	.149	1.391	0.788 8	0.160 313	0.079 159	0.050 41	0.012 232	0.017 29	0.028 269	0.019 167	0.010 61
DCP 8	.200	1.134	0.665 14	0.126 309	0.066 160	0.019 38	0.005 309	0.017 349	0.024 231	0.016 108	0.008 36
DCP 9	.249	0.983	0.571 13	0.108 295	0.075 127	0.040 13	0.005 178	0.017 306	0.024 187	0.019 68	0.007 59
DCP10	.300	0.856	0.491 14	0.077 284	0.067 106	0.036 347	0.011 177	0.009 298	0.014 147	0.012 56	0.006 34
DCP11	.399	0.604	0.398 28	0.059 298	0.061 118	0.028 354	0.008 221	0.007 220	0.014 115	0.013 16	0.009 170
DCP12	.501	0.574	0.321 34	0.045 280	0.043 101	0.029 320	0.011 208	0.006 232	0.014 82	0.009 323	0.009 149
DCP13	.600	0.416	0.262 47	0.039 303	0.051 96	0.024 304	0.010 154	0.006 244	0.012 39	0.004 330	0.006 127
DCP14	.701	0.368	0.237 65	0.032 315	0.047 92	0.023 277	0.015 137	0.005 152	0.011 355	0.005 246	0.004 136
DCP15	.800	0.154	0.149 66	0.018 262	0.038 93	0.021 260	0.006 125	0.008 154	0.015 352	0.001 302	0.003 107
DCP16	.900	-0.040	0.070 49	0.027 207	0.024 56	0.008 211	0.001 351	0.010 193	0.036 292	0.005 90	0.005 189
DCP17	.969	-0.057	0.025 53	0.016 235	0.012 44	0.005 190	0.002 233	0.003 267	0.009 300	0.002 192	0.008 190

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	51.94	0.199	0.411	5.57	0.0	10.13	12085.3	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TOR	EXT DAMP
	138.3	50068.	0.65E 07	-0.133	1.418	15.70	-0.00054	0.618	0.0
	(453.7)	(1045.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		10.127	5.573 0	0.428 16	0.325 298	0.025 28	0.034 68	0.021 15	0.031 105	0.012 78	0.010 206
CN		0.845	0.459 36	0.099 324	0.019 220	0.027 99	0.009 338	0.011 339	0.008 233	0.008 163	0.000 239
CM		-0.019	0.065 239	0.008 54	0.017 315	0.012 260	0.007 149	0.004 113	0.005 26	0.004 298	0.002 211
DCP 1	.010	3.173	0.916 16	0.989 71	0.398 4	0.139 22	0.093 355	0.070 325	0.017 9	0.008 194	0.009 334
DCP 2	.020	3.090	1.027 32	0.874 56	0.243 0	0.141 14	0.097 332	0.073 301	0.011 253	0.009 327	0.028 327
DCP 3	.030	2.711	1.807 58	0.777 58	0.353 303	0.098 306	0.052 300	0.067 271	0.032 182	0.006 186	0.007 302
DCP 4	.049	2.533	1.887 61	0.555 34	0.183 314	0.054 342	0.054 263	0.020 219	0.010 64	0.016 287	0.027 268
DCP 5	.074	2.232	0.842 52	0.464 19	0.151 292	0.027 321	0.043 226	0.003 74	0.011 306	0.020 204	0.011 220
DCP 6	.099	2.003	0.798 45	0.402 0	0.116 287	0.061 317	0.062 216	0.023 92	0.015 316	0.025 224	0.021 194
DCP 7	.149	1.566	0.703 39	0.335 346	0.101 267	0.051 265	0.058 191	0.020 145	0.031 134	0.016 80	0.008 27
DCP 8	.200	1.295	0.698 34	0.239 343	0.070 260	0.037 236	0.037 179	0.017 129	0.020 105	0.007 6	0.007 160
DCP 9	.250	1.146	0.681 34	0.248 318	0.086 232	0.060 175	0.052 120	0.032 59	0.023 19	0.015 335	0.016 299
DCP10	.300	1.015	0.614 32	0.208 334	0.078 217	0.068 156	0.047 91	0.034 37	0.026 1	0.024 291	0.020 231
DCP11	.399	0.852	0.555 35	0.166 297	0.063 215	0.077 153	0.042 82	0.035 37	0.030 336	0.029 255	0.023 264
DCP12	.501	0.643	0.460 36	0.145 279	0.061 189	0.080 121	0.053 28	0.036 346	0.039 273	0.031 197	0.018 139
DCP13	.600	0.530	0.386 37	0.133 261	0.066 154	0.073 94	0.048 353	0.037 325	0.034 251	0.045 168	0.028 71
DCP14	.701	0.446	0.284 42	0.121 236	0.069 115	0.065 62	0.046 304	0.022 297	0.037 206	0.031 110	0.019 12
DCP15	.800	0.267	0.217 28	0.124 219	0.069 101	0.050 51	0.038 303	0.024 267	0.033 170	0.025 82	0.009 2
DCP16	.900	0.019	0.136 16	0.079 221	0.039 118	0.043 28	0.030 277	0.021 211	0.018 135	0.015 73	0.010 297
DCP17	.969	-0.038	0.062 5	0.038 232	0.027 137	0.028 48	0.019 292	0.015 231	0.018 170	0.018 63	0.004 341

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	53.93	0.200	0.409	5.47	0.0	12.28	12085.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
137.4	49561.	0.65E 07	-0.227	1.688	17.48	-0.00042	0.477	0.0
(450.8)	(1035.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		12.278	5.470	0	0.454	26	0.381	323	0.062	108	0.050	98	0.037	355	0.047	133	0.025	195	0.015	180
CN		0.979	0.497	43	0.091	358	0.071	294	0.040	188	0.020	124	0.013	60	0.010	29	0.007	289	0.003	173
CM		-0.041	0.086	196	0.047	77	0.028	36	0.021	312	0.007	252	0.006	241	0.007	171	0.005	94	0.003	7
DCP 1	.010	3.442	0.392	117	1.229	87	0.274	77	0.112	53	0.182	147	0.090	46	0.042	215	0.083	136	0.036	62
DCP 2	.020	3.256	0.667	90	0.890	81	0.279	50	0.104	43	0.140	90	0.125	41	0.031	49	0.082	127	0.065	69
DCP 3	.030	3.013	0.658	93	0.898	75	0.294	24	0.096	27	0.121	50	0.113	7	0.060	0	0.024	26	0.047	4
DCP 4	.049	2.810	0.791	73	0.567	54	0.132	25	0.101	8	0.051	37	0.066	343	0.010	47	0.014	30	0.018	354
DCP 5	.074	2.426	0.774	67	0.427	41	0.122	14	0.091	340	0.031	12	0.058	321	0.004	310	0.016	312	0.017	326
DCP 6	.099	2.178	0.768	63	0.342	35	0.150	17	0.108	317	0.020	344	0.061	310	0.020	245	0.013	271	0.015	322
DCP 7	.149	1.738	0.776	52	0.291	16	0.172	348	0.118	283	0.032	263	0.041	258	0.023	232	0.019	194	0.012	220
DCP 8	.200	1.446	0.711	54	0.252	23	0.186	337	0.096	260	0.030	273	0.020	236	0.027	273	0.029	201	0.006	194
DCP 9	.250	1.306	0.701	47	0.229	10	0.236	321	0.144	245	0.062	214	0.025	193	0.046	183	0.033	130	0.017	92
DCP10	.300	1.159	0.636	43	0.184	3	0.211	311	0.140	226	0.063	189	0.032	166	0.055	142	0.028	80	0.019	60
DCP11	.399	1.002	0.618	42	0.129	350	0.185	312	0.140	229	0.071	183	0.043	163	0.059	131	0.033	53	0.015	86
DCP12	.501	0.813	0.572	36	0.121	313	0.149	283	0.111	196	0.070	158	0.058	112	0.051	67	0.040	349	0.014	319
DCP13	.600	0.675	0.534	32	0.153	282	0.136	249	0.117	160	0.062	126	0.066	89	0.075	35	0.065	315	0.037	265
DCP14	.701	0.573	0.454	29	0.190	261	0.133	214	0.122	128	0.065	74	0.055	37	0.059	344	0.051	265	0.028	196
DCP15	.800	0.369	0.375	19	0.188	252	0.150	191	0.130	102	0.071	32	0.041	342	0.042	308	0.032	212	0.020	129
DCP16	.900	0.092	0.240	3	0.114	239	0.094	171	0.067	76	0.031	6	0.019	357	0.034	301	0.024	209	0.019	153
DCP17	.969	-0.006	0.102	2	0.050	253	0.042	176	0.038	77	0.026	6	0.006	324	0.018	265	0.003	80	0.006	202

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	53.73	0.201	0.406	5.44	0.0	15.08	12085.5	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
136.1	48809.	0.65E 07	-0.262	1.833	19.03	-0.00081	0.906	0.0
(446.6)	(1019.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		15.082	5.438	0	0.303	36	0.328	15	0.083	172	0.029	199	0.045	69	0.053	246	0.009	334	0.020	186
CN		1.063	0.526	55	0.076	37	0.081	358	0.067	283	0.019	199	0.010	211	0.016	201	0.011	118	0.005	307
CM		-0.049	0.115	197	0.034	124	0.031	97	0.022	50	0.007	317	0.005	22	0.004	331	0.037	258	0.005	171
DCP 1	.010	3.679	1.487	156	0.690	117	0.248	167	0.107	265	0.107	213	0.024	336	0.031	321	0.051	276	0.025	315
DCP 2	.020	3.385	1.025	132	0.562	109	0.223	132	0.099	188	0.166	202	0.060	188	0.080	279	0.054	284	0.049	314
DCP 3	.030	2.967	1.135	136	0.562	105	0.342	126	0.144	87	0.115	178	0.108	127	0.048	191	0.044	274	0.043	229
DCP 4	.049	2.865	0.985	105	0.250	84	0.251	103	0.069	44	0.020	155	0.050	128	0.005	188	0.022	270	0.042	223
DCP 5	.074	2.404	0.936	94	0.209	77	0.260	79	0.060	0	0.041	118	0.048	91	0.015	107	0.019	113	0.034	187
DCP 6	.099	2.240	0.874	88	0.184	87	0.248	69	0.070	344	0.026	117	0.045	104	0.009	82	0.016	171	0.040	178
DCP 7	.149	1.926	0.802	71	0.182	79	0.281	41	0.084	330	0.029	352	0.042	57	0.042	324	0.026	248	0.020	157
DCP 8	.200	1.566	0.767	68	0.203	71	0.251	35	0.105	346	0.032	324	0.043	11	0.036	301	0.016	259	0.013	240
DCP 9	.250	1.403	0.739	59	0.709	60	0.259	12	0.134	319	0.057	291	0.028	315	0.036	285	0.014	253	0.014	329
DCP10	.300	1.262	0.673	53	0.182	57	0.221	5	0.136	319	0.049	279	0.035	337	0.035	252	0.014	199	0.019	271
DCP11	.399	1.117	0.684	49	0.127	45	0.194	0	0.166	323	0.065	272	0.056	298	0.052	231	0.011	215	0.020	241
DCP12	.501	0.915	0.647	41	0.101	4	0.154	347	0.155	297	0.067	232	0.060	245	0.055	191	0.021	185	0.023	133
DCP13	.600	0.773	0.631	36	0.118	330	0.147	311	0.144	266	0.053	213	0.066	216	0.051	180	0.049	132	0.034	68
DCP14	.701	0.655	0.547	30	0.138	305	0.160	274	0.134	229	0.072	149	0.059	164	0.036	117	0.054	94	0.040	1
DCP15	.800	0.452	0.457	20	0.151	297	0.159	249	0.124	200	0.069	118	0.030	113	0.017	97	0.037	64	0.030	331
DCP16	.900	0.146	0.299	8	0.094	290	0.090	231	0.078	175	0.042	82	0.009	133	0.034	105	0.041	23	0.031	295
DCP17	.969	0.021	0.141	14	0.062	297	0.051	234	0.049	166	0.037	71	0.008	18	0.009	195	0.010	48	0.005	17

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	58.53	0.252	0.409	5.75	0.0	1.33	12081.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
138.4	49398.	0.65E 07	-0.053	0.592	6.95	-0.03386	0.767	0.0
(454.0)	(1031.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		1.000	5.750 0	0.478 356	0.148 227	0.096 129	0.035 267	0.043 47	0.028 196	0.014 43	0.016 167
CN		0.167	0.416 6	0.035 20	0.011 275	0.004 165	0.005 273	0.003 159	0.003 21	0.001 72	0.001 184
CM		-0.018	0.029 286	0.006 294	0.003 134	0.001 112	0.001 111	0.001 213	0.001 22	0.000 167	0.001 20
DCP 1	.013	-0.529	2.933 343	0.343 1	0.095 124	0.023 156	0.024 165	0.023 199	0.012 241	0.008 177	0.003 353
DCP 2	.020	-0.184	2.098 352	0.184 333	0.038 235	0.002 215	0.011 296	0.039 189	0.037 22	0.005 209	0.006 269
DCP 3	.030	0.099	1.792 351	0.124 330	0.028 217	0.017 134	0.023 249	0.034 295	0.013 19	0.008 71	0.003 274
DCP 4	.049	0.270	1.464 353	0.122 337	0.034 232	0.018 173	0.014 216	0.038 301	0.005 19	0.010 102	0.007 312
DCP 5	.074	0.404	1.188 354	0.100 345	0.030 228	0.021 161	0.004 188	0.005 136	0.004 31	0.011 34	0.004 5
DCP 6	.099	0.426	1.328 356	0.085 355	0.013 232	0.023 153	0.001 203	0.002 232	0.007 21	0.006 147	0.006 92
DCP 7	.149	0.309	3.773 358	0.072 0	0.012 254	0.016 149	0.004 294	0.034 285	0.004 21	0.005 218	0.011 215
DCP 8	.200	0.252	0.633 4	0.050 25	0.013 252	0.002 123	0.012 282	0.031 173	0.035 41	0.031 345	0.011 213
DCP 9	.250	0.335	3.550 4	0.057 13	0.012 266	0.005 207	0.008 274	0.036 117	0.037 11	0.004 118	0.005 123
DCP10	.300	0.232	0.488 6	0.050 14	0.016 271	0.006 168	0.007 294	0.001 95	0.003 19	0.002 255	0.006 69
DCP11	.399	0.208	0.382 20	0.040 40	0.018 297	0.036 191	0.036 289	0.032 223	0.025 189	0.011 151	0.007 114
DCP12	.501	0.158	0.303 26	0.034 44	0.017 287	0.035 297	0.011 277	0.035 232	0.005 19	0.006 9	0.003 124
DCP13	.600	0.170	0.244 34	0.030 70	0.013 295	0.039 274	0.007 299	0.004 257	0.003 19	0.007 346	0.000 292
DCP14	.701	0.215	0.177 37	0.023 74	0.010 283	0.033 248	0.033 262	0.034 84	0.032 19	0.005 344	0.006 231
DCP15	.800	0.109	0.117 47	0.017 130	0.012 315	0.002 324	0.003 146	0.035 19	0.003 173	0.002 340	0.006 212
DCP16	.900	-0.065	0.054 61	0.017 133	0.009 338	0.004 90	0.003 313	0.009 73	0.035 244	0.030 282	0.037 196
DCP17	.969	-0.036	0.329 183	0.003 138	0.008 294	0.035 243	0.001 210	0.036 323	0.037 322	0.006 150	0.005 235

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	69.72	0.259	0.406	5.93	0.0	2.45	12081.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
137.0	48718.	0.64E 07	-0.051	0.785	8.72	-0.03371	0.815	0.0
(449.6)	(1017.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.456	5.933 3	0.508 340	0.123 231	0.053 133	0.027 333	0.023 88	0.014 175	0.006 86	0.007 214
CN		0.370	0.412 5	0.035 11	0.008 283	0.001 116	0.003 317	0.005 163	0.002 193	0.001 61	0.000 139
CM		-0.011	0.035 295	0.006 279	0.002 151	0.031 187	0.031 174	0.031 8	0.031 3	0.033 325	0.003 352
DCP 1	.010	1.002	2.881 341	0.226 322	0.046 152	0.024 72	0.028 243	0.013 97	0.005 63	0.030 1	0.011 263
DCP 2	.020	3.893	2.248 349	0.171 332	0.326 235	0.039 136	0.016 270	0.012 148	0.003 6	0.004 41	0.006 307
DCP 3	.030	3.982	1.913 348	0.140 331	0.025 259	0.006 115	0.013 269	0.011 123	0.005 63	0.001 336	0.002 36
DCP 4	.049	1.025	1.584 350	0.129 329	0.023 218	0.011 161	0.005 254	0.007 99	0.007 194	0.004 289	0.005 1
DCP 5	.074	1.023	1.259 350	0.103 335	0.013 234	0.008 117	0.008 246	0.013 76	0.036 154	0.004 43	0.000 159
DCP 6	.099	0.948	1.067 353	0.093 347	0.018 263	0.009 142	0.005 257	0.009 72	0.034 149	0.001 279	0.005 34
DCP 7	.149	0.692	0.786 356	0.072 353	0.013 230	0.005 125	0.001 266	0.008 99	0.032 11	0.002 68	0.004 359
DCP 8	.200	0.562	3.651 4	0.058 5	0.011 278	0.006 239	0.005 316	0.013 208	0.013 154	0.005 139	0.004 163
DCP 9	.250	0.592	0.549 3	0.056 0	0.015 260	0.002 179	0.006 285	0.005 166	0.006 84	0.005 330	0.005 45
DCP10	.300	0.449	3.459 4	0.047 16	0.008 287	0.002 159	0.001 294	0.036 114	0.032 74	0.004 28	0.002 74
DCP11	.399	0.376	3.371 21	0.041 38	0.007 290	0.003 296	0.009 359	0.007 209	0.034 186	0.004 32	0.005 196
DCP12	.501	0.283	0.290 27	0.041 37	0.010 295	0.007 231	0.003 11	0.005 198	0.032 113	0.034 189	0.004 356
DCP13	.630	0.263	3.231 36	0.032 59	0.013 310	0.303 88	0.007 345	0.009 163	0.033 42	0.001 124	0.003 227
DCP14	.701	0.280	0.160 45	0.025 63	0.012 315	0.007 37	0.004 31	0.007 151	0.004 173	0.002 15	0.002 102
DCP15	.800	0.143	0.113 60	0.016 81	0.306 318	0.333 13	0.005 319	0.004 158	0.036 244	0.036 245	0.002 88
DCP16	.900	-0.070	0.050 87	0.015 124	0.005 287	0.001 335	0.008 192	0.013 217	0.036 154	0.007 125	0.005 197
DCP17	.969	-0.053	0.029 157	0.002 151	0.011 43	0.003 89	0.004 351	0.003 136	0.004 153	0.002 281	0.002 164

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	69.83	0.261	0.404	5.90	0.0	4.96	12031.0	20

	V	Q	RN	CNMINI	CNMAXI	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	136.3	48354.	0.64E 07	-0.044	1.027	11.01	-0.00077	0.081	0.0
	(447.2)	(1009.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.956	5.904 0	0.498 343	0.096 208	0.022 127	0.001 157	0.021 105	0.016 159	0.006 341	0.009 97
CN		0.613	0.438 6	0.042 12	0.037 273	0.033 261	0.003 238	0.034 248	0.032 61	0.051 37	0.032 94
CM		-0.005	0.038 246	0.006 250	0.002 150	0.001 205	0.001 83	0.002 88	0.001 61	0.000 351	0.001 272
DCP 1	.010	2.828	3.189 342	0.341 277	0.398 155	0.051 191	0.082 111	0.361 26	0.027 159	0.379 343	0.014 198
DCP 2	.023	2.144	2.244 349	0.192 329	0.051 231	0.367 66	0.082 338	0.058 242	0.043 111	0.048 49	0.014 60
DCP 3	.030	2.040	1.877 349	0.145 350	0.024 330	0.023 235	0.019 169	0.009 98	0.002 144	0.007 327	0.004 166
DCP 4	.049	1.937	1.565 353	0.126 348	0.034 333	0.317 225	0.012 150	0.034 136	0.031 159	0.003 355	0.001 233
DCP 5	.074	1.741	1.233 352	0.087 354	0.018 276	0.024 208	0.017 196	0.010 217	0.012 179	0.005 20	0.008 25
DCP 6	.099	1.550	1.042 354	0.091 354	0.012 266	0.034 231	0.031 98	0.036 143	0.031 159	0.031 70	0.001 34
DCP 7	.149	1.144	0.773 356	0.068 357	0.010 257	0.033 313	0.009 249	0.012 200	0.032 179	0.004 87	0.009 259
DCP 8	.200	0.932	0.641 6	0.068 8	0.011 263	0.005 209	0.004 336	0.005 139	0.001 159	0.003 299	0.003 229
DCP 9	.250	0.900	0.543 6	0.058 359	0.015 216	0.034 308	0.036 234	0.034 155	0.035 159	0.036 283	0.032 293
DCP13	.333	0.713	0.449 7	0.056 11	0.010 230	0.004 139	0.005 180	0.005 242	0.033 359	0.005 328	0.001 211
DCP11	.399	0.586	0.360 22	0.051 34	0.010 262	0.034 273	0.004 256	0.006 233	0.002 159	0.006 20	0.007 95
DCP12	.501	0.441	0.290 33	0.045 37	0.007 333	0.033 22	0.036 265	0.013 239	0.037 159	0.005 154	0.002 305
DCP13	.603	0.379	0.230 41	0.036 49	0.010 334	0.006 338	0.002 222	0.008 278	0.035 17	0.006 200	0.006 51
DCP14	.701	0.355	0.184 54	0.034 44	0.008 281	0.032 49	0.005 209	0.039 302	0.038 159	0.034 217	0.008 129
DCP15	.833	0.179	0.123 67	0.023 56	0.008 316	0.034 74	0.004 256	0.033 276	0.035 56	0.005 143	0.013 84
DCP16	.900	-0.052	0.058 86	0.009 43	0.005 331	0.003 60	0.008 307	0.005 279	0.007 159	0.002 351	0.003 94
DCP17	.969	-0.062	0.024 153	0.008 18	0.005 33	0.003 13	0.005 221	0.037 172	0.034 179	0.034 29	0.007 265

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	69.74	0.262	0.402	5.88	0.0	7.44	12031.4	20

	V	Q	RN	CNMINI	CNMAXI	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	135.4	47895.	0.64E 07	-0.046	1.292	13.32	-0.00386	0.474	0.0
	(444.4)	(1000.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.439	5.883 0	0.579 345	0.089 159	0.026 163	0.022 164	0.033 106	0.017 159	0.011 162	0.009 26
CN		0.778	0.451 20	0.056 323	0.010 86	0.012 263	0.008 182	0.036 75	0.038 159	0.007 331	0.000 70
CM		-0.001	0.040 278	0.012 10	0.011 232	0.006 97	0.001 10	0.032 167	0.003 71	0.001 276	0.000 172
DCP 1	.013	3.418	1.989 353	0.078 27	0.031 298	0.255 186	0.087 309	0.162 183	0.111 72	0.032 228	0.059 76
DCP 2	.020	2.883	1.800 3	0.575 14	0.332 280	0.157 201	0.066 178	0.103 150	0.061 92	0.064 43	0.060 11
DCP 3	.030	2.787	1.716 1	0.418 358	0.242 272	0.168 184	0.094 121	0.074 86	0.069 66	0.068 319	0.053 252
DCP 4	.049	2.551	1.531 2	0.323 340	0.135 230	0.371 120	0.011 215	0.056 106	0.053 304	0.043 262	0.014 176
DCP 5	.074	2.257	1.246 3	0.257 332	0.107 214	0.052 108	0.017 166	0.055 67	0.057 324	0.043 226	0.012 123
DCP 6	.099	1.980	1.345 7	0.221 329	0.096 198	0.052 87	0.013 243	0.035 78	0.043 34	0.031 226	0.007 159
DCP 7	.149	1.476	0.837 8	0.162 318	0.070 174	0.027 75	0.012 139	0.025 19	0.047 159	0.021 151	0.008 90
DCP 8	.200	1.217	0.718 15	0.133 310	0.072 166	0.030 41	0.015 177	0.017 353	0.032 63	0.019 179	0.008 87
DCP 9	.253	1.163	0.649 12	0.133 278	0.076 112	0.032 337	0.009 167	0.024 286	0.031 47	0.019 34	0.007 316
DCP10	.300	0.920	0.541 14	0.069 267	0.059 89	0.040 309	0.018 174	0.010 209	0.010 155	0.011 279	0.003 183
DCP11	.399	0.750	0.455 29	0.053 269	0.057 93	0.043 329	0.019 247	0.013 239	0.015 65	0.013 4	0.009 220
DCP12	.501	0.553	0.384 37	0.092 262	0.051 72	0.044 287	0.013 172	0.004 91	0.011 159	0.005 198	0.004 256
DCP13	.600	0.443	0.301 49	0.017 276	0.040 56	0.031 269	0.005 157	0.001 37	0.013 159	0.005 211	0.003 284
DCP14	.701	0.371	0.263 65	0.016 279	0.040 46	0.033 257	0.037 124	0.008 38	0.019 159	0.007 138	0.009 13
DCP15	.800	0.193	0.191 71	0.017 213	0.035 20	0.020 212	0.003 315	0.009 64	0.015 159	0.002 68	0.004 261
DCP16	.900	-0.032	0.081 54	0.035 173	0.027 355	0.010 210	0.006 156	0.007 13	0.013 159	0.032 91	0.006 73
DCP17	.969	-0.064	0.019 78	0.016 173	0.015 10	0.033 201	0.004 276	0.015 355	0.014 159	0.004 282	0.004 112

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	0.0	69.56	0.262	0.402	5.78	0.0	9.92	12031.5	28

	V	Q	RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	135.3	47837.	0.64E 07	-0.156	1.515	15.91	-0.00028	0.314	0.0
	(443.9)	(999.1)			HARMONIC ANALYSIS				

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		9.918	5.780 0	0.775 347	0.117 126	0.035 159	0.042 171	0.019 61	0.019 16	0.014 179	0.011 54
CN		0.897	0.538 31	0.109 304	0.045 156	0.029 28	0.018 274	0.018 231	0.014 91	0.002 310	0.005 83
CM		-0.019	0.048 236	0.047 29	0.025 289	0.015 184	0.006 90	0.007 35	0.013 251	0.004 110	0.002 261
DCP 1	.010	3.001	1.268 17	1.043 44	0.434 340	0.071 15	0.126 342	0.036 345	0.103 331	0.101 281	0.071 215
DCP 2	.020	3.108	1.123 32	0.883 42	0.379 345	0.163 312	0.123 279	0.063 237	0.047 299	0.068 276	0.084 239
DCP 3	.030	2.814	1.014 42	0.907 31	0.356 317	0.074 297	0.173 279	0.152 208	0.043 166	0.052 195	0.074 137
DCP 4	.049	2.673	1.097 33	0.624 15	0.158 330	0.356 311	0.123 244	0.369 165	0.026 251	0.070 163	0.052 92
DCP 5	.074	2.355	1.007 37	0.562 2	0.149 273	0.051 275	0.114 212	0.063 143	0.025 171	0.072 104	0.052 14
DCP 6	.099	2.101	0.978 37	0.482 351	0.131 250	0.046 275	0.111 199	0.059 125	0.018 116	0.047 77	0.024 7
DCP 7	.149	1.633	0.891 31	0.347 329	0.103 214	0.349 239	0.071 138	0.025 34	0.028 16	0.028 21	0.011 247
DCP 8	.200	1.378	0.845 34	0.301 324	0.108 217	0.061 198	0.066 134	0.033 47	0.031 16	0.027 323	0.016 261
DCP 9	.250	1.319	0.806 27	0.273 299	0.116 189	0.081 144	0.070 58	0.033 333	0.030 361	0.027 232	0.019 183
DCP13	.333	1.093	0.741 24	0.245 285	0.116 183	0.385 125	0.061 37	0.037 334	0.045 271	0.022 170	0.004 122
DCP11	.399	0.913	0.642 32	0.209 282	0.136 189	0.103 102	0.063 10	0.042 320	0.051 269	0.035 146	0.012 60
DCP12	.501	0.693	0.533 32	0.174 257	0.135 152	0.135 58	0.072 325	0.063 269	0.038 171	0.049 72	0.017 352
DCP13	.600	0.555	0.433 35	0.156 236	0.124 126	0.133 26	0.059 293	0.065 245	0.077 161	0.041 10	0.007 27
DCP14	.701	0.464	0.339 37	0.157 213	0.112 98	0.089 357	0.057 256	0.051 208	0.063 41	0.047 314	0.015 177
DCP15	.800	0.283	0.236 23	0.161 189	0.098 73	0.079 329	0.043 221	0.044 179	0.061 51	0.038 263	0.014 137
DCP16	.900	0.014	0.141 10	0.104 188	0.062 72	0.073 316	0.037 205	0.035 133	0.041 43	0.032 227	0.024 65
DCP17	.969	-0.037	0.050 356	0.044 202	0.036 84	0.036 329	0.016 217	0.015 169	0.027 46	0.019 264	0.006 105

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	0.0	68.60	0.252	0.409	5.66	0.0	12.39	12033.1	20

	V	Q	RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	138.5	49527.	0.65E 07	-0.259	1.754	18.37	0.00024	-0.276	0.3
	(454.3)	(1034.4)			HARMONIC ANALYSIS				

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.387	5.656 0	0.853 356	0.120 162	0.042 131	0.042 191	0.029 29	0.016 201	0.014 146	0.004 177
CN		1.055	0.541 35	0.104 332	0.045 214	0.315 114	0.011 134	0.024 23	0.015 63	0.003 142	0.007 4
CM		-0.057	0.105 183	0.066 48	0.030 331	0.012 224	0.003 269	0.010 171	0.011 56	0.004 292	0.002 201
DCP 1	.010	3.989	3.694 141	1.514 83	0.137 7	0.234 85	0.063 42	0.356 212	0.099 113	0.050 111	0.030 107
DCP 2	.020	3.256	0.752 108	1.111 64	0.261 25	0.133 87	0.170 34	0.062 323	0.056 111	0.051 72	0.042 100
DCP 3	.030	3.069	0.741 96	0.950 54	0.161 7	0.148 72	0.145 17	0.093 342	0.065 6	0.047 352	0.039 329
DCP 4	.049	2.927	0.709 66	0.572 46	0.148 57	0.142 22	0.072 339	0.058 337	0.027 303	0.034 322	0.022 313
DCP 5	.074	2.250	0.763 60	0.485 32	0.120 25	0.100 337	0.044 295	0.047 314	0.016 311	0.036 292	0.035 263
DCP 6	.099	2.325	0.789 59	0.452 23	0.121 7	0.113 317	0.347 263	0.031 301	0.022 259	0.035 221	0.013 331
DCP 7	.149	1.834	0.827 50	0.402 4	0.119 311	0.095 264	0.051 229	0.025 210	0.034 166	0.018 171	0.013 202
DCP 8	.200	1.560	0.813 51	0.391 5	0.174 301	0.105 236	0.026 233	0.045 226	0.089 156	0.005 190	0.015 140
DCP 9	.250	1.384	0.789 43	0.363 350	0.223 276	0.125 204	0.054 213	0.369 157	0.067 166	0.017 37	0.021 59
DCP13	.300	1.229	0.744 38	0.313 337	0.219 260	0.138 181	0.054 169	0.073 120	0.053 66	0.020 310	0.024 27
DCP11	.399	1.072	0.705 38	0.232 328	0.199 297	0.118 182	0.072 173	0.095 100	0.063 44	0.028 322	0.031 342
DCP12	.501	0.889	0.667 29	0.230 288	0.157 223	0.391 153	0.082 120	0.111 53	0.063 317	0.028 256	0.020 276
DCP13	.600	0.779	0.621 21	0.243 253	0.157 181	0.088 107	0.070 91	0.133 13	0.113 269	0.049 201	0.022 144
DCP14	.701	0.662	0.529 12	0.289 228	0.187 148	0.120 56	0.052 32	0.133 329	0.096 251	0.051 117	0.012 73
DCP15	.600	0.447	0.438 2	0.279 213	0.180 125	0.132 23	0.047 315	0.063 273	0.063 161	0.038 69	0.022 21
DCP16	.900	0.126	0.276 347	0.171 196	0.120 95	0.071 328	0.010 321	0.037 279	0.054 176	0.028 66	0.021 332
DCP17	.969	0.031	0.148 343	0.096 203	0.065 95	0.362 340	0.323 236	0.337 8	0.011 253	0.014 195	0.016 96

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
3.3	69.06	0.257	0.405	5.63	0.0	14.69	12389.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
136.6	48527.	0.64E 07	-0.904	1.984	15.94	-0.03037	3.375	0.0
(448.2)	(1013.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		14.947	5.632 0	0.695 0	0.203 235	0.027 218	0.042 196	0.206 23	0.045 264	0.006 173	0.012 242
CN		1.162	0.587 39	0.192 11	0.059 263	0.020 227	0.023 212	0.020 109	0.011 262	0.008 141	0.011 92
CM		-0.076	0.145 186	0.058 85	0.034 16	0.009 295	0.013 18	0.015 263	0.020 66	0.031 3	0.032 258
DCP 1	.013	4.134	1.654 160	1.024 79	0.269 110	0.193 162	0.102 79	0.127 293	0.061 264	0.054 307	0.101 259
DCP 2	.070	3.384	1.089 141	0.934 91	0.211 63	0.283 197	0.175 125	0.202 264	0.327 299	0.081 288
DCP 3	.030	3.140	1.349 130	0.759 76	0.224 135	0.193 132	0.212 197	0.302 95	0.138 263	0.067 131	0.051 194
DCP 4	.049	3.088	0.717 92	0.457 76	0.275 77	0.256 98	0.063 82	0.311 82	0.005 161	0.076 167	0.059 159
DCP 5	.074	2.377	0.812 97	0.385 64	0.223 95	0.373 94	0.153 43	0.238 19	0.327 264	0.062 115	0.045 82
DCP 6	.099	2.471	0.632 70	0.386 55	0.204 76	0.065 81	0.101 4	0.042 356	0.005 264	0.021 63	0.014 110
DCP 7	.149	1.657	0.627 60	0.399 45	0.275 348	0.045 273	0.055 5	0.075 319	0.005 264	0.068 246	0.018 61
DCP 8	.203	1.672	0.813 61	0.449 47	0.300 343	0.052 283	0.356 352	0.381 323	0.034 64	0.014 31	0.004 120
DCP 9	.250	1.517	0.792 50	0.434 33	0.306 319	0.090 273	0.061 304	0.284 249	0.011 162	0.032 272	0.014 176
DCP10	.300	1.355	0.754 44	0.370 22	0.290 305	0.116 256	0.082 259	0.078 235	0.017 162	0.027 218	0.022 132
DCP11	.399	1.205	0.785 41	0.298 16	0.254 307	0.151 271	0.098 246	0.123 198	0.383 161	0.036 164	0.042 109
DCP12	.501	1.028	0.795 30	0.211 338	0.206 289	0.120 241	0.115 210	0.149 157	0.042 84	0.039 91	0.047 57
DCP13	.600	0.903	0.801 23	0.246 263	0.198 230	0.380 239	0.137 186	0.138 137	0.042	0.041 63	0.047 11
DCP14	.701	0.767	0.719 15	0.274 268	0.223 193	0.391 151	0.381 126	0.133 55	0.073 314	0.015 327	0.036 287
DCP15	.800	0.525	0.583 4	0.266 248	0.216 188	0.106 83	0.020 44	0.072 31	0.018 264	0.017 200	0.018 170
DCP16	.900	0.177	0.337 352	0.146 227	0.123 128	0.259 33	0.307 198	0.359 29	0.035 264	0.019 190	0.027 98
DCP17	.969	0.051	0.175 353	0.096 235	0.086 125	0.063 25	0.037 260	0.334 97	0.033 264	0.031 209	0.031 172

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
3.3	69.04	0.261	0.399	5.63	0.0	17.31	12093.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
134.6	47320.	0.64E 07	-0.333	2.077	21.37	-0.00031	3.334	0.0
(441.5)	(988.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		17.307	5.633 0	0.498 7	0.227 233	0.026 246	0.039 165	0.031 29	0.021 264	0.001 337	0.008 208
CN		1.200	0.580 42	0.193 33	0.091 306	0.014 256	0.017 240	0.017 225	0.005 264	0.334 99	0.004 313
CM		-0.091	0.146 187	0.361 136	0.038 66	0.035 326	0.009 44	0.039 351	0.038 264	0.039 248	0.001 84
DCP 1	.010	3.839	2.086 158	0.490 117	0.137 156	0.188 181	0.093 351	0.375 52	0.085 344	0.047 50	0.065 356
DCP 2	.023	3.210	1.351 144	0.661 110	0.195 179	0.228 160	0.107 225	0.316 333	0.333 314	0.033 46	0.052 27
DCP 3	.030	2.925	1.328 130	0.422 114	0.250 121	0.230 204	0.104 181	0.111 214	0.091 264	0.046 264	0.041 297
DCP 4	.049	3.055	0.802 97	0.425 124	0.228 97	0.132 151	0.386 156	0.321 132	0.061 264	0.341 293	0.026 277
DCP 5	.074	2.399	0.806 78	0.397 113	0.190 66	0.382 114	0.095 126	0.334 32	0.072 264	0.023 227	0.047 339
DCP 6	.099	2.510	0.838 69	0.365 100	0.146 54	0.085 87	0.068 114	0.330 16	0.092 264	0.005 60	0.018 12
DCP 7	.149	1.990	0.812 62	0.483 79	0.217 1	0.334 31	0.357 73	0.319 28	0.039 264	0.312 193	0.013 136
DCP 8	.200	1.738	0.807 66	0.519 71	0.226 9	0.059 4	0.086 75	0.041 21	0.022 264	0.019 75	0.001 243
DCP 9	.250	1.545	0.774 52	0.493 55	0.246 348	0.095 319	0.054 12	0.066 320	0.034 264	0.006 25	0.013 228
DCP10	.300	1.421	0.750 45	0.465 48	0.249 345	0.113 314	0.066 332	0.371 311	0.025 264	0.015 343	0.013 228
DCP11	.399	1.281	0.771 41	0.424 41	0.255 343	0.130 318	0.109 310	0.389 285	0.031 264	0.022 276	0.015 202
DCP12	.501	1.093	0.790 30	0.340 16	0.239 313	0.101 283	0.116 276	0.133 233	0.024 264	0.344 181	0.013 114
DCP13	.603	0.941	0.793 23	0.316 344	0.246 280	0.093 238	0.113 233	0.398 193	0.393 162	0.037 141	0.029 84
DCP14	.701	0.798	0.706 15	0.310 318	0.258 248	0.116 180	0.095 167	0.065 133	0.042 64	0.038 81	0.034 1
DCP15	.800	0.591	0.571 7	0.275 292	0.211 212	0.103 132	0.353 133	0.337 113	0.031 16	0.012 94	0.018 297
DCP16	.900	0.243	0.321 1	0.144 272	0.127 185	0.375 64	0.018 186	0.340 120	0.044 16	0.019 344	0.037 219
DCP17	.969	0.092	0.183 2	0.099 265	0.097 176	0.069 72	0.027 319	0.017 195	0.024 64	0.029 27	0.022 293

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	69.05	0.269	0.396	5.72	0.0	19.65	12663.4	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	133.4	46631.	0.63E 07	-0.347	2.039	23.08	-0.00128	1.624	0.0
	(437.7)	(973.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		19.665	5.721 0	0.347 395	0.157 299	0.016 241	0.309 159	0.032 44	0.067 44	0.001 55	0.002 225
CN		1.222	3.551 48	0.167 64	3.117 357	3.323 315	0.314 7	3.313 298	0.204 45	0.336 95	0.038 63
CM		-0.113	3.143 232	0.350 183	0.045 191	3.308 54	0.009 155	3.313 74	0.037 44	0.002 0	3.009 199
DCP 1	.010	3.455	2.383 169	0.328 226	0.114 147	3.171 323	3.121 142	3.328 71	0.095 44	0.042 232	3.347 170
DCP 2	.023	2.903	1.279 155	0.362 190	0.155 238	3.270 301	3.342 286	0.349 3	0.204 44	0.021 261	3.025 130
DCP 3	.030	2.693	1.110 139	0.479 191	0.075 162	3.217 263	0.140 288	0.348 1	0.056 44	0.399 53	3.332 113
DCP 4	.049	2.847	3.746 133	3.522 167	3.123 193	3.265 171	3.399 275	3.395 237	0.345 4	0.315 75	3.019 119
DCP 5	.074	2.274	0.724 73	0.442 154	0.095 157	3.091 96	0.091 222	3.390 312	3.044 44	0.010 72	3.356 132
DCP 6	.099	2.425	3.703 58	0.366 147	0.114 127	3.051 36	3.399 226	3.324 156	3.343 44	3.329 62	3.336 97
DCP 7	.149	1.624	3.682 61	0.480 47	3.129 48	3.336 5	3.373 146	3.342 115	3.319 44	3.017 44	3.023 37
DCP 8	.200	1.670	0.635 65	0.425 49	0.210 71	3.039 11	0.068 168	3.340 143	3.654 44	0.017 85	3.023 112
DCP 9	.250	1.558	0.662 53	0.415 82	3.259 48	3.255 7	3.376 99	3.141 73	3.289 44	3.311 86	3.326 48
DCP10	.330	1.458	3.656 49	3.382 77	0.289 41	3.349 12	3.391 77	3.393 59	3.018 4	0.010 128	3.001 5
DCP11	.349	1.957	0.704 47	0.233 74	0.295 48	3.079 22	0.100 61	3.365 53	3.617 44	0.091 99	3.012 7
DCP12	.531	1.177	3.731 38	3.279 48	0.284 5	3.383 3	3.136 15	3.176 351	3.232 44	3.326 49	3.013 263
DCP13	.603	1.028	3.742 33	0.255 25	0.261 316	3.373 313	3.089 341	3.379 298	3.044 44	0.097 326	3.001 112
DCP14	.701	3.876	3.689 28	0.253 1	0.294 308	3.132 259	0.068 282	3.377 249	3.041 44	3.038 262	3.337 194
DCP15	.830	3.673	3.573 74	3.187 346	0.236 293	3.099 226	3.354 236	3.353 212	3.032 44	3.019 226	3.034 21
DCP16	.900	0.287	0.326 22	0.084 321	0.135 249	3.047 151	3.023 247	3.057 212	3.053 44	0.068 110	3.043 9
DCP17	.969	3.103	0.184 27	0.069 294	3.387 229	3.352 131	3.231 33	3.331 287	3.345 44	3.337 189	3.333 83

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	88.37	0.336	0.395	6.68	0.0	-0.00	12089.1	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	133.7	17266.	0.23E 07	-0.069	0.657	7.86	-0.00078	0.887	0.0
	(438.7)	(360.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		-0.001	6.678 0	1.228 301	0.090 218	0.090 95	0.051 353	0.015 55	0.036 353	0.010 228	0.008 156
CN		0.112	0.448 14	0.077 290	0.011 308	0.005 267	0.005 262	0.003 313	0.005 11	0.005 216	0.002 11
CM		-0.016	0.055 291	0.007 98	0.003 130	0.002 42	0.002 26	0.001 177	0.003 196	0.001 58	0.000 237
DCP 1	.010	-0.767	3.395 341	0.283 262	0.032 311	0.027 6	0.031 228	0.011 78	0.014 199	0.015 321	0.017 111
DCP 2	.020	-0.299	2.342 352	0.321 267	0.008 10	0.036 198	0.047 282	0.007 353	0.027 228	0.010 11	0.012 132
DCP 3	.030	-0.099	2.069 351	0.260 267	0.013 291	0.002 356	0.010 392	0.003 199	0.014 239	0.007 79	0.002 250
DCP 4	.049	0.158	1.722 353	0.205 274	0.016 370	0.010 243	0.004 311	0.006 317	0.012 130	0.002 337	0.008 9
DCP 5	.074	0.286	1.417 354	0.169 284	0.020 254	0.008 153	0.007 359	0.005 312	0.016 139	0.003 334	0.005 219
DCP 6	.099	0.330	1.194 357	0.130 290	0.013 276	0.011 167	0.016 7	0.011 290	0.022 190	0.002 191	0.003 45
DCP 7	.149	0.245	0.886 0	0.108 305	0.021 299	0.019 188	0.015 265	0.008 343	0.007 126	0.005 221	0.010 273
DCP 8	.200	0.196	0.732 13	0.091 339	0.018 49	0.016 320	0.001 80	0.010 308	0.012 324	0.002 125	0.009 68
DCP 9	.250	0.151	0.654 8	0.136 278	0.003 228	0.034 354	0.011 301	0.007 151	0.001 34	0.008 125	0.002 131
DCP10	.300	0.164	0.550 11	0.096 291	0.017 306	0.019 342	0.016 312	0.004 196	0.007 107	0.014 181	0.014 287
DCP11	.399	0.138	0.445 32	0.096 305	0.010 275	0.019 332	0.009 329	0.015 210	0.006 348	0.016 221	0.008 50
DCP12	.501	0.107	0.371 41	0.074 314	0.009 322	0.016 255	0.007 278	0.016 333	0.015 289	0.006 156	0.005 342
DCP13	.600	0.138	0.311 44	0.063 306	0.016 322	0.022 223	0.005 92	0.004 337	0.013 5	0.021 222	0.006 31
DCP14	.701	0.206	0.252 48	0.043 313	0.017 293	0.002 132	0.008 143	0.013 96	0.025 26	0.006 335	0.008 38
DCP15	.800	0.102	0.198 74	0.036 244	0.010 269	0.017 161	0.013 172	0.006 36	0.022 10	0.010 216	0.005 273
DCP16	.900	-0.093	0.108 102	0.059 245	0.012 7	0.014 183	0.024 233	0.008 230	0.003 174	0.007 359	0.012 206
DCP17	.969	-0.050	0.050 157	0.061 234	0.016 300	0.022 332	0.009 264	0.012 348	0.011 109	0.034 293	0.017 78

FORCED PITCHING OSCILLATION   AIRFOIL   NLF 1

TOWER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	88.56	0.338	0.395	4.87	0.0	2.46	12089.2	20

V	Q	RN	CM(MIN)	CM(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
133.5	17294.	0.23E 07	-0.069	0.883	10.29	-0.50085	0.467	0.0
(438.1)	(361.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
AL PHA		2.456	4.670 0	1.226 302	0.069 211	0.079 102	0.059 352	0.020 84	0.093 359	0.022 224	0.007 181
CN		5.361	3.461 15	0.367 316	0.005 90	0.010 258	0.002 266	0.002 271	0.001 160	0.004 168	0.003 29
CM		-0.309	3.057 245	0.010 718	0.001 267	0.003 67	0.001 12	0.001 359	0.002 166	0.002 341	0.001 245
CP 1	.010	0.982	3.224 341	0.372 251	0.046 99	0.045 355	0.034 232	0.023 199	0.048 80	0.025 190	0.004 249
CP 2	.020	0.955	2.616 351	0.413 268	0.095 169	0.060 75	0.357 325	0.041 280	0.028 166	0.022 119	0.015 44
CP 3	.010	0.967	2.100 350	0.219 276	0.046 314	0.037 227	0.011 173	0.004 98	0.021 167	0.015 029	0.021 260
CP 4	.040	1.056	1.788 355	0.261 280	0.007 67	0.023 180	0.300 129	0.039 350	0.014 81	0.017 366	0.021 319
CP 5	.014	1.015	1.430 356	0.189 282	0.056 233	0.008 177	0.001 316	0.005 294	0.019 99	0.003 357	0.009 288
CP 6	.099	0.938	1.194 357	0.159 294	0.013 313	0.023 161	0.011 270	0.004 355	0.015 133	0.010 11	0.021 324
CP 7	.145	0.794	0.902 1	0.117 310	0.006 342	0.012 270	0.016 341	0.011 16	0.023 355	0.002 193	0.011 280
CP 8	.200	0.676	0.720 13	0.113 324	0.075 331	0.010 156	0.010 35	0.011 287	0.007 131	0.007 215	0.004 7
CP 9	.250	0.487	0.631 12	0.111 301	0.012 109	0.015 297	0.001 313	0.007 357	0.003 197	0.008 198	0.013 284
CP10	.300	0.446	0.541 14	0.091 309	0.012 144	0.011 219	0.004 197	0.005 191	0.012 168	0.004 261	0.010 34
CP11	.390	0.366	0.438 34	0.090 344	0.008 45	0.015 269	0.012 23	0.013 354	0.020 245	0.005 147	0.016 44
CP12	.501	0.280	0.362 41	0.074 350	0.006 3	0.018 241	0.007 322	0.005 191	0.011 276	0.013 179	0.006 109
CP13	.600	0.257	0.337 36	0.058 354	0.012 105	0.018 259	0.008 262	0.012 373	0.013 309	0.016 179	0.011 66
CP14	.701	0.282	0.261 66	0.030 6	0.006 166	0.019 231	0.018 185	0.008 145	0.015 356	0.004 181	0.005 206
CP15	.850	0.165	0.187 66	0.005 34	0.010 212	0.014 213	0.004 196	0.006 259	0.005 59	0.013 90	0.036 58
CP16	.900	-0.399	0.100 100	0.008 46	0.011 79	0.008 222	0.008 282	0.016 119	0.010 44	0.009 317	0.015 147
CP17	.969	-0.060	0.041 156	0.010 265	0.017 47	0.011 358	0.009 147	0.007 782	0.002 182	0.004 58	0.013 279

FORCED PITCHING OSCILLATION   AIRFOIL   NLF 1

TOWER HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	88.20	0.338	0.393	4.66	0.0	4.95	12089.3	20

V	Q	RN	CM(MIN)	CM(MAX)	ALPHA.NMAX	AERO DAMP	TDP	EXT DAMP
132.9	17093.	0.23E 07	-0.066	1.118	12.95	-0.00091	1.953	0.0
(435.9)	(357.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
AL PHA		4.948	4.661 3	1.707 306	0.070 215	0.076 98	0.059 357	0.012 60	0.048 1	0.013 251	0.036 162
CN		5.431	3.445 17	0.372 335	0.005 62	0.006 292	0.010 371	0.001 151	0.005 368	0.002 155	0.002 274
CM		-0.001	3.058 245	0.021 214	0.001 210	0.004 72	0.002 152	0.001 196	0.001 134	0.002 342	0.008 149
CP 1	.010	2.465	3.250 341	0.451 245	0.059 222	0.065 158	0.093 76	3.347 323	0.034 166	0.020 116	0.021 269
CP 2	.020	2.431	2.990 353	0.634 266	0.104 145	0.051 118	0.060 157	0.060 61	0.043 207	0.041 169	0.051 12
CP 3	.010	2.055	2.390 351	0.322 250	0.120 140	0.166 93	0.144 339	0.105 219	0.076 142	0.026 44	0.007 343
CP 4	.040	1.026	1.778 356	0.223 277	0.020 230	0.032 77	0.047 312	3.058 213	0.067 107	0.046 351	0.099 261
CP 5	.174	1.712	1.403 356	0.176 287	0.028 244	0.012 120	0.023 106	0.026 106	0.033 106	0.022 312	0.023 196
CP 6	.006	1.527	1.161 0	3.143 290	0.018 248	1.039 85	0.010 266	3.013 155	0.029 120	0.013 306	0.011 201
CP 7	.140	1.158	0.871 3	0.197 298	0.015 39	0.010 150	0.014 355	0.010 93	0.023 199	0.012 136	0.011 308
CP 8	.200	0.956	0.718 15	0.190 117	0.018 351	0.008 339	0.001 215	0.017 146	0.013 294	0.009 0	0.012 135
CP 9	.290	0.796	0.645 13	0.197 326	0.007 349	0.559 336	0.017 291	3.001 7	0.011 362	0.010 87	0.020 337
CP10	.300	0.701	0.534 16	0.086 320	0.007 277	0.027 299	0.010 303	0.003 25	0.017 170	0.006 187	0.001 117
CP11	.390	0.578	0.460 37	0.096 10	0.018 4	0.030 289	0.009 16	0.011 31	3.019 242	0.006 209	0.034 143
CP12	.521	0.431	0.372 44	0.098 1	0.099 137	0.012 314	0.005 12	0.059 350	0.013 276	0.004 164	0.005 234
CP13	.600	0.363	0.322 47	0.083 23	0.013 78	0.028 296	0.010 246	0.007 61	0.023 317	0.010 304	0.010 1
CP14	.721	0.351	0.751 48	0.098 17	0.010 77	0.022 213	0.021 319	0.007 141	3.016 339	0.036 181	0.003 102
CP15	.800	0.175	0.141 85	0.064 19	0.012 354	0.015 179	0.005 331	0.005 58	0.005 80	0.005 92	0.036 106
CP16	.900	-0.082	0.104 93	0.099 99	0.013 90	0.006 127	0.008 765	0.014 266	3.015 325	0.036 183	0.005 271
CP17	.969	-0.079	0.061 149	0.024 96	0.007 94	0.012 991	0.015 37	0.003 96	0.008 179	0.007 134	0.009 295

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	87.77	0.334	0.396	6.65	0.0	7.40	12089.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
133.6	17323.	0.23E 07	-0.058	1.391	15.22	-0.00070	0.341	0.0
(438.4)	(361.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.403	6.651 0	1.393 299	0.076 214	0.063 148	0.050 344	0.017 28	0.065 352	0.017 222	0.004 82
CN		3.762	0.582 20	0.048 256	0.040 6	0.032 224	0.006 61	0.007 74	0.007 291	0.002 262	0.008 145
CM		-0.309	0.029 253	0.041 332	0.021 178	0.006 31	0.002 215	0.000 332	0.002 93	0.001 233	0.003 338
CP 1	.010	2.917	1.982	0.883 5	0.404 298	0.214 219	0.160 173	0.100 112	0.082 52	0.029 333	0.034 343
CP 2	.020	2.663	1.890 8	0.848 8	0.443 304	0.259 260	0.216 219	0.111 154	0.053 152	0.065 89	0.039 354
CP 3	.030	2.465	1.73 10	0.723 351	0.373 258	0.195 168	0.158 157	0.172 85	0.095 39	0.102 0	0.077 311
CP 4	.040	2.207	1.46 17	0.510 366	0.191 262	0.131 223	0.137 142	0.116 43	0.045 16	0.083 120	0.086 244
CP 5	.074	1.891	1.45 17	0.519 333	0.152 226	0.104 195	0.120 104	0.107 10	0.042 334	0.059 264	0.061 172
CP 6	.099	1.813	1.252 19	0.461 322	0.145 200	0.092 189	0.140 84	0.109 348	0.026 284	0.070 242	0.052 159
CP 7	.149	1.649	1.113 13	0.346 329	0.122 162	0.092 138	0.152 76	0.139 285	0.068 190	0.062 169	0.076 70
CP 8	.200	1.603	1.003 14	0.242 334	0.124 147	0.076 108	0.151 57	0.095 270	0.086 209	0.069 53	0.074 59
CP 9	.250		.507 8	0.258 316	0.141 45	0.061 13	0.109 409	0.100 197	0.092 122	0.069 53	0.046 300
CP10	.300	1.704	0.219 23	0.219 23	0.141 82	0.079 328	0.122 21	0.049 143	0.051 41	0.047 112	0.034 220
CP11	.399	0.704	0.131 2	0.194 59	0.090 311	0.107 245	0.063 162	0.061 13	0.044 192	0.034 172	
CP12	.501		0.152 19	0.152 19	0.096 256	0.070 197	0.096 71	0.039 292	0.040 169	0.023 83	
CP13	.600	0.466	0.097 45	0.129 156	0.061 5	0.074 223	0.045 157	0.062 7	0.075 251	0.033 107	0.024 0
CP14	.701	0.344	0.172 54	0.135 14	0.139 303	0.069 182	0.042 74	0.034 239	0.016 194	0.027 81	0.025 217
CP15	.800	0.254	0.134 58	0.112 15	0.104 318	0.042 155	0.074 50	0.022 254	0.010 71	0.018 19	0.023 177
CP16	.900	-0.056	0.069 28	0.079 115	0.144 297	0.033 138	0.027 5	0.013 197	0.021 92	0.024 286	0.023 114
CP17	.969	-0.164	0.019 348	0.061 157	0.018 327	0.025 250	0.019 21	0.004 190	0.016 134	0.028 320	0.012 168

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	88.48	0.332	0.401	6.63	1.0	9.89	12091.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
135.3	17950.	2.24E 07	-0.174	1.604	16.00	0.00033	-0.342	0.0
(445.5)	(374.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		9.888	6.625 0	1.609 302	0.091 212	0.092 169	0.036 339	0.013 15	0.064 1	0.022 203	0.003 104
CN		3.937	0.632 20	0.038 312	0.035 33	0.027 307	0.015 177	0.013 288	0.009 156	0.013 102	0.005 9
CM		-0.042	0.050 170	0.047 329	0.024 131	0.017 146	0.008 7	0.003 153	0.004 148	0.004 325	0.003 124
CP 1	.010	3.994	1.761 44	0.997 13	0.296 347	0.264 298	0.091 265	0.114 263	0.073 192	0.046 179	0.034 104
CP 2	.020	2.763	1.445 48	0.984 26	0.396 5	0.295 330	0.105 311	0.126 304	0.058 240	0.039 273	0.038 178
CP 3	.030	2.614	1.304 41	0.799 10	0.294 332	0.302 281	0.162 234	0.166 229	0.161 195	0.089 160	0.105 138
CP 4	.040	2.497	1.266 31	0.492 1	0.192 340	0.231 285	0.117 209	0.093 199	0.128 130	0.048 79	0.067 87
CP 5	.074	2.271	1.240 28	0.425 344	0.181 332	0.245 255	0.171 170	0.086 156	0.123 96	0.063 22	0.047 35
CP 6	.099	2.078	1.199 28	0.377 334	0.168 324	0.251 243	0.138 159	0.085 127	0.099 87	0.072 19	0.092 352
CP 7	.149	1.652	1.187 25	0.381 306	0.109 270	0.292 211	0.147 122	0.127 76	0.083 20	0.056 338	0.061 275
CP 8	.200	1.412	1.092 31	0.373 308	0.171 257	0.183 183	0.131 123	0.120 77	0.090 351	0.058 322	0.059 257
CP 9	.250	1.292	1.019 19	0.300 299	0.176 217	0.197 127	0.122 43	0.106 344	0.092 250	0.056 189	0.062 149
CP10	.300	1.162	0.916 15	0.240 281	0.166 197	0.203 99	0.140 10	0.131 295	0.110 206	0.066 130	0.072 87
CP11	.399	1.042	0.810 17	0.147 245	0.124 173	0.193 87	0.148 359	0.153 285	0.126 209	0.098 118	0.053 55
CP12	.501	0.834	0.662 11	0.181 191	0.126 107	0.194 35	0.154 288	0.123 211	0.102 123	0.072 79	0.057 301
CP13	.600	0.694	0.495 11	0.213 163	0.161 66	0.187 344	0.144 234	0.078 152	0.099 54	0.078 300	0.040 204
CP14	.701	0.552	0.337 10	0.220 140	0.182 35	0.165 301	0.116 183	0.072 68	0.072 337	0.066 211	0.031 96
CP15	.800	0.318	0.188 3	0.195 127	0.146 23	0.146 278	0.112 135	0.063 353	0.039 309	0.059 145	0.017 343
CP16	.900	0.097	0.112 338	0.135 95	0.097 356	0.091 247	0.055 109	0.021 314	0.018 240	0.031 73	0.029 256
CP17	.969	-0.336	0.032 339	0.065 59	0.052 10	0.030 231	0.029 174	0.019 20	0.022 286	0.012 60	0.020 304

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	88.26	0.331	0.401	6.56	0.0	13.89	12091.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
135.7	17960.	0.24E 07	-0.257	1.954	21.37	0.00110	-1.270	0.0
(445.1)	(375.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		13.889	6.564	0	1.815	304	0.105	252	0.082	190	0.042	15	0.011	329	0.077	355	0.022	237	0.004	98
CN		1.185	0.678	23	0.059	337	0.030	39	0.044	276	0.027	68	0.017	183	0.029	2	0.015	264	0.005	206
CM		-0.084	0.128	156	0.041	354	0.015	264	0.005	81	0.016	209	0.012	25	0.009	169	0.004	57	0.003	292
DCP 1	.010	3.174	1.848	105	0.510	43	0.414	80	0.095	130	0.107	90	0.074	95	0.036	40	0.045	75	0.023	253
DCP 2	.020	2.994	1.837	104	0.581	65	0.413	101	0.162	149	0.059	113	3.121	128	0.023	113	0.049	120	0.028	205
DCP 3	.030	2.797	1.487	91	0.532	46	0.429	57	0.176	64	0.158	47	0.135	79	0.087	64	0.098	83	0.038	64
DCP 4	.049	3.061	1.050	57	0.190	31	0.299	67	0.155	21	0.118	355	0.077	19	3.085	350	0.058	359	0.074	330
DCP 5	.074	2.808	1.074	42	0.112	24	0.324	45	0.197	343	0.129	312	0.064	2	0.110	314	0.054	286	0.055	284
DCP 6	.099	2.591	1.110	38	0.091	11	0.341	35	0.249	330	0.149	293	0.049	332	0.102	306	0.084	268	0.046	254
DCP 7	.149	1.927	1.188	48	0.448	344	0.170	320	0.184	323	0.188	265	0.068	224	0.072	238	0.060	207	0.070	189
DCP 8	.200	1.641	1.154	52	0.449	346	0.162	310	0.206	311	0.180	251	0.097	235	0.085	196	0.084	191	0.057	168
DCP 9	.250	1.480	1.075	37	0.468	342	0.216	280	0.224	253	0.191	184	0.113	147	0.100	104	0.061	72	0.065	20
DCP10	.300	1.362	0.995	30	0.402	335	0.253	257	0.189	219	0.175	145	3.123	133	0.084	52	0.064	16	0.048	320
DCP11	.399	1.310	0.954	23	0.282	337	0.259	250	0.135	209	0.232	145	0.148	81	0.100	45	0.094	0	0.081	309
DCP12	.501	1.164	0.995	4	0.157	247	0.133	202	0.164	170	0.284	79	0.142	339	0.081	347	0.143	266	0.097	188
DCP13	.600	1.011	0.855	354	0.277	206	0.167	126	0.070	119	3.267	41	0.188	280	0.016	249	0.079	201	0.077	121
DCP14	.701	0.770	0.621	347	0.284	175	0.212	91	0.097	358	0.140	340	0.148	210	0.030	349	0.053	124	0.040	21
DCP15	.800	0.500	0.428	336	0.246	164	0.219	68	0.143	321	3.057	296	0.004	171	0.069	354	0.028	277	0.023	101
DCP16	.900	0.175	0.255	317	0.169	108	0.125	8	0.045	288	0.077	284	0.076	127	0.033	292	0.010	126	0.015	14
DCP17	.969	0.027	0.104	313	0.110	88	0.093	359	0.029	145	0.054	340	0.042	185	0.071	208	0.008	3	0.026	216

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	87.93	0.333	0.398	6.56	0.0	14.90	12091.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
134.6	17653.	0.24E 07	-0.310	2.012	21.73	0.00118	-1.355	0.0
(441.6)	(368.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		14.903	6.562	0	1.756	305	0.098	209	0.041	182	0.045	8	0.019	319	3.069	358	0.024	238	0.003	268
CN		1.255	0.689	25	0.024	36	0.037	81	0.074	277	0.034	92	0.022	170	0.019	38	0.006	299	0.010	294
CM		-0.100	0.145	150	0.053	353	0.020	271	0.015	59	0.022	230	0.010	39	0.006	188	0.007	81	0.003	107
DCP 1	.010	3.195	1.975	113	0.277	73	0.348	101	3.249	156	0.075	155	0.087	127	3.023	105	0.040	75	0.043	160
DCP 2	.020	3.054	1.937	113	0.369	99	0.357	125	3.292	175	0.090	227	0.102	155	0.071	232	0.021	155	0.055	212
DCP 3	.030	2.803	1.562	98	0.452	72	0.380	74	3.223	119	0.115	111	0.159	121	3.076	147	0.078	139	0.067	179
DCP 4	.049	3.144	1.115	65	0.129	61	0.252	70	3.151	78	0.073	15	0.122	84	0.074	59	0.078	65	0.051	76
DCP 5	.074	2.900	1.071	49	0.096	74	0.270	53	3.151	30	0.083	340	0.101	56	0.065	25	0.071	21	0.044	21
DCP 6	.099	2.674	1.067	42	0.062	69	0.294	48	3.200	6	0.084	325	0.092	19	0.083	1	3.058	350	0.044	353
DCP 7	.149	1.994	1.197	55	0.443	351	0.078	333	0.230	1	0.155	294	0.052	306	0.058	301	0.061	261	0.055	262
DCP 8	.200	1.711	1.154	55	0.421	351	0.110	318	0.217	340	0.163	290	0.084	255	0.070	284	0.050	239	0.070	284
DCP 9	.250	1.585	1.105	41	0.462	3	0.140	284	3.259	303	0.173	221	0.123	147	0.085	163	0.105	143	0.045	152
DCP10	.300	1.445	0.991	34	0.406	358	0.251	271	0.231	262	0.166	189	0.142	147	0.089	109	0.064	99	0.052	61
DCP11	.399	1.384	0.967	27	0.259	1	0.232	263	0.248	269	0.242	178	0.146	138	0.104	114	0.091	74	0.064	11
DCP12	.501	1.220	0.952	7	0.174	271	0.152	199	0.183	213	0.292	116	0.127	33	0.099	17	0.089	330	0.095	257
DCP13	.600	1.078	0.941	358	0.272	215	0.208	139	0.110	204	0.293	77	0.159	324	0.059	312	0.078	284	0.072	194
DCP14	.701	0.860	3.730	349	0.332	190	0.251	136	0.010	335	0.191	72	0.137	247	0.019	180	0.036	235	0.042	48
DCP15	.800	0.570	0.512	333	0.336	170	0.251	76	3.098	303	0.092	2	0.137	191	0.057	21	0.041	266	0.023	157
DCP16	.900	0.221	0.391	316	0.278	127	0.147	15	0.064	180	0.121	324	0.072	119	0.042	320	0.044	193	0.012	267
DCP17	.969	0.062	3.118	310	0.209	125	0.133	357	0.028	182	3.064	355	0.039	224	0.099	123	0.004	168	0.030	300

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	22.59	0.068	0.505	5.14	0.0	0.00	12035.1	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	169.3	74439.	0.79E 07	-0.037	0.653	5.00	-0.00076	1.032	0.0
	(555.4)	(1554.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.003	5.142 0	0.213 9	0.037 259	0.006 197	0.028 351	0.035 136	0.019 274	0.046 323	0.005 248
CN		0.126	0.523 354	0.009 324	0.007 289	0.002 244	0.004 321	0.002 145	0.005 340	0.011 335	0.001 144
CM		-0.016	0.015 318	0.002 26	0.002 116	0.001 158	0.000 184	0.000 53	0.001 179	0.003 149	0.000 344
DCP 1	.010	-0.669	3.295 348	0.118 274	0.252 317	0.219 36	0.116 108	0.046 164	0.016 42	0.041 157	0.040 238
DCP 2	.020	-0.380	2.633 351	0.059 319	0.034 303	0.018 19	0.018 88	0.052 177	0.061 285	0.048 354	0.023 75
DCP 3	.030	-0.142	2.379 350	0.090 35	0.078 155	0.063 226	0.038 316	0.020 138	0.033 278	0.034 347	0.027 61
DCP 4	.049	0.149	1.965 350	0.065 20	0.081 145	0.072 217	0.055 296	0.024 38	0.008 20	0.008 342	0.012 54
DCP 5	.074	0.311	1.580 350	0.043 356	0.034 138	0.039 206	0.039 288	0.018 15	0.016 32	0.005 87	0.004 240
DCP 6	.099	0.388	1.312 351	0.031 334	0.002 71	0.018 205	0.018 288	0.006 35	0.009 358	0.004 48	0.005 225
DCP 7	.149	0.265	0.960 351	0.020 321	0.009 300	0.003 172	0.005 298	0.003 128	0.008 346	0.001 330	0.002 225
DCP 8	.200	0.209	0.784 354	0.018 320	0.012 316	0.002 50	0.002 340	0.005 167	0.007 342	0.006 357	0.003 128
DCP 9	.250	0.189	0.678 353	0.016 335	0.009 288	0.002 227	0.006 307	0.005 181	0.004 323	0.011 327	0.002 217
DCP10	.300	0.197	0.570 353	0.012 336	0.008 292	0.001 259	0.004 329	0.001 251	0.005 333	0.009 322	0.002 221
DCP11	.399	0.181	0.457 358	0.008 338	0.007 297	0.000 42	0.004 339	0.002 174	0.005 15	0.016 329	0.001 85
DCP12	.501	0.128	0.343 359	0.005 327	0.010 299	0.003 331	0.003 26	0.006 165	0.004 0	0.012 339	0.002 111
DCP13	.600	0.142	0.258 1	0.005 280	0.009 302	0.002 324	0.002 61	0.002 160	0.004 290	0.013 340	0.001 156
DCP14	.701	0.208	0.179 2	0.003 196	0.008 296	0.000 336	0.004 338	0.001 147	0.003 331	0.014 336	0.003 160
DCP15	.800	0.094	0.100 7	0.006 207	0.010 300	0.002 277	0.003 0	0.001 273	0.003 309	0.014 326	0.002 229
DCP16	.900	-0.091	0.019 40	0.013 230	0.008 278	0.004 333	0.004 314	0.000 284	0.007 355	0.012 320	0.003 341
DCP17	.969	-0.047	0.027 175	0.007 218	0.007 272	0.001 260	0.003 303	0.001 320	0.003 81	0.013 339	0.004 134

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	22.67	0.069	0.502	5.16	0.0	2.45	12035.2	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	167.8	73621.	0.79E 07	-0.027	0.929	7.69	-0.00075	1.008	0.0
	(550.6)	(1537.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.447	5.157 0	0.228 9	0.051 263	0.006 214	0.020 17	0.018 55	0.029 188	0.065 179	0.005 305
CN		0.396	0.531 353	0.024 0	0.005 311	0.001 247	0.002 269	0.001 69	0.001 249	0.018 188	0.002 69
CM		-0.009	0.015 321	0.004 253	0.001 170	0.000 119	0.000 78	0.000 256	0.000 85	0.005 20	0.000 158
DCP 1	.010	1.132	3.595 348	0.165 311	0.130 145	0.011 144	0.022 184	0.038 28	0.032 305	0.041 175	0.014 91
DCP 2	.020	1.073	2.891 350	0.213 288	0.139 164	0.106 66	0.061 318	0.020 209	0.021 338	0.060 206	0.050 125
DCP 3	.030	1.140	2.438 350	0.162 288	0.098 163	0.119 60	0.120 321	0.103 228	0.077 130	0.029 63	0.007 54
DCP 4	.049	1.157	1.913 350	0.079 1	0.096 328	0.087 239	0.066 147	0.053 44	0.032 310	0.034 181	0.009 75
DCP 5	.074	1.135	1.594 350	0.069 332	0.022 303	0.015 236	0.009 154	0.003 104	0.004 304	0.019 162	0.003 101
DCP 6	.099	1.063	1.327 351	0.057 347	0.018 309	0.007 251	0.004 179	0.001 72	0.002 133	0.018 157	0.001 8
DCP 7	.149	0.756	0.970 351	0.042 358	0.013 302	0.005 242	0.002 198	0.001 103	0.002 136	0.014 156	0.002 340
DCP 8	.200	0.608	0.793 354	0.039 6	0.011 319	0.002 236	0.002 210	0.002 7	0.001 162	0.016 166	0.002 46
DCP 9	.250	0.530	0.677 353	0.035 15	0.011 314	0.002 265	0.001 208	0.000 133	0.001 340	0.018 181	0.002 84
DCP10	.300	0.488	0.564 353	0.032 17	0.010 319	0.002 250	0.002 272	0.001 112	0.002 130	0.014 173	0.002 26
DCP11	.399	0.410	0.452 357	0.027 27	0.007 347	0.001 263	0.002 293	0.001 28	0.002 231	0.023 196	0.003 34
DCP12	.501	0.300	0.345 358	0.021 27	0.005 325	0.002 308	0.003 320	0.000 81	0.003 273	0.017 202	0.002 98
DCP13	.600	0.273	0.261 0	0.018 32	0.006 314	0.002 209	0.002 293	0.003 62	0.001 201	0.020 200	0.001 84
DCP14	.701	0.298	0.174 1	0.020 42	0.002 332	0.002 323	0.001 268	0.002 17	0.000 199	0.018 196	0.001 103
DCP15	.800	0.139	0.099 5	0.013 54	0.004 359	0.001 171	0.001 245	0.003 89	0.001 295	0.019 197	0.003 300
DCP16	.900	-0.085	0.029 12	0.004 11	0.004 9	0.002 43	0.003 276	0.002 155	0.001 253	0.022 191	0.001 31
DCP17	.969	-0.059	0.021 163	0.003 348	0.001 298	0.002 100	0.003 149	0.002 43	0.002 355	0.017 201	0.002 77

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.80	0.070	0.499	5.17	0.0	4.93	12035.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
166.7	72893.	0.79E 07	-0.020	1.148	10.14	-0.00098	1.304	0.0
(547.0)	(1522.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.928	5.167 0	0.218 10	0.052 267	0.013 234	0.017 74	0.029 25	0.043 177	0.015 107	0.004 301
CN		0.643	0.481 357	0.063 13	0.023 260	0.012 114	0.008 337	0.005 230	0.003 135	0.002 71	0.003 58
CM		0.001	0.024 329	0.006 239	0.001 25	0.003 241	0.003 127	0.002 17	0.001 261	0.001 189	0.000 276
DCP 1	.010	2.656	3.018 349	0.359 39	0.298 324	0.178 224	0.039 104	0.036 269	0.020 204	0.045 181	0.037 95
DCP 2	.020	2.474	2.834 352	0.180 346	0.154 325	0.185 241	0.106 142	0.028 305	0.059 156	0.011 99	0.046 124
DCP 3	.030	2.436	2.599 352	0.221 309	0.049 291	0.120 249	0.121 158	0.033 55	0.060 146	0.072 51	0.017 312
DCP 4	.049	2.295	2.161 353	0.206 329	0.100 294	0.125 244	0.154 161	0.132 62	0.063 309	0.035 132	0.056 350
DCP 5	.074	1.874	1.459 355	0.253 4	0.164 263	0.098 148	0.041 60	0.024 83	0.053 17	0.054 287	0.024 227
DCP 6	.099	1.643	1.147 354	0.183 23	0.091 270	0.074 142	0.065 47	0.052 330	0.034 270	0.039 218	0.026 159
DCP 7	.149	1.191	0.841 354	0.112 28	0.034 285	0.021 104	0.021 6	0.018 285	0.012 216	0.012 170	0.009 72
DCP 8	.200	1.004	0.772 357	0.077 340	0.062 196	0.061 86	0.047 352	0.032 267	0.018 186	0.013 156	0.013 76
DCP 9	.250	0.881	0.674 355	0.058 316	0.064 163	0.066 54	0.055 314	0.036 223	0.022 147	0.018 84	0.017 20
DCP10	.300	0.768	0.537 356	0.052 344	0.039 172	0.044 59	0.038 310	0.026 213	0.018 126	0.013 41	0.009 333
DCP11	.399	0.618	0.401 1	0.052 21	0.011 221	0.017 63	0.018 302	0.012 184	0.007 82	0.004 18	0.002 73
DCP12	.501	0.446	0.284 5	0.057 33	0.016 281	0.008 95	0.010 302	0.009 191	0.006 94	0.004 14	0.000 268
DCP13	.600	0.369	0.195 10	0.063 38	0.027 287	0.011 143	0.007 354	0.006 208	0.006 73	0.004 336	0.002 128
DCP14	.701	0.348	0.103 23	0.068 43	0.028 288	0.012 144	0.008 0	0.006 232	0.004 105	0.003 16	0.002 67
DCP15	.800	0.164	0.056 37	0.044 46	0.014 278	0.008 102	0.009 315	0.007 218	0.002 185	0.003 356	0.003 131
DCP16	.900	-0.071	0.029 28	0.012 340	0.009 158	0.011 41	0.009 263	0.006 126	0.004 8	0.001 335	0.001 79
DCP17	.969	-0.065	0.005 149	0.013 260	0.007 159	0.006 45	0.005 293	0.002 164	0.002 256	0.004 53	0.002 31

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.38	0.069	0.498	5.14	0.0	7.39	12035.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
166.0	72366.	0.79E 07	-0.049	1.262	11.52	-0.00122	1.623	0.0
(544.6)	(1511.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.389	5.143 0	0.192 28	0.048 331	0.016 339	0.054 328	0.046 212	0.065 100	0.105 293	0.018 239
CN		0.801	0.297 10	0.154 45	0.054 330	0.023 285	0.022 230	0.017 153	0.012 56	0.025 324	0.004 317
CM		0.000	0.018 287	0.015 117	0.012 15	0.004 323	0.005 320	0.005 247	0.003 175	0.011 121	0.001 78
DCP 1	.010	3.545	1.634 347	1.077 70	0.430 352	0.105 349	0.083 309	0.039 273	0.030 149	0.102 40	0.009 256
DCP 2	.020	3.202	1.590 351	0.936 78	0.563 359	0.110 323	0.184 322	0.079 252	0.049 262	0.099 80	0.042 303
DCP 3	.030	3.086	1.530 350	0.733 81	0.511 7	0.142 322	0.207 325	0.121 255	0.094 286	0.062 157	0.040 308
DCP 4	.049	2.731	1.033 352	0.804 77	0.469 1	0.077 322	0.221 344	0.195 257	0.008 13	0.052 258	0.039 235
DCP 5	.074	2.253	0.733 7	0.535 55	0.197 5	0.159 328	0.092 274	0.085 252	0.044 178	0.016 332	0.060 194
DCP 6	.099	1.995	0.620 7	0.420 51	0.140 342	0.099 308	0.095 242	0.062 193	0.042 149	0.052 97	0.022 124
DCP 7	.149	1.495	0.528 7	0.293 44	0.126 330	0.084 276	0.076 216	0.060 160	0.043 100	0.043 70	0.016 54
DCP 8	.200	1.246	0.503 11	0.228 36	0.102 319	0.072 275	0.074 221	0.063 164	0.045 99	0.044 78	0.023 55
DCP 9	.250	1.111	0.484 11	0.195 19	0.095 295	0.067 243	0.071 193	0.064 130	0.048 72	0.039 353	0.034 355
DCP10	.300	0.961	0.387 11	0.153 21	0.061 298	0.045 257	0.056 198	0.054 126	0.039 56	0.035 331	0.022 347
DCP11	.399	0.772	0.296 18	0.125 8	0.043 294	0.024 256	0.036 203	0.035 127	0.026 53	0.047 325	0.013 337
DCP12	.501	0.562	0.208 24	0.100 30	0.029 277	0.008 222	0.017 189	0.021 101	0.017 23	0.042 312	0.010 266
DCP13	.600	0.446	0.141 37	0.090 30	0.024 261	0.005 149	0.011 183	0.018 88	0.014 10	0.040 303	0.006 266
DCP14	.701	0.391	0.086 69	0.074 29	0.022 217	0.014 86	0.004 193	0.013 69	0.013 338	0.038 297	0.004 212
DCP15	.800	0.205	0.071 55	0.042 350	0.026 197	0.011 110	0.010 141	0.015 43	0.011 330	0.036 299	0.002 241
DCP16	.900	-0.039	0.066 24	0.037 299	0.018 195	0.012 179	0.016 114	0.011 31	0.006 318	0.040 299	0.005 173
DCP17	.969	-0.059	0.024 20	0.027 285	0.007 196	0.007 199	0.007 113	0.004 63	0.003 309	0.035 308	0.002 171

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ 0.0	DRIVE HZ 22.77	K 0.071	MACH NO 0.493	DEL.ALPHA 5.02	DEL.H 0.0	ALPHA.0 9.88	TEST POINT 12035.5	CYCLES ANALYSED 20
	V 164.1 (538.4)	Q 69857. (1459.0)	RN 0.77E 07	CN(MIN) -0.071	CN(MAX) 1.350	ALPHA.NMAX 11.96	AERO DAMP -0.00138	TDR 1.811	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		9.881	5.015	0	0.247	27	0.034	265	0.033	88	0.042	58	0.113	35	0.148	244	0.036	268	0.018	147
CN		0.932	0.176	47	0.132	52	0.046	81	0.040	18	0.019	350	0.018	307	0.016	240	0.014	287	0.010	185
CM		-0.010	0.034	218	0.027	100	0.002	172	0.012	94	0.004	60	0.007	64	0.005	19	0.002	87	0.004	332
DCP 1	.010	3.937	0.306	184	1.267	72	0.201	125	0.223	80	0.084	12	0.044	127	0.053	318	0.020	266	0.035	317
DCP 2	.020	3.552	0.104	215	1.294	79	0.144	137	0.367	80	0.106	82	0.059	113	0.077	28	0.045	213	0.064	327
DCP 3	.030	3.486	0.243	320	1.043	85	0.113	122	0.400	85	0.137	93	0.119	74	0.118	78	0.061	233	0.034	31
DCP 4	.049	3.017	0.150	161	0.866	79	0.192	152	0.377	82	0.074	168	0.241	74	0.060	171	0.074	67	0.069	133
DCP 5	.074	2.510	0.289	95	0.467	75	0.245	96	0.154	77	0.120	56	0.097	74	0.040	39	0.057	91	0.023	96
DCP 6	.099	2.231	0.231	77	0.366	65	0.147	87	0.115	41	0.093	20	0.068	0	0.039	345	0.044	0	0.042	353
DCP 7	.149	1.706	0.265	54	0.289	53	0.089	58	0.096	15	0.065	341	0.050	334	0.043	299	0.039	303	0.019	284
DCP 8	.200	1.435	0.301	49	0.251	54	0.110	52	0.108	14	0.078	351	0.068	334	0.053	301	0.049	310	0.031	277
DCP 9	.250	1.307	0.342	36	0.189	40	0.105	39	0.103	349	0.075	333	0.076	304	0.059	269	0.066	270	0.046	222
DCP10	.300	1.138	0.305	35	0.135	32	0.070	45	0.071	348	0.055	333	0.063	292	0.041	242	0.041	264	0.036	203
DCP11	.399	0.917	0.259	40	0.095	24	0.045	74	0.054	354	0.032	332	0.043	292	0.035	243	0.022	273	0.017	204
DCP12	.501	0.684	0.215	44	0.072	6	0.030	91	0.037	335	0.014	312	0.032	276	0.029	216	0.011	269	0.018	182
DCP13	.600	0.535	0.166	51	0.059	336	0.024	124	0.038	302	0.018	236	0.037	249	0.038	193	0.008	232	0.025	164
DCP14	.701	0.456	0.129	67	0.051	313	0.031	120	0.031	295	0.012	190	0.018	230	0.018	169	0.005	333	0.014	133
DCP15	.800	0.265	0.128	44	0.063	297	0.007	68	0.036	267	0.012	182	0.018	226	0.011	186	0.002	270	0.012	117
DCP16	.900	0.008	0.123	19	0.047	287	0.020	68	0.027	256	0.006	272	0.014	215	0.005	187	0.005	294	0.010	131
DCP17	.969	-0.045	0.058	17	0.022	293	0.015	349	0.011	286	0.008	286	0.009	229	0.005	248	0.005	307	0.007	121

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ 0.0	DRIVE HZ 23.06	K 0.070	MACH NO 0.503	DEL.ALPHA 4.95	DEL.H 0.0	ALPHA.0 12.38	TEST POINT 12037.1	CYCLES ANALYSED 20
	V 168.8 (553.9)	Q 74109. (1547.8)	RN 0.79E 07	CN(MIN) -0.089	CN(MAX) 1.287	ALPHA.NMAX 11.61	AERO DAMP -0.00152	TDR 2.052	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		12.381	4.948	0	0.215	20	0.048	156	0.015	167	0.040	247	0.079	183	0.036	313	0.011	182	0.002	198
CN		0.984	0.166	89	0.030	103	0.050	122	0.030	145	0.013	121	0.018	132	0.006	21	0.002	284	0.007	152
CM		-0.023	0.058	200	0.008	108	0.014	181	0.005	239	0.006	177	0.006	247	0.003	179	0.003	147	0.001	354
DCP 1	.010	4.058	1.217	171	0.122	85	0.405	164	0.067	170	0.096	150	0.064	216	0.044	110	0.043	259	0.036	95
DCP 2	.020	3.766	1.229	172	0.105	92	0.458	170	0.082	216	0.115	172	0.092	238	0.042	142	0.061	273	0.023	134
DCP 3	.030	3.605	1.102	172	0.179	104	0.373	175	0.118	236	0.108	191	0.083	255	0.030	215	0.067	284	0.004	174
DCP 4	.049	3.102	1.121	173	0.037	238	0.385	172	0.242	253	0.029	172	0.105	255	0.058	356	0.040	271	0.041	20
DCP 5	.074	2.472	0.538	138	0.259	133	0.291	172	0.176	211	0.114	231	0.099	268	0.106	348	0.077	63	0.059	109
DCP 6	.099	2.232	0.402	128	0.117	127	0.178	146	0.124	160	0.119	173	0.073	195	0.040	232	0.025	241	0.020	339
DCP 7	.149	1.747	0.303	103	0.092	92	0.135	118	0.072	133	0.063	122	0.053	146	0.016	155	0.024	156	0.018	237
DCP 8	.200	1.464	0.278	103	0.152	103	0.128	117	0.091	138	0.059	135	0.065	157	0.021	175	0.039	179	0.027	205
DCP 9	.250	1.342	0.281	86	0.148	87	0.127	99	0.093	112	0.071	102	0.065	124	0.033	125	0.040	164	0.034	156
DCP10	.300	1.166	0.242	73	0.094	88	0.089	92	0.067	109	0.046	102	0.050	109	0.022	126	0.025	130	0.029	150
DCP11	.399	0.982	0.238	58	0.037	73	0.045	72	0.030	132	0.023	69	0.032	113	0.009	91	0.013	88	0.013	156
DCP12	.501	0.764	0.228	49	0.011	317	0.032	54	0.029	127	0.018	29	0.030	103	0.014	31	0.011	45	0.006	146
DCP13	.600	0.617	0.204	47	0.033	267	0.031	21	0.017	140	0.021	348	0.025	92	0.019	4	0.016	338	0.004	145
DCP14	.701	0.508	0.173	45	0.056	258	0.030	19	0.013	113	0.025	335	0.023	78	0.020	334	0.016	331	0.002	197
DCP15	.800	0.321	0.182	30	0.031	271	0.038	8	0.019	38	0.018	326	0.015	46	0.012	340	0.020	318	0.002	262
DCP16	.900	0.061	0.165	15	0.017	350	0.026	348	0.018	28	0.006	29	0.016	11	0.011	343	0.019	290	0.002	93
DCP17	.969	-0.019	0.080	14	0.011	11	0.015	22	0.007	53	0.008	60	0.006	93	0.008	36	0.016	304	0.002	51

209

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.01	0.070	0.500	4.96	0.0	17.33	12037.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
167.5	73266.	0.79E 07	-0.123	1.127	19.59	-0.00212	2.842	0.0
(549.4)	(1530.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		17.335	4.959	0	0.210	5	0.025	267	0.010	105	0.022	34	0.021	51	0.015	252	0.036	152	0.008	55
CN		0.972	0.152	88	0.006	106	0.011	241	0.009	307	0.004	291	0.005	228	0.008	283	0.003	222	0.001	49
CM		-0.066	0.052	209	0.012	260	0.004	44	0.001	91	0.001	52	0.001	348	0.001	87	0.003	318	0.001	139
DCP 1	.010	3.147	0.595	179	0.220	340	0.134	352	0.057	339	0.036	252	0.041	179	0.054	261	0.018	280	0.034	101
DCP 2	.020	2.939	0.450	175	0.195	327	0.116	8	0.036	26	0.017	306	0.028	167	0.055	291	0.027	294	0.020	139
DCP 3	.030	2.794	0.821	169	0.188	325	0.034	350	0.047	21	0.014	303	0.035	350	0.011	259	0.027	320	0.018	167
DCP 4	.049	2.184	0.483	158	0.134	266	0.033	40	0.002	355	0.031	24	0.017	298	0.026	336	0.039	306	0.013	126
DCP 5	.074	1.998	0.448	153	0.104	248	0.001	203	0.009	309	0.026	6	0.021	269	0.019	283	0.021	315	0.009	49
DCP 6	.099	1.868	0.375	143	0.089	235	0.022	223	0.009	269	0.014	302	0.024	234	0.011	298	0.020	308	0.002	41
DCP 7	.149	1.626	0.272	126	0.056	220	0.016	195	0.010	197	0.010	243	0.001	170	0.018	281	0.023	297	0.005	305
DCP 8	.200	1.449	0.208	119	0.055	235	0.017	324	0.019	315	0.014	272	0.006	319	0.011	301	0.023	305	0.021	15
DCP 9	.250	1.355	0.231	112	0.041	209	0.024	210	0.015	324	0.013	105	0.014	209	0.009	241	0.007	158	0.004	243
DCP10	.300	1.223	0.211	97	0.028	171	0.022	211	0.022	297	0.013	19	0.010	169	0.003	163	0.009	135	0.010	195
DCP11	.399	1.070	0.217	79	0.031	130	0.024	220	0.019	292	0.002	109	0.010	248	0.004	223	0.012	210	0.008	93
DCP12	.501	0.871	0.213	58	0.036	98	0.020	249	0.020	321	0.007	332	0.010	265	0.009	330	0.011	188	0.002	353
DCP13	.600	0.719	0.227	44	0.045	91	0.015	236	0.010	295	0.008	291	0.004	249	0.011	317	0.009	127	0.003	225
DCP14	.701	0.603	0.216	34	0.047	71	0.013	231	0.004	272	0.004	222	0.006	175	0.007	269	0.009	105	0.002	24
DCP15	.800	0.451	0.195	30	0.045	66	0.015	225	0.001	70	0.012	235	0.004	176	0.011	248	0.006	169	0.002	347
DCP16	.900	0.176	0.138	34	0.040	55	0.006	234	0.008	183	0.039	226	0.004	106	0.003	240	0.008	103	0.003	314
DCP17	.969	0.024	0.055	46	0.013	51	0.009	240	0.003	39	0.002	251	0.004	97	0.001	315	0.011	156	0.003	357

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	22.80	0.070	0.499	4.99	0.0	19.80	12037.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
166.8	72917.	0.79E 07	-0.136	1.145	21.63	-0.00234	3.115	0.0
(547.1)	(1522.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		19.801	4.995	0	0.218	12	0.047	260	0.006	177	0.023	38	0.024	63	0.023	209	0.043	165	0.003	354
CN		0.989	0.149	79	0.001	92	0.008	153	0.002	356	0.008	276	0.003	335	0.004	204	0.008	268	0.002	31
CM		-0.084	0.042	223	0.009	222	0.002	281	0.002	218	0.002	56	0.002	163	0.001	26	0.002	110	0.000	245
DCP 1	.010	2.711	0.701	167	0.126	63	0.025	110	0.056	295	0.069	12	0.032	217	0.031	190	0.037	295	0.019	33
DCP 2	.020	2.509	0.586	168	0.107	75	0.038	195	0.009	323	0.052	37	0.035	204	0.014	227	0.052	279	0.021	58
DCP 3	.030	2.384	0.693	162	0.169	271	0.067	121	0.039	290	0.022	75	0.027	211	0.015	263	0.017	237	0.003	211
DCP 4	.049	2.129	0.174	125	0.098	233	0.025	211	0.015	7	0.025	144	0.023	138	0.024	160	0.017	276	0.009	51
DCP 5	.074	1.971	0.188	122	0.099	231	0.019	254	0.024	297	0.014	149	0.018	174	0.014	163	0.030	247	0.010	139
DCP 6	.099	1.874	0.165	104	0.091	224	0.021	194	0.025	265	0.011	258	0.010	231	0.014	65	0.008	261	0.010	261
DCP 7	.149	1.628	0.145	98	0.057	199	0.024	225	0.016	218	0.015	326	0.009	271	0.007	16	0.023	276	0.016	66
DCP 8	.200	1.427	0.166	91	0.038	208	0.023	258	0.036	8	0.021	316	0.004	127	0.012	334	0.007	21	0.011	81
DCP 9	.250	1.347	0.186	95	0.040	210	0.015	239	0.014	141	0.017	261	0.004	141	0.009	259	0.007	168	0.007	353
DCP10	.300	1.232	0.186	85	0.026	198	0.012	147	0.012	150	0.017	290	0.005	52	0.005	193	0.012	182	0.005	270
DCP11	.399	1.106	0.198	75	0.008	34	0.018	121	0.008	94	0.017	289	0.011	23	0.009	202	0.012	235	0.010	309
DCP12	.501	0.927	0.192	63	0.021	52	0.015	105	0.006	65	0.011	287	0.012	0	0.003	355	0.000	301	0.003	271
DCP13	.600	0.789	0.191	55	0.026	48	0.008	119	0.007	60	0.012	257	0.011	9	0.008	192	0.005	283	0.004	163
DCP14	.701	0.673	0.189	46	0.041	37	0.009	77	0.010	23	0.009	240	0.007	356	0.009	217	0.011	300	0.003	247
DCP15	.800	0.517	0.177	44	0.043	50	0.008	149	0.008	342	0.008	219	0.010	306	0.006	172	0.011	282	0.006	87
DCP16	.900	0.213	0.120	53	0.029	28	0.008	115	0.007	352	0.008	176	0.009	293	0.006	219	0.010	294	0.005	52
DCP17	.969	0.043	0.054	67	0.010	2	0.002	121	0.002	338	0.004	224	0.002	335	0.001	82	0.011	284	0.002	66

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.09	0.069	0.512	5.03	0.0	10.45	12043.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
171.6	76326.	0.80E 07	-0.072	1.251	12.59	-0.00127	1.735	0.0
(562.9)	(1594.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		10.452	5.032	0	0.243	28	0.021	111	0.040	81	0.030	9	0.088	28	0.114	267	0.027	231	0.028	192
CN		0.872	0.155	49	0.118	53	0.047	88	0.034	24	0.020	7	0.024	315	0.016	239	0.006	249	0.007	221
CM		-0.012	0.032	217	0.023	102	0.002	142	0.011	97	0.003	68	0.007	61	0.004	7	0.002	351	0.002	317
DCP 1	.010	3.741	0.165	194	1.038	71	0.218	120	0.180	90	0.084	47	0.019	55	0.055	307	0.021	298	0.033	322
DCP 2	.020	3.339	0.098	247	1.095	80	0.170	126	0.301	86	0.121	87	0.033	76	0.063	17	0.033	240	0.048	318
DCP 3	.030	3.207	0.171	312	0.929	83	0.099	118	0.341	89	0.122	95	0.076	78	0.099	83	0.046	224	0.042	358
DCP 4	.049	2.743	0.232	174	0.786	82	0.214	142	0.355	84	0.049	139	0.189	68	0.062	176	0.061	64	0.049	142
DCP 5	.074	2.302	0.255	110	0.436	78	0.247	99	0.157	80	0.125	57	0.087	66	0.031	38	0.054	97	0.021	117
DCP 6	.099	2.056	0.207	93	0.340	67	0.163	95	0.126	47	0.092	22	0.077	6	0.048	338	0.028	5	0.030	346
DCP 7	.149	1.608	0.234	53	0.232	51	0.087	70	0.087	20	0.068	355	0.086	327	0.053	273	0.036	297	0.035	274
DCP 8	.200	1.354	0.265	48	0.194	51	0.046	66	0.086	20	0.067	9	0.088	338	0.053	288	0.031	300	0.033	282
DCP 9	.250	1.221	.053	40	0.181	44	0.093	47	0.091	359	0.071	344	0.078	312	0.054	272	0.039	278	0.041	258
DCP10	.300	1.050	.047	39	0.133	38	0.070	52	0.072	354	0.058	336	0.068	294	0.044	242	0.028	261	0.031	231
DCP11	.399	0.858	0.236	41	0.085	26	0.039	75	0.043	343	0.021	349	0.045	297	0.034	226	0.014	228	0.020	203
DCP12	.501	0.647	3.197	43	0.061	10	0.030	82	0.035	321	0.010	316	0.029	276	0.023	221	0.013	208	0.013	172
DCP13	.600	0.518	0.162	51	0.049	345	0.030	110	0.029	308	0.003	195	0.018	260	0.016	196	0.007	179	0.011	137
DCP14	.701	0.435	0.122	67	0.050	317	0.028	124	0.023	297	0.006	221	0.019	244	0.015	170	0.009	147	0.011	121
DCP15	.800	0.261	0.114	40	0.052	300	0.008	142	0.026	280	0.007	202	0.023	234	0.015	155	0.007	165	0.011	97
DCP16	.900	0.009	0.112	21	0.045	296	0.018	322	0.020	262	0.012	257	0.016	208	0.009	177	0.008	115	0.005	102
DCP17	.969	-0.039	0.056	12	0.021	302	0.014	333	0.010	265	0.008	286	0.005	228	0.003	195	0.002	166	0.002	231

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.07	0.069	0.508	4.97	0.0	12.31	12043.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
170.0	75368.	0.80E 07	-0.075	1.276	11.96	-0.00160	2.172	0.0
(557.7)	(1574.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		12.307	4.965	0	0.239	19	0.069	204	0.014	224	0.014	184	0.044	211	0.040	151	0.032	142	0.009	0
CN		0.948	0.165	94	0.046	92	0.046	115	0.033	141	0.018	96	0.012	136	0.006	102	0.007	140	0.004	100
CM		-0.018	0.052	203	0.009	107	0.014	182	0.004	244	0.006	193	0.005	239	0.002	236	0.002	225	0.001	214
DCP 1	.010	4.135	1.010	168	0.220	67	0.322	166	0.038	157	0.085	167	0.034	223	0.041	193	0.002	193	0.009	158
DCP 2	.020	3.746	1.124	174	0.255	85	0.403	174	0.052	162	0.100	181	0.054	262	0.063	213	0.028	279	0.029	199
DCP 3	.030	3.610	0.927	177	0.234	91	0.374	176	0.059	220	0.118	192	0.059	265	0.068	207	0.027	317	0.023	226
DCP 4	.049	2.950	1.192	171	0.112	87	0.398	169	0.204	244	0.023	177	0.107	249	0.045	346	0.041	256	0.054	5
DCP 5	.074	2.360	0.633	146	0.301	123	0.259	165	0.141	202	0.085	211	0.138	268	0.088	348	0.045	59	0.041	75
DCP 6	.099	2.107	0.472	138	0.183	108	0.156	130	0.113	151	0.085	157	0.070	205	0.058	217	0.056	246	0.020	311
DCP 7	.149	1.704	0.303	108	0.149	89	0.116	113	0.087	137	0.061	116	0.049	148	0.015	152	0.035	194	0.018	187
DCP 8	.200	1.446	0.259	95	0.143	92	0.091	116	0.090	139	0.060	121	0.067	142	0.022	166	0.022	165	0.013	246
DCP 9	.250	1.309	0.253	77	0.126	89	0.097	98	0.090	118	0.062	89	0.057	128	0.040	127	0.049	150	0.029	155
DCP10	.300	1.149	0.250	66	0.081	84	0.081	92	0.073	115	0.052	84	0.043	116	0.033	114	0.033	130	0.027	133
DCP11	.399	0.949	0.224	59	0.041	88	0.054	78	0.063	127	0.036	70	0.025	114	0.022	99	0.025	120	0.016	90
DCP12	.501	0.723	0.203	52	0.006	107	0.050	55	0.018	112	0.024	34	0.021	81	0.011	27	0.013	95	0.010	50
DCP13	.600	0.571	0.183	53	0.026	265	0.034	41	0.014	151	0.019	25	0.012	75	0.008	24	0.006	19	0.002	303
DCP14	.701	0.471	0.152	56	0.047	267	0.032	12	0.011	154	0.021	357	0.010	65	0.002	0	0.015	16	0.010	304
DCP15	.800	0.347	0.166	38	0.028	294	0.036	359	0.015	81	0.014	10	0.017	60	0.010	70	0.008	14	0.006	72
DCP16	.900	0.049	0.148	21	0.021	359	0.032	349	0.017	42	0.009	4	0.013	8	0.005	20	0.004	288	0.004	5
DCP17	.969	-0.025	0.071	19	0.013	33	0.015	2	0.010	51	0.005	58	0.006	38	0.001	16	0.002	243	0.001	247

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.07	0.069	0.506	4.91	0.0	14.97	12043.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
169.4	74990.	0.80E 07	-0.102	1.191	11.61	-0.00189	2.555	0.0
(555.7)	(1566.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		14.970	4.911 0	0.236 2	0.023 254	0.025 256	0.038 3	0.040 34	0.046 187	0.014 151	0.005 37
CN		0.479	0.173 102	0.050 214	0.031 267	0.007 194	0.010 224	0.001 294	0.003 178	0.001 71	0.001 77
CM		-0.036	0.065 200	0.012 254	0.005 54	0.005 282	0.004 339	0.001 11	0.001 325	0.001 251	0.000 219
DCP 1	.010	3.732	1.236 168	0.179 274	0.138 76	0.098 241	0.009 282	0.032 213	0.016 2	0.024 332	0.015 149
DCP 2	.020	3.432	1.316 173	0.345 270	0.091 68	0.145 264	0.029 355	0.027 171	0.023 263	0.008 0	0.025 207
DCP 3	.030	3.298	1.335 175	0.320 263	0.062 335	0.164 267	0.109 349	0.026 114	0.015 38	0.021 146	0.058 192
DCP 4	.049	2.794	1.112 169	0.603 263	0.198 356	0.025 200	0.060 322	0.056 97	0.059 191	0.038 249	0.012 13
DCP 5	.074	2.353	0.723 157	0.317 241	0.114 320	0.023 259	0.036 279	0.015 340	0.011 169	0.029 187	0.022 255
DCP 6	.099	2.080	0.511 146	0.201 221	0.062 280	0.025 224	0.026 258	0.015 333	0.010 23	0.018 120	0.017 191
DCP 7	.149	1.703	0.300 120	0.102 191	0.032 219	0.034 195	0.031 238	0.018 252	0.004 337	0.012 69	0.008 56
DCP 8	.200	1.482	0.307 126	0.124 214	0.081 271	0.032 352	0.001 66	0.006 73	0.012 265	0.002 287	0.006 149
DCP 9	.250	1.390	0.302 114	0.130 186	0.098 247	0.024 321	0.003 270	0.012 53	0.012 210	0.010 263	0.012 71
DCP10	.300	1.220	0.246 96	0.106 171	0.087 245	0.017 256	0.023 253	0.014 1	0.013 134	0.010 298	0.011 19
DCP11	.399	1.020	0.233 75	0.070 158	0.051 239	0.019 209	0.034 248	0.014 337	0.001 84	0.013 27	0.010 16
DCP12	.501	0.786	0.225 51	0.040 135	0.026 251	0.024 157	0.029 206	0.018 269	0.006 289	0.010 318	0.007 325
DCP13	.600	0.621	0.223 42	0.012 130	0.026 273	0.020 109	0.024 177	0.008 229	0.007 122	0.008 177	0.004 54
DCP14	.701	0.512	0.219 33	0.009 26	0.019 287	0.031 96	0.021 139	0.009 162	0.008 116	0.009 127	0.006 205
DCP15	.800	0.356	0.222 24	0.025 32	0.016 259	0.019 105	0.013 139	0.005 132	0.006 152	0.010 57	0.004 196
DCP16	.900	0.108	0.154 26	0.029 45	0.011 199	0.006 90	0.006 86	0.008 110	0.005 249	0.006 79	0.003 55
DCP17	.969	0.006	0.063 33	0.019 67	0.006 231	0.002 277	0.000 73	0.004 182	0.002 178	0.004 85	0.005 86

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.25	0.134	0.511	5.52	0.0	0.03	12039.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
171.5	76316.	0.80E 07	-0.046	0.607	5.41	-0.00073	1.018	0.0
(562.7)	(1593.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.028	5.518 0	0.267 3	0.082 292	0.049 328	0.010 65	0.011 51	0.037 177	0.015 170	0.001 155
CN		0.129	0.443 354	0.011 10	0.004 281	0.010 338	0.002 291	0.001 307	0.000 87	0.001 82	0.002 86
CM		-0.016	0.023 298	0.003 331	0.001 54	0.006 159	0.000 94	0.000 208	0.000 50	0.000 335	0.000 34
DCP 1	.010	-0.662	3.161 342	0.089 301	0.210 292	0.200 6	0.134 63	0.053 123	0.019 42	0.032 90	0.021 148
DCP 2	.020	-0.351	2.500 347	0.078 349	0.019 264	0.017 288	0.023 10	0.028 135	0.051 216	0.038 313	0.030 16
DCP 3	.030	-0.126	2.236 346	0.120 20	0.075 128	0.003 199	0.046 282	0.012 3	0.010 140	0.016 296	0.022 352
DCP 4	.049	0.175	1.831 347	0.082 0	0.063 117	0.074 178	0.045 258	0.030 321	0.020 45	0.011 91	0.003 317
DCP 5	.074	0.321	1.449 347	0.056 342	0.014 86	0.039 154	0.023 245	0.018 300	0.012 2	0.009 70	0.005 132
DCP 6	.099	0.391	1.223 348	0.041 329	0.017 327	0.026 147	0.004 208	0.007 270	0.003 344	0.008 60	0.002 106
DCP 7	.149	0.273	0.896 349	0.027 334	0.000 322	0.014 135	0.001 182	0.004 277	0.001 315	0.004 316	0.004 97
DCP 8	.200	0.214	0.731 355	0.019 353	0.011 315	0.015 146	0.003 321	0.002 278	0.002 279	0.004 54	0.003 130
DCP 9	.250	0.199	0.631 352	0.017 14	0.009 307	0.019 332	0.001 276	0.003 255	0.005 186	0.003 297	0.003 92
DCP10	.300	0.190	0.530 3?	0.018 359	0.004 340	0.018 316	0.003 119	0.005 281	0.004 116	0.007 241	0.007 87
DCP11	.399	0.171	0.426 2	0.013 33	0.008 309	0.021 339	0.002 137	0.000 195	0.003 208	0.002 160	0.002 100
DCP12	.501	0.125	0.317 6	0.008 69	0.005 338	0.019 346	0.001 275	0.002 143	0.003 130	0.003 124	0.002 114
DCP13	.600	0.166	0.241 11	0.010 80	0.003 261	0.019 338	0.003 329	0.003 224	0.003 50	0.005 58	0.001 175
DCP14	.701	0.210	0.169 14	0.012 95	0.002 249	0.018 339	0.003 311	0.001 0	0.003 316	0.004 106	0.003 34
DCP15	.800	0.100	0.098 26	0.011 153	0.008 233	0.025 334	0.002 10	0.004 44	0.002 134	0.004 166	0.003 251
DCP16	.900	-0.091	0.034 75	0.016 185	0.009 227	0.017 329	0.007 277	0.003 303	0.001 326	0.004 298	0.002 41
DCP17	.969	-0.045	0.029 162	0.008 191	0.007 195	0.016 4	0.005 204	0.001 122	0.004 297	0.000 320	0.003 223

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.27	0.136	0.506	5.49	0.0	2.48	12039.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
169.4	74990.	0.80E 07	-0.034	0.871	7.95	-0.00072	0.987	0.0
(555.9)	(1566.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.480	5.494 0	0.265 6	0.088 294	0.052 140	0.017 48	0.025 58	0.012 240	0.026 143	0.003 290
CN		0.387	0.485 353	0.022 0	0.005 325	0.008 131	0.000 296	0.002 146	0.002 318	0.002 339	0.001 4
CM		-0.008	0.023 301	0.003 251	0.001 132	0.004 320	0.000 249	0.001 248	0.001 147	0.001 155	0.000 201
DCP 1	.010	1.118	3.370 341	0.136 291	0.106 115	0.021 358	0.010 237	0.015 337	0.020 250	0.012 150	0.015 17
DCP 2	.020	1.058	2.678 346	0.164 283	0.100 148	0.094 42	0.063 307	0.031 199	0.003 337	0.030 198	0.033 79
DCP 3	.030	1.085	2.212 346	0.093 301	0.026 150	0.060 40	0.082 304	0.088 202	0.075 103	0.055 358	0.043 265
DCP 4	.049	1.176	1.867 346	0.067 315	0.049 316	0.035 226	0.327 118	0.021 27	0.021 269	0.019 193	0.008 69
DCP 5	.074	1.120	1.498 347	0.058 326	0.022 306	0.009 255	0.007 116	0.005 145	0.006 233	0.005 185	0.001 273
DCP 6	.099	1.044	1.236 348	0.054 347	0.023 319	0.010 288	0.004 196	0.003 171	0.004 290	0.010 162	0.001 93
DCP 7	.149	0.755	0.898 349	0.044 357	0.017 323	0.004 291	0.004 123	0.002 142	0.001 279	0.006 139	0.003 153
DCP 8	.200	0.604	0.734 354	0.037 12	0.014 326	0.009 310	0.004 144	0.001 4	0.004 271	0.010 291	0.003 36
DCP 9	.250	0.514	0.625 352	0.034 16	0.011 326	0.013 136	0.002 19	0.003 107	0.001 244	0.002 86	0.003 358
DCP10	.300	0.464	0.570 353	0.033 14	0.009 310	0.009 126	0.002 138	0.001 238	0.001 11	0.005 70	0.003 217
DCP11	.399	0.388	0.416 3	0.026 20	0.006 354	0.017 139	0.002 131	0.002 76	0.002 322	0.005 12	0.002 345
DCP12	.501	0.288	0.313 5	0.025 31	0.003 355	0.012 134	0.002 228	0.001 16	0.004 315	0.005 11	0.003 1
DCP13	.600	0.267	0.241 10	0.021 39	0.001 294	0.010 138	0.003 132	0.001 276	0.002 348	0.006 345	0.001 337
DCP14	.701	0.292	0.161 15	0.015 40	0.004 344	0.013 139	0.001 288	0.004 116	0.005 314	0.003 308	0.001 255
DCP15	.800	0.140	0.092 26	0.010 45	0.001 281	0.016 137	0.001 294	0.004 115	0.004 321	0.006 310	0.004 36
DCP16	.900	-0.085	0.030 45	0.003 284	0.003 21	0.010 130	0.004 39	0.004 28	0.002 337	0.004 222	0.001 191
DCP17	.969	-0.058	0.025 176	0.002 196	0.009 235	0.015 137	0.005 302	0.001 135	0.003 346	0.006 53	0.006 32

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.34	0.136	0.506	5.50	0.0	4.89	12039.3	20

V	Q	RN	CNMIN)	CNMAX)	ALPHA.NMAX	AERO DAMP	TOR	EXT DAMP
169.3	75009.	0.80E 07	-0.029	1.096	10.33	-0.00090	1.235	0.0
(555.6)	(1566.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.892	5.502 0	0.261 10	0.113 294	0.048 358	0.033 56	0.019 91	0.010 232	0.018 120	0.004 229
CN		0.620	0.459 359	0.047 344	0.007 201	0.011 11	0.005 194	0.004 84	0.003 333	0.002 272	0.001 127
CM		-0.000	0.031 308	0.004 219	0.003 288	0.005 183	0.002 26	0.001 277	0.001 159	0.001 124	0.000 327
DCP 1	.010	2.523	2.960 343	0.216 11	0.205 300	0.110 184	0.053 352	0.078 192	0.041 70	0.011 205	0.020 34
DCP 2	.020	2.372	2.741 349	0.176 302	0.006 316	0.125 226	0.056 107	0.043 227	0.066 115	0.021 358	0.021 103
DCP 3	.030	2.310	2.478 348	0.214 282	0.022 306	0.108 232	0.103 125	0.027 9	0.049 120	0.061 14	0.022 282
DCP 4	.049	2.097	1.895 352	0.262 341	0.197 274	0.160 192	0.137 102	0.095 4	0.044 238	0.038 66	0.055 288
DCP 5	.074	1.799	1.417 353	0.221 341	0.138 241	0.088 128	0.049 38	0.024 21	0.044 319	0.040 225	0.016 167
DCP 6	.099	1.599	1.148 353	0.140 347	0.067 225	0.067 99	0.063 0	0.040 275	0.025 226	0.028 166	0.021 91
DCP 7	.149	1.168	0.844 354	0.074 344	0.026 177	0.035 41	0.030 297	0.019 206	0.007 76	0.001 187	0.002 217
DCP 8	.200	0.988	0.732 358	0.048 305	0.053 126	0.052 14	0.041 272	0.024 165	0.010 66	0.003 330	0.006 316
DCP 9	.250	0.851	0.634 355	0.035 263	0.063 94	0.071 344	0.053 223	0.039 111	0.024 6	0.011 272	0.008 183
DCP10	.300	0.733	0.507 357	0.024 314	0.036 82	0.044 333	0.031 201	0.024 82	0.017 330	0.012 220	0.011 95
DCP11	.399	0.593	0.390 9	0.033 2	0.015 92	0.024 355	0.015 210	0.013 72	0.009 307	0.002 31	0.002 82
DCP12	.501	0.434	0.289 15	0.040 7	0.004 112	0.013 4	0.005 190	0.006 58	0.005 284	0.002 20	0.004 43
DCP13	.600	0.364	0.207 26	0.045 12	0.008 203	0.013 41	0.008 190	0.006 44	0.004 1	0.002 345	0.001 302
DCP14	.701	0.344	0.134 44	0.051 16	0.012 224	0.014 35	0.003 173	0.003 87	0.002 294	0.003 281	0.001 45
DCP15	.800	0.167	0.086 60	0.031 10	0.006 211	0.015 19	0.005 170	0.005 197	0.002 344	0.005 292	0.006 162
DCP16	.900	-0.073	0.040 62	0.006 301	0.005 100	0.010 344	0.003 155	0.003 21	0.003 119	0.004 281	0.002 172
DCP17	.969	-0.086	0.046 137	0.014 264	0.008 108	0.011 318	0.004 153	0.003 354	0.002 24	0.006 12	0.003 247

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.20	0.137	0.505	5.45	0.0	7.47	12039.4	20

V	Q	RN	CNMIN)	CNMAX)	ALPHA.NMAX	AERO DAMP	TOR	EXT DAMP
168.7	74693.	0.80E 07	-0.057	1.297	12.47	-0.00070	0.942	0.0
(553.6)	(1560.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.470	5.434 0	0.294 26	0.183 314	0.122 119	0.015 43	0.015 85	0.011 240	0.009 194	0.011 274
CN		0.741	0.364 24	0.138 3	0.038 261	0.020 159	0.005 79	0.006 313	0.005 209	0.003 147	0.002 67
CM		-0.002	0.023 255	0.022 62	0.019 332	0.006 263	0.002 215	0.002 156	0.001 67	0.001 230	0.000 155
DCP 1	.010	3.247	1.614 352	0.874 57	0.546 336	0.119 240	0.027 1	0.029 280	0.026 210	0.033 77	0.058 336
DCP 2	.020	2.913	1.539 1	0.713 62	0.585 351	0.222 260	0.062 31	0.107 282	0.039 231	0.043 183	0.066 16
DCP 3	.030	2.728	1.340 1	0.619 59	0.539 354	0.276 273	0.018 297	0.159 261	0.086 170	0.035 257	0.021 176
DCP 4	.049	2.375	0.927 20	0.756 41	0.348 331	0.095 304	0.081 288	0.084 269	0.089 223	0.059 183	0.031 188
DCP 5	.074	2.105	0.795 22	0.607 33	0.289 316	0.067 252	0.053 279	0.077 235	0.057 188	0.050 178	0.043 149
DCP 6	.099	1.864	0.678 23	0.474 26	0.232 297	0.091 202	0.027 183	0.050 178	0.054 122	0.032 94	0.033 67
DCP 7	.149	1.426	0.653 23	0.355 1	0.194 260	0.105 161	0.027 110	0.032 129	0.041 69	0.024 24	0.021 344
DCP 8	.200	1.184	0.606 27	0.292 356	0.161 255	0.082 168	0.037 136	0.043 101	0.033 34	0.020 322	0.019 4
DCP 9	.250	0.995	0.549 16	0.183 337	0.085 270	0.046 137	0.025 136	0.036 60	0.028 339	0.021 277	0.016 220
DCP10	.300	0.868	0.477 17	0.153 329	0.073 203	0.036 117	0.018 133	0.026 45	0.016 309	0.008 249	0.005 175
DCP11	.399	0.710	0.402 20	0.136 332	0.070 204	0.040 129	0.016 111	0.026 31	0.023 289	0.011 185	0.005 131
DCP12	.501	0.525	0.313 33	0.106 327	0.060 185	0.037 106	0.016 48	0.020 336	0.015 230	0.011 131	0.004 47
DCP13	.600	0.429	0.241 42	0.080 324	0.053 167	0.021 95	0.010 60	0.017 331	0.012 226	0.007 106	0.006 103
DCP14	.701	0.382	0.173 50	0.063 324	0.051 153	0.019 60	0.010 350	0.012 297	0.007 184	0.004 88	0.004 68
DCP15	.800	0.206	0.123 53	0.050 294	0.044 146	0.013 72	0.007 25	0.013 289	0.003 181	0.004 74	0.003 350
DCP16	.900	-0.043	0.077 31	0.052 260	0.033 130	0.008 105	0.009 5	0.011 262	0.010 138	0.009 5	0.003 215
DCP17	.969	-0.058	0.010 28	0.030 257	0.016 133	0.009 156	0.008 1	0.006 235	0.001 68	0.002 33	0.005 308

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	45.35	0.138	0.501	5.33	0.0	9.94	12039.5	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
167.0	73142.	0.79E 07	-0.134	1.454	14.14	-2.00107	1.449	0.0
(549.0)	(1527.6)							

HARMONIC ANALYSIS

DATA TYPE	K/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		9.936	5.330	0	0.313	38	0.144	352	0.194	209	0.011	149	0.036	77	0.012	220	0.009	138	0.021	238
CN		0.876	0.354	53	0.149	15	0.040	341	0.036	249	0.015	176	0.010	109	0.007	73	0.006	12	0.003	258
CM		-0.015	0.049	223	0.038	101	0.012	53	0.017	16	0.009	305	0.004	274	0.002	234	0.002	168	0.001	66
DCP 1	.010	3.725	0.303	33	1.181	71	0.206	0	0.115	85	0.013	355	0.024	74	0.034	344	0.063	266	0.040	218
DCP 2	.020	3.298	0.473	41	1.076	81	0.307	14	0.214	97	0.093	352	0.092	109	0.024	30	0.024	318	0.034	238
DCP 3	.030	3.066	0.438	41	0.888	84	0.373	33	0.186	74	3.141	7	0.129	91	0.094	9	0.030	116	0.004	267
DCP 4	.049	2.734	0.602	76	0.714	63	0.185	57	0.120	64	0.105	57	0.084	47	0.076	44	0.050	62	0.044	38
DCP 5	.074	2.387	0.584	74	0.577	55	0.156	44	0.123	31	0.066	17	0.079	33	0.067	24	0.064	31	0.059	16
DCP 6	.099	2.081	0.519	71	0.449	45	0.112	19	0.119	344	0.079	296	0.036	317	0.040	299	0.034	330	0.054	293
DCP 7	.149	1.621	0.567	57	0.356	23	0.110	354	0.149	312	0.096	261	0.055	259	0.045	225	0.019	250	0.050	226
DCP 8	.200	1.338	0.545	57	0.294	22	0.100	350	0.141	309	0.078	262	0.044	260	0.042	231	0.033	223	0.031	195
DCP 9	.250	1.166	0.519	49	0.234	2	0.082	332	0.105	276	0.066	216	0.035	206	0.037	165	0.024	147	0.026	126
DCP10	.300	1.037	0.476	47	0.207	356	0.082	323	0.101	259	0.057	190	0.021	176	0.026	142	0.013	114	0.013	121
DCP11	.399	0.857	0.439	53	0.172	353	0.059	326	0.086	259	0.045	196	0.023	178	0.027	142	0.017	113	0.015	88
DCP12	.501	0.654	0.374	51	0.134	338	0.042	307	0.082	238	0.047	165	0.029	143	0.031	102	0.023	44	0.013	6
DCP13	.600	0.535	0.332	55	0.128	322	0.028	285	0.069	219	0.046	138	0.025	104	0.026	67	0.021	6	0.010	307
DCP14	.701	0.462	0.269	58	0.121	302	0.031	216	0.062	193	0.038	104	0.023	92	0.024	33	0.015	329	0.010	285
DCP15	.800	0.278	0.224	44	0.119	287	0.036	226	0.070	176	0.035	87	0.023	69	0.018	350	0.012	338	0.008	255
DCP16	.900	0.012	0.160	24	0.084	281	0.043	235	0.057	156	0.024	87	0.023	44	0.013	316	0.011	286	0.007	187
DCP17	.969	-0.046	0.065	24	0.044	288	0.021	251	0.032	163	0.013	103	0.009	57	0.004	56	0.007	331	0.006	258

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	45.65	0.136	0.506	5.23	0.0	12.01	12041.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
170.4	75325.	0.80E 07	-0.153	1.492	13.97	-0.00138	1.905	0.0
(559.2)	(1573.2)							

HARMONIC ANALYSIS

DATA TYPE	K/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		12.014	5.227	0	0.170	32	0.188	91	0.123	224	0.045	324	0.006	216	0.008	77	0.017	190	0.016	33
CN		0.954	0.337	72	0.090	55	0.065	42	0.021	0	0.026	308	0.036	268	0.007	291	0.002	248	0.005	357
CM		-0.030	0.070	213	0.021	130	0.023	147	0.007	124	0.011	96	0.004	41	0.002	41	0.001	336	0.000	206
DCP 1	.010	3.937	0.477	161	0.607	81	0.191	138	0.076	87	0.048	162	0.012	72	0.036	158	0.034	187	0.028	144
DCP 2	.020	3.552	0.748	156	0.612	92	0.261	151	0.062	105	0.059	199	0.019	28	0.051	191	0.035	263	0.055	209
DCP 3	.030	3.204	0.628	156	0.752	99	0.323	148	0.106	206	0.022	356	0.047	48	0.044	159	0.050	211	0.036	247
DCP 4	.049	2.780	0.801	123	0.359	104	0.257	147	0.103	190	0.073	211	0.075	275	0.046	302	0.029	344	0.020	1
DCP 5	.074	2.446	0.710	114	0.324	86	0.245	125	0.069	145	0.061	177	0.058	258	0.049	265	0.065	312	0.042	345
DCP 6	.099	2.144	0.591	108	0.270	72	0.208	100	0.063	64	0.055	107	0.021	130	0.030	166	0.028	213	0.013	254
DCP 7	.149	1.692	0.546	84	0.216	65	0.214	76	0.070	34	0.060	65	0.027	64	0.028	77	0.007	223	0.007	177
DCP 8	.200	1.409	0.492	80	0.184	66	0.171	68	0.062	30	0.061	30	0.008	44	0.009	69	0.031	148	0.013	92
DCP 9	.250	1.288	0.486	70	0.142	58	0.172	49	0.073	16	0.060	6	0.036	16	0.035	3	0.028	21	0.020	15
DCP10	.300	1.127	0.453	64	0.112	50	0.144	38	0.055	358	0.047	344	0.021	358	0.017	330	0.016	39	0.026	13
DCP11	.399	0.949	0.430	63	0.090	47	0.122	25	0.035	14	0.048	343	0.025	309	0.022	298	0.011	29	0.013	0
DCP12	.501	0.744	0.391	58	0.059	17	0.098	10	0.042	335	0.066	311	0.026	268	0.016	259	0.011	296	0.005	343
DCP13	.600	0.622	0.343	56	0.058	347	0.090	352	0.025	324	0.066	295	0.022	244	0.021	250	0.013	252	0.003	219
DCP14	.701	0.527	0.305	53	0.063	314	0.077	331	0.028	282	0.056	262	0.014	198	0.015	240	0.010	179	0.004	337
DCP15	.800	0.349	0.288	40	0.080	317	0.078	312	0.027	279	0.065	252	0.022	205	0.012	157	0.010	192	0.003	191
DCP16	.900	0.065	0.207	26	0.064	333	0.054	03	0.070	300	0.034	229	0.015	195	0.013	156	0.007	122	0.001	62
DCP17	.969	-0.017	0.087	26	0.036	353	0.032	320	0.008	327	3.019	248	0.007	209	0.006	194	3.007	47	0.004	66

215

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	45.45	0.137	0.504	5.23	0.0	14.79	12041.2	20

V	Q	RN	CNR(MIN)	CNR(MAX)	ALPHA.HMAX	AERO DAMP	TDR	EXT DAMP
169.1	74593.	0.80E 07	-0.154	1.499	14.93	-0.00171	2.350	0.0
(554.8)	(1557.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		14.790	5.226 0	0.164 2	0.001 176	0.069 124	0.046 62	0.028 87	0.011 239	0.029 106	0.003 266
CN		0.983	0.345 88	0.073 113	0.039 103	0.018 107	0.021 100	0.011 99	0.006 52	0.001 147	0.008 33
CM		-0.041	0.007 210	0.019 222	0.015 192	0.010 221	0.006 230	0.004 200	0.001 201	0.001 239	0.001 191
DCP 1	.010	3.832	1.463 160	0.003 120	0.213 174	0.064 199	0.021 350	0.017 311	0.032 287	0.019 236	0.027 80
DCP 2	.020	3.635	1.390 171	0.113 195	0.250 179	0.074 236	0.020 49	0.024 334	0.031 65	0.012 65	0.037 99
DCP 3	.030	3.301	1.448 173	0.080 171	0.182 175	0.121 262	0.020 350	0.020 312	0.059 66	0.015 144	0.026 87
DCP 4	.049	2.704	1.362 156	0.292 235	0.071 175	0.041 301	0.029 9	0.077 37	0.030 101	0.045 88	0.019 132
DCP 5	.074	2.307	0.904 139	0.270 184	0.193 199	0.100 294	0.051 72	0.048 112	0.018 175	0.023 250	0.020 25
DCP 6	.099	2.069	0.798 128	0.196 150	0.203 156	0.119 228	0.021 337	0.034 65	0.015 195	0.007 154	
DCP 7	.149	1.686	0.632 105	0.177 135	0.160 127	0.110 166	0.040 200	0.012 231	0.025 315	0.019 344	0.014 47
DCP 8	.200	1.475	0.552 98	0.189 136	0.162 135	0.098 166	0.005 191	0.015 236	0.015 286	0.009 252	0.012 58
DCP 9	.250	1.326	0.532 84	0.180 119	0.122 107	0.087 128	0.074 155	0.037 164	0.010 174	0.016 273	0.011 30
DCP10	.300	1.175	0.476 76	0.159 110	0.005 92	0.084 121	0.060 130	0.035 146	0.010 96	0.012 167	0.014 318
DCP11	.399	0.994	0.429 70	0.121 111	0.064 74	0.050 98	0.055 122	0.026 103	0.013 86	0.003 31	0.017 16
DCP12	.501	0.797	0.390 60	0.090 87	0.043 41	0.042 78	0.035 97	0.025 63	0.006 62	0.004 100	0.010 351
DCP13	.600	0.663	0.384 55	0.066 77	0.043 25	0.039 46	0.034 79	0.023 49	0.010 97	0.005 147	0.009 64
DCP14	.701	0.562	0.369 50	0.053 42	7.047 359	0.039 31	0.026 53	0.023 15	0.009 35	0.005 75	0.009 32
DCP15	.800	0.392	0.326 39	0.066 28	0.052 6	0.036 17	0.023 23	0.016 8	0.009 34	0.003 298	0.009 73
DCP16	.900	0.110	0.218 33	0.075 27	0.044 19	0.030 16	0.024 12	0.019 14	0.012 329	0.003 118	0.006 320
DCP17	.969	0.002	0.096 39	0.044 35	0.023 28	0.018 29	0.015 45	0.013 343	0.004 332	0.009 6	0.004 351

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	45.44	0.138	0.503	5.27	0.0	17.27	12041.3	20

V	Q	RN	CNR(MIN)	CNR(MAX)	ALPHA.HMAX	AERO DAMP	TDR	EXT DAMP
168.4	74095.	0.79E 07	-0.155	1.377	15.76	-0.00210	2.874	0.0
(552.5)	(1547.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		17.266	5.267 0	0.195 357	0.098 270	0.050 108	0.034 38	0.013 93	0.022 237	0.019 167	0.005 332
CN		0.994	0.325 87	0.048 145	0.026 154	0.010 14	0.003 267	0.002 116	0.006 332	0.001 145	0.003 310
CM		-0.061	0.003 220	0.023 241	0.009 295	0.004 308	0.001 22	0.001 348	0.003 133	0.001 285	0.001 103
DCP 1	.010	3.131	1.247 163	0.077 238	0.040 6	0.040 73	0.017 310	0.038 73	0.009 233	0.034 212	0.005 180
DCP 2	.020	3.045	1.183 166	0.206 237	0.102 18	0.046 99	0.022 49	0.012 109	0.014 261	0.018 280	0.007 28
DCP 3	.030	2.911	1.258 169	0.340 272	0.074 356	0.075 70	0.061 130	0.020 103	0.051 177	0.035 311	0.012 4
DCP 4	.049	2.470	0.865 151	0.363 251	0.094 356	0.057 44	0.039 187	0.022 190	0.020 309	0.003 133	0.015 50
DCP 5	.074	2.185	0.630 135	0.263 224	0.034 267	0.014 340	0.024 8	0.025 130	0.015 262	0.011 313	0.009 319
DCP 6	.099	1.998	0.553 120	0.207 209	0.026 243	0.024 287	0.031 6	0.025 92	0.017 136	0.008 350	0.009 23
DCP 7	.149	1.701	0.487 101	0.183 182	0.051 199	0.016 202	0.022 252	0.012 324	0.005 351	0.008 43	0.012 50
DCP 8	.200	1.470	0.432 107	0.161 178	0.062 230	0.035 314	0.026 358	0.022 22	0.010 171	0.015 295	0.012 246
DCP 9	.250	1.370	0.445 96	0.149 156	0.055 190	0.018 189	0.010 357	0.011 39	0.016 71	0.012 184	0.014 157
DCP10	.300	1.227	0.418 87	0.129 140	0.077 177	0.022 201	0.020 282	0.014 8	0.008 9	0.005 248	0.004 214
DCP11	.399	1.066	0.415 79	0.111 131	0.067 179	0.019 236	0.013 260	0.010 295	0.019 24	0.010 189	0.004 290
DCP12	.501	0.861	0.400 65	0.099 106	0.065 153	0.029 187	0.020 206	0.017 258	0.034 357	0.008 122	0.014 73
DCP13	.600	0.714	0.384 58	0.085 81	0.048 127	0.023 163	0.014 181	0.012 183	0.022 327	0.010 151	0.018 306
DCP14	.701	0.598	0.360 48	0.074 52	0.029 91	0.022 125	0.007 109	0.015 159	0.017 307	0.007 65	0.013 314
DCP15	.800	0.453	0.330 46	0.084 44	0.036 87	0.026 97	0.008 27	0.011 113	0.013 270	0.009 39	0.005 240
DCP16	.900	0.170	0.227 48	0.056 37	0.031 66	0.012 104	0.006 205	0.006 111	0.007 233	0.004 127	0.005 265
DCP17	.969	0.027	0.097 58	0.027 41	0.018 100	0.015 122	0.005 28	0.005 84	0.013 266	0.002 99	0.006 212

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.67	0.138	0.503	5.26	0.0	19.82	12041.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
168.2	74066.	0.79E 07	-0.160	1.299	20.30	-0.00224	3.064	0.0
(551.9)	(1546.9)							

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		19.823	5.264	0	0.227	3	0.031	280	0.023	274	0.032	32	0.008	67	0.024	221	0.008	140	0.005	326
CN		0.999	0.283	75	0.030	127	0.012	151	0.010	208	0.003	129	0.007	314	0.003	111	0.004	315	0.003	65
CM		-0.085	0.072	234	0.013	238	0.005	209	0.004	86	0.001	301	0.002	101	0.001	271	0.002	130	0.001	245
DCP 1	.010	2.344	0.584	155	0.019	186	0.051	95	0.040	82	0.042	36	0.025	28	0.022	337	0.013	339	0.020	267
DCP 2	.020	2.387	0.500	158	0.034	184	0.027	221	0.045	109	0.024	68	0.020	133	0.022	38	0.007	109	0.015	49
DCP 3	.030	2.349	0.720	160	0.217	267	0.050	199	0.019	354	0.058	102	0.038	160	0.015	194	0.014	214	0.011	255
DCP 4	.049	2.206	0.269	119	0.121	231	0.052	347	0.023	91	0.036	217	0.006	27	0.012	341	0.009	193	0.010	130
DCP 5	.074	2.061	0.280	107	0.114	216	0.040	317	0.007	29	0.016	220	0.027	339	0.012	88	0.016	187	0.004	333
DCP 6	.099	1.971	0.286	85	0.132	205	0.045	296	0.011	326	0.012	137	0.009	75	0.012	88	0.005	193	0.016	348
DCP 7	.149	1.675	0.278	87	0.119	165	0.095	245	0.026	359	0.030	345	0.026	333	0.010	129	0.007	344	0.022	110
DCP 8	.200	1.423	0.289	88	0.065	171	0.032	219	0.026	335	0.002	242	0.016	33	0.019	92	0.009	179	0.002	123
DCP 9	.250	1.361	0.325	84	0.060	147	0.039	191	0.015	260	0.008	278	0.011	344	0.013	120	0.013	214	0.011	9
DCP10	.300	1.240	0.328	77	0.062	136	0.035	181	0.009	276	0.011	231	0.013	317	0.017	211	0.005	344	0.005	244
DCP11	.399	1.118	0.381	74	0.059	121	0.037	157	0.022	262	0.006	199	0.010	288	0.008	330	0.012	93	0.005	51
DCP12	.501	0.936	0.380	66	0.063	103	0.034	130	0.017	265	0.007	104	0.006	168	0.013	268	0.021	356	0.006	34
DCP13	.600	0.795	0.364	62	0.054	86	0.023	112	0.012	280	0.007	163	0.013	306	0.006	148	0.012	325	0.004	85
DCP14	.701	0.682	0.329	56	0.055	50	0.023	97	0.009	264	0.002	81	0.008	299	0.006	143	0.013	293	0.004	178
DCP15	.800	0.524	0.298	54	0.046	44	0.018	81	0.007	298	0.005	118	0.011	261	0.007	90	0.007	271	0.004	105
DCP16	.900	0.219	0.217	56	0.061	29	0.012	84	0.013	270	0.010	95	0.008	298	0.010	51	0.008	208	0.006	44
DCP17	.969	0.047	0.104	68	0.012	61	0.009	109	0.015	262	0.003	169	0.005	304	0.008	70	0.001	108	0.006	15

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.71	0.200	0.524	5.96	0.0	0.77	12047.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
175.2	79505.	0.87E 07	-0.948	0.567	7.11	-0.00065	9.945	0.0
(574.7)	(1660.5)							

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		0.771	5.962	0	3.516	343	0.134	218	0.049	154	0.009	42	0.023	64	0.002	58	0.012	117	0.007	116
CN		0.627	0.441	359	0.028	15	0.005	258	0.035	195	0.003	258	0.001	148	0.001	276	0.001	251	0.001	59
CM		-0.011	0.011	241	0.006	281	0.001	133	0.001	60	0.000	206	0.001	8	0.000	105	0.001	41	0.000	17
DCP 1	.010	-0.468	2.852	339	0.169	281	0.221	266	0.181	334	0.133	21	0.044	50	0.024	6	0.040	37	0.028	84
DCP 2	.020	-0.190	2.250	346	0.127	324	0.047	232	0.022	266	0.328	336	0.041	90	0.036	188	0.030	288	0.022	343
DCP 3	.030	0.042	2.027	346	0.145	395	0.072	155	0.071	177	0.051	256	0.017	26	0.010	168	0.015	257	0.016	320
DCP 4	.049	0.271	1.763	347	0.126	356	0.069	113	0.064	156	0.056	232	0.017	316	0.005	327	0.003	351	0.007	287
DCP 5	.074	0.367	1.362	347	0.103	343	0.017	90	0.057	127	0.038	264	0.013	264	0.015	299	0.016	14	0.007	101
DCP 6	.099	2.413	1.136	348	0.056	340	0.039	178	0.024	141	0.022	195	0.006	32	0.011	324	0.008	2	0.014	125
DCP 7	.149	0.498	0.821	151	0.055	344	0.011	259	0.110	110	0.009	240	0.306	61	0.005	233	0.009	195	0.002	281
DCP 8	.200	0.035	0.671	159	0.059	6	0.015	204	0.002	214	0.012	121	0.07	112	0.07	156	0.003	116	0.006	66
DCP 9	.250	0.172	0.547	256	0.060	158	0.012	242	0.039	178	0.005	168	0.035	143	0.002	250	0.009	67	0.005	152
DCP10	.300	0.053	0.404	157	0.039	119	0.304	259	0.037	207	0.001	156	0.042	121	0.001	355	0.005	131	0.005	322
DCP11	.399	0.147	0.365	62	0.056	11	0.047	223	0.047	236	0.001	248	0.035	203	0.002	298	0.004	213	0.003	16
DCP12	.501	0.004	0.306	14	0.093	45	0.006	148	0.006	222	0.015	8	0.003	235	0.003	67	0.001	269	0.003	49
DCP13	.600	0.114	0.235	25	0.026	59	0.306	105	0.335	63	0.005	45	0.064	183	0.032	75	0.003	206	0.006	131
DCP14	.701	0.145	0.169	32	0.024	67	0.003	277	0.004	219	0.306	295	0.002	34	0.001	156	0.003	257	0.003	183
DCP15	.800	0.003	0.125	48	0.023	84	0.006	320	0.002	236	0.003	316	0.001	155	0.001	344	0.004	239	0.003	185
DCP16	.900	-0.084	0.049	79	0.018	120	0.003	238	0.003	242	0.004	207	0.004	195	0.004	229	0.003	232	0.004	284
DCP17	.969	-0.045	0.030	171	0.012	162	0.001	107	0.003	242	0.002	116	0.002	143	0.002	269	0.001	37	0.001	227

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.56	0.202	0.518	5.95	0.0	2.50	12047.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA,NMAX	AERO DAMP	TDR	EXT DAMP
172.9	78141.	0.81E 07	-0.042	0.807	8.76	-0.00066	0.945	0.0
(567.4)	(1633.0)							

HARMONIC ANALYSES

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.501	5.951 3	0.489 360	0.093 197	0.014 186	0.020 153	0.026 73	0.012 210	0.008 138	0.005 45
CN		0.360	0.444 356	0.013 395	0.004 261	0.001 58	0.004 248	0.001 185	0.002 210	0.001 3	0.000 168
CM		-0.009	0.042 294	0.006 251	0.001 114	0.000 206	0.001 132	0.000 86	0.000 55	0.000 246	0.000 272
DCP 1	.000	0.994	1.190 337	0.215 289	0.116 105	5.042 10	0.026 175	0.015 62	0.011 178	0.005 119	0.006 359
DCP 2	.020	0.913	2.476 345	0.204 293	0.090 149	0.079 52	0.052 242	0.034 103	0.016 112	0.006 334	0.008 94
DCP 3	.050	0.921	1.977 345	0.112 334	0.044 312	0.016 200	0.013 209	0.013 179	0.021 102	0.021 351	0.013 244
DCP 4	.069	1.101	1.795 346	0.121 330	0.015 261	0.013 173	0.017 168	0.013 46	0.004 241	0.002 183	0.004 84
DCP 5	.074	1.035	1.601 346	0.096 316	0.014 252	0.007 199	0.012 157	0.000 77	0.002 208	0.007 52	0.002 311
DCP 6	.094	0.970	1.194 346	0.082 329	0.013 263	0.006 203	0.010 160	0.005 46	0.003 166	0.001 243	0.001 288
DCP 7	.149	0.701	0.836 350	0.062 317	0.008 285	0.006 185	0.008 179	0.002 128	0.003 198	0.002 11	0.000 110
DCP 8	.230	0.550	0.661 350	3.051 0	0.009 312	0.002 308	0.007 222	0.003 144	0.002 132	0.003 271	0.002 130
DCP 9	.290	0.498	0.561 356	0.052 354	0.009 305	0.002 226	0.006 217	0.003 207	0.005 251	0.004 353	0.001 300
DCP10	.500	0.437	0.443 358	0.045 1	0.008 286	0.002 321	0.008 214	0.004 179	0.003 337	0.004 318	0.002 203
DCP11	.599	0.368	0.391 12	0.041 20	0.006 313	0.002 157	0.003 272	0.001 260	0.001 215	0.001 309	0.001 199
DCP12	.501	0.274	0.299 18	0.038 24	0.006 294	0.002 5	0.004 303	0.004 262	0.003 260	0.002 328	0.004 233
DCP 9	.800	0.245	0.281 25	0.029 46	0.006 307	0.004 358	0.005 294	0.004 280	0.004 255	0.002 181	0.001 71
DCP14	.701	0.206	0.163 33	0.026 43	0.000 284	0.005 88	0.007 329	0.001 209	0.001 220	0.002 100	0.002 61
DCP15	.800	0.125	0.100 47	0.020 53	0.005 224	0.002 9	0.005 310	0.001 75	0.003 178	0.003 68	0.001 278
DCP16	.933	-0.062	0.041 76	0.010 62	5.002 187	0.004 101	0.002 254	0.002 140	0.003 206	0.002 62	0.002 60
DCP17	.949	-0.057	0.026 172	0.004 178	0.004 2	0.005 2	0.004 317	0.002 299	0.001 199	0.003 335	0.002 88

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.86	0.201	0.522	5.61	0.0	5.01	12051.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA,NMAX	AERO DAMP	TDR	EXT DAMP
174.6	79314.	0.82E 07	-0.016	1.050	11.21	-0.08079	1.131	0.0
(573.7)	(1656.5)							

HARMONIC ANALYSES

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		5.014	5.915 0	0.485 347	0.141 190	0.020 204	0.018 156	0.026 75	0.027 237	0.004 43	0.007 199
CN		0.591	0.625 3	0.050 345	0.012 229	0.002 18	0.002 198	0.001 266	0.001 177	0.002 17	0.001 210
CM		0.003	1.040 330	0.307 219	0.001 236	0.002 153	0.000 21	0.001 125	0.000 59	0.000 324	0.000 287
DCP 1	.000	2.420	1.843 330	0.109 349	0.118 302	0.091 189	0.018 116	0.032 133	0.010 42	0.011 315	0.006 306
DCP 2	.020	2.101	2.570 346	0.179 276	5.039 330	0.095 225	0.061 128	0.003 227	0.032 115	0.021 1	0.009 133
DCP 3	.050	2.020	2.335 349	0.219 206	0.021 206	0.072 209	0.076 117	0.030 17	0.014 107	0.029 4	0.014 275
DCP 4	.069	2.134	1.667 349	0.236 318	0.136 245	0.096 170	0.062 94	0.004 1	0.020 242	0.016 70	0.018 331
DCP 5	.074	1.754	1.393 352	0.225 323	0.199 225	0.373 116	0.021 39	0.021 35	0.024 313	0.017 244	0.006 180
DCP 6	.094	1.465	1.118 357	0.142 625	0.069 191	0.068 65	0.061 319	0.045 225	0.022 118	0.009 352	0.008 172
DCP 7	.149	1.127	0.812 359	0.096 322	0.042 131	0.043 359	0.099 256	0.127 160	0.016 50	0.011 301	0.013 181
DCP 8	.230	0.891	0.668 2	0.061 6	0.000 171	0.010 417	0.011 234	0.003 224	0.006 203	0.009 106	0.007 27
DCP 9	.290	0.768	0.566 3	0.060 349	0.004 262	0.013 280	0.011 168	0.009 315	0.004 236	0.004 61	0.004 254
DCP10	.500	0.672	1.449 3	0.196 341	0.376 225	0.209 330	0.009 165	0.002 241	0.005 190	0.005 58	0.004 172
DCP11	.599	0.550	0.363 18	0.055 13	0.010 258	0.207 433	0.004 244	0.002 2	0.004 210	0.006 141	0.004 257
DCP12	.501	0.415	0.201 27	0.040 16	0.004 201	0.303 1	0.001 16	0.001 95	0.036 169	0.031 130	0.002 194
DCP 9	.800	0.391	0.223 37	0.044 19	0.007 323	0.007 12	0.004 241	0.001 129	0.002 218	0.003 282	0.004 203
DCP14	.701	0.146	0.162 54	0.046 15	0.006 221	0.006 16	0.003 265	0.032 347	0.001 194	0.008 40	0.004 22
DCP15	.800	0.160	0.111 60	0.02 4	0.114 100	0.006 116	0.008 156	0.032 296	0.004 250	2.001 60	0.002 161
DCP16	.933	-0.009	0.055 74	0.006 166	0.196 60	0.006 261	0.007 137	0.007 310	0.002 330	0.051 309	2.003 13
DCP17	.949	-0.009	0.023 195	0.042 201	0.005 74	0.006 307	0.006 65	0.003 247	0.002 125	0.002 238	0.004 180

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.79	0.201	0.523	5.85	0.0	7.51	12051.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
174.2	79299.	0.82E 07	-0.073	1.283	13.66	-0.00049	0.710	0.0
(571.6)	(1656.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.509	5.852	0	0.725	358	0.212	140	0.046	156	0.007	238	0.006	78	0.020	200	0.012	191	0.010	45
CN		3.708	0.475	24	0.116	315	0.337	168	0.016	18	0.315	279	0.012	193	0.002	164	0.003	90	0.004	33
CM		-0.009	0.032	242	0.030	41	0.019	275	0.037	193	0.005	130	0.003	28	0.001	288	0.002	243	0.002	155
DCP 1	.010	2.719	1.661	354	0.833	34	0.437	298	0.134	149	0.073	307	0.107	174	0.078	48	0.069	284	0.036	196
DCP 2	.020	2.444	1.552	10	0.705	27	0.344	310	0.124	252	0.056	287	0.123	227	0.080	124	0.050	323	0.030	185
DCP 3	.030	2.328	1.367	10	0.615	22	0.293	305	0.141	269	0.110	238	0.108	203	0.084	157	0.031	114	0.019	130
DCP 4	.049	2.159	1.170	17	0.632	16	0.246	292	0.069	295	0.133	259	0.123	189	0.053	146	0.049	143	0.068	80
DCP 5	.074	1.967	1.064	20	0.530	6	0.200	276	0.065	287	0.132	238	0.112	164	0.041	126	0.046	129	0.063	74
DCP 6	.099	1.756	0.930	20	0.407	352	0.170	264	0.019	158	0.368	207	0.086	120	0.046	39	0.026	17	0.041	349
DCP 7	.149	1.368	0.864	17	0.323	323	0.173	205	0.038	122	0.052	156	0.064	68	0.042	345	0.029	323	0.038	280
DCP 8	.200	1.111	0.764	24	0.272	322	0.153	204	0.035	122	0.044	137	0.058	52	0.048	332	0.025	296	0.030	241
DCP 9	.250	1.004	0.709	17	0.236	293	0.148	166	0.047	70	0.040	54	0.051	329	0.040	248	0.022	210	0.028	139
DCP10	.30	0.667	0.618	17	0.199	283	0.114	152	0.026	51	0.033	63	0.040	320	0.034	245	0.019	188	0.025	121
DCP11	.349	0.707	0.520	30	0.164	285	0.107	153	0.045	54	0.031	18	0.043	292	0.028	224	0.015	135	0.012	97
DCP12	.501	0.525	0.416	33	0.118	269	0.088	124	0.044	17	0.031	328	0.036	239	0.023	161	0.019	79	0.015	2
DCP13	.600	0.428	0.342	39	0.101	260	0.080	108	0.040	12	0.085	302	0.032	205	0.011	122	0.011	107	0.017	10
DCP14	.731	0.380	0.254	51	0.070	244	0.059	77	0.019	320	0.027	300	0.027	161	0.013	74	0.009	23	0.011	288
DCP15	.800	0.203	0.181	46	0.078	221	0.057	73	0.021	336	0.028	287	0.021	153	0.009	48	0.009	34	0.008	333
DCP16	.900	-0.033	0.101	25	0.066	209	0.033	60	0.017	9	0.030	261	0.015	142	0.006	34	0.001	350	0.001	65
DCP17	.965	-0.056	0.031	11	0.039	217	0.022	74	0.013	12	0.013	247	0.011	128	0.005	51	0.008	20	0.005	303

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.80	0.203	0.517	5.73	0.0	10.01	12051.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
172.3	77939.	0.81E 07	-0.161	1.494	15.74	-0.00053	0.761	0.0
(565.5)	(1627.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		10.012	5.727	0	0.768	11	0.235	167	0.069	172	0.012	341	0.042	5	0.025	201	0.014	192	0.007	57
CN		0.833	0.489	41	0.136	337	0.034	252	0.032	149	0.023	30	0.014	324	0.002	337	0.004	270	0.001	200
CM		-0.020	0.061	213	0.045	69	0.017	2	0.017	306	0.009	210	0.004	152	0.002	105	0.003	38	0.002	282
DCP 1	.010	3.263	0.763	16	0.982	49	0.208	339	0.209	72	0.139	322	0.043	221	0.016	194	0.008	220	0.032	145
DCP 2	.020	2.942	0.963	32	0.867	54	0.273	340	0.160	102	0.115	6	0.052	67	0.062	340	0.029	218	0.019	184
DCP 3	.030	2.627	0.728	47	0.810	57	0.422	14	0.134	8	0.124	13	0.067	334	0.056	332	0.011	321	0.012	2
DCP 4	.049	2.474	0.762	56	0.647	46	0.147	31	0.174	32	0.105	337	0.051	350	0.062	338	0.037	300	0.005	297
DCP 5	.074	2.168	0.776	56	0.594	36	0.133	13	0.165	10	0.104	317	0.088	335	0.070	309	0.030	288	0.026	327
DCP 6	.099	1.953	0.736	52	0.441	20	0.074	325	0.100	335	0.073	263	0.034	288	0.057	252	0.038	183	0.006	189
DCP 7	.149	1.550	0.792	42	0.375	336	0.096	294	0.101	261	0.077	222	0.030	223	0.050	186	0.031	130	0.016	144
DCP 8	.200	1.292	0.757	44	0.320	355	0.117	295	0.098	258	0.047	208	0.035	241	0.062	174	0.017	137	0.020	182
DCP 9	.250	1.140	0.702	37	0.263	330	0.085	267	0.103	219	0.061	143	0.018	132	0.040	100	0.037	57	0.034	2
DCP10	.300	1.009	0.663	34	0.241	318	0.086	253	0.101	196	0.047	103	0.015	182	0.045	94	0.041	18	0.026	302
DCP11	.349	0.838	0.596	43	0.196	316	0.079	255	0.105	193	0.056	95	0.010	95	0.034	88	0.035	18	0.032	313
DCP12	.501	0.644	0.523	42	0.173	330	0.073	231	0.100	165	0.064	72	0.021	23	0.030	32	0.040	318	0.028	235
DCP13	.600	0.520	0.443	43	0.155	279	0.064	200	0.094	138	0.071	39	0.032	343	0.020	340	0.038	266	0.031	168
DCP14	.731	0.458	0.363	43	0.154	256	0.061	161	0.071	112	0.052	6	0.025	340	0.018	291	0.027	219	0.020	116
DCP15	.800	0.263	0.263	29	0.146	241	0.051	157	0.072	96	0.044	356	0.028	327	0.023	251	0.021	178	0.016	73
DCP16	.900	0.018	0.183	16	0.103	239	0.061	172	0.063	73	0.034	337	0.025	296	0.017	235	0.024	162	0.018	53
DCP17	.965	-0.044	0.071	19	0.047	260	0.026	197	0.038	87	0.017	355	0.006	280	0.015	273	0.023	180	0.014	86

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.76	0.207	0.506	5.67	0.0	12.53	12051.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
169.1	75545.	0.80E 07	-0.229	1.709	17.45	-0.30091	1.267	0.0
(554.8)	(1577.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.530	5.888 0	0.542 19	0.208 219	0.071 220	0.024 128	0.048 43	0.014 252	0.008 286	0.010 180
CN		0.942	0.929 54	0.122 9	0.057 324	0.044 240	0.033 160	0.014 108	0.007 94	0.004 8	0.002 164
CM		-0.034	0.046 207	0.039 131	0.031 77	0.014 18	0.012 318	0.034 283	0.003 240	0.002 171	0.001 121
DCP 1	.010	4.552	0.711 127	0.573 91	0.174 121	0.118 24	0.097 208	0.082 99	0.046 8	0.056 5	0.033 311
DCP 2	.020	3.168	0.779 101	0.901 76	0.176 97	0.153 55	0.154 224	0.095 185	0.092 191	0.049 80	0.036 55
DCP 3	.050	2.665	0.899 107	0.748 82	0.259 92	0.212 99	0.094 153	0.113 130	0.048 142	0.011 294	0.018 154
DCP 4	.075	2.720	0.611 100	0.483 71	0.293 111	0.098 96	0.131 130	0.092 106	0.046 134	0.047 156	0.048 163
DCP 5	.075	2.303	0.816 89	0.412 62	0.273 91	0.088 57	0.114 113	0.070 87	0.055 124	0.051 133	0.044 137
DCP 6	.125	2.114	0.770 82	0.343 48	0.222 65	0.117 353	0.050 70	0.060 32	0.047 45	0.037 33	0.073 52
DCP 7	.144	1.753	0.801 61	0.296 32	0.231 25	0.121 311	0.043 357	0.031 349	0.060 2	0.040 314	0.037 173
DCP 8	.250	1.421	0.790 62	0.266 61	0.212 20	0.122 312	0.035 345	0.022 352	0.066 356	0.035 331	0.029 315
DCP 9	.250	1.268	0.735 51	0.211 13	0.197 349	0.111 274	0.043 280	0.028 280	0.065 368	0.037 247	0.019 219

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
		0.214	0.489	5.65	0.0	16.48	12058.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
162.0	7102.		-0.287	1.856	19.00	-0.00166	2.245	0.0
(536.5)	(1483.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA					0.053 311	0.035 0	0.031 2	0.016 11	0.013 221	0.006 109	0.031 209
CN					0.055 73	0.041 13	0.027 356	0.009 322	0.006 7	0.004 277	0.006 164
CM					0.028 121	0.019 164	0.008 143	0.004 122	0.004 142	0.004 44	0.002 358
DCP 1	.010	0.331	0.557 160	0.115 216	0.190 117	0.054 242	0.077 31	0.041 16	0.067 17	0.031 73	0.029 44
DCP 2	.020	3.245	0.349 157	0.103 227	0.117 132	0.084 241	0.082 99	0.071 90	0.048 113	0.039 106	0.046 140
DCP 3	.050	3.244	0.271 155	0.072 235	0.115 232	0.338 348	0.070 335	0.054 84	0.035 84	0.010 126	0.031 165
DCP 4	.075	2.775	0.201 179	0.055 208	0.095 274	0.142 326	0.140 44	0.056 96	0.014 181	0.024 280	0.009 178
DCP 5	.075	2.318	0.671 107	0.221 174	0.076 160	0.070 230	0.086 326	0.063 12	0.041 83	0.023 87	0.014 149
DCP 6	.125	2.026	0.798 77	0.272 156	0.072 168	0.085 180	0.086 292	0.049 410	0.034 23	0.033 74	0.020 87
DCP 7	.144	1.882	0.708 74	0.241 128	0.115 196	0.067 143	0.043 204	0.092 274	0.025 315	0.023 293	0.017 39
DCP 8	.250	1.567	0.686 73	0.242 118	0.127 145	0.072 136	0.032 182	0.041 263	0.037 293	0.024 338	0.021 349
DCP 9	.250	1.444	0.698 63	0.276 65	0.160 101	0.085 66	0.043 85	0.042 184	0.035 183	0.036 204	0.034 217
DCP10	.330	1.249	0.662 57	0.263 72	0.156 92	0.098 51	0.043 60	0.024 160	0.026 153	0.076 179	0.016 194
DCP11	.344	1.135	0.701 56	0.235 67	0.150 100	0.091 62	0.058 57	0.023 95	0.020 130	0.011 190	0.008 211
DCP12	.501	0.937	0.674 48	0.213 41	0.113 67	0.097 28	0.059 18	0.030 38	0.018 70	0.019 61	0.012 110
DCP13	.600	0.787	0.683 44	0.219 25	0.108 39	0.100 9	0.055 356	0.034 355	0.023 25	0.015 27	0.008 115
DCP14	.731	0.679	0.612 31	0.220 8	0.107 8	0.098 334	0.062 320	0.020 300	0.021 346	0.028 324	0.002 169
DCP15	.830	0.584	0.534 35	0.203 357	0.114 352	0.093 318	0.048 287	0.027 281	0.021 323	0.023 248	0.008 164
DCP16	.900	0.397	0.361 34	0.140 339	0.082 332	0.060 307	0.029 285	0.024 286	0.034 288	0.031 264	0.015 170
DCP17	.969	0.241	0.168 42	0.076 349	0.043 329	0.032 324	0.019 317	0.014 265	0.014 312	0.015 225	0.005 244

	TUNED HZ	DRIVE HZ	K	MACH NO	DFL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	3.0	68.84	0.200	0.524	5.95	0.0	0.05	12049.1	20
	V	W	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	175.2 (574.9)	79553. (1661.5)	0.82E 07	-0.052	0.554	6.38	-0.00066	0.950	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.046	5.946 0	0.517 343	0.111 204	0.057 152	0.008 108	0.022 68	0.007 177	0.001 104	0.009 133
CN		0.106	0.447 358	0.029 6	0.007 233	0.004 204	0.004 254	0.002 104	0.001 215	0.001 311	0.000 35
CM		-0.015	0.032 293	0.006 286	0.001 103	0.001 56	0.001 160	0.001 300	0.001 352	0.000 53	0.001 10
DCP 1	.010	-0.733	2.994 339	0.171 288	0.212 262	0.182 333	0.096 27	0.045 58	0.015 347	0.030 17	0.020 73
DCP 2	.020	-3.409	2.348 346	0.150 329	0.043 208	0.018 204	0.021 317	0.036 93	0.031 183	0.024 264	0.016 333
DCP 3	.030	-0.193	2.108 345	0.160 352	0.079 131	0.062 177	0.043 246	0.014 10	0.010 137	0.012 244	0.018 307
DCP 4	.049	0.128	1.753 346	0.144 345	0.074 119	0.067 163	0.053 223	0.024 297	0.014 2	0.004 34	0.006 323
DCP 5	.074	0.268	1.368 347	0.114 335	0.029 110	0.033 135	0.036 196	0.018 246	0.020 275	0.018 338	0.013 32
DCP 6	.099	0.337	1.156 349	0.086 334	0.005 198	0.017 147	0.023 193	0.008 264	0.009 318	0.012 43	0.009 132
DCP 7	.149	0.237	0.836 351	0.053 334	0.018 229	0.001 155	0.007 186	0.004 107	0.003 254	0.006 337	0.004 351
DCP 8	.200	0.183	0.666 359	0.046 351	0.016 262	0.005 296	0.003 3	0.005 69	0.002 175	0.002 307	0.004 332
DCP 9	.250	0.174	0.591 356	0.045 354	0.008 254	0.007 184	0.001 146	0.006 95	0.001 155	0.005 141	0.002 286
DCP10	.300	0.160	0.499 358	0.037 2	0.005 242	0.008 217	0.006 251	0.007 105	0.001 119	0.002 116	0.002 63
DCP11	.399	0.147	0.399 12	0.034 30	0.009 274	0.006 234	0.006 274	0.006 163	0.002 239	0.001 346	0.002 87
DCP12	.501	0.110	0.307 18	0.031 34	0.010 277	0.005 258	0.003 287	0.002 121	0.001 7	0.001 270	0.001 78
DCP13	.600	0.117	0.237 25	0.023 53	0.010 262	0.005 236	0.007 265	0.002 39	0.001 20	0.006 250	0.002 241
DCP14	.701	0.105	0.169 53	0.024 65	0.006 261	0.005 198	0.007 322	0.003 70	0.004 170	0.002 189	0.002 203
DCP15	.800	0.092	0.105 45	0.022 87	0.007 257	0.002 201	0.004 343	0.004 117	0.003 195	0.003 235	0.002 193
DCP16	.900	-0.088	0.045 46	0.018 134	0.005 178	0.005 258	0.007 0	0.004 133	0.004 148	0.004 300	0.004 173
DCP17	.965	-0.046	0.036 172	0.011 158	0.000 199	0.006 109	0.004 168	0.003 125	0.007 203	0.005 55	0.003 218

	TUNED HZ	DRIVE HZ	K	MACH NO	DFL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	3.0	68.87	0.202	0.520	5.93	0.0	2.49	12049.2	20
	V	W	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	173.4 (568.9)	78562. (1640.8)	0.82E 07	-0.042	0.606	8.73	-0.00065	0.935	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.486	5.925 0	0.502 341	0.106 197	0.016 190	0.026 153	0.019 99	0.013 204	0.008 164	0.005 91
CN		0.358	0.444 357	0.034 356	0.002 203	0.001 341	0.003 235	0.003 237	0.001 164	0.002 51	0.001 118
CM		-0.008	0.032 247	0.007 251	0.001 165	0.000 232	0.000 170	0.001 106	0.000 8	0.000 273	0.000 238
DCP 1	.010	0.452	3.174 337	0.216 265	0.133 111	0.033 12	0.024 194	0.008 38	0.016 229	0.013 91	0.012 11
DCP 2	.020	0.928	2.497 345	0.215 269	0.138 147	0.067 46	0.064 244	0.044 198	0.017 110	0.002 247	0.019 81
DCP 3	.030	0.936	2.014 344	0.116 321	0.020 307	0.019 336	0.029 284	0.041 183	0.045 91	0.046 350	0.037 266
DCP 4	.049	1.105	1.765 346	0.128 333	0.020 252	0.021 194	0.016 146	0.013 21	0.013 251	0.007 122	0.007 73
DCP 5	.074	1.036	1.411 346	0.103 316	0.013 241	0.007 214	0.038 171	0.005 104	0.002 251	0.004 57	0.008 131
DCP 6	.099	0.971	1.168 348	0.085 331	0.017 271	0.006 212	0.013 148	0.002 141	0.001 227	0.004 64	0.003 150
DCP 7	.149	0.703	0.846 351	0.061 337	0.013 279	0.010 204	0.007 208	0.001 184	0.002 278	0.005 50	0.002 152
DCP 8	.200	0.556	0.696 356	0.056 359	0.013 284	0.003 330	0.008 219	0.006 244	0.001 101	0.003 152	0.004 155
DCP 9	.250	0.493	0.583 356	0.058 356	0.013 273	0.004 330	0.006 147	0.006 183	0.001 155	0.001 158	0.003 266
DCP10	.300	0.429	0.482 357	0.050 9	0.006 262	0.002 246	0.004 196	0.003 144	0.002 164	0.001 353	0.001 1
DCP11	.399	0.362	0.385 12	0.045 23	0.002 220	0.005 261	0.003 227	0.004 268	0.002 150	0.002 26	0.003 124
DCP12	.501	0.274	0.298 17	0.034 27	0.003 338	0.004 317	0.006 264	0.005 272	0.003 184	0.003 23	0.003 89
DCP13	.600	0.243	0.226 25	0.034 41	0.004 23	0.004 269	0.006 269	0.006 308	0.001 214	0.000 250	0.001 85
DCP14	.701	0.275	0.154 33	0.033 53	0.002 2	0.003 12	0.003 260	0.004 243	0.004 29	0.002 84	0.001 164
DCP15	.600	0.133	0.096 47	0.022 57	0.003 15	0.001 69	0.003 164	0.003 263	0.001 114	0.005 92	0.001 41
DCP16	.900	-0.062	0.038 60	0.007 52	0.002 319	0.006 118	0.005 26	0.005 304	0.002 194	0.001 21	0.002 202
DCP17	.965	-0.054	0.028 175	0.004 111	0.005 240	0.003 26	0.002 17	0.002 133	0.001 246	0.001 83	0.005 14

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.03	0.059	0.604	5.19	0.0	0.31	12055.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
199.8	104077.	0.93E 07	-0.043	0.653	5.46	-0.00091	1.452	0.0
(655.4)	(2173.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.307	5.186 0	0.231 8	0.035 249	0.018 200	0.027 40	0.022 99	0.021 238	0.009 285	0.004 141
CN		0.132	0.524 353	0.010 308	0.010 272	0.006 257	0.002 43	0.002 56	0.001 351	0.001 35	0.001 238
CM		-0.019	0.017 316	0.003 14	0.004 117	0.000 88	0.001 130	0.000 71	0.000 264	0.000 211	0.001 60
DCP 1	.010	-0.737	2.818 347	0.200 264	0.307 306	0.185 5	0.057 73	0.043 7	0.035 60	0.011 290	0.028 20
DCP 2	.020	-0.523	2.388 349	0.075 298	0.150 306	0.123 9	0.086 98	0.001 107	0.053 74	0.043 170	0.010 308
DCP 3	.030	-0.282	2.198 348	0.103 34	0.018 231	0.036 336	0.067 97	0.044 175	0.004 245	0.022 165	0.028 228
DCP 4	.049	0.125	1.999 349	0.074 32	0.073 154	0.065 242	0.038 79	0.042 154	0.035 260	0.016 307	0.008 278
DCP 5	.074	0.353	1.717 349	0.046 316	0.099 147	0.052 217	0.019 305	0.014 66	0.322 248	0.013 309	0.011 39
DCP 6	.099	0.443	1.549 350	0.110 275	0.114 151	0.015 190	0.024 294	0.028 39	0.321 278	0.010 221	0.009 55
DCP 7	.149	0.244	0.915 350	0.062 36	0.011 10	0.045 206	0.010 263	0.017 347	0.008 46	0.006 13	0.106 195
DCP 8	.200	0.214	0.744 353	0.027 155	0.015 332	0.018 212	0.005 295	0.010 22	0.005 52	0.006 81	0.005 133
DCP 9	.250	0.209	0.725 353	0.014 345	0.018 296	0.010 219	0.001 306	0.003 14	0.003 346	0.003 69	0.000 44
DCP10	.300	0.199	0.603 353	0.004 337	0.018 297	0.004 238	0.003 73	0.001 110	0.004 0	0.003 59	0.001 194
DCP11	.399	0.184	0.477 357	0.008 299	0.016 292	0.002 283	0.001 95	0.002 238	0.004 16	0.002 49	0.002 152
DCP12	.501	0.138	0.356 359	0.008 263	0.016 291	0.003 315	0.002 64	0.001 193	0.001 10	0.002 40	0.002 220
DCP13	.600	0.153	0.260 1	0.008 248	0.016 294	0.004 290	0.003 14	0.001 116	0.001 52	0.001 96	0.005 249
DCP14	.701	0.230	0.172 3	0.002 184	0.015 288	0.004 278	0.002 7	0.002 108	0.001 70	0.002 21	0.003 258
DCP15	.800	0.101	0.083 13	0.010 205	0.015 295	0.003 298	0.002 14	0.002 165	0.002 122	0.001 315	0.003 247
DCP16	.900	-0.093	0.021 117	0.021 208	0.013 276	0.005 274	0.001 238	0.003 356	0.002 130	0.000 17	0.002 262
DCP17	.969	-0.050	0.043 172	0.009 221	0.004 255	0.002 240	0.005 355	0.001 69	0.002 331	0.001 235	0.001 191

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.07	0.059	0.601	5.20	0.0	2.38	12055.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
198.5	103397.	0.93E 07	-0.027	0.982	7.62	-0.00094	1.492	0.0
(651.2)	(2159.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.377	5.198 0	0.206 6	0.039 267	0.020 204	0.021 32	0.014 71	0.018 226	0.011 152	0.004 4
CN		0.398	0.568 353	0.036 357	0.011 256	0.006 120	0.003 351	0.001 320	0.003 270	0.002 113	0.001 339
CM		-0.006	0.024 329	0.006 247	0.002 126	0.000 316	0.001 191	0.001 89	0.001 325	0.000 234	0.000 13
DCP 1	.010	0.596	3.289 347	0.370 40	0.044 85	0.066 202	0.022 183	0.008 131	0.013 236	0.020 344	0.010 348
DCP 2	.020	0.724	2.627 349	0.144 12	0.009 311	0.016 127	0.024 243	0.048 18	0.027 28	0.033 193	0.033 230
DCP 3	.030	0.877	2.280 349	0.102 359	0.024 280	0.039 47	0.007 114	0.016 73	0.031 290	0.011 244	0.006 327
DCP 4	.049	1.128	2.026 349	0.095 17	0.052 312	0.016 64	0.032 309	0.012 180	0.026 287	0.015 201	0.008 103
DCP 5	.074	1.241	1.853 349	0.080 342	0.061 313	0.016 203	0.027 314	0.024 199	0.005 310	0.013 195	0.014 90
DCP 6	.099	1.319	1.800 350	0.100 287	0.073 321	0.063 226	0.010 329	0.044 209	0.018 113	0.013 203	0.025 95
DCP 7	.149	0.977	1.426 352	0.261 273	0.114 175	0.033 197	0.108 133	0.116 35	0.060 295	0.011 29	0.043 289
DCP 8	.200	0.617	0.875 355	0.084 331	0.060 196	0.056 82	0.029 340	0.003 287	0.011 317	0.006 256	0.006 185
DCP 9	.250	0.552	0.720 353	0.044 347	0.036 165	0.052 56	0.043 320	0.025 235	0.013 191	0.014 139	0.015 57
DCP10	.300	0.465	0.566 354	0.055 18	0.017 208	0.034 64	0.037 320	0.032 226	0.019 140	0.013 71	0.012 10
DCP11	.399	0.389	0.442 358	0.058 43	0.020 322	0.005 199	0.002 335	0.003 234	0.002 105	0.002 47	0.002 337
DCP12	.501	0.289	0.333 359	0.045 40	0.017 314	0.005 206	0.002 303	0.002 270	0.001 284	0.001 59	0.002 198
DCP13	.600	0.257	0.247 1	0.040 41	0.016 307	0.004 196	0.002 58	0.002 300	0.001 311	0.002 74	0.003 172
DCP14	.701	0.291	0.148 5	0.039 48	0.014 307	0.005 198	0.002 47	0.002 337	0.002 230	0.001 45	0.002 129
DCP15	.800	0.127	0.082 11	0.021 44	0.011 291	0.003 156	0.004 48	0.002 341	0.001 238	0.003 68	0.002 217
DCP16	.930	-0.102	0.019 31	0.002 334	0.007 270	0.003 124	0.003 53	0.002 313	0.002 151	0.001 94	0.000 270
DCP17	.969	-0.067	0.024 177	0.007 258	0.004 193	0.001 44	0.002 337	0.001 346	0.001 216	0.001 210	0.002 247

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNEC HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.07	0.060	0.548	5.19	0.0	5.02	12055.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TOR	EXT DAMP
197.3	102296.	0.93E 07	-0.019	1.154	9.48	-0.00116	1.821	0.0
(647.3)	(2136.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		5.021	5.168 0	0.224 13	0.030 268	0.015 324	0.030 338	0.028 236	0.043 86	0.005 198	0.007 266
CN		0.635	0.446 359	0.106 36	0.044 327	0.029 268	0.021 190	0.011 123	0.009 79	0.003 355	0.000 69
CM		0.004	0.026 323	0.005 180	0.005 24	0.002 304	0.002 288	0.002 227	0.002 117	0.000 63	0.001 58
DCP 1	.010	2.045	2.332 348	0.471 47	0.100 336	0.017 324	0.025 305	0.011 275	0.012 9	0.009 191	0.005 296
DCP 2	.020	1.905	2.126 352	0.324 41	0.085 338	0.046 261	0.009 157	0.025 239	0.023 104	0.018 212	0.017 121
DCP 3	.030	1.919	1.909 352	0.262 36	0.064 332	0.048 254	0.022 150	0.024 234	0.031 109	0.012 204	0.019 113
DCP 4	.044	2.011	1.624 351	0.305 50	0.083 354	0.065 304	0.361 163	0.027 128	0.055 86	0.021 351	0.007 105
DCP 5	.074	1.945	1.441 350	0.335 60	0.169 354	0.103 305	0.086 204	0.047 113	0.057 80	0.038 4	0.010 287
DCP 6	.099	1.956	1.335 350	0.416 65	0.282 345	0.095 304	0.070 226	0.040 83	0.030 98	0.050 25	0.015 358
DCP 7	.149	1.421	1.080 358	0.250 36	0.281 338	0.147 264	0.097 294	0.139 220	0.014 158	0.088 202	0.041 125
DCP 8	.200	1.052	0.819 3	0.162 358	0.058 317	0.104 265	0.080 185	0.024 155	0.038 125	0.014 84	0.012 122
DCP 9	.250	0.909	0.673 359	0.106 350	0.024 286	0.069 253	0.077 165	0.034 102	0.040 102	0.038 38	0.016 351
DCP10	.300	0.766	0.530 1	0.103 357	0.027 270	0.049 250	0.068 168	0.044 96	0.036 75	0.037 18	0.022 323
DCP11	.344	0.595	0.363 5	0.086 29	0.017 282	0.012 244	0.027 163	0.030 78	0.019 6	0.012 306	0.007 275
DCP12	.501	0.426	0.246 10	0.084 37	0.018 294	0.006 227	0.011 144	0.013 59	0.006 341	0.004 270	0.003 255
DCP13	.600	0.341	0.155 18	0.082 44	0.020 308	0.005 259	0.006 183	0.009 72	0.004 340	0.004 263	0.004 236
DCP14	.701	0.326	0.067 49	0.083 50	0.018 315	0.003 324	0.004 228	0.003 75	0.003 290	0.003 209	0.002 181
DCP15	.800	0.149	0.053 51	0.044 32	0.014 265	0.005 138	0.004 107	0.004 24	0.005 268	0.003 178	0.003 167
DCP16	.900	-0.087	0.037 35	0.021 327	0.015 225	0.006 143	0.003 132	0.004 50	0.004 290	0.002 195	0.002 132
DCP17	.969	-0.076	0.008 149	0.013 285	0.004 237	0.003 225	0.004 124	0.003 56	0.003 266	0.001 134	0.000 286

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNEC HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.01	0.060	0.591	5.07	0.0	7.49	12055.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TOR	EXT DAMP
194.6	98207.	0.90E 07	-0.035	1.237	9.97	-0.00129	2.001	0.0
(638.6)	(2051.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.469	5.065 0	0.254 27	0.031 275	0.029 86	0.053 39	0.063 4	0.110 222	0.025 171	0.008 55
CN		0.805	0.286 14	0.144 53	0.038 33	0.033 17	0.029 325	0.014 278	0.012 271	0.004 208	0.003 125
CM		-0.002	0.020 252	0.020 100	0.005 8	0.005 90	0.004 14	0.002 5	0.001 318	0.002 311	0.001 223
DCP 1	.010	2.930	1.327 350	0.596 62	0.121 44	0.072 10	0.017 302	0.031 235	0.045 158	0.019 72	0.026 67
DCP 2	.020	2.677	1.255 352	0.508 71	0.172 36	0.097 19	0.382 325	0.039 292	0.043 220	0.017 68	0.028 117
DCP 3	.030	2.592	1.123 351	0.444 75	0.191 35	0.095 4	0.086 325	0.049 317	0.059 250	0.008 134	0.026 124
DCP 4	.044	2.476	0.831 348	0.564 76	0.160 36	0.053 46	0.117 347	0.061 299	0.063 276	0.324 273	0.019 209
DCP 5	.074	2.348	0.620 349	0.661 73	0.119 35	0.092 67	0.132 354	0.054 273	0.058 401	0.045 266	0.025 222
DCP 6	.099	2.251	0.311 353	0.763 70	0.091 90	0.157 61	0.113 356	0.043 247	0.079 306	0.042 262	0.024 247
DCP 7	.149	1.668	0.445 20	0.565 63	0.126 25	0.284 51	0.062 5	0.112 27	0.060 104	0.136 21	0.063 84
DCP 8	.200	1.298	0.531 27	0.277 53	0.166 12	0.373 11	0.106 333	0.023 310	0.041 322	0.012 322	0.005 58
DCP 9	.250	1.181	0.472 11	0.178 46	0.124 357	0.050 326	0.096 313	0.049 265	0.065 286	0.031 225	0.022 271
DCP10	.350	0.947	0.406 14	0.126 52	0.088 3	0.051 311	0.064 312	0.050 260	0.045 247	0.028 227	0.027 262
DCP11	.344	0.706	0.314 14	0.077 16	0.070 50	0.043 320	0.022 287	0.027 255	0.024 238	0.021 188	0.009 176
DCP12	.501	0.547	0.213 24	0.062 4	0.012 101	0.021 318	0.010 266	0.016 246	0.012 194	0.004 172	0.012 146
DCP13	.600	0.450	0.156 36	0.050 4	0.022 135	0.015 347	0.007 251	0.009 236	0.007 202	0.010 135	0.006 66
DCP14	.701	0.389	0.098 70	0.044 357	0.031 159	0.010 19	0.008 204	0.008 153	0.006 78	0.007 92	0.006 51
DCP15	.800	0.149	0.067 49	0.039 318	0.018 156	0.012 315	0.013 192	0.005 124	0.004 102	0.008 97	0.005 30
DCP16	.900	-0.050	0.063 21	0.038 296	0.004 270	0.011 275	0.007 208	0.006 183	0.004 115	0.007 118	0.007 31
DCP17	.969	-0.072	0.026 23	0.022 287	0.003 316	0.008 298	0.004 232	0.004 192	0.001 77	0.004 148	0.003 50

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.03	0.060	0.591	4.96	0.0	10.00	12055.5	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
194.1 (636.7)	97393. (2034.1)	0.90E 07	-0.071	1.243	10.18	-0.00135	2.092	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		9.996	4.956 0	0.261 24	0.058 219	0.022 128	0.008 138	0.037 123	0.061 92	0.008 12	0.015 332
CN		0.930	0.148 48	0.095 70	0.053 125	0.021 101	0.025 109	0.009 48	0.011 111	0.002 68	0.005 96
CM		-0.013	0.045 204	0.322 90	0.007 188	0.003 106	0.002 182	0.002 163	0.002 178	0.001 124	0.002 173
DCP 1	.013	3.379	0.194 358	0.536 74	0.112 77	0.016 94	0.039 2	0.030 342	0.020 253	0.010 38	0.014 303
DCP 2	.020	3.075	0.288 355	0.596 81	0.107 92	0.045 121	0.047 86	0.006 57	0.023 302	0.020 34	0.017 7
DCP 3	.030	2.908	0.236 351	0.572 81	0.087 110	0.094 110	0.058 78	0.022 145	0.023 353	0.012 11	0.006 27
DCP 4	.049	2.746	0.118 217	0.461 89	0.106 154	0.155 111	0.086 130	0.035 115	0.030 112	0.024 96	0.008 132
DCP 5	.070	2.618	0.258 177	0.368 82	0.189 164	0.142 100	0.087 137	0.056 100	0.041 132	0.030 116	0.021 132
DC 6	.095	2.498	0.497 166	0.288 76	0.268 158	0.095 97	0.113 145	0.062 89	0.056 143	0.025 119	0.032 145
DCP 7	.149	1.951	0.391 133	0.346 79	0.366 147	0.139 213	0.015 280	0.007 222	0.027 236	0.016 21	0.035 182
DCP 8	.200	1.434	0.290 83	0.359 83	0.129 123	0.093 97	0.062 138	0.004 206	0.014 172	0.009 286	0.010 99
DCP 9	.250	1.266	0.242 41	0.202 67	0.069 106	0.096 53	0.100 123	0.009 105	0.055 125	0.028 181	0.018 100
DCP10	.300	1.110	0.254 36	0.175 66	0.049 88	0.081 61	0.079 114	0.032 64	0.064 115	0.028 131	0.019 101
DCP11	.399	0.910	0.261 34	0.057 34	0.029 66	0.022 61	0.029 72	0.024 29	0.026 78	0.014 24	0.016 70
DCP12	.531	0.693	0.247 33	0.031 336	0.027 64	0.001 290	0.016 72	0.011 22	0.013 68	0.008 14	0.013 47
DCP13	.600	0.542	0.205 38	0.049 279	0.031 63	0.010 265	0.011 48	0.008 352	0.011 12	0.009 292	0.008 47
DCP14	.701	0.441	0.154 43	0.073 265	0.020 86	0.019 235	0.006 43	0.007 311	0.005 326	0.009 302	0.006 305
DCP15	.830	0.268	0.159 28	0.060 269	0.016 60	0.012 252	0.004 349	0.007 323	0.007 282	0.002 290	0.008 336
DCP16	.900	0.010	0.148 9	0.032 271	0.013 6	0.006 100	0.008 337	0.006 15	0.006 313	0.003 329	0.006 315
DCP17	.965	-0.052	0.057 12	0.012 332	0.007 346	0.005 68	0.004 35	0.007 5	0.004 357	0.004 263	0.002 326

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.17	0.060	0.591	4.59	0.0	9.02	12057.1	23

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
198.0 (649.7)	102248. (2135.5)	0.92E 07	-0.062	1.175	13.34	-0.00132	2.177	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		9.007	4.596 3	0.247 16	0.084 177	0.016 5	0.017 35	0.019 103	0.036 3	0.040 261	0.002 299
CN		0.912	0.148 48	0.005 72	0.042 124	0.018 98	0.014 95	0.009 71	0.003 37	0.001 68	0.003 65
CM		-0.016	0.047 237	0.317 97	0.007 166	0.002 113	0.005 148	0.003 168	0.002 95	0.002 87	0.001 108
DCP 1	.013	3.215	0.244 355	0.473 75	0.104 105	0.024 135	0.012 350	0.024 53	0.017 1	0.014 30	0.011 16
DCP 2	.020	3.025	0.343 356	0.521 80	0.094 111	0.050 135	0.049 130	0.017 147	0.019 340	0.025 40	0.015 66
DCP 3	.030	2.871	0.443 1	0.499 75	0.071 72	0.095 133	0.047 76	0.016 221	0.017 336	0.019 340	0.005 82
DCP 4	.049	2.677	0.307 225	0.409 41	0.127 173	0.154 127	0.046 130	0.022 136	0.021 100	0.046 126	0.012 110
DCP 5	.070	2.548	0.252 176	0.346 74	0.156 174	0.157 99	0.079 155	0.077 103	0.031 145	0.052 116	0.012 110
DC 6	.095	2.425	0.433 151	0.295 50	0.264 157	0.035 47	0.135 150	0.061 161	0.061 154	0.025 108	0.026 144
DCP 7	.149	1.894	0.367 153	0.256 51	0.369 144	0.143 239	0.014 169	0.009 160	0.025 232	0.032 47	0.018 178
DCP 8	.200	1.356	0.279 56	0.304 47	0.157 172	0.078 133	0.077 136	0.013 153	0.021 148	0.006 72	0.004 50
DCP 9	.250	1.271	0.255 40	0.190 61	0.073 57	0.069 13	0.082 71	0.308 15	0.043 45	0.014 147	0.016 60
DCP10	.300	1.112	0.272 35	0.123 62	0.063 41	0.069 26	0.054 55	0.028 39	0.044 44	0.008 39	0.026 54
DCP11	.399	0.907	0.248 32	0.044 45	0.069 25	0.017 26	0.026 17	0.013 17	0.021 16	0.015 297	0.004 23
DCP12	.531	0.698	0.224 33	0.024 339	0.023 16	0.002 18	0.011 348	0.009 36	0.013 343	0.013 273	0.007 18
DCP13	.600	0.530	0.176 39	0.034 247	0.010 32	0.011 172	0.006 317	0.009 56	0.015 287	0.005 249	0.013 304
DCP14	.701	0.446	0.122 53	0.047 259	0.009 110	0.014 148	0.006 352	0.009 358	0.015 249	0.010 236	0.006 242
DCP15	.830	0.250	0.124 51	0.040 261	0.005 54	0.006 153	0.004 234	0.008 12	0.013 238	0.003 210	0.005 214
DCP16	.900	0.000	0.120 13	0.020 273	0.009 333	0.002 336	0.035 242	0.007 330	0.010 216	0.002 344	0.006 265
DCP17	.965	-0.047	0.051 13	0.008 281	0.011 337	0.003 315	0.031 44	0.007 357	0.005 258	0.006 294	0.005 260

FORCED PITCHING OSCILLATION　　　　AIRFOIL　　NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.10	0.060	0.601	4.89	0.0	12.19	12057.2	20

V	L	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
197.6	102033.	0.92E 07	-0.083	1.164	10.60	-0.00122	1.922	0.0
(648.3)	(2131.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.191	4.890 0	0.242 10	0.040 240	0.018 279	0.026 36	0.016 342	0.322 296	0.030 283	0.004 109
CN		0.985	0.130 79	0.014 144	0.023 177	0.017 219	0.010 238	0.008 206	0.006 315	0.004 352	0.001 330
CM		-0.022	0.058 195	0.001 132	0.006 158	0.003 284	0.001 315	0.002 306	0.001 101	0.001 87	0.001 234
DCP 1	.010	3.196	0.353 146	0.259 68	0.143 152	0.045 34	0.058 162	0.022 25	0.016 138	0.018 53	0.015 71
DCP 2	.020	3.184	0.345 142	0.240 71	0.149 153	0.032 50	0.019 133	0.010 133	0.013 135	0.008 159	0.022 77
DCP 3	.035	3.114	0.206 170	0.257 92	0.111 167	0.034 104	0.035 206	0.011 176	0.016 189	0.004 21	0.005 219
DCP 4	.049	2.725	0.522 170	0.113 61	0.178 185	0.057 252	0.054 214	0.056 241	0.012 257	0.005 299	0.014 316
DCP 5	.074	2.574	0.591 168	0.022 4	0.153 174	0.115 258	0.029 250	0.056 243	0.016 19	0.011 315	0.014 18
DCP 6	.099	2.419	0.732 164	0.135 293	0.110 161	0.131 249	0.050 303	0.028 218	0.026 5	0.026 16	0.003 221
DCP 7	.149	1.997	0.554 145	0.224 232	0.055 292	0.003 34	0.009 222	0.030 72	0.017 119	0.017 231
DCP 8	.200	1.567	0.265 114	0.088 171	0.086 179	0.034 248	0.013 306	0.006 189	0.011 358	0.019 31	0.006 166
DCP 9	.250	1.468	0.231 108	0.048 167	0.076 162	0.064 220	0.025 255	0.016 271	0.020 321	0.006 11	0.014 350
DCP10	.300	1.243	0.169 66	0.068 98	0.074 152	0.064 217	0.032 256	0.019 262	0.029 296	0.013 330	0.010 309
DCP11	.399	1.035	0.251 43	0.075 63	0.031 136	0.036 172	0.021 228	0.015 236	0.023 264	0.010 312	0.006 228
DCP12	.531	0.762	0.246 34	0.026 78	0.008 447	0.024 146	0.007 261	0.016 174	0.009 247	0.005 341	0.006 240
DCP13	.601	0.591	0.230 28	0.007 233	0.025 317	0.008 109	0.005 181	0.007 135	0.004 329	0.004 284	0.006 104
DCP14	.701	0.475	0.189 26	0.037 244	0.033 420	0.008 68	0.007 205	0.014 127	0.004 37	0.003 146	0.006 115
DCP15	.803	0.298	0.196 19	0.021 244	0.010 329	0.009 74	0.005 121	0.006 110	0.004 61	0.002 217	0.007 49
DCP16	.904	0.037	0.150 20	0.015 14	0.004 267	0.010 85	0.102 45	0.003 154	0.002 442	0.002 317	0.006 8
DCP17	.964	-0.035	0.058 15	0.012 44	0.006 67	0.001 345	0.007 85	0.000 89	0.003 227	0.002 257	0.006 24

FORCED PITCHING OSCILLATION　　　　AIRFOIL　　NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	24.12	0.060	0.599	4.92	0.0	14.85	12057.3	20

V	L	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
196.6	100960.	0.92E 07	-0.100	1.167	17.48	-0.00145	2.269	0.0
(645.1)	(2108.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		14.849	4.922 0	0.206 4	0.025 279	0.021 209	0.033 10	0.023 24	0.011 74	0.028 130	0.010 305
CN		1.010	0.147 71	0.013 251	0.009 346	0.005 213	0.004 245	0.008 287	0.002 11	0.004 185	0.003 202
CM		-0.043	0.054 199	0.006 213	0.001 105	0.001 335	0.002 339	0.002 38	0.001 22	0.002 328	0.001 47
DCP 1	.010	3.290	0.992 149	0.052 55	0.021 139	0.019 293	0.002 154	0.026 290	0.012 332	0.035 276	0.006 120
DCP 2	.020	3.341	0.430 143	0.037 81	0.073 121	0.051 238	0.026 157	0.029 345	0.024 327	0.045 266	0.006 102
DCP 3	.035	3.001	0.624 164	0.353 35	0.150 174	0.019 259	0.018 282	0.062 260	0.039 286	0.036 198	0.007 240
DCP 4	.049	2.656	0.539 150	0.168 251	0.050 278	0.057 299	0.022 335	0.012 321	0.022 32	0.003 92	0.006 1
DCP 5	.074	2.456	0.526 143	0.219 251	0.098 345	0.032 353	0.040 356	0.010 77	0.015 85	0.005 198	0.004 242
DCP 6	.099	2.220	0.442 136	0.147 252	0.062 351	0.018 57	0.019 30	0.007 31	0.024 10	0.009 9	0.015 21
DCP 7	.149	1.800	0.224 100	0.015 338	0.050 23	0.015 137	0.016 276	0.017 9	0.027 72	0.017 258	0.007 286
DCP 8	.200	1.499	0.125 132	0.056 245	0.024 337	0.020 273	0.004 16	0.017 240	0.010 174	0.011 230	0.009 77
DCP 9	.250	1.452	0.148 101	0.033 227	0.015 343	0.012 200	0.032 274	0.026 308	0.001 84	0.004 232	0.002 129
DCP10	.300	1.242	0.150 85	0.038 191	0.007 63	0.011 155	0.021 249	0.017 327	0.004 42	0.005 170	0.010 179
DCP11	.399	1.085	0.196 60	0.031 158	0.012 102	0.018 171	0.013 230	0.023 296	0.012 322	0.006 51	0.014 169
DCP12	.531	0.658	0.222 45	0.025 98	0.007 28	0.013 162	0.017 173	0.019 267	0.009 337	0.004 143	0.001 200
DCP13	.601	0.665	0.233 32	0.033 48	0.009 0	0.005 151	0.006 133	0.006 236	0.004 20	0.014 144	0.005 187
DCP14	.701	0.550	0.221 27	0.020 31	0.010 307	0.006 273	0.009 166	0.010 177	0.007 161	0.007 144	0.005 304
DCP15	.803	0.372	0.216 20	0.017 9	0.011 295	0.010 274	0.006 128	0.006 160	0.007 193	0.010 146	0.005 246
DCP16	.904	0.105	0.149 27	0.025 17	0.010 238	0.003 303	0.004 0	0.011 217	0.010 197	0.004 231	0.004 229
DCP17	.964	-0.008	0.058 36	0.010 34	0.032 220	0.005 308	0.002 102	0.001 70	0.006 212	0.004 178	0.007 241

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

FREQ. HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
3.3	23.15	3.063	3.596	4.97	3.0	17.15	12357.4	20

V	W	RN	CM(MIN)	CM(MAX)	ALPHA.MAX	AER. DAMP	TDR	EXT DAMP
195.4	99524.	0.91E 07	-3.119	1.197	16.95	-3.00199	3.094	0.0
(641.2)	(2078.6)							

HARMONIC ANALYSIS

DATA TYPE	K/	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		17.150	4.946 0	0.143 7	0.043 273	0.016 195	0.327 37	0.010 59	0.313 216	0.034 126	0.079 309
CN		1.016	0.141 66	0.327 52	0.038 232	0.002 55	0.334 343	0.002 313	0.035 281	0.001 1	0.032 198
CM		-0.077	0.345 211	0.307 234	0.003 43	0.032 238	0.003 151	0.001 169	0.001 59	0.000 95	0.001 53

(numeric data rows — largely illegible)

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

FREQ. HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
3.3	23.20	3.095	3.606	5.19	0.0	0.93	12054.1	20

V	W	RN	CM(MIN)	CM(MAX)	ALPHA.MAX	AERO DAMP	TDR	EXT DAMP
199.7	69465.	0.62E 07	-0.026	3.563	5.53	-0.00086	1.045	0.0
(655.2)	(1450.8)							

HARMONIC ANALYSIS

DATA TYPE	K/	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.528	5.176 0	0.202 4	0.061 273	0.023 179	0.028	026 121	0.017 216	0.003 194	0.006 334
CN		0.143	0.423 355	3.012 231	3.334 291	3.001 29	3.002	.001 146	0.030 231	0.005 219	0.002 131
CM		-0.017	0.009 265	3.001 338	3.001 106	3.001 19	3.001 167	0.000 169	0.000 111	0.001 350	0.000 110

(numeric data rows — largely illegible)

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.33	0.060	0.605	5.20	0.0	2.41	12059.2	20

V_	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
199.3 (653.9)	69292. (1447.2)	0.62E 07	-0.040	0.910	7.52	-0.00096	1.522	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.407	5.201 0	0.275 359	0.098 301	0.029 183	0.042 22	0.020 145	0.018 22	0.164 6	0.025 177
CN		0.345	0.548 354	0.031 340	0.018 314	0.010 174	0.008 45	0.003 202	0.012 14	0.040 15	0.007 179
CM		0.002	0.024 330	0.002 210	0.004 171	0.001 304	0.002 207	0.002 25	0.004 198	0.015 196	0.002 353
DCP 1	.010	0.306	3.149 347	0.300 47	0.033 357	0.063 224	0.012 145	0.027 131	0.011 181	0.010 303	0.006 259
DCP 2	.020	0.750	2.595 350	0.150 27	0.038 138	0.060 203	0.061 291	0.067 20	0.039 60	0.035 170	0.022 249
DCP 3	.030	0.929	2.200 350	0.084 348	0.035 303	0.033 59	0.005 3	0.014 90	0.021 304	0.012 232	0.002 337
DCP 4	.049	1.147	1.954 350	0.073 12	0.062 318	0.015 93	0.034 316	0.017 191	0.016 304	0.015 210	0.004 103
DCP 5	.074	1.253	1.799 350	0.055 333	0.071 323	0.023 206	0.024 323	0.027 195	0.005 101	0.011 210	0.010 88
DCP 6	.099	1.297	1.720 351	0.064 290	0.084 323	0.079 226	0.021 111	0.020 215	0.019 127	0.000 146	0.010 92
DCP 7	.149	0.952	1.342 353	0.225 280	0.087 197	0.065 194	0.103 126	0.078 38	0.023 307	0.017 17	0.026 286
DCP 8	.200	0.629	0.861 355	0.068 310	0.062 176	0.061 73	0.032 338	0.002 279	0.014 285	0.009 227	0.007 156
DCP 9	.250	0.361	0.675 354	0.048 11	0.026 302	0.013 127	0.024 347	0.013 265	0.012 10	0.043 14	0.017 138
DCP10	.300	0.324	0.558 353	0.043 25	0.031 330	0.006 102	0.005 2	0.013 227	0.014 47	0.040 359	0.003 154
DCP11	.399	0.279	0.450 357	0.032 26	0.035 329	0.009 191	0.007 9	0.010 229	0.017 35	0.056 13	0.012 171
DCP12	.501	0.210	0.338 359	0.031 28	0.028 315	0.008 241	0.007 51	0.007 251	0.012 9	0.052 25	0.014 191
DCP13	.600	0.199	0.234 2	0.021 7	0.023 336	0.010 189	0.009 41	0.002 166	0.015 4	0.056 20	0.007 202
DCP14	.701	0.252	0.152 6	0.018 27	0.019 331	0.011 138	0.013 37	0.008 197	0.020 24	0.055 17	0.005 227
DCP15	.800	0.109	0.068 19	0.019 348	0.014 350	0.003 100	0.008 10	0.014 192	0.016 18	0.062 17	0.006 151
DCP16	.900	-0.099	0.009 112	0.007 286	0.014 31	0.005 131	0.012 39	0.006 191	0.022 19	0.060 8	0.020 162
DCP17	.969	-0.061	0.040 170	0.018 272	0.016 336	0.006 173	0.009 27	0.012 197	0.013 2	0.048 24	0.005 185

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.25	0.060	0.601	5.20	0.0	4.89	12059.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
197.8 (649.1)	68526. (1431.2)	0.62E 07	-0.016	0.954	9.56	-0.00103	1.630	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.887	5.204 0	0.208 14	0.059 289	0.008 208	0.032 352	0.012 246	0.029 128	0.008 91	0.012 297
CN		0.603	0.363 0	0.068 45	0.013 9	0.004 351	0.004 101	0.007 50	0.006 11	0.005 348	0.004 302
CM		0.002	0.016 302	0.010 186	0.007 75	0.003 352	0.001 289	0.001 263	0.001 104	0.001 78	0.000 240
DCP 1	.010	1.773	1.824 349	0.218 80	0.068 41	0.010 44	0.016 51	0.012 10	0.004 73	0.007 19	0.005 140
DCP 2	.020	1.841	1.625 352	0.152 73	0.052 45	0.027 342	0.008 261	0.013 12	0.012 336	0.010 51	0.005 317
DCP 3	.030	1.860	1.445 352	0.131 66	0.038 66	0.034 353	0.021 279	0.009 15	0.013 305	0.004 82	0.005 341
DCP 4	.049	1.921	1.201 350	0.164 90	0.075 66	0.059 22	0.044 291	0.015 220	0.010 276	0.006 172	0.003 196
DCP 5	.074	1.868	1.015 349	0.198 102	0.136 66	0.071 28	0.040 328	0.016 242	0.009 324	0.008 247	0.005 229
DCP 6	.099	1.788	0.907 350	0.221 101	0.178 57	0.055 37	0.036 11	0.006 187	0.022 24	0.008 313	0.004 208
DCP 7	.149	1.334	0.778 358	0.108 74	0.158 50	0.080 351	0.043 39	0.054 358	0.026 41	0.039 19	0.007 253
DCP 8	.200	1.018	0.614 1	0.067 32	0.034 38	0.064 345	0.043 282	0.013 260	0.016 328	0.007 284	0.009 273
DCP 9	.250	0.859	0.643 1	0.127 353	0.047 264	0.055 235	0.068 163	0.044 93	0.026 71	0.028 26	0.021 325
DCP10	.300	0.723	0.491 1	0.099 4	0.040 250	0.030 200	0.041 138	0.033 67	0.019 25	0.019 346	0.018 306
DCP11	.399	0.571	0.349 7	0.093 27	0.027 273	0.017 185	0.014 123	0.012 67	0.007 23	0.007 352	0.009 306
DCP12	.501	0.417	0.248 11	0.083 31	0.027 277	0.010 168	0.007 94	0.006 69	0.005 9	0.004 302	0.003 266
DCP13	.600	0.333	0.160 20	0.080 40	0.024 289	0.010 171	0.008 73	0.007 17	0.003 280	0.004 244	0.001 338
DCP14	.701	0.323	0.072 45	0.072 46	0.017 302	0.004 157	0.002 312	0.001 222	0.003 291	0.002 210	0.002 60
DCP15	.800	0.144	0.050 48	0.037 32	0.010 267	0.004 121	0.003 72	0.001 201	0.003 203	0.004 240	0.004 115
DCP16	.900	-0.087	0.037 27	0.022 308	0.015 219	0.009 133	0.005 69	0.002 100	0.003 265	0.002 276	0.003 70
DCP17	.969	-0.075	0.010 170	0.009 295	0.006 255	0.004 154	0.004 46	0.001 77	0.003 327	0.003 304	0.000 96

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.26	0.060	0.600	5.06	0.0	6.60	12059.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
197.4	68397.	0.62E 07	-0.029	1.097	9.79	-0.00112	1.766	0.0
(647.6)	(1428.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		6.596	5.063 0	0.249 19	0.044 263	0.008 83	0.033 27	0.035 359	0.051 181	0.034 114	0.003 160
CN		0.709	0.294 9	0.133 49	0.030 357	0.017 6	0.014 323	0.008 287	0.006 220	0.010 129	0.000 99
CM		-0.003	0.016 263	0.015 102	0.005 7	0.002 100	0.001 26	0.001 69	0.002 354	0.003 286	0.000 137
DCP 1	.010	2.345	1.624 350	0.503 58	0.062 15	0.034 18	0.008 311	0.010 240	0.016 130	0.006 166	0.006 19
DCP 2	.020	2.343	1.567 353	0.387 58	0.091 8	0.034 18	0.031 311	0.008 276	0.006 210	0.006 170	0.006 64
DCP 3	.030	2.335	1.376 353	0.349 60	0.109 6	0.026 347	0.033 327	0.019 309	0.013 249	0.005 199	0.011 153
DCP 4	.049	2.186	0.814 349	0.543 74	0.172 14	0.029 314	0.036 352	0.022 320	0.021 301	0.016 271	0.013 234
DCP 5	.074	2.075	0.591 349	0.613 72	0.137 12	0.045 36	0.049 345	0.013 234	0.015 334	0.007 301	0.011 293
DCP 6	.099	1.948	0.468 354	0.672 70	0.099 10	0.099 49	0.033 357	0.008 24	0.021 305	0.014 162	0.020 331
DCP 7	.149	1.682	0.571 9	0.471 62	0.163 359	0.117 42	0.054 340	0.035 23	0.013 86	0.014 191	0.036 89
DCP 8	.200	1.156	0.547 12	0.227 46	0.128 348	0.031 303	0.041 326	0.016 290	0.009 257	0.008 44	0.005 331
DCP 9	.250	1.004	0.472 11	0.162 29	0.069 340	0.022 292	0.033 318	0.020 271	0.019 271	0.013 177	0.011 262
DCP10	.300	0.856	0.380 11	0.121 20	0.029 321	0.019 313	0.024 293	0.015 260	0.019 250	0.020 171	0.011 193
DCP11	.399	0.668	0.294 18	0.093 21	0.006 305	0.014 343	0.011 311	0.015 276	0.012 208	0.015 13	0.005 167
DCP12	.501	0.516	0.230 23	0.069 15	0.006 161	0.016 2	0.012 312	0.015 276	0.016 197	0.016 1	0.003 175
DCP13	.600	0.408	0.169 29	0.062 9	0.012 201	0.007 356	0.037 293	0.011 261	0.012 185	0.016 112	0.005 74
DCP14	.701	0.368	0.091 52	0.339 4	0.016 153	0.012 344	0.006 207	0.002 353	0.008 180	0.012 103	0.003 347
DCP15	.800	0.182	0.083 42	0.032 352	0.007 224	0.005 284	0.003 147	0.001 92	0.003 180	0.010 90	0.003 6
DCP16	.900	-0.053	0.080 14	0.029 262	0.001 146	0.008 285	0.003 289	0.005 216	0.005 99	0.011 99	0.005 273
DCP17	.969	-0.068	0.018 5	0.017 260	0.002 268	0.002 329	0.002 50	0.002 276	0.006 169	0.011 120	0.002 42

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.26	0.060	0.599	4.96	0.0	9.80	12059.5	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
196.8	68210.	0.62E 07	-0.093	1.125	9.40	-0.00132	1.598	0.0
(645.8)	(1424.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		9.803	4.964 0	0.247 11	0.097 308	0.057 162	0.043 74	0.118 138	0.163 235	0.159 222	0.035 45
CN		0.859	0.138 61	0.108 58	0.031 106	0.039 97	0.004 319	0.017 74	0.015 223	0.040 237	0.012 81
CM		-0.016	0.044 199	0.019 106	0.007 198	0.007 212	0.005 106	0.006 180	0.009 60	0.017 52	0.006 212
DCP 1	.010	3.190	0.285 358	0.466 70	0.083 108	0.039 118	0.024 30	0.006 323	0.015 7	0.073 342	0.015 340
DCP 2	.020	3.018	0.405 358	0.474 77	0.111 109	0.032 112	0.044 104	0.013 133	0.013 14	0.023 16	0.008 325
DCP 3	.030	2.829	0.279 357	0.517 78	0.080 93	0.050 97	0.038 89	0.014 197	0.003 82	0.016 14	0.007 225
DCP 4	.049	2.454	0.350 183	0.519 85	0.092 154	0.131 109	0.067 99	0.026 133	0.043 84	0.021 345	0.018 158
DCP 5	.074	2.331	0.506 174	0.394 80	0.152 162	0.089 108	0.061 131	0.018 155	0.034 111	0.004 234	0.015 147
DCP 6	.099	2.235	0.636 165	0.263 73	0.214 156	0.061 156	0.060 151	0.009 148	0.024 119	0.008 241	0.005 180
DCP 7	.149	1.761	0.603 135	0.329 73	0.280 144	0.111 199	0.037 267	0.005 226	0.008 14	0.011 327	0.014 256
DCP 8	.200	1.327	0.262 72	0.324 72	0.115 131	0.071 87	0.070 133	0.022 177	0.016 129	0.001 65	0.005 204
DCP 9	.250	1.140	0.266 58	0.262 74	0.092 8	0.160 109	0.024 14	0.127 101	0.017 231	0.028 110	0.057 199
DCP10	.300	1.011	0.288 53	0.214 60	0.113 2	0.082 93	0.030 0	0.081 95	0.024 124	0.025 243	0.007 157
DCP11	.399	0.822	0.237 51	0.110 27	0.040 328	0.070 121	0.032 338	0.056 136	0.016 94	0.058 248	0.051 80
DCP12	.501	0.652	0.258 41	0.069 344	0.034 39	0.030 84	0.028 323	0.032 85	0.020 284	0.056 248	0.018 60
DCP13	.600	0.512	0.178 39	0.055 316	0.005 154	0.033 81	0.019 349	0.040 332	0.029 228	0.063 256	0.026 58
DCP14	.701	0.456	0.149 30	0.067 273	0.032 101	0.021 11	0.018 257	0.048 353	0.071 240	0.055 202	0.048 5
DCP15	.800	0.260	0.138 27	0.046 313	0.025 47	0.032 15	0.025 266	0.019 316	0.036 226	0.069 238	0.020 344
DCP16	.900	0.033	0.166 356	0.024 289	0.034 80	0.038 37	0.011 243	0.020 348	0.035 249	0.085 222	0.022 40
DCP17	.969	-0.037	0.052 333	0.018 342	0.010 20	0.029 9	0.017 193	0.033 16	0.005 226	0.067 241	0.014 62

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.21	0.060	0.599	4.94	0.0	12.31	12059.6	23

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
196.8	68201.	0.62E 07	-0.099	1.097	11.42	-0.00122	1.914	0.0
(645.6)	(1424.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.306	4.937 0	0.224 10	0.048 244	0.012 203	0.027 47	0.019 46	0.033 221	0.032 189	0.014 3
CN		0.926	0.156 91	0.022 21	0.024 157	0.006 289	0.007 248	0.002 149	0.004 164	0.002 210	0.003 64
CM		-0.030	0.067 193	0.003 152	0.007 158	0.002 236	0.001 21	0.001 264	0.002 296	0.002 53	0.001 198
DCP 1	.010	3.405	0.158 143	0.154 75	0.096 159	0.015 77	0.029 154	0.006 247	0.023 154	0.008 98	0.006 109
DCP 2	.020	3.307	0.129 159	0.211 97	0.102 155	0.038 127	0.004 7	0.020 222	0.015 195	0.011 199	0.002 193
DCP 3	.030	3.082	0.236 172	0.234 93	0.117 170	0.050 126	0.011 227	0.011 164	0.006 248	0.001 12	0.006 34
DCP 4	.049	2.419	0.902 169	0.164 53	0.247 183	0.029 285	0.083 228	0.007 212	0.037 249	0.008 63	0.015 300
DCP 5	.074	2.241	0.898 165	0.088 339	0.154 177	0.070 290	0.031 282	0.007 333	0.010 33	0.017 94	0.009 39
DCP 6	.099	2.087	0.870 160	0.108 283	0.054 165	0.056 288	0.034 356	0.015 87	0.015 120	0.016 105	0.024 146
DCP 7	.149	1.755	0.659 145	0.151 262	0.013 99	0.036 349	0.044 87	0.032 183	0.012 255	0.005 185	0.007 258
DCP 8	.200	1.465	0.396 126	0.013 102	0.095 158	0.037 266	0.006 314	0.007 301	0.005 29	0.002 70	0.005 114
DCP 9	.250	1.335	0.299 106	0.070 67	0.116 139	0.053 231	0.036 308	0.017 344	0.011 290	0.005 54	0.006 107
DCP10	.300	1.151	0.242 77	0.095 56	0.094 135	0.034 218	0.025 274	0.011 355	0.007 254	0.005 314	0.007 49
DCP11	.399	0.930	0.230 52	0.077 61	0.026 109	0.005 65	0.020 242	0.014 225	0.015 212	0.007 239	0.003 128
DCP12	.501	0.730	0.258 42	0.046 34	0.009 328	0.011 46	0.015 208	0.006 95	0.010 149	0.004 78	0.012 87
DCP13	.600	0.563	0.248 34	0.024 336	0.025 319	0.003 62	0.010 184	0.012 114	0.012 85	0.008 269	0.008 63
DCP14	.701	0.443	0.219 25	0.037 276	0.032 318	0.014 17	0.007 251	0.005 10	0.008 108	0.004 219	0.004 74
DCP15	.800	0.324	0.228 15	0.022 253	0.023 344	0.007 35	0.003 286	0.006 145	0.007 109	0.008 239	0.012 349
DCP16	.900	0.075	0.168 5	0.013 18	0.011 299	0.007 60	0.007 170	0.002 20	0.006 133	0.005 192	0.003 275
DCP17	.969	-0.019	0.081 3	0.010 16	0.003 256	0.006 47	0.004 115	0.002 25	0.001 159	0.010 210	0.006 333

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.28	0.061	0.597	4.97	0.0	14.84	12059.7	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
195.8	67832.	0.62E 07	-0.112	1.136	14.81	-0.00189	2.953	0.0
(642.3)	(1416.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		14.843	4.971 0	0.217 4	0.047 261	0.017 188	0.024 60	0.009 317	0.032 262	0.034 148	0.011 0
CN		0.960	0.164 82	0.017 332	0.020 98	0.003 244	0.013 60	0.007 145	0.002 205	0.010 178	0.008 333
CM		-0.056	0.060 232	0.015 245	0.004 282	0.003 266	0.003 249	0.002 270	0.002 344	0.002 339	0.002 194
DCP 1	.010	3.380	0.411 168	0.021 212	0.091 166	0.040 253	0.009 300	0.031 289	0.017 295	0.004 334	0.003 278
DCP 2	.020	3.253	0.383 171	0.021 236	0.101 174	0.025 300	0.015 351	0.034 344	0.014 22	0.007 12	0.004 224
DCP 3	.030	2.780	0.509 174	0.178 267	0.067 261	0.059 320	0.017 298	0.033 359	0.034 119	0.018 222	0.007 156
DCP 4	.049	2.282	0.768 163	0.240 279	0.006 134	0.071 317	0.041 71	0.001 175	0.030 54	0.014 188	0.008 242
DCP 5	.074	2.053	0.583 154	0.194 281	0.034 52	0.015 309	0.029 79	0.007 199	0.014 39	0.016 156	0.008 289
DCP 6	.099	1.904	0.451 144	0.128 278	0.029 62	0.015 250	0.032 34	0.013 150	0.021 347	0.026 122	0.009 207
DCP 7	.149	1.660	0.339 122	0.095 257	0.021 33	0.020 250	0.026 15	0.006 158	0.017 323	0.023 109	0.009 322
DCP 8	.200	1.487	0.286 112	0.089 245	0.015 38	0.014 263	0.009 46	0.008 207	0.007 342	0.006 106	0.009 281
DCP 9	.250	1.317	0.251 104	0.104 246	0.049 87	0.025 228	0.006 350	0.027 222	0.014 338	0.017 191	0.008 271
DCP10	.300	1.171	0.229 94	0.052 244	0.041 95	0.023 221	0.025 64	0.024 156	0.010 201	0.024 219	0.025 308
DCP11	.399	1.011	0.203 73	0.015 281	0.035 96	0.027 235	0.002 220	0.018 199	0.023 267	0.021 260	0.017 13
DCP12	.501	0.824	0.231 53	0.026 56	0.033 112	0.016 215	0.011 68	0.024 166	0.009 186	0.027 232	0.014 305
DCP13	.600	0.682	0.246 40	0.069 55	0.022 117	0.019 114	0.021 107	0.021 128	0.009 186	0.008 162	0.014 359
DCP14	.701	0.590	0.253 30	0.071 64	0.019 88	0.030 61	0.023 91	0.010 49	0.015 146	0.018 127	0.005 44
DCP15	.800	0.417	0.240 21	0.050 67	0.011 129	0.021 91	0.016 26	0.013 34	0.008 97	0.017 131	0.004 3
DCP16	.900	0.157	0.183 22	0.040 42	0.006 113	0.013 27	0.017 43	0.013 45	0.010 156	0.012 100	0.008 95
DCP17	.969	0.010	0.081 27	0.017 28	0.012 78	0.007 350	0.007 334	0.008 43	0.009 129	0.014 188	0.008 38

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.23	0.060	0.597	5.02	0.0	17.35	12059.8	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
195.5	67861.	0.62E 07	-0.130	1.095	21.37	-0.00229	3.579	0.0
(641.5)	(1417.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		17.349	5.018 0	0.210 6	0.042 278	0.014 188	0.034 31	0.022 57	0.019 226	0.029 223	0.012 317
CN		0.947	0.155 62	3.013 216	0.009 283	0.003 118	0.006 254	0.001 70	0.001 352	0.003 46	0.002 306
CM		-0.083	0.046 218	0.008 254	0.003 32	0.001 267	0.002 31	0.001 152	0.001 196	0.001 82	0.001 103
DCP 1	.010	3.259	0.150 172	0.035 337	0.045 3	0.004 237	0.020 25	0.035 204	0.004 346	0.021 75	0.004 8
DCP 2	.020	3.123	0.209 166	0.066 11	0.041 347	0.006 21	0.010 330	0.030 221	0.014 275	0.030 88	0.004 107
DCP 3	.030	2.907	0.335 160	0.031 268	0.037 328	0.009 88	0.024 307	0.010 259	0.001 14	0.018 150	0.004 303
DCP 4	.049	1.867	0.290 139	0.143 257	0.041 347	0.003 342	0.009 352	0.018 65	0.009 98	0.031 73	0.013 96
DCP 5	.074	1.709	0.208 123	0.100 254	0.024 339	0.012 315	0.008 348	0.015 67	0.011 217	0.023 62	0.004 128
DCP 6	.099	1.606	0.166 105	0.073 257	0.010 352	0.005 271	0.009 308	0.010 126	0.007 202	0.031 68	0.006 162
DCP 7	.149	1.439	0.153 77	0.040 247	0.010 352	0.010 110	0.007 245	0.006 81	0.005 165	0.021 68	0.002 219
DCP 8	.200	1.328	0.147 71	0.042 228	0.011 291	0.007 183	0.010 283	0.006 86	0.004 169	0.019 83	0.013 268
DCP 9	.250	1.229	0.176 72	0.086 231	0.032 307	0.004 49	0.005 243	0.005 183	0.007 267	0.008 289	0.007 40
DCP10	.300	1.127	0.175 67	0.069 219	0.019 290	0.002 55	0.005 287	0.002 177	0.004 259	0.013 299	0.011 20
DCP11	.399	1.020	0.191 62	0.050 207	0.018 260	0.010 208	0.008 233	0.012 169	0.004 249	0.010 236	0.011 303
DCP12	.501	0.879	0.200 52	0.019 197	0.008 273	0.007 180	0.016 294	0.010 13	0.001 25	0.011 296	0.007 329
DCP13	.600	0.764	0.217 50	0.025 112	0.010 210	0.010 180	0.015 285	0.013 20	0.011 46	0.005 290	0.006 231
DCP14	.701	0.685	0.212 43	0.043 75	0.008 162	0.014 106	0.010 199	0.003 309	0.007 20	0.005 4	3.006 178
DCP15	.800	0.520	0.193 31	0.049 53	0.014 228	0.012 36	0.009 172	0.003 261	0.004 36	0.005 114	0.004 336
DCP16	.900	0.241	0.147 44	0.035 57	0.009 237	0.007 44	0.011 179	0.004 282	0.005 336	0.002 95	0.003 242
DCP17	.969	0.055	0.072 57	0.018 42	0.005 197	0.006 57	0.009 213	0.000 73	0.002 214	0.005 202	0.000 100

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.11	0.060	0.597	5.19	0.0	2.52	12061.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
197.3	34316.	0.31E 07	-0.031	0.932	7.72	-0.00100	1.566	0.0
(647.2)	(716.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.517	5.194 0	0.202 11	0.063 288	0.023 167	0.038 353	0.014 46	0.019 189	0.012 293	0.008 6
CN		0.394	0.541 354	0.034 4	0.014 282	0.008 167	0.004 59	0.001 170	0.002 290	0.010 318	0.003 40
CM		-0.004	0.025 329	0.004 254	0.001 114	0.000 319	0.001 200	0.001 39	0.001 135	0.003 131	0.001 268
DCP 1	.010	0.760	3.124 347	0.250 41	0.037 319	0.038 191	0.039 147	0.022 139	0.008 148	0.004 89	0.018 312
DCP 2	.020	0.689	2.671 350	0.221 41	0.066 149	0.042 197	0.042 268	0.018 51	0.024 291	0.008 290	0.015 22
DCP 3	.030	0.940	2.184 350	0.082 347	0.060 295	0.054 63	0.014 320	0.017 73	0.013 329	0.024 182	0.015 255
DCP 4	.049	1.151	1.965 350	0.079 10	0.074 312	0.029 94	0.002 314	0.023 187	0.008 279	0.014 196	0.005 56
DCP 5	.074	1.231	1.773 350	0.064 1	0.108 321	0.043 216	0.007 332	0.020 213	0.007 175	0.016 199	0.014 90
DCP 6	.099	1.217	1.610 351	0.074 324	0.094 316	0.066 225	0.015 176	0.023 202	0.020 132	0.003 217	0.007 93
DCP 7	.149	0.928	1.276 354	0.151 297	0.049 260	0.106 225	0.139 136	0.065 41	0.028 100	0.067 20	0.035 297
DCP 8	.200	0.658	0.916 355	0.100 293	0.073 181	0.051 84	0.012 358	0.016 56	0.023 291	0.019 200	0.001 227
DCP 9	.250	0.543	0.722 354	0.047 332	0.047 169	0.052 68	0.040 321	0.019 233	0.006 210	0.013 282	0.009 62
DCP10	.300	0.465	0.570 354	0.045 14	0.011 181	0.024 71	0.024 322	0.017 231	0.007 224	0.004 284	0.010 79
DCP11	.399	0.403	0.436 359	0.055 42	0.013 328	0.005 89	0.011 336	0.007 242	0.000 318	0.016 318	0.009 32
DCP12	.501	0.292	0.323 1	0.041 43	0.014 319	0.003 131	0.008 353	0.003 259	0.004 321	0.017 310	0.003 30
DCP13	.600	0.261	0.219 6	0.042 53	0.020 311	0.008 180	0.012 24	0.003 197	0.004 293	0.009 313	0.005 70
DCP14	.701	0.265	0.131 9	0.036 55	0.013 306	0.006 242	0.004 58	0.005 156	0.007 351	0.011 325	0.004 132
DCP15	.800	0.120	0.056 26	0.020 45	0.010 297	0.007 201	0.009 84	0.001 156	0.005 245	0.010 316	0.001 134
DCP16	.900	-0.099	0.018 45	0.012 250	0.010 211	0.006 171	0.002 327	0.001 216	0.003 343	0.019 300	0.005 54
DCP17	.969	-0.075	0.029 171	0.012 236	0.003 30	0.003 165	0.006 105	0.001 69	0.005 328	0.009 330	0.002 116

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.4	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	23.09	0.060	0.505	5.11	0.0	7.54	12061.4	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	196.5	34210.	0.31E 07	-0.057	1.128	10.41	-0.00123	1.926	0.0
	(644.7)	(714.5)							

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.543	5.112 0	0.249 19	0.029 272	0.001 117	0.064 38	0.001 305	0.023 132	0.019 155	0.008 223
CN		0.752	0.247 16	0.144 56	0.033 15	0.022 29	0.021 343	0.017 246	0.007 110	0.001 128	0.001 243
CM		-0.007	0.028 222	0.024 101	0.005 16	0.004 101	0.004 59	0.004 10	0.002 286	0.001 328	0.001 198
DCP 1	.010	2.993	1.259 350	0.161 62	0.087 33	0.060 31	0.032 328	0.019 240	0.008 135	0.006 70	0.014 100
DCP 2	.020	2.543	1.251 354	0.194 66	0.115 17	0.061 46	0.062 341	0.024 339	0.028 296	0.010 337	0.014 207
DCP 3	.030	2.509	1.137 353	0.386 66	0.113 21	0.051 44	0.079 344	0.026 329	0.038 293	0.011 5	0.010 199
DCP 4	.049	2.217	0.616 336	0.664 84	0.207 38	0.032 49	0.100 24	0.076 329	0.061 260	0.013 352	0.025 280
DCP 5	.074	2.062	0.229 328	0.695 81	0.138 53	0.060 87	0.109 44	0.056 309	0.005 316	0.037 7	0.029 274
DCP 6	.099	1.908	0.137 354	0.676 76	0.093 78	0.120 77	0.083 50	0.020 305	0.018 94	0.030 32	0.012 267
DCP 7	.149	1.504	0.305 18	0.564 72	0.092 20	0.203 55	0.098 87	0.021 13	0.104 108	0.031 145	0.036 119
DCP 8	.200	1.206	0.386 16	0.339 67	0.173 357	0.057 48	0.099 339	0.024 320	0.006 22	0.030 33	0.002 26
DCP 9	.250	1.060	0.399 16	0.262 51	0.144 348	0.035 344	0.097 325	0.052 259	0.025 291	0.025 283	0.023 259
DCP10	.300	0.907	0.347 19	0.177 38	0.091 345	0.030 310	0.064 317	0.049 244	0.011 265	0.024 240	0.017 223
DCP11	.399	0.758	0.311 24	0.119 23	0.029 329	0.025 312	0.034 304	0.043 235	0.008 162	0.018 229	0.007 161
DCP12	.501	0.564	0.250 23	0.072 3	0.008 221	0.008 314	0.019 279	0.026 220	0.014 137	0.005 108	0.001 243
DCP13	.600	0.455	0.199 30	0.061 341	0.017 170	0.010 330	0.013 240	0.017 200	0.014 92	0.005 169	0.009 38
DCP14	.701	0.378	0.131 40	0.050 338	0.032 153	0.009 335	0.005 178	0.012 181	0.011 91	0.004 75	0.005 357
DCP15	.800	0.208	0.129 29	0.053 294	0.014 144	0.009 301	0.011 240	0.015 175	0.010 77	0.004 132	0.005 2
DCP16	.900	-0.034	0.122 9	0.046 284	0.003 163	0.014 309	0.014 249	0.011 186	0.006 116	0.008 93	0.003 16
DCP17	.969	-0.071	0.044 10	0.022 283	0.002 357	0.008 331	0.003 197	0.007 188	0.005 167	0.007 117	0.005 4

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.4	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	23.12	0.060	0.594	4.88	0.0	10.04	12061.5	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	196.1	34143.	0.31E 07	-0.081	1.078	10.12	-0.00137	2.148	0.0
	(643.4)	(713.1)							

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		10.039	4.880 0	0.259 9	0.053 211	0.008 13	0.023 66	0.057 12	0.043 132	0.029 195	0.004 96
CN		0.849	0.132 58	0.088 61	0.038 136	0.013 66	0.007 150	0.008 340	0.036 164	0.005 192	0.002 210
CM		-0.016	0.053 200	0.018 99	0.008 173	0.004 106	0.001 210	0.004 123	0.001 359	0.001 30	0.001 56
DCP 1	.010	3.305	0.255 356	0.438 73	0.145 128	0.063 93	0.029 55	0.033 26	0.025 351	0.019 345	0.007 318
DCP 2	.020	2.962	0.412 356	0.445 79	0.135 131	0.073 88	0.052 129	0.014 93	0.005 343	0.007 112	0.003 348
DCP 3	.030	2.835	0.330 354	0.446 83	0.109 111	0.064 84	0.058 121	0.005 73	0.008 238	0.003 131	0.009 289
DCP 4	.049	2.358	0.446 185	0.481 87	0.161 173	0.169 109	0.041 126	0.064 148	0.038 94	0.027 203	0.018 155
DCP 5	.074	2.199	0.601 175	0.350 83	0.199 170	0.127 106	0.036 188	0.051 127	0.004 165	0.017 175	0.012 221
DCP 6	.099	2.060	0.632 166	0.248 80	0.236 166	0.054 113	0.044 204	0.014 143	0.001 220	0.018 227	0.008 298
DCP 7	.149	1.770	0.507 150	0.195 80	0.214 152	0.038 191	0.057 270	0.041 22	0.015 236	0.018 320	0.007 290
DCP 8	.200	1.337	0.197 81	0.346 79	0.169 147	0.073 83	0.045 150	0.009 296	0.010 265	0.015 108	0.006 7
DCP 9	.250	1.160	0.238 46	0.232 61	0.048 101	0.072 32	0.028 117	0.009 16	0.025 142	0.026 149	0.014 136
DCP10	.300	0.998	0.243 43	0.145 50	0.033 71	0.052 24	0.008 84	0.015 5	0.011 100	0.020 125	0.012 89
DCP11	.399	0.846	0.256 41	0.089 33	0.024 49	0.024 4	0.011 113	0.020 352	0.008 161	0.015 154	0.011 90
DCP12	.501	0.646	0.240 37	0.047 5	0.026 49	0.022 319	0.005 151	0.014 324	0.011 133	0.004 28	0.005 251
DCP13	.600	0.530	0.229 35	0.044 323	0.023 9	0.021 299	0.003 149	0.015 311	0.008 179	0.005 215	0.008 231
DCP14	.701	0.436	0.178 32	0.058 273	0.008 35	0.010 227	0.003 77	0.016 299	0.012 197	0.008 240	0.009 229
DCP15	.800	0.243	0.161 23	0.049 275	0.008 6	0.005 283	0.002 265	0.012 304	0.006 230	0.008 216	0.007 255
DCP16	.900	0.014	0.161 8	0.032 276	0.012 4	0.006 285	0.011 39	0.011 240	0.002 127	0.006 213	0.006 254
DCP17	.969	-0.050	0.064 7	0.011 263	0.009 349	0.004 204	0.004 11	0.008 283	0.004 131	0.004 260	0.003 243

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.05	0.060	0.594	5.03	0.0	11.94	12061.6	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
195.9	34057.	0.31E 07	-0.106	1.135	11.49	-0.00151	2.359	0.0
(642.7)	(711.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		11.941	5.031 0	0.207 9	0.047 218	0.006 192	0.015 0	0.010 358	0.010 144	0.015 156	0.006 311
CN		0.908	0.145 85	0.033 76	0.042 142	0.008 262	0.018 137	0.007 207	0.010 103	0.001 96	0.003 70
CM		-0.032	0.066 196	0.005 216	0.008 185	0.001 193	0.002 277	0.002 341	0.003 231	0.003 271	0.001 172
DCP 1	.010	3.564	0.116 141	0.188 83	0.133 149	0.038 186	0.030 138	0.014 211	0.021 141	0.006 193	0.012 166
DCP 2	.020	3.117	0.037 124	0.219 90	0.121 161	0.034 180	0.034 186	0.016 215	0.011 171	0.013 246	0.002 205
DCP 3	.030	2.942	0.131 167	0.265 91	0.103 163	0.035 160	0.029 212	0.021 188	0.002 182	0.011 295	0.004 205
DCP 4	.049	2.349	0.742 174	0.101 86	0.237 177	0.029 231	0.079 172	0.033 276	0.042 153	0.035 309	0.021 206
DCP 5	.074	2.166	0.765 169	0.008 330	0.200 174	0.038 263	0.053 158	0.028 255	0.017 160	0.019 291	0.002 126
DCP 6	.099	1.988	0.701 163	0.064 262	0.164 170	0.031 274	0.029 156	0.014 298	0.022 119	0.011 229	0.001 236
DCP 7	.149	1.695	0.524 148	0.038 242	0.112 151	0.026 278	0.025 87	0.024 188	0.012 204	0.012 299	0.007 42
DCP 8	.200	1.435	0.345 132	0.064 92	0.127 152	0.017 234	0.030 135	0.011 225	0.009 161	0.004 308	0.009 126
DCP 9	.250	1.290	0.298 110	0.049 111	0.115 150	0.031 258	0.027 165	0.006 298	0.015 149	0.016 258	0.007 61
DCP10	.300	1.109	0.231 -1	0.069 91	0.089 138	0.013 237	0.021 172	0.007 332	0.018 149	0.009 279	0.015 108
DCP11	.399	0.933	0.248 61	0.068 75	0.065 124	0.005 232	0.029 133	0.006 182	0.016 108	0.011 112	0.016 107
DCP12	.501	0.731	0.259 43	0.050 66	0.039 63	0.010 324	0.021 109	0.012 219	0.017 97	0.006 204	0.010 63
DCP13	.600	0.585	0.262 34	0.022 26	0.027 41	0.009 351	0.020 97	0.006 236	0.009 60	0.007 117	0.007 37
DCP14	.701	0.489	0.247 24	0.017 16	0.032 354	0.011 355	0.011 121	0.014 178	0.017 56	0.013 96	0.004 330
DCP15	.800	0.330	0.236 15	0.009 36	0.025 350	0.004 219	0.004 137	0.009 146	0.016 47	0.016 65	0.012 317
DCP16	.900	0.082	0.189 7	0.023 45	0.014 332	0.008 157	0.008 99	0.012 149	0.011 41	0.007 70	0.004 237
DCP17	.969	-0.020	0.077 5	0.016 64	0.002 29	0.004 317	0.003 179	0.008 174	0.003 23	0.006 116	0.002 236

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.09	0.060	0.594	5.01	0.0	14.87	12061.7	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
196.0	34076.	0.31E 07	-0.115	1.093	12.17	-0.00183	2.855	0.0
(643.0)	(711.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		14.868	5.008 0	0.197 2	0.038 267	0.017 221	0.039 42	0.023 94	0.024 227	0.006 320	0.004 36
CN		0.946	0.146 85	0.022 242	0.009 104	0.015 174	0.006 283	0.006 345	0.003 252	0.008 2	0.003 224
CM		-0.057	0.057 203	0.015 253	0.001 276	0.003 289	0.003 61	0.003 144	0.001 50	0.003 176	0.001 41
DCP 1	.010	3.609	0.333 160	0.080 275	0.050 181	0.003 245	0.011 338	0.001 155	0.010 325	0.009 219	0.008 107
DCP 2	.020	3.139	0.338 165	0.059 299	0.043 200	0.016 252	0.008 353	0.003 156	0.004 207	0.012 208	0.007 167
DCP 3	.030	2.934	0.398 170	0.059 312	0.085 198	0.010 262	0.016 171	0.008 68	0.005 207	0.014 207	0.004 90
DCP 4	.049	2.178	0.683 167	0.275 274	0.067 103	0.003 253	0.048 46	0.021 100	0.011 334	0.008 140	0.014 240
DCP 5	.074	1.947	0.552 162	0.246 267	0.041 88	0.045 220	0.028 44	0.012 184	0.009 342	0.008 118	0.012 259
DCP 6	.099	1.791	0.428 152	0.204 257	0.028 72	0.038 217	0.016 38	0.002 213	0.004 7	0.005 127	0.011 187
DCP 7	.149	1.598	0.335 139	0.174 245	0.012 26	0.038 186	0.012 45	0.017 123	0.010 199	0.015 265	0.008 297
DCP 8	.200	1.436	0.277 132	0.132 244	0.007 88	0.024 200	0.008 97	0.011 129	0.004 267	0.007 235	0.005 320
DCP 9	.250	1.331	0.235 109	0.111 229	0.015 305	0.028 179	0.018 310	0.010 47	0.005 281	0.020 25	0.005 140
DCP10	.300	1.171	0.213 90	0.068 207	0.004 315	0.030 170	0.023 277	0.018 4	0.008 56	0.013 23	0.010 91
DCP11	.399	1.000	0.214 72	0.028 159	0.019 71	0.021 152	0.021 297	0.016 17	0.010 274	0.023 37	0.002 276
DCP12	.501	0.812	0.227 55	0.033 113	0.012 112	0.017 157	0.019 261	0.011 355	0.008 209	0.012 357	0.001 94
DCP13	.600	0.667	0.237 43	0.060 80	0.017 111	0.013 144	0.010 237	0.011 321	0.006 224	0.013 10	0.010 250
DCP14	.701	0.579	0.228 28	0.063 70	0.011 130	0.016 115	0.017 319	0.008 223	0.004 292	0.013 348	0.004 282
DCP15	.800	0.431	0.215 21	0.050 57	0.004 136	0.011 113	0.006 249	0.010 307	0.004 202	0.011 321	0.004 180
DCP16	.900	0.159	0.152 17	0.039 41	0.002 296	0.006 71	0.007 205	0.012 324	0.001 121	0.006 350	0.007 199
DCP17	.969	0.007	0.063 22	0.019 35	0.003 9	0.004 124	0.004 233	0.008 290	0.003 314	0.006 350	0.005 232

FORCED PITCHING OSCILLATION　　　　AIRFOIL　　NLR 1

	TUNED HZ 0.0	DRIVE HZ 45.83	K 0.119	MACH NO 0.592	DEL.ALPHA 5.18	DEL.H 0.0	ALPHA.0 12.54	TEST POINT 12067.1	CYCLES ANALYSED 20
	V 195.5 (641.4)	Q 101037. (2110.2)	RN 0.93E 07	CN(MIN) -0.116	CN(MAX) 1.410	ALPHA.NMAX 12.66	AERO DAMP -0.00140	TDR 2.220	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		12.542	5.185	0	0.275	3	0.195	185	0.083	52	0.053	18	0.028	62	0.029	198	0.011	115	0.012	42
CN		0.997	0.284	79	0.055	97	0.048	101	0.019	126	0.006	85	0.007	123	0.003	125	0.006	56	0.005	346
CM		-0.028	0.075	209	0.005	196	0.017	181	0.008	207	0.004	184	0.004	222	0.001	199	0.003	215	0.002	157
DCP 1	.010	3.441	0.254	152	0.219	88	0.167	152	0.084	93	0.039	157	0.024	107	0.039	127	0.025	86	0.030	79
DCP 2	.020	3.220	0.220	159	0.250	102	0.180	168	0.098	121	0.042	192	0.040	157	0.038	179	0.042	166	0.033	145
DCP 3	.030	3.209	0.176	111	0.264	85	0.143	155	0.094	96	0.020	160	0.029	92	0.014	139	0.010	42	0.010	188
DCP 4	.049	2.783	0.531	154	0.176	79	0.244	162	0.035	137	0.084	170	0.018	206	0.047	181	0.017	222	0.030	176
DCP 5	.074	2.596	0.637	147	0.084	57	0.249	153	0.069	225	0.071	152	0.056	237	0.025	186	0.031	232	0.018	264
DCP 6	.099	2.370	0.897	152	0.020	179	0.245	143	0.122	215	0.033	116	0.070	226	0.016	236	0.012	197	0.021	297
DCP 7	.149	2.018	0.857	135	0.199	198	0.082	113	0.075	189	0.016	309	0.021	291	0.016	340	0.019	34	0.012	8
DCP 8	.200	1.553	0.540	105	0.191	129	0.144	149	0.067	206	0.012	270	0.009	158	0.006	85	0.002	129	0.004	269
DCP 9	.250	1.388	0.453	79	0.173	87	0.145	115	0.064	168	0.012	90	0.028	126	0.005	57	0.012	77	0.015	160
DCP10	.300	1.145	0.441	67	0.168	92	0.125	110	0.071	154	0.015	192	0.023	211	0.020	246	0.021	308	0.012	33
DCP11	.399	0.985	0.425	58	0.088	75	0.076	67	0.058	110	0.032	99	0.040	143	0.019	131	0.019	142	0.004	71
DCP12	.501	0.782	0.382	48	0.038	78	0.051	34	0.045	88	0.016	58	0.035	117	0.023	82	0.014	102	0.009	12
DCP13	.600	0.632	0.354	47	0.012	53	0.051	23	0.038	52	0.017	5	0.023	79	0.016	97	0.019	50	0.009	25
DCP14	.701	0.527	0.284	45	0.012	237	0.059	359	0.030	19	0.012	340	0.027	35	0.014	328	0.009	65	0.014	353
DCP15	.800	0.333	0.259	36	0.013	6	0.058	357	0.032	14	0.021	4	0.020	345	0.008	359	0.014	8	0.010	338
DCP16	.900	0.053	0.199	25	0.036	26	0.044	357	0.030	354	0.010	333	0.018	12	0.009	268	0.015	22	0.012	293
DCP17	.969	-0.023	0.081	27	0.023	59	0.022	28	0.021	357	0.003	52	0.010	352	0.003	223	0.012	2	0.010	281

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.88	0.121	0.587	5.15	0.0	15.09	12067.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
193.6	99778.	0.92E 07	-0.116	1.297	13.20	-0.00167	2.618	0.0
(635.3)	(2083.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		15.092	5.153 0	0.237 1	0.051 277	0.074 120	0.004 82	0.015 35	0.019 221	0.008 96	0.001 205
CN		1.041	0.256 78	0.034 166	0.013 186	0.007 217	0.005 239	0.001 352	0.003 317	0.003 256	0.002 98
CM		-0.042	0.177 213	0.012 250	0.004 341	0.003 282	0.002 335	0.000 28	0.002 90	0.002 96	0.001 304
DCP 1	.010	3.488	0.520 143	0.103 55	3.125 159	0.036 228	0.044 120	0.024 218	0.011 105	0.024 224	0.015 175
DCP 2	.020	3.373	3.468 148	2.075 76	0.130 175	0.053 248	0.048 171	0.026 266	0.007 81	0.024 266	0.005 238
DCP 3	.030	3.031	0.622 171	0.037 96	0.134 191	0.048 270	0.006 174	0.019 349	0.009 58	0.020 62	0.009 213
DCP 4	.049	2.743	0.634 155	0.244 268	0.068 155	0.121 282	0.344 336	0.010 264	0.032 42	0.010 143	0.019 68
DCP 5	.074	2.543	0.593 147	0.295 256	0.044 10	0.052 259	0.047 339	0.030 82	0.012 102	0.009 140	0.012 191
DCP 6	.399	2.346	0.581 144	0.279 238	0.079 345	0.007 176	0.011 319	0.034 34	0.024 136	0.011 223	0.007 338
DCP 7	.149	1.945	0.385 119	0.145 206	0.027 1	0.016 165	0.029 309	0.015 125	0.009 351	0.031 177	0.016 15
DCP 8	.200	1.608	0.336 113	0.110 203	0.026 291	0.020 198	0.021 278	0.009 350	0.003 77	0.012 168	0.010 295
DCP 9	.250	1.467	0.344 95	0.128 187	0.021 275	0.009 141	0.017 230	0.012 20	0.005 352	0.010 337	0.014 44
DCP10	.300	1.300	0.338 81	0.092 168	0.031 228	0.012 281	0.019 267	0.010 276	0.008 332	0.007 19	0.002 316
DCP11	.399	1.097	0.384 69	0.069 151	0.017 203	0.015 226	0.021 196	0.005 204	0.006 138	0.015 56	0.010 342
DCP12	.501	0.865	0.377 55	0.054 115	0.031 168	0.007 193	0.010 191	0.010 286	0.011 307	0.001 58	0.014 163
DCP13	.600	0.683	0.356 47	0.045 96	0.025 161	0.018 175	0.005 84	0.005 350	0.021 330	0.019 334	0.008 181
DCP14	.701	0.555	0.308 39	0.026 77	0.010 181	0.011 73	0.013 147	0.011 189	0.011 261	0.016 278	0.011 147
DCP15	.800	0.383	0.295 34	0.038 50	0.014 161	0.013 87	0.001 294	0.005 184	0.006 255	0.011 233	0.007 86
DCP16	.900	0.104	0.207 37	0.036 31	0.016 142	0.007 107	0.007 166	0.007 62	0.007 189	0.014 226	0.005 42
DCP17	.969	-0.008	0.090 50	0.022 27	0.013 141	0.004 35	0.006 48	0.004 2	0.005 159	0.003 196	0.004 86

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.87	0.122	0.583	5.18	0.0	17.53	12067.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
191.9	98427.	0.92E 07	-0.148	1.329	17.60	-0.00184	2.861	0.0
(629.5)	(2055.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		17.528	5.182 0	0.246 5	0.056 292	0.074 110	0.010 94	0.024 54	0.023 203	0.016 136	0.003 1
CN		1.043	0.288 73	0.017 186	0.001 82	0.010 160	0.002 223	0.004 66	0.003 148	0.001 317	0.006 131
CM		-0.074	0.075 218	0.009 235	0.004 327	0.002 297	0.001 264	0.002 224	0.000 248	0.001 217	0.001 310
DCP 1	.010	2.922	0.829 151	0.178 243	0.044 80	0.055 241	0.031 304	0.021 143	0.013 227	0.010 103	0.011 35
DCP 2	.020	2.837	0.721 150	0.177 247	0.043 340	0.067 242	0.023 319	0.022 176	0.021 301	0.004 286	0.010 72
DCP 3	.030	3.041	0.639 154	0.126 299	0.019 146	0.001 170	0.028 15	0.033 148	0.006 185	0.022 201	0.022 160
DCP 4	.049	2.374	0.506 129	0.162 257	0.100 17	0.024 109	0.018 285	0.004 3	0.022 195	0.013 4	0.028 86
DCP 5	.074	2.154	0.419 121	0.093 244	0.050 10	0.035 128	0.014 225	0.018 346	0.008 28	0.014 346	0.017 83
DCP 6	.099	2.008	0.397 115	0.080 233	0.031 15	0.013 150	0.029 212	0.015 298	0.012 116	0.025 267	0.017 135
DCP 7	.149	1.794	0.380 99	0.092 199	0.037 327	0.018 131	0.007 145	0.004 289	0.014 146	0.013 291	0.010 59
DCP 8	.200	1.549	0.349 96	0.085 188	0.021 306	0.014 230	0.002 353	0.020 159	0.002 46	0.023 156	0.002 314
DCP 9	.250	1.448	0.320 82	0.069 175	0.029 260	0.012 181	0.006 130	0.004 103	0.025 153	0.008 233	0.010 247
DCP10	.300	1.307	0.334 73	0.044 170	0.011 281	0.012 179	0.006 348	0.008 150	0.004 116	0.003 84	0.011 138
DCP11	.399	1.145	0.374 68	0.044 158	0.025 203	0.017 232	0.011 213	0.005 138	0.005 231	0.002 135	0.011 242
DCP12	.501	0.949	0.372 56	0.030 170	0.014 183	0.015 201	0.017 251	0.009 9	0.006 258	0.003 351	0.005 191
DCP13	.600	0.786	0.367 51	0.027 89	0.012 147	0.009 146	0.001 306	0.007 92	0.005 113	0.006 0	0.009 124
DCP14	.701	0.670	0.340 45	0.032 55	0.018 121	0.015 143	0.002 335	0.010 24	0.002 245	0.006 358	0.009 117
DCP15	.800	0.497	0.310 41	0.033 36	0.011 119	0.018 98	0.015 88	0.013 44	0.010 65	0.010 90	0.013 127
DCP16	.900	0.176	0.226 44	0.027 4	0.014 99	0.013 85	0.006 68	0.011 42	0.003 92	0.004 293	0.005 63
DCP17	.969	0.017	0.101 56	0.018 359	0.010 137	0.008 106	0.010 78	0.003 74	0.001 248	0.002 319	0.002 97

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.78	0.119	0.591	5.27	0.0	9.96	12065.1	20

V	Q	RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
195.3	100774.	0.93E 07	-5.118	1.469	12.50	-0.00133	2.750	0.0
(640.8)	(2104.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		9.960	5.272 0	0.203 23	0.195 116	0.224 269	0.030 300	0.009 359	0.024 177	0.009 224	0.014 51
CN		0.910	0.302 58	0.140 44	0.051 35	0.034 353	0.014 332	0.012 311	0.076 224	0.001 233	0.006 89
CM		-0.014	0.055 222	0.025 113	0.013 145	0.011 87	0.006 79	0.006 34	0.004 5	0.002 347	0.003 292
DCP 1	.010	3.155	0.383 357	0.525 69	0.098 61	0.017 50	0.032 2	0.031 329	0.038 292	0.014 227	0.012 257
DCP 2	.020	2.989	0.431 7	0.592 76	0.096 44	0.071 60	0.041 48	0.025 311	0.044 333	0.043 251	0.025 273
DCP 3	.330	2.967	0.561 1	0.554 78	0.127 34	0.069 63	0.047 51	0.038 292	0.018 330	0.036 253	0.031 249
DCP 4	.040	2.598	0.760 129	0.595 66	0.031 73	0.172 58	0.040 20	0.060 49	0.040 13	0.021 342	0.041 305
DCP 5	.074	2.479	0.419 135	0.536 60	0.075 128	0.171 50	0.021 79	0.088 29	0.019 9	0.032 26	0.031 332
DCP 6	.099	2.413	0.586 139	0.481 59	0.171 120	0.146 37	0.029 66	0.073 23	0.033 42	0.036 17	0.025 331
DCP 7	.149	1.854	0.574 83	0.536 70	0.292 125	0.034 153	0.018 83	0.028 335	0.011 303	0.011 85	0.011 56
DCP 8	.200	1.441	0.503 62	0.387 71	0.191 67	0.139 67	0.064 152	0.050 95	0.040 179	0.024 170	0.024 160
DCP 9	.250	1.274	0.503 48	0.261 44	0.157 21	0.125 7	0.042 8	0.054 352	0.017 94	0.009 317	0.026 87
DCP10	.300	1.110	0.480 47	0.214 34	0.154 17	0.110 351	0.062 345	0.055 335	0.021 341	0.012 300	0.028 29
DCP11	.399	0.896	0.409 51	0.128 20	0.105 7	0.068 320	0.047 317	0.046 292	0.023 283	0.032 276	0.007 136
DCP12	.501	0.686	0.361 49	0.100 352	0.055 354	0.050 311	0.036 312	0.037 274	0.028 250	0.025 240	0.012 177
DCP13	.600	0.548	0.315 56	0.080 336	0.043 340	0.036 289	0.028 332	0.023 235	0.024 236	0.020 186	0.013 127
DCP14	.701	0.463	0.248 60	0.071 308	0.029 344	0.042 262	0.023 244	0.026 191	0.023 174	0.019 130	0.012 73
DCP15	.800	0.266	0.216 46	0.068 309	0.040 329	0.046 250	0.023 273	0.023 178	0.016 148	0.007 86	0.012 111
DCP16	.900	-0.006	0.143 30	0.365 320	0.046 304	0.028 257	0.021 208	0.020 178	0.018 176	0.007 80	0.012 89
DCP17	.969	-0.054	0.070 30	0.036 333	0.027 325	0.017 292	0.016 253	0.015 233	0.013 160	0.009 121	0.007 148

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	66.97	0.176	0.603	5.95	0.0	0.02	12069.1	20

V	Q	RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
199.0	103905.	0.94E 07	-0.062	0.679	6.35	-0.00078	1.790	0.0
(652.9)	(2170.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.021	5.952 0	0.519 339	0.129 207	0.025 185	0.053 99	0.027 50	0.011 297	0.011 266	0.008 106
CN		0.121	0.515 354	0.028 349	0.039 203	0.005 196	0.006 167	0.003 125	0.001 321	0.001 134	0.001 144
CM		-0.018	0.039 298	0.007 270	0.002 97	0.001 342	0.001 46	0.001 317	0.000 234	0.000 254	0.000 316
DCP 1	.010	-0.807	3.392 336	0.223 246	0.293 258	0.179 304	0.043 319	0.091 288	0.042 316	0.019 260	0.039 264
DCP 2	.020	-0.584	2.636 342	0.131 313	0.134 269	0.113 332	0.083 61	0.035 51	0.047 357	0.054 68	0.017 156
DCP 3	.030	-0.308	2.166 341	0.117 352	0.028 151	0.030 301	0.071 65	0.051 110	0.021 185	0.016 88	0.027 145
DCP 4	.040	0.103	2.145 342	0.114 346	0.111 119	0.052 201	0.025 83	0.027 79	0.031 182	0.008 279	0.007 194
DCP 5	.074	0.320	1.830 342	0.125 306	0.123 111	0.044 158	0.035 193	0.017 347	0.008 176	0.029 190	0.009 306
DCP 6	.099	0.456	1.588 344	0.168 279	0.134 130	0.047 83	0.044 224	0.001 317	0.022 311	0.318 196	0.016 44
DCP 7	.149	0.246	0.959 346	0.084 349	0.026 292	0.090 167	0.032 126	0.009 319	0.017 354	0.001 240	0.002 203
DCP 8	.200	0.196	0.787 355	0.051 344	0.021 277	0.015 187	0.012 152	0.005 43	0.004 24	0.001 90	0.000 286
DCP 9	.250	0.189	0.665 352	0.046 340	0.021 247	0.008 193	0.009 139	0.002 113	0.001 53	0.004 51	0.002 350
DCP10	.300	0.194	0.562 354	0.041 348	0.018 244	0.006 202	0.007 147	0.001 38	0.002 24	0.002 116	0.000 67
DCP11	.399	0.168	0.447 8	0.036 14	0.019 271	0.008 229	0.006 212	0.005 159	0.001 178	0.001 192	0.002 74
DCP12	.501	0.131	0.340 14	0.033 39	0.029 268	0.005 228	0.007 199	0.009 124	0.002 38	0.003 185	0.002 165
DCP13	.600	0.144	0.254 22	0.030 49	0.009 258	0.003 233	0.007 228	0.005 146	0.001 140	0.001 95	0.003 187
DCP14	.701	0.227	0.171 39	0.078 56	0.005 243	0.004 109	0.001 216	0.006 143	0.002 349	0.001 59	0.001 182
DCP15	.800	0.097	0.103 49	0.020 82	0.004 274	0.003 211	0.003 294	0.007 174	0.003 20	0.001 111	0.033 79
DCP16	.900	-0.094	0.055 105	0.022 134	0.007 197	0.004 156	0.006 172	0.004 137	0.001 198	0.001 71	0.002 104
DCP17	.965	-0.050	0.046 163	0.010 139	0.006 147	0.001 161	0.002 187	0.003 178	0.004 17	0.002 65	0.004 231

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TIMED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	0.0	68.87	0.177	0.600	5.99	0.0	2.47	12069.2	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	197.7	102990.	0.93E 07	-0.043	0.942	8.75	-0.00078	1.263	0.0
	(648.5)	(2151.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.468	5.985 0	0.499 347	0.190 140	0.031 163	0.021 96	0.011 64	0.013 228	0.013 131	0.003 252
CN		0.367	0.517 353	0.038 332	0.013 290	0.003 358	0.004 236	0.001 197	0.002 234	0.002 111	0.002 77
CM		-0.006	0.239 299	0.008 224	0.003 110	0.001 109	0.001 71	0.003 243	0.000 120	0.000 149	0.000 353
DCP 1	.010	0.574	3.122 333	0.284 7	0.060 90	0.041 158	0.032 94	0.007 208	0.012 118	0.011 310	0.010 274
DCP 2	.020	0.791	2.448 341	0.098 304	0.019 237	0.035 355	0.027 91	0.008 94	0.023 219	0.014 146	0.004 344
DCP 3	.030	0.900	2.174 340	0.386 311	0.027 159	0.023 2	0.006 174	0.008 344	0.021 237	0.015 137	0.006 6
DCP 4	.040	1.164	1.935 340	0.051 329	0.027 270	0.005 27	0.024 254	0.015 152	0.007 222	0.016 110	0.012 349
DCP 5	.074	1.252	1.750 341	0.364 291	0.333 278	0.026 197	0.009 265	0.027 159	0.016 24	0.004 131	0.014 350
DCP 6	.099	1.311	1.498 342	0.146 251	0.319 310	0.077 208	0.033 94	0.031 191	0.033 61	0.014 284	0.015 53
DCP 7	.149	0.985	1.320 346	0.299 257	0.203 145	0.067 39	0.070 11	0.052 310	0.044 212	0.019 104	0.016 149
DCP 8	.200	0.616	1.411 355	0.087 315	0.052 172	0.048 32	0.003 274	0.013 183	0.009 249	0.013 125	0.009 357
DCP 9	.253	0.419	1.443 352	0.358 352	0.013 160	0.029 326	0.034 210	0.022 111	0.015 351	0.003 245	0.004 142
DCP10	.300	0.448	0.507 356	0.081 9	0.028 264	0.012 235	0.015 154	0.006 52	0.037 272	0.005 127	0.003 46
DCP11	.399	0.345	0.421 4	0.017 20	0.023 275	0.005 255	0.005 221	0.002 226	0.003 336	0.001 98	0.003 97
DCP12	.501	0.293	0.323 15	0.049 18	0.017 271	0.004 258	0.005 237	0.003 278	0.001 220	0.003 141	0.002 178
DCP13	.600	0.262	0.246 23	0.041 21	0.012 264	0.001 264	0.007 257	0.001 69	0.001 150	0.001 315	0.004 112
DCP14	.701	0.200	0.162 34	0.043 23	0.013 266	0.001 210	0.004 267	0.004 99	0.002 146	0.003 24	0.003 120
DCP15	.800	0.132	0.100 49	0.023 36	0.004 256	0.003 34	0.002 204	0.002 77	0.001 442	0.003 1	0.003 243
DCP16	.902	-0.101	0.034 39	0.036 39	0.006 322	0.004 306	0.003 247	0.001 340	0.001 218	0.003 98	0.001 34
DCP17	.960	-0.067	0.031 170	0.004 221	0.034 127	0.005 288	0.004 1	0.003 203	0.001 64	0.003 325	0.002 320

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TIMED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	0.0	68.88	0.178	0.597	5.99	0.0	4.99	12069.3	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	196.7	102315.	0.93E 07	-0.039	1.229	11.71	-0.00080	1.286	0.0
	(645.2)	(2136.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.987	5.002 0	0.654 3	0.263 148	0.047 166	0.073 91	0.026 344	0.023 204	0.024 202	0.008 358
CN		0.635	0.509 7	0.095 313	0.054 172	0.015 18	0.003 232	0.003 191	0.005 59	0.002 317	0.002 199
CM		-0.000	0.241 294	0.013 68	0.014 254	0.011 156	0.005 35	0.001 344	0.001 236	0.001 80	0.001 350
DCP 1	.010	1.840	2.410 339	0.268 34	0.023 313	0.050 200	0.011 274	0.029 126	0.006 303	0.008 67	0.013 330
DCP 2	.020	1.764	2.203 346	0.179 27	0.013 224	0.062 211	0.036 69	0.023 98	0.011 79	0.010 16
DCP 3	.030	1.414	2.009 345	0.179 2	0.025 148	0.051 219	0.018 92	0.011 164	0.024 67	0.010 357	0.014 45
DCP 4	.040	1.571	1.610 347	0.255 25	0.128 252	0.099 154	0.007 45	0.048 285	0.024 132	0.024 336	0.007 222
DCP 5	.074	1.474	1.429 350	0.209 10	0.198 257	0.137 141	0.001 17	0.038 268	0.006 281	0.015 257	0.026 142
DCP 6	.099	1.747	1.314 356	0.333 10	0.277 266	0.166 140	0.115 346	0.031 171	0.044 311	0.045 180	0.001 86
DCP 7	.149	1.735	1.187 1	0.395 316	0.207 224	0.091 203	0.089 151	0.060 137	0.056 49	0.021 334	0.013 35
DCP 8	.200	1.333	0.967 3	0.285 304	0.144 195	0.046 124	0.040 126	0.033 60	0.033 7	0.014 1	0.013 287
DCP 9	.250	0.866	0.771 3	0.189 291	0.155 155	0.058 45	0.017 40	0.035 342	0.033 293	0.017 166	0.006 91
DCP10	.300	0.746	0.633 4	0.151 276	0.130 145	0.069 29	0.029 335	0.035 275	0.028 183	0.016 71	0.005 139
DCP11	.399	0.587	0.479 23	0.091 292	0.097 148	0.070 17	0.030 280	0.017 235	0.025 157	0.022 60	0.014 289
DCP12	.501	0.411	0.369 27	0.065 249	0.080 133	0.058 355	0.029 246	0.015 193	0.019 97	0.012 340	0.011 222
DCP13	.600	0.344	0.288 41	0.061 301	0.054 131	0.055 343	0.031 274	0.014 147	0.016 60	0.015 307	0.014 206
DCP14	.701	0.156	0.214 59	0.054 309	0.064 132	0.042 326	0.025 182	0.005 45	0.007 13	0.011 261	0.015 157
DCP15	.800	0.154	0.144 60	0.039 273	0.035 123	0.028 313	0.013 143	0.002 157	0.008 22	0.012 235	0.007 123
DCP16	.900	-0.091	0.066 53	0.030 236	0.032 70	0.018 301	0.009 195	0.002 124	0.006 326	0.010 196	0.004 71
DCP17	.960	-0.080	0.018 143	0.027 248	0.017 88	0.008 305	0.004 265	0.006 141	0.013 338	0.006 260	0.002 121

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.91	0.181	0.593	5.80	0.0	7.48	12069.4	20

	G	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
293.9	99806.	0.925 37	-0.137	1.491	13.41	-0.00062	0.988	0.0
(636.1)	(2084.5)			HARMONIC ANALYSIS				

DATA TYPE	X/P	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.477	5.400 2	0.784 17	0.958 164	0.059 161	0.022 96	0.052 331	0.016 215	0.016 189	0.019 317
CN		7.778	0.469 28	0.167 332	0.066 221	0.015 165	0.013 51	0.012 290	0.009 189	0.005 136	0.006 345
CM		-0.010	0.067 237	0.047 75	0.025 324	0.011 248	0.010 196	0.008 48	0.005 10	0.033 278	0.003 189
DCP 1	.010	7.551	1.526 340	.545 43	0.192 431	0.105 196	0.052 76	0.039 350	0.027 301	0.036 365	0.036 176
DCP 2	.020	0.384	1.436 4	0.434 48	0.231 311	0.160 218	0.031 80	0.006 164	0.025 8	0.025 314	0.034 244
DCP 3	.030	0.376	1.345 356	0.343 43	0.257 315	0.154 222	0.014 69	0.075 191	0.016 35	0.023 327	0.042 254
DCP 4	.040	0.288	0.978 4	0.541 39	0.251 291	0.157 207	0.015 295	0.091 173	0.067 61	0.091 306	0.015 270
DCP 5	.074	0.044	0.778 12	0.627 34	0.247 274	0.060 184	0.051 253	0.199 155	0.074 44	0.014 248	0.014 18
DCP 6	.099	0.087	0.784 23	0.694 33	0.257 240	0.042 43	0.114 215	0.057 115	0.045 84	0.011 116	0.042 358
DCP 7	.149	0.541	0.710 33	0.514 359	0.229 338	0.128 265	0.073 269	0.053 290	0.064 273	0.019 189	0.026 344
DCP 8	.200	0.261	0.485 34	0.425 355	0.199 289	0.132 266	0.084 233	0.055 239	0.049 206	0.041 158	0.018 138
DCP 9	.250	0.007	0.778 34	0.434 3	0.154 339	0.042 205	0.075 142	0.237 76	0.022 117	0.029 47	0.006 300
DCP10	.300	0.357	0.676 43	0.225 404	0.147 309	0.071 175	0.075 112	0.039 45	0.017 56	0.025 351	0.215 264
DCP11	.400	0.705	0.581 43	0.232 397	0.143 337	0.057 160	0.073 102	0.049 33	0.017 327	0.019 314	0.017 153
DCP12	.501	0.546	0.478 36	0.184 268	0.141 187	0.056 118	0.072 60	0.052 331	0.026 261	0.019 126	0.017 173
DCP13	.600	0.460	0.391 43	0.164 297	0.136 166	0.051 87	0.062 24	0.054 292	0.031 227	0.026 167	0.325 75
DCP14	.701	0.35	0.297 47	0.118 274	0.104 143	0.046 55	0.051 1	0.053 264	0.032 187	0.027 119	0.027 30
DCP15	.800	0.221	0.721 44	0.175 260	0.064 133	0.035 30	0.037 342	0.036 244	0.022 193	0.021 8	0.015 352
DCP16	.900	0.143	0.130 24	0.106 244	0.060 126	0.037 47	0.036 316	0.079 215	0.017 135	0.021 52	0.018 374
DCP17	.969	0.063	0.061 26	0.056 260	0.037 160	0.022 69	0.022 345	0.015 256	0.016 168	0.014 66	0.016 348

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.75	0.182	0.582	5.71	0.0	10.94	12071.1	20

	G	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
192.5	98581.	0.924 37	-0.193	1.632	15.44	-0.00098	1.545	0.0
(63.7)	(2058.9)			HARMONIC ANALYSIS				

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		10.939	5.711 3	0.632 34	0.255 210	0.079 204	0.020 108	0.059 93	0.020 211	0.018 299	0.021 118
CN		0.946	1.951 48	0.164 353	0.041 313	0.031 251	0.013 160	0.012 87	0.003 8	0.005 4	0.003 312
CM		-0.027	0.080 219	0.049 99	0.015 57	0.021 13	0.010 285	0.006 260	0.004 208	0.002 144	0.001 129
DCP 1	.010	5.002	0.627 9	0.659 57	0.157 315	0.026 341	0.044 274	0.041 189	0.019 135	0.038 165	0.025 75
DCP 2	.020	2.809	0.527 18	0.597 66	0.175 338	0.056 52	0.052 312	0.028 237	0.012 144	0.031 234	0.040 134
DCP 3	.033	2.648	0.358 24	0.552 69	0.073 16	0.057 299	0.021 203	0.007 147	0.037 218	0.027 127
DCP 4	.049	2.836	0.316 69	0.326 49	0.089 310	0.159 43	0.117 308	0.021 17	0.058 284	0.049 184	0.028 63
DCP 5	.074	2.521	0.360 49	0.514 42	0.024 295	0.182 21	0.100 272	0.042 45	0.048 284	0.020 48	0.034 273
DCP 6	.099	2.453	0.403 102	0.525 39	0.034 137	0.172 2	0.071 244	0.059 9	0.047 252	0.025 28	0.035 247
DCP 7	.149	2.778	0.775 61	0.441 49	0.156 65	0.105 25	0.051 163	0.013 107	0.028 249	0.026 265	0.021 292
DCP 8	.200	1.468	0.701 57	0.356 15	0.169 35	0.132 9	0.046 38	0.052 29	0.014 81	0.028 34	0.019 30
DCP 9	.250	1.295	0.761 44	0.293 354	0.168 346	0.133 291	0.036 285	0.099 276	0.004 298	0.024 322	0.005 222
DCP10	.300	1.113	0.672 42	0.256 342	0.140 327	0.128 268	0.045 240	0.036 239	0.024 206	0.012 86	0.014 305
DCP11	.399	0.429	0.629 49	0.230 336	0.093 322	0.122 265	0.045 219	0.033 211	0.019 175	0.022 161	0.016 140
DCP12	.501	0.728	0.504 46	0.213 316	0.064 288	0.117 238	0.054 171	0.050 149	0.040 99	0.030 66	0.010 43
DCP13	.600	0.593	0.490 47	0.203 302	0.084 249	0.100 207	0.050 129	0.051 115	0.039 57	0.026 25	0.017 346
DCP14	.701	0.504	0.382 50	0.179 290	0.050 226	0.082 188	0.052 108	0.046 75	0.028 10	0.022 328	0.008 241
DCP15	.800	0.298	0.322 39	0.169 281	0.065 219	0.081 159	0.043 73	0.031 39	0.015 333	0.011 287	0.003 75
DCP16	.900	0.006	0.218 23	0.119 276	0.063 226	0.063 149	0.041 69	0.032 26	0.025 317	0.018 254	0.010 232
DCP17	.969	-0.053	0.085 27	0.063 295	0.029 250	0.032 175	0.022 106	0.016 46	0.008 17	0.015 279	0.005 278

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.70	0.185	0.572	5.61	0.0	12.54	12073.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
189.2 (620.9)	95871. (2002.3)	0.91E 07	-0.201	1.721	15.30	-0.00147	2.292	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.537	5.615 0	0.407 22	0.051 268	0.038 268	0.028 38	0.024 234	0.003 244	0.013 149	0.013 318
CN		1.033	0.476 70	0.114 33	0.057 41	0.020 8	0.012 301	0.004 243	0.006 221	0.003 227	0.007 207
CM		-0.029	0.103 219	0.029 139	0.026 131	0.011 110	0.011 81	0.004 74	0.005 54	0.001 355	0.003 17
PCP 1	.010	3.503	0.338 136	0.417 63	0.068 153	0.124 67	0.025 78	0.059 60	0.027 17	0.045 1	0.042 324
PCP 2	.020	3.282	0.284 119	0.428 76	0.099 149	0.130 84	0.018 99	0.053 98	0.027 69	0.035 58	0.034 51
PCP 3	.030	3.090	0.359 129	0.525 75	0.077 105	0.121 68	0.030 31	0.028 45	0.004 237	0.016 40	0.006 9
PCP 4	.040	2.884	0.527 130	0.370 59	0.243 144	0.140 56	0.075 141	0.057 42	0.052 105	0.050 15	0.015 115
PCP 5	.074	2.690	0.685 131	0.297 51	0.286 130	0.091 29	0.106 122	0.017 282	0.075 106	0.017 321	0.034 84
PCP 6	.099	2.561	0.920 136	0.212 48	0.313 113	0.020 341	0.120 102	0.042 201	0.070 82	0.021 194	0.026 50
PCP 7	.149	2.150	0.990 113	0.121 126	0.226 83	0.187 168	0.012 10	0.024 113	0.029 131	0.035 175	0.023 223
PCP 8	.200	1.597	0.812 77	0.335 86	0.247 101	0.103 129	0.030 150	0.058 193	0.013 216	0.020 246	0.015 267
PCP 9	.250	1.411	0.768 61	0.268 55	0.195 61	0.063 58	0.051 69	0.022 128	0.008 120	0.018 301	0.012 182
PCP10	.300	1.236	0.692 56	0.237 47	0.182 37	0.081 48	0.064 16	0.034 66	0.014 327	0.007 131	0.013 155
PCP11	.399	1.020	0.630 61	0.154 33	0.137 22	0.058 17	0.071 350	0.029 5	0.023 320	0.014 2	0.009 295
PCP12	.501	0.804	0.574 55	0.108 10	0.107 0	0.055 353	0.071 316	0.029 319	0.040 287	0.008 264	0.012 273
PCP13	.600	0.653	0.541 55	0.113 341	0.096 337	0.055 315	0.060 292	0.034 289	0.034 272	0.018 285	0.028 239
PCP14	.701	0.551	0.452 54	0.107 321	0.089 307	0.046 284	0.054 248	0.025 245	0.033 219	0.015 189	0.022 201
PCP15	.800	0.357	0.408 43	0.124 320	0.104 290	0.046 265	0.056 221	0.020 194	0.017 180	0.009 153	0.016 185
PCP16	.900	0.056	0.294 33	0.113 324	0.081 284	0.042 270	0.044 201	0.022 223	0.025 150	0.013 115	0.012 99
PCP17	.969	-0.039	0.120 40	0.062 341	0.039 297	0.025 289	0.018 262	0.010 183	0.018 214	0.010 140	0.012 126

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.61	0.198	0.562	5.62	0.0	15.09	12073.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
185.9 (610.0)	93218. (1946.9)	0.90E 07	-0.175	1.681	15.68	-0.00165	2.516	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		15.090	5.618 0	0.261 349	0.023 150	0.031 81	0.037 47	0.025 4	0.016 178	0.005 153	0.009 72
CN		1.083	0.474 75	0.078 84	0.030 122	0.024 126	0.011 88	0.036 26	0.002 290	0.003 50	0.003 352
CM		-0.043	0.115 216	0.023 206	0.005 177	0.009 234	0.007 226	0.004 211	0.003 213	0.001 209	0.000 213
PCP 1	.010	3.480	0.829 140	0.330 46	0.160 115	0.041 336	0.030 192	0.022 229	0.031 136	0.010 122	0.018 71
PCP 2	.020	3.304	0.840 145	0.270 69	0.218 117	0.022 318	0.066 131	0.022 268	0.021 187	0.026 205	0.016 184
PCP 3	.030	3.221	0.716 140	0.292 73	0.155 155	0.009 202	0.047 128	0.047 294	0.029 191	0.019 273	0.006 310
PCP 4	.040	2.873	0.823 146	0.029 287	0.164 148	0.124 238	0.018 234	0.034 281	0.051 287	0.020 247	0.032 90
PCP 5	.074	2.684	0.872 139	0.128 230	0.105 114	0.134 216	0.054 306	0.015 345	0.042 289	0.027 17	0.026 0
PCP 6	.099	2.424	0.953 132	0.236 211	0.041 69	0.090 191	0.054 265	0.027 327	0.025 210	0.010 212	0.013 331
PCP 7	.149	2.063	0.777 105	0.201 165	0.011 109	0.025 197	0.018 114	0.007 67	0.077 262	0.010 311	0.019 278
PCP 8	.200	1.607	0.647 92	0.159 110	0.043 152	0.051 168	0.015 220	0.012 129	0.009 233	0.006 220	0.010 292
PCP 9	.250	1.568	0.719 83	0.222 117	0.052 153	0.051 160	0.010 194	0.007 344	0.007 257	0.010 43	0.007 341
PCP10	.300	1.377	0.678 72	0.238 100	0.088 126	0.078 135	0.020 181	0.014 147	0.007 147	0.014 67	0.015 82
PCP11	.399	1.124	0.654 67	0.190 91	0.072 134	0.077 135	0.050 161	0.032 192	0.027 215	0.008 179	0.003 216
PCP12	.501	0.868	0.569 56	0.105 70	0.030 125	0.054 95	0.037 110	0.009 79	0.007 99	0.008 134	0.004 239
PCP13	.600	0.697	0.552 52	0.080 50	0.007 82	0.038 71	0.037 49	0.013 78	0.024 43	0.009 147	0.010 23
PCP14	.731	0.592	0.495 45	0.073 22	0.012 343	0.043 48	0.064 36	0.020 35	0.010 31	0.016 56	0.006 202
PCP15	.800	0.414	0.457 40	0.101 14	0.027 374	0.012 17	0.032 22	0.027 11	0.014 11	0.017 125	0.006 341
PCP16	.900	0.107	0.316 38	0.098 8	0.032 15	0.010 8	0.032 1	0.014 352	0.016 314	0.008 328	0.006 18
PCP17	.969	-0.016	0.152 49	0.056 10	0.022 36	0.013 42	0.016 17	0.020 19	0.007 25	0.008 13	0.006 80

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

| | TUNED HZ 0.0 | DRIVE HZ 23.08 | K 0.052 | MACH NO 0.694 | DEL.ALPHA 4.88 | DEL.H 0.0 | ALPHA.0 0.02 | TEST POINT 12075.1 | CYCLES ANALYSED 20 |

| | V 226.0 (741.5) | Q 127390. (2660.6) | RN 0.10E 08 | CN(MIN) -0.058 | CN(MAX) 0.807 | ALPHA.NMAX 4.66 | AERO DAMP -0.00117 | TDR 2.098 | EXT DAMP 0.0 |

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.016	4.884 0	0.082 349	0.153 344	0.118 153	0.034 326	0.064 96	0.071 317	0.024 132	0.021 229
CN		0.130	0.667 350	0.024 332	0.008 103	0.009 139	0.005 339	0.001 123	0.002 37	0.003 189	0.002 103
CM		-0.022	0.032 332	0.005 60	0.001 54	0.001 324	0.002 113	0.001 142	0.001 240	0.001 357	0.000 67
DCP 1	.010	-0.928	2.696 345	0.180 264	0.308 312	0.029 7	0.108 292	0.031 1	0.035 280	0.036 316	0.008 244
DCP 2	.020	-0.778	2.513 348	0.071 339	0.259 319	0.076 27	0.057 309	0.055 7	0.018 5	0.033 329	0.022 43
DCP 3	.030	-0.606	2.390 347	0.152 37	0.223 321	0.112 31	0.325 341	0.063 11	0.040 59	0.022 347	0.042 56
DCP 4	.049	-0.217	2.282 347	0.245 48	0.156 322	0.120 31	0.049 85	0.028 18	0.067 66	0.029 144	0.034 55
DCP 5	.074	0.025	2.143 346	0.309 49	0.086 330	0.104 24	0.100 86	0.035 156	0.050 48	0.074 133	0.032 208
DCP 6	.099	0.233	2.046 346	0.321 48	0.036 58	0.023 22	0.093 78	0.110 163	0.025 259	0.060 134	0.075 198
DCP 7	.149	0.315	1.836 346	0.204 42	0.132 111	0.171 200	0.028 93	0.128 169	0.073 219	0.067 284	0.034 42
DCP 8	.200	0.406	1.441 350	0.094 265	0.112 124	0.192 207	0.032 200	0.047 334	0.049 80	0.064 333	0.013 17
DCP 9	.250	0.432	1.125 348	0.239 267	0.121 127	0.077 197	0.043 152	0.112 356	0.016 297	0.036 352	0.055 245
DCP10	.300	0.373	0.843 350	0.288 250	0.153 146	0.105 47	0.057 288	0.040 347	0.040 280	0.045 153	0.019 92
DCP11	.399	0.208	0.461 357	0.059 267	0.016 199	0.060 44	0.051 302	0.022 185	0.009 61	0.016 175	0.012 71
DCP12	.501	0.124	0.293 0	0.027 32	0.042 315	0.004 68	0.014 307	0.011 169	0.013 73	0.002 307	0.007 252
DCP13	.600	0.131	0.218 1	0.031 42	0.034 318	0.014 190	0.003 21	0.003 19	0.004 65	0.006 176	0.004 256
DCP14	.701	0.229	0.144 2	0.022 50	0.020 314	0.011 180	0.003 3	0.002 332	0.003 75	0.004 176	0.003 246
DCP15	.800	0.088	0.070 8	0.005 356	0.005 344	0.008 165	0.002 76	0.003 316	0.004 71	0.004 182	0.003 211
DCP16	.900	-0.121	0.006 96	0.009 260	0.005 125	0.005 168	0.003 45	0.003 353	0.003 50	0.005 168	0.003 186
DCP17	.969	-0.058	0.030 184	0.002 245	0.007 122	0.005 172	0.003 91	0.001 314	0.001 279	0.003 194	0.001 14

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

| | TUNED HZ 0.0 | DRIVE HZ 22.37 | K 0.050 | MACH NO 0.696 | DEL.ALPHA 5.16 | DEL.H 0.0 | ALPHA.0 2.33 | TEST POINT 12075.2 | CYCLES ANALYSED 20 |

| | V 226.5 (743.1) | Q 128110. (2675.8) | RN 0.10E 08 | CN(MIN) -0.038 | CN(MAX) 1.031 | ALPHA.NMAX 7.14 | AERO DAMP -0.00133 | TDR 2.387 | EXT DAMP 0.0 |

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.327	5.161 0	0.211 23	0.050 326	0.015 266	0.036 278	0.042 119	0.030 356	0.029 190	0.006 208
CN		0.398	0.581 355	0.088 14	0.045 281	0.019 187	0.005 148	0.009 114	0.006 353	0.002 223	0.001 139
CM		-0.013	0.021 303	0.010 121	0.008 39	0.005 309	0.003 244	0.002 171	0.002 100	0.002 3	0.002 274
DCP 1	.010	0.102	2.610 346	0.395 32	0.054 271	0.094 32	0.055 88	0.050 150	0.003 1	0.012 157	0.022 200
DCP 2	.020	0.172	2.292 349	0.410 40	0.048 160	0.049 78	0.028 77	0.040 165	0.025 255	0.022 300	0.002 240
DCP 3	.030	0.314	2.045 349	0.421 42	0.112 145	0.069 138	0.015 314	0.020 173	0.032 259	0.042 312	0.023 38
DCP 4	.049	0.674	1.756 348	0.396 46	0.101 141	0.071 182	0.084 280	0.061 348	0.037 59	0.006 116	0.019 43
DCP 5	.074	0.944	1.408 349	0.206 39	0.058 296	0.054 38	0.016 91	0.007 231	0.018 53	0.021 132	0.011 185
DCP 6	.099	1.082	1.374 349	0.206 42	0.068 297	0.067 33	0.022 90	0.008 132	0.006 108	0.003 248	0.006 20
DCP 7	.149	1.034	1.374 349	0.152 38	0.123 308	0.037 44	0.045 286	0.018 33	0.031 251	0.030 335	0.012 213
DCP 8	.200	0.937	1.303 351	0.077 23	0.164 319	0.044 211	0.067 296	0.021 136	0.055 280	0.016 166	0.040 248
DCP 9	.250	0.800	1.027 351	0.144 44	0.297 319	0.189 216	0.011 250	0.090 171	0.032 29	0.026 171	0.028 246
DCP10	.300	0.615	0.792 359	0.152 349	0.138 307	0.138 238	0.074 185	0.094 158	0.075 81	0.026 65	0.042 19
DCP11	.399	0.445	0.563 2	0.093 326	0.027 218	0.039 243	0.060 147	0.027 73	0.026 61	0.024 339	0.004 220
DCP12	.501	0.316	0.396 7	0.095 331	0.064 209	0.023 137	0.036 126	0.041 49	0.029 338	0.018 284	0.012 239
DCP13	.600	0.269	0.246 11	0.069 354	0.053 215	0.037 112	0.021 60	0.024 18	0.025 311	0.024 236	0.017 165
DCP14	.701	0.272	0.104 28	0.069 28	0.032 242	0.029 111	0.023 22	0.018 312	0.017 245	0.016 176	0.015 99
DCP15	.800	0.112	0.069 31	0.034 2	0.028 236	0.021 114	0.015 14	0.011 297	0.009 230	0.011 153	0.010 80
DCP16	.900	0.023	0.029 29	0.030 280	0.024 210	0.020 94	0.014 350	0.011 281	0.009 211	0.012 128	0.010 52
DCP17	.969	0.049	0.026 173	0.017 272	0.014 225	0.009 97	0.006 329	0.001 250	0.003 233	0.004 139	0.005 63

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.39	0.050	0.698	5.08	0.0	4.95	12075.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
226.3	128075.	0.10E 08	-0.056	1.121	8.37	-0.00177	3.193	0.0
(742.6)	(2674.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		4.947	5.075	0	0.199	31	0.028	235	0.039	77	0.049	359	0.013	86	0.032	217	0.034	192	0.000	125
CN		0.637	0.431	4	0.127	34	0.035	359	0.031	307	0.010	216	0.003	292	0.003	296	0.006	227	0.004	148
CM		-0.010	0.024	258	0.015	131	0.005	97	0.007	78	0.004	355	0.001	269	0.000	299	0.001	18	0.001	291
DCP 1	.010	1.283	1.780	350	0.354	36	0.059	49	0.062	238	0.005	355	0.009	243	0.018	257	0.009	251	0.005	65
DCP 2	.020	1.250	1.568	354	0.270	31	0.034	84	0.043	246	0.014	151	0.006	217	0.010	217	0.004	130	0.004	93
DCP 3	.030	1.296	1.374	354	0.219	24	0.029	105	0.044	243	0.021	152	0.007	217	0.011	197	0.006	102	0.003	104
DCP 4	.049	1.501	1.149	354	0.221	31	0.042	123	0.028	230	0.015	130	0.005	156	0.006	244	0.004	95	0.003	38
DCP 5	.074	1.594	1.013	354	0.203	33	0.031	118	0.020	221	0.004	156	0.007	32	0.002	5	0.003	107	0.007	27
DCP 6	.099	1.700	0.967	353	0.220	39	0.049	114	0.028	229	0.005	239	0.007	157	0.005	244	0.006	344	0.010	10
DCP 7	.149	1.577	0.972	351	0.328	52	0.055	77	0.067	309	0.047	124	0.057	160	0.015	314	0.004	115	0.028	205
DCP 8	.200	1.320	0.805	353	0.459	63	0.123	351	0.089	0	0.045	135	0.023	199	0.047	72	0.048	164	0.004	152
DCP 9	.250	1.068	0.610	358	0.439	59	0.117	345	0.215	22	0.061	273	0.091	352	0.015	144	0.014	294	0.027	69
DCP10	.330	0.867	0.580	9	0.228	56	0.186	9	0.107	2	0.096	319	0.067	340	0.054	308	0.056	297	0.023	271
DCP11	.399	0.661	0.470	11	0.073	26	0.100	4	0.058	271	0.041	310	0.028	233	0.024	289	0.020	226	0.007	244
DCP12	.501	0.484	0.363	19	0.094	352	0.051	352	0.073	272	0.025	228	0.028	230	0.015	213	0.022	206	0.017	165
DCP13	.600	0.377	0.258	25	0.093	343	0.018	303	0.055	269	0.036	194	0.016	196	0.020	168	0.012	158	0.018	145
DCP14	.701	0.344	0.132	47	0.074	343	0.030	209	0.022	245	0.032	160	0.016	88	0.008	91	0.007	89	0.010	71
DCP15	.800	0.160	0.111	39	0.066	328	0.030	226	0.019	227	0.026	145	0.014	62	0.005	38	0.002	32	0.004	62
DCP16	.900	-0.089	0.083	25	0.057	310	0.026	245	0.021	229	0.023	140	0.011	65	0.007	51	0.003	8	0.005	30
DCP17	.969	-0.075	0.012	69	0.026	310	0.011	255	0.010	258	0.010	163	0.005	98	0.005	43	0.003	224	0.004	108

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.94	0.051	0.703	4.97	0.0	7.47	12077.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
229.0	129741.	0.10E 08	-0.071	1.147	8.83	-0.00199	3.634	0.0
(751.3)	(2709.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.467	4.970	0	0.160	33	0.056	276	0.059	167	0.022	49	0.007	103	0.007	208	0.039	80	0.017	279
CN		0.823	0.265	22	0.097	59	0.042	79	0.023	66	0.012	343	0.002	49	0.001	70	0.008	66	0.003	327
CM		-0.020	0.037	224	0.008	120	0.007	219	0.005	193	0.004	150	0.001	162	0.001	167	0.002	186	0.001	95
DCP 1	.010	2.088	1.158	356	0.251	58	0.062	34	0.028	65	0.005	295	0.012	62	0.006	313	0.004	29	0.004	168
DCP 2	.020	1.921	1.066	359	0.181	58	0.077	35	0.018	48	0.027	349	0.013	334	0.017	287	0.005	135	0.003	259
DCP 3	.030	1.894	0.977	359	0.144	49	0.079	14	0.009	296	0.017	327	0.006	47	0.013	324	0.005	34	0.007	332
DCP 4	.049	2.009	0.788	0	0.117	42	0.046	20	0.011	277	0.013	297	0.006	214	0.002	333	0.005	3	0.006	297
DCP 5	.074	2.007	0.628	1	0.146	56	0.057	22	0.016	284	0.013	298	0.016	258	0.010	190	0.007	67	0.005	272
DCP 6	.099	2.041	0.460	1	0.207	69	0.084	18	0.017	308	0.021	328	0.027	269	0.019	194	0.006	86	0.009	214
DCP 7	.149	1.893	0.246	14	0.270	63	0.045	18	0.053	49	0.053	316	0.025	241	0.014	212	0.008	143	0.001	229
DCP 8	.200	1.633	0.110	95	0.292	68	0.062	119	0.094	62	0.028	349	0.021	25	0.018	300	0.008	151	0.004	11
DCP 9	.250	1.390	0.143	93	0.245	60	0.245	131	0.081	186	0.004	357	0.020	6	0.065	67	0.046	121	0.021	78
DCP10	.300	1.071	0.310	37	0.291	69	0.204	133	0.111	147	0.047	153	0.051	155	0.031	218	0.013	79	0.015	27
DCP11	.399	0.812	0.365	23	0.139	70	0.028	100	0.079	72	0.030	108	0.018	114	0.006	115	0.011	130	0.010	284
DCP12	.501	0.628	0.334	27	0.069	57	0.052	38	0.086	55	0.020	40	0.026	56	0.015	111	0.024	90	0.010	53
DCP13	.600	0.499	0.278	33	0.031	0	0.060	36	0.039	33	0.033	3	0.022	34	0.017	48	0.028	28	0.006	16
DCP14	.701	0.427	0.186	43	0.049	294	0.041	37	0.023	322	0.029	333	0.014	298	0.010	330	0.016	352	0.013	301
DCP15	.800	0.247	0.185	31	0.052	302	0.036	30	0.028	316	0.026	309	0.012	268	0.009	298	0.009	290	0.007	222
DCP16	.900	-0.024	0.143	17	0.053	311	0.032	7	0.020	331	0.026	295	0.011	273	0.008	267	0.010	322	0.010	235
DCP17	.969	-0.060	0.032	22	0.011	314	0.006	18	0.010	31	0.015	312	0.003	268	0.003	302	0.006	7	0.005	253

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.03	0.051	0.704	4.90	0.0	9.84	12077.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
228.7	129703.	0.10E 08	-0.076	1.104	10.36	-0.00167	3.032	0.0
(750.4)	(2708.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		9.841	4.901	0	0.219	13	0.044	274	0.012	134	0.024	347	0.022	42	0.014	137	0.014	59	0.022	312
CN		0.935	0.187	35	0.061	103	0.019	150	0.004	149	0.007	172	0.001	39	0.002	208	0.003	0	0.005	29
CM		-0.031	0.045	207	0.007	14	0.003	281	0.002	335	0.003	309	0.001	14	0.001	59	0.002	73	0.001	102
DCP 1	.010	2.498	0.814	1	0.199	66	0.036	130	0.007	150	0.014	129	0.004	211	0.007	164	0.008	315	0.006	236
DCP 2	.020	2.331	0.824	2	0.184	72	0.024	48	0.019	84	0.011	157	0.007	233	0.012	165	0.002	354	0.001	347
DCP 3	.030	2.153	0.609	2	0.262	80	0.054	18	0.041	86	0.016	32	0.015	249	0.013	137	0.003	310	0.004	42
DCP 4	.049	2.260	0.563	3	0.163	72	0.060	11	0.015	349	0.009	252	0.004	115	0.007	198	0.007	123	0.007	59
DCP 5	.074	2.171	0.330	9	0.213	76	0.055	12	0.030	49	0.031	325	0.006	199	0.002	323	0.005	130	0.010	56
DCP 6	.099	2.168	0.179	18	0.214	77	0.019	81	0.057	68	0.023	330	0.017	78	0.010	336	0.011	29	0.013	11
DCP 7	.149	1.991	0.095	93	0.160	71	0.089	146	0.047	55	0.032	152	0.034	57	0.007	152	0.023	65	0.008	51
DCP 8	.200	1.730	0.221	136	0.076	77	0.131	155	0.018	141	0.047	153	0.003	275	0.034	160	0.007	111	0.019	119
DCP 9	.250	1.530	0.271	136	0.078	244	0.011	216	0.057	216	0.051	270	0.011	31	0.013	259	0.020	340	0.017	30
DCP10	.300	1.305	0.244	116	0.134	222	0.097	258	0.068	319	0.009	192	0.021	334	0.017	8	0.031	49	0.019	53
DCP11	.399	0.989	0.213	48	0.026	85	0.038	187	0.025	248	0.010	235	0.009	89	0.003	356	0.006	11	0.009	28
DCP12	.501	0.751	0.288	35	0.070	97	0.064	163	0.037	234	0.009	245	0.018	324	0.007	32	0.006	326	0.014	20
DCP13	.600	0.573	0.299	26	0.055	111	0.037	133	0.022	179	0.017	183	0.019	235	0.007	295	0.019	313	0.013	340
DCP14	.701	0.473	0.249	24	0.032	188	0.026	60	0.023	95	0.021	124	0.010	180	0.011	210	0.009	251	0.007	269
DCP15	.800	0.309	0.239	15	0.030	186	0.033	36	0.016	103	0.016	107	0.012	131	0.008	154	0.006	220	0.007	177
DCP16	.900	0.016	0.173	10	0.015	153	0.013	57	0.016	107	0.014	96	0.004	178	0.004	235	0.010	195	0.004	230
DCP17	.969	-0.058	0.042	20	0.004	118	0.006	45	0.008	89	0.002	249	0.005	149	0.004	304	0.010	212	0.006	250

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.05	0.051	0.705	4.90	0.0	12.49	12077.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
228.7	129636.	0.10E 08	-0.098	1.147	16.13	-0.00145	2.841	0.0
(750.5)	(2707.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		12.491	4.899	0	0.177	16	0.037	285	0.010	175	0.020	7	0.027	74	0.018	226	0.007	249	0.006	60
CN		0.999	0.157	37	0.027	80	0.014	125	0.008	199	0.002	113	0.001	201	0.001	38	0.003	267	0.002	76
CM		-0.049	0.049	201	0.004	236	0.002	159	0.001	350	0.002	143	0.000	398	0.001	153	0.000	328	0.001	204
DCP 1	.010	2.669	0.467	1	0.116	78	0.028	127	0.019	134	0.010	133	0.016	59	0.008	204	0.012	111	0.006	351
DCP 2	.020	2.607	0.496	2	0.152	80	0.034	131	0.021	178	0.011	101	0.006	41	0.006	144	0.014	148	0.007	41
DCP 3	.030	2.424	0.361	1	0.161	88	0.073	129	0.004	50	0.018	143	0.015	8	0.016	144	0.010	36	0.005	204
DCP 4	.049	2.381	0.220	9	0.254	80	0.034	51	0.026	73	0.012	346	0.013	65	0.009	3	0.002	342	0.008	287
DCP 5	.074	2.276	0.100	21	0.184	82	0.055	150	0.043	102	0.029	130	0.024	77	0.015	93	0.008	49	0.005	116
DCP 6	.099	2.240	0.071	117	0.140	79	0.075	154	0.018	151	0.051	144	0.006	87	0.023	144	0.003	162	0.014	142
DCP 7	.149	2.048	0.160	133	0.006	345	0.089	153	0.049	216	0.027	154	0.021	193	0.004	225	0.014	234	0.009	206
DCP 8	.200	1.753	0.270	141	0.113	237	0.050	137	0.064	234	0.012	279	0.017	235	0.020	322	0.008	251	0.007	248
DCP 9	.250	1.433	0.167	95	0.073	237	0.011	88	0.008	343	0.023	79	0.006	22	0.005	298	0.017	301	0.001	183
DCP10	.500	1.232	0.148	64	0.026	264	0.023	96	0.024	249	0.010	102	0.012	298	0.003	108	0.011	297	0.004	173
DCP11	.399	1.048	0.194	56	0.023	32	0.015	37	0.003	24	0.003	7	0.011	279	0.008	53	0.013	307	0.003	77
DCP12	.501	0.855	0.226	42	0.024	76	0.009	50	0.005	202	0.004	329	0.001	185	0.002	43	0.009	287	0.010	97
DCP13	.600	0.695	0.248	29	0.036	72	0.009	29	0.008	108	0.006	294	0.007	193	0.004	69	0.005	164	0.006	71
DCP14	.701	0.574	0.259	18	0.038	79	0.001	107	0.007	164	0.006	312	0.002	164	0.002	8	0.010	146	0.006	42
DCP15	.800	0.396	0.258	10	0.036	79	0.004	231	0.014	130	0.003	330	0.006	62	0.004	278	0.006	132	0.009	1
DCP16	.900	0.086	0.176	9	0.019	54	0.003	254	0.009	209	0.004	33	0.005	103	0.003	308	0.004	97	0.006	292
DCP17	.969	-0.047	0.039	27	0.009	22	0.004	3	0.008	259	0.005	331	0.004	42	0.002	266	0.003	340	0.002	56

FORCED PITCHING OSCILLATION   AIRFOIL.   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.02	0.188	0.204	7.89	0.0	2.43	12153.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
69.7	12506.	0.33E 07	-0.059	0.999	10.41	-0.00133	0.757	0.0
(228.8)	(261.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.430	7.889 0	0.855 356	0.121 319	0.032 355	0.061 324	0.016 357	0.017 265	0.040 232	0.019 277
CN		0.373	0.597 359	0.043 13	0.004 51	0.005 26	0.005 51	0.005 18	0.011 338	0.025 213	0.004 163
CM		-0.022	0.028 294	0.003 272	0.002 308	0.001 214	0.003 256	0.003 218	0.004 153	0.009 7	0.001 331
DCP 1	.010	0.931	4.176 347	0.303 6	0.064 125	0.030 70	0.033 306	0.009 202	0.005 135	0.054 268	0.011 91
DCP 2	.020	0.793	3.122 350	0.194 357	0.026 329	0.018 49	0.027 299	0.006 196	0.005 298	0.064 286	0.016 62
DCP 3	.030	1.018	2.658 350	0.157 354	0.031 325	0.008 30	0.015 296	0.012 225	0.005 248	0.038 285	0.010 107
DCP 4	.049	0.829	2.159 351	0.129 347	0.028 330	0.010 18	0.006 235	0.013 190	0.007 227	0.043 297	0.002 357
DCP 5	.074	0.820	1.749 351	0.102 354	0.017 338	0.005 307	0.010 295	0.005 245	0.001 158	0.031 288	0.001 234
DCP 6	.099	0.937	1.471 352	0.086 357	0.020 6	0.011 12	0.009 236	0.006 161	0.001 175	0.030 286	0.005 282
DCP 7	.149	0.664	1.094 354	0.071 2	0.001 292	0.005 249	0.006 17	0.008 289	0.003 241	0.036 280	0.009 147
DCP 8	.200	0.592	0.899 358	0.060 7	0.005 291	0.002 103	0.003 118	0.008 180	0.012 103	0.033 305	0.007 217
DCP 9	.250	0.485	0.773 359	0.060 6	0.017 359	0.010 55	0.007 310	0.004 269	0.023 10	0.026 176	0.009 114
DCP10	.300	0.480	0.655 359	0.058 14	0.019 25	0.008 326	0.005 318	0.012 340	0.012 348	0.029 178	0.006 203
DCP11	.399	0.411	0.534 7	0.049 24	0.009 73	0.011 21	0.009 56	0.005 26	0.014 353	0.045 207	0.006 233
DCP12	.501	0.285	0.407 11	0.035 33	0.003 85	0.003 155	0.013 28	0.013 11	0.011 320	0.032 200	0.007 138
DCP13	.600	0.315	0.312 16	0.029 39	0.006 253	0.002 72	0.012 67	0.011 1	0.017 310	0.024 204	0.004 53
DCP14	.701	0.293	0.213 24	0.033 42	0.015 135	0.008 354	0.015 69	0.008 33	0.021 339	0.036 190	0.005 252
DCP15	.800	0.155	0.132 35	0.012 41	0.014 102	0.010 12	0.009 130	0.008 11	0.016 355	0.028 191	0.003 216
DCP16	.900	-0.039	0.055 54	0.011 169	0.007 202	0.011 85	0.013 57	0.010 62	0.013 301	0.039 188	0.009 136
DCP17	.969	0.018	0.017 173	0.006 334	0.009 54	0.003 350	0.007 55	0.019 79	0.022 342	0.025 202	0.020 128

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.09	0.171	0.200	7.89	0.0	4.83	12153.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
68.5	12133.	0.32E 07	-0.055	1.153	12.57	-0.00144	0.810	0.0
(224.9)	(253.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.833	7.895 0	0.622 357	0.123 313	0.029 4	0.051 326	0.015 353	0.017 226	0.026 272	0.021 277
CN		0.585	0.596 0	0.047 33	0.014 335	0.003 300	0.004 283	0.004 283	0.002 188	0.011 11	0.006 284
CM		-0.015	0.031 294	0.007 285	0.002 115	0.001 125	0.001 154	0.002 66	0.001 22	0.005 201	0.002 104
DCP 1	.010	2.339	3.906 347	0.349 27	0.157 250	0.112 240	0.058 137	0.008 56	0.037 117	0.011 18	0.027 290
DCP 2	.020	1.911	3.167 350	0.211 2	0.031 10	0.015 34	0.011 328	0.002 200	0.014 104	0.030 235	0.012 261
DCP 3	.030	1.974	2.721 350	0.169 358	0.027 5	0.016 19	0.009 20	0.005 330	0.003 171	0.013 251	0.003 344
DCP 4	.049	1.618	2.206 350	0.130 354	0.025 337	0.002 310	0.002 47	0.004 282	0.005 6	0.014 218	0.003 314
DCP 5	.074	1.460	1.780 351	0.116 359	0.021 11	0.004 4	0.004 221	0.004 43	0.006 57	0.014 216	0.003 229
DCP 6	.099	1.475	1.491 353	0.098 4	0.025 41	0.003 43	0.009 340	0.005 16	0.008 147	0.020 229	0.003 247
DCP 7	.149	1.088	1.111 355	0.071 2	0.012 38	0.006 195	0.005 273	0.008 98	0.004 40	0.013 190	0.006 248
DCP 8	.200	0.915	0.917 359	0.059 16	0.019 6	0.004 225	0.011 357	0.008 0	0.005 342	0.020 213	0.004 29
DCP 9	.250	0.754	0.779 359	0.072 24	0.022 318	0.002 17	0.012 310	0.006 283	0.007 134	0.025 0	0.011 214
DCP10	.300	0.719	0.649 1	0.059 34	0.011 306	0.012 328	0.006 324	0.004 325	0.008 234	0.017 6	0.010 255
DCP11	.399	0.598	0.512 8	0.048 51	0.014 317	0.005 31	0.001 256	0.009 307	0.004 332	0.023 24	0.020 321
DCP12	.501	0.421	0.399 13	0.045 58	0.016 310	0.007 69	0.009 289	0.008 341	0.004 231	0.011 0	0.006 270
DCP13	.600	0.412	0.306 18	0.048 60	0.020 337	0.002 279	0.010 333	0.011 296	0.009 249	0.019 29	0.008 322
DCP14	.701	0.361	0.212 26	0.045 71	0.028 331	0.006 276	0.003 246	0.008 211	0.008 169	0.012 24	0.009 215
DCP15	.800	0.189	0.135 38	0.025 97	0.004 345	0.006 329	0.006 119	0.008 240	0.007 72	0.025 30	0.010 286
DCP16	.900	-0.039	0.056 51	0.015 114	0.015 228	0.011 302	0.014 6	0.007 293	0.018 200	0.016 339	0.008 272
DCP17	.969	-0.003	0.017 132	0.002 241	0.011 336	0.003 17	0.012 383	0.021 199	0.009 56	0.033 26	0.004 352

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ 0.0	DRIVE HZ 23.13	K 0.174	MACH NO 0.199	DEL.ALPHA 7.91	DEL.H 0.0	ALPHA.O 7.43	TEST POINT 12153.4	CYCLES ANALYSED 20
V 67.8 (222.5)	Q 11893. (248.4)	RN 0.32E 07	CN(MIN) -0.048	CN(MAX) 1.377	ALPHA.NMAX 15.29	AERO DAMP -0.00154	TOR 0.857	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.430	7.906	0	0.585	357	0.080	298	0.022	82	0.030	329	0.012	93	0.021	176	0.029	237	0.009	293
CN		0.807	0.589	2	0.050	17	0.009	354	0.006	6	0.001	153	0.005	232	0.001	230	0.008	292	0.004	293
CM		-0.008	0.033	292	0.004	257	0.000	37	0.001	161	0.002	313	0.001	38	0.000	65	0.002	90	0.001	128
DCP 1	.010	3.749	3.604	347	0.375	29	0.077	349	0.101	60	0.134	317	0.052	219	0.052	297	0.057	230	0.015	188
DCP 2	.020	3.115	3.140	351	0.215	359	0.056	5	0.007	280	0.009	31	0.020	207	0.005	37	0.025	330	0.007	316
DCP 3	.030	3.003	2.720	351	0.185	355	0.034	3	0.006	302	0.006	346	0.011	227	0.008	188	0.015	345	0.003	343
DCP 4	.049	2.469	2.193	352	0.174	357	0.028	323	0.014	5	0.014	263	0.006	239	0.011	265	0.019	350	0.007	274
DCP 5	.074	2.144	1.765	352	0.129	358	0.023	3	0.013	3	0.009	302	0.006	226	0.013	206	0.020	3	0.002	116
DCP 6	.099	2.037	1.471	354	0.118	1	0.018	351	0.015	30	0.007	286	0.016	173	0.002	265	0.018	342	0.005	265
DCP 7	.149	1.485	1.101	356	0.072	4	0.025	13	0.013	357	0.014	286	0.016	342	0.003	25	0.018	345	0.011	330
DCP 8	.200	1.250	0.913	359	0.056	9	0.016	16	0.010	292	0.006	43	0.011	231	0.016	121	0.021	356	0.003	256
DCP 9	.250	1.047	0.775	1	0.060	359	0.006	268	0.003	355	0.001	246	0.008	294	0.011	99	0.010	249	0.006	268
DCP10	.300	0.962	0.646	2	0.053	12	0.014	351	0.003	9	0.005	116	0.013	259	0.002	168	0.010	223	0.010	280
DCP11	.399	0.789	0.512	10	0.045	30	0.006	31	0.004	14	0.003	148	0.005	250	0.006	263	0.013	255	0.006	243
DCP12	.501	0.567	0.403	16	0.039	32	0.009	333	0.009	15	0.003	118	0.005	217	0.002	244	0.002	154	0.005	243
DCP13	.600	0.509	0.300	23	0.046	53	0.008	344	0.010	4	0.004	141	0.011	180	0.005	352	0.005	186	0.007	8
DCP14	.701	0.417	0.197	34	0.052	58	0.002	157	0.003	281	0.008	163	0.003	159	0.006	240	0.014	272	0.003	349
DCP15	.800	0.223	0.134	44	0.033	53	0.005	91	0.002	243	0.006	72	0.007	169	0.003	186	0.016	274	0.009	277
DCP16	.900	-0.027	0.080	47	0.029	271	0.009	154	0.003	297	0.010	139	0.014	321	0.002	42	0.011	331	0.008	22
DCP17	.969	-0.009	0.023	60	0.008	321	0.023	306	0.013	41	0.013	134	0.008	166	0.006	230	0.009	282	0.014	273

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ 0.0	DRIVE HZ 23.11	K 0.174	MACH NO 0.198	DEL.ALPHA 7.88	DEL.H 0.0	ALPHA.O 9.92	TEST POINT 12153.5	CYCLES ANALYSED 20
V 67.6 (221.7)	Q 11831. (247.1)	RN 0.32E 07	CN(MIN) -0.050	CN(MAX) 1.617	ALPHA.NMAX 17.83	AERO DAMP -0.00119	TOR 0.662	EXT DAMP 0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		9.920	7.883	0	0.649	357	0.094	295	0.032	28	0.035	324	0.021	7	0.005	298	0.031	230	0.012	261
CN		0.916	0.631	16	0.069	309	0.035	93	0.006	274	0.008	79	0.007	18	0.001	64	0.017	238	0.007	248
CM		-0.010	0.024	257	0.021	356	0.014	220	0.006	30	0.003	234	0.001	252	0.001	237	0.005	52	0.003	56
DCP 1	.010	4.625	3.472	358	0.375	346	0.077	177	0.105	89	0.021	93	0.099	51	0.046	340	0.025	39	0.064	343
DCP 2	.020	3.855	3.076	1	0.313	329	0.030	104	0.020	327	0.011	290	0.017	328	0.001	316	0.025	290	0.012	357
DCP 3	.030	3.649	2.725	0	0.262	319	0.048	102	0.031	346	0.017	276	0.001	125	0.006	329	0.019	278	0.010	325
DCP 4	.049	2.620	1.760	17	0.678	0	0.261	252	0.116	141	0.049	62	0.043	356	0.034	279	0.031	224	0.000	240
DCP 5	.074	2.281	1.479	19	0.553	349	0.222	223	0.103	95	0.025	344	0.025	353	0.023	256	0.020	212	0.002	126
DCP 6	.099	2.165	1.319	19	0.433	339	0.179	197	0.094	63	0.021	294	0.011	2	0.018	218	0.006	259	0.009	260
DCP 7	.149	1.672	1.133	14	0.261	311	0.123	150	0.091	9	0.024	203	0.013	352	0.027	184	0.002	252	0.011	277
DCP 8	.200	1.443	1.010	14	0.190	292	0.111	125	0.057	343	0.024	221	0.016	309	0.015	112	0.038	304	0.012	217
DCP 9	.250	1.213	0.866	12	0.126	285	0.097	92	0.052	301	0.017	142	0.011	0	0.010	3	0.029	227	0.014	149
DCP10	.300	1.107	0.731	13	0.082	267	0.090	85	0.050	292	0.015	118	0.004	355	0.007	41	0.029	226	0.001	170
DCP11	.399	0.906	0.607	18	0.063	241	0.083	77	0.037	288	0.019	92	0.007	102	0.007	73	0.030	237	0.006	285
DCP12	.501	0.650	0.484	23	0.050	221	0.074	66	0.030	246	0.020	114	0.010	75	0.006	18	0.011	208	0.002	303
DCP13	.600	0.553	0.376	29	0.043	201	0.070	54	0.029	231	0.020	60	0.005	9	0.007	8	0.014	230	0.018	263
DCP14	.701	0.447	0.270	38	0.042	172	0.058	38	0.033	204	0.028	50	0.003	224	0.008	159	0.015	215	0.011	239
DCP15	.800	0.245	0.182	42	0.052	173	0.046	21	0.032	178	0.013	45	0.004	41	0.002	124	0.022	234	0.011	209
DCP16	.900	0.010	0.116	27	0.032	184	0.019	356	0.020	136	0.013	312	0.002	122	0.005	345	0.019	238	0.014	241
DCP17	.969	0.006	0.042	9	0.015	229	0.009	93	0.012	119	0.005	256	0.017	16	0.003	84	0.019	258	0.010	240

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.12	0.175	0.197	7.02	0.0	12.22	12153.6	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
67.4	11783.	0.52E 07	-0.277	2.160	19.06	-0.00006	0.035	0.0
(321.2)	(246.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		12.219	7.824 0	0.676 350	0.150 303	0.014 201	0.071 2	0.034 266	0.020 269	0.028 204	0.016 275
CN		1.070	0.710 28	0.224 300	0.133 166	0.004 62	0.053 314	0.033 224	0.018 109	0.031 351	0.011 244
CM		-0.038	0.062 188	0.366 41	0.045 291	0.028 188	0.021 86	0.012 352	0.009 248	0.010 169	0.004 59
DCP 1	.010	4.199	1.813 47	1.556 24	0.431 290	0.101 270	0.225 215	0.151 145	0.098 126	0.069 45	0.031 310
DCP 2	.020	3.630	1.927 41	1.278 16	0.425 282	0.101 205	0.076 179	0.051 88	0.025 88	0.062 337	0.022 265
DCP 3	.030	3.455	1.771 40	1.154 11	0.457 278	0.182 195	0.119 130	0.103 57	0.070 337	0.096 276	0.069 194
DCP 4	.049	2.952	1.502 37	0.881 11	0.360 272	0.164 157	0.076 40	0.045 256	0.042 133	0.050 345	0.023 256
DCP 5	.074	2.614	1.403 35	0.745 355	0.330 243	0.171 134	0.082 31	0.021 295	0.010 82	0.053 304	0.033 201
DCP 6	.099	2.450	1.324 34	0.655 342	0.324 226	0.172 119	0.080 44	0.029 346	0.025 313	0.052 285	0.037 104
DCP 7	.149	1.905	1.191 30	0.519 322	0.286 203	0.134 114	0.082 40	0.052 321	0.014 255	0.047 209	0.035 101
DCP 8	.200	1.642	1.079 29	0.454 316	0.232 202	0.153 123	0.111 43	0.071 303	0.026 269	0.027 255	0.031 155
DCP 9	.250	1.435	1.038 25	0.415 302	0.265 187	0.182 102	0.142 9	0.104 280	0.051 222	0.028 145	0.028 76
DCP10	.300	1.325	0.910 25	0.372 292	0.242 176	0.171 86	0.129 353	0.088 262	0.056 200	0.032 89	0.038 13
DCP11	.399	1.114	0.808 26	0.333 280	0.247 165	0.175 73	0.134 339	0.093 255	0.064 175	0.069 56	0.046 351
DCP12	.501	0.836	0.675 24	0.282 263	0.221 143	0.151 48	0.116 311	0.079 225	0.064 127	0.065 23	0.037 296
DCP13	.600	0.715	0.562 23	0.264 247	0.209 127	0.150 23	0.115 284	0.079 197	0.063 91	0.059 354	0.025 260
DCP14	.701	0.584	0.421 22	0.250 229	0.210 111	0.135 6	0.115 255	0.066 158	0.056 59	0.057 333	0.043 222
DCP15	.800	0.357	0.308 18	0.207 221	0.160 105	0.113 359	0.098 243	0.059 141	0.055 48	0.060 328	0.044 208
DCP16	.900	0.076	0.212 5	0.126 221	0.076 92	0.069 336	0.043 235	0.036 130	0.030 39	0.033 318	0.009 166
DCP17	.969	0.046	0.102 359	0.054 213	0.049 90	0.035 323	0.032 219	0.024 96	0.033 336	0.010 207	0.011 87

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.03	0.114	0.301	7.91	0.0	0.65	12155.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
102.5	27359.	0.49E 07	-0.040	0.803	8.65	-0.00086	0.709	0.0
(336.4)	(571.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.647	7.909 0	0.575 357	0.079 301	0.015 100	0.032 324	0.022 95	0.019 162	0.029 230	0.004 277
CN		0.141	0.670 357	0.042 3	0.010 326	0.005 301	0.005 322	0.004 272	0.003 226	0.000 43	0.004 204
CM		-0.017	0.019 299	0.004 319	0.001 724	0.001 71	0.001 153	0.001 163	0.000 249	0.001 21	0.001 18
DCP 1	.010	-0.616	4.680 349	0.391 9	0.122 315	0.118 11	0.043 90	0.038 190	0.017 214	0.009 16	0.009 222
DCP 2	.020	-0.247	3.409 352	0.259 351	0.070 323	0.026 299	0.018 276	0.021 250	0.021 221	0.019 30	0.003 331
DCP 3	.030	0.083	2.846 352	0.214 342	0.057 318	0.021 297	0.017 281	0.021 248	0.016 226	0.011 9	0.007 243
DCP 4	.049	0.215	2.319 352	0.183 342	0.040 299	0.012 311	0.018 301	0.014 245	0.011 236	0.014 345	0.004 216
DCP 5	.074	0.306	1.695 352	0.150 345	0.029 294	0.008 301	0.016 294	0.009 250	0.009 229	0.009 1	0.003 236
DCP 6	.099	0.419	1.607 353	0.125 350	0.025 294	0.001 319	0.015 302	0.009 266	0.012 235	0.012 20	0.005 240
DCP 7	.149	0.279	1.204 354	0.090 347	0.011 272	0.008 335	0.007 320	0.005 223	0.008 245	0.011 43	0.004 17
DCP 8	.200	0.251	0.996 354	0.074 351	0.007 266	0.003 321	0.008 342	0.013 273	0.013 221	0.016 33	0.004 123
DCP 9	.250	0.193	0.889 356	0.054 9	0.014 329	0.003 312	0.007 342	0.001 198	0.001 181	0.001 203	0.001 129
DCP10	.300	0.198	0.748 356	0.044 10	0.006 4	0.007 261	0.003 329	0.004 182	0.001 190	0.004 182	0.008 203
DCP11	.399	0.183	0.593 2	0.033 24	0.011 15	0.004 242	0.006 308	0.003 314	0.003 221	0.005 227	0.004 206
DCP12	.501	0.124	0.459 3	0.027 35	0.011 350	0.006 4	0.004 289	0.002 321	0.005 204	0.003 179	
DCP13	.600	0.151	0.351 7	0.019 33	0.006 59	0.006 289	0.008 331	0.006 320	0.001 70	0.004 193	0.008 230
DCP14	.701	0.208	0.247 9	0.017 65	0.009 330	0.004 259	0.004 319	0.002 331	0.002 208	0.001 217	0.005 175
DCP15	.800	0.097	0.144 16	0.010 68	0.005 0	0.003 285	0.004 309	0.003 237	0.001 341	0.004 174	0.009 211
DCP16	.900	-0.075	0.040 38	0.010 173	0.004 250	0.007 264	0.004 317	0.005 339	0.004 174	0.004 257	0.003 251
DCP17	.969	-0.027	0.027 169	0.005 211	0.007 304	0.002 315	0.004 132	0.004 4	0.004 35	0.002 131	0.006 94

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.03	0.116	0.248	7.91	0.0	2.23	12155.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
101.3 (332.4)	26885. (561.5)	0.48E 07	-0.039	1.030	10.25	-0.00094	0.768	0.0

HARMONIC ANALYSIS

DATA TYPE	R/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.235	7.912 0	0.609 356	0.098 312	0.016 23	0.043 343	0.006 19	0.011 156	0.021 249	0.013 322
CN		0.354	0.691 356	0.047 8	0.011 8	0.002 357	0.003 317	0.002 295	0.002 262	0.002 251	0.001 306
CM		-0.015	0.022 304	0.003 282	0.001 222	0.001 212	0.001 117	0.000 123	0.001 75	0.000 107	0.000 305
DCP 1	.010	0.773	4.815 348	0.390 13	0.061 73	0.050 176	0.021 189	0.010 10	0.015 301	0.015 253	0.006 277
DCP 2	.020	0.764	3.610 351	0.231 353	0.046 348	0.012 344	0.010 295	0.003 267	0.008 276	0.008 281	0.007 274
DCP 3	.030	0.935	3.039 350	0.188 347	0.042 334	0.010 345	0.016 297	0.007 267	0.008 263	0.003 259	0.007 307
DCP 4	.049	0.932	2.481 351	0.152 343	0.030 328	0.008 292	0.009 341	0.006 226	0.007 315	0.008 248	0.009 296
DCP 5	.074	0.895	2.009 351	0.125 349	0.026 331	0.007 317	0.004 338	0.005 239	0.004 254	0.002 184	0.004 327
DCP 6	.099	0.917	1.692 352	0.110 357	0.020 339	0.006 334	0.003 308	0.004 359	0.004 260	0.006 220	0.006 305
DCP 7	.149	0.669	1.265 353	0.079 354	0.018 345	0.002 227	0.004 334	0.003 254	0.002 165	0.003 236	0.003 348
DCP 8	.200	0.542	1.039 356	0.066 6	0.014 10	0.005 100	0.004 24	0.005 271	0.005 227	0.004 204	0.004 285
DCP 9	.250	0.494	0.896 355	0.064 5	0.014 0	0.008 15	0.007 314	0.001 281	0.001 77	0.003 350	0.003 57
DCP10	.300	0.441	0.753 356	0.054 7	0.015 10	0.004 0	0.005 1	0.003 3	0.003 320	0.003 229	0.002 79
DCP11	.399	0.391	0.600 1	0.045 19	0.011 10	0.005 319	0.003 332	0.001 245	0.005 83	0.002 161	0.002 192
DCP12	.501	0.281	0.459 4	0.036 24	0.008 28	0.003 288	0.005 346	0.003 304	0.003 299	0.002 250	0.002 285
DCP13	.600	0.268	0.351 7	0.031 34	0.012 45	0.003 357	0.005 283	0.004 296	0.004 196	0.001 224	0.003 138
DCP14	.701	0.203	0.235 10	0.024 52	0.010 18	0.003 60	0.000 322	0.001 332	0.002 354	0.003 286	0.003 342
DCP15	.800	0.140	0.140 17	0.017 62	0.010 30	0.007 45	0.001 182	0.002 39	0.006 286	0.005 350	0.002 159
DCP16	.900	-0.071	0.047 27	0.006 51	0.003 15	0.005 296	0.008 262	0.004 159	0.006 222	0.002 176	0.003 291
DCP17	.969	-0.034	0.021 181	0.010 263	0.002 320	0.006 125	0.003 43	0.004 296	0.006 278	0.006 252	0.005 97

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.02	0.116	0.297	7.88	0.0	4.72	12155.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
100.7 (330.5)	26669. (557.0)	0.48E 07	-0.035	1.260	12.74	-0.00103	0.840	0.0

HARMONIC ANALYSIS

DATA TYPE	R/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.722	7.878 0	0.614 356	0.098 306	0.017 2	0.027 334	0.024 339	0.015 165	0.019 223	0.013 265
CN		0.591	0.675 357	0.059 11	0.009 323	0.001 100	0.003 340	0.004 322	0.000 191	0.000 163	0.001 348
CM		-0.010	0.025 305	0.003 254	0.000 115	0.001 350	0.000 171	0.001 198	0.000 207	0.000 341	0.000 82
DCP 1	.010	2.504	4.671 348	0.361 346	0.065 174	0.070 83	0.074 333	0.059 252	0.025 137	0.003 118	0.015 82
DCP 2	.020	1.981	3.527 351	0.266 7	0.076 342	0.032 294	0.010 189	0.006 310	0.005 156	0.011 25	0.008 357
DCP 3	.030	1.979	3.047 351	0.219 355	0.039 324	0.014 339	0.003 268	0.011 315	0.006 138	0.008 27	0.005 7
DCP 4	.049	1.790	2.482 351	0.180 355	0.043 331	0.010 313	0.003 179	0.006 317	0.003 236	0.006 357	0.009 19
DCP 5	.074	1.588	1.995 351	0.152 358	0.033 327	0.005 327	0.003 289	0.010 322	0.004 328	0.003 54	0.004 43
DCP 6	.099	1.494	1.673 352	0.135 4	0.022 337	0.004 246	0.004 36	0.009 316	0.003 188	0.005 332	0.005 70
DCP 7	.149	1.085	1.253 353	0.097 2	0.022 329	0.004 7	0.004 302	0.003 354	0.006 257	0.004 300	0.006 351
DCP 8	.200	0.900	1.029 357	0.080 9	0.017 299	0.002 72	0.005 265	0.008 325	0.001 254	0.003 23	0.005 304
DCP 9	.250	0.799	0.873 356	0.077 9	0.016 323	0.002 339	0.003 49	0.002 317	0.004 248	0.004 121	0.003 177
DCP10	.300	0.720	0.731 357	0.068 15	0.009 312	0.007 107	0.007 0	0.009 301	0.003 300	0.003 177	0.006 92
DCP11	.399	0.593	0.579 2	0.063 23	0.005 254	0.003 254	0.007 27	0.002 338	0.002 354	0.003 358	0.000 170
DCP12	.501	0.438	0.444 5	0.045 33	0.005 300	0.002 54	0.006 301	0.005 4	0.006 123	0.004 203	0.004 313
DCP13	.600	0.378	0.332 9	0.038 31	0.010 335	0.002 289	0.005 4	0.004 322	0.003 154	0.004 211	0.004 265
DCP14	.701	0.159	0.220 15	0.038 37	0.005 34	0.003 173	0.001 113	0.002 321	0.004 335	0.001 10	0.003 43
DCP15	.800	0.181	0.132 22	0.023 31	0.005 276	0.007 141	0.002 285	0.003 17	0.002 66	0.004 55	0.001 304
DCP16	.900	-0.054	0.050 28	0.006 6	0.003 337	0.003 286	0.003 293	0.005 33	0.001 274	0.004 67	0.002 275
DCP17	.969	-0.038	0.014 154	0.008 286	0.010 270	0.006 146	0.003 125	0.006 226	0.001 250	0.006 192	0.004 272

245

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	23.03	0.117	0.295	7.86	0.0	7.34	12155.4	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	100.3	26468.	0.48E 07	-0.106	1.470	15.17	-0.00080	0.647	0.0
	(329.0)	(552.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.336	7.854 0	0.635 359	0.131 305	0.009 184	0.043 15	0.040 318	0.011 106	0.028 243	0.011 249
CN		0.752	0.035 10	0.138 349	0.046 192	0.032 52	0.022 313	0.016 220	0.021 100	0.014 334	0.005 286
CM		-0.014	0.021 245	0.022 62	0.023 308	0.016 193	0.009 96	0.006 353	0.007 253	0.007 115	0.002 357
DCP 1	.010	3.116	2.917 359	1.285 37	0.731 321	0.477 237	0.286 160	0.167 95	0.168 18	0.088 295	0.046 200
DCP 2	.020	2.505	2.319 2	1.041 39	0.599 322	0.415 234	0.287 148	0.177 71	0.131 3	0.065 296	0.041 258
DCP 3	.030	2.330	1.896 5	0.999 36	0.567 312	0.354 221	0.203 132	0.077 63	0.072 40	0.062 345	0.094 266
DCP 4	.049	2.358	2.047 0	0.464 12	0.157 289	0.074 190	0.056 87	0.037 340	0.026 278	0.027 162	0.022 81
DCP 5	.074	2.033	1.616 2	0.400 13	0.135 283	0.063 179	0.047 70	0.037 315	0.018 222	0.024 114	0.017 37
DCP 6	.099	1.652	1.335 6	0.355 12	0.126 273	0.070 162	0.052 51	0.041 297	0.024 206	0.029 107	0.018 9
DCP 7	.149	1.356	1.033 6	0.296 2	0.129 253	0.075 130	0.053 19	0.035 285	0.015 147	0.020 72	0.012 15
DCP 8	.200	1.159	0.931 9	0.257 347	0.141 215	0.098 100	0.071 357	0.049 256	0.032 165	0.024 70	0.015 0
DCP 9	.250	1.030	0.868 9	0.242 328	0.154 191	0.121 76	0.080 337	0.053 254	0.032 157	0.016 95	0.032 0
DCP10	.300	0.937	0.765 9	0.219 316	0.163 181	0.127 70	0.083 335	0.055 260	0.050 165	0.029 72	0.031 332
DCP11	.399	0.772	0.630 16	0.167 314	0.138 173	0.112 64	0.073 326	0.049 249	0.051 149	0.031 34	0.028 311
DCP12	.501	0.567	0.479 17	0.110 312	0.102 154	0.084 35	0.057 300	0.041 212	0.049 110	0.035 344	0.019 256
DCP13	.600	0.458	0.351 22	0.073 310	0.086 137	0.086 13	0.057 271	0.039 172	0.048 82	0.041 320	0.022 221
DCP14	.701	0.406	0.231 31	0.048 317	0.072 117	0.064 350	0.040 234	0.032 137	0.040 48	0.040 290	0.020 161
DCP15	.800	0.236	0.174 24	0.046 280	0.064 112	0.044 348	0.023 234	0.016 155	0.024 49	0.028 279	0.013 124
DCP16	.900	-0.014	0.094 12	0.041 227	0.037 104	0.033 328	0.011 249	0.016 118	0.022 22	0.028 261	0.011 137
DCP17	.969	-0.030	0.027 1	0.026 229	0.010 40	0.004 249	0.013 285	0.011 152	0.015 45	0.013 274	0.006 202

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	23.08	0.117	0.295	7.81	0.0	9.96	12155.5	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	100.1	26620.	0.48E 07	-0.186	1.766	17.58	-0.00083	0.676	0.0
	(328.4)	(551.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		9.959	7.808 0	0.605 2	0.126 324	0.044 314	0.049 221	0.074 59	0.026 208	0.044 235	0.008 288
CN		0.878	0.501 24	0.228 8	0.082 274	0.055 189	0.041 104	0.027 28	0.022 320	0.020 250	0.014 180
CM		-0.024	0.047 211	0.044 89	0.027 1	0.016 303	0.015 230	0.009 147	0.006 112	0.007 39	0.005 328
DCP 1	.010	3.492	1.037 14	1.916 62	0.856 0	0.369 319	0.243 283	0.122 267	0.183 239	0.157 186	0.127 140
DCP 2	.020	2.936	1.061 18	1.457 62	0.680 358	0.300 305	0.161 266	0.075 251	0.125 234	0.110 181	0.116 144
DCP 3	.030	2.687	0.828 21	1.303 62	0.590 359	0.232 309	0.139 294	0.135 267	0.156 219	0.111 161	0.093 132
DCP 4	.049	2.731	1.253 13	0.798 46	0.353 345	0.200 285	0.157 223	0.116 147	0.073 80	0.058 18	0.028 307
DCP 5	.074	2.326	1.002 18	0.691 40	0.283 327	0.137 258	0.093 197	0.078 116	0.046 42	0.020 339	0.016 261
DCP 6	.099	2.098	0.873 24	0.653 33	0.292 310	0.140 227	0.087 171	0.074 100	0.047 23	0.031 318	0.021 225
DCP 7	.149	1.593	0.811 26	0.526 17	0.231 284	0.113 209	0.072 157	0.071 103	0.036 24	0.027 340	0.016 314
DCP 8	.200	1.342	0.738 29	0.445 14	0.221 287	0.151 219	0.134 156	0.107 81	0.063 10	0.031 314	0.030 262
DCP 9	.250	1.170	0.732 27	0.381 359	0.192 270	0.129 202	0.110 130	0.079 54	0.036 332	0.022 327	0.020 280
DCP10	.300	1.055	0.660 26	0.342 351	0.175 260	0.132 195	0.112 122	0.077 45	0.040 344	0.033 317	0.038 260
DCP11	.399	0.885	0.592 30	0.276 344	0.145 251	0.110 186	0.100 112	0.068 37	0.039 359	0.035 301	0.034 240
DCP12	.501	0.675	0.499 29	0.211 332	0.112 229	0.093 163	0.091 83	0.055 359	0.035 317	0.041 268	0.040 197
DCP13	.600	0.559	0.408 30	0.170 317	0.100 203	0.078 137	0.083 59	0.059 342	0.036 297	0.043 238	0.036 168
DCP14	.701	0.489	0.301 35	0.129 299	0.096 178	0.065 114	0.064 39	0.047 312	0.026 268	0.041 209	0.034 123
DCP15	.800	0.299	0.242 24	0.118 275	0.085 166	0.057 102	0.047 26	0.026 302	0.031 269	0.033 195	0.028 101
DCP16	.900	0.033	0.157 9	0.078 261	0.037 163	0.041 108	0.037 10	0.021 262	0.007 256	0.027 192	0.026 87
DCP17	.969	-0.016	0.063 11	0.044 264	0.011 199	0.016 137	0.013 0	0.007 271	0.013 304	0.017 195	0.008 97

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.07	0.117	0.295	7.79	0.0	12.35	12155.6	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
100.0	26401.	0.48E 07	-0.236	2.005	18.50	-0.00121	0.982	0.0
(328.1)	(551.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		12.352	7.788	0	0.581	1	0.055	340	0.059	31	0.118	335	0.110	219	0.034	4	0.025	53	0.015	322
CN		1.001	0.461	45	0.256	21	0.100	323	0.061	265	0.052	227	0.048	153	0.030	73	0.027	74	0.017	344
CM		-0.039	0.073	206	0.045	107	0.023	71	0.021	18	0.015	347	0.017	276	0.010	211	0.006	215	0.006	117
DCP 1	.010	3.667	0.889	121	1.795	66	0.434	65	0.420	40	0.181	25	0.141	18	0.165	18	0.200	350	0.167	310
DCP 2	.020	3.122	0.727	102	1.451	66	0.361	48	0.315	30	0.139	352	0.066	352	0.095	14	0.113	354	0.142	322
DCP 3	.030	2.855	0.573	110	1.235	71	0.331	57	0.329	49	0.241	7	0.114	335	0.114	352	0.105	319	0.092	292
DCP 4	.049	3.034	0.700	38	0.871	66	0.394	28	0.236	345	0.166	305	0.119	255	0.071	237	0.066	181	0.035	154
DCP 5	.074	2.583	0.639	47	0.744	55	0.284	10	0.152	322	0.099	285	0.075	234	0.032	203	0.045	157	0.018	116
DCP 6	.099	2.311	0.666	53	0.899	46	0.260	353	0.150	307	0.109	265	0.087	211	0.035	162	0.035	138	0.011	114
DCP 7	.149	1.788	0.710	50	0.536	28	0.175	342	0.158	305	0.125	249	0.102	201	0.056	150	0.043	119	0.026	57
DCP 8	.200	1.488	0.663	53	0.483	30	0.207	343	0.167	297	0.116	254	0.106	215	0.070	151	0.035	128	0.028	102
DCP 9	.250	1.323	0.683	48	0.433	18	0.208	326	0.154	278	0.105	238	0.102	192	0.055	127	0.055	109	0.017	80
DCP10	.300	1.201	0.646	46	0.385	11	0.192	319	0.145	270	0.109	240	0.114	187	0.066	123	0.059	102	0.039	63
DCP11	.399	1.028	0.600	44	0.305	6	0.166	314	0.119	262	0.102	243	0.119	178	0.065	112	0.068	109	0.045	54
DCP12	.501	0.809	0.535	39	0.233	349	0.131	297	0.099	237	0.082	219	0.105	150	0.071	82	0.064	73	0.050	7
DCP13	.600	0.665	0.466	38	0.196	332	0.103	275	0.097	217	0.078	184	0.095	120	0.070	53	0.053	52	0.052	334
DCP14	.701	0.581	0.382	37	0.169	311	0.092	251	0.096	197	0.060	158	0.096	89	0.075	16	0.036	359	0.048	294
DCP15	.800	0.376	0.307	26	0.132	291	0.076	241	0.077	182	0.052	143	0.081	64	0.050	2	0.029	343	0.039	255
DCP16	.900	0.077	0.193	15	0.072	285	0.040	248	0.031	166	0.027	151	0.041	57	0.020	343	0.020	7	0.020	257
DCP17	.969	-0.001	0.085	13	0.048	299	0.028	254	0.016	144	0.005	161	0.026	57	0.017	348	0.006	208	0.013	211

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.73	0.086	0.348	7.91	0.0	0.01	12157.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
134.6	47866.	0.65E 07	-0.046	0.864	8.06	-0.00086	0.926	0.0
(441.5)	(999.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		0.010	7.909	0	0.644	356	0.106	316	0.015	330	0.045	343	0.013	9	0.015	215	0.047	239	0.016	281
CN		0.163	0.684	357	0.033	293	0.030	302	0.010	327	0.008	318	0.008	359	0.007	79	0.014	209	0.005	169
CM		-0.014	0.019	301	0.006	292	0.003	12	0.002	82	0.000	290	0.001	40	0.001	112	0.003	67	0.001	114
DCP 1	.010	-0.453	4.625	350	0.399	271	0.543	310	0.510	28	0.311	96	0.175	172	0.063	206	0.053	220	0.034	282
DCP 2	.020	-0.241	3.655	352	0.166	307	0.144	295	0.096	355	0.069	70	0.065	166	0.057	231	0.047	287	0.034	32
DCP 3	.030	-0.063	3.299	352	0.164	11	0.043	206	0.040	282	0.030	81	0.053	191	0.044	255	0.024	304	0.005	57
DCP 4	.049	0.213	2.666	352	0.121	358	0.052	185	0.076	244	0.060	315	0.035	39	0.030	125	0.036	209	0.008	285
DCP 5	.074	1.156	0.629	0	1.100	254	0.586	327	0.074	59	0.246	293	0.345	10	0.283	78	0.164	129	0.154	142
DCP 6	.099	0.390	1.827	353	0.096	5	0.012	204	0.035	233	0.033	300	0.016	359	0.018	98	0.028	198	0.005	269
DCP 7	.149	0.271	1.349	353	0.061	1	0.014	221	0.016	246	0.010	289	0.013	358	0.008	58	0.014	179	0.008	216
DCP 8	.200	0.226	1.099	356	0.050	359	0.009	295	0.010	260	0.009	298	0.009	323	0.006	51	0.021	189	0.008	188
DCP 9	.250	0.203	0.957	355	0.053	2	0.014	299	0.011	240	0.013	267	0.013	282	0.011	341	0.007	206	0.006	133
DCP10	.300	0.208	0.789	356	0.037	351	0.024	296	0.013	332	0.004	9	0.003	265	0.005	259	0.009	227	0.003	220
DCP11	.399	0.186	0.523	1	0.021	358	0.021	288	0.012	331	0.004	18	0.001	310	0.001	110	0.015	243	0.003	208
DCP12	.501	0.139	0.477	3	0.011	12	0.016	294	0.008	295	0.003	356	0.005	290	0.001	232	0.017	236	0.006	281
DCP13	.600	0.152	0.355	6	0.005	34	0.014	286	0.008	303	0.005	298	0.004	290	0.002	131	0.014	239	0.004	173
DCP14	.701	0.219	0.246	8	0.006	121	0.011	279	0.008	313	0.002	310	0.002	265	0.004	358	0.012	226	0.004	211
DCP15	.800	3.101	0.135	18	0.013	158	0.014	261	0.007	306	0.005	7	0.002	342	0.003	10	0.012	234	0.001	203
DCP16	.900	-0.074	0.037	59	0.024	202	0.016	261	0.006	274	0.001	251	0.002	292	0.003	45	0.015	219	0.004	70
DCP17	.969	-0.039	0.035	169	0.007	173	0.006	223	0.002	289	0.003	345	0.004	124	0.000	248	0.012	248	0.006	283

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.05	0.088	0.396	7.91	0.0	2.44	12157.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
133.6	47406.	0.64E 07	-0.032	1.077	10.44	-0.00084	0.901	0.0
(438.4)	(990.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.440	7.914 0	0.682 355	0.136 319	0.064 332	0.056 321	0.029 332	0.012 194	0.029 272	0.030 278
CN		0.381	0.698 355	0.058 349	0.029 324	0.005 234	0.013 303	0.015 4	0.011 100	0.006 153	0.002 269
CM		-0.006	0.019 305	0.009 256	0.002 61	0.000 102	0.002 275	0.002 8	0.002 72	0.002 176	0.001 148
DCP 1	.010	1.016	5.460 349	0.472 352	0.168 144	0.068 200	0.044 175	0.049 56	0.049 319	0.028 250	0.015 292
DCP 2	.020	0.923	3.851 351	0.304 342	0.055 267	0.076 73	0.091 3	0.089 266	0.068 186	0.040 92	0.033 343
DCP 3	.030	1.001	3.181 351	0.235 356	0.101 330	0.034 288	0.010 260	0.005 327	0.007 246	0.003 228	0.017 323
DCP 4	.049	1.070	2.631 351	0.192 353	0.083 330	0.034 269	0.009 243	0.004 346	0.005 243	0.005 221	0.003 298
DCP 5	.074	1.729	0.839 354	0.889 261	0.472 336	0.117 186	0.413 291	0.523 12	0.440 89	0.257 160	0.076 186
DCP 6	.099	0.971	1.802 352	0.143 2	0.048 326	0.010 275	0.006 291	0.008 350	0.004 240	0.004 166	0.005 308
DCP 7	.149	0.701	1.343 353	0.107 359	0.028 330	0.008 275	0.005 337	0.008 242	0.002 212	0.008 174	0.002 19
DCP 8	.200	0.572	1.101 355	0.089 7	0.024 330	0.006 273	0.005 339	0.006 296	0.006 268	0.004 203	0.004 263
DCP 9	.250	0.499	0.949 355	0.087 5	0.022 314	0.007 311	0.010 309	0.004 1	0.002 217	0.003 54	0.006 338
DCP10	.300	0.452	0.790 355	0.076 7	0.018 314	0.005 328	0.006 314	0.004 328	0.002 129	0.002 11	0.003 311
DCP11	.399	0.372	0.628 0	0.064 19	0.018 317	0.004 278	0.006 351	0.003 316	0.002 208	0.002 82	0.004 302
DCP12	.501	0.276	0.480 2	0.053 21	0.016 314	0.003 305	0.004 45	0.003 352	0.003 79	0.003 331	0.001 296
DCP13	.600	0.245	0.354 4	0.043 33	0.016 319	0.006 268	0.002 294	0.003 9	0.003 197	0.002 277	0.000 1
DCP14	.701	0.280	0.235 7	0.043 43	0.018 308	0.005 225	0.003 57	0.003 67	0.004 149	0.002 8	0.003 144
DCP15	.800	0.128	0.131 14	0.031 45	0.018 302	0.004 231	0.003 76	0.004 337	0.003 183	0.004 44	0.003 329
DCP16	.900	-0.078	0.045 25	0.010 40	0.008 276	0.005 191	0.005 327	0.005 132	0.000 19	0.004 47	0.001 274
DCP17	.969	-0.050	0.027 168	0.006 227	0.008 210	0.002 50	0.003 23	0.007 246	0.005 171	0.002 8	0.003 317

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.73	0.087	0.394	7.90	0.0	4.72	12157.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
133.1	47100.	0.64E 07	-0.030	1.265	12.52	-0.00090	0.959	0.0
(436.6)	(983.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.717	7.896 0	0.742 354	0.217 324	0.093 311	0.062 302	0.053 329	0.034 251	0.067 248	0.043 261
CN		0.548	0.600 1	0.142 13	0.062 290	0.028 170	0.011 338	0.015 359	0.011 92	0.012 212	0.004 247
CM		-0.003	0.020 291	0.006 258	0.011 2	0.010 252	0.006 167	0.006 33	0.002 50	0.002 85	0.001 256
DCP 1	.010	2.032	4.051 349	0.799 52	0.568 3	0.482 280	0.328 203	0.144 120	0.048 54	0.023 170	0.037 81
DCP 2	.020	1.676	3.098 354	0.681 39	0.384 335	0.233 265	0.173 199	0.117 126	0.088 66	0.036 2	0.032 341
DCP 3	.030	1.728	2.745 354	0.529 30	0.288 322	0.159 248	0.116 173	0.079 97	0.054 45	0.042 343	0.050 288
DCP 4	.049	1.622	2.184 354	0.469 36	0.272 327	0.146 248	0.092 167	0.055 78	0.027 5	0.011 318	0.019 312
DCP 5	.074	1.985	0.861 0	0.432 293	0.434 333	0.302 204	0.375 285	0.566 14	0.429 89	0.265 169	0.066 239
DCP 6	.099	1.368	1.518 357	0.351 26	0.181 303	0.107 207	0.075 115	0.053 22	0.026 297	0.012 211	0.010 283
DCP 7	.149	1.026	1.178 358	0.260 13	0.137 281	0.092 177	0.061 83	0.043 354	0.025 268	0.009 223	0.013 250
DCP 8	.200	0.837	0.975 1	0.220 14	0.114 279	0.074 171	0.051 78	0.035 351	0.017 265	0.010 213	0.014 241
DCP 9	.250	0.752	0.844 1	0.218 5	0.106 268	0.060 153	0.040 41	0.029 316	0.009 246	0.018 252	0.012 204
DCP10	.300	0.671	0.712 2	0.187 1	0.088 257	0.056 134	0.039 25	0.024 298	0.006 209	0.015 257	0.008 194
DCP11	.399	0.542	0.562 7	0.144 7	0.064 253	0.047 122	0.039 11	0.024 270	0.013 178	0.006 278	0.003 257
DCP12	.501	0.399	0.423 10	0.117 11	0.049 251	0.033 109	0.020 352	0.016 251	0.008 131	0.013 247	0.003 111
DCP13	.600	0.322	0.300 14	0.100 17	0.036 255	0.029 97	0.025 327	0.016 226	0.004 111	0.012 235	0.007 156
DCP14	.701	0.318	0.176 25	0.093 28	0.027 245	0.031 81	0.024 322	0.017 205	0.006 79	0.010 228	0.004 72
DCP15	.800	0.158	0.116 27	0.045 12	0.020 206	0.024 68	0.019 312	0.013 190	0.001 110	0.009 202	0.002 38
DCP16	.900	-0.050	0.076 17	0.030 291	0.026 165	0.018 54	0.008 336	0.006 153	0.002 91	0.008 264	0.005 327
DCP17	.969	-0.048	0.005 52	0.018 273	0.019 163	0.008 68	0.010 255	0.002 193	0.005 178	0.003 237	0.004 332

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.97	0.088	0.394	7.83	0.0	7.66	12157.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
132.8 (435.8)	47018. (982.0)	0.64E 07	-0.096	1.380	14.49	-0.00100	1.069	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALP A		7.457	7.834 0	0.577 2	0.110 330	0.026 316	0.049 301	0.057 148	0.037 324	0.027 244	0.007 278
CN		0.706	0.468 13	0.201 28	0.065 303	0.021 270	0.016 216	0.018 70	0.011 16	0.005 200	0.006 233
CM		-0.011	0.020 237	0.023 116	0.019 15	0.008 306	0.008 300	0.005 221	0.004 150	0.002 104	0.002 23
DCP 1	.010	3.033	2.653 347	1.172 76	0.679 25	0.302 342	0.236 323	0.149 276	0.095 271	0.083 275	0.104 222
DCP 2	.020	2.462	2.130 356	0.934 60	0.381 16	0.225 345	0.167 300	0.080 256	0.086 270	0.066 226	0.072 185
DCP 3	.030	2.276	1.688 354	0.875 69	0.462 24	0.312 336	0.222 282	0.135 224	0.059 208	0.048 173	0.054 135
DCP 4	.049	2.141	1.413 0	0.415 55	0.381 351	0.169 291	0.069 234	0.022 178	0.034 277	0.023 181	0.025 127
DCP 5	.074	2.191	0.563 22	0.297 47	0.469 323	0.269 277	0.254 308	0.289 30	0.245 103	0.190 171	0.061 236
DCP 6	.099	1.674	0.918 6	0.016 47	0.261 333	0.095 268	0.039 240	0.031 200	0.015 210	0.026 111	0.019 61
DCP 7	.149	1.283	0.799 11	0.468 33	0.203 313	0.066 253	0.041 229	0.039 169	0.016 87	0.021 81	0.021 30
DCP 8	.200	1.076	0.721 13	0.363 31	0.135 309	0.047 262	0.045 230	0.039 158	0.012 53	0.015 101	0.020 41
DCP 9	.250	0.948	0.679 13	0.309 18	0.119 286	0.043 237	0.048 198	0.045 125	0.029 39	0.015 51	0.023 337
DCP 10	.300	0.843	0.591 14	0.263 12	0.105 276	0.041 226	0.049 183	0.047 110	0.032 26	0.014 10	0.021 315
DCP 11	.399	0.704	0.517 18	0.206 8	0.083 259	0.029 207	0.044 167	0.039 89	0.029 24	0.013 1	0.024 292
DCP 12	.501	0.533	0.408 21	0.154 2	0.059 243	0.016 179	0.020 155	0.031 64	0.024 352	0.009 327	0.020 255
DCP 13	.600	0.425	0.307 27	0.124 1	0.052 228	0.014 110	0.019 133	0.027 49	0.021 341	0.015 260	0.018 210
DCP 14	.701	0.388	0.197 36	0.099 358	0.051 204	0.025 88	0.011 125	0.024 37	0.017 317	0.009 244	0.014 198
DCP 15	.800	0.219	0.167 32	0.070 326	0.053 191	0.020 101	0.018 108	0.024 15	0.016 317	0.011 243	0.012 173
DCP 16	.900	-0.015	0.117 19	0.057 289	0.031 196	0.015 151	0.021 97	0.018 1	0.008 297	0.011 231	0.015 163
DCP 17	.969	-0.039	0.039 13	0.038 279	0.013 211	0.009 177	0.009 128	0.009 24	0.003 307	0.008 241	0.008 137

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.64	0.087	0.394	7.75	0.0	9.97	12157.5	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
132.6 (435.0)	46947. (980.5)	0.64E 07	-0.160	1.517	15.66	-0.00130	1.386	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		9.965	7.749 0	0.587 3	0.052 323	0.066 36	0.071 353	0.103 299	0.120 158	0.016 51	0.017 319
CN		0.862	3.375 31	0.199 31	0.049 6	0.042 304	0.017 261	0.011 256	0.028 132	0.011 71	0.004 19
CM		-0.024	0.052 216	0.034 120	0.012 67	0.016 55	0.010 352	0.011 340	0.006 278	0.006 210	0.003 197
DCP 1	.010	3.627	1.313 343	1.373 85	0.455 52	0.266 85	0.293 53	0.173 20	0.119 27	0.026 346	0.056 37
DCP 2	.020	2.862	0.957 357	1.019 62	0.421 72	0.263 52	0.211 38	0.183 355	0.058 337	0.040 318	0.043 335
DCP 3	.030	2.598	0.652 352	1.013 87	0.475 62	0.247 31	0.150 21	0.141 355	0.077 331	0.054 297	0.059 307
DCP 4	.049	2.399	0.577 19	0.932 67	0.281 31	0.129 14	0.064 6	0.069 326	0.038 258	0.034 207	0.006 3
DCP 5	.074	2.444	0.447 117	0.323 44	0.347 356	0.066 354	0.313 308	0.365 6	0.274 100	0.231 177	0.121 249
DCP 6	.099	1.889	0.529 37	0.636 51	0.117 21	0.113 13	0.068 325	0.060 309	0.038 233	0.024 218	0.016 251
DCP 7	.149	1.501	0.608 33	0.467 35	0.073 19	0.109 353	0.070 301	0.066 283	0.053 204	0.020 200	0.022 204
DCP 8	.200	1.266	0.582 33	0.353 33	0.067 19	0.096 341	0.050 291	0.055 260	0.049 201	0.022 209	0.022 177
DCP 9	.250	1.119	0.555 30	0.298 25	0.080 9	0.103 319	0.054 261	0.054 253	0.057 182	0.014 120	0.022 131
DCP 10	.300	1.001	0.481 30	0.250 21	0.082 0	0.106 308	0.059 251	0.061 250	0.060 161	0.024 109	0.027 103
DCP 11	.399	0.847	0.481 32	0.207 14	0.056 350	0.085 297	0.047 238	0.047 219	0.051 157	0.029 86	0.022 91
DCP 12	.501	0.663	0.419 32	0.167 2	0.039 323	0.068 272	0.033 211	0.043 199	0.044 131	0.027 68	0.021 51
DCP 13	.600	0.538	0.354 35	0.142 350	0.029 291	0.060 257	0.034 187	0.035 175	0.038 113	0.033 42	0.018 13
DCP 14	.701	0.478	0.268 41	0.122 333	0.033 236	0.053 232	0.039 155	0.032 140	0.039 87	0.035 21	0.020 348
DCP 15	.800	0.293	0.231 33	0.107 317	0.038 249	0.056 223	0.038 151	0.034 130	0.030 71	0.028 17	0.012 343
DCP 16	.900	0.031	0.173 21	0.075 303	0.033 263	0.044 215	0.026 158	0.028 127	0.017 52	0.027 16	0.008 321
DCP 17	.969	-0.030	0.060 14	0.035 305	0.016 282	0.020 237	0.009 206	0.012 147	0.008 85	0.020 39	0.005 307

249

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	0.0	45.39	0.172	0.397	8.46	0.0	-0.01	12159.1	20

	V	Q	RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	134.5	48010.	0.65E 07	-0.073	0.790	8.63	-0.00087	0.955	0.0
	(441.2)	(1002.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		-0.008	8.462 0	0.733 356	0.200 307	0.050 209	0.020 182	0.059 82	0.016 131	0.016 230	0.009 148
CN		0.133	0.682 359	0.043 33	0.009 330	0.010 225	0.002 285	0.002 169	0.001 213	0.003 197	0.003 165
CM		-0.017	0.039 296	0.009 305	0.002 305	0.003 10	0.001 17	0.001 3	0.001 96	0.001 51	0.000 54
DCP 1	.010	-0.525	4.501 345	0.253 281	3.546 292	0.469 358	0.316 60	0.168 121	0.066 153	0.041 150	0.035 181
DCP 2	.020	-0.294	3.549 350	0.190 347	3.111 291	0.071 305	0.057 8	0.043 113	0.069 191	0.034 285	0.037 8
DCP 3	.030	-0.085	3.162 349	0.236 12	0.004 140	0.038 243	0.022 43	0.049 156	0.049 215	0.025 296	0.004 321
DCP 4	.049	0.197	2.545 350	0.175 3	3.013 144	0.067 215	0.054 276	0.037 346	0.025 72	0.017 137	0.011 184
DCP 5	.074	0.303	2.064 350	0.156 6	0.016 44	0.050 199	0.047 258	0.036 325	0.029 40	0.026 102	0.024 154
DCP 6	.099	0.379	1.741 351	0.137 9	0.015 9	0.034 197	0.026 269	0.018 322	0.012 55	0.020 150	0.014 199
DCP 7	.149	0.269	1.280 353	0.093 9	0.013 351	0.014 205	0.016 243	0.013 338	0.007 357	0.007 62	0.014 167
DCP 8	.230	0.216	1.034 358	0.079 20	0.026 358	0.016 165	0.008 211	0.013 257	0.014 308	0.008 357	0.014 69
DCP 9	.250	0.195	0.902 357	0.069 21	0.017 11	0.007 190	0.010 192	0.012 174	0.009 227	0.006 238	0.003 293
DCP10	.300	0.201	0.751 359	0.052 27	0.019 330	0.006 254	0.005 317	0.004 97	0.007 143	0.006 229	0.004 227
DCP11	.399	0.180	0.602 9	0.049 51	0.013 20	0.016 229	0.002 236	0.002 208	0.003 187	0.005 245	0.001 178
DCP12	.531	0.133	0.459 14	0.037 66	0.010 41	0.010 229	0.001 287	0.006 208	0.005 235	0.003 238	0.006 120
DCP13	.600	0.148	0.348 20	0.036 77	0.007 344	0.010 193	0.002 223	0.009 192	0.004 289	0.009 214	0.002 82
DCP14	.701	0.208	0.246 26	0.036 84	0.007 84	0.013 102	0.002 102	0.004 221	0.007 229	0.001 148	0.002 203
DCP15	.803	0.395	0.152 43	0.029 104	0.006 135	0.011 183	0.000 90	0.004 90	0.004 61	0.004 128	0.002 217
DCP16	.900	-0.083	0.077 79	0.034 147	0.012 193	0.015 205	0.006 222	0.001 183	0.005 289	0.002 199	0.002 257
DCP17	.969	-0.041	0.043 151	0.014 153	0.009 186	0.013 218	0.002 174	0.007 98	0.003 72	0.009 253	0.005 205

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	0.0	45.07	0.172	0.395	8.44	0.0	2.44	12159.2	20

	V	Q	RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	133.5	47464.	0.64E 07	-0.056	1.045	11.06	-0.00061	0.888	0.0
	(437.9)	(991.3)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.440	8.442 0	0.757 356	0.199 309	0.046 102	0.005 47	0.021 58	0.018 212	0.011 250	0.006 196
CN		0.370	0.683 358	0.062 20	0.014 345	0.016 135	0.003 214	0.001 196	0.001 276	0.003 185	0.001 148
CM		-0.009	0.037 297	0.007 271	0.001 253	0.004 313	0.000 46	0.001 2	0.001 220	0.001 0	0.001 347
DCP 1	.010	1.079	5.234 343	0.422 342	0.161 126	0.081 121	0.040 143	0.047 20	0.044 271	0.020 217	0.002 231
DCP 2	.020	0.901	3.590 349	0.281 359	0.062 325	0.040 113	0.028 357	0.045 253	0.053 168	0.042 56	0.040 328
DCP 3	.030	1.021	3.039 348	3.219 356	0.092 325	0.019 203	0.017 181	0.010 60	0.012 279	0.005 227	0.003 309
DCP 4	.049	1.088	2.513 349	0.181 352	3.072 323	0.023 181	0.013 176	0.004 63	0.005 238	0.009 210	0.004 210
DCP 5	.074	1.026	2.029 349	0.155 357	0.052 321	0.013 174	0.007 157	0.005 29	0.002 245	0.009 165	0.002 111
DCP 6	.099	0.987	1.701 351	0.140 4	0.045 324	0.014 134	0.004 257	0.006 321	0.002 177	0.008 183	0.005 179
DCP 7	.149	0.720	1.265 352	0.107 4	0.010 343	0.015 153	0.004 95	0.005 119	0.003 311	0.010 142	0.002 49
DCP 8	.200	0.577	1.026 358	0.093 16	0.027 336	0.013 143	0.005 257	0.003 182	0.002 85	0.007 293	0.004 205
DCP 9	.250	0.501	3.889 356	0.084 16	0.019 343	0.016 101	0.004 239	0.001 171	0.011 232	0.003 288	0.002 182
DCP10	.300	0.457	0.749 356	0.077 17	0.019 334	0.011 126	0.007 195	0.002 252	0.003 279	0.003 162	0.004 59
DCP11	.399	0.381	0.599 8	0.065 39	0.018 0	0.018 129	0.006 235	0.004 208	0.004 265	0.003 244	0.004 42
DCP12	.501	0.285	0.458 12	0.051 46	0.012 1	0.016 123	0.003 264	0.005 237	0.006 332	0.002 164	0.001 97
DCP13	.600	0.256	0.344 18	0.046 47	0.012 19	0.015 147	0.005 294	0.004 88	0.003 136	0.006 198	0.001 29
DCP14	.701	0.260	3.233 24	3.043 53	0.007 24	0.016 142	0.004 124	0.004 168	0.005 38	0.002 186	0.002 186
DCP15	.800	0.132	0.147 38	0.030 69	0.005 20	0.019 133	0.002 303	0.005 216	0.003 88	0.006 139	0.003 1
DCP16	.900	-0.085	0.056 54	0.010 77	0.003 156	0.022 132	0.003 191	0.001 399	0.004 49	0.004 277	0.006
DCP17	.969	-0.057	0.033 158	0.008 10	3.005 177	0.016 134	0.003 193	0.006 150	0.003 290	0.006 133	0.009

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	45.05	0.173	0.394	8.41	0.0	4.99	12159.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
132.6	47143.	0.64E 07	-0.344	1.271	13.28	-0.00087	0.952	0.0
(435.9)	(984.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.994	8.414 0	0.729 0	0.199 294	0.096 4	0.043 106	0.036 91	0.010 101	0.012 164	0.010 99
CN		0.554	0.629 8	0.118 347	0.009 198	0.026 10	0.016 212	0.002 340	0.010 26	0.006 276	0.011 197
CM		-0.003	0.039 285	0.004 56	0.014 304	0.018 157	0.003 59	0.002 267	0.001 315	0.001 113	0.001 7
DCP 1	.010	2.066	3.740 348	0.911 35	0.681 326	0.525 229	0.270 140	0.028 8	0.096 132	0.119 42	0.063 302
DCP 2	.020	1.778	3.094 355	0.666 24	0.398 317	0.286 225	0.171 158	0.105 95	0.097 46	0.068 351	0.063 296
DCP 3	.030	1.814	2.720 354	0.502 13	0.286 307	0.199 213	0.154 137	0.118 59	0.095 356	0.078 288	0.070 217
DCP 4	.044	1.714	2.216 356	0.448 9	0.228 293	0.126 181	0.051 82	0.009 324	0.034 57	0.057 325	0.067 236
DCP 5	.074	1.742	1.361 356	0.597 31	0.411 345	0.418 111	0.241 168	0.234 285	0.178 19	0.043 108	0.130 200
DCP 6	.099	1.442	1.565 359	0.323 356	0.127 251	0.092 131	0.044 16	0.008 274	0.035 7	0.061 268	0.067 178
DCP 7	.149	1.093	1.234 1	0.241 338	0.098 213	0.084 98	0.046 336	0.013 253	0.025 298	0.036 216	0.038 129
DCP 8	.200	0.841	1.025 4	0.183 348	0.075 197	0.070 79	0.030 321	0.002 323	0.023 304	0.038 216	0.035 119
DCP 9	.250	0.776	0.895 4	0.146 328	0.079 162	0.068 26	0.037 284	0.009 162	0.008 283	0.019 165	0.020 67
DCP10	.300	0.686	0.759 6	0.114 326	0.065 146	0.066 12	0.030 269	0.013 193	0.009 173	0.017 90	0.018 323
DCP11	.399	0.560	0.638 16	0.085 335	0.065 145	0.071 9	0.034 273	0.009 177	0.007 135	0.002 152	0.007 304
DCP12	.501	0.407	0.467 23	0.073 343	0.051 136	0.063 353	0.026 227	0.013 91	0.007 88	0.010 355	0.010 260
DCP13	.600	0.325	0.347 33	0.063 359	0.037 137	0.065 345	0.023 219	0.010 96	0.005 106	0.009 339	0.015 245
DCP14	.701	0.310	0.244 48	0.065 3	0.028 128	0.057 333	0.023 204	0.012 54	0.007 55	0.010 297	0.015 195
DCP15	.800	0.153	0.168 53	0.030 339	0.037 117	0.059 332	0.020 202	0.009 58	0.008 55	0.012 283	0.015 177
DCP16	.900	-0.067	0.077 48	0.023 263	0.032 75	0.044 307	0.013 103	0.003 324	0.008 5	0.006 231	0.007 120
DCP17	.969	-0.358	0.018 117	0.019 263	0.012 100	0.038 333	0.006 146	0.005 343	0.006 79	0.010 292	0.009 185

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	45.11	0.174	0.392	8.30	0.0	7.49	12159.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
132.3	46884.	0.64E 07	-0.148	1.545	16.01	-0.00069	0.750	0.0
(434.2)	(979.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.494	8.303 0	0.794 5	0.272 301	0.082 90	0.043 62	0.015 100	0.017 100	0.036 194	0.009 219
CN		0.718	0.625 21	0.181 342	0.033 217	0.020 157	0.021 346	0.014 293	0.010 194	0.016 180	0.014 47
CM		-0.018	0.047 231	0.038 69	0.030 326	0.011 246	0.011 172	0.007 62	0.005 43	0.005 285	0.006 188
DCP 1	.010	2.750	2.610 354	1.120 57	0.727 0	0.400 290	0.121 287	0.158 267	0.112 215	0.072 185	0.092 184
DCP 2	.020	2.227	2.060 4	1.005 51	0.521 353	0.286 300	0.149 280	0.137 242	0.104 201	0.114 172	0.084 130
DCP 3	.030	2.034	1.621 8	1.028 49	0.558 341	0.289 275	0.092 245	0.105 236	0.125 181	0.119 129	0.075 72
DCP 4	.044	2.089	1.667 9	0.732 30	0.313 314	0.087 257	0.061 299	0.090 211	0.058 117	0.006 284	0.042 178
DCP 5	.074	2.108	0.889 15	0.743 348	0.411 357	0.315 168	0.314 264	0.208 15	0.252 106	0.154 222	0.056 31
DCP 6	.099	1.708	1.243 15	0.541 14	0.210 288	0.052 233	0.040 252	0.071 167	0.050 75	0.013 228	0.031 86
DCP 7	.149	1.330	1.086 17	0.418 356	0.174 268	0.060 214	0.056 181	0.068 95	0.048 17	0.012 218	0.036 19
DCP 8	.200	1.109	0.977 22	0.374 354	0.165 260	0.068 207	0.064 157	0.069 93	0.042 23	0.011 313	0.027 344
DCP 9	.250	0.976	0.897 20	0.317 336	0.136 226	0.064 174	0.062 110	0.067 31	0.044 306	0.026 239	0.013 267
DCP10	.300	0.875	0.802 21	0.272 328	0.127 211	0.073 151	0.074 79	0.061 351	0.028 265	0.023 256	0.027 203
DCP11	.399	0.743	0.711 27	0.222 323	0.115 203	0.069 155	0.061 70	0.066 343	0.036 271	0.031 260	0.039 179
DCP12	.501	0.565	0.579 29	0.169 305	0.112 173	0.060 107	0.075 26	0.061 294	0.034 239	0.044 193	0.046 93
DCP13	.600	0.458	0.471 34	0.146 293	0.118 156	0.055 84	0.071 359	0.054 263	0.027 215	0.039 166	0.053 59
DCP14	.701	0.413	0.345 39	0.121 275	0.114 135	0.051 41	0.056 328	0.042 227	0.020 189	0.037 129	0.053 20
DCP15	.800	0.238	0.252 34	0.108 250	0.103 120	0.041 26	0.047 310	0.030 212	0.021 186	0.033 94	0.039 344
DCP16	.900	-0.012	0.145 24	0.089 243	0.059 124	0.018 24	0.045 294	0.027 187	0.018 150	0.026 48	0.029 300
DCP17	.969	-0.042	0.037 21	0.048 257	0.021 144	0.007 104	0.025 305	0.020 188	0.004 203	0.014 51	0.010 344

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	A	MACH NO	DEL. ALPHA	DEL. H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.49	0.175	0.392	6.25	0.0	9.96	12159.5	20

V	U	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TOR	EXT DAMP
132.0	46741.	0.64E 07	-0.237	1.615	16.13	-3.00001	3.664	0.0
(433.1)	(976.2)							

HARMONIC ANALYSIS

DATA TYPE	XYC	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPH		9.903	0.269 0	0.769 0	0.274 313	0.189 196	0.007 117	0.037 44	0.036 158	0.056 311	0.013 28
CN		0.895	0.626 33	0.177 352	0.067 303	0.352 293	0.320 118	0.020 50	0.005 353	0.017 311	0.011 234
CM		-0.016	0.063 209	0.062 83	0.033 6	0.025 336	0.015 229	0.003 131	0.005 146	0.005 125	0.000 19
DCP 1	.012	3.219	1.297 353	1.057 76	0.706 19	0.379 351	0.192 341	0.133 30	0.195 345	0.150 263	0.032 61
DCP 2	.030	2.674	1.004 15	1.300 75	0.600 24	0.389 348	0.117 336	0.126 0	0.161 317	0.155 271	0.052 225
DCP 3	.050	2.496	0.877 21	0.161 68	0.469 13	0.241 345	0.191 356	0.129 324	0.133 784	0.113 273	0.093 240
DCP 4	.064	2.490	1.169 25	0.613 44	0.199 345	0.105 2	0.088 319	0.084 336	0.055 286	0.047 256	0.031 253
DCP 5	.074	1.941	0.717 38	0.623 14	0.246 26	0.094 241	0.107 200	0.110 25	0.179 132	0.167 236	0.129 24
DCP 6	.099	2.019	1.031 31	0.555 28	0.149 344	0.196 332	0.091 247	0.017 323	0.078 239	0.039 187	0.023 189
DCP 7	.149	1.593	0.976 29	0.429 15	0.174 33	0.197 295	0.114 233	0.221 172	0.069 193	0.037 109	0.025 86
DCP 8	.200	1.335	0.696 35	0.194 19	0.221 335	0.216 284	0.140 201	0.069 165	0.055 175	0.034 129	0.046 109
DCP 9	.250	1.145	0.052 31	0.324 4	0.198 319	0.204 265	0.136 166	0.054 127	0.047 129	0.043 81	0.059 48
DCP10	.300	1.067	0.764 30	0.276 354	0.173 309	0.183 237	0.136 146	0.062 107	0.040 67	0.041 42	0.057 5
DCP11	.399	0.973	0.763 35	0.249 341	0.132 295	0.157 232	0.129 152	0.068 116	0.050 85	0.068 39	0.068 345
DCP12	.501	0.763	0.642 32	0.223 316	0.135 256	0.174 191	0.137 116	0.055 85	0.068 32	0.078 352	0.078 281
DCP13	.601	0.619	0.627 45	0.207 295	0.116 211	0.120 153	0.110 80	0.047 35	0.054 357	0.073 318	0.092 238
DCP14	.701	0.546	0.455 33	0.238 274	0.139 176	0.133 117	0.130 37	0.054 337	0.051 300	0.052 261	0.077 189
DCP15	.800	0.351	0.344 24	0.227 263	0.142 168	0.140 99	0.137 11	0.054 299	0.050 253	0.028 212	0.045 166
DCP16	.900	0.058	0.242 11	0.145 242	0.080 161	0.086 69	0.067 327	0.075 245	0.010 262	0.024 233	0.047 140
DCP17	.960	0.015	0.048 6	0.079 253	0.036 156	0.019 65	0.129 333	0.01 223	0.033 303	0.018 264	0.022 161

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	A	MACH NO	DEL. ALPHA	DEL. H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	72.47	0.089	0.496	7.90	0.0	-0.00	12161.1	20

V	U	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TOR	EXT DAMP
166.5	74042.	0.80E 07	-0.057	0.925	7.85	-3.00086	1.174	0.0
(546.3)	(1546.4)							

HARMONIC ANALYSIS

DATA TYPE	XYC	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		-0.001	1.001 0	0.007 355	0.134 318	0.043 322	0.056 333	0.019 309	0.023 285	0.045 295	0.032 275
CN		0.162	0.756 357	0.072 316	0.026 271	0.014 289	0.010 317	0.005 329	0.001 73	0.005 319	0.004 262
CM		-0.016	0.027 321	0.005 319	0.002 45	0.003 36	0.002 66	0.002 102	0.001 144	0.001 189	0.000 29
DCP 1	.013	-0.056	6.370 351	0.808 262	0.476 311	0.201 28	0.048 347	0.078 33	0.025 252	0.111 298	0.087 25
DCP 2	.030	-0.032	3.838 353	0.475 276	0.151 284	0.174 49	0.049 13	0.065 292	0.023 245	0.056 312	0.017 29
DCP 3	.050	3.054	3.482 353	0.232 297	0.018 232	0.116 55	0.056 393	0.090 290	0.052 142	0.009 45	0.047 290
DCP 4	.064	0.245	2.911 353	0.114 340	0.091 300	0.067 330	0.087 123	0.037 173	0.027 293	0.012 223	0.030 263
DCP 5	.074	0.558	2.042 356	0.254 244	0.273 284	0.196 334	0.130 32	0.107 74	0.088 118	0.061 185	0.058 243
DCP 6	.099	0.384	2.306 353	0.139 27	0.049 177	0.073 245	0.038 311	0.012 17	0.001 17	0.012 305	0.005 320
DCP 7	.149	0.274	1.487 354	0.043 26	0.038 170	0.059 240	0.036 299	0.021 5	0.007 63	0.010 339	0.004 211
DCP 8	.200	0.226	1.189 357	0.062 24	0.022 203	0.039 254	0.033 305	0.017 359	0.011 84	0.005 286	0.007 252
DCP 9	.250	0.201	1.030 359	0.064 23	0.011 213	0.032 239	0.026 286	0.013 328	0.007 344	0.007 349	0.002 133
DCP10	.300	0.210	0.646 356	0.044 16	0.012 262	0.020 241	0.018 286	0.009 326	0.003 32	0.002 333	0.005 262
DCP11	.399	0.191	0.653 1	0.023 354	0.022 293	0.008 279	0.005 290	0.007 268	0.006 275	0.011 349	0.005 335
DCP12	.501	0.156	0.490 3	0.009 358	0.018 286	0.010 272	0.009 276	0.008 310	0.003 327	0.006 347	0.003 269
DCP13	.600	0.164	0.357 8	0.005 246	0.017 282	0.008 278	0.006 302	0.007 286	0.003 327	0.006 4	0.002 301
DCP14	.701	0.202	0.242 0	0.008 145	0.016 272	0.007 258	0.007 280	0.005 294	0.002 85	0.005 342	0.004 281
DCP15	.800	0.140	0.123 21	0.016 191	0.018 273	0.006 245	0.005 252	0.005 281	0.002 343	0.005 333	0.003 275
DCP16	.900	-0.073	3.017 93	0.091 201	0.019 238	0.007 260	0.005 272	0.006 294	0.005 321	0.006 354	0.000 329
DCP17	.969	-0.046	0.044 163	0.014 189	0.011 188	0.007 242	0.006 271	0.001 201	0.002 94	0.001 64	0.003 171

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

		TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.-H	ALPHA.0	TEST POINT	CYCLES ANALYSED
		3.0	22.03	0.068	0.493	7.91	0.0	2.46	12161.2	20
				RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
		165.3	73305.	0.80E 07	-0.035	1.195	10.46	-0.00088	1.165	0.0
		(542.4)	(1531.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.460	7.937 0	0.605 394	0.115 317	0.044 323	0.026 298	0.045 353	0.034 210	0.030 268	0.029 282
CN		3.377	0.743 357	0.084 3	0.067 289	0.006 176	0.012 13	0.010 308	0.002 174	0.002 13	0.001 239
CM		-0.005	0.028 326	0.007 267	0.002 86	0.001 186	0.003 186	0.002 42	0.001 356	0.002 185	0.001 161
DCP 1	.010	0.911	4.839 353	0.403 11	0.426 322	0.193 317	0.231 114	0.072 149	0.054 252	0.010 293	0.035 219
DCP 2	.020	1.049	4.169 353	0.380 335	0.145 304	0.133 281	0.097 168	0.071 82	0.048 275	0.024 312	0.044 4
DCP 3	.030	1.160	3.778 353	0.191 331	0.089 209	0.089 248	0.076 229	0.073 67	0.044 348	0.022 275	0.040 353
DCP 4	.049	1.199	3.054 353	0.365 354	0.134 291	0.193 232	0.116 199	0.127 59	0.120 359	0.084 244	0.044 146
DCP 5	.074	1.290	1.818 356	0.298 295	0.421 302	0.037 83	0.072 85	0.122 336	0.088 51	0.083 137	0.095 207
DCP 6	.099	0.971	1.872 353	0.246 15	0.097 295	0.065 188	0.036 31	0.074 330	0.026 266	0.024 183	0.015 179
DCP 7	.149	0.713	1.364 354	0.156 7	0.068 292	0.013 163	0.027 21	0.030 297	0.015 216	0.005 196	0.003 207
DCP 8	.200	0.597	1.168 357	0.130 351	0.055 253	0.035 101	0.045 11	0.036 206	0.024 205	0.006 94	0.005 31
DCP 9	.250	0.532	1.028 356	0.106 340	0.046 218	0.051 77	0.055 348	0.041 264	0.029 172	0.019 58	0.016 334
DCP10	.300	0.469	0.839 356	0.094 353	0.034 239	0.033 83	0.039 344	0.026 261	0.016 159	0.017 34	0.006 317
DCP11	.399	0.371	0.641 0	0.079 16	0.030 288	0.007 100	0.020 351	0.012 259	0.007 165	0.009 6	0.006 253
DCP12	.501	0.277	0.472 2	0.068 26	0.031 297	0.002 123	0.012 353	0.007 247	0.007 147	0.008 8	0.003 284
DCP13	.600	0.236	0.355 6	0.065 16	0.039 301	0.008 227	0.009 66	0.005 292	0.006 186	0.005 331	0.002 305
DCP14	.701	0.206	0.199 10	0.066 50	0.038 306	0.011 211	0.009 19	0.003 283	0.002 174	0.008 352	0.003 286
DCP15	.800	0.116	0.107 20	0.041 54	0.028 296	0.005 201	0.011 9	0.004 266	0.003 159	0.006 354	0.002 251
DCP16	.900	-0.082	0.036 44	0.010 281	0.015 241	0.007 25	0.009 336	0.004 204	0.006 25	0.005 3	0.003 107
DCP17	.969	-0.054	0.026 170	0.017 245	0.006 200	0.004 84	0.006 296	0.002 197	0.001 140	0.003 33	0.001 17

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

		TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.-H	ALPHA.0	TEST POINT	CYCLES ANALYSED
			22.04		0.492	7.86	0.0	4.85	12161.3	20
				RN	CM(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
		165.3	73041.	0.80E 07	-0.044	1.750	9.97	-0.00091	1.157	0.0
		(54.9)	(1525.5)							

HARMONIC ANALYSIS

(Lower table data rows too faded to transcribe reliably.)

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.64	0.070	0.491	7.82	0.0	7.45	12161.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
164.3	72778.	0.80E 07	-0.098	1.328	12.94	-0.00114	1.494	0.0
(539.2)	(1520.0)							

HARMONIC ANALYSES

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.453	7.817 0	0.676 2	0.174 338	0.076 3	0.122 343	0.103 298	0.076 199	0.011 143	0.045 300
CN		0.695	0.413 11	0.214 42	0.084 348	0.048 347	0.022 283	0.007 268	0.007 198	0.011 118	0.007 335
CM		-0.014	0.034 233	0.028 127	0.014 28	0.007 50	0.010 359	0.004 283	0.003 308	0.004 267	0.002 155
DCP 1	.010	2.578	2.079 341	1.497 76	0.575 24	0.275 20	0.239 334	0.112 299	0.066 286	0.033 313	0.004 271
DCP 2	.020	2.360	1.883 345	1.271 82	0.621 22	0.174 17	0.275 354	0.150 293	0.082 310	0.048 285	0.041 280
DCP 3	.030	2.355	1.786 346	1.000 83	0.552 75	0.126 0	0.234 11	0.174 303	0.074 310	0.072 275	0.038 281
DCP 4	.049	2.021	1.080 351	1.028 72	0.368 19	0.176 32	0.197 359	0.106 310	0.078 336	0.067 288	0.026 276
DCP 5	.074	2.145	0.280 48	0.254 80	0.558 332	0.428 15	0.171 25	0.071 1	0.013 71	0.070 207	0.086 229
DCP 6	.099	1.617	0.751 3	0.660 58	0.177 7	0.116 11	0.094 317	0.049 265	0.024 265	0.023 239	0.019 167
DCP 7	.149	1.265	0.710 4	0.462 45	0.127 349	0.094 355	0.083 292	0.035 240	0.013 235	0.011 201	0.006 113
DCP 8	.200	1.054	0.648 12	0.371 44	0.104 356	0.088 346	0.079 283	0.044 231	0.027 205	0.017 141	0.022 82
DCP 9	.250	0.958	0.628 11	0.310 33	0.097 344	0.086 320	0.067 253	0.034 206	0.028 173	0.040 115	0.028 36
DCP10	.300	0.850	0.553 12	0.252 27	0.067 341	0.069 318	0.052 244	0.017 205	0.022 182	0.031 111	0.019 23
DCP11	.399	0.691	0.464 18	0.205 26	0.039 328	0.048 328	0.041 247	0.010 203	0.020 188	0.033 116	0.020 16
DCP12	.501	0.535	0.375 21	0.164 17	0.027 297	0.035 316	0.036 222	0.011 121	0.015 185	0.027 106	0.015 6
DCP13	.600	0.430	0.294 27	0.140 10	0.030 255	0.017 312	0.027 202	0.012 90	0.007 147	0.017 80	0.015 317
DCP14	.701	0.398	0.196 37	0.109 1	0.036 212	0.007 340	0.023 181	0.015 70	0.005 154	0.015 74	0.013 300
DCP15	.800	0.223	0.174 33	0.091 288	0.036 221	0.015 253	0.030 173	0.017 89	0.010 88	0.011 63	0.009 302
DCP16	.900	-0.019	0.128 20	0.066 308	0.019 241	0.023 228	0.020 141	0.004 80	0.012 93	0.006 65	0.005 274
DCP17	.969	-0.048	0.038 23	0.037 294	0.009 271	0.017 248	0.010 150	0.004 67	0.003 59	0.007 154	0.003 318

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.31	0.139	0.494	8.41	0.0	-0.01	12163.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
166.0	73846.	0.80E 07	-0.071	0.853	8.36	-0.00082	1.106	0.0
(544.6)	(1542.3)							

HARMONIC ANALYSES

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		-0.006	8.410 0	0.746 354	0.192 306	0.014 15	0.009 176	0.013 24	0.030 217	0.013 284	0.008 314
CN		0.151	0.725 358	0.034 28	0.008 247	0.014 306	0.009 266	0.005 298	0.002 245	0.003 159	0.004 197
CM		-0.014	0.036 300	0.010 297	0.003 317	0.003 227	0.003 340	0.001 355	0.002 85	0.001 30	0.000 118
DCP 1	.010	-0.278	4.218 346	0.632 251	0.455 286	0.269 346	0.105 298	0.096 322	0.041 62	0.056 218	0.049 308
DCP 2	.020	-0.081	3.603 350	0.349 278	0.174 280	0.144 16	0.063 325	0.076 228	0.047 135	0.010 225	0.041 260
DCP 3	.030.	0.032	3.150 350	0.148 306	0.149 287	0.091 355	0.017 65	0.085 223	0.031 95	0.067 42	0.075 246
DCP 4	.049	0.236	2.064 350	0.136 357	0.066 252	0.089 305	0.044 60	0.021 105	0.018 228	0.028 155	0.038 167
DCP 5	.074	0.526	2.018 351	0.047 288	0.131 228	0.235 264	0.234 326	0.188 30	0.106 90	0.075 102	0.128 134
DCP 6	.099	0.372	1.985 350	0.187 23	0.041 130	0.061 229	0.041 265	0.019 301	0.006 177	0.011 223	0.013 270
DCP 7	.149	0.255	1.438 351	0.144 21	0.036 100	0.037 207	0.032 232	0.023 281	0.010 280	0.009 260	0.003 34
DCP 8	.200	0.214	1.139 357	0.099 26	0.017 82	0.023 235	0.028 245	0.020 282	0.011 295	0.002 308	0.007 7
DCP 9	.250	0.193	0.996 355	0.097 27	0.026 71	0.015 167	0.026 211	0.017 267	0.011 268	0.003 331	0.003 287
DCP10	.300	0.197	0.822 356	0.074 29	0.014 43	0.004 156	0.015 192	0.009 249	0.007 232	0.002 235	0.010 270
DCP11	.399	0.187	0.636 6	0.042 48	0.009 334	0.015 359	0.007 207	0.006 236	0.009 262	0.001 180	0.003 275
DCP12	.501	0.149	0.480 11	0.036 61	0.004 292	0.011 353	0.007 204	0.004 273	0.008 312	0.001 300	0.004 170
DCP13	.600	0.152	0.359 17	0.031 92	0.006 223	0.012 349	0.004 195	0.003 206	0.008 270	0.002 222	0.001 202
DCP14	.701	0.227	0.248 23	0.035 94	0.008 198	0.011 4	0.004 173	0.002 221	0.004 262	0.004 178	0.005 208
DCP15	.800	0.105	0.144 38	0.030 118	0.009 185	0.009 6	0.004 179	0.006 164	0.003 256	0.005 147	0.005 194
DCP16	.900	-0.074	0.073 88	0.031 155	0.014 177	0.012 11	0.004 166	0.003 170	0.007 247	0.006 180	0.003 218
DCP17	.969	-0.042	0.049 155	0.021 148	0.014 183	0.006 0	0.009 198	0.003 130	0.004 177	0.009 224	0.003 28

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.09	0.139	0.493	8.44	0.0	2.30	12163.2	20

V.	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
165.3	73444.	0.80E 07	-0.049	1.081	10.86	-0.00083	1.115	0.0
(542.3)	(1533.9)							

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.300	8.445 0	0.738 353	0.201 313	0.071 2	0.017 222	0.026 50	0.011 271	0.035 221	0.013 227
CN		0.563	0.709 357	0.064 356	0.009 266	0.020 22	0.010 259	0.005 56	0.007 297	0.004 216	0.002 70
CM		-0.005	0.040 303	0.006 255	0.003 48	0.008 226	0.001 57	0.001 263	0.001 116	0.001 215	0.000 19
DCP 1	.010	0.724	4.587 343	0.303 338	0.212 300	0.097 287	0.104 13	0.013 105	0.033 20	0.026 261	0.022 92
DCP 2	.020	1.006	3.969 349	0.313 309	0.028 278	0.071 269	0.022 123	0.028 344	0.008 101	0.017 260	0.049 211
DCP 3	.030	1.103	3.563 348	0.284 307	0.069 136	0.04 228	0.024 163	0.036 330	0.030 251	0.005 247	0.039 210
DCP 4	.049	1.226	3.004 349	0.283 312	0.053 171	0.029 180	0.029 184	0.032 327	0.047 256	0.003 162	0.006 265
DCP 5	.074	1.225	1.945 349	0.337 315	0.018 170	0.069 185	0.124 298	0.060 346	0.033 105	0.047 209	0.069 3
DCP 6	.099	0.951	1.767 351	0.187 357	0.061 276	0.017 96	0.022 358	0.034 247	0.019 190	0.009 345	0.005 351
DCP 7	.149	0.674	1.263 352	0.115 7	0.043 304	0.030 294	0.002 249	0.003 340	0.011 255	0.009 180	0.007 68
DCP 8	.200	0.572	1.089 357	0.062 344	0.021 74	0.058 334	0.026 230	0.018 105	0.017 313	0.008 243	0.002 152
DCP 9	.250	0.498	0.974 354	0.053 35	0.031 60	0.069 349	0.050 216	0.044 99	0.038 338	0.033 232	0.021 121
DCP10	.300	0.444	0.796 356	0.070 8	0.010 23	0.035 354	0.020 220	0.019 72	0.012 312	0.015 190	0.009 68
DCP11	.399	0.363	0.622 4	0.072 23	0.009 328	0.034 42	0.009 256	0.008 101	0.011 311	0.009 197	0.007 78
DCP12	.501	0.271	0.448 11	0.058 29	0.013 263	0.026 41	0.007 296	0.002 67	0.006 278	0.005 105	0.004 317
DCP13	.600	0.231	0.347 17	0.054 30	0.016 254	0.029 55	0.007 285	0.001 81	0.005 292	0.001 16	0.004 105
DCP14	.701	0.269	0.222 27	0.056 38	0.017 258	0.025 56	0.007 296	0.002 84	0.005 314	0.003 41	0.004 199
DCP15	.800	0.119	0.134 43	0.037 44	0.016 240	0.026 52	0.006 290	0.003 115	0.005 309	0.006 348	0.003 210
DCP16	.900	-0.087	0.058 71	0.009 259	0.014 198	0.033 33	0.009 221	0.004 10	0.007 269	0.001 335	0.005 249
DCP17	.969	-0.055	0.039 169	0.008 240	0.010 177	0.015 38	0.006 165	0.004 326	0.005 188	0.004 51	0.000 33

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.10	0.139	0.491	8.34	0.0	4.93	12163.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
164.7	73142.	0.80E 07	-0.088	1.297	13.34	-0.00086	0.891	0.0
(540.4)	(1527.6)							

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.932	8.343 0	0.804 3	0.339 312	0.158 42	0.036 304	0.020 354	0.029 91	0.050 195	0.026 200
CN		0.921	0.629 13	0.160 353	0.052 236	0.017 64	0.021 329	0.011 287	0.013 162	0.004 67	0.003 36
CM		-0.010	0.033 261	0.021 60	0.026 327	0.021 202	0.006 124	0.004 61	0.004 351	0.002 224	0.001 145
DCP 1	.010	1.496	3.459 348	1.023 38	0.635 334	0.354 223	0.130 134	0.066 289	0.025 185	0.030 101	0.027 292
DCP 2	.020	1.503	2.889 355	0.803 35	0.553 337	0.348 249	0.153 166	0.037 323	0.085 178	0.077 80	0.052 309
DCP 3	.030	1.529	2.483 356	0.712 32	0.445 328	0.251 253	0.147 191	0.056 127	0.033 115	0.056 80	0.049 342
DCP 4	.049	1.493	1.939 359	0.744 30	0.452 319	0.186 235	0.056 223	0.080 204	0.087 121	0.052 56	0.031 312
DCP 5	.074	1.661	1.165 5	0.521 1	0.351 306	0.301 226	0.207 308	0.119 33	0.153 104	0.078 22	0.085 54
DCP 6	.099	1.281	1.383 3	0.520 17	0.256 293	0.128 185	0.034 81	0.004 258	0.038 61	0.045 326	0.040 250
DCP 7	.149	0.993	1.158 5	0.384 356	0.185 260	0.120 154	0.041 51	0.018 28	0.034 349	0.050 262	0.038 179
DCP 8	.200	0.826	1.014 11	0.324 353	0.153 250	0.105 150	0.038 55	0.021 27	0.033 346	0.048 254	0.032 179
DCP 9	.250	0.735	0.922 8	0.279 337	0.147 214	0.099 94	0.061 6	0.030 312	0.023 275	0.041 213	0.029 137
DCP10	.300	0.659	0.785 9	0.230 331	0.120 199	0.082 76	0.050 350	0.025 293	0.019 240	0.027 177	0.016 101
DCP11	.399	0.541	0.646 18	0.184 337	0.107 199	0.073 73	0.042 5	0.030 321	0.036 241	0.032 161	0.025 75
DCP12	.501	0.404	0.505 22	0.140 330	0.094 179	0.077 53	0.043 335	0.029 279	0.039 201	0.029 117	0.025 37
DCP13	.600	0.322	0.383 29	0.104 331	0.081 165	0.072 50	0.034 309	0.020 255	0.032 174	0.029 42	0.023 330
DCP14	.701	0.325	0.262 39	0.075 327	0.074 145	0.077 10	0.030 272	0.013 225	0.029 156	0.027 34	0.016 292
DCP15	.800	0.164	0.188 40	0.057 295	0.069 139	0.068 1	0.021 267	0.010 221	0.021 138	0.019 7	0.009 250
DCP16	.900	-0.058	0.101 29	0.061 257	0.050 133	0.054 350	0.015 280	0.016 208	0.019 93	0.015 319	0.001 226
DCP17	.969	-0.053	0.012 58	0.041 258	0.029 142	0.037 356	0.010 296	0.011 216	0.009 102	0.006 357	0.003 230

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	45.39	0.141	0.490	8.27	0.0	7.30	12163.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
164.0	72543.	0.80E 07	-0.174	1.576	15.49	-0.00075	1.003	0.0
(538.2)	(1515.1)							

HARMONIC ANALYSIS

DATA TYPE	R/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.297	8.274 0	0.752 11	0.325 324	0.241 172	0.061 132	0.054 56	0.022 184	0.012 341	0.004 145
CN		0.674	0.559 24	0.224 2	0.056 278	0.046 203	0.030 131	0.025 37	0.013 320	0.009 286	0.004 155
CM		-0.021	0.052 231	0.039 98	0.025 0	0.017 340	0.017 267	0.011 184	0.008 121	0.004 51	0.003 11
DCP 1	.010	2.208	2.161 351	1.277 54	0.638 342	0.109 249	0.094 354	0.204 261	0.065 180	0.041 176	0.019 102
DCP 2	.020	2.088	1.958 2	1.073 56	0.580 354	0.194 282	0.043 347	0.113 268	0.042 157	0.073 288	0.077 195
DCP 3	.030	1.981	1.636 2	0.897 55	0.444 2	0.211 317	0.098 278	0.088 260	0.071 202	0.034 215	0.062 171
DCP 4	.049	1.886	1.297 10	0.885 48	0.332 343	0.093 348	0.115 316	0.094 255	0.053 202	0.022 205	0.036 192
DCP 5	.074	2.021	0.644 28	0.998 14	0.993 348	0.052 236	0.261 299	0.043 353	0.076 165	0.054 309	0.148 78
DCP 6	.099	1.562	0.988 18	0.621 34	0.206 319	0.067 309	0.070 268	0.060 187	0.026 108	0.007 207	0.031 126
DCP 7	.149	1.225	0.929 20	0.441 13	0.157 291	0.044 279	0.078 222	0.066 137	0.035 55	0.013 31	0.026 35
DCP 8	.200	1.020	0.852 25	0.398 12	0.137 291	0.062 261	0.082 202	0.059 123	0.023 50	0.019 61	0.022 21
DCP 9	.250	0.932	0.812 23	0.367 356	0.130 272	0.093 228	0.110 178	0.040 102	0.037 54	0.042 38	0.036 345
DCP10	.300	0.830	0.719 24	0.310 349	0.106 258	0.085 212	0.094 155	0.064 74	0.027 16	0.026 15	0.023 324
DCP11	.399	0.698	0.641 31	0.269 348	0.081 251	0.086 215	0.094 155	0.072 75	0.040 15	0.030 351	0.024 289
DCP12	.501	0.543	0.544 33	0.206 336	0.076 229	0.083 197	0.086 128	0.066 45	0.040 344	0.026 300	0.020 246
DCP13	.600	0.437	0.450 37	0.174 326	0.076 206	0.071 182	0.076 107	0.061 19	0.034 323	0.030 286	0.027 213
DCP14	.701	0.414	0.339 43	0.145 310	0.084 177	0.058 156	0.071 76	0.058 347	0.036 290	0.030 231	0.022 163
DCP15	.800	0.241	0.271 37	0.135 289	0.086 173	0.061 146	0.067 63	0.054 330	0.035 274	0.027 208	0.017 136
DCP16	.900	-0.015	0.163 26	0.099 273	0.051 176	0.060 144	0.054 43	0.036 314	0.026 253	0.020 181	0.014 117
DCP17	.949	-0.048	0.044 26	0.054 281	0.022 200	0.038 161	0.029 57	0.016 337	0.019 285	0.014 199	0.006 151

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.20	0.057	0.592	7.95	0.0	-0.02	12165.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
197.0	103168.	0.94E 07	-0.060	1.005	8.01	-0.00101	1.991	0.0
(646.4)	(2154.7)							

HARMONIC ANALYSIS

DATA TYPE	R/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		-0.023	7.951 0	0.738 353	0.167 322	0.074 319	0.063 323	0.026 315	0.061 301	0.026 4	0.035 255
CN		0.166	0.806 357	0.028 320	0.039 265	0.008 274	0.009 343	0.006 319	0.004 329	0.004 108	0.003 198
CM		-0.015	0.036 328	0.008 275	0.001 101	0.004 26	0.002 80	0.002 87	0.001 72	0.003 257	0.001 129
DCP 1	.010	-0.380	3.803 351	0.559 258	0.566 317	0.046 351	0.153 285	0.158 9	0.026 302	0.116 320	0.089 14
DCP 2	.020	-0.189	3.437 354	0.393 266	0.378 317	0.105 46	0.079 282	0.123 8	0.052 63	0.068 306	0.091 68
DCP 3	.030	-0.055	3.228 353	0.369 282	0.228 306	0.106 32	0.020 12	0.043 17	0.048 82	0.052 237	0.026 78
DCP 4	.049	0.255	2.981 353	0.073 329	0.160 307	0.068 16	0.054 101	0.040 221	0.027 114	0.046 231	0.001 113
DCP 5	.074	0.562	2.545 353	0.154 217	0.257 258	0.214 300	0.136 9	0.102 33	0.149 84	0.134 138	0.126 192
DCP 6	.099	0.588	2.560 353	0.126 302	0.049 243	0.066 283	0.099 122	0.036 165	0.017 212	0.007 98	0.032 263
DCP 7	.149	0.437	1.956 355	0.211 293	0.192 193	0.020 98	0.083 114	0.082 70	0.115 317	0.067 230	0.023 163
DCP 8	.200	0.228	1.300 357	0.081 3	0.086 216	0.023 118	0.057 7	0.021 247	0.016 260	0.024 267	0.017 144
DCP 9	.250	0.206	1.144 355	0.075 358	0.058 180	0.023 89	0.058 325	0.047 251	0.010 226	0.025 46	0.005 112
DCP10	.300	0.196	0.915 356	0.070 13	0.028 189	0.014 93	0.056 313	0.037 249	0.015 147	0.024 22	0.007 290
DCP11	.399	0.173	0.667 1	0.051 41	0.028 307	0.022 252	0.017 291	0.015 278	0.006 283	0.013 64	0.003 311
DCP12	.501	0.145	0.487 3	0.032 43	0.032 300	0.019 245	0.011 287	0.007 302	0.005 281	0.007 57	0.003 301
DCP13	.600	0.157	0.343 7	0.019 53	0.031 303	0.015 233	0.007 265	0.008 310	0.003 248	0.009 90	0.005 314
DCP14	.701	0.234	0.209 13	0.027 82	0.031 300	0.016 232	0.003 230	0.007 320	0.004 301	0.010 98	0.001 189
DCP15	.800	0.106	0.099 31	0.012 133	0.023 282	0.013 222	0.005 266	0.007 324	0.003 302	0.013 93	0.002 216
DCP16	.900	-0.061	0.049 118	0.027 205	0.015 237	0.015 198	0.005 253	0.004 300	0.005 230	0.010 84	0.003 274
DCP17	.949	-0.043	0.050 144	0.011 181	0.015 179	0.006 191	0.007 242	0.005 251	0.004 293	0.010 97	0.001 220

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	22.81	0.059	0.590	7.94	0.0	2.45	12165.2	20

	V	Q	RN	CH(MIN)	CH(MAX)	ALPHA.HMAX	AERO DAMP	TDR	EXT DAMP
	196.1	102555.	0.94E 07	-0.045	1.153	9.92	-0.00101	1.575	0.0
	(643.4)	(2141.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.451	7.941 0	0.609 358	0.099 330	0.025 302	0.031 299	0.036 130	0.036 6	0.026 167	0.005 220
CN		0.358	0.731 357	0.122 33	0.075 310	0.040 253	0.012 158	0.015 58	0.010 18	0.032 124	0.006 219
CM		-0.008	0.034 322	0.003 166	0.008 55	0.005 294	0.003 225	0.003 160	0.002 101	0.002 325	0.001 287
DCP 1	.010	0.391	4.062 349	0.439 39	0.503 321	0.258 3	0.157 78	0.059 160	0.039 102	0.038 161	0.047 202
DCP 2	.020	0.566	3.628 352	0.405 35	0.258 319	0.144 348	0.135 94	0.104 166	0.049 131	0.020 315	0.044 241
DCP 3	.030	0.707	3.209 351	0.428 37	0.127 333	0.081 288	0.033 151	0.054 154	0.022 265	0.052 336	0.028 283
DCP 4	.049	0.942	2.759 351	0.455 50	0.156 354	0.138 268	0.075 244	0.065 123	0.033 346	0.062 316	0.026 299
DCP 5	.074	1.160	2.178 353	0.276 76	0.253 322	0.310 281	0.141 296	0.132 58	0.142 69	0.069 147	0.077 205
DCP 6	.099	1.099	2.094 351	0.380 60	0.329 357	0.247 259	0.112 237	0.016 194	0.049 48	0.011 215	0.008 84
DCP 7	.149	0.824	1.578 355	0.247 24	0.214 337	0.222 253	0.102 184	0.018 246	0.070 125	0.349 55	0.013 111
DCP 8	.200	0.605	1.213 0	0.221 6	0.103 291	0.085 243	0.069 183	0.056 85	0.036 21	0.014 348	0.014 288
DCP 9	.250	0.528	1.029 358	0.177 6	0.100 283	0.060 224	0.084 147	0.063 62	0.037 352	0.012 324	0.021 281
DCP10	.330	0.462	0.835 359	0.162 7	0.093 271	0.042 195	0.041 126	0.048 54	0.037 348	0.017 291	0.021 239
DCP11	.399	0.363	0.627 3	0.119 25	0.069 283	0.025 178	0.024 80	0.024 22	0.018 323	0.009 227	0.012 221
DCP12	.501	0.270	0.455 5	0.097 32	0.053 292	0.013 188	0.015 63	0.013 5	0.010 299	0.007 169	0.005 183
DCP13	.600	0.228	0.310 10	0.083 42	0.050 295	0.008 199	0.013 40	0.009 350	0.007 277	0.010 156	0.005 136
DCP14	.701	0.260	0.160 18	0.086 55	0.042 306	0.006 249	0.007 18	0.008 291	0.003 241	0.008 116	0.004 89
DCP15	.800	0.118	0.098 30	0.034 41	0.032 277	0.002 134	0.009 34	0.009 345	0.005 273	0.010 131	0.004 110
DCP16	.900	-0.083	0.036 61	0.024 261	0.030 244	0.001 164	0.006 51	0.011 0	0.007 300	0.010 132	0.002 140
DCP17	.969	-0.054	0.034 159	0.019 267	0.017 222	0.004 149	0.002 316	0.003 46	0.005 14	0.006 121	0.004 126

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	22.36	0.058	0.589	7.45	0.0	4.97	12165.3	20

	V	Q	RN	CH(MIN)	CH(MAX)	ALPHA.HMAX	AERO DAMP	TDR	EXT DAMP
	195.3	103192.	0.93E 07	-0.060	1.232	10.88	-0.00103	1.605	0.0
	(640.9)	(2155.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.965	7.852 0	0.631 3	0.146 337	0.087 0	0.099 330	0.094 299	0.124 174	0.047 346	0.039 312
CN		0.536	0.561 0	0.192 47	0.088 349	0.049 319	0.024 269	0.015 241	0.015 172	0.006 54	0.001 350
CM		-0.008	0.023 269	0.018 127	0.013 22	0.003 0	0.005 348	0.004 289	0.003 254	0.004 180	0.001 121
DCP 1	.010	1.285	3.445 347	1.050 52	0.204 39	0.057 352	0.101 286	0.037 234	0.025 221	0.025 339	0.038 344
DCP 2	.020	1.509	2.863 351	0.631 54	0.233 9	0.133 354	0.089 305	0.067 235	0.030 190	0.012 182	0.009 59
DCP 3	.030	1.515	2.454 350	0.573 58	0.237 15	0.129 344	0.059 311	0.070 253	0.056 205	0.026 170	0.036 56
DCP 4	.049	1.686	1.789 347	0.779 74	0.379 15	0.171 333	0.051 298	0.076 293	0.076 210	0.025 152	0.032 87
DCP 5	.074	1.790	0.923 350	0.393 102	0.623 338	0.319 354	0.113 357	0.103 336	0.091 128	0.130 144	0.079 207
DCP 6	.099	1.450	1.316 348	0.787 74	0.413 359	0.114 358	0.154 324	0.077 280	0.058 239	0.004 337	0.011 235
DCP 7	.149	1.069	1.056 0	0.512 55	0.315 357	0.133 324	0.150 312	0.103 269	0.054 279	0.071 227	0.014 275
DCP 8	.200	0.851	0.920 4	0.335 44	0.174 3	0.145 311	0.082 255	0.059 234	0.046 186	0.017 169	0.020 114
DCP 9	.250	0.778	0.847 1	0.260 39	0.159 355	0.134 290	0.063 224	0.045 224	0.048 165	0.011 77	0.022 114
DCP10	.330	0.683	0.705 2	0.221 44	0.116 349	0.104 288	0.059 212	0.031 205	0.047 159	0.031 79	0.025 54
DCP11	.399	0.544	0.562 7	0.168 31	0.052 330	0.045 286	0.037 204	0.016 155	0.020 136	0.025 42	0.012 10
DCP12	.501	0.407	0.419 10	0.134 75	0.028 296	0.013 294	0.013 193	0.000 151	0.011 161	0.021 25	0.009 289
DCP13	.600	0.325	0.296 16	0.113 23	0.025 268	0.005 350	0.010 204	0.005 93	0.005 119	0.018 19	0.009 321
DCP14	.701	0.324	0.167 27	0.088 23	0.022 220	0.012 49	0.007 218	0.010 91	0.008 10	0.013 350	0.005 275
DCP15	.800	0.157	0.130 30	0.060 356	0.028 227	0.001 149	0.011 185	0.010 100	0.007 55	0.013 342	0.006 270
DCP16	.900	-0.063	0.094 20	0.050 299	0.024 221	0.004 243	0.008 186	0.009 153	0.012 97	0.012 345	0.004 283
DCP17	.969	-0.054	0.012 62	0.033 284	0.011 231	0.006 270	0.005 218	0.006 153	0.008 94	0.008 336	0.005 260

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.37	0.058	0.594	7.85	0.0	-0.03	12167.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDA	EXT DAMP
197.8	103689.	0.94E 07	-0.087	1.328	7.78	-0.00139	2.185	0.0
(648.9)	(2165.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		-0.033	7.854 0	0.570 358	0.142 333	0.048 334	0.008 76	0.062 97	0.110 345	0.040 27	0.018 146
CN		0.172	1.062 358	0.073 9	0.114 260	0.020 249	0.025 29	0.005 32	0.011 334	0.009 348	0.007 105
CM		-0.027	0.034 304	0.006 172	0.018 0	0.014 332	0.001 211	0.005 94	0.004 94	0.002 255	0.002 274
DCP 1	.010	-0.999	3.954 352	0.429 272	0.421 302	0.138 316	0.249 308	0.052 12	0.074 292	0.064 304	0.025 270
DCP 2	.020	-0.744	3.570 353	0.287 277	0.501 300	0.185 342	0.232 333	0.063 29	0.027 298	0.043 316	0.031 267
DCP 3	.030	-0.559	3.349 353	0.138 297	0.516 300	0.182 5	0.179 326	0.098 353	0.070 353	0.016 37
DCP 4	.049	-0.236	3.307 352	0.218 39	0.395 302	0.169 3	0.154 328	0.124 6	0.058 58	0.023 351	0.021 15
DCP 5	.074	0.533	2.202 352	0.420 265	0.450 314	0.220 7	0.256 327	0.314 26	0.211 97	0.031 203	0.005 54
DCP 6	.099	0.279	2.988 352	0.289 56	0.324 296	0.212 0	0.100 28	0.034 31	0.070 56	0.031 125	0.041 24
DCP 7	.149	0.422	2.682 353	0.221 66	0.213 278	0.143 319	0.124 57	0.111 182	0.024 9	0.043 152	0.020 199
DCP 8	.200	0.479	2.517 357	0.157 98	0.227 263	0.232 277	0.154 91	0.166 195	0.085 287	0.017 343	0.044 130
DCP 9	.250	0.416	1.925 356	0.148 29	0.171 290	0.293 229	0.137 112	0.039 196	0.030 97	0.084 343	0.052 159
DCP10	.300	0.315	1.447 359	0.221 2	0.130 241	0.174 232	0.099 153	0.079 105	0.015 15	0.062 350	0.028 263
DCP11	.399	0.224	1.021 3	0.153 2	0.117 205	0.053 203	0.015 260	0.054 80	0.039 294	0.029 301	0.012 27
DCP12	.501	0.189	0.704 6	0.113 352	0.100 219	0.072 150	0.023 347	0.034 16	0.026 312	0.027 253	0.011 159
DCP13	.600	0.193	0.442 11	0.067 355	0.073 234	0.063 140	0.023 1	0.038 320	0.022 312	0.013 192	0.020 151
DCP14	.701	0.262	0.248 19	0.059 49	0.055 241	0.039 139	0.028 350	0.039 282	0.012 241	0.015 94	0.015 79
DCP15	.800	0.123	0.138 32	0.008 332	0.054 227	0.027 126	0.022 358	0.028 269	0.006 122	0.017 68	0.008 34
DCP16	.900	-0.113	0.050 87	0.056 241	0.053 210	0.024 106	0.016 344	0.026 268	0.007 184	0.016 75	0.008 60
DCP17	.969	-0.064	0.048 166	0.009 197	0.026 196	0.011 154	0.004 118	0.005 247	0.011 273	0.009 62	0.009 47

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.48	0.058	0.592	7.87	0.0	2.45	12167.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDA	EXT DAMP
196.6	102536.	0.94E 07	-0.088	1.484	9.13	-0.00168	2.631	0.0
(645.0)	(2141.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.449	7.868 0	0.629 4	0.135 332	0.090 19	0.104 320	0.025 278	0.081 197	0.021 50	0.043 350
CN		0.417	0.963 358	0.233 27	0.092 327	0.043 264	0.026 213	0.005 46	0.005 193	0.008 66	0.011 359
CM		-0.025	0.038 287	0.018 129	0.014 59	0.008 58	0.008 351	0.005 252	0.002 222	0.005 224	0.003 134
DCP 1	.010	-0.027	4.113 349	0.593 23	0.449 321	0.238 8	0.046 64	0.100 334	0.068 79	0.030 27	0.046 20
DCP 2	.020	0.042	3.800 351	0.606 28	0.284 321	0.216 18	0.089 94	0.043 9	0.069 80	0.036 94	0.021 6
DCP 3	.030	0.187	3.507 351	0.661 33	0.156 317	0.191 25	0.131 101	0.018 80	0.058 83	0.051 122	0.016 271
DCP 4	.049	0.537	3.201 390	0.743 41	0.063 329	0.157 30	0.139 93	0.047 160	0.008 105	0.042 127	0.052 223
DCP 5	.074	1.260	2.039 349	0.358 339	0.362 335	0.195 36	0.100 23	0.165 61	0.143 136	0.056 203	0.041 195
DCP 6	.099	0.947	2.800 349	0.792 46	0.096 68	0.010 91	0.069 95	0.081 135	0.099 231	0.076 301	0.017 172
DCP 7	.149	0.949	2.453 349	0.710 45	0.173 29	0.157 197	0.100 253	0.050 66	0.111 245	0.117 291	0.081 330
DCP 8	.200	0.438	1.843 351	0.634 56	0.340 0	0.246 222	0.238 270	0.093 304	0.072 0	0.055 107	0.055 324
DCP 9	.250	0.734	1.603 357	0.413 40	0.311 340	0.117 252	0.146 279	0.113 240	0.059 317	0.085 162	0.038 43
DCP10	.300	0.668	1.128 2	0.260 22	0.239 337	0.158 262	0.063 262	0.100 293	0.059 195	0.055 159	0.062 100
DCP11	.399	0.513	0.864 7	0.153 6	0.113 323	0.107 290	0.049 155	0.015 313	0.031 165	0.016 102	0.033 97
DCP12	.501	0.383	0.689 10	0.159 358	0.075 290	0.062 286	0.050 177	0.014 84	0.024 148	0.034 73	0.024 23
DCP13	.600	0.314	0.483 13	0.152 1	0.069 271	0.035 261	0.048 177	0.031 93	0.014 98	0.035 49	0.029 343
DCP14	.701	0.347	0.266 24	0.119 4	0.057 245	0.012 204	0.033 162	0.034 74	0.014 24	0.026 25	0.030 300
DCP15	.800	0.155	0.182 29	0.086 344	0.099 239	0.023 185	0.026 152	0.028 65	0.013 355	0.011 357	0.015 272
DCP16	.900	-0.115	0.093 30	0.049 321	0.046 234	0.030 205	0.025 152	0.025 60	0.008 11	0.011 1	0.016 259
DCP17	.969	-0.072	0.024 153	0.029 300	0.017 226	0.016 228	0.015 180	0.013 89	0.003 77	0.007 42	0.007 271

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	22.13	0.057	0.591	7.72	0.0	4.05	12167.3	20

	V	Q	RN	CNMIN)	CNMAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	196.0	101741.	0.93E 07	-0.111	1.553	9.91	-0.00195	3.039	0.0
	(642.9)	(2124.9)							

HARMONIC ANALYSIS

DATA TYPE	H/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		4.050	7.716 0	0.637 5	0.006 331	0.046 27	0.070 10	0.069 309	0.069 17	0.019 303	0.026 262
CN		0.674	0.761 3	0.267 38	0.079 359	0.064 348	0.043 283	0.010 266	0.006 80	0.005 328	0.003 266
CM		-0.028	0.045 244	0.026 128	0.006 104	0.011 101	0.005 49	0.004 11	0.002 59	0.001 300	0.001 358
DCP 1	.014	0.931	3.540 348	0.985 45	0.202 56	0.140 350	0.042 63	0.046 190	0.025 208	0.032 295	0.029 300
DCP 2	.020	0.986	3.188 351	0.862 45	0.224 77	0.103 330	0.048 251	0.049 240	0.089 186	0.029 327	0.050 348
DCP 3	.030	1.091	2.809 351	0.789 45	0.234 88	0.091 292	0.100 251	0.047 275	0.018 138	0.025 320	0.032 359
DCP 4	.045	1.413	2.376 351	0.756 45	0.194 94	0.078 255	0.117 294	0.081 324	0.080 61	0.046 92	0.013 200
DCP 5	.074	2.043	1.113 354	0.188 333	0.379 340	0.144 0	0.119 282	0.133 2	0.176 85	0.078 113	0.039 142
DCP 6	.099	1.702	1.072 352	0.664 52	0.143 6	0.124 347	0.001 27	0.062 191	0.055 115	0.017 357	0.015 325
DCP 7	.149	1.531	1.474 352	0.734 56	0.186 345	0.154 15	0.037 282	0.041 211	0.090 68	0.011 266	0.028 35
DCP 8	.200	1.233	1.141 355	0.790 60	0.217 340	0.234 39	0.111 306	0.041 332	0.039 68	0.064 295	0.041 70
DCP 9	.250	1.053	1.002 357	0.599 56	0.165 350	0.249 28	0.125 292	0.097 3	0.037 258	0.070 335	0.017 220
DCP10	.300	0.997	0.891 15	0.385 50	0.189 11	0.132 15	0.125 320	0.044 346	0.057 306	0.050 316	0.033 275
DCP11	.399	0.712	0.762 10	0.225 39	0.114 7	0.068 327	0.077 314	0.032 208	0.028 319	0.008 258	0.026 251
DCP12	.501	0.558	0.431 15	0.178 15	0.068 6	0.039 306	0.041 284	0.028 220	0.015 286	0.015 207	0.012 253
DCP13	.600	0.442	0.492 22	0.166 2	0.040 354	0.071 299	0.032 248	0.023 237	0.017 209	0.012 162	0.006 177
DCP14	.701	0.459	0.315 32	0.139 349	0.010 244	0.049 296	0.033 214	0.016 193	0.013 162	0.008 125	0.009 146
DCP15	.800	0.242	0.263 29	0.123 326	0.028 250	0.060 286	0.032 209	0.012 164	0.007 149	0.006 86	0.008 132
DCP16	.900	-0.070	0.165 25	0.094 310	0.037 287	0.043 270	0.026 207	0.017 184	0.011 133	0.014 77	0.007 70
DCP17	.969	-0.074	0.022 92	0.039 295	0.012 297	0.019 291	0.011 214	0.004 176	0.002 87	0.007 58	0.001 107

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	22.97	0.067	0.732	10.90	0.0	0.01	12171.1	20

	V	Q	RN	CNMIN)	CNMAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	69.9	12411.	0.89E 07	-0.077	0.966	13.48	-0.00141	0.909	0.0
	(229.3)	(259.2)							

HARMONIC ANALYSIS

DATA TYPE	H/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.007	10.299 0	0.401 356	0.150 327	0.029 22	0.315 284	0.036 184	0.024 167	0.026 136	0.004 87
CN		0.149	0.632 4	0.061 14	0.006 344	0.004 26	0.302 279	0.002 290	0.007 335	0.013 144	0.003 48
CM		-0.025	0.039 298	0.007 287	0.002 329	0.001 327	0.001 358	0.000 292	0.002 172	0.007 139	0.001 188
DCP 1	.014	-0.910	3.029 349	0.826 396	0.216 207	0.199 8	0.072 42	0.051 266	0.059 27	0.082 70	0.099 136
DCP 2	.020	-0.290	4.216 350	0.312 327	0.046 332	0.010 244	0.363 303	0.027 204	0.036 208	0.026 12	0.016 70
DCP 3	.030	0.121	3.586 350	0.297 366	0.046 334	0.006 322	0.309 313	0.014 293	0.910 220	0.011 15	0.009 130
DCP 4	.045	0.146	2.975 351	0.230 361	0.041 332	0.012 291	0.304 294	0.006 132	0.013 279	0.016 42	0.016 358
DCP 5	.074	0.247	2.043 351	0.176 361	0.032 343	0.038 315	0.011 284	0.007 330	0.006 318	0.011 8	0.003 43
DCP 6	.099	0.446	1.677 353	0.167 350	0.176 352	0.070 13	0.013 294	0.008 141	0.006 280	0.013 336	0.008 77
DCP 7	.149	0.831	1.490 353	0.121 4	0.315 11	0.037 349	0.005 332	0.006 271	0.205 249	0.019 43	0.009 94
DCP 8	.200	0.696	1.222 356	0.042 18	0.013 15	0.008 1	0.036 164	0.037 39	0.013 319	0.019 43	0.015 152
DCP 9	.250	0.226	1.244 359	0.299 15	0.007 349	0.004 35	0.005 253	0.006 134	0.011 350	0.023 161	0.008 13
DCP10	.300	0.668	0.874 0	0.075 23	0.007 175	0.006 175	0.308 251	0.005 304	0.005 331	0.022 142	0.002 185
DCP11	.399	0.219	0.699 7	0.304 30	0.007 30	0.003 107	0.309 340	0.003 336	0.309 309	0.023 157	0.004 35
DCP12	.501	0.448	0.542 12	0.069 41	0.006 62	0.001 56	0.305 265	0.010 280	0.006 334	0.021 164	0.010 328
DCP13	.600	0.195	0.412 18	0.045 60	0.036 44	0.007 9	0.007 108	0.011 196	0.013 330	0.019 172	0.006 79
DCP14	.701	0.244	0.268 23	0.346 62	0.032 243	0.008 55	0.009 141	0.009 155	0.036 101	0.023 151	0.004 277
DCP15	.800	0.140	0.174 37	0.026 89	0.003 144	0.002 317	0.002 197	0.005 37	0.006 0	0.024 156	0.003 3
DCP16	.900	-0.064	0.065 64	0.013 128	0.007 284	0.011 184	0.009 250	0.036 179	0.005 2	0.027 130	0.002 305
DCP17	.969	0.310	0.029 153	0.107 264	0.016 162	0.074 173	0.007 86	0.018 10	0.011 14	0.033 175	0.017 97

259

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNNEL HZ	FREQ HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.01	0.177	0.195	10.32	0.3	7.47	12171.4	20

		RN	C(M(1))	C(M(K))	ALPHA.WMAX	BEND.DAMP	TDR	EXT.DAMP
66.3	11391.	0.315 07	-0.303	1.024	1..1	-0.00134	0.727	0.0
(217.5)	(237.9)							

HARMONIC ANALYSIS

DATA TYPE	K/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.447	10.323 0	0.993 355	0.164 323	0.040 17	0.062 224	0.054 151	0.013 140	0.009 236	0.006 164
CN		0.751	0.640 12	0.153 326	0.154 43	0.023 326	0.334 93	0.036 349	0.012 232	0.021 351	0.003 233
CM		-0.016	0.035 268	0.022 4	0.022 245	0.013 24	0.033 279	0.001 173	0.304 61	0.034 136	0.002 12
CCP 1	.110	3.043	4.343 356	1.115 16	0.364 260	0.276 15	0.17 53	0.115 345	0.106 296	0.040 261	0.020 37
CCP 2	.051	2.071	3.923 1	3.763 2	0.272 274	0.176 155	0.064 57	0.064 324	0.044 239	0.059 54	0.029 35
CCP 3	.030	2.756	4.975 0	0.673 541	0.123 213	0.117 64	0.074 316	0.057 164	0.020 4	0.046 7	0.013 288
CCP 4	.049	2.316	2.544 7	0.420 358	0.239 258	0.044 132	0.052 34	0.032 304	0.016 259	0.041 27	0.007 62
CCP 5	.074	1.857	2.148 6	0.605 351	0.209 230	0.171 133	0.360 164	0.026 268	0.045 233	0.041 17	0.017 16
CCP 6	.049	1.840	1.835 9	0.443 343	0.176 208	0.119 77	0.063 321	0.025 252	0.019 166	0.055 42	0.016 354
CCP 7	.149	1.376	1.550 8	0.335 323	0.155 159	0.115 15	0.062 276	0.039 168	0.019 191	0.062 26	0.031 302
CCP 8	.200	1.228	1.377 8	0.221 333	0.145 130	0.115 15	0.056 258	0.021 168	0.021 168	0.069 33	0.030 314
CCP 9	.253	1.021	1.136 8	0.167 284	0.103 94	0.112 335	0.056 215	0.051 114	0.017 54	0.235 302	0.016 191
CCP10	.300	0.936	0.967 9	0.094 219	0.152 93	0.086 321	0.043 165	0.021 61	0.036 334	0.023 285	0.016 151
CCP11	.349	0.772	0.796 16	0.047 251	0.113 76	0.066 332	0.029 146	0.023 29	0.016 235	0.017 333	0.003 179
CCP12	.401	0.541	0.633 23	0.034 250	0.043 72	0.051 280	0.027 119	0.016 0	0.017 226	0.023 342	0.007 257
CCP13	.600	0.468	0.441 27	0.022 230	0.089 65	0.044 275	0.027 111	0.009 345	0.021 239	0.022 305	0.012 133
CCP14	.701	0.391	0.346 35	0.021 165	0.077 60	0.034 279	0.046 77	0.011 292	0.019 249	0.017 297	0.005 18
CCP15	.80	0.222	0.237 42	0.032 137	0.067 51	0.032 247	0.018 46	0.009 279	0.016 249	0.023 334	0.017 202
CCP16	.900	0.019	0.136 53	0.036 149	0.064 25	0.020 199	0.013 76	0.008 35	0.008 282	0.021 2	0.015 201
CCP17	.950	0.016	0.038 44	0.094 231	0.323 37	0.011 265	0.019 27	0.005 242	0.021 235	0.017 0	0.005 294

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	23.33	0.177	0.191		7.0	4.95	12171.4	20

| 66.3 | 11328. | 0.315 07 | -0.204 | | 23.13 | -0.00031 | 0.16m | |
| (216.7) | (236.6) | | | | | | | |

HARMONIC ANALYSIS

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	D CL ALPHA	DEL CM	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.98	0.113	0.296	10.35	0.0	0.02	12175.1	20

V	Q	RN	CM(MIN)	CM(MAX)	ALPHA.VMAX	AERO DAMP	TDR	EXT DAMP
103.2 (338.7)	27368. (571.6)	3.46E 07	-0.072	1.325	13.56	-0.00107	0.892	0.0

HARMONIC ANALYSIS

DATA TYPE	R/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		0.017	10.353	0	0.945	352	0.144	327	0.027	43	0.012	277	0.025	186	0.019	196	0.018	88	0.007	291
CN		0.150	3.817	359	0.367	11	0.316	125	0.073	161	0.015	223	0.011	254	0.036	261	0.004	53	0.004	243
CM		-0.016	0.393	299	0.008	273	0.004	262	0.005	314	0.035	343	0.004	23	0.004	73	0.001	208	0.001	56
DCP 1	.013	0.041	5.110	354	0.412	224	0.435	276	0.536	341	0.295	36	0.142	77	0.043	133	0.037	20	0.105	70
DCP 2	.020	0.068	4.009	356	0.267	245	0.409	269	0.266	322	0.130	21	0.094	88	0.046	167	0.027	313	0.037	45
DCP 3	.030	0.204	3.697	356	0.100	320	0.164	242	0.123	341	0.089	355	0.025	88	0.018	199	0.022	24	0.329	104
DCP 4	.049	0.356	3.052	355	0.385	333	0.124	229	0.120	71	0.097	333	0.055	38	0.036	136	0.013	252	0.02	353
DCP 5	.074	0.527	7.034	353	0.183	19	0.082	161	0.002	326	0.083	49	0.054	6	0.044	157	0.031	180	0.037	277
DCP 6	.099	0.309	2.291	394	0.210	29	0.103	141	0.112	237	0.044	276	0.064	342	0.036	75	0.020	167	0.032	266
DCP 7	.149	0.247	1.700	354	0.223	29	0.114	119	0.113	162	0.082	259	0.051	310	0.022	40	0.011	129	0.023	242
DCP 8	.230	0.203	1.430	357	0.140	29	0.099	105	0.096	171	0.067	234	0.052	293	0.020	4	0.015	97	0.022	217
DCP 9	.250	0.179	1.234	355	0.192	26	0.146	66	0.092	150	0.068	238	0.046	262	0.023	326	0.017	72	0.015	210
DCP10	.300	0.101	1.027	356	0.147	23	0.383	76	0.073	135	0.056	155	0.041	296	0.023	296	0.013	41	0.014	139
DCP11	.399	0.190	0.738	3	0.081	30	0.035	69	0.035	126	0.031	159	0.024	223	0.028	264	0.012	357	0.008	59
DCP12	.501	0.150	0.525	7	0.148	43	0.039	67	0.013	136	0.017	154	0.017	210	0.014	242	0.005	313	0.005	265
DCP13	.600	0.176	0.442	12	0.037	63	0.30	133	0.013	169	0.013	161	0.011	201	0.010	217	0.006	96	0.004	190
DCP14	.701	0.221	0.336	13	0.043	72	0.307	76	0.012	152	0.011	179	0.011	213	0.012	245	0.003	4	0.002	271
DCP15	.800	0.106	0.164	26	0.272	42	0.013	133	0.005	159	0.038	186	0.009	166	0.007	229	0.005	2	0.001	300
DCP16	.900	-0.043	0.073	68	0.024	147	0.011	213	0.012	141	0.009	173	0.009	223	0.013	248	0.007	44	0.007	254
DCP17	.965	-0.026	0.035	144	0.004	128	0.013	130	0.015	271	0.015	166	0.010	181	0.005	256	0.007	59	0.006	211

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	D CL ALPHA	DEL CM	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.98	0.115	0.296	13.39	0.0	4.94	12175.3	20

V	Q	RN	CM(MIN)	CM(MAX)	ALPHA.VMAX	AERO DAMP	TDR	EXT DAMP
101.5 (333.1)	26650. (556.6)	3.48E 07	-0.384	1.427	15.27	-0.00084	5.687	0.0

HARMONIC ANALYSIS

DATA TYPE	R/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		4.941	10.343	0	0.948	356	0.161	326	0.014	11	0.016	172	0.012	257	0.022	154	0.009	93	0.006	69
CN		0.530	0.922	5	0.158	355	0.032	205	0.385	56	0.013	249	0.011	168	0.007	77	0.010	344	0.006	279
CM		-0.016	0.024	260	0.015	53	0.027	308	0.017	190	0.011	73	0.006	312	0.003	217	0.004	157	0.002	65
DCP 1	.013	1.709	4.920	354	1.320	23	0.465	303	0.354	204	0.146	119	0.032	352	0.041	133	0.059	24	0.063	295
DCP 2	.020	1.521	3.792	355	1.014	22	0.511	304	0.326	204	0.229	110	0.151	13	0.073	290	0.025	205	0.014	274
DCP 3	.030	1.410	2.896	359	1.016	31	0.606	311	0.364	214	0.223	120	0.137	30	0.036	5	0.064	322	0.005	240
DCP 4	.049	1.562	2.707	356	0.569	7	0.148	287	0.074	176	0.041	64	0.026	339	0.018	256	0.014	165	0.012	92
DCP 5	.074	1.388	2.223	356	0.475	8	0.160	263	0.064	165	0.035	46	0.027	308	0.017	216	0.016	141	0.015	48
DCP 6	.099	1.291	.669	0	0.419	6	0.160	274	0.070	152	0.064	39	0.042	307	0.021	207	0.019	136	0.013	45
DCP 7	.149	0.973	1.440	2	0.334	1	0.122	259	0.066	116	0.055	71	0.034	286	0.023	183	0.010	129	0.010	3
DCP 8	.230	0.616	1.232	5	0.278	355	0.119	232	0.093	110	0.069	3	0.040	256	0.023	152	0.010	108	0.006	66
DCP 9	.250	0.731	1.113	5	0.225	342	0.100	195	0.006	73	0.066	313	0.037	204	0.017	72	0.015	299	0.004	127
DCP10	.300	0.690	0.947	4	0.190	325	0.124	179	0.124	59	0.085	311	0.047	210	0.024	126	0.016	28	0.012	344
DCP11	.399	0.578	0.616	9	0.139	323	0.156	162	0.105	50	0.073	296	0.035	190	0.021	131	0.016	25	0.014	315
DCP12	.501	0.415	0.626	11	0.103	326	0.094	156	0.092	36	0.063	266	0.040	165	0.023	63	0.020	341	0.008	303
DCP13	.600	0.342	0.493	17	0.073	342	0.353	141	0.071	18	0.054	249	0.036	133	0.025	23	0.019	319	0.011	289
DCP14	.701	0.326	0.291	23	0.369	3	0.345	128	0.066	233	0.008	111	0.016	16	0.017	312	0.012	242		
DCP15	.800	0.174	0.232	26	0.319	307	0.051	119	0.001	349	0.036	222	0.020	97	0.003	307	0.013	355	0.013	246
DCP16	.900	-0.026	0.168	40	0.041	243	0.039	102	0.030	341	0.021	204	0.005	61	0.006	20	0.017	337	0.006	238
DCP17	.965	-0.029	0.013	1	0.030	243	0.316	103	0.013	325	0.004	176	0.008	78	0.007	144	0.010			

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
2.0	22.97	0.115	0.297	11.81	0.0	7.50	12175.4	20

V	N	RN	CM(MIN)	CM(MAX)	ALPHA.MMAX	AERO DAMP	TDR	EXT DAMP
101.1	26492.	0.489 37	-0.215	1.047	17.67	-0.33079	3.647	0.0
(331.8)	(553.3)							

HARMONIC ANALYSIS

DATA TYPE	X/L	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.496	10.338 3	0.043 157	0.136 326	0.358 313	0.089 162	0.080 50	0.049 168	0.033 197	0.013 72
CN		0.677	2.713 15	0.272 7	0.143 261	0.071 166	0.356 77	0.045 352	0.031 264	0.018 223	0.019 149
CM		-0.328	3.345 221	0.343 91	0.736 3	0.323 262	0.320 208	0.019 128	0.013 59	0.006 9	0.007 292
DCP 1	.010	2.180	2.882 356	2.085 51	1.975 349	0.604 209	0.203 259	0.169 227	0.189 176	0.144 129	0.166 74
DCP 2	.020	1.926	2.392 3	1.976 51	1.774 346	0.942 279	0.156 245	0.069 199	0.111 174	0.091 123	0.134 76
DCP 3	.030	1.849	1.993 3	1.863 53	1.703 348	0.943 284	0.143 241	0.087 222	0.110 179	0.112 123	0.104 72
DCP 4	.040	1.928	1.895 4	2.039 42	1.444 333	0.217 263	0.192 190	0.066 117	0.043 83	0.043 11	0.024 324
DCP 5	.074	1.715	1.651 6	1.743 33	1.357 317	0.167 235	0.160 157	0.054 75	0.026 62	0.033 335	0.021 270
DCP 6	.099	1.574	1.415 9	1.707 28	1.313 304	0.162 216	0.101 139	0.039 61	0.032 4	0.036 318	0.027 252
DCP 7	.149	1.253	1.230 12	1.560 14	1.287 281	0.162 169	0.098 121	0.015 52	0.042 354	0.044 308	0.035 242
DCP 8	.200	1.029	1.055 16	1.493 12	1.255 279	0.166 195	0.128 122	0.007 53	0.002 337	0.036 291	0.035 234
DCP 9	.250	0.920	0.907 15	0.427 359	0.736 260	0.162 176	0.163 133	0.106 62	0.070 268	0.053 264	0.038 260
DCP10	.300	0.840	0.868 16	0.361 354	0.233 251	0.145 166	0.116 97	0.103 28	0.056 296	0.063 252	0.032 225
DCP11	.394	0.719	0.768 20	0.302 349	0.187 243	0.147 161	0.120 67	0.104 13	3.067 285	0.043 255	0.048 203
DCP12	.501	0.548	0.630 22	0.228 349	0.154 224	0.154 141	0.100 65	0.081 356	0.061 273	0.037 235	0.050 170
DCP13	.600	0.462	0.510 24	0.186 326	0.145 235	0.139 118	0.095 44	0.064 321	0.063 243	0.033 203	0.044 146
DCP14	.731	0.427	0.378 27	0.161 303	0.132 164	0.096 94	0.080 21	0.038 300	0.061 228	0.035 174	0.043 103
DCP15	.800	0.255	0.296 23	0.174 284	0.110 171	0.064 86	0.074 11	0.062 247	0.036 213	0.034 165	0.042 76
DCP16	.900	0.015	0.162 17	0.207 275	0.065 166	0.065 88	0.052 4	0.038 266	0.021 211	0.018 133	0.028 59
DCP17	.965	-0.019	0.047 16	0.044 271	0.022 197	0.011 156	0.021 12	0.019 259	0.012 148	0.008 206	0.011 63

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
2.0	22.94	0.116	0.297	10.30	0.0	9.98	12175.5	20

V	N	RN	CM(MIN)	CM(MAX)	ALPHA.MMAX	AERO DAMP	TDR	EXT DAMP
100.9	26392.	0.489 37	-3.280	2.276	19.46	-0.30091	3.741	0.0
(330.9)	(551.2)							

HARMONIC ANALYSIS

DATA TYPE	X/L	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		9.978	10.345 0	0.965 159	0.169 341	0.061 7	0.111 266	0.141 156	0.043 119	0.025 277	0.013 76
CN		0.882	3.074 25	0.307 8	0.065 287	0.094 246	0.052 176	0.050 115	0.041 32	0.022 325	0.019 302
CM		-0.043	3.078 238	0.360 48	0.031 42	0.021 352	0.163 208	0.017 227	0.016 169	0.010 96	0.006 72
DCP 1	.010	2.055	2.203 2	2.222 59	1.611 9	0.374 29	0.340 329	0.127 291	0.203 294	0.195 253	0.171 209
DCP 2	.020	2.337	1.858 14	1.774 57	1.543 1	0.215 4	0.230 317	0.088 255	0.119 303	0.143 260	0.129 216
DCP 3	.030	2.184	1.840 19	1.508 60	0.465 13	0.273 13	0.242 321	0.149 256	0.084 264	0.089 240	0.088 199
DCP 4	.040	2.119	1.625 13	1.316 51	0.393 9	0.220 336	0.183 264	0.116 225	0.063 231	0.066 150	0.053 97
DCP 5	.074	2.046	1.292 18	0.860 41	0.283 349	0.166 316	0.131 266	0.089 199	0.053 176	0.048 121	0.036 64
DCP 6	.099	1.869	1.143 23	0.782 33	0.293 328	0.112 295	0.116 246	0.086 175	0.044 149	0.039 104	0.038 55
DCP 7	.149	1.476	1.048 26	0.656 20	0.212 311	0.131 269	0.153 223	0.116 151	0.049 103	0.033 70	0.025 16
DCP 8	.200	1.237	3.946 29	0.557 20	0.217 316	0.164 274	0.155 215	0.128 158	0.077 107	0.047 41	0.027 3
DCP 9	.250	1.101	0.903 29	0.502 10	0.194 303	0.162 268	0.163 208	0.140 149	0.100 89	0.032 47	0.051 0
DCP10	.300	1.000	0.821 29	0.429 3	0.160 292	0.164 297	0.166 198	0.130 142	0.111 83	0.087 33	0.062 348
DCP11	.394	0.876	0.760 31	0.359 355	0.139 278	0.124 250	0.131 193	0.129 139	0.121 60	0.085 23	0.067 348
DCP12	.501	0.700	0.708 29	0.306 337	0.132 247	0.098 221	0.115 162	0.111 110	0.112 41	0.078 340	0.071 315
DCP13	.600	0.597	0.622 28	0.272 321	0.142 225	0.094 192	0.123 132	0.107 73	0.112 9	0.077 298	0.055 277
DCP14	.701	0.544	0.444 28	0.235 303	0.133 201	0.094 165	0.118 100	0.107 37	0.107 338	0.083 263	0.053 228
DCP15	.800	0.366	0.385 21	0.183 286	0.119 191	0.091 151	0.107 80	0.087 10	0.085 108	0.066 231	0.033 194
DCP16	.900	0.086	0.227 14	0.113 268	0.044 183	0.064 139	0.044 61	0.032 3	0.035 299	0.026 233	0.021 192
DCP17	.965	-0.002	0.096 17	0.074 276	0.033 197	0.027 134	0.027 47	0.027 348	0.030 274	0.021 202	0.019 138

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	0.0	22.97	0.086	0.551	10.56	0.0	0.02	12177.1	20

	V	Q	RN	CHEMINI	CHEMAXI	ALPHA.HMAX	AERO DAMP	TDR	EXT DAMP
	135.8	47875.	0.64E 07	-0.375	1.077	10.61	-0.00090	0.084	0.0
	(445.5)	(999.9)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.029	10.363 0	0.986 352	0.150 321	0.043 26	0.004 97	0.034 125	0.027 196	0.013 102	0.008 17
CN		0.162	0.918 359	0.049 44	0.031 223	0.027 252	0.011 277	0.007 293	0.008 270	0.001 296	0.006 12
CM		-0.012	0.026 306	0.012 260	0.007 309	0.009 2	0.006 55	0.004 109	0.002 117	0.000 39	0.002 126
DCP 1	.010	0.447	5.118 353	1.303 258	0.897 309	0.558 18	0.087 107	0.250 32	0.271 85	0.215 179	0.078 206
DCP 2	.020	0.519	3.985 356	0.661 259	0.534 299	0.265 32	0.191 299	0.064 124	0.171 133	0.031 274	
DCP 3	.030	0.172	1.892 355	0.043 315	0.219 281	0.113 338	0.045 198	0.017 347	0.044 152	0.029 244	
DCP 4	.049	0.444	3.111 356	0.126 269	0.243 283	0.147 334	0.099 91	0.074 171	0.041 303	0.034 74	0.044 179
DCP 5	.074	0.425	2.674 356	0.058 28	0.168 247	0.118 299	0.066 45	0.052 147	0.347 269	0.032 34	0.037 133
DCP 6	.099	0.449	2.793 356	0.105 52	0.117 233	0.102 299	0.055 36	0.050 151	0.054 257	0.042 354	0.037 87
DCP 7	.149	0.273	1.823 356	0.164 57	0.110 195	0.100 259	0.046 353	0.027 129	0.037 245	0.030 314	0.036 66
DCP 8	.200	0.209	1.449 359	0.158 59	0.130 182	0.094 249	0.052 334	0.019 90	0.039 242	0.028 326	0.042 59
DCP 9	.250	0.173	1.294 357	0.161 48	0.087 157	0.081 216	0.043 292	0.013 334	0.014 235	0.021 303	0.026 1
DCP10	.300	0.166	1.133 357	0.158 48	0.093 144	0.096 203	0.050 269	0.125 339	0.007 247	0.016 279	0.025 351
DCP11	.399	0.168	0.837 3	0.107 49	0.047 143	0.062 196	0.045 257	0.029 314	0.006 321	0.004 277	0.015 344
DCP12	.501	0.137	0.619 5	0.065 47	0.071 147	0.042 184	0.034 241	0.027 295	0.011 336	0.003 105	0.006 277
DCP13	.600	0.153	0.452 8	0.039 62	0.011 188	0.024 182	0.018 225	0.015 271	0.012 291	0.004 261	0.008 329
DCP14	.701	0.213	0.308 13	0.046 75	0.011 210	0.023 208	0.012 226	0.008 295	0.006 287	0.003 158	0.007 278
DCP15	.800	0.101	0.172 24	0.033 90	0.013 233	0.023 194	0.012 223	0.013 247	0.005 293	0.004 157	0.006 298
DCP16	.900	-0.043	0.055 74	0.019 165	0.012 216	0.017 186	0.012 213	0.015 280	0.004 281	0.002 179	0.003 229
DCP17	.969	-0.041	0.032 155	0.008 123	0.011 197	0.012 168	0.005 229	0.009 231	0.004 270	0.004 48	0.005 332

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	0.0	22.94	0.087	0.398	10.35	0.0	7.50	12177.2	20

	V	Q	RN	CHEMINI	CHEMAXI	ALPHA.HMAX	AERO DAMP	TDR	EXT DAMP
	134.8	47363.	0.64E 07	-0.051	1.245	12.96	-0.00092	0.900	0.0
	(442.4)	(989.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.509	10.351 0	0.988 351	0.148 315	0.012 351	0.039 148	0.010 17	0.046 167	0.032 131	0.019 20
CN		0.323	0.856 0	0.143 16	0.065 277	0.019 171	0.017 24	0.007 277	0.007 175	0.001 322	0.004 16
CM		-0.011	0.031 306	0.003 66	0.010 20	0.007 249	0.008 148	0.004 47	0.001 304	0.000 156	0.001 221
DCP 1	.010	3.591	5.329 350	0.780 43	0.882 337	0.595 312	0.528 148	0.468 132	0.081 263	0.075 284	0.101 23
DCP 2	.020	0.615	4.176 354	0.714 33	0.479 329	0.305 264	0.197 172	0.178 107	0.075 52	0.104 334	0.076 334
DCP 3	.030	0.775	1.828 354	0.669 76	0.244 234	0.256 234	0.135 163	0.131 92	0.083 352	0.117 311	0.034 271
DCP 4	.049	0.926	3.194 355	0.481 19	0.184 307	0.152 223	0.029 149	3.081 21	0.019 31	0.028 197	0.029 222
DCP 5	.074	0.902	2.539 355	0.403 14	0.144 292	0.113 195	0.034 69	0.076 341	0.019 256	0.036 147	0.013 128
DCP 6	.099	0.847	2.084 356	0.362 20	0.143 299	0.096 201	0.040 84	3.062 346	0.022 238	0.030 143	0.012 77
DCP 7	.149	0.642	1.606 357	0.283 13	0.124 279	0.085 178	0.051 60	0.047 334	0.015 208	0.011 107	0.014 247
DCP 8	.200	0.522	1.323 0	0.225 12	0.102 273	0.061 163	0.049 46	0.036 317	0.015 199	0.008 42	0.008 241
DCP 9	.250	0.451	1.144 359	0.193 0	0.093 248	0.066 129	0.054 13	3.047 289	0.027 178	0.012 126	0.012 57
DCP10	.300	0.420	0.951 0	0.156 359	0.078 249	0.047 113	0.047 17	0.027 271	0.027 187	0.008 181	0.010 56
DCP11	.399	0.346	0.760 5	0.126 10	0.061 250	0.036 114	0.039 1	3.026 260	0.020 169	0.005 94	0.003 83
DCP12	.501	0.252	0.569 8	0.103 14	0.054 254	0.031 114	0.036 358	0.023 246	0.017 157	0.008 359	0.006 5
DCP13	.600	0.229	3.415 13	0.086 23	0.049 254	0.018 116	3.026 352	0.018 238	0.013 138	0.002 333	0.008 20
DCP14	.701	0.244	0.260 20	0.079 37	0.044 264	0.012 97	0.026 328	0.015 206	0.006 90	0.006 352	0.005 16
DCP15	.800	0.172	0.160 27	0.032 90	0.030 236	0.012 40	0.022 314	0.013 178	0.006 57	0.003 285	0.005 28
DCP16	.900	-0.052	0.070 41	0.026 247	0.028 235	0.023 20	0.020 293	0.006 187	0.007 7	0.007 285	0.002 178
DCP17	.969	-0.038	0.018 142	0.026 251	0.023 192	0.008 54	0.008 317	0.006 147	0.005 221	0.001 199	0.002 16

TUNEL HZ	PRTVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.92	0.087	0.497	15.11	0.0	4.95	12177.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
134.3	47071.	0.64E 07	-0.171	1.464	15.12	-0.00091	0.981	0.0
(440.6)	(983.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		4.948	10.309	0	0.062	351	0.189	119	0.028	300	0.040	224	0.067	140	0.045	281	0.031	168	0.023	61
CN		0.492	7.749	4	0.233	23	0.390	295	0.035	198	0.021	134	0.021	55	0.022	310	0.014	245	0.009	163
CM		-0.216	0.029	299	0.024	114	0.024	71	0.016	291	0.009	229	0.008	173	0.007	113	0.007	22	0.004	314
DCP 1	.010	1.493	4.737	348	1.341	62	0.777	29	0.451	306	0.264	295	0.176	243	0.186	218	0.087	176	0.110	116
DCP 2	.020	1.341	3.505	353	0.986	53	0.526	4	0.275	315	0.172	262	0.130	211	0.107	214	0.079	155	0.110	99
DCP 3	.030	1.308	2.804	353	0.955	59	0.618	4	0.389	306	0.272	299	0.170	171	0.089	134	0.064	66	0.259	59
DCP 4	.049	1.390	2.415	356	0.799	46	0.461	342	0.732	273	0.136	236	0.079	192	0.015	67	0.031	10	0.016	11
DCP 5	.074	1.248	1.959	357	0.603	42	0.395	332	0.195	255	0.111	182	0.069	112	0.027	45	0.047	5	0.032	319
DCP 6	.099	1.164	1.616	359	0.611	40	0.319	176	0.158	243	0.085	166	0.047	97	0.015	10	0.011	3	0.023	308
DCP 7	.149	0.908	1.324	1	0.471	78	0.244	338	0.125	220	0.058	148	0.038	104	0.023	43	0.034	351	0.024	290
DCP 8	.200	0.747	1.112	5	0.385	28	0.192	356	0.099	215	0.058	156	0.051	100	0.038	25	0.037	336	0.024	259
DCP 9	.250	0.660	1.001	5	0.335	15	0.163	243	0.081	196	0.053	133	0.049	81	0.045	6	0.038	309	0.021	243
DCP10	.300	0.632	0.964	8	0.292	19	0.145	273	0.085	192	0.060	129	0.052	63	0.054	348	0.039	283	0.022	221
DCP11	.399	0.512	0.749	11	0.235	6	0.174	261	0.076	165	0.046	104	0.047	57	0.047	346	0.033	271	0.021	209
DCP12	.571	0.393	0.566	14	0.181	5	0.296	249	0.058	143	0.035	85	0.038	17	0.047	322	0.038	237	0.026	181
DCP13	.602	0.271	0.436	17	0.146	0	0.093	235	0.035	126	0.031	58	0.031	13	0.041	309	0.035	216	0.026	147
DCP14	.701	0.120	0.248	23	0.108	2	0.060	221	0.042	107	0.025	34	0.028	346	0.034	284	0.032	194	0.019	116
DCP15	.800	0.178	0.211	24	0.078	352	0.065	207	0.051	100	0.027	53	0.028	335	0.024	261	0.026	173	0.012	108
DCP16	.900	-0.029	0.121	21	0.060	291	0.047	194	0.028	97	0.017	43	0.025	333	0.023	241	0.023	177	0.013	97
DCP17	.965	-0.075	0.021	42	0.046	279	0.025	217	0.012	130	0.007	86	0.015	353	0.013	260	0.013	182	0.011	100

TUNEL HZ	PRTVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.96	0.087	0.498	15.32	0.0	7.51	12177.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
133.9	46927.	0.64E 07	-0.141	1.636	16.38	-0.00106	1.135	0.0
(439.4)	(980.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.512	10.329	0	0.041	358	0.163	347	0.079	16	0.060	315	0.129	217	0.076	114	0.042	45	0.009	358
CN		0.638	8.623	12	0.202	31	0.386	325	0.066	296	0.036	212	0.022	170	0.030	114	0.024	47	0.016	337
CM		-0.027	0.046	228	0.056	118	0.022	36	0.011	22	0.016	330	0.011	267	0.009	245	0.011	178	0.007	112
DCP 1	.010	2.336	5.117	344	1.613	77	0.934	34	0.297	0	0.310	349	0.204	298	0.132	311	0.111	241	0.065	224
DCP 2	.020	1.801	2.362	353	1.290	70	0.538	52	0.296	11	0.221	340	0.161	296	0.093	276	0.077	223	0.062	227
DCP 3	.030	1.750	1.824	352	1.240	72	0.643	22	0.294	342	0.166	324	0.197	267	0.110	253	0.109	196	0.061	173
DCP 4	.049	1.702	1.619	3	1.063	59	0.459	1	0.169	326	0.125	307	0.116	253	0.053	195	0.063	168	0.030	126
DCP 5	.074	1.505	1.336	3	0.911	52	0.356	349	0.110	319	0.103	297	0.099	237	0.050	166	0.048	150	0.036	105
DCP 6	.099	1.449	1.158	0	0.777	46	0.282	342	0.093	313	0.092	269	0.095	227	0.055	154	0.044	137	0.033	91
DCP 7	.149	1.153	1.010	13	0.583	37	0.238	379	0.065	332	0.085	259	0.071	205	0.049	146	0.042	118	0.026	54
DCP 8	.200	0.966	0.935	13	0.461	36	0.165	331	0.069	302	0.083	252	0.064	203	0.053	151	0.039	111	0.031	50
DCP 9	.250	0.664	0.826	13	0.414	27	0.142	321	0.091	269	0.090	232	0.068	185	0.064	134	0.054	97	0.044	45
DCP10	.300	0.777	0.728	15	0.353	23	0.125	316	0.094	276	0.387	215	0.057	170	0.059	127	0.060	83	0.048	21
DCP11	.399	0.600	0.656	20	0.280	17	0.368	302	0.069	289	0.376	214	0.068	166	0.063	130	0.063	76	0.045	14
DCP12	.571	0.522	0.556	22	0.223	6	0.069	278	0.050	266	0.089	192	0.042	141	0.054	112	0.055	45	0.045	343
DCP13	.602	0.434	0.456	25	0.167	357	0.067	256	0.042	236	0.065	168	0.046	107	0.045	90	0.056	18	0.042	308
DCP14	.731	0.416	0.341	29	0.151	345	0.073	227	0.030	206	0.060	152	0.043	82	0.040	60	0.057	348	0.042	277
DCP15	.800	0.254	0.277	26	0.125	321	0.066	270	0.058	196	0.061	137	0.046	69	0.032	39	0.048	336	0.032	267
DCP16	.900	0.016	0.178	20	0.091	330	0.045	229	0.035	193	0.042	121	0.028	59	0.030	27	0.036	322	0.024	267
DCP17	.965	-0.327	0.051	24	0.046	291	0.019	243	0.025	215	0.020	135	0.009	76	0.009	45	0.016	341	0.008	249

FORCED PITCHING OSCILLATION AIRFOIL NLF 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.7	22.97	3.399	0.396	13.25	0.0	9.99	12177.5	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TPD	EXT DAMP
135.7	46860.	0.66E 07	-0.223	1.739	17.13	-0.00131	1.404	0.0
(438.5)	(978.7)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		5.990	10.254 3	0.043 358	0.172 347	0.091 96	3.010 42	3.141 320	0.221 175	0.058 123	0.033 49
CN		0.763	3.509 26	0.076 358	0.045 313	0.021 300	0.097 248	0.044 182	0.008 162	0.016 115	
CM		-0.337	0.069 219	0.044 125	0.020 48	0.022 57	0.011 17	3.016 4	0.012 312	0.010 251	0.039 240
DCP 1	.010	2.970	1.648 340	1.820 42	0.673 49	0.409 60	0.274 40	0.226 28	0.162 35	0.083 325	0.074 4
DCP 2	.020	2.457	1.380 355	1.443 76	0.496 58	0.275 49	3.186 48	0.751 19	0.089 27	0.112 324	0.050 329
DCP 3	.030	2.148	0.950 353	1.381 78	0.478 51	0.246 60	0.287 43	3.257 356	0.085 356	0.116 324	0.119 306
DCP 4	.040	2.051	0.866 14	1.146 63	0.390 19	0.241 99	0.157 5	0.154 339	0.065 277	0.074 265	0.050 257
DCP 5	.074	1.440	0.716 23	0.976 51	0.271 13	3.190 42	0.139 323	0.164 356	0.044 217	0.112 234	0.075 273
DCP 6	.099	1.142	0.708 27	0.877 52	0.161 29	3.183 24	0.104 337	0.138 326	0.084 251	0.064 242	0.057 222
DCP 7	.149	0.941	0.751 28	0.677 41	0.134 16	0.148 0	0.087 316	0.105 304	0.097 228	0.055 223	0.056 192
DCP 8	.200	1.194	0.700 29	0.532 42	0.147 16	3.127 342	0.067 313	0.098 298	0.094 224	3.045 229	0.055 193
DCP 9	.250	1.122	0.681 27	0.430 32	0.134 357	0.131 316	0.055 298	3.094 274	0.098 205	0.050 198	0.058 151
DCP10	.300	0.919	0.671 28	0.359 29	0.117 357	0.096 308	0.046 292	3.087 269	0.092 199	0.042 189	3.052 148
DCP11	.399	0.794	0.603 31	0.297 26	0.098 349	5.089 297	0.039 290	3.073 263	0.084 204	0.038 188	0.050 146
DCP12	.501	0.636	0.546 32	0.243 11	0.080 336	0.078 277	0.033 256	0.067 239	0.077 187	0.034 144	0.051 117
DCP13	.600	0.531	0.480 33	0.208 357	0.069 332	0.078 256	3.036 215	0.063 209	0.071 156	0.038 95	0.046 83
DCP14	.701	0.482	0.391 37	3.195 342	0.062 274	3.078 239	0.040 188	3.063 184	0.068 125	0.048 64	0.050 45
DCP15	.800	0.320	0.194 31	0.155 329	0.068 267	0.080 228	0.043 181	0.064 166	0.062 103	0.049 46	0.044 23
DCP16	.900	0.353	0.272 22	0.136 312	0.051 271	3.051 217	0.023 182	0.040 160	3.028 90	0.029 46	0.025 18
DCP17	.969	-0.015	0.079 24	3.048 313	0.036 296	0.028 231	3.013 198	0.019 164	0.017 114	0.021 45	0.012 38

FORCED PITCHING OSCILLATION AIRFOIL NLF 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	45.64	0.171	0.400	11.06	0.0	0.00	12178.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TPD	EXT DAMP
135.9	48043.	0.66E 07	-0.096	1.005	11.33	-0.00082	0.916	0.0
(446.0)	(1003.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.004	11.064 0	1.193 355	0.176 330	0.054 208	0.071 178	0.051 107	0.040 128	3.040 199	0.010 172
CN		0.160	0.905 1	5.113 41	0.032 67	0.020 152	0.013 189	0.005 207	0.003 203	7.003 194	0.034 163
CM		-0.012	0.045 291	0.015 251	0.012 253	0.011 288	0.005 310	0.003 15	0.001 54	0.001 227	0.002 316
DCP 1	.010	0.540	0.009 350	1.319 230	0.874 270	0.433 352	0.031 184	0.242 316	0.278 3	0.106 84	0.049 45
DCP 2	.020	0.277	1.856 355	0.303 236	0.514 289	0.265 321	0.027 50	0.070 293	3.103 350	0.108 68	0.049 104
DCP 3	.030	0.206	3.811 352	0.174 4	0.178 295	0.121 318	0.060 107	0.051 166	0.015 292	0.018 180	0.323 230
DCP 4	.040	0.437	9.123 354	0.990 53	0.176 256	3.191 208	0.072 15	0.060 115	0.045 240	0.044 334	0.041 81
DCP 5	.074	0.399	2.694 353	0.240 41	0.074 192	0.144 254	0.057 326	0.041 82	0.043 208	0.050 296	0.046 35
DCP 6	.099	0.422	2.300 354	0.269 42	0.061 152	0.107 241	3.056 308	0.040 74	0.041 180	0.045 268	0.029 358
DCP 7	.149	0.258	1.819 356	0.299 40	0.114 116	0.102 205	0.054 260	0.025 42	0.033 164	0.048 236	0.031 309
DCP 8	.200	0.217	1.461 0	0.251 44	0.105 104	0.079 194	0.054 258	0.014 11	0.027 150	0.046 234	0.037 294
DCP 9	.250	0.166	1.292 356	0.257 32	0.121 80	0.079 158	0.054 215	0.039 309	3.031 172	0.044 169	0.035 222
DCP10	.300	0.159	1.377 357	0.235 28	0.127 66	0.084 133	0.058 190	0.021 245	0.015 57	0.030 140	0.035 186
DCP11	.399	0.158	0.833 7	0.168 17	0.096 61	0.070 123	0.043 181	3.025 236	0.007 319	0.014 123	0.025 185
DCP12	.501	0.137	0.617 13	0.139 41	0.057 53	0.064 96	3.026 142	0.019 194	0.005 277	0.007 90	0.016 137
DCP13	.600	0.155	0.469 21	0.087 55	0.047 55	0.034 101	0.015 156	0.012 216	0.008 297	0.013 35	0.007 109
DCP14	.701	0.214	0.326 27	0.074 60	3.033 49	7.027 89	0.022 110	3.011 198	0.011 251	0.009 350	0.011 76
DCP15	.800	0.104	0.207 41	0.055 79	0.026 70	0.027 97	0.014 87	3.039 158	0.007 212	0.002 331	0.003 120
DCP16	.900	-0.060	0.107 80	0.056 114	0.018 140	0.019 119	0.010 107	0.007 146	0.007 122	0.005 356	0.004 97
DCP17	.969	-0.039	0.056 137	0.022 131	0.014 110	0.022 148	0.007 107	0.039 194	0.006 308	0.004 32	0.004 46

	TUNED HZ	DRIVE HZ	K	MACH NO	DFL.ALPHA	DFL.H	ALPHA.O	TEST POINT	CYCLES ANALYSFD
	0.0	45.47	0.172	0.398	11.07	0.0	2.48	12179.2	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	134.8	47478.	0.64E 07	-0.076	1.229	11.60	-0.00093	1.023	0.0
	(442.3)	(991.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RFS 0	RFS 1 PHI	RFS 2 PHI	RFS 3 PHI	RFS 4 PHI	RFS 5 PHI	RFS 6 PHI	RFS 7 PHI	RFS 8 PHI	RFS 9 PHI
ALPHA		2.483	11.066 3	1.198 357	0.406 325	0.034 310	0.061 186	0.091 112	0.030 117	0.040 197	0.005 158
CN		0.337	0.850 4	0.123 9	0.013 250	0.007 330	0.014 278	0.006 111	0.004 20	0.005 273	0.003 224
CM		-0.009	0.035 284	0.004 304	0.010 319	0.007 177	0.006 71	0.002 309	0.002 171	0.001 109	0.001 101
DCP 1	.010	0.656	5.490 348	0.820 75	0.774 318	0.455 271	0.454 102	0.291 88	0.170 176	0.023 85	0.137 306
DCP 2	.020	0.725	4.300 353	0.658 16	0.179 316	0.272 233	0.131 149	0.151 63	0.075 24	0.063 285	0.050 267
DCP 3	.030	0.857	3.878 352	0.652 11	0.171 304	0.244 206	0.090 126	0.124 32	0.072 306	0.102 756	0.029 183
DCP 4	.040	0.981	3.123 353	0.673 2	0.131 307	0.113 199	0.007 114	0.066 340	0.025 333	0.027 166	0.049 164
CCP 5	.074	0.961	2.560 353	0.336 354	0.079 237	0.051 149	0.039 344	0.047 285	0.019 170	0.012 101	0.018 117
DCP 6	.099	0.894	2.122 355	0.313 2	0.069 290	0.056 152	0.028 350	0.049 287	0.017 188	0.016 91	0.017 90
PCP 7	.149	0.686	1.629 357	0.231 353	0.053 249	0.045 113	0.049 343	0.026 259	0.013 135	0.012 229	0.020 152
DCP 8	.200	0.557	1.334 3	0.179 0	0.032 236	0.034 94	0.044 334	0.021 229	0.013 128	0.006 80	0.005 156
DCP 9	.250	0.482	1.155 1	0.149 351	0.034 170	0.040 46	0.048 289	0.016 179	0.001 113	0.001 121	0.007 11
DCP10	.300	0.431	0.955 3	0.125 356	0.025 149	0.038 15	0.044 279	0.021 173	0.014 63	0.010 263	0.002 271
DCP11	.399	0.346	0.744 14	0.132 16	0.027 137	0.030 24	0.035 293	0.018 196	0.011 48	0.014 335	0.009 251
DCP12	.501	0.260	0.588 19	0.087 18	0.023 151	0.024 4	0.028 267	0.017 144	0.014 19	0.006 309	0.007 249
DCP13	.600	0.223	0.444 20	0.076 29	0.018 160	0.022 0	0.026 262	0.014 104	0.015 348	0.006 286	0.005 261
CCP14	.701	0.245	0.309 41	0.074 31	0.032 170	0.021 4	0.023 247	0.019 132	0.011 334	0.005 239	0.001 42
DCP15	.800	0.116	0.210 52	0.038 39	0.022 149	0.027 332	0.019 224	0.012 64	0.009 294	0.003 200	0.007 301
DCP16	.900	-0.063	0.101 67	0.016 189	0.020 137	0.025 300	0.013 197	0.003 75	0.002 51	0.012 297	0.007 121
DCP17	.969	-0.050	0.045 131	0.016 238	0.017 148	0.012 303	0.008 218	0.002 351	0.006 351	0.004 200	0.009 263

	TUNED HZ	DRIVE HZ	K	MACH NO	DFL.ALPHA	DFL.H	ALPHA.O	TEST POINT	CYCLES ANALYSFD
	0.0	45.56	0.173	0.396	11.00	0.0	4.91	12179.3	20

	V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	134.0	47105.	0.64E 07	-0.176	1.518	16.08	-0.00069	3.761	0.0
	(439.7)	(983.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RFS 0	RFS 1 PHI	RFS 2 PHI	RFS 3 PHI	RFS 4 PHI	RFS 5 PHI	RFS 6 PHI	RFS 7 PHI	RFS 8 PHI	RFS 9 PHI
ALPHA		4.914	11.000 0	1.247 0	0.460 319	0.087 78	0.042 159	0.023 172	0.035 109	0.043 173	0.012 143
CN		0.489	0.845 12	0.192 350	0.039 216	0.014 109	0.024 4	0.012 254	0.005 195	0.009 152	0.010 45
PM		-0.020	0.047 252	0.031 64	0.011 317	0.017 216	0.012 145	0.007 45	0.002 305	0.002 276	0.004 187
DCP 1	.010	1.292	4.494 349	1.444 43	0.728 358	0.487 269	0.202 216	0.086 230	0.131 177	0.141 112	0.064 52
DCP 2	.020	1.179	3.442 357	1.037 38	0.576 342	0.288 276	0.148 247	0.142 196	0.119 141	0.091 92	0.059 42
DCP 3	.030	1.149	2.732 359	1.041 37	0.646 329	0.342 252	0.121 198	0.049 179	0.123 131	0.121 71	0.092 7
DCP 4	.040	1.358	2.578 0	0.762 20	0.493 311	0.195 225	0.057 137	0.010 158	0.044 114	0.040 58	0.040 337
CCP 5	.074	1.264	2.117 2	0.684 12	0.286 297	0.167 208	0.052 87	0.039 114	0.095 21	0.042 351	0.014 227
PCP 6	.099	1.166	1.912 4	0.562 11	0.243 298	0.110 191	0.037 85	0.014 154	0.032 51	0.026 310	0.016 253
PCP 7	.149	0.931	1.505 7	0.443 355	0.182 260	0.093 156	0.040 82	0.036 70	0.046 354	0.018 293	0.011 196
DCP 8	.200	0.782	1.295 11	0.370 354	0.193 250	0.092 148	0.051 83	0.047 41	0.037 323	0.030 236	0.033 227
DCP 9	.290	0.687	1.164 11	0.330 339	0.143 221	0.074 140	0.099 67	0.062 0	0.044 287	0.038 216	0.018 159
DCP10	.300	0.625	1.010 12	0.268 331	0.119 202	0.055 119	0.058 338	0.058 338	0.043 255	0.029 200	0.021 116
DCP11	.399	0.538	0.875 20	0.201 327	0.115 196	0.061 104	0.061 43	0.050 319	0.039 263	0.040 213	0.038 171
DCP12	.501	0.413	0.699 22	0.149 315	0.111 163	0.061 70	0.060 10	0.047 280	0.028 212	0.029 162	0.040 86
DCP13	.600	0.332	0.541 29	0.107 310	0.106 148	0.067 48	0.064 337	0.066 241	0.021 165	0.027 114	0.043 48
DCP14	.701	0.329	0.398 35	0.076 290	0.138 129	0.069 23	0.057 315	0.047 211	0.073 123	0.020 84	0.035 2
DCP15	.808	0.187	0.277 35	0.074 251	0.097 121	0.057 19	0.047 301	0.036 202	0.022 95	0.019 54	0.039 314
DCP16	.900	-0.028	0.141 91	0.069 245	0.061 120	0.040 7	0.040 296	0.032 168	0.023 68	0.018 31	0.027 293
DCP17	.969	-0.042	0.024 57	0.048 252	0.029 132	0.017 7	0.020 283	0.018 207	0.012 81	0.014 38	0.009 303

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	RE NO HZ	C	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	45.67	0.174	0.905	11.85	0.0	7.50	12170.6	20

Y	C	AN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	48451	0.648 07	-0.234	1.743	16.75	-0.00069	0.567	0.0

HARMONIC ANALYSIS

DATA		RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

	DRIVE HZ	C	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	86.13	0.256	0.925	11.68	0.0	-0.10	12187.1	20

Y	C	AN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	48555.	0.648 07	-0.112	1.042	12.23	-3.00075	0.857	0.0

HARMONIC ANALYSIS

DATA		RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		-0.240	11.186 2	0.491 346	0.265 196	0.170 181	0.037 81	0.019 155	0.048 125	0.022 110	0.026 216
		0.114	3.699 6	0.189 28	0.008 352	0.007 18	0.016 93	0.010 130	0.007 135	0.001 244	0.003 238
		-0.015	0.040 296	0.024 299	0.015 174	0.011 200	0.036 254	0.003 273	0.002 299	0.001 299	0.001 85
		0.142	4.804 95	0.094 244	0.018 235	0.291 329	0.099 22	0.196 245	0.255 308	0.080 318	0.009 174
		0.121	7.802 357	0.141 281	0.537 244	0.196 296	0.081 19	0.085 252	0.115 285	0.062 14	0.077 68
		0.048	3.455 342	0.361 345	0.243 231	0.166 295	0.112 29	0.086 123	0.069 167	0.016 5	0.039 140
		0.246	3.128 355	0.287 7	0.268 226	0.190 255	0.057 351	0.084 123	0.055 216	0.078 299	0.044 26
		0.117	7.254 356	0.426 23	0.165 154	0.149 213	0.063 286	0.043 53	0.061 134	0.055 216	0.042 279
		0.168	1.174 356	0.441 23	0.166 119	0.130 119	0.047 244	0.025 9	0.057 104	0.049 177	0.044 239
		0.178	4.443 7	5.406 30	0.121 103	0.107 171	0.055 224	0.031 333	0.039 93	0.051 147	0.049 209
		0.137	1.279 359	0.393 18	0.117 66	0.397 121	0.095 162	0.017 242	0.027 36	0.034 86	0.032 131
		0.113	1.241 359	0.345 12	0.111 35	0.083 87	0.063 134	0.038 206	0.023 307	0.039 17	0.038 86
		0.120	0.826 15	0.272 32	0.048 29	0.072 80	0.070 136	0.037 199	0.015 284	0.029 23	0.021 92
		0.160	2.455 23	0.174 19	0.076 333	0.075 19	0.367 83	0.030 134	0.018 194	0.022 289	0.020 327
		0.124	0.486 33	0.142 48	0.060 330	0.048 6	0.033 58	0.021 103	0.013 169	0.016 228	0.022 273
		0.190	3.905 41	0.117 64	0.060 310	0.058 345	0.037 55	0.026 88	0.026 125	0.018 176	0.021 234
		0.264	0.246 50	0.089 74	0.034 338	0.032 340	0.024 19	0.023 69	0.015 99	0.011 97	0.005 220
		-0.057	0.141 83	0.088 51	0.022 334	0.026 0	0.007 357	0.007 35	0.006 67	0.003 331	0.004 72

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
7.0	68.53	0.255	0.400	11.05	0.0	2.49	12107.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
134.6	47666.	0.64E 07	-0.105	1.264	15.12	-0.00089	0.997	0.0
(441.5)	(995.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		2.493	11.855	0	2.158	349	0.200	184	0.119	163	0.318	148	0.022	150	0.031	139	0.026	118	0.012	212
CN		0.329	0.857	10	0.165	15	0.329	232	0.016	308	0.038	203	0.005	73	0.004	209	0.004	201	0.003	189
CM		-0.012	0.079	96	0.019	290	0.035	271	0.011	158	0.005	27	0.002	276	0.001	104	0.002	15	0.000	345
DCP 1	.010	0.665	4.505	344	0.840	1	0.655	288	0.573	256	0.359	65	0.401	50	0.125	111	0.051	104	0.057	269
DCP 2	.020	0.634	4.035	353	0.808	5	0.315	288	0.327	236	0.131	121	0.177	54	0.073	52	0.040	291	0.071	254
DCP 3	.030	0.781	3.340	352	0.774	359	0.171	248	0.257	195	0.127	95	0.132	23	0.051	256	0.097	230	0.020	249
DCP 4	.049	0.518	3.122	353	0.624	353	0.122	212	0.177	170	0.021	114	0.111	316	0.039	302	0.042	88	0.044	115
DCP 5	.099	0.895	2.104	356	0.456	359	0.073	208	0.087	151	0.011	75	0.070	264	0.024	220	0.023	44	0.027	78
DCP 6	.149	0.640	1.632	359	0.347	353	0.089	185	0.073	110	0.025	342	0.055	234	0.030	177	0.008	34	0.018	18
DCP 7	.200	0.533	1.342	8	0.255	3	0.087	199	0.047	77	0.033	358	0.035	229	0.039	184	0.004	215	0.013	355
DCP 8	.250	0.483	1.175	5	0.203	359	0.075	162	0.051	24	0.039	274	0.040	174	0.019	143	0.001	278	0.018	317
DCP 9	.300	0.430	0.587	7	0.183	1	0.060	151	0.057	0	0.034	261	0.039	146	0.026	102	0.012	330	0.018	202
DCP10	.399	0.362	0.797	24	0.140	37	0.036	169	0.052	352	0.037	251	0.025	138	0.010	17	0.010	297	0.017	191
DCP11	.501	0.266	0.636	31	0.122	50	0.016	157	0.057	339	0.029	217	0.032	108	0.013	347	0.028	237	0.024	211
DCP12	.600	0.228	0.507	42	0.116	53	0.010	180	0.033	330	0.023	215	0.015	56	0.012	285	0.011	191	0.007	188
DCP13	.701	0.251	0.391	53	0.106	55	0.016	211	0.043	321	0.018	184	0.023	54	0.016	258	0.019	177	0.005	295
DCP14	.800	0.112	0.280	64	0.073	66	0.009	83	0.033	327	0.017	165	0.013	15	0.005	255	0.009	92	0.006	92
DCP15	.900	-0.063	0.148	76	0.048	113	0.016	54	0.031	289	0.018	139	0.006	327	0.004	188	0.007	187	0.014	33

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	69.94	0.267	0.397	11.06	0.0	5.00	12107.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
133.4	46927.	0.64E 07	-0.122	1.515	17.91	-0.00062	0.691	0.0
(437.7)	(980.1)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		5.001	11.663	0	2.356	349	0.240	160	0.100	163	0.033	164	0.015	176	0.037	160	0.033	127	0.036	189
CN		0.516	0.908	14	0.162	356	0.037	156	0.011	24	0.017	269	0.011	145	0.008	260	0.001	280	0.005	136
CM		-0.025	0.062	256	0.038	2	0.028	268	0.018	158	0.012	59	0.008	301	0.006	168	0.004	84	0.006	340
DCP 1	.010	1.064	4.423	344	1.722	23	0.690	351	0.425	240	0.253	182	0.065	165	0.145	138	0.074	91	0.044	358
DCP 2	.020	1.129	3.338	357	1.273	29	0.568	334	0.355	259	0.196	191	0.117	136	0.083	142	0.069	87	0.078	38
DCP 3	.030	1.157	2.823	358	1.182	22	0.524	314	0.296	233	0.133	169	0.089	142	0.118	112	0.111	28	0.082	323
DCP 4	.049	1.197	2.677	0	0.885	9	0.314	294	0.201	210	0.096	141	0.061	93	0.028	66	0.042	348	0.037	316
DCP 5	.099	1.223	1.647	5	0.670	359	0.222	252	0.130	169	0.061	98	0.057	59	0.057	324	0.047	270	0.021	237
DCP 6	.149	0.986	1.424	7	0.513	346	0.208	217	0.115	130	0.070	68	0.067	5	0.079	264	0.038	182	0.010	66
DCP 7	.200	0.824	1.431	16	0.412	346	0.214	215	0.123	138	0.000	76	0.104	4	0.100	280	0.058	205	0.033	141
DCP 8	.240	0.741	1.305	12	0.337	183	0.207	183	0.115	101	0.099	24	0.102	310	0.100	219	0.053	132	0.053	60
DCP 9	.300	0.686	1.157	17	0.252	316	0.175	158	0.106	83	0.110	1	0.102	269	0.090	183	0.047	99	0.046	36
DCP10	.399	0.573	0.963	24	0.132	326	0.162	165	0.120	73	0.126	346	0.102	249	0.056	173	0.047	105	0.044	40
DCP11	.501	0.434	0.790	29	0.056	295	0.161	135	0.130	34	0.140	289	0.113	182	0.044	100	0.054	27	0.065	289
DCP12	.600	0.356	0.621	35	0.036	202	0.142	109	0.127	354	0.117	254	0.089	145	0.054	47	0.060	349	0.075	237
DCP13	.701	0.348	0.456	42	0.086	163	0.136	69	0.099	312	0.096	211	0.084	138	0.056	348	0.061	273	0.087	168
DCP14	.800	0.201	0.294	41	0.128	156	0.114	43	0.088	290	0.063	184	0.059	72	0.050	332	0.042	239	0.050	129
DCP15	.900	-0.029	0.142	44	0.091	155	0.084	32	0.068	270	0.053	158	0.042	28	0.033	291	0.035	197	0.032	70

FORCED PITCHING OSCILLATION　　　AIRFOIL　NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	70.78	0.271	0.396	11.59	0.0	7.57	12187.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
133.0	46722.	0.63E 07	-0.219	1.002	20.49	-0.00013	0.107	0.0
(436.2)	(975.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		7.574	11.59C 0	2.469 346	0.134 137	0.073 138	0.056 158	0.027 153	0.030 137	0.032 96	0.048 166
CN		0.744	0.940 15	0.150 355	0.012 136	0.013 215	0.013 108	0.019 318	0.014 171	0.010 33	0.011 187
CM		-0.06C	0.074 157	0.077 8	0.039 258	0.011 144	0.002 154	0.007 89	0.011 308	0.038 176	0.006 10
DCP 1	.010	1.570	2.672 351	2.095 70	0.047 336	0.152 284	0.164 284	0.191 229	0.111 191	0.047 147	0.018 167
DCP 2	.020	1.569	2.551 5	1.701 36	0.540 335	0.130 286	0.113 307	0.155 255	0.102 207	0.057 154	0.038 138
DCP 3	.030	1.583	2.326 8	1.488 32	0.493 326	0.156 281	0.115 275	0.146 225	0.091 172	0.062 125	0.058 90
DCP 4	.049	1.823	2.156 5	1.029 25	0.368 339	0.272 280	0.204 208	0.109 136	0.031 38	0.031 126	0.036 55
DCP 5	.059	1.554	1.714 13	0.408 7	0.197 282	0.122 252	0.160 188	0.134 134	0.062 16	0.023 343	0.030 331
DCP 6	.149	1.293	1.570 16	0.667 352	0.207 247	0.114 212	0.151 146	0.115 55	0.073 332	0.026 279	0.018 276
DCP 7	.200	1.079	1.475 24	0.599 354	0.253 250	0.153 200	0.150 143	0.111 67	0.064 12	0.053 309	0.024 258
DCP 8	.250	0.971	1.397 20	0.521 335	0.270 223	0.195 152	0.155 82	0.117 13	0.098 307	0.067 229	0.026 171
DCP 9	.300	0.981	1.200 20	0.449 328	0.281 209	0.214 128	0.147 52	0.105 341	0.091 281	0.065 190	0.025 108
DCP10	.309	0.812	1.115 26	0.295 318	0.268 199	0.223 117	0.156 33	0.109 328	0.110 265	0.111 173	0.063 93
DCP11	.531	0.715	0.984 19	0.202 249	0.227 147	0.164 71	0.128 346	0.124 278	0.155 190	0.131 86	0.050 348
DCP12	.600	0.251	0.823 12	0.299 202	0.269 95	0.139 356	0.082 294	0.113 248	0.172 146	0.166 33	0.10C 272
DCP13	.701	0.590	0.575 11	0.328 177	0.281 62	0.157 310	0.076 218	0.347 178	0.109 103	0.115 338	0.109 200
DCP14	.800	0.341	0.355 11	0.278 163	0.218 43	0.148 286	0.084 179	0.029 59	0.041 62	0.050 295	0.053 153
DCP15	.900	0.066	0.184 354	0.196 148	0.150 11	0.085 242	0.032 116	0.008 170	0.047 31	0.045 243	0.034 88

FORCED PITCHING OSCILLATION　　　AIRFOIL　NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	22.97	0.070	0.497	10.36	0.0	0.00	12181.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
167.2	73621.	0.80E 07	-0.071	1.187	10.60	-0.00095	1.260	0.0
(548.6)	(1537.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.004	10.365 0	0.958 351	0.151 325	0.060 17	0.055 141	0.034 125	0.051 189	0.024 128	0.017 3
CN		0.180	0.940 1	0.034 16	0.075 247	0.026 231	0.021 355	0.010 304	0.010 167	0.002 20	0.004 10
CM		-0.007	0.030 314	0.019 266	0.010 335	0.011 27	0.010 113	0.003 121	0.003 296	0.000 97	0.002 115
DCP 1	.010	0.387	4.606 353	1.035 262	0.962 320	0.127 332	0.082 183	0.259 41	0.017 95	0.037 35	0.051 40
DCP 2	.020	0.449	4.229 357	0.662 270	0.547 309	0.142 21	0.139 151	0.159 82	0.055 41	0.079 233	0.022 31
DCP 3	.030	0.429	4.188 356	0.542 276	0.331 291	0.143 40	0.128 149	0.082 103	0.084 34	0.073 255	0.009 187
DCP 4	.049	0.635	3.534 357	0.454 280	0.405 278	0.113 49	0.186 125	0.049 97	0.088 33	0.084 247	0.087 202
DCP 5	.074	0.481	2.801 357	0.136 352	0.294 279	0.040 247	0.153 101	0.029 129	0.044 287	0.027 195	0.028 224
DCP 6	.099	0.475	2.380 358	0.076 21	0.247 263	0.048 314	0.140 75	0.046 273	0.081 257	0.047 127	0.034 105
DCP 7	.149	0.312	1.845 358	0.104 47	0.159 233	0.048 273	0.081 32	0.035 254	0.058 224	0.034 76	0.035 56
DCP 8	.200	0.259	1.533 0	0.083 38	0.138 233	0.029 268	0.084 15	0.033 268	0.049 219	0.028 62	0.031 65
DCP 9	.250	0.220	1.356 358	0.079 40	0.113 194	0.016 234	0.084 355	0.044 234	0.041 165	0.039 33	0.026 7
DCP10	.300	0.205	1.129 359	0.069 43	0.108 192	0.025 217	0.066 329	0.028 241	0.037 168	0.028 9	0.023 4
DCP11	.349	0.189	0.846 4	0.073 56	0.062 210	0.042 233	0.051 321	0.009 314	0.023 136	0.011 348	0.009 338
DCP12	.501	0.138	0.616 7	0.066 63	0.047 225	0.046 224	0.034 315	0.013 336	0.013 128	0.010 325	0.004 324
DCP13	.600	0.141	0.448 11	0.066 67	0.039 233	0.050 217	0.027 307	0.016 317	0.011 117	0.005 258	0.008 336
DCP14	.701	0.202	0.285 17	0.076 75	0.033 247	0.050 219	0.022 307	0.020 346	0.014 112	0.004 191	0.008 275
DCP15	.800	0.089	0.157 27	0.051 78	0.022 225	0.043 202	0.024 286	0.019 309	0.009 97	0.003 136	0.007 250
DCP16	.900	-0.074	0.051 67	0.018 157	0.029 179	0.027 191	0.025 275	0.011 277	0.006 81	0.005 202	0.004 261
DCP17	.949	-0.050	0.019 144	0.016 103	0.030 170	0.012 200	0.016 277	0.004 209	0.037 96	0.006 207	0.004 292

FORCED PITCHING OSCILLATION　　AIRFOIL　NLR 1

TIMED HZ	TORQUE HT	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
5.5	29.00	0.175	0.495	10.92	0.0	2.49	12181.2	20

V	Q	RN	CH(MIN)	CH(MAX)	ALPHA.MAX	ATPD DAMP	TDB	EXT DAMP
166.2 (545.3)	73003. (1524.7)	5.79E 07	-0.368	1.326	12.75	-0.30093	1.238	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	AFS 0	AFS 1 PHI	AFS 2 PHI	AFS 3 PHI	AFS 4 PHI	AFS 5 PHI	AFS 6 PHI	AFS 7 PHI	AFS 8 PHI	AFS 9 PHI
ALPHA		7.499	13.323 0	0.085 151	0.153 328	0.015 205	0.046 201	0.091 118	0.048 265	0.019 181	0.028 44
CN		5.321	3.847 1	0.176 31	0.107 350	0.059 222	0.017 122	0.018 40	0.014 299	0.009 362	0.005 158
CM		-0.014	0.093 105	0.008 100	0.018 39	0.013 500	0.011 207	0.009 133	0.005 97	0.003 25	0.003 311
NCP 1	.010	5.820	4.836 351	0.170 44	1.024 394	0.435 329	0.213 163	0.118 159	0.117 125	0.076 87	0.079 18
NCP 2	.020	0.764	4.194 351	0.474 50	0.775 351	0.492 303	0.340 199	0.213 146	0.049 147	0.062 49	0.036 173
NCP 3	.030	0.787	3.460 351	0.560 45	0.511 2	0.477 297	0.349 239	0.237 191	0.099 134	0.101 69	0.051 354
NCP 4	.045	0.876	3.165 355	0.697 44	0.473 314	0.556 272	0.192 199	0.102 144	0.094 209	0.058 91	0.089 42
NCP 5	.074	0.818	2.440 356	0.671 41	1.294 344	0.289 242	0.109 251	0.106 112	0.080 165	0.071 192	0.083 49
NCP 6	.099	0.785	2.140 356	0.554 47	3.226 177	0.231 298	0.073 275	0.073 81	0.032 66	0.015 110	0.039 322
NCP 7	.149	0.612	1.647 358	0.400 12	0.184 297	0.191 220	0.060 152	0.090 54	0.051 8	0.018 294	0.033 248
NCP 8	.200	0.509	1.329 1	0.319 31	0.144 331	0.140 221	0.053 148	0.071 59	0.048 17	0.030 331	0.037 260
NCP 9	.299	0.442	1.162 0	0.254 19	0.144 280	0.122 199	0.060 112	0.068 29	0.054 331	0.046 268	0.019 202
NCP10	.300	0.407	0.962 1	0.210 19	0.126 277	0.091 188	0.050 95	0.052 17	0.049 319	0.028 248	0.020 196
NCP11	.350	0.344	0.793 6	0.148 23	3.107 265	0.062 182	0.044 77	0.035 199	0.034 290	0.017 236	0.014 184
NCP12	.501	0.297	0.567 8	0.121 22	0.090 274	0.048 176	0.038 58	0.030 147	0.029 281	0.015 275	0.015 191
NCP13	.600	0.727	0.409 16	0.095 77	0.095 271	0.041 169	0.036 46	0.029 125	0.023 274	0.036 225	0.011 131
NCP14	.701	0.299	0.294 20	0.077 94	5.068 260	0.030 190	0.095 29	0.026 352	0.014 248	0.008 209	0.015 120
NCP15	.800	0.134	0.183 79	0.093 7	0.095 243	0.030 159	0.013 12	0.023 289	0.014 260	0.008 108	0.013 109
NCP16	.900	-0.050	0.271 51	0.063 266	0.055 225	0.026 116	0.073 5	0.021 304	0.014 272	0.009 190	0.012 87
NCP17	.969	-0.338	0.326 141	0.098 261	0.133 219	0.011 144	0.011 41	0.013 333	0.014 273	0.003 351	0.008 98

FORCED PITCHING OSCILLATION　　AIRFOIL　NLR 1

TIMED HZ	TORQUE HT	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
5.5	29.01	0.071	0.496	11.22	0.0	4.93	12181.1	20

V	Q	RN	CH(MIN)	CH(MAX)	ALPHA.MAX	ATPD DAMP	TDB	EXT DAMP
165.6 (543.3)	72721. (1518.0)	5.79E 07	-0.134	1.441	13.99	-0.00009	1.756	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	AFS 0	AFS 1 PHI	AFS 2 PHI	AFS 3 PHI	AFS 4 PHI	AFS 5 PHI	AFS 6 PHI	AFS 7 PHI	AFS 8 PHI	AFS 9 PHI
ALPHA		4.434	10.230 0	0.046 342	0.120 327	0.045 17	0.025 329	0.113 239	0.110 112	0.047 97	0.098 322
CN		3.465	3.824 9	0.756 46	5.094 323	0.083 274	0.093 264	0.028 150	0.025 63	0.032 17	0.011 314
CM		.646	0.094 261	0.020 116	0.022 37	0.000 314	0.107 174	3.006 250	0.037 236	0.004 146	0.005 86
NCP 1	.010	1.912	4.935 348	1.040 62	0.710 359	0.943 329	0.163 2	0.194 208	0.144 221	0.070 234	0.208 349
NCP 2	.020	1.294	4.442 351	1.167 47	0.717 9	0.325 379	0.148 316	0.234 266	0.347 192	0.360 203	0.036 158
NCP 3	.030	1.200	3.306 350	1.071 70	3.003 22	0.814 308	0.165 205	0.248 279	0.113 203	0.360 156	0.061 146
NCP 4	.045	1.313	2.621 399	1.327 91	5.479 356	0.216 337	0.446 277	0.145 292	0.023 197	0.474 152	0.080 147
NCP 5	.074	1.308	1.771 303	0.814 99	3.414 19	0.153 249	0.263 292	0.016 74	0.131 169	0.074 273	0.086 67
NCP 6	.099	1.144	1.617 398	0.567 44	0.305 344	0.151 249	0.197 296	0.079 211	0.044 111	0.014 97	0.027 83
NCP 7	.149	0.504	1.739 1	0.547 30	0.237 327	0.140 297	0.047 234	0.070 176	0.065 103	0.043 99	0.036 17
NCP 8	.233	0.726	1.300 4	0.347 37	0.164 326	0.071 206	0.304 143	0.064 136	0.043 62	0.032 13	—
NCP 9	.250	0.609	0.975 5	0.116 26	0.145 314	0.084 214	0.308 278	0.053 143	0.054 77	0.038 35	0.035 330
NCP10	.322	0.508	0.897 3	0.286 24	5.126 303	0.038 203	0.044 16	1.052 144	0.098 72	0.039 27	0.034 349
NCP11	.390	0.441	0.698 11	0.285 24	0.305 247	0.036 207	0.059 233	1.609 197	0.065 63	0.033 31	0.051 320
NCP12	.521	0.172	0.508 1	0.161 18	3.371 274	0.065 270	0.360 207	0.040 123	0.037 65	0.023 48	0.024 306
NCP13	.600	0.313	0.417 7	0.153 16	5.764 288	0.013 142	0.317 166	0.030 132	0.031 48	0.084 362	0.321 283
NCP14	.731	0.310	0.378 24	0.122 18	0.059 244	0.020 126	0.314 157	0.009 136	0.025 73	0.016 305	0.021 250
NCP15	.800	0.170	0.213 25	3.086 362	0.064 243	0.035 133	0.017 117	0.047 61	0.020 8	0.013 262	0.018 244
NCP16	.900	-0.031	0.122 23	0.366 295	3.747 278	0.054 157	0.114 116	3.043 59	0.013 11	0.013 268	0.017 227
NCP17	.969	-0.338	0.021 97	0.304 283	0.321 276	0.047 174	0.336 195	0.004 73	0.313 94	0.010 317	0.044 249

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DFL.ALPHA	DFL.H	ALPHA.O	TEST POINT	CYCLES ANALYSIS
0.0	23.06	0.071	0.493	10.26	0.0	7.49	12181.4	70

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TAU	EXT DAMP
165.1	72213.	0.79E 07	-0.150	1.558	14.69	-0.59194	1.369	0.0
(541.6)	(1508.2)							

HARMONIC ANALYSIS

Data Type	H/C	RFS 0	RFS 1 PHI	RFS 2 PHI	RFS 3 PHI	RFS 4 PHI	RFS 5 PHI	RFS 6 PHI	RFS 7 PHI	RFS 8 PHI	RFS 9 PHI
ALPHA		7.494	10.296 0	0.940 357	0.125 357	0.084 56	0.365 348	0.089 338	0.271 212	0.100 113	0.043 54
CN		0.692	0.585 10	0.288 40	0.077 11	0.054 142	0.038 287	0.021 291	0.045 102	0.019 145	0.016 99
CM		-0.323	0.045 239	0.093 121	0.014 56	0.013 78	0.014 3	0.009 353	0.019 325	0.011 262	0.007 291
CP 1	.010	7.053	2.884 345	1.875 68	0.511 99	0.328 55	0.286 353	0.194 1	0.098 310	0.071 262	0.031 253
CP 2	.020	1.840	2.120 351	1.540 72	0.548 27	0.248 55	0.129 11	0.149 340	0.123 348	0.150 272	0.024 311
CP 3	.030	1.416	1.985 349	1.308 76	0.569 95	0.247 35	0.314 15	0.236 323	0.070 7	0.196 289	0.063 215
CP 4	.040	1.804	1.628 3	1.185 60	0.561 74	0.303 29	0.206 352	0.190 343	0.119 273	0.058 270	0.062 267
CP 5	.174	1.705	1.041 356	0.847 45	0.444 48	0.122 108	0.378 309	0.338 10	0.167 195	0.211 255	0.125 3
CP 6	.095	1.468	1.134 3	0.784 56	0.211 27	0.103 20	0.130 331	0.093 317	0.096 248	0.071 173	0.046 195
CP 7	.140	1.159	0.481 8	0.599 45	0.161 7	0.143 357	0.109 324	0.078 285	0.105 279	0.068 195	0.058 175
CP 8	.200	0.953	0.848 10	0.456 48	0.141 17	0.118 352	0.078 302	0.068 290	0.100 226	0.054 194	0.052 170
CP 9	.250	0.857	0.701 10	0.381 39	0.123 7	0.112 331	0.081 280	0.078 251	0.091 197	0.062 155	0.061 137
CP10	.300	0.770	0.698 11	0.315 33	0.069 7	0.095 325	0.063 265	0.050 245	0.079 195	0.040 199	0.098 123
CP11	.390	0.692	0.617 17	0.299 29	0.052 350	0.069 326	0.051 256	0.034 239	0.067 197	0.047 194	0.033 118
CP12	.501	0.505	0.516 20	0.209 18	0.031 319	0.054 312	0.041 234	0.025 220	0.057 182	0.044 110	0.027 91
CP13	.600	0.417	0.429 25	0.173 9	0.026 288	0.044 301	0.040 215	0.022 209	0.049 171	0.042 94	0.025 74
CP14	.701	0.401	0.308 31	0.145 399	0.030 242	0.036 285	0.043 199	0.020 165	0.039 150	0.037 74	0.027 49
CP15	.800	0.245	0.262 28	0.111 334	0.033 248	0.045 259	0.048 176	0.019 149	0.095 137	0.034 71	0.031 92
CP16	.900	0.302	0.176 21	0.086 311	0.037 267	0.041 246	0.032 174	0.022 167	0.079 118	0.029 68	0.027 29
CP17	.969	-0.034	0.049 28	0.045 300	0.014 287	0.021 258	0.011 194	0.011 209	0.017 199	0.014 83	0.013 26

FORCED PITCHING OSCILLATION AIRFOIL NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DFL.ALPHA	DFL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.08	0.073	0.493	9.96	0.0	6.62	12383.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TAU	EXT DAMP
199.2	103910.			1.450	9.75	-0.00046	1.574	0.0
(653.6)	(2170.2)							

HARMONIC ANALYSIS

Data Type	H/C	RFS 0	RFS 1 PHI	RFS 2 PHI	RFS 3 PHI	RFS 4 PHI	RFS 5 PHI	RFS 6 PHI	RFS 7 PHI	RFS 8 PHI	RFS 9 PHI
ALPHA											
CN											
CM											

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	29.21	0.352	0.700	10.23	0.0	2.42	12185.2	20

V	C	RN	CH(MIN)	CH(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
227.1	127936.	0.10E 08	-0.108	1.308	10.73	-0.00129	2.324	0.0
(745.1)	(2672.0)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		2.413	10.232	0	0.904	358	0.170	342	0.126	53	0.386	324	0.036	214	0.127	205	0.049	138	0.384	52
CN		0.273	0.924	0	0.244	44	0.064	315	0.071	297	0.037	249	0.012	176	0.018	202	0.013	146	0.011	57
CM		-0.031	0.038	268	0.022	115	0.012	42	0.013	56	0.011	18	0.002	241	0.003	314	0.005	235	0.005	210
DCP 1	.010	-0.053	3.990	350	0.443	32	0.494	323	0.254	349	0.069	287	0.112	344	0.076	84	0.025	1	0.044	28
DCP 2	.020	0.014	3.331	353	0.444	38	0.351	325	0.252	357	0.026	283	0.079	0	0.090	95	0.043	82	0.038	48
DCP 3	.070	0.108	3.124	352	0.515	40	0.273	325	0.239	2	0.063	144	0.037	24	0.042	92	0.043	97	0.029	51
DCP 4	.069	0.351	2.969	352	0.024	43	0.155	317	0.192	21	0.101	120	0.019	28	0.044	86	0.053	135	0.005	262
DCP 5	.095	0.597	2.447	351	0.727	58	0.129	353	0.185	345	0.067	129	0.089	159	0.035	130	0.051	142	0.356	219
DCP 6	.149	0.527	1.998	351	0.777	67	0.147	347	0.156	307	0.068	313	0.080	170	0.097	242	0.016	245	0.052	213
DCP 7	.200	0.453	1.905	357	0.716	71	0.142	313	0.173	300	0.234	323	0.100	164	0.108	266	0.046	272	0.022	43
DCP 8	.250	0.639	1.291	359	0.502	55	0.172	338	0.112	284	0.182	292	0.060	206	0.106	265	0.073	197	0.013	13
DCP 9	.330	0.391	1.124	2	0.384	43	0.120	358	0.140	278	0.120	282	0.065	243	0.065	226	0.086	211	0.034	99
DCP10	.399	0.324	0.884	9	0.244	33	0.028	11	0.099	266	0.064	251	0.028	320	0.034	171	0.042	214	0.034	78
DCP11	.501	0.281	0.675	12	0.172	15	0.037	303	0.074	271	0.071	223	0.016	288	0.032	151	0.027	121	0.024	79
DCP12	.600	0.260	0.909	17	0.136	0	0.056	270	0.055	273	0.068	203	0.009	183	0.028	152	0.041	90	0.031	57
DCP13	.701	0.303	0.320	27	0.102	354	0.062	239	0.038	269	0.052	196	0.017	86	0.018	120	0.039	62	0.025	27
DCP14	.800	0.199	0.231	28	0.075	311	0.061	232	0.038	250	0.045	169	0.029	73	0.010	75	0.030	35	0.018	337
DCP15	.900	-0.098	0.111	35	0.083	273	0.061	238	0.041	240	0.034	167	0.016	94	0.009	79	0.027	32	0.019	357

FCRCED PITCHING CSCILLATION   AIRFOIL   NLR 1

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
	C.0	23.20	0.052	0.698	10.17	0.0	4.97	12185.3	20

	V	G	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDA	EXT DAMP
	226.0	127256.	0.10E 08	-0.134	1.376	11.69	-0.00142	2.562	0.0
	(741.6)	(2657.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		4.970	10.171	0	0.915	4	0.105	343	0.095	70	0.066	87	0.066	7	0.056	337	0.070	197	0.037	171
CN		0.451	0.787	1	0.300	41	0.076	24	0.063	353	0.041	285	0.023	279	0.006	261	0.014	236	0.011	166
CM		-0.037	0.048	242	0.029	109	0.038	116	0.015	104	0.008	65	0.007	17	0.003	334	0.004	353	0.004	308
CP 1	.010	0.472	3.247	347	0.965	50	0.340	4	0.357	1	0.110	67	0.027	303	0.053	59	0.081	131	0.027	163
CP 2	.020	0.492	2.991	350	0.882	51	0.289	25	3.274	1	0.108	89	0.018	244	0.020	157	0.072	161	0.057	184
CP 3	.030	0.537	2.886	349	0.916	52	0.269	38	0.218	353	0.085	85	0.072	212	0.055	178	0.053	162	0.072	193
CP 4	.045	0.881	2.607	350	0.825	45	0.208	79	0.157	359	0.056	110	0.090	178	0.074	184	0.023	156	0.017	167
CP 5	.350	0.954	1.581	348	0.908	53	0.277	74	0.059	36	0.044	278	0.027	247	0.064	183	0.098	255	0.038	330
CP 6	.145	0.850	1.505	348	0.952	53	0.163	50	0.144	100	0.102	275	0.129	318	0.057	14	0.086	258	0.047	353
CP 7	.200	0.755	1.135	355	0.781	57	0.112	32	0.186	61	0.159	276	0.194	342	0.092	3	0.073	26	0.052	156
CP 8	.250	0.706	0.950	0	0.551	52	0.138	0	0.195	30	0.118	298	0.136	340	0.056	306	0.081	347	0.035	167
CP 9	.300	0.641	0.838	6	0.369	47	0.109	359	0.137	12	0.125	325	0.056	337	0.079	305	0.041	311	0.039	245
CP10	.395	0.528	0.739	11	0.213	38	0.124	3	0.074	342	0.065	335	0.023	222	0.022	293	0.021	201	0.020	288
CP11	.501	0.425	0.630	15	0.178	22	0.078	2	0.062	319	0.044	300	0.035	230	0.018	229	0.031	210	0.015	182
CP12	.600	0.367	0.527	15	0.153	5	0.055	4	0.084	308	0.042	264	0.043	229	0.022	193	0.033	206	0.029	160
CP13	.721	0.377	0.365	25	0.128	344	0.010	44	0.069	302	0.039	233	0.037	204	0.021	149	0.024	196	0.030	136
CP14	.800	0.215	0.295	22	0.117	313	0.009	249	0.058	282	0.044	213	0.032	186	0.023	127	0.015	146	0.023	108
CP15	.900	-0.025	0.182	15	0.097	302	0.033	294	0.053	270	0.043	222	0.031	183	0.020	130	0.016	139	0.018	92

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	39.70	0.251	0.234	5.25	0.0	13.89	12087.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
81.0	16447.	0.37E 07	-0.108	1.339	19.15	0.00006	-0.038	0.0
(264.2)	(343.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		13.887	5.246 0	0.306 359	0.036 144	0.087 263	0.052 45	0.014 353	0.029 136	0.024 204	0.017 70
CN		1.045	0.377 17	0.080 146	0.036 144	0.009 267	0.014 59	0.005 304	0.009 68	0.008 197	0.006 72
CM		-0.023	0.017 162	0.039 281	0.020 142	0.009 280	0.007 163	0.004 84	0.004 208	0.002 91	0.002 291
DCP 1	.010	4.060	1.485 49	0.706 326	0.287 231	0.180 219	0.154 98	0.023 100	0.084 212	0.086 183	0.022 130
DCP 2	.020	3.800	1.340 38	0.507 310	0.190 212	0.060 257	0.081 60	0.017 343	0.046 146	0.084 187	0.051 54
DCP 3	.030	3.733	1.364 25	0.451 282	0.271 157	0.132 335	0.053 274	0.112 168	0.109 45	0.097 235	0.033 148
DCP 4	.049	3.106	0.943 38	0.262 320	0.155 178	0.066 312	0.076 146	0.032 79	0.016 9	0.045 232	0.011 165
DCP 5	.074	2.673	0.851 30	0.253 282	0.149 140	0.068 321	0.031 105	0.030 53	0.008 107	0.055 175	0.023 59
DCP 6	.099	2.502	0.789 25	0.257 255	0.141 125	0.114 308	0.038 29	0.018 334	0.018 121	0.052 138	0.027 2
DCP 7	.149	2.015	0.690 13	0.272 216	0.150 78	0.092 340	0.028 340	0.017 126	0.018 237	0.021 77	0.013 240
DCP 8	.200	1.768	0.632 2	0.298 198	0.132 74	0.082 269	0.051 254	0.018 156	0.016 51	0.0.. 276	0.022 81
DCP 9	.250	1.392	0.609 7	0.233 163	0.098 40	0.035 294	0.083 163	0.051 94	0.021 5	0.029 212	0.013 74
DCP10	.300	1.187	0.499 6	0.206 148	0.097 17	0.045 240	0.061 124	0.032 13	0.021 202	0.022 131	0.029 25
DCP11	.399	0.983	0.415 13	0.203 141	0.100 8	0.036 210	0.060 111	0.031 4	0.033 184	0.023 61	0.011 14
DCP12	.501	0.767	0.325 16	0.188 125	0.099 340	0.031 184	0.050 66	0.035 300	0.022 104	0.014 338	0.021 284
DCP13	.600	0.685	0.257 19	0.170 115	0.086 333	0.039 116	0.046 31	0.038 287	0.041 77	0.009 351	0.010 188
DCP14	.701	0.511	0.172 21	0.143 96	0.093 303	0.032 112	0.048 345	0.027 226	0.034 38	0.017 260	0.021 150
DCP15	.800	0.323	0.092 4	0.133 85	0.081 305	0.039 85	0.053 319	0.017 229	0.032 7	0.019 275	0.016 101
DCP16	.900	0.088	0.055 335	0.086 71	0.038 274	0.042 53	0.028 298	0.015 173	0.011 262	0.023 192	0.016 94
DCP17	.969	0.020	0.040 337	0.042 54	0.029 25	0.024 75	0.024 303	0.007 8	0.023 322	0.016 192	0.014 21

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	39.11	0.293	0.198	5.38	0.0	15.01	12087.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
68.0	11893.	0.32E 07	-0.272	1.935	19.68	0.00215	-1.231	0.0
(223.0)	(248.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		15.005	5.384 0	0.276 352	0.023 243	0.072 293	0.047 29	0.017 79	0.025 192	0.003 266	0.001 181
CN		1.281	0.656 14	0.161 185	0.090 36	0.027 266	0.007 258	0.026 274	0.016 129	0.015 351	0.016 166
CM		-0.052	0.069 129	0.072 317	0.038 167	0.014 17	0.005 218	0.010 109	0.005 297	0.006 177	0.036 346
DCP 1	.010	4.273	2.369 67	0.727 4	0.320 5	0.428 269	0.216 225	0.141 168	0.062 135	0.089 38	0.067 320
DCP 2	.020	4.186	2.119 52	0.572 342	0.178 23	0.252 271	0.173 191	0.138 121	0.067 7	0.040 291	0.006 212
DCP 3	.030	4.133	2.152 45	0.776 317	0.190 162	0.086 138	0.127 25	0.137 246	0.071 162	0.054 68	0.078 6
DCP 4	.049	3.409	1.734 44	0.583 324	0.149 180	0.035 301	0.092 176	0.027 35	0.036 240	0.038 284	0.064 131
DCP 5	.074	2.963	1.594 37	0.527 296	0.187 153	0.007 272	0.055 111	0.053 319	0.010 128	0.046 271	0.050 139
DCP 6	.099	2.811	1.469 33	0.453 279	0.158 138	0.033 148	0.071 63	0.073 298	0.044 184	0.024 256	0.039 135
DCP 7	.149	2.232	1.288 24	0.388 250	0.144 112	0.084 91	0.082 2	0.067 263	0.037 158	0.017 164	0.043 50
DCP 8	.200	1.953	1.183 19	0.375 243	0.168 143	0.098 71	0.086 341	0.068 260	0.056 159	0.008 186	0.009 325
DCP 9	.250	1.762	1.046 8	0.374 211	0.198 131	0.152 9	0.103 283	0.079 208	0.050 101	0.030 3	0.034 298
DCP10	.300	1.565	0.928 2	0.405 192	0.232 71	0.154 335	0.115 242	0.061 154	0.046 38	0.024 347	0.016 216
DCP11	.399	1.302	0.771 2	0.384 181	0.217 58	0.134 321	0.125 227	0.068 100	0.036 334	0.005 289	0.036 194
DCP12	.501	1.017	0.610 359	0.348 166	0.213 33	0.122 277	0.075 174	0.062 18	0.021 262	0.016 257	0.033 156
DCP13	.600	0.887	0.479 354	0.345 152	0.215 15	0.127 243	0.084 113	0.100 326	0.030 168	0.027 87	0.015 280
DCP14	.701	0.689	0.344 345	0.306 132	0.203 340	0.115 191	0.059 49	0.076 287	0.043 149	0.048 35	0.044 205
DCP15	.800	0.441	0.245 323	0.282 119	0.176 323	0.107 153	0.056 8	0.070 252	0.036 116	0.042 337	0.042 151
DCP16	.900	0.127	0.160 314	0.142 105	0.113 307	0.059 149	0.041 356	0.039 268	0.029 103	0.033 345	0.043 110
DCP17	.969	0.051	0.072 321	0.029 107	0.041 307	0.026 161	0.045 5	0.034 234	0.031 66	0.033 310	0.005 217

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	39.15	0.297	0.197	5.39	0.0	16.08	12087.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
67.2	11707.	0.32E 07	-0.310	1.875	20.75	0.00253	-1.437	0.0
(220.5)	(244.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		16.079	5.389	0	0.298	351	0.026	236	0.073	299	0.045	48	0.013	52	0.028	197	0.007	257	0.024	178
CN		1.275	0.651	18	0.120	191	0.072	29	0.035	278	0.029	167	0.037	316	0.015	141	0.032	319	0.021	105
CM		-0.058	0.080	7	0.077	316	0.041	174	0.014	44	0.009	272	0.017	103	0.010	293	0.013	140	0.008	246
DCP 1	.010	4.191	2.030	77	0.751	20	0.451	30	0.434	305	0.330	271	0.138	258	0.089	239	0.105	88	0.095	152
DCP 2	.020	4.105	2.080	66	0.563	356	0.263	56	0.264	321	0.246	289	0.164	203	0.122	153	0.077	61	0.050	99
DCP 3	.030	4.046	2.218	56	0.825	334	0.175	252	0.215	193	0.126	93	0.084	340	0.114	285	0.105	213	0.092	122
DCP 4	.049	3.356	1.953	57	0.779	330	0.210	229	0.114	174	0.049	184	0.055	70	0.036	233	0.056	34	0.012	316
DCP 5	.074	2.977	1.737	48	0.655	311	0.198	207	0.102	157	0.027	153	0.075	19	0.047	251	0.054	351	0.040	246
DCP 6	.099	2.800	1.555	43	0.556	300	0.186	199	0.080	154	0.053	133	0.128	18	0.063	274	0.050	302	0.043	219
DCP 7	.149	2.251	1.367	31	0.465	281	0.196	187	0.066	106	0.086	129	0.136	351	0.055	241	0.047	281	0.049	140
DCP 8	.200	1.978	1.277	27	0.450	269	0.228	178	0.084	97	0.068	91	0.105	349	0.060	225	0.042	198	0.075	144
DCP 9	.250	1.785	1.085	9	0.412	215	0.221	102	0.155	15	0.097	306	0.096	226	0.084	102	0.023	11	0.057	273
DCP10	.300	1.600	0.963	1	0.417	198	0.243	84	0.212	335	0.124	238	0.097	143	0.085	49	0.081	309	0.046	172
DCP11	.399	1.315	0.792	2	0.358	187	0.223	68	0.191	337	0.156	214	0.094	89	0.035	350	0.022	247	0.046	75
DCP12	.501	1.038	0.606	356	0.339	168	0.213	41	0.113	292	0.133	184	0.076	13	0.047	271	0.030	186	0.048	80
DCP13	.600	0.897	0.448	352	0.336	151	0.228	9	0.130	251	0.114	125	0.121	317	0.029	197	0.042	55	0.015	31
DCP14	.701	0.694	0.357	345	0.329	130	0.226	343	0.153	204	0.073	58	0.104	276	0.094	138	0.097	355	0.032	137
DCP15	.800	0.472	0.281	320	0.310	120	0.211	330	0.092	159	0.051	47	0.075	255	0.063	140	0.077	328	0.035	32
DCP16	.900	0.157	0.162	311	0.192	91	0.120	306	0.051	177	0.049	11	0.092	293	0.059	90	0.075	295	0.055	36
DCP17	.969	0.042	0.033	318	0.011	330	0.040	344	0.020	254	0.067	82	0.071	256	0.050	46	0.076	278	0.058	134

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	39.72	0.278	0.210	6.17	0.0	13.19	12169.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
72.7	13818.	0.35E 07	-0.256	2.436	19.38	0.00113	-0.692	0.0
(238.6)	(288.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		13.190	6.169	0	0.603	2	0.116	300	0.058	354	0.018	107	0.015	192	0.028	271	0.027	320	0.021	224
CN		1.396	0.697	31	0.254	267	0.099	172	0.029	10	0.044	348	0.048	16	0.016	294	0.016	128	0.021	131
CM		-0.039	0.073	153	0.074	0	0.043	262	0.020	139	0.013	25	0.010	316	0.002	69	0.002	228	0.007	121
DCP 1	.010	4.124	2.294	77	1.376	2	0.404	313	0.383	271	0.202	171	0.090	73	0.038	285	0.135	268	0.115	182
DCP 2	.020	3.861	2.130	67	1.249	357	0.303	312	0.296	280	0.146	156	0.108	105	0.061	9	0.117	323	0.063	266
DCP 3	.030	3.764	2.100	65	1.361	346	0.307	275	0.239	275	0.193	172	0.077	121	0.084	81	0.161	345	0.119	317
DCP 4	.049	3.836	1.837	49	1.146	336	0.361	237	0.096	98	0.084	89	0.040	9	0.059	295	0.099	282	0.037	141
DCP 5	.074	4.782	1.594	82	0.968	235	1.388	224	1.197	260	1.376	326	1.350	16	0.660	71	0.516	89	0.818	127
DCP 6	.099	3.532	1.573	41	0.874	314	0.219	240	0.159	115	0.142	84	0.079	334	0.105	273	0.091	263	0.033	238
DCP 7	.149	2.970	1.445	37	0.785	296	0.181	222	0.246	96	0.157	65	0.106	322	0.155	275	0.065	234	0.043	206
DCP 8	.200	2.631	1.347	39	0.697	292	0.234	230	0.243	94	0.179	87	0.061	308	0.113	280	0.041	243	0.049	165
DCP 9	.250	1.480	1.036	22	0.448	286	0.224	197	0.221	127	0.133	45	0.131	9	0.111	308	0.096	217	0.077	162
DCP10	.300	1.455	0.903	19	0.385	273	0.234	179	0.197	96	0.126	21	0.120	341	0.119	252	0.115	158	0.071	80
DCP11	.399	1.231	0.823	22	0.381	260	0.249	172	0.228	63	0.164	2	0.101	287	0.086	225	0.122	133	0.077	74
DCP12	.501	1.017	0.652	16	0.336	237	0.237	135	0.207	35	0.131	311	0.104	215	0.058	135	0.068	63	0.065	341
DCP13	.600	0.892	0.520	10	0.318	210	0.208	101	0.180	347	0.111	268	0.113	156	0.050	73	0.047	11	0.064	291
DCP14	.701	0.726	0.380	1	0.326	184	0.202	70	0.164	305	0.101	210	0.119	98	0.041	17	0.045	290	0.036	240
DCP15	.800	0.453	0.265	353	0.230	178	0.111	62	0.143	291	0.075	193	0.110	78	0.063	344	0.014	233	0.018	74
DCP16	.900	0.127	0.145	0	0.147	158	0.078	65	0.102	266	0.045	156	0.031	39	0.013	249	0.015	190	0.013	164
DCP17	.969	0.121	0.150	322	0.178	161	0.113	45	0.147	233	0.084	133	0.085	320	0.075	201	0.061	35	0.055	245

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	39.70	0.280	0.209	8.10	0.0	14.84	12169.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
72.1	1.478.	0.34E 07	-0.345	2.378	23.16	0.00100	-0.609	0.0
(236.6)	(281.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		14.840	8.101 0	0.747 354	0.127 288	0.060 358	0.027 88	0.012 109	0.010 207	0.019 217	0.021 146
CN		1.246	0.905 29	0.206 266	0.112 157	0.020 356	0.010 20	0.046 35	0.018 52	0.009 95	0.025 95
CM		-0.070	0.112 162	0.094 7	0.052 255	0.016 163	0.011 3	0.006 23	0.003 274	0.005 65	0.004 234
DCP 1	.010	3.817	2.297 77	1.483 22	0.286 13	0.434 297	0.138 213	0.066 190	0.046 115	0.076 275	0.019 261
DCP 2	.020	3.413	2.280 69	1.348 18	0.266 347	0.328 301	0.098 206	0.068 168	0.101 136	0.075 82	0.133 31
DCP 3	.030	3.295	2.126 66	1.309 15	0.338 332	0.383 293	0.190 215	0.131 174	0.172 134	0.127 74	0.125 45
DCP 4	.049	3.184	1.996 48	1.084 0	0.424 266	0.163 199	0.126 125	0.155 70	0.079 1	0.028 321	0.035 326
DCP 5	.074	3.454	1.925 78	0.404 272	1.126 290	1.072 254	0.918 326	1.013 26	0.591 59	0.435 77	0.576 127
DCP 6	.099	2.665	1.738 40	0.728 334	0.299 241	0.177 182	0.188 111	0.152 52	0.082 3	0.078 315	0.081 245
DCP 7	.149	2.143	1.633 35	0.659 311	0.303 222	0.216 153	0.169 87	0.139 38	0.087 329	0.056 281	0.071 216
DCP 8	.200	1.878	1.568 34	0.629 307	0.334 215	0.197 140	0.149 100	0.138 41	0.080 328	0.058 299	0.029 234
DCP 9	.250	1.689	1.411 28	0.550 289	0.327 188	0.187 104	0.109 61	0.113 6	0.102 264	0.069 178	0.070 112
DCP10	.300	1.493	1.250 27	0.478 279	0.335 178	0.204 85	0.113 29	0.093 316	0.085 221	0.079 134	0.084 54
DCP11	.399	1.271	1.130 25	0.436 263	0.335 166	0.240 73	0.124 359	0.082 271	0.064 196	0.065 113	0.052 39
DCP12	.501	1.073	0.962 17	0.425 236	0.324 130	0.228 34	0.135 292	0.073 192	0.047 126	0.050 51	0.026 12
DCP13	.600	0.937	0.780 9	0.425 207	0.295 101	0.189 356	0.124 242	0.101 143	0.065 64	0.040 333	0.011 96
DCP14	.701	0.744	0.559 4	0.380 183	0.262 73	0.165 318	0.114 194	0.074 82	0.038 14	0.043 241	0.018 81
DCP15	.800	0.450	0.383 2	0.285 175	0.179 63	0.126 298	0.119 179	0.086 52	0.033 284	0.028 152	0.040 345
DCP16	.900	0.175	0.285 338	0.220 155	0.148 11	0.099 217	0.057 96	0.029 273	0.051 60	0.049 227	0.038 91
DCP17	.969	0.151	0.279 322	0.231 156	0.204 18	0.174 219	0.119 78	0.110 280	0.062 108	0.065 317	0.082 152

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	39.70	0.286	0.205	8.19	0.0	16.06	12169.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
70.7	13033.	0.34E 07	-0.383	2.501	24.50	0.00128	-0.765	0.0
(231.9)	(272.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		16.063	8.188 0	0.783 356	0.147 271	0.077 35	0.041 103	0.027 107	0.017 222	0.015 223	0.026 174
CN		1.317	0.912 33	0.205 287	0.120 178	0.014 83	0.021 16	0.036 38	0.029 86	0.009 328	0.024 136
CM		-0.081	0.141 163	0.099 17	0.056 272	0.020 204	0.002 324	0.015 57	0.007 321	0.006 136	0.006 31
DCP 1	.010	3.911	2.525 92	1.426 31	0.459 34	0.435 310	0.176 306	0.152 222	0.044 178	0.025 90	0.123 359
DCP 2	.020	3.487	2.383 82	1.327 28	0.405 19	0.324 317	0.120 315	0.133 218	0.097 199	0.126 156	0.116 94
DCP 3	.030	3.408	2.146 78	1.330 27	0.395 3	0.401 316	0.150 276	0.129 235	0.152 199	0.133 178	0.161 130
DCP 4	.049	3.294	1.847 60	1.179 16	0.409 299	0.229 272	0.197 192	0.188 127	0.084 92	0.058 40	0.073 1
DCP 5	.074	3.799	2.054 97	0.363 288	0.977 237	1.370 254	1.211 316	1.235 34	0.754 87	0.358 78	0.425 105
DCP 6	.099	2.772	1.693 49	0.820 352	0.347 271	0.220 223	0.226 150	0.137 95	0.073 91	0.091 30	0.090 331
DCP 7	.149	2.224	1.628 43	0.704 332	0.350 256	0.223 185	0.175 130	0.139 88	0.101 40	0.070 333	0.052 293
DCP 8	.200	1.929	1.553 43	0.698 331	0.421 244	0.189 180	0.203 138	0.176 85	0.096 22	0.079 324	0.053 315
DCP 9	.250	1.727	1.469 35	0.640 310	0.444 217	0.272 138	0.218 102	0.168 44	0.122 347	0.113 298	0.106 219
DCP10	.300	1.566	1.297 31	0.545 300	0.404 206	0.281 120	0.195 71	0.150 5	0.101 299	0.096 247	0.099 145
DCP11	.399	1.356	1.202 29	0.500 285	0.433 191	0.310 103	0.181 46	0.138 329	0.085 269	0.094 204	0.079 145
DCP12	.501	1.155	1.049 19	0.452 252	0.405 157	0.302 64	0.164 343	0.118 257	0.076 194	0.073 134	0.048 69
DCP13	.600	0.898	0.874 10	0.444 219	0.369 122	0.260 30	0.173 300	0.127 207	0.069 132	0.056 68	0.026 10
DCP14	.701	0.792	0.647 3	0.421 196	0.313 95	0.222 351	0.153 241	0.099 147	0.039 71	0.031 339	0.011 313
DCP15	.800	0.498	0.433 354	0.305 180	0.216 72	0.132 330	0.134 218	0.097 113	0.058 17	0.048 236	0.035 68
DCP16	.900	0.232	0.373 334	0.280 159	0.235 5	0.159 230	0.108 86	0.076 271	0.098 104	0.100 317	0.089 197
DCP17	.969	0.180	0.308 321	0.256 162	0.259 23	0.213 241	0.183 97	0.157 304	0.127 166	0.103 31	0.080 242

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	39.67	0.287	0.204	10.66	0.0	13.97	12173.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
70.5	12727.	0.33E 07	-0.397	2.417	24.85	0.00068	-0.401	0.3
(231.2)	(265.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		13.972	10.662 0	1.207 354	0.230 319	0.072 0	0.067 152	0.055 137	0.023 114	0.020 272	0.013 194
CN		1.179	1.059 26	0.174 282	0.098 139	0.042 50	0.037 82	0.008 92	0.018 109	0.028 314	0.021 141
CM		-0.098	0.122 165	0.116 4	0.055 252	0.017 153	0.006 319	0.004 12	0.011 270	0.016 123	0.012 335
DCP 1	.010	3.211	2.274 60	1.042 27	0.376 6	0.422 303	0.130 245	0.037 170	0.089 133	0.030 36	0.044 270
DCP 2	.020	2.975	2.429 54	1.026 23	0.372 352	0.429 300	0.143 242	0.120 184	0.172 134	0.162 77	0.131 23
DCP 3	.030	2.908	2.211 53	1.458 21	0.394 345	0.427 297	0.167 233	0.103 193	0.163 150	0.145 90	0.114 52
DCP 4	.049	2.675	2.143 46	1.217 10	0.281 305	0.259 274	0.137 179	0.092 117	0.070 111	0.066 65	0.063 28
DCP 5	.074	2.407	2.327 42	1.019 356	0.276 277	0.206 239	0.155 146	0.115 101	0.041 72	0.073 32	0.079 336
DCP 6	.099	2.375	1.940 39	0.875 347	0.270 264	0.213 219	0.171 129	0.135 88	0.097 51	0.078 5	0.077 296
DCP 7	.149	1.937	1.812 36	0.764 330	0.339 242	0.260 180	0.231 102	0.162 53	0.113 344	0.049 296	0.052 245
DCP 8	.200	1.740	1.727 36	0.704 326	0.380 232	0.282 166	0.226 101	0.196 46	0.124 328	0.082 281	0.067 229
DCP 9	.250	1.585	1.631 29	0.650 300	0.422 202	0.351 118	0.274 60	0.216 354	0.174 272	0.115 224	0.114 144
DCP10	.300	1.416	1.486 25	0.566 287	0.430 186	0.353 99	0.263 36	0.212 321	0.147 233	0.094 176	0.092 102
DCP11	.399	1.271	1.347 25	0.512 266	0.465 166	0.346 76	0.237 359	0.174 266	0.136 179	0.065 95	0.056 77
DCP12	.501	1.069	1.124 18	0.470 234	0.429 131	0.371 35	0.194 300	0.165 200	0.125 118	0.099 17	0.028 313
DCP13	.600	0.977	0.906 11	0.473 204	0.388 99	0.298 358	0.173 242	0.156 140	0.130 62	0.086 324	0.033 224
DCP14	.701	0.792	0.658 4	0.453 181	0.319 67	0.222 318	0.173 192	0.138 101	0.057 354	0.056 263	0.030 122
DCP15	.800	0.499	0.420 1	0.322 166	0.208 50	0.160 294	0.162 170	0.130 69	0.056 291	0.034 194	0.026 21
DCP16	.900	0.273	0.351 333	0.327 145	0.225 2	0.164 210	0.137 69	0.082 244	0.102 72	0.121 288	0.122 144
DCP17	.969	0.227	0.349 317	0.326 152	0.323 7	0.275 212	0.234 73	0.181 270	0.166 119	0.165 331	0.139 187

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.M	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	39.69	0.294	0.200	10.63	0.0	14.97	12173.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
68.8	12281.	0.33E 07	-0.380	2.562	25.84	0.00076	-0.441	0.0
(225.7)	(256.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		14.973	10.633 0	1.202 355	0.257 318	0.046 21	0.066 197	0.047 140	0.025 105	0.008 285	0.011 152
CN		1.242	1.079 29	0.183 303	0.079 171	0.036 99	0.041 73	0.013 1	0.027 136	0.017 351	0.036 213
CM		-0.100	0.137 166	3.113 8	0.049 262	0.011 176	0.010 206	0.012 79	0.015 304	0.010 143	0.004 23
DCP 1	.010	3.386	2.206 72	1.029 13	0.503 31	0.404 322	0.141 279	0.113 251	0.105 161	0.061 184	0.056 92
DCP 2	.020	3.092	2.338 65	1.049 31	0.472 16	0.442 318	0.150 261	0.126 241	0.143 185	0.136 155	0.173 96
DCP 3	.030	3.045	2.137 62	1.512 29	0.469 7	0.472 318	0.225 265	0.139 237	0.171 192	0.136 156	0.167 113
DCP 4	.049	2.819	2.366 53	1.319 19	0.352 327	0.309 293	0.211 215	0.130 148	0.066 116	0.060 133	0.074 49
DCP 5	.074	2.568	1.993 48	1.092 5	0.321 299	0.253 255	0.190 186	0.156 125	0.049 86	0.088 84	0.090 11
DCP 6	.099	2.519	1.946 45	0.938 355	0.313 285	0.238 231	0.202 162	0.163 111	0.117 82	0.112 43	0.103 345
DCP 7	.149	2.049	1.886 39	0.833 338	0.384 258	0.296 184	0.221 137	0.196 64	0.128 36	0.136 352	0.095 267
DCP 8	.200	1.861	1.790 40	0.809 333	0.462 252	0.320 184	0.251 136	0.243 79	0.129 10	0.106 334	0.061 276
DCP 9	.250	1.661	1.697 32	0.715 315	0.483 222	0.352 146	0.300 91	0.282 26	0.169 317	0.093 272	0.061 200
DCP10	.300	1.520	1.533 29	0.601 300	0.452 205	0.352 124	0.289 60	0.231 346	0.160 261	0.079 216	0.067 147
DCP11	.399	1.375	1.429 26	0.542 280	0.501 189	0.411 102	0.312 29	0.214 308	0.158 216	0.077 152	0.075 97
DCP12	.501	1.132	1.201 19	0.480 240	0.444 149	0.370 56	0.226 330	0.150 236	0.125 161	0.076 86	0.056 4
DCP13	.600	1.012	0.949 14	0.435 210	0.385 114	0.293 14	0.179 274	0.133 177	0.060 111	0.059 23	0.050 281
DCP14	.701	0.795	0.674 8	0.421 184	0.280 62	0.228 341	0.166 225	0.108 110	0.067 47	0.030 340	0.042 265
DCP15	.800	0.497	0.427 2	0.307 169	0.197 63	0.169 317	0.128 190	0.063 77	0.023 344	0.019 214	0.039 221
DCP16	.900	0.298	0.433 328	0.374 148	0.309 4	0.217 216	0.167 56	0.127 247	0.128 87	0.133 289	0.095 152
DCP17	.969	0.241	0.400 318	0.346 153	0.148 8	0.367 228	0.243 61	0.195 292	0.197 143	0.144 358	0.111 216

279

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	39.68	0.298	0.197	10.67	0.0	15.94	12173.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
67.8	11994.	0.32E 07	-0.404	2.680	26.81	0.00080	-0.459	0.0
(222.6)	(250.5)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		15.936	10.666 0	1.216 356	0.270 321	0.046 27	0.075 168	0.051 140	0.027 99	0.019 314	0.014 191
CN		1.294	1.096 31	0.195 318	0.079 190	0.036 138	0.043 96	0.018 335	0.023 140	0.025 6	0.018 186
CM		-0.106	0.152 168	0.112 15	0.047 280	0.006 250	0.015 222	0.020 100	0.017 314	0.016 168	0.010 25
DCP 1	.010	3.521	2.221 63	1.833 40	0.653 42	0.506 332	0.166 312	0.149 271	0.124 236	0.107 186	0.054 158
DCP 2	.020	3.183	2.277 74	1.644 39	0.604 31	0.484 333	0.191 303	0.128 257	0.118 235	0.177 180	0.159 141
DCP 3	.030	3.129	2.071 71	1.521 36	0.536 27	0.516 336	0.234 295	0.170 271	0.188 232	0.183 193	0.181 155
DCP 4	.049	2.917	2.070 60	1.342 24	0.379 349	0.375 310	0.233 245	0.149 192	0.120 174	0.135 125	0.098 92
DCP 5	.074	2.649	2.005 55	1.134 13	0.348 326	0.312 283	0.225 213	0.175 163	0.121 141	0.155 98	0.106 56
DCP 6	.099	2.578	1.927 51	0.994 5	0.357 307	0.282 261	0.235 197	0.190 145	0.118 119	0.166 84	0.115 39
DCP 7	.149	2.129	1.884 43	0.871 349	0.426 283	0.306 225	0.284 172	0.226 115	0.135 74	0.148 48	0.122 338
DCP 8	.200	1.922	1.627 43	0.843 345	0.481 269	0.310 212	0.317 168	0.256 105	0.144 59	0.157 17	0.096 313
DCP 9	.250	1.730	1.711 36	0.746 324	0.518 234	0.349 167	0.333 120	0.290 51	0.206 0	0.216 304	0.148 230
DCP10	.300	1.591	1.578 31	0.642 311	0.511 220	0.368 147	0.353 87	0.261 11	0.177 313	0.159 258	0.123 190
DCP11	.399	1.448	1.500 28	0.580 293	0.561 203	0.452 122	0.328 52	0.242 337	0.159 267	0.095 205	0.094 160
DCP12	.501	1.206	1.286 23	0.482 257	0.477 165	0.381 77	0.265 354	0.164 271	0.138 202	0.081 125	0.068 57
DCP 3	.600	1.034	0.991 14	0.418 219	0.382 129	0.306 37	0.204 299	0.130 207	0.098 150	0.092 64	0.045 343
DCP14	.701	0.826	0.712 9	0.416 190	0.312 96	0.216 355	0.156 245	0.087 151	0.063 62	0.047 339	0.006 299
DCP15	.800	0.523	0.467 2	0.323 174	0.221 72	0.140 315	0.117 210	0.071 98	0.027 39	0.012 254	0.015 100
DCP16	.900	0.325	0.472 331	0.382 154	0.311 18	0.251 226	0.195 73	0.177 267	0.164 111	0.162 333	0.105 188
DCP17	.969	0.249	0.380 322	0.335 159	0.333 13	0.300 232	0.235 93	0.224 303	0.196 148	0.187 12	0.142 231

TABLE   A.   ACCELERATION TARES

Transducer   P1

Average Orifice
Location, X/C = 0.010

Units: psi
$\Delta\alpha = 5^{\circ}$ (nominal)

F_D (Hz)	Steady	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
24.2	-0,006		RESULTANT	SINE COEFF	COS COEFF	PHASE
		1,	0,014	-0,014	0,001	174,800
		2,	0,027	-0,021	-0,017	218,300
		3,	0,042	0,042	0,001	1,312
		4,	0,020	0,016	0,012	35,800
		5,	0,015	0,014	-0,006	336,200
		6,	0,017	0,016	0,005	15,840
		7,	0,012	0,012	0,003	15,670
		8,	0,023	0,002	-0,023	274,700
		9,	0,004	0,004	0,000	6,444
48.0	0,027	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
		1,	0,140	-0,073	0,120	121,200
		2,	0,069	0,057	-0,038	326,800
		3,	0,018	0,018	0,002	4,738
		4,	0,079	0,064	0,047	36,200
		5,	0,010	0,009	0,003	15,320
		6,	0,018	0,014	0,011	37,460
		7,	0,013	0,011	0,007	32,480
		8,	0,011	0,010	-0,005	335,000
		9,	0,009	-0,004	0,008	116,000
56.2	-0,005	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
		1,	0,017	0,017	0,008	6,237
		2,	0,026	-0,026	-0,001	182,500
		3,	0,071	-0,069	-0,019	195,500
		4,	0,026	0,023	0,012	26,900
		5,	0,023	0,023	0,001	1,818
		6,	0,033	-0,008	0,032	103,800
		7,	0,006	-0,004	0,005	127,000
		8,	0,005	0,005	-0,000	356,500
		9,	0,011	-0,008	-0,008	222,460
71.8	0,003	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
		1,	0,038	-0,036	-0,012	198,800
		2,	0,019	0,004	0,018	77,590
		3,	0,029	-0,012	0,027	113,700
		4,	0,009	0,008	0,005	32,060
		5,	0,014	0,012	-0,006	332,200
		6,	0,012	0,002	0,012	74,800
		7,	0,006	-0,003	-0,005	242,400
		8,	0,008	0,006	0,005	36,420
		9,	0,006	0,005	-0,002	341,200

TABLE B. ACCELERATION TARES

Transducer P2

Acceleration Tares

Average Orifice
Location, X/C = 0.020

$\frac{\text{Units:}}{\Delta\alpha = 5^{\circ}}$ psi

F_D(Hz)	Steady	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
24.2	0.006	1.	0.015	-0.015	-0.002	186.400
		2.	0.017	-0.011	-0.013	229.700
		3.	0.033	0.033	0.002	2.767
		4.	0.017	0.014	0.010	34.470
		5.	0.019	0.019	-0.001	356.700
		6.	0.017	0.013	0.011	39.320
		7.	0.005	0.003	0.004	51.700
		8.	0.033	0.013	-0.030	294.360
		9.	0.008	0.008	0.002	16.940
48.0	0.033	1.	0.140	-0.092	0.105	131.200
		2.	0.059	0.047	-0.036	323.100
		3.	0.016	0.015	0.007	24.330
		4.	0.082	0.058	0.059	45.590
		5.	0.027	0.025	0.007	16.130
		6.	0.017	-0.001	0.017	92.480
		7.	0.024	0.020	-0.012	328.100
		8.	0.015	0.015	0.003	11.570
		9.	0.019	0.012	-0.015	310.400
56.2	-0.003	1.	0.100	0.100	0.003	1.497
		2.	0.037	-0.033	-0.018	208.400
		3.	0.080	-0.059	-0.054	222.200
		4.	0.025	0.022	0.012	27.360
		5.	0.018	0.012	0.013	47.370
		6.	0.039	-0.015	0.036	112.700
		7.	0.012	-0.002	0.012	101.000
		8.	0.015	0.015	-0.003	349.400
		9.	0.006	-0.002	-0.006	253.300
71.8	0.015	1.	0.023	-0.020	-0.009	204.600
		2.	0.026	-0.025	0.004	170.900
		3.	0.038	-0.023	0.030	128.000
		4.	0.015	0.015	0.000	1.536
		5.	0.010	-0.009	-0.006	215.100
		6.	0.019	0.005	0.019	75.450
		7.	0.014	0.006	-0.013	294.900
		8.	0.005	-0.005	0.001	167.300
		9.	0.019	-0.007	0.018	111.100

TABLE C. ACCELERATION TARES

Transducer P03		Acceleration Tares		
Average Orifice Location, X/C = 0.030		Units: psi $\Delta\alpha = 5°$		

F_D(Hz)	Steady	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
24.2	-0.004					
		1.	0.001	-0.000	0.001	103.800
		2.	0.012	-0.009	-0.008	222.100
		3.	0.018	0.018	0.004	14.270
		4.	0.011	0.007	0.008	51.150
		5.	0.006	0.006	-0.000	357.400
		6.	0.007	-0.005	0.005	131.600
		7.	0.005	0.000	0.005	89.190
		8.	0.019	0.007	-0.017	293.700
		9.	0.004	0.004	-0.001	347.200
48.0	0.016					
		1.	0.082	-0.049	0.065	127.000
		2.	0.041	0.037	-0.018	333.700
		3.	0.013	0.013	0.001	4.407
		4.	0.049	0.037	0.033	41.760
		5.	0.006	0.006	0.000	4.220
		6.	0.005	0.005	-0.000	359.900
		7.	0.006	0.005	-0.004	322.300
		8.	0.020	0.020	-0.003	352.500
		9.	0.009	-0.009	0.000	177.800
56.2	-0.007					
		1.	0.055	0.055	0.007	6.933
		2.	0.022	-0.022	0.002	175.700
		3.	0.051	-0.043	-0.027	212.500
		4.	0.015	0.012	0.010	38.100
		5.	0.013	0.013	0.002	10.800
		6.	0.019	-0.013	0.014	132.800
		7.	0.008	-0.008	0.004	154.800
		8.	0.002	-0.002	-0.002	229.200
		9.	0.009	-0.006	-0.006	224.700
71.8	0.015					
		1.	0.028	-0.026	-0.010	201.900
		2.	0.016	-0.013	0.010	141.300
		3.	0.019	-0.007	0.018	111.000
		4.	0.009	0.007	-0.007	314.900
		5.	0.006	-0.001	-0.006	255.900
		6.	0.020	-0.018	0.007	158.600
		7.	0.007	-0.004	-0.005	230.100
		8.	0.002	-0.001	0.002	108.300
		9.	0.003	0.003	-0.002	322.600

283

Transducer P64   Acceleration Tares

Average Orifice   Units: psi
Location, X/C = 0.049 $\overline{\Delta\alpha} = 5^o$

F_D (Hz)	Steady	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
24.2	-0.015	1.	0.014	-0.011	0.009	139.200
		2.	0.014	-0.013	-0.006	206.800
		3.	0.035	0.027	0.022	39.270
		4.	0.021	0.019	0.010	27.230
		5.	0.007	-0.006	-0.002	201.300
		6.	0.007	-0.007	0.001	169.300
		7.	0.012	0.002	0.012	82.090
		8.	0.032	0.004	-0.031	277.400
		9.	0.028	0.022	0.018	39.270
48.0	0.026	1.	0.068	-0.057	0.037	147.400
		2.	0.065	0.017	-0.063	285.500
		3.	0.039	0.014	-0.037	290.900
		4.	0.061	0.045	0.042	43.490
		5.	0.023	0.021	0.011	27.500
		6.	0.027	0.020	0.019	44.010
		7.	0.005	0.005	-0.001	352.700
		8.	0.023	0.019	0.014	36.260
		9.	0.006	-0.003	0.006	115.300
56.2	-0.022	1.	0.040	0.038	-0.013	341.200
		2.	0.034	-0.028	0.019	146.100
		3.	0.049	-0.036	-0.033	222.700
		4.	0.031	0.021	0.022	45.460
		5.	0.021	0.017	-0.012	323.900
		6.	0.012	-0.009	0.008	139.600
		7.	0.017	0.008	-0.015	297.900
		8.	0.045	0.042	-0.015	340.200
		9.	0.036	-0.027	-0.023	220.300
71.8	0.003	1.	0.028	-0.028	-0.000	180.300
		2.	0.025	-0.024	-0.004	190.400
		3.	0.044	-0.030	0.032	133.900
		4.	0.018	-0.000	-0.018	269.900
		5.	0.031	0.011	-0.029	291.400
		6.	0.015	0.007	0.014	65.960
		7.	0.029	0.029	-0.004	352.900
		8.	0.016	-0.011	0.011	133.200
		9.	0.015	-0.012	0.009	141.900

Transducer P05   Acceleration Tares

Average Orifice   Units: psi
Location, X/C = 0.074 $\overline{\Delta\alpha = 5}$°

F_D(Hz)	Steady	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
24.2	0.001	1.	0.014	-0.014	0.000	179.300
		2.	0.018	-0.011	-0.014	231.900
		3.	0.025	0.025	0.006	13.700
		4.	0.014	0.011	0.009	39.390
		5.	0.006	0.006	-0.001	348.900
		6.	0.005	0.005	0.000	0.537
		7.	0.002	-0.000	0.002	96.190
		8.	0.019	0.003	-0.018	280.600
		9.	0.006	0.002	0.005	69.520
48.0	0.022	1.	0.083	-0.052	0.065	128.700
		2.	0.032	0.026	-0.018	325.600
		3.	0.024	0.023	-0.007	343.400
		4.	0.056	0.037	0.042	48.350
		5.	0.010	0.010	0.003	17.740
		6.	0.015	0.015	0.003	10.420
		7.	0.007	0.006	0.002	21.120
		8.	0.012	0.012	-0.001	356.600
		9.	0.002	0.002	-0.002	310.200
56.2	0.003	1.	0.048	0.047	0.011	12.920
		2.	0.022	-0.021	-0.007	197.600
		3.	0.049	-0.041	-0.027	213.800
		4.	0.033	0.028	0.018	33.040
		5.	0.010	0.010	0.002	13.080
		6.	0.011	-0.011	0.003	164.900
		7.	0.013	0.004	0.012	72.470
		8.	0.005	0.002	0.005	64.270
		9.	0.005	-0.005	0.000	177.300
71.8	0.005	1.	0.028	-0.028	-0.002	183.200
		2.	0.022	-0.013	0.018	126.700
		3.	0.027	-0.019	0.020	133.100
		4.	0.011	0.011	-0.001	353.700
		5.	0.016	-0.004	-0.016	255.600
		6.	0.013	-0.011	0.006	145.100
		7.	0.012	-0.012	-0.001	164.000
		8.	0.006	0.006	-0.002	343.400
		9.	0.014	-0.014	-0.005	199.200

285

TABLE F. ACCELERATION TARES

Transducer P06   Acceleration Tares

Average Orifice
Location, X/C = 0.099

Units: psi
$\Delta\alpha = 5°$

F_D(Hz)	Steady	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
24.2	-0.015	1.	0.001	-0.001	-0.000	199.400
		2.	0.020	-0.016	-0.012	216.800
		3.	0.020	0.018	0.007	22.140
		4.	0.014	0.013	0.005	18.590
		5.	0.007	0.007	-0.002	346.400
		6.	0.003	0.001	0.002	63.350
		7.	0.006	0.004	0.004	46.890
		8.	0.016	0.003	-0.015	282.600
		9.	0.005	0.005	0.001	13.040
43.0	0.015	1.	0.095	-0.058	0.075	127.900
		2.	0.033	0.029	-0.016	331.400
		3.	0.019	0.018	-0.006	340.600
		4.	0.059	0.039	0.044	48.500
		5.	0.009	0.003	0.009	67.920
		6.	0.002	0.001	0.001	22.240
		7.	0.009	0.005	0.008	66.790
		8.	0.017	0.017	0.004	12.700
		9.	0.010	-0.002	0.009	100.100
56.2	-0.016	1.	0.064	0.064	0.008	6.796
		2.	0.023	-0.023	0.005	168.900
		3.	0.044	-0.042	-0.009	192.600
		4.	0.025	0.020	0.014	35.240
		5.	0.006	-0.001	0.006	97.010
		6.	0.023	-0.011	0.020	114.800
		7.	0.011	-0.000	0.011	90.680
		8.	0.014	0.014	-0.004	342.700
		9.	0.009	-0.009	-0.000	182.500
71.8	-0.005	1.	0.022	-0.022	-0.001	183.300
		2.	0.008	-0.007	0.004	150.900
		3.	0.024	-0.017	0.017	134.000
		4.	0.011	0.010	-0.003	343.200
		5.	0.008	0.007	-0.004	332.600
		6.	0.015	-0.015	0.002	173.700
		7.	0.015	0.000	-0.015	271.500
		8.	0.009	-0.009	-0.001	187.100
		9.	0.009	0.005	0.007	52.470

<u>Transducer P07</u>   <u>Acceleration Tares</u>

Average Orifice   <u>Units:</u> psi
Location, X/C = 0.149 $\overline{\Delta\alpha} = 5^\circ$

F_D(Hz)	Steady	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
24.2	-0.026	1.	0.009	-0.009	-0.001	167.100
		2.	0.014	-0.008	-0.011	234.300
		3.	0.018	0.016	0.009	28.720
		4.	0.010	0.007	0.008	47.920
		5.	0.005	0.005	0.000	0.547
		6.	0.005	0.004	0.004	46.650
		7.	0.013	0.000	0.013	84.290
		8.	0.017	0.001	-0.017	275.000
		9.	0.008	0.008	-0.001	350.300
48.0	-0.006	1.	0.096	-0.054	0.079	124.400
		2.	0.036	0.034	-0.012	340.100
		3.	0.015	0.014	-0.006	334.100
		4.	0.048	0.028	0.039	53.760
		5.	0.009	0.005	0.007	53.300
		6.	0.004	0.003	-0.002	328.900
		7.	0.010	0.007	0.007	44.290
		8.	0.012	0.011	0.005	25.850
		9.	0.003	0.002	-0.002	310.300
56.2	-0.023	1.	0.053	0.053	0.004	4.636
		2.	0.023	-0.022	-0.007	196.800
		3.	0.045	-0.041	-0.019	204.900
		4.	0.021	0.020	0.004	24.290
		5.	0.017	0.012	0.012	44.020
		6.	0.014	-0.009	0.011	128.500
		7.	0.010	0.001	0.010	86.810
		8.	0.009	-0.009	-0.002	194.200
		9.	0.004	0.000	0.004	84.680
71.8	-0.010	1.	0.036	-0.036	-0.006	188.400
		2.	0.013	-0.011	0.006	151.100
		3.	0.009	-0.007	0.006	140.400
		4.	0.005	0.004	0.003	32.510
		5.	0.013	-0.004	-0.012	252.400
		6.	0.017	-0.015	0.007	154.400
		7.	0.012	-0.012	-0.001	183.300
		8.	0.003	0.003	-0.001	348.500
		9.	0.007	-0.006	-0.003	208.700

Transducer P08   Acceleration Tares

Average Orifice   Units: psi
Location, X/C = 0.200 $\Delta \alpha = 5^\circ$

F_D(Hz)	Steady	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
24.2	0.005	1.	0.008	-0.008	0.001	171.200
		2.	0.022	-0.016	-0.015	224.300
		3.	0.026	0.022	0.013	31.940
		4.	0.011	0.011	-0.002	349.500
		5.	0.023	0.023	0.003	8.500
		6.	0.019	0.009	0.017	61.110
		7.	0.021	0.021	0.005	14.870
		8.	0.024	0.002	-0.024	274.900
		9.	0.008	-0.002	-0.007	255.300
48.0	0.035	1.	0.097	-0.046	0.085	118.400
		2.	0.052	0.049	-0.016	341.700
		3.	0.011	0.011	0.003	13.650
		4.	0.056	0.031	0.046	56.000
		5.	0.026	0.023	-0.014	329.000
		6.	0.010	0.010	-0.000	358.800
		7.	0.022	0.014	-0.017	309.500
		8.	0.022	0.020	-0.009	335.700
		9.	0.012	-0.007	-0.010	234.500
56.2	0.003	1.	0.065	0.061	0.023	20.630
		2.	0.034	-0.013	-0.031	247.500
		3.	0.031	-0.029	-0.009	196.900
		4.	0.017	0.010	0.014	52.870
		5.	0.007	-0.004	0.005	129.100
		6.	0.018	-0.011	0.014	128.900
		7.	0.012	0.005	0.012	76.560
		8.	0.009	0.006	-0.007	307.900
		9.	0.009	0.007	-0.005	326.500
71.8	0.021	1.	0.014	0.012	-0.007	329.300
		2.	0.005	-0.002	-0.005	245.500
		3.	0.010	-0.008	-0.007	220.900
		4.	0.012	-0.002	-0.012	259.100
		5.	0.016	-0.001	-0.016	264.900
		6.	0.009	0.008	0.004	24.430
		7.	0.013	0.009	0.010	49.650
		8.	0.009	-0.007	-0.006	225.300
		9.	0.023	-0.023	-0.006	194.400

288

CONTENTS

iii

TABLE I. ACCELERATION TARES

Transducer P09   Acceleration Tares

Average Orifice   Units: psi
Location, X/C = 0.250 $\Delta\alpha = 5°$

F_D(Hz)	Steady	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
24.2	-0.013	1.	0.003	-0.000	0.003	91.900
		2.	0.006	0.002	-0.006	288.000
		3.	0.013	-0.007	0.011	123.800
		4.	0.002	0.001	0.002	74.260
		5.	0.009	-0.007	0.006	140.100
		6.	0.002	0.001	-0.002	302.400
		7.	0.005	0.004	0.001	14.770
		8.	0.026	-0.025	0.007	163.800
		9.	0.005	-0.005	0.000	177.700
48.0	-0.012	1.	0.011	0.009	-0.006	325.200
		2.	0.004	0.004	-0.001	339.800
		3.	0.013	0.005	-0.012	294.400
		4.	0.134	-0.054	0.123	113.700
		5.	0.014	-0.003	0.014	104.300
		6.	0.015	-0.014	0.004	162.900
		7.	0.022	0.002	0.022	84.810
		8.	0.018	-0.018	-0.005	195.200
		9.	0.007	0.004	0.006	57.100
56.2	-0.008	1.	0.062	0.058	-0.021	340.200
		2.	0.015	-0.008	-0.012	235.200
		3.	0.031	0.007	-0.030	283.900
		4.	0.021	-0.002	0.021	95.290
		5.	0.012	0.006	0.010	61.990
		6.	0.007	-0.007	0.003	159.100
		7.	0.006	0.001	-0.006	283.100
		8.	0.021	0.011	0.018	58.920
		9.	0.004	-0.004	-0.001	198.700
71.8	-0.010	1.	0.038	0.027	-0.027	315.700
		2.	0.010	0.005	-0.008	301.400
		3.	0.006	0.002	0.006	71.420
		4.	0.013	-0.006	-0.012	243.700
		5.	0.006	-0.006	-0.003	205.100
		6.	0.015	0.015	0.004	13.400
		7.	0.014	0.013	-0.005	339.600
		8.	0.016	0.003	-0.015	281.800
		9.	0.003	-0.001	-0.003	255.100

Transducer P10   Acceleration Tares

Average Orifice   Units: psi
Location, X/C = 0.30 $\overline{\Delta \alpha = 5}$°

F_D(Hz)	Steady	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
24.2	0.009	1.	0.003	0.002	0.002	54.370
		2.	0.002	0.002	0.002	43.490
		3.	0.004	-0.002	0.003	117.500
		4.	0.005	0.002	0.005	71.070
		5.	0.001	0.000	0.001	74.910
		6.	0.003	0.003	0.000	6.036
		7.	0.002	0.002	-0.001	343.300
		8.	0.021	-0.020	0.007	161.800
		9.	0.007	-0.006	-0.005	217.900
48.0	0.003	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
		1.	0.007	0.003	-0.007	290.900
		2.	0.009	-0.005	-0.008	238.500
		3.	0.020	0.014	-0.015	313.500
		4.	0.112	-0.037	0.106	109.200
		5.	0.009	-0.006	0.007	131.200
		6.	0.015	-0.015	-0.005	197.600
		7.	0.017	0.004	0.017	77.210
		8.	0.013	-0.008	0.011	126.700
		9.	0.005	-0.002	0.005	117.000
56.2	0.004	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
		1.	0.058	0.054	-0.021	338.700
		2.	0.008	-0.005	-0.006	233.800
		3.	0.025	0.002	-0.025	275.100
		4.	0.018	0.001	0.018	86.490
		5.	0.003	-0.001	0.002	104.500
		6.	0.008	0.003	0.007	66.440
		7.	0.001	0.000	0.001	83.700
		8.	0.014	0.006	0.013	67.410
		9.	0.008	-0.008	-0.002	193.800
71.8	0.002	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
		1.	0.022	0.009	-0.020	294.100
		2.	0.007	-0.006	-0.004	217.900
		3.	0.011	0.010	0.003	16.150
		4.	0.012	-0.010	-0.005	204.500
		5.	0.007	-0.005	0.005	133.900
		6.	0.005	0.003	-0.004	311.400
		7.	0.007	0.007	-0.001	355.800
		8.	0.009	0.007	-0.007	314.100
		9.	0.003	0.002	0.002	39.810

TABLE   K.   ACCELERATION TARES

<u>Transducer P11</u>

Average Orifice
Location, X/C - 0.399

<u>Acceleration Tares</u>

Units: psi
$\Delta\alpha = 5^{\circ}$

F_D (Hz)	Steady	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
24.2	-0.021	1.	0.014	-0.012	0.007	150.300
		2.	0.008	0.008	-0.001	352.500
		3.	0.006	-0.001	0.006	95.260
		4.	0.008	-0.003	0.008	113.000
		5.	0.008	-0.005	-0.006	234.400
		6.	0.002	-0.002	0.000	174.200
		7.	0.008	0.008	-0.003	339.100
		8.	0.034	-0.033	0.004	173.200
		9.	0.011	-0.005	-0.010	243.500
48.0	-0.032	1.	0.042	-0.041	-0.007	189.400
		2.	0.011	0.003	0.011	75.020
		3.	0.020	-0.001	-0.019	268.200
		4.	0.157	-0.097	0.123	128.200
		5.	0.015	-0.011	0.011	132.900
		6.	0.013	-0.012	-0.005	202.400
		7.	0.034	-0.004	0.034	96.200
		8.	0.017	-0.007	0.015	114.200
		9.	0.006	-0.005	0.004	143.500
56.2	-0.021	1.	0.034	0.019	-0.028	304.100
		2.	0.004	0.004	0.001	12.150
		3.	0.029	0.000	-0.029	270.700
		4.	0.019	-0.008	0.017	113.600
		5.	0.012	-0.005	0.011	104.400
		6.	0.019	-0.012	0.015	128.700
		7.	0.007	-0.005	-0.006	228.800
		8.	0.032	-0.002	0.032	94.270
		9.	0.005	0.001	-0.005	276.400
71.8	-0.028	1.	0.080	-0.067	-0.043	212.600
		2.	0.028	0.025	-0.011	336.200
		3.	0.026	0.019	0.018	42.970
		4.	0.018	-0.017	-0.006	198.600
		5.	0.024	0.007	0.023	72.010
		6.	0.022	0.011	0.019	60.560
		7.	0.013	0.013	0.003	15.200
		8.	0.001	-0.001	-0.001	217.000
		9.	0.006	-0.006	-0.001	192.600

TABLE   L.   ACCELERATION TARES

Transducer P12

Average Orifice
Location, X/C = 0.501

Acceleration Tares

Units: psi
$\overline{\Delta\alpha = 5^\circ}$

F_D (Hz)	Steady	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
24.2	-0.010	1.	0.002	-0.000	0.002	100.500
		2.	0.005	0.005	0.002	27.030
		3.	0.005	-0.005	0.002	158.800
		4.	0.008	-0.000	0.008	90.490
		5.	0.002	0.001	0.001	40.530
		6.	0.003	0.003	0.000	4.264
		7.	0.001	0.000	-0.001	261.600
		8.	0.020	-0.020	0.003	171.400
		9.	0.009	-0.007	-0.005	216.100
48.0	-0.014	1.	0.017	0.017	0.005	16.380
		2.	0.007	-0.004	-0.005	233.300
		3.	0.020	0.020	0.003	7.381
		4.	0.127	-0.074	0.103	125.700
		5.	0.010	-0.010	-0.002	191.300
		6.	0.012	-0.012	-0.000	181.200
		7.	0.021	-0.007	0.020	109.900
		8.	0.007	-0.005	0.004	141.000
		9.	0.013	-0.010	0.009	137.900
56.2	-0.008	1.	0.084	0.084	0.002	1.264
		2.	0.018	-0.007	-0.017	246.200
		3.	0.038	0.032	-0.022	325.500
		4.	0.025	-0.016	0.019	131.000
		5.	0.006	-0.004	0.004	129.400
		6.	0.012	-0.011	0.004	160.100
		7.	0.002	-0.001	-0.001	224.300
		8.	0.014	-0.000	0.014	90.100
		9.	0.002	-0.001	-0.002	235.500
71.8	-0.009	1.	0.054	0.052	-0.014	345.000
		2.	0.023	-0.019	-0.014	216.100
		3.	0.008	0.003	-0.008	288.100
		4.	0.004	0.004	-0.002	338.200
		5.	0.012	-0.009	0.009	133.800
		6.	0.007	0.005	0.005	41.570
		7.	0.012	0.012	-0.001	353.400
		8.	0.010	0.010	-0.002	349.000
		9.	0.008	0.008	0.000	1.685

TABLE M. ACCELERATION TARES

Transducer P13   Acceleration Tares

Average Orifice   Units: psi
Location, X/C = 0.600 $\Delta\alpha = 5^\circ$

F_D(Hz)	Steady
24.2	-0.027

HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
1.	0.006	0.005	-0.003	327.700
2.	0.011	0.009	0.006	35.410
3.	0.008	-0.006	0.006	134.300
4.	0.021	0.002	0.021	85.310
5.	0.007	-0.007	0.001	168.600
6.	0.006	0.003	0.005	54.360
7.	0.004	0.002	0.004	65.530
8.	0.015	-0.015	0.003	167.900
9.	0.006	-0.006	-0.003	260.600

F_D(Hz)	Steady
48.0	-0.043

HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
1.	0.019	0.014	-0.015	317.200
2.	0.013	-0.002	-0.012	254.200
3.	0.031	0.020	-0.024	310.700
4.	0.145	-0.081	0.120	124.100
5.	0.017	-0.014	0.010	144.900
6.	0.020	-0.011	0.017	122.100
7.	0.019	0.001	0.019	87.420
8.	0.010	0.009	0.003	15.860
9.	0.013	0.002	0.013	82.000

F_D(Hz)	Steady
56.2	-0.023

HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
1.	0.083	0.083	-0.001	359.000
2.	0.015	-0.015	0.002	171.300
3.	0.041	0.017	-0.037	294.100
4.	0.036	-0.013	0.033	110.700
5.	0.030	0.007	0.029	77.050
6.	0.015	-0.006	0.014	112.400
7.	0.016	-0.002	-0.016	263.200
8.	0.029	-0.001	0.029	91.750
9.	0.011	0.002	-0.011	278.600

F_D(Hz)	Steady
71.8	-0.017

HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
1.	0.062	0.050	-0.037	323.200
2.	0.006	0.006	0.000	0.290
3.	0.014	0.004	-0.013	286.000
4.	0.010	-0.010	0.001	173.400
5.	0.013	0.003	0.013	74.960
6.	0.017	0.007	0.016	66.630
7.	0.017	0.015	0.007	24.740
8.	0.013	0.012	-0.004	340.400
9.	0.010	-0.010	0.001	176.600

TABLE N. ACCELERATION TARES

Transducer P14   Acceleration Tares

Average Orifice   Units: psi
Location, X/C = 0.701 $\overline{\Delta \alpha} = 5^\circ$

F_D(Hz)	Steady	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
24.2	-0.001					
		1.	0.007	0.006	-0.002	343.700
		2.	0.011	0.010	-0.003	342.500
		3.	0.011	-0.010	0.004	156.100
		4.	0.002	-0.002	0.001	159.500
		5.	0.009	-0.006	-0.007	232.800
		6.	0.002	-0.002	-0.001	141.700
		7.	0.008	-0.006	0.004	144.000
		8.	0.023	-0.023	0.005	166.800
		9.	0.010	-0.008	-0.006	219.300
48.0	-0.010					
		1.	0.017	0.016	-0.006	338.100
		2.	0.004	-0.003	-0.002	208.800
		3.	0.020	0.017	-0.011	328.200
		4.	0.126	-0.071	0.104	124.500
		5.	0.009	-0.005	0.007	125.600
		6.	0.007	-0.005	0.004	142.800
		7.	0.023	-0.001	0.023	92.790
		8.	0.010	0.004	0.009	67.950
		9.	0.005	-0.003	0.004	122.900
56.2	-0.009					
		1.	0.083	0.082	-0.016	348.700
		2.	0.011	0.001	-0.011	273.600
		3.	0.024	0.014	-0.019	306.000
		4.	0.024	-0.006	0.023	104.200
		5.	0.010	0.005	-0.009	291.000
		6.	0.012	-0.007	0.010	127.600
		7.	0.012	-0.006	-0.010	230.900
		8.	0.019	0.002	0.019	85.230
		9.	0.011	-0.002	-0.011	260.500
71.8	-0.001					
		1.	0.036	0.029	-0.022	322.500
		2.	0.014	-0.013	-0.006	206.000
		3.	0.010	0.006	0.007	41.450
		4.	0.016	-0.012	0.011	136.800
		5.	0.006	-0.005	0.002	155.300
		6.	0.008	-0.001	0.008	48.160
		7.	0.002	0.002	0.001	24.440
		8.	0.003	0.002	-0.002	314.500
		9.	0.004	-0.002	-0.004	234.000

TABLE O. ACCELERATION TARES

<u>Transducer P15</u>

<u>Acceleration Tares</u>

Average Orifice
Location, X/C = 0.800

$\frac{\text{Units:}}{\Delta\alpha = 5^\circ}$ psi

F_D(Hz)	Steady	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
24.2	-0.013	1.	0.004	0.003	0.002	27.160
		2.	0.004	0.004	-0.001	338.600
		3.	0.005	-0.003	0.005	120.700
		4.	0.008	-0.001	0.008	98.990
		5.	0.001	-0.001	-0.000	165.500
		6.	0.004	0.003	-0.002	323.800
		7.	0.004	-0.002	-0.004	238.400
		8.	0.023	-0.022	0.004	169.300
		9.	0.003	-0.003	0.000	179.000
48.0	-0.020	1.	0.015	0.014	0.005	19.790
		2.	0.010	-0.004	-0.009	246.400
		3.	0.021	0.019	-0.010	332.100
		4.	0.132	-0.074	0.109	124.160
		5.	0.017	-0.017	-0.004	192.600
		6.	0.017	-0.010	0.014	125.800
		7.	0.026	0.000	0.026	89.040
		8.	0.020	0.018	0.008	22.470
		9.	0.007	0.004	0.005	55.960
56.2	-0.006	1.	0.095	0.093	-0.016	350.100
		2.	0.010	-0.003	-0.010	250.900
		3.	0.055	0.034	-0.040	310.600
		4.	0.014	-0.006	0.012	121.900
		5.	0.003	0.003	0.001	12.900
		6.	0.013	-0.007	0.011	123.300
		7.	0.013	0.011	-0.006	332.200
		8.	0.025	-0.001	0.025	92.210
		9.	0.012	-0.003	-0.012	254.500
71.8	-0.006	1.	0.045	0.045	-0.004	354.900
		2.	0.014	-0.014	-0.001	185.000
		3.	0.015	0.015	0.002	8.229
		4.	0.006	0.003	0.005	57.400
		5.	0.009	0.005	0.009	71.260
		6.	0.026	0.018	0.019	47.650
		7.	0.002	0.002	0.001	24.250
		8.	0.004	0.001	-0.003	245.900
		9.	0.020	-0.014	0.015	134.200

TABLE P. ACCELERATION TARES

Transducer P16

Average Orifice
Location, X/C = 0.900

Acceleration Tares

Units: psi
$\overline{\Delta \alpha = 5^\circ}$

F_D(Hz)	Steady	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
24.2	-0.008	1.	0.001	-0.001	0.001	120.200
		2.	0.008	0.007	-0.004	329.700
		3.	0.009	-0.009	-0.003	199.400
		4.	0.013	-0.004	0.012	110.300
		5.	0.002	0.002	-0.001	338.400
		6.	0.001	0.001	-0.000	336.900
		7.	0.004	0.001	0.003	76.410
		8.	0.025	-0.025	-0.003	186.500
		9.	0.002	0.000	-0.002	273.500
48.0	-0.021	1.	0.009	0.008	0.005	31.290
		2.	0.013	-0.013	0.001	176.500
		3.	0.016	0.012	-0.010	320.500
		4.	0.147	-0.076	0.126	121.000
		5.	0.016	-0.009	0.014	122.100
		6.	0.012	-0.007	0.010	123.600
		7.	0.033	-0.008	0.032	104.300
		8.	0.017	0.017	-0.003	349.200
		9.	0.021	-0.002	0.021	95.420
56.2	-0.014	1.	0.092	0.092	-0.005	357.000
		2.	0.014	-0.011	-0.009	220.300
		3.	0.032	0.014	-0.029	296.300
		4.	0.037	-0.010	0.036	106.200
		5.	0.020	-0.018	0.008	155.400
		6.	0.014	0.009	0.011	50.220
		7.	0.012	-0.010	-0.006	213.000
		8.	0.010	-0.000	0.010	92.000
		9.	0.013	-0.013	0.001	177.200
71.8	-0.022	1.	0.040	0.029	-0.027	316.500
		2.	0.017	-0.014	-0.009	212.600
		3.	0.011	0.006	-0.010	301.500
		4.	0.009	0.009	0.002	13.030
		5.	0.023	-0.007	0.022	106.500
		6.	0.009	0.002	0.009	76.120
		7.	0.007	0.007	-0.002	345.400
		8.	0.009	0.008	0.003	19.000
		9.	0.004	0.002	0.003	54.330

TABLE Q. ACCELERATION TARES

Transducer P17

Average Orifice
Location, X/C = 0.969

Acceleration Tares

Units: psi
$\Delta\alpha = 5^{\circ}$

F_D(Hz)	Steady	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
24.2	-0.029	1.	0.003	0.003	-0.001	333.200
		2.	0.007	0.007	0.000	1.962
		3.	0.003	-0.001	0.003	120.000
		4.	0.007	0.006	0.002	15.880
		5.	0.008	0.002	-0.008	284.300
		6.	0.004	-0.002	-0.003	231.800
		7.	0.004	0.004	-0.000	356.300
		8.	0.020	-0.019	-0.008	203.200
		9.	0.014	-0.012	-0.007	212.400
48.0	-0.037	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
		1.	0.011	0.010	-0.005	332.000
		2.	0.008	-0.004	0.007	120.700
		3.	0.005	0.004	-0.003	322.400
		4.	0.134	-0.083	0.106	128.200
		5.	0.020	-0.020	0.004	169.600
		6.	0.018	-0.013	-0.013	224.800
		7.	0.024	0.001	0.024	86.870
		8.	0.012	-0.001	0.012	47.090
		9.	0.014	-0.002	0.014	49.720
56.2	-0.045	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
		1.	0.066	0.064	-0.016	346.300
		2.	0.007	-0.005	-0.005	225.900
		3.	0.027	0.014	-0.024	299.600
		4.	0.017	-0.005	0.016	107.300
		5.	0.008	0.001	0.008	80.530
		6.	0.010	-0.006	0.006	140.200
		7.	0.005	0.005	-0.000	358.300
		8.	0.021	-0.013	0.016	128.000
		9.	0.014	-0.010	-0.009	223.700
71.8	-0.024	HARM	RESULTANT	SINE COEFF	COS COEFF	PHASE
		1.	0.036	0.015	-0.032	245.700
		2.	0.011	-0.007	-0.009	232.600
		3.	0.019	0.004	0.019	77.600
		4.	0.019	-0.005	-0.019	255.800
		5.	0.002	-0.000	-0.002	265.600
		6.	0.038	0.037	0.010	15.300
		7.	0.011	-0.008	-0.007	214.800
		8.	0.015	0.002	-0.014	277.100
		9.	0.020	-0.005	0.014	104.900

FORCED PITCHING OSCILLATION AIRFOIL NLR 1 ACCELERATION TARES

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	68.67	0.483	0.212	5.91	0.0	0.02	12007.1	20

	V	W	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	72.4 (237.4)	13406. (280.0)	0.34E 07	-0.078	0.557	4.12	-0.00112	0.714	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.015	5.906 0	0.507 344	0.136 196	0.086 132	0.026 123	0.016 109	0.023 251	0.016 72	0.017 66
CN		0.141	0.356 33	0.036 52	0.022 306	0.001 54	0.012 255	0.001 255	0.008 255	0.002 83
CM		-0.023	0.053 293	0.008 300	0.007 138	0.002 175	0.003 88	0.002 44	0.001 354	0.003 320	0.001 291
DCP 1	.010	-0.534	2.476 348	0.242 359	0.059 118	0.011 162	0.023 171	0.016 616	0.008 298	0.004 125	0.014 244
DCP 2	.020	-0.337	1.780 356	0.176 354	0.014 121	0.025 212	0.021 207	0.018 199	0.014 289	0.013 134	0.013 299
DCP 3	.030	0.049	1.478 358	0.129 346	0.016 220	0.008 126	0.023 192	0.018 244	0.015 87	0.014 144	0.009 203
DCP 4	.049	-0.023	1.205 1	0.106 359	0.015 147	0.006 20	0.029 201	0.010 155	0.013 293	0.017 214	0.008 52
DCP 5	.074	0.160	0.973 3	0.086 357	0.009 212	0.024 150	0.013 206	0.009 214	0.004 340	0.004 103	0.011 129
DCP 6	.099	0.370	0.840 8	0.080 13	0.019 284	0.029 147	0.012 264	0.015 233	0.003 240	0.006 171	0.014 264
DCP 7	.149	0.236	0.637 15	0.073 27	0.018 271	0.013 136	0.015 251	0.013 129	0.009 246	0.008 6	0.012 50
DCP 8	.200	0.252	0.564 27	0.080 42	0.025 279	0.016 292	0.015 242	0.006 45	0.005 107	0.012 262	0.019 157
DCP 9	.250	0.195	0.445 28	0.053 47	0.032 297	0.014 190	0.015 192	0.018 161	0.009 52	0.020 107	0.009 194
DCP10	.300	0.211	0.417 35	0.046 42	0.016 276	0.008 225	0.012 245	0.002 113	0.004 268	0.014 145	0.011 351
DCP11	.349	0.228	0.382 59	0.046 63	0.029 318	0.006 316	0.019 324	0.016 257	0.013 302	0.005 186	0.019 81
DCP12	.501	0.141	0.380 60	0.053 69	0.031 288	0.010 89	0.013 256	0.003 71	0.015 326	0.005 302	0.013 354
DCP13	.600	0.209	0.308 68	0.057 89	0.037 296	0.015 58	0.026 281	0.003 10	0.021 14	0.030 168	0.015 290
DCP14	.701	0.201	0.249 76	0.030 108	0.024 318	0.014 359	0.011 239	0.009 297	0.017 129	0.012 87	0.010 197
DCP15	.800	0.097	0.188 89	0.028 103	0.025 335	0.005 351	0.011 283	0.024 210	0.015 166	0.015 121	0.020 97
DCP16	.900	-0.073	0.086 103	0.029 111	0.036 293	0.021 311	0.009 191	0.019 214	0.016 228	0.013 226	0.015 302
DCP17	.969	0.010	0.049 166	0.029 243	0.037 17	0.017 145	0.022 255	0.014 72	0.020 170	0.030 111	0.026 142

FORCED PITCHING OSCILLATION AIRFOIL NLR 1 ACCELERATION TARES

	TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
	0.0	68.58	0.499	0.205	5.95	0.0	2.52	12007.2	20

	V	W	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
	69.9 (229.4)	12655. (264.3)	0.33E 07	-0.083	0.766	6.64	-0.00115	0.712	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		2.520	5.946 0	0.511 345	0.150 189	0.072 136	0.006 129	0.019 14	0.016 227	0.025 123	0.002 123
CN		0.365	0.355 34	0.050 61	0.012 329	0.007 306	0.004 199	0.001 83	0.004 22	0.006 145	0.005 98
CM		-0.020	0.057 298	0.013 294	0.006 168	0.004 156	0.000 170	0.002 302	0.001 123	0.002 283	0.002 299
DCP 1	.010	0.957	2.352 349	0.232 354	0.061 166	0.024 139	0.030 198	0.002 355	0.015 323	0.008 303	0.018 63
DCP 2	.020	0.756	1.828 358	0.187 0	0.018 183	0.016 196	0.039 179	0.007 349	0.014 57	0.006 155	0.019 4
DCP 3	.033	0.974	1.521 358	0.156 356	0.015 274	0.003 249	0.017 172	0.019 254	0.010 167	0.018 100	0.009 0
DCP 4	.049	0.562	1.249 1	0.129 358	0.013 168	0.010 229	0.030 205	0.013 246	0.012 90	0.019 244	0.004 144
DCP 5	.074	0.812	1.004 4	0.104 1	0.026 196	0.024 164	0.022 228	0.021 293	0.016 71	0.013 183	0.006 72
DCP 6	.099	0.934	0.849 9	0.097 10	0.017 214	0.012 166	0.021 232	0.022 297	0.019 73	0.026 245	0.006 220
DCP 7	.149	0.645	0.638 16	0.084 27	0.024 190	0.013 223	0.014 219	0.016 312	0.026 96	0.008 149	0.011 285
DCP 8	.200	0.581	0.561 29	0.071 39	0.026 247	0.008 260	0.008 238	0.023 17	0.011 354	0.007 26	0.038 72
DCP 9	.250	0.473	0.514 26	0.070 49	0.007 30	0.005 211	0.016 208	0.003 268	0.009 228	0.022 155	0.010 324
DCP10	.300	0.471	0.457 32	0.067 52	0.019 297	0.008 226	0.007 42	0.004 85	0.012 147	0.006 186	0.012 93
DCP11	.499	0.425	0.361 57	0.070 87	0.023 17	0.018 301	0.012 87	0.013 251	0.017 1	0.008 153	0.008 117
DCP12	.501	0.277	0.383 63	0.077 79	0.017 331	0.008 274	0.012 86	0.011 114	0.007 345	0.002 50	0.006 150
DCP13	.600	0.322	0.298 72	0.062 111	0.017 327	0.010 350	0.007 95	0.014 106	0.020 3	0.017 195	0.011 133
DCP14	.701	0.277	0.259 84	0.066 86	0.024 271	0.025 271	0.016 75	0.004 350	0.011 118	0.003 291
DCP15	.800	0.147	0.213 95	0.034 118	0.042 341	0.011 338	0.004 262	0.004 104	0.007 67	0.015 59	0.007 66
DCP16	.900	-0.051	0.108 126	0.038 89	0.019 338	0.024 338	0.013 119	0.008 76	0.011 327	0.017 171	0.025 174
DCP17	.969	0.007	0.044 191	0.019 195	0.015 27	0.016 312	0.010 288	0.027 203	0.008 219	0.024 40	0.011 15

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1   ACCELERATION TARES

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.48	0.511	0.201	5.93	0.0	5.05	12007.3	20

V	J	KN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TOR	EXT DAMP
68.3	12099.	0.328 07	-0.381	1.025	6.71	-0.00120	0.726	0.0
(224.0)	(252.7)							

HARMONIC ANALYSIS

DATA TYPE	K/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		5.053	5.929	0	0.519	345	0.149	185	0.065	136	0.021	349	0.026	28	0.017	166	0.023	129	0.011	162
CN		0.593	0.371	35	0.353	59	0.024	353	0.010	260	0.032	43	0.004	247	0.006	291	0.005	170	0.005	74
CM		-0.015	0.057	297	0.014	282	0.009	188	0.004	119	0.003	257	0.001	47	0.002	109	0.002	344	0.002	266
DCP 1	.010	7.534	2.438	349	0.219	324	0.092	168	0.038	94	0.037	236	0.011	104	0.018	294	0.015	142	0.013	312
DCP 2	.020	1.940	1.882	358	0.179	1	0.024	184	0.019	119	0.020	215	0.013	199	0.011	270	0.010	15	0.029	11
DCP 3	.030	1.977	1.594	356	0.142	0	0.016	198	0.023	108	0.026	231	0.003	279	0.008	332	0.005	25	0.006	332
DCP 4	.049	1.606	1.306	2	0.125	358	0.019	166	0.017	148	0.033	256	0.008	203	0.007	269	0.008	273	0.006	268
DCP 5	.074	1.483	1.029	4	0.104	357	0.017	197	0.025	175	0.024	245	0.002	142	0.013	55	0.010	94	0.010	317
DCP 6	.299	1.481	0.873	10	0.090	11	0.014	292	0.023	169	0.014	286	0.014	285	0.004	184	0.009	302	0.008	302
DCP 7	.149	1.071	0.678	17	0.063	26	0.009	293	0.015	219	0.014	236	0.023	283	0.015	209	0.052	107	0.008	123
DCP 8	.200	0.916	0.596	28	0.070	44	0.038	284	0.013	245	0.017	283	0.005	273	0.004	177	0.011	285	0.022	90
DCP 9	.250	0.753	0.516	33	0.080	54	0.020	323	0.016	131	0.017	301	0.011	153	0.017	252	0.011	129	0.012	199
DCP10	.300	0.718	0.459	36	0.066	61	0.025	331	0.010	275	0.005	149	0.014	76	0.013	338	0.029	154	0.015	304
DCP11	.395	0.635	0.386	59	0.064	87	0.040	3	0.027	306	0.023	40	0.014	227	0.005	22	0.012	220	0.006	71
DCP12	.531	0.431	0.373	62	0.077	60	0.045	353	0.019	292	0.006	178	0.010	302	0.014	135	0.006	222	0.006	291
DCP13	.600	0.417	0.311	72	0.074	89	0.042	354	0.025	252	0.009	90	0.017	263	0.016	286	0.003	68	0.010	311
DCP14	.731	0.362	0.258	83	0.065	62	0.026	15	0.029	289	0.009	57	0.004	276	0.011	303	0.003	179	0.019	82
DCP15	.830	0.162	0.209	94	0.043	88	0.034	5	0.013	248	0.017	45	0.014	191	0.013	263	0.012	65	0.009	119
DCP16	.900	-0.031	0.108	118	0.025	99	0.036	343	0.010	6	0.018	52	0.023	57	0.008	119	0.017	219	0.029	148
DCP17	.969	-0.008	0.020	165	0.030	115	0.050	63	0.028	13	0.031	181	0.023	235	0.009	265	0.024	150	0.041	19

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1   ACCELERATION TARES

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.50	0.511	0.201	5.93	0.0	7.54	12007.4	20

V	J	KN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TOR	EXT DAMP
68.3	12104.	0.328 07	-0.085	1.248	11.64	-0.00136	0.822	0.0
(224.1)	(252.8)							

HARMONIC ANALYSIS

DATA TYPE	K/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.542	5.930	0	0.509	344	0.159	186	0.062	129	0.026	353	0.020	12	0.022	192	0.024	114	0.005	198
CN		0.806	0.383	36	0.080	65	0.015	302	0.010	255	0.003	290	0.009	231	0.007	331	0.006	109	0.005	99
CM		-0.010	0.063	292	0.014	290	0.004	130	0.003	67	0.002	265	0.003	84	0.002	134	0.002	257	0.001	270
DCP 1	.010	3.845	2.155	347	0.291	34	0.153	339	0.065	226	0.057	245	0.061	206	0.024	146	0.025	122	0.012	72
DCP 2	.020	3.092	1.892	358	0.165	1	0.019	131	0.028	160	0.027	278	0.027	139	0.012	355	0.013	254	0.017	331
DCP 3	.030	2.932	1.596	358	0.149	359	0.012	128	0.015	142	0.019	272	0.009	287	0.007	126	0.017	193	0.004	224
DCP 4	.049	2.418	1.312	1	0.145	5	0.027	90	0.012	38	0.040	266	0.013	162	0.018	295	0.019	215	0.025	44
DCP 5	.074	2.140	1.047	4	0.108	7	0.014	126	0.004	98	0.023	263	0.010	236	0.003	293	0.020	136	0.019	72
DCP 6	.099	2.012	0.894	9	0.093	19	0.007	316	0.005	83	0.022	272	0.001	137	0.003	208	0.022	163	0.012	57
DCP 7	.149	1.474	0.678	16	0.093	36	0.015	293	0.021	265	0.000	306	0.015	314	0.019	74	0.007	103	0.010	132
DCP 8	.200	1.234	0.599	29	0.079	53	0.002	44	0.006	47	0.019	281	0.008	15	0.024	339	0.008	275	0.022	121
DCP 9	.250	1.029	0.517	31	0.079	51	0.027	245	0.005	328	0.010	260	0.014	263	0.009	327	0.010	53	0.003	107
DCP10	.300	0.946	0.452	38	0.062	49	0.026	249	0.012	282	0.009	242	0.013	201	0.006	5	0.016	48	0.010	122
DCP11	.395	0.815	0.402	62	0.078	86	0.026	318	0.016	314	0.022	50	0.024	240	0.012	353	0.010	72	0.009	194
DCP12	.531	0.574	0.410	62	0.079	84	0.025	290	0.024	293	0.006	268	0.007	177	0.017	301	0.012	109	0.006	278
DCP13	.600	0.507	0.348	71	0.070	101	0.020	283	0.014	253	0.003	37	0.005	113	0.010	340	0.017	150	0.006	180
DCP14	.701	0.422	0.286	82	0.055	79	0.014	324	0.027	251	0.007	230	0.022	276	0.002	144	0.006	291	0.006	11
DCP15	.800	0.225	0.213	90	0.057	130	0.027	318	0.015	221	0.006	56	0.016	227	0.003	46	0.010	67	0.016	61
DCP16	.900	-0.018	0.130	106	0.045	109	0.012	276	0.012	165	0.022	99	0.022	314	0.001	330	0.016	83	0.013	150
DCP17	.969	-0.012	0.059	138	0.028	109	0.028	48	0.013	357	0.011	267	0.011	109	0.024	197	0.010	23	0.020	61

299

300

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1   ACCELERATION TARES

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
2.0	68.19	0.519	0.199	5.93	0.0	10.06	12007.5	20

V	Q	RN	CMHMIN	CNHMAX	ALPHA.HMAX	AERO DAMP	TDR	EXT DAMP
67.7 (222.1)	11917. (248.9)	3.32E 07	-3.074	1.489	13.68	-0.00141	0.844	0.0

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1   ACCELERATION TARES

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
3.3	67.57	3.508	0.199	5.90	0.0	12.52	12007.6	20

V	Q	RN	CMHMIN	CNHMAX	ALF A.HMAX	AERO DAMP	TDR	EXT DAMP
67.7 (222.2)	11937. (249.3)	3.32E 07	-3.068	1.595	16.59	-0.00123	0.739	0.0

HARMONIC ANALYSIS

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1   ACCELERATION TARES

TUNE HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	67.31	0.504	0.200	5.90	0.0	15.07	12007.7	20

	Q		RK	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
67.9 (222.9)	12018. (251.0)	0.529 07	-0.086	1.589	19.06	-0.00016	0.045	0.0

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		15.072	5.007 0	0.047 337	0.116 194	5.065 148	0.063 359	0.021 116	0.007 152	0.020 188	0.012 15
CN		1.234	0.474 10	0.114 85	2.036 304	5.019 330	0.010 221	0.007 190	0.005 183	0.004 334	0.007 142
CM		-0.017	0.203 156	0.042 251	0.313 46	0.303 165	0.002 271	0.001 169	0.001 348	5.002 158	0.000 46

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1   ACCELERATION TARES

TUNE HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	66.74	0.516	0.200	5.96	0.0	17.56	12007.6	25

	Q		RK	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
67.8 (222.6)	12023. (251.1)	0.528 07	-0.259	1.799	23.99	0.00113	-0.492	0.0

HARMONIC ANALYSIS

DATA TYPE	A/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		17.561	5.962 0	0.486 331	0.130 203	0.053 115	0.051 1	0.024 58	0.025 174	0.016 125	0.005 311
CN		1.325	0.568 199	0.134 104	0.034 271	0.036 53	0.013 245	0.010 19	0.008 199	0.011 153	0.035 347
CM		-0.077	0.279 94	0.076 243	0.322 66	0.006 234	0.006 13	0.006 229	0.001 294	0.003 59	0.002 78

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1   ACCELERATION TARES

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	68.82	0.520	0.198	5.93	0.0	19.97	12007.9	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
67.3	11846.	0.32E 07	-0.319	2.073	25.44	0.00222	-1.330	0.0
(220.9)	(247.4)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		19.473	5.931 0	0.532 352	0.100 210	0.060 138	0.045 19	0.015 46	0.018 193	0.019 132	0.003 41
CN		1.442	0.659 6	0.056 154	0.033 337	0.032 174	0.009 40	0.016 107	0.003 57	0.011 347	0.008 263
CM		-0.136	0.115 73	0.059 266	0.020 174	0.013 32	0.009 176	0.008 334	0.003 57	0.004 251	0.002 27
DCP 1	.010	3.621	2.713 68	0.619 52	0.230 323	0.132 358	0.234 26	0.163 356	0.135 282	0.151 245	0.127 170
DCP 2	.020	3.413	2.628 62	0.646 43	0.295 318	0.237 256	0.154 161	0.127 94	0.060 43	0.059 328	0.063 313
DCP 3	.030	3.346	2.517 57	0.634 25	0.416 305	0.208 262	0.269 199	0.178 151	0.160 95	0.126 67	0.135 3
DCP 4	.049	3.264	2.264 49	0.595 347	0.353 278	0.237 209	0.135 178	0.175 117	0.105 73	0.110 15	0.122 338
DCP 5	.074	2.402	2.014 40	0.519 325	0.399 252	0.263 174	0.137 129	0.152 69	0.081 22	0.107 329	0.079 274
DCP 6	.099	2.724	1.842 32	0.461 338	0.358 233	0.275 157	0.147 99	0.134 39	0.057 327	0.094 292	0.069 230
DCP 7	.149	2.307	1.740 20	0.524 286	0.319 213	0.293 136	0.116 65	0.146 0	0.085 298	0.100 219	0.091 145
DCP 8	.200	2.063	1.698 19	0.598 271	0.361 199	0.305 138	0.164 39	0.142 333	0.071 265	0.054 213	0.051 134
DCP 9	.250	1.900	1.564 6	0.649 234	0.406 143	0.361 51	0.208 315	0.149 243	0.082 169	0.076 74	0.075 20
DCP10	.300	1.767	1.308 358	0.590 213	0.384 104	0.306 4	0.184 263	0.114 184	0.074 117	0.066 9	0.076 303
DCP11	.399	1.596	1.017 349	0.622 185	0.435 63	0.268 318	0.114 204	0.080 136	0.045 94	0.055 313	0.039 228
DCP12	.501	1.313	0.796 329	0.582 143	0.414 12	0.251 242	0.116 123	0.046 26	0.033 8	0.025 168	0.017 116
DCP13	.600	1.143	0.563 302	0.524 110	0.375 333	0.221 195	0.073 67	0.025 320	0.030 16	0.015 53	0.027 11
DCP14	.701	0.967	0.384 262	0.432 73	0.271 291	0.122 126	0.040 327	0.020 197	0.009 134	0.005 256	0.035 266
DCP15	.800	0.745	0.251 221	0.307 46	0.194 255	0.091 82	0.029 232	0.013 211	0.033 127	0.014 221	0.005 295
DCP16	.900	0.417	0.245 203	0.264 5	0.073 164	0.086 170	0.088 340	0.075 94	0.055 235	0.039 32	0.035 170
DCP17	.969	0.336	0.397 214	0.348 352	0.236 120	0.177 248	0.143 24	0.143 161	0.089 282	0.080 81	0.013 170

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1   ACCELERATION TARES

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.12	0.113	0.338	5.14	0.0	0.03	12009.1	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
104.4	28259.	0.49E 07	-0.338	0.558	5.24	-0.00081	0.686	0.0
(342.5)	(590.2)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1 PHI	RES 2 PHI	RES 3 PHI	RES 4 PHI	RES 5 PHI	RES 6 PHI	RES 7 PHI	RES 8 PHI	RES 9 PHI
ALPHA		0.048	5.136 0	0.238 5	0.050 258	0.004 125	0.007 53	0.029 76	0.034 187	0.041 17	0.004 308
CN		0.126	0.430 355	0.016 2	0.001 124	0.001 237	0.003 272	0.001 106	0.005 211	0.015 214	0.001 49
CM		-0.018	0.012 303	0.002 355	0.001 1	0.000 104	0.001 82	0.001 182	0.002 24	0.006 22	0.001 203
DCP 1	.010	-0.632	3.101 347	0.233 31	0.043 106	0.019 190	0.004 267	0.015 131	0.004 323	0.022 326	0.011 170
DCP 2	.020	-0.331	2.241 350	0.091 351	0.016 353	0.006 217	0.005 339	0.015 155	0.008 350	0.018 349	0.009 195
DCP 3	.030	-0.015	1.868 350	0.074 334	0.012 340	0.005 243	0.004 282	0.005 143	0.001 260	0.013 348	0.005 201
DCP 4	.049	0.106	1.517 350	0.061 334	0.015 358	0.007 211	0.004 208	0.005 126	0.004 46	0.019 349	0.005 312
DCP 5	.074	0.276	1.213 350	0.049 348	0.008 341	0.005 213	0.003 189	0.008 138	0.002 39	0.015 340	0.003 161
DCP 6	.099	0.365	1.053 351	0.044 354	0.014 350	0.005 173	0.003 184	0.003 94	0.002 343	0.014 323	0.006 199
DCP 7	.149	0.231	0.703 352	0.035 7	0.007 9	0.002 36	0.005 312	0.007 170	0.006 332	0.009 325	0.005 163
DCP 8	.200	0.205	0.640 355	0.032 1	0.010 21	0.005 161	0.004 322	0.008 176	0.008 334	0.011 359	0.005 195
DCP 9	.250	0.175	0.554 354	0.026 7	0.003 144	0.002 141	0.003 235	0.001 93	0.007 178	0.023 202	0.003 334
DCP10	.300	0.190	0.466 355	0.018 358	0.002 178	0.003 27	0.006 255	0.003 48	0.006 182	0.015 200	0.004 205
DCP11	.394	0.183	0.371 1	0.010 18	0.005 143	0.004 0	0.010 265	0.003 54	0.008 214	0.024 211	0.003 332
DCP12	.501	0.120	0.283 4	0.008 9	0.008 150	0.003 283	0.003 318	0.001 220	0.006 223	0.021 209	0.003 142
DCP13	.600	0.151	0.220 6	0.005 35	0.005 154	0.008 245	0.003 258	0.003 281	0.007 17	0.024 209	0.004 31
DCP14	.731	0.195	0.156 5	0.002 34	0.005 201	0.001 188	0.002 271	0.003 292	0.008 189	0.024 202	0.004 49
DCP 5	.800	0.096	0.094 14	0.001 109	0.001 118	0.001 154	0.004 353	0.003 21	0.010 217	0.023 210	0.004 28
DCP16	.900	-0.061	0.029 14	0.005 200	0.002 224	0.007 28	0.008 232	0.002 359	0.005 210	0.017 190	0.006 8
DCP17	.964	-0.028	0.022 215	0.006 194	0.006 199	0.009 224	0.003 169	0.009 65	0.012 198	0.023 208	0.002 280

FORCED PITCHING OSCILLATION — AIRFOIL NLR 1 — ACCELERATION TARES

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.1?	0.115	0.304	5.15	0.0	2.46	12009.2	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
102.9	27617.	0.4?E 07	-0.030	0.785	7.53	-0.00091	0.753	0.0
(337.7)	(576.8)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		2.455	5.155	0	0.233	8	0.049	261	0.005	263	0.015	14	0.011	84	0.023	162	0.006	142	0.006	21
CN		0.358	0.433	355	0.016	16	0.003	47	0.002	301	0.001	271	0.001	152	0.001	94	0.002	29	0.002	359
CM		-0.001	0.014	299	0.002	272	0.001	197	0.001	139	0.001	355	0.001	155	0.001	348	0.001	221	0.000	175
DCP 1	.010	1.005	2.894	347	0.124	9	0.018	1	0.008	179	0.014	244	0.014	174	0.006	1	0.001	197	0.016	302
DCP 2	.020	0.850	2.154	350	0.064	358	0.046	347	0.003	55	0.010	360	0.019	194	0.007	114	0.005	66	0.015	310
DCP 3	.030	0.989	1.903	350	0.070	355	0.032	334	0.003	169	0.012	318	0.012	191	0.009	80	0.003	155	0.011	330
DCP 4	.044	0.929	1.563	350	0.056	344	0.021	354	0.008	165	0.006	290	0.004	213	0.002	2	0.001	303	0.012	354
DCP 5	.074	0.442	1.254	350	0.045	350	0.017	354	0.006	198	0.006	303	0.002	153	0.003	268	0.001	67	0.004	303
DCP 6	.099	0.924	1.064	351	0.044	1	0.011	352	0.004	156	0.004	311	0.001	157	0.002	243	0.002	160	0.004	363
DCP 7	.149	0.000	0.800	2?4	0.033	3	0.007	0	0.005	229	0.003	80	0.005	164	0.003	36	0.003	160	0.005	329
DCP 8	.200	0.553	0.652	355	0.030	6	0.014	5	0.002	70	0.007	235	0.005	213	0.005	340	0.003	214	0.005	86
DCP 9	.250	0.470	0.567	355	0.026	13	0.006	222	0.003	31	0.011	171	0.001	118	0.002	317	0.005	22	0.006	82
DCP10	.300	0.447	0.475	355	0.022	20	0.001	278	0.005	318	0.003	75	0.006	213	0.004	4	0.003	330	0.002	341
DCP11	.399	0.365	0.371	1	0.015	32	0.005	105	0.004	322	0.005	186	0.001	123	0.002	356	0.004	356	0.002	326
DCP12	.501	0.272	0.293	4	0.011	37	0.003	121	0.001	285	0.003	285	0.002	95	0.005	100	0.002	247	0.001	158
DCP13	.600	0.204	0.224	0	0.014	49	0.011	145	0.008	276	0.005	199	0.006	338	0.004	144	0.002	240	0.010	56
DCP14	.701	0.075	0.154	10	0.016	49	0.007	76	0.004	0	0.006	177	0.006	10	0.007	140	0.006	40	0.004	8
DCP15	.800	0.142	0.042	17	0.010	41	0.007	18	0.004	285	0.003	67	0.002	309	0.004	154	0.003	37	0.003	22
DCP16	.900	-0.048	0.029	28	0.008	82	0.007	314	0.008	348	0.003	182	0.005	228	0.006	267	0.005	46	0.007	161
DCP17	.969	-0.034	0.013	103	0.004	331	0.011	172	0.001	237	0.004	284	0.001	263	0.002	274	0.005	92	0.003	178

FORCED PITCHING OSCILLATION — AIRFOIL NLR 1 — ACCELERATION TARES

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.16	0.115	0.302	5.15	0.0	5.01	12009.3	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
102.1	27273.	0.48E 07	-0.026	1.009	9.80	-0.00094	0.780	0.0
(335.1)	(569.6)							

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		5.009	5.147	0	0.237	8	0.036	257	0.033	305	0.013	351	0.006	213	0.027	229	0.005	225	0.004	77
CN		0.594	0.426	356	0.022	19	0.006	44	0.005	248	0.002	321	0.002	202	0.006	350	0.010	334	0.004	222
CM		-0.009	0.015	334	0.002	277	0.001	284	0.001	106	0.000	206	0.000	4	0.001	185	0.002	144	0.001	60
DCP 1	.010	2.563	2.771	347	0.150	16	0.076	340	0.055	224	0.017	154	0.013	145	0.007	339	0.027	352	0.005	223
DCP 2	.020	2.096	2.259	350	0.104	357	0.026	352	0.311	220	0.002	325	0.000	253	0.007	344	0.014	359	0.037	207
DCP 3	.033	2.015	1.913	350	0.087	354	0.013	355	0.002	415	0.005	220	0.000	253	0.007	344	0.014	359	0.037	207
DCP 4	.069	1.747	1.586	350	0.070	348	0.019	355	0.006	173	0.004	262	0.007	251	0.012	143	0.016	9	0.005	152
DCP 5	.074	1.632	1.256	351	0.056	358	0.020	356	0.008	148	0.007	305	0.005	299	0.010	335	0.013	352	0.011	180
DCP 6	.099	1.510	1.061	351	0.050	0	0.015	358	0.005	188	0.005	315	0.005	227	0.008	350	0.012	347	0.008	175
DCP 7	.149	1.098	0.788	353	0.033	5	0.011	340	0.011	195	0.011	298	0.006	215	0.009	5	0.015	338	0.002	164
DCP 8	.200	0.905	0.644	356	0.035	10	0.317	20	0.008	196	0.006	2	0.003	183	0.010	343	0.011	345	0.009	193
DCP 9	.250	0.774	0.557	356	0.030	13	0.008	159	0.005	255	0.003	73	0.005	186	0.001	355	0.011	324	0.002	284
DCP10	.300	0.706	0.461	356	0.022	22	0.006	64	0.002	259	0.006	278	0.005	153	0.005	302	0.010	313	0.004	234
DCP11	.399	0.592	0.364	1	0.018	36	0.012	89	0.004	308	0.008	314	0.002	233	0.010	343	0.008	336	0.007	251
DCP12	.501	0.429	0.280	5	0.018	30	0.008	109	0.007	265	0.002	166	0.001	244	0.005	335	0.010	334	0.002	297
DCP13	.600	0.360	0.211	7	0.015	22	0.011	74	0.011	262	0.004	128	0.005	352	0.002	9	0.008	311	0.002	242
DCP14	.701	0.353	0.144	11	0.020	70	0.006	26	0.032	299	0.007	66	0.003	318	0.008	350	0.010	326	0.006	216
DCP15	.800	0.188	0.083	20	0.011	64	0.007	41	0.001	286	0.006	47	0.004	230	0.004	17	0.012	315	0.003	240
DCP16	.900	-0.044	0.031	35	0.006	110	0.004	104	0.008	291	0.009	272	0.008	162	0.007	0	0.010	356	0.005	241
DCP17	.969	-0.043	0.010	223	0.002	67	0.008	180	0.004	180	0.005	199	0.003	112	0.010	23	0.010	330	0.005	199

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1   ACCELERATION TARES

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
3.0	23.13	3.116	0.300	5.14	0.0	7.48	12009.4	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
101.6 (333.2)	27019. (564.3)	0.48E 07	-0.025	1.206	12.50	-0.30112	0.920	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		7.477	5.140	0	0.247	7	0.351	264	0.003	308	0.012	55	0.013	354	0.020	201	0.006	170	0.006	133
CN		0.816	0.403	358	0.028	23	0.002	3	0.003	126	0.002	5	0.000	106	0.002	344	0.010	338	0.004	206
CM		-0.003	0.018	337	0.002	269	0.001	292	0.000	49	0.001	309	0.001	227	0.000	62	0.002	134	0.000	21
DCP 1	.010	4.060	2.718	348	0.158	333	0.100	168	0.129	66	0.084	323	0.014	244	0.022	305	0.021	14	0.015	215
DCP 2	.020	3.261	2.132	351	0.129	23	0.062	342	0.021	223	0.011	300	0.016	198	0.008	334	0.024	33	0.009	244
DCP 3	.030	3.024	1.861	351	0.047	0	0.020	341	0.012	219	0.006	312	0.009	207	0.005	14	0.009	31	0.010	220
DCP 4	.049	2.834	1.528	351	0.093	11	0.030	341	0.011	209	0.003	72	0.003	307	0.009	35	0.020	27	0.004	246
DCP 5	.074	2.245	1.202	352	0.075	15	0.022	336	0.008	209	0.003	349	0.002	16	0.005	16	0.016	20	0.036	166
DCP 6	.099	2.302	1.016	353	0.065	17	0.019	339	0.004	208	0.004	287	0.004	348	0.017	25	0.003	206
DCP 7	.149	1.512	0.768	354	0.050	21	0.007	353	0.010	154	0.008	346	0.006	175	0.010	3	0.015	9	0.004	205
DCP 8	.200	1.243	0.673	357	0.048	16	0.016	337	0.004	148	0.004	26	0.010	208	0.007	11	0.016	22	0.038	149
DCP 9	.250	1.065	0.537	357	0.030	9	0.008	239	0.008	118	0.005	65	0.031	96	0.004	22	0.013	341	0.002	165
DCP10	.300	0.944	0.435	358	0.033	20	0.001	126	0.005	52	0.004	165	0.001	35	0.003	38	0.004	292	0.036	265
DCP11	.349	0.782	0.344	5	0.030	33	0.002	140	0.003	5	0.002	289	0.004	72	0.001	268	0.017	323	0.006	175
DCP12	.501	0.573	0.262	8	0.022	19	0.004	191	0.005	125	0.003	12	0.003	55	0.004	228	0.011	300	0.007	199
DCP13	.600	0.476	0.195	12	0.019	50	0.007	138	0.004	157	0.005	77	0.002	74	0.001	281	0.013	317	0.005	203
DCP14	.701	0.422	0.124	23	0.023	51	0.001	182	0.005	59	0.003	141	0.004	359	0.004	49	0.004	337	0.003	191
DCP15	.800	0.227	0.069	45	0.011	50	0.005	51	0.004	256	0.004	115	0.001	325	0.004	155	0.007	312	0.003	278
DCP16	.900	-0.024	0.079	45	0.001	82	0.005	7	0.006	264	0.002	180	0.011	36	0.007	214	0.009	309	0.004	132
DCP17	.949	-0.045	0.011	100	0.034	273	0.035	149	0.008	135	0.005	302	0.004	125	0.008	310	0.015	0	0.003	305

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1   ACCELERATION TARES

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
3.0	23.26	0.117	0.300	5.12	0.0	9.99	12009.5	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
101.2 (331.9)	26875. (561.3)	0.48E 07	-0.095	1.398	15.10	-0.00046	0.390	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		9.993	5.121	0	0.266	14	0.062	265	0.012	195	0.032	78	0.037	347	0.031	164	0.013	154	0.007	304
CN		0.443	0.351	22	0.099	339	0.037	173	0.020	31	0.014	309	0.014	229	0.015	137	0.013	50	0.014	308
CM		-0.011	0.019	208	0.026	51	0.022	294	0.013	171	0.005	86	0.004	11	0.003	296	0.003	207	0.004	110
DCP 1	.010	4.406	1.172	23	1.153	38	0.619	315	0.396	243	0.315	179	0.208	109	0.113	28	0.056	265	0.078	185
DCP 2	.020	3.521	0.900	29	1.022	45	0.613	320	0.366	236	0.238	166	0.168	102	0.126	48	0.065	355	0.071	302
DCP 3	.030	3.143	0.757	41	0.989	38	0.561	305	0.257	211	0.087	161	0.117	140	0.166	61	0.118	333	0.090	258
DCP 4	.049	3.074	1.076	12	0.383	16	0.135	283	0.076	173	0.048	78	0.034	350	0.015	273	0.010	161	0.004	33
DCP 5	.074	2.612	0.815	15	0.341	16	0.124	275	0.074	161	0.041	53	0.033	324	0.021	216	0.021	133	0.013	16
DCP 6	.099	2.246	0.679	20	0.321	15	0.125	269	0.060	153	0.045	44	0.033	316	0.021	210	0.016	119	0.007	333
DCP 7	.149	1.710	0.553	24	0.267	2	0.116	243	0.062	133	0.036	21	0.020	295	0.005	214	0.012	145	0.004	292
DCP 8	.200	1.450	0.560	23	0.227	339	0.134	211	0.093	96	0.059	357	0.033	277	0.023	204	0.025	120	0.009	347
DCP 9	.250	1.274	0.564	19	0.215	313	0.161	178	0.105	74	0.061	352	0.053	281	0.052	191	0.039	100	0.033	14
DCP10	.300	1.138	0.502	17	0.194	330	0.151	170	0.095	69	0.066	356	0.063	276	0.056	179	0.036	77	0.022	2
DCP11	.449	0.943	1.413	20	0.145	292	0.125	156	0.080	44	0.049	326	0.048	255	0.040	159	0.029	55	0.020	329
DCP12	.501	0.687	1.303	23	0.093	281	0.102	131	0.075	16	0.050	286	0.036	204	0.034	127	0.025	33	0.024	313
DCP13	.600	0.546	0.229	29	0.070	271	0.088	115	0.061	347	0.038	257	0.034	175	0.023	89	0.018	27	0.020	313
DCP14	.701	0.457	0.193	19	0.050	257	0.073	105	0.064	329	0.024	241	0.015	158	0.016	93	0.015	354	0.022	289
DCP15	.830	0.268	0.119	29	0.061	232	0.064	93	0.044	318	0.013	232	0.004	167	0.009	116	0.010	14	0.026	279
DCP16	.950	-0.016	0.085	1	0.045	210	0.021	87	0.020	308	0.014	222	0.017	123	0.010	6	0.003	302	0.009	231
DCP17	.949	-0.032	0.036	349	0.026	219	0.019	66	0.012	293	0.006	161	0.004	120	0.008	25	0.005	65	0.008	217

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.22	0.117	0.299	5.06	0.0	12.48	12009.6	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
100.8 (330.8)	26732. (558.3)	0.48E 07	-0.183	1.697	16.66	-0.00106	0.878	0.0

HARMONIC ANALYSIS

| DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		12.478	3.064	0	0.239	14	0.016	315	0.052	351	0.039	291	0.071	165	0.025	230	0.016	35	0.013	306
CN		1.045	0.299	52	0.160	17	0.081	302	0.064	219	0.041	144	0.032	71	0.020	359	0.012	27	0.024	291
CM		-0.025	0.054	199	0.036	93	0.021	45	0.019	347	0.013	281	0.011	210	0.006	139	0.001	102	0.005	76
DCP 1	.010	4.584	0.778	143	1.356	81	0.732	39	0.422	357	0.239	333	0.152	341	0.200	307	0.102	254	0.060	217
DCP 2	.020	3.801	0.606	134	1.171	79	0.497	31	0.259	359	0.167	326	0.065	326	0.149	305	0.106	258	0.098	242
DCP 3	.040	3.302	0.745	135	1.064	69	0.250	25	0.234	39	0.206	340	0.093	319	0.136	308	0.115	255	0.076	233
DCP 4	.049	3.323	0.455	61	0.623	61	0.269	7	0.144	311	0.105	260	0.072	205	0.050	150	0.049	98	0.017	6
DCP 5	.074	2.792	0.414	75	0.560	54	0.232	348	0.116	260	0.066	224	0.049	165	0.029	111	0.036	68	0.015	328
DCP 6	.099	2.448	0.427	60	0.516	48	0.217	336	0.111	265	0.054	236	0.034	161	0.027	118	0.035	81	0.013	344
DCP 7	.149	1.880	0.439	64	0.384	29	0.155	314	0.091	246	0.055	186	0.028	125	0.011	59	0.022	81	0.009	326
DCP 8	.200	1.575	0.461	60	0.344	21	0.169	316	0.136	254	0.096	197	0.062	139	0.034	77	0.033	57	0.019	326
DCP 9	.250	1.365	0.468	53	0.305	8	0.172	305	0.160	241	0.129	168	0.073	111	0.045	70	0.046	41	0.031	316
DCP10	.300	1.229	0.456	50	0.276	1	0.173	300	0.164	234	0.116	165	0.079	115	0.052	61	0.049	36	0.045	334
DCP11	.399	1.041	0.424	48	0.221	351	0.150	294	0.146	229	0.103	163	0.061	107	0.044	54	0.045	48	0.061	341
DCP12	.501	0.747	0.305	41	0.156	331	0.109	273	0.119	203	0.090	129	0.073	74	0.043	16	0.036	13	0.061	303
DCP13	.600	0.637	0.303	40	0.125	309	0.080	241	0.095	182	0.077	106	0.055	41	0.042	350	0.019	349	0.053	275
DCP14	.701	0.542	0.245	38	0.117	287	0.070	220	0.085	155	0.061	82	0.054	16	0.041	316	0.021	258	0.033	240
DCP15	.800	0.345	0.236	21	0.104	269	0.064	218	0.073	143	0.039	66	0.047	9	0.044	293	0.022	232	0.025	198
DCP16	.900	0.071	0.147	6	0.063	264	0.049	215	0.036	136	0.028	65	0.040	354	0.025	265	0.014	197	0.018	208
DCP17	.965	-0.003	0.079	357	0.027	279	0.025	242	0.019	150	0.014	94	0.023	355	0.013	275	0.007	191	0.014	184

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1   ACCELERATION TARES

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.0	TEST POINT	CYCLES ANALYSED
0.0	23.24	0.118	0.298	5.05	0.0	15.04	12009.7	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
100.6 (330.0)	26660. (556.8)	0.48E 07	-0.218	1.826	17.62	-0.00164	1.332	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		15.036	5.048	0	0.224	16	0.022	192	0.027	96	0.062	60	0.136	326	0.040	186	0.039	159	0.014	189
CN		1.093	0.324	52	0.150	57	0.076	5	0.061	341	0.058	285	0.046	246	0.035	205	0.022	167	0.013	162
CM		-0.043	0.375	198	0.024	142	0.027	121	0.016	106	0.018	62	0.013	27	0.010	153	0.010	314	0.003	286
DCP 1	.010	4.240	1.993	159	0.940	110	0.534	126	0.411	129	0.209	114	0.177	154	0.163	154	0.077	119	0.089	110
DCP 2	.020	3.642	1.592	155	0.717	102	0.400	174	0.225	115	0.136	107	0.108	152	0.138	143	0.109	134	0.138	134
DCP 3	.040	3.187	1.463	149	0.417	98	0.475	138	0.145	114	0.212	132	0.091	117	0.130	133	0.070	106	0.093	134
DCP 4	.049	3.356	0.652	136	0.584	130	0.297	81	0.189	51	0.122	17	0.090	346	0.051	301	0.021	337	0.021	18
DCP 5	.074	2.608	0.608	128	0.434	83	0.205	64	0.127	34	0.087	346	0.055	327	0.045	279	0.019	312	0.015	336
DCP 6	.099	2.452	0.668	121	0.391	70	0.165	55	0.115	21	0.086	327	0.039	299	0.037	265	0.014	303	0.004	339
DCP 7	.149	1.939	0.598	96	0.266	55	0.177	41	0.101	3	0.096	331	0.063	286	0.036	245	0.020	312	0.015	234
DCP 8	.200	1.617	0.550	92	0.282	60	0.203	35	0.121	8	0.127	333	0.082	293	0.050	270	0.034	304	0.013	248
DCP 9	.250	1.448	0.530	82	0.291	49	0.200	15	0.133	356	0.140	316	0.095	284	0.060	249	0.037	252	0.033	224
DCP10	.300	1.261	0.479	76	0.263	46	0.181	6	0.139	352	0.126	308	0.088	279	0.049	252	0.043	246	0.035	228
DCP11	.349	1.103	0.430	69	0.209	40	0.149	355	0.117	347	0.106	299	0.090	279	0.050	243	0.051	230	0.038	228
DCP12	.501	0.871	0.374	57	0.144	24	0.122	330	0.083	325	0.087	276	0.073	247	0.053	218	0.057	196	0.036	183
DCP13	.600	0.715	0.344	48	0.104	3	0.117	318	0.083	298	0.099	259	0.062	226	0.065	200	0.063	167	0.041	146
DCP14	.701	0.608	0.332	39	0.068	329	0.133	299	0.070	284	0.096	239	0.073	200	0.062	170	0.054	130	0.030	109
DCP15	.800	0.417	0.267	23	0.059	317	0.084	293	0.066	261	0.074	225	0.061	187	0.054	155	0.056	101	0.024	77
DCP16	.900	0.136	0.191	11	0.049	333	0.046	282	0.047	266	0.035	199	0.039	168	0.028	128	0.046	100	0.021	17
DCP17	.969	0.023	0.068	12	0.030	348	0.030	268	0.018	256	0.023	219	0.017	161	0.022	137	0.023	109	0.015	51

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1   ACCELERATION TARES

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.27	0.118	0.299	5.04	0.0	17.51	12009.8	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
100.6 (330.1)	26703. (557.7)	0.48E 07	-0.214	1.846	17.99	-0.00264	2.151	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		17.512	5.041	0	0.199	4	0.067	238	0.030	189	0.031	142	0.069	112	0.019	236	0.028	34	0.009	56
CN		1.090	0.352	96	0.133	33	0.077	91	0.053	67	0.046	55	0.043	40	0.022	32	0.033	28	0.013	44
CM		-0.057	0.075	206	0.036	237	0.020	196	0.016	197	0.014	186	0.013	182	0.004	169	0.010	180	0.004	166
DCP 1	.010	3.647	2.459	164	0.680	178	0.675	201	0.280	235	0.254	253	0.133	308	0.145	295	0.084	317	0.116	320
DCP 2	.020	3.176	1.924	160	0.475	178	0.416	189	0.194	222	0.145	264	0.127	307	0.141	323	0.131	344	0.114	2
DCP 3	.030	2.760	1.665	153	0.561	206	0.290	180	0.297	220	0.145	268	0.094	260	0.121	302	0.076	337	0.066	344
DCP 4	.044	3.311	0.869	154	0.396	140	0.224	150	0.148	162	0.110	150	0.076	145	0.031	119	0.046	187	0.036	152
DCP 5	.074	2.756	0.830	141	0.287	120	0.157	137	0.101	146	0.084	114	0.038	120	0.025	87	0.027	181	0.028	131
DCP 6	.099	2.416	0.797	129	0.219	113	0.179	123	0.078	111	0.085	99	0.031	83	0.036	82	0.019	143	0.024	114
DCP 7	.149	1.922	0.614	135	0.199	116	0.143	103	0.091	114	0.073	98	0.057	92	0.038	62	0.024	118	0.013	113
DCP 8	.200	1.578	0.599	108	0.270	138	0.177	107	0.149	99	0.113	95	0.082	92	0.037	81	0.055	101	0.023	126
DCP 9	.250	1.435	0.572	99	0.267	97	0.184	100	0.156	80	0.112	93	0.069	73	0.051	86	0.050	64	0.035	107
DCP10	.300	1.291	0.518	91	0.245	88	0.178	97	0.145	80	0.117	85	0.087	77	0.054	76	0.049	76	0.032	105
DCP11	.395	1.115	0.459	82	0.201	77	0.146	85	0.114	73	0.097	74	0.087	72	0.048	67	0.075	67	0.030	84
DCP12	.501	0.901	0.343	62	0.176	57	0.106	62	0.090	43	0.083	46	0.077	43	0.048	39	0.074	30	0.037	61
DCP13	.600	0.746	0.361	58	0.156	45	0.094	42	0.080	19	0.074	25	0.077	15	0.036	6	0.068	9	0.029	33
DCP14	.701	0.636	0.309	46	0.138	37	0.077	12	0.072	7	0.067	357	0.072	355	0.031	336	0.050	344	0.026	351
DCP15	.800	0.463	0.235	31	0.129	29	0.068	357	0.055	6	0.062	341	0.055	337	0.028	294	0.041	325	0.026	316
DCP16	.900	0.184	0.139	25	0.096	11	0.046	354	0.027	347	0.038	330	0.036	320	0.011	307	0.029	339	0.025	293
DCP17	.969	0.041	0.064	30	0.044	26	0.011	17	0.010	0	0.018	326	0.011	339	0.008	395	0.013	356	0.010	304

FORCED PITCHING OSCILLATION   AIRFOIL   NLR 1   ACCELERATION TARES

TUNED HZ	DRIVE HZ	K	MACH NO	DEL.ALPHA	DEL.H	ALPHA.O	TEST POINT	CYCLES ANALYSED
0.0	23.16	0.118	0.298	5.07	0.0	19.95	12009.9	20

V	Q	RN	CN(MIN)	CN(MAX)	ALPHA.NMAX	AERO DAMP	TDR	EXT DAMP
100.4 (329.3)	26607. (555.7)	0.48E 07	-0.199	1.589	18.52	-0.00417	3.388	0.0

HARMONIC ANALYSIS

DATA TYPE	X/C	RES 0	RES 1	PHI	RES 2	PHI	RES 3	PHI	RES 4	PHI	RES 5	PHI	RES 6	PHI	RES 7	PHI	RES 8	PHI	RES 9	PHI
ALPHA		19.946	5.065	0	0.215	6	0.059	245	0.012	251	0.013	8	0.031	298	0.030	193	0.002	105	0.008	21
CN		1.058	0.316	100	0.049	133	0.060	149	0.034	170	0.032	163	0.029	177	0.018	183	0.003	26	0.003	193
CM		-0.065	0.065	234	0.022	243	0.018	276	0.010	295	0.010	308	0.008	335	0.003	349	0.002	191	0.002	355
DCP 1	.010	2.814	1.655	161	0.579	229	0.222	251	0.226	296	0.115	9	0.036	60	0.053	88	0.046	105	0.022	148
DCP 2	.020	2.480	1.201	161	0.459	232	0.193	260	0.157	305	0.072	0	0.035	58	0.021	103	0.051	113	0.018	235
DCP 3	.030	2.276	0.936	155	0.476	227	0.206	284	0.094	323	0.030	16	0.030	56	0.031	132	0.035	125	0.019	216
DCP 4	.044	2.513	0.846	164	0.140	222	0.243	224	0.059	236	0.066	256	0.014	294	0.015	124	0.046	57	0.043	26
DCP 5	.074	2.433	0.619	145	0.113	254	0.182	222	0.030	196	0.041	228	0.007	134	0.017	152	0.033	56	0.031	5
DCP 6	.099	2.116	0.514	126	0.086	230	0.092	214	0.044	201	0.042	204	0.012	157	0.025	152	0.021	67	0.012	36
DCP 7	.149	1.734	0.412	100	0.100	148	0.085	190	0.060	168	0.030	144	0.014	166	0.012	208	0.009	121	0.012	20
DCP 8	.200	1.471	0.410	109	0.124	155	0.111	178	0.058	210	0.054	211	0.044	235	0.026	241	0.005	284	0.007	329
DCP 9	.250	1.363	0.429	103	0.126	148	0.136	152	0.086	193	0.068	187	0.055	217	0.040	219	0.030	277	0.004	341
DCP10	.300	1.255	0.430	98	0.122	142	0.120	149	0.082	191	0.059	192	0.050	212	0.032	210	0.024	262	0.009	286
DCP11	.395	1.147	0.393	94	0.103	131	0.119	139	0.077	189	0.051	188	0.057	202	0.033	217	0.022	272	0.011	238
DCP12	.501	0.959	0.359	84	0.087	103	0.099	126	0.062	163	0.050	162	0.051	171	0.037	180	0.014	230	0.009	238
DCP13	.600	0.812	0.333	74	0.084	75	0.077	106	0.050	132	0.060	139	0.045	163	0.026	150	0.021	137	0.019	190
DCP14	.701	0.712	0.310	65	0.094	62	0.072	99	0.047	108	0.045	121	0.034	146	0.013	131	0.021	75	0.010	157
DCP15	.800	0.559	0.262	62	0.079	52	0.057	91	0.043	98	0.041	118	0.037	142	0.015	192	0.019	16	0.012	120
DCP16	.900	0.247	0.166	63	0.045	42	0.028	87	0.027	68	0.027	96	0.023	126	0.012	125	0.023	4	0.006	102
DCP17	.969	0.072	0.083	71	0.012	67	0.013	95	0.011	87	0.009	122	0.008	124	0.004	109	0.003	340	0.015	203

RESONANCE TEST OF PRESSURE TRANSDUCER CAVITY
AND DUCTS TO MODEL SURFACE

307

1. Report No. NASA CR-2915	2. Government Accession No.	3. Recipient's Catalog No.
4. Title and Subtitle TWO-DIMENSIONAL WIND TUNNEL TEST OF AN OSCILLATING ROTOR AIRFOIL - Volume II		5. Report Date December 1977
		6. Performing Organization Code
7. Author(s) Dadone, L. U.		8. Performing Organization Report No. D 210-11188-2
		10. Work Unit No.
9. Performing Organization Name and Address Boeing Vertol Company Boeing Center, P.O. Box 16858 Philadelphia, Pa. 19142		11. Contract or Grant No. NAS1-13795
12. Sponsoring Agency Name and Address NASA Langley Research Center Hampton, Va. 23665		13. Type of Report and Period Covered Final
		14. Sponsoring Agency Code

16. Abstract

A two-dimensional wind tunnel test was conducted to obtain the quasi-steady and unsteady characteristics of the NLR 7223-62, an advanced airfoil designed for helicopter rotor applications.

Differential pressures were measured at 17 locations along the chord of the airfoil model. The airfoil motion were sinusoidal forced pitch oscillations about the quarter chord at amplitudes varying from 2.5° to 10.0° and at frequencies from 23 Hz to 90 Hz. The quasi-steady tests were conducted at Mach numbers from 0.2 to 0.9, and the oscillatory tests between M = 0.2 and M = 0.7. At quasi-steady conditions a limited number of drag measurements was made with a wake-traversing probe. The results of the test are outlined and discussed in Volume I. A systematic tabulation of test results is presented in Volume II.

| 17. Key Words (Suggested by Author(s)) AIRFOILS UNSTEADY AERODYNAMICS ROTORS	18. Distribution Statement Unlimited - Unclassified Subject Category 02	
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of Pages 309	22. Price* $9.75

90

50

END

5. 12. 78